## CLAIMS

1. A composition comprising:

   (i) a) 50 ppm to 500 ppm of hypochlorous acid or 50 ppm to 500 ppm of free available chlorine,
   b) 10 ppm to 250 ppm of a copper chloride and 10 ppm to 250 ppm of a zinc chloride, and
   c) 10 ppm to 250 ppm of calcium oxide; or

   (ii) a) 200 ppm to 1,000 ppm of hypochlorous acid or 200 ppm to 1,000 ppm of free available chlorine,
   b) 50 ppm to 500 ppm of a copper chloride and 50 ppm to 500 ppm of a zinc chloride, and
   c) 50 ppm to 500 ppm of calcium oxide.

2. The composition according to Claim 1, wherein the composition comprises:
   a) 50 ppm to 500 ppm of the hypochlorous acid or 50 ppm to 500 ppm of the free available chlorine,
   b) 10 ppm to 250 ppm of the copper chloride and 10 ppm to 250 ppm of the zinc chloride, and
   c) 10 ppm to 250 ppm of the calcium oxide.

3. The composition according to Claim 2, wherein the composition comprises:
   a) 150 ppm to 450 ppm of the hypochlorous acid or 150 ppm to 450 ppm of the free available chlorine,
   b) 10 ppm to 160 ppm of the copper chloride and 10 ppm to 160 ppm of the zinc chloride, and
   c) 40 ppm to 200 ppm of the calcium oxide.

4. The composition according to Claim 2, wherein the composition comprises: a) 150 to 450 ppm of the hypochlorous acid or 150 to 450 ppm of the free available chlorine,
   b) 20 ppm to 220 ppm of the copper chloride and 20 to 220 ppm of the zinc chloride, and
   c) 80 ppm to 240 ppm of the calcium oxide.

5. The composition according to Claim 2, wherein the composition comprises:
   a) 200 ppm to 400 ppm of the hypochlorous acid or 200 ppm to 400 ppm of the free available chlorine,
   b) 20 ppm to 140 ppm of the copper chloride and 20 ppm to 140 ppm of the zinc chloride, and
   c) 60 ppm to 180 ppm of the calcium oxide.

6. The composition according to Claim 2, wherein the composition comprises:
   a) 260 ppm to 360 ppm of the hypochlorous acid or 260 ppm to 360 ppm of the free available chlorine,
   b) 40 ppm to 120 ppm of the copper chloride and 40 ppm to 120 ppm of the zinc chloride, and
   c) 80 ppm to 160 ppm of the calcium oxide.

7. The composition according to Claim 2, wherein the composition comprises:
   a) 75 ppm to 400 ppm of the hypochlorous acid or 75 ppm to 400 ppm of the free available chlorine,
   b) 20 ppm to 200 ppm of the copper chloride and 20 ppm to 200 ppm of the zinc chloride, and
   c) 20 ppm to 200 ppm of the calcium oxide.

8. The composition according to Claim 2, wherein composition comprises:
   a) 100 ppm to 350 ppm of the hypochlorous acid or 100 ppm to 350 ppm of the free available chlorine,
   b) 40 ppm to 160 ppm of the copper chloride and 40 ppm to 160 ppm of the zinc chloride, and
   c) 40 ppm to 160 ppm of the calcium oxide.

9. The composition according to any one of Claims 1-8, wherein the composition further comprises a phosphate buffer.

10. The composition according to Claim 9, wherein the phosphate buffer is calcium phosphate or sodium phosphate.

11. The composition according to any one of Claims 1-10, wherein the composition pH is at least pH 5.

12. The composition according to Claim 11, wherein the composition pH is pH 5 to 7.

13. The composition according to Claim 12, wherein the composition pH is pH 5 to 6.

14. The composition according to any one of Claims 1-10, wherein the composition pH is pH 4.5 to 8.

15. The composition according to Claim 2, wherein the composition comprises:
   a) 340 ppm of the hypochlorous acid or 340 ppm of the free available chlorine,
   b) 80 ppm of the copper chloride and 80 ppm of the zinc chloride, and
   c) 80 ppm of the calcium oxide.

16. The composition according to Claim 2, wherein the composition comprises:
   a) 310 ppm of the hypochlorous acid or 310 ppm of the free available chlorine,
   b) 40 ppm, 80 ppm or 120 ppm of the copper chloride and 40 ppm, 80 ppm or 120 ppm of the zinc chloride, and
   c) 80 ppm or 160 ppm of the calcium oxide.

17. The composition according to Claim 2, wherein the composition comprises:
   a) 310 ppm of the hypochlorous acid or 310 ppm of the free available chlorine,
   b) 40 ppm of the copper chloride and 40 ppm of the zinc chloride, and
   c) 160 ppm of the calcium oxide.

18. The composition according to Claim 2, wherein the composition comprises:
   a) 320 ppm of the hypochlorous acid or 320 ppm of the free available chlorine,
   b) 80 ppm of the copper chloride and 80 ppm of the zinc chloride, and
   c) 80 ppm of the calcium oxide.

19. The composition according to Claim 1, part (ii).

20. A method of cleaning or disinfecting a hard surface, the method comprising applying to the hard surface a composition as defined in any one of Claims 1-19.