

"SAFETY CLOSURE"

This invention relates to safety closures for necked containers, and more particularly, to improved safety closures of the type having an integral flap that is mounted and locked in a depression in the top surface or panel of the closure such that no edge portion of said flap projects out of said depression. Such locking flap carries means on its underside for sealingly engaging one or more dispensing openings provided in the top or panel portion of the closure.

There has been a number of disclosures in the prior art of so-called child resistant or safety closures for necked containers which have utilized a closure body portion and an integrally molded, hinged locking flap portion cooperating with the body portion to effect the closing of one or more dispensing openings in the body portion. Typical of such prior art disclosures are United States Patent Nos. 3,845,872 to Townes; 3,927,805 to Stull; and 4,022,352 to Pehr. The alleged safety feature found in each of these prior art safety closure constructions is the necessity for the application by the finger of a significant downward force to a specific location on the top wall or panel of the closure. It has been recognized, however, that this type of acutation may be inadvertently applied by a child through the simple expedient of banging the container with the closure attached against a hard surface in such manner that a downward opening force of the proper magnitude is applied to the proper spot of the safety closure. The possibility of such inadvertent opening of the closure by children significantly limits the usefulness of such prior art safety closure constructions.

In the co-pending application, Serial No. 8013784, (case No. 14,461) which is assigned

to the Assignee of this application, there is disclosed and claimed a safety closure construction wherein a segment of the annular wall of the closure is depressible by a compression action of the fingers to effect the release of co-operating latching surfaces holding the locking flap in closed position. This construction requires not only the application of a compression force by the fingers but the concurrent application of a lifting force on the free end of the locking flap to effect the opening of the closure. There still remains the possibility, although a much smaller possibility, that a child could inadvertently effect the opening of such closure.

15 SUMMARY OF THE INVENTION

In accordance with this invention, a safety closure is provided comprising:

- (1) a body member molded from a resilient plastic and having a circular top panel portion and an integral depending annular sidewall;
- (2) means on said annular sidewall for securing the closure to a container neck;
- (3) a locking flap connected by an integral hinge to a peripheral portion of said top panel portion
- (4) a recess in said top panel portion corresponding in configuration to said locking flap and having a radial end wall, remote from said integral hinge, which is inwardly deformable by finger compression;
- (5) means in said recess defining a dispensing opening for the container contents;
- (6) a depending protuberance on said locking flap sealingly engageable with said dispensing opening; and
- (7) two sets of co-operating surfaces provided on said panel portion and said locking flap for holding the locking flap in the recess,

wherein said locking flap is foldable about said integral hinge to lie snugly in said recess with no edge portion of the locking flap projecting out of said recess, with the free end of said locking flap abutting said radial end wall, said free end of said locking flap and said radial end wall with which it is in abutment comprising one of said two sets of co-operating surfaces, with the protuberance engaging said dispensing opening, and with the two sets of surfaces in abutment and co-operating to hold the locking cap in the recess,

and wherein, with said locking flap lying in said recess, application of downward pressure on a selected portion of said locking flap causes said one of the set of surfaces to move out of abutment, and inward deformation of said radial end wall causes the other set of surfaces to move out of abutment whereby the locking flap may be removed from the recess.

The two distinct sets of surfaces provided on the locking flap and the panel portion of the closure secure the locking flap in its closed, folded position. More importantly, the provision of the two sets of cooperating surfaces requires the sequential and concurrent application of both a downward force to a selected position on the locking flap of the closure, so that the one set of surfaces are disengaged and the radial end wall underlies the free end of the locking flap, plus a compression force exerted on the radial end wall now underlying the free end of the locking flap, so that the locking flap is raised and the other set of surfaces is released.

The downward force effects a pivoting of the free end portion of the locking flap upwardly, disengaging one set of surfaces, to permit the radial depression of the radial end wall by a concurrent application of a compressive force. Such depression of the radial end wall underlying the locking flap raises the locking flap and releases the second set of surfaces. The free end of the closure is then elevated slightly out of the panel recess, above the level of the top panel of the closure, in a position where it may be engaged by the fingers and lifted to a fully opened position.

According to a second aspect of the invention, there is provided a safety closure for a container neck comprising:

- (1) a body member molded from a resilient plastic and having a circular top panel portion and an integral depending annular sidewall;
- (2) means on said annular sidewall for securing the closure to a container neck;
- (3) a locking flap connected by an integral hinge to a peripheral portion of said top panel portion;
- (4) a recess in said top panel portion corresponding in configuration to said locking flap and having a radial end wall, remote from said integral hinge, which is inwardly deformable by finger compression;
- (5) means in said recess defining a dispensing opening for the container contents;
- (6) means in the base of said recess defining a locking shoulder located on the side of said dispensing opening remote from said hinge;
- (7) a first depending protuberance on said locking

flap defining a hook portion resiliently engage-
able with said locking shoulder to lock said
locking flap within said recess; and

(8) a second depending protuberance on
5 said locking flap sealingly engageable with said
dispensing opening;

wherein said locking flap is foldable about
said integral hinge to lie in said recess with
no edge portion of the locking flap projecting
10 out of said recess, with the free end of the
locking flap overlying a portion of said side-
wall and abutting said radial end wall, with said
first protuberance engaging said locking shoulder
and with said second protuberance engaging said
15 dispensing opening,

and wherein, with said locking flap lying
in said recess, application of a downward force
to the portion of the locking flap over
said second protuberance displaces the free end
20 of the locking flap in an upward direction with-
out releasing said hook portion from its locking
engagement with said locking shoulder, and inward
deformation of said radial end wall cams the free
end of the locking flap upwardly out of said
25 recess sufficient to release said hook portion
from said locking shoulder and to permit said
free end to be engaged by the fingers and lifted
to remove said second protuberance from said
dispensing opening.

30 A closure of this type may be fabricated
by injection molding and, hence, represents an
item that can be economically produced at high
speeds on a large multicavity injection molding
machine. Since the combination of a downward force
35 on a specific area of the locking flap of the

closure followed by the concurrent exertion of inward deformation by applying a compression force on the radial end wall is required to effect the initial opening of the locking flap, it is readily apparent that such sequential and concurrent action is beyond the capability of any child, but still well within the capability of a typical adult, including senior citizens. Under no circumstances can the opening of the closure be effected merely by banging the closure against a rigid object.

Other advantages of the invention will become apparent to those skilled in the art from the following detailed description, taken in conjunction with the annexed sheets of drawings on which are one embodiment of this invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a vertical sectional view of a safety closure embodying this invention shown in assembled relationship to the neck of a container, with the integral locking flap of the closure being disposed in its locked position.

Figure 2 is a vertical sectional view of the safety closure showing the closure components in their positions as molded in an injection mold.

Figure 3 is a view similar to Figure 1 illustrating the positions of the closure components when a downward force is applied to the central portion of the locking flap.

Figure 4 is a view similar to Figure 3 but illustrating the positions of the components of the closure when a compressing action on the sidewall of the closure is concurrently applied with the downward force.

Figure 5 illustrates the removal of the locking flap from its locking position by the fingernail of the manipulator.

DESCRIPTION OF PREFERRED EMBODIMENT

Referring to the drawings, the numeral 1 indicates generally a safety closure embodying this invention. Closure 1 comprises an ~~inverted cup-shaped~~ body portion 10 having a panel portion 20 and an integral annular depending wall 15. A locking flap 30 is integrally molded with body portion 10, being connected thereto by an integral hinge 11 located at a peripheral portion of the panel 20. The top surface of panel 20 is provided with a recess 21 which is proportioned to snugly receive the flap 30 therein when such flap is folded to the closed position of the closure indicated in Figure 1. In such closed position of the locking flap 30, the end face 31 of the locking flap is in snug engagement with the end wall 21a of the

8
of the recess 21.

5 The annular wall 15 of the closure is provided with appropriate ribs or threads 15a on the internal surface for detachably mounting the closure 1 to the threaded neck 2a of a container 2. Additionally, a plurality of peripherally spaced serrations 15b are provided on the lower portion of the annular wall 15 to engage locking serrations 2b provided on the neck portion of the container 2.

10 Panel portion 20 is provided with a depending annular flange 22 which, in cooperation with the adjacent internal surface of the annular wall 15, defines a space to snugly receive the top end of the container neck 2a and effect a seal therewith. Panel 20 is additionally provided with a dispensing opening 23a defined by a depending annular
15 protuberance 23 formed in the center of panel 20. The protuberance 23 has an internal end flange 23b for purpose to be hereafter described. Lastly, the panel recess 21 is provided with an upstanding locking shoulder 24 located on that side of the dispensing opening 23a opposite to the
20 integral hinge 11.

Locking flap 30 is provided with an annular protuberance 32, which in the closed position of the locking flap, enters the opening defined by the annular protuberance 23 to effect a seal of the dispensing opening 23a and, equally
25 importantly, it should be noted that the end surface of the locking flap protuberance 32 can move into abutting engagement with the internal flange 23b.

Locking flap 30 is additionally provided with a second depending member 33 which defines a hook surface 34 engage-
30 able with the upstanding locking projection 24 provided in

the base of recess 21. Also, the free end portion of the locking flap 30 is somewhat enlarged in thickness and defines an inclined cam surface 31a beneath end surface 31 for a purpose hereafter to be described.

5 From the foregoing description, it will be noted that when the locking flap 30 is folded about the integral hinge 11 to lie in the closed position illustrated in Figure 1, the protuberance 32 is in sealing engagement with the dispensing opening 23a, the second protuberance 33 defining the locking hook 34 is in latched engagement with the upstanding locking projection 24, and the end surface 31 of the locking flap is in abutment with the vertical end wall 31a of the panel recess 31.

10 To effect an opening of the closure, the sequential and concurrent application of two radically different forces to the closure assembly is required. First, a downward force has to be applied to the top central portion of the locking flap 30 immediately above the protuberance 32. This downward force not only depresses the center of the locking flap 30 but
15 concurrently depresses the central portion of the panel 20 of the closure. The effect of this depression is illustrated in Figure 3 where it is clear that the hook portion 34 of the locking flap 30 remains in locked engagement with the upstanding locking shoulder 24 provided in the recess 21; however, the free end surface 31 of the locking flap 30 is
20 moved upwardly sufficient to bring the inclined cam surface 31a in position to be engaged by the end wall 21a of the recess, if such end wall is depressed inwardly.

25 An open topped recess 25 is provided in a portion of the annular end wall
30

15 immediately underlying the free end of the locking flap 30. Such recess permits the surrounding wall portion 15c to be radially inwardly depressed through the application of compressing force by the fingers to the side wall segment. The effect of such radially inward movement of the side wall segment portion 15c is illustrated in Figure 4 wherein it will be seen that the free end of the locking flap 30 is cammed upwardly sufficiently to release the depending locking hook 34 from the upstanding locking shoulder 24. The free end of the locking flap 30 can now be engaged by the fingernail (Figure 5) and the locking flap elevated to its unlocked position, opening the dispensing aperture 23a to dispense the contents of the container 2 therethrough.

It is important to note that the sequential and concurrent application of the downward force to the central portion of the locking flap 30 and the compression force to the wall segment 15c is required to effect the opening of the locking flap 30. If only a downward force is applied, the depending locking hook 34 on the locking flap does not disengage from the upstanding locking shoulder 24 provided in the panel recess 31. As soon as the downward force is released, the locking flap 30 returns to its original position shown in Figure 1. On the other hand, if only a compression force is applied to the side wall segment 15c, without the preceding and concurrent application of a downward force to the central portion of the locking flap 30, then no action results because radial inward movement of the side wall segment 15c is effectively blocked by the vertical end face 31 of the locking flap 30.

From the foregoing description, it will be apparent

that a safety closure embodying this invention incorporates two distinct sets of cooperating locking surfaces for holding the locking flap in its closed locked position in the panel recess. The first set of such cooperating locking surfaces is the vertical end surface 31 of locking flap 30 which cooperates with the adjacent end wall 21a of the panel recess 21. The second set of locking surfaces comprises the upstanding member 24 defining the locking surface in the panel recess 21 and the depending hook member 34 formed on the locking flap 30. The first set of locking surfaces are disengageable by the application of a downward force to the central portion of the locking flap 30. Such downward movement, as explained above, does not effect the disengagement of the locking surface 24 with the locking hook 34. The locking hook 34 is then disengageable from the locking surface 24 by the concurrent inward depression of the wall segment 15c which lies adjacent the free end of the locking flap 30. Such inward depressing movement of the wall segment 15c effects an upward camming of the locking flap 30 to disengage the second set of locking surfaces, thereby freeing the locking flap 30 to be lifted by the finger to a fully opened position.

It will be obvious to those skilled in the art that the sequential and concurrent application of a downward force in a specific location with a compression force applied to another specific location on the side wall 15 is beyond the capability of any child, hence the safety closure embodying this invention provides an unusual degree of safety from inadvertent opening by a child, without in any manner interfering with the easy opening of the closure by an adult who follows the opening instructions.

Modifications of this invention will be readily apparent to those skilled in the art and it is intended that the scope of the invention be determined solely by the appended claims.

CLAIMS

1. A safety closure for a container neck comprising:

5 (1) a body member molded from a resilient plastic and having a circular top panel portion and an integral depending annular sidewall;

(2) means on said annular sidewall for securing the closure to a container neck;

10 (3) a locking flap connected by an integral hinge to a peripheral portion of said top panel portion;

(4) a recess in said top panel portion corresponding in configuration to said locking flap and having a radial end wall, remote from said integral hinge, which is inwardly deformable by finger compression;

15 (5) means in said recess defining a dispensing opening for the container contents;

(6) means in the base of said recess defining a locking shoulder located on the side of said dispensing opening remote from said hinge;

20 (7) a first depending protuberance on said locking flap defining a hook portion resiliently engageable with said locking shoulder to lock said locking flap within said recess; and

25 (8) a second depending protuberance on said locking flap sealingly engageable with said dispensing opening;

30 wherein said locking flap is foldable about said integral hinge to lie in said recess with no edge portion of the locking flap projecting out of said recess, with the free end of the locking flap overlying a portion of said sidewall and abutting said radial end wall, with said first protuberance engaging said locking shoulder and with said second protuberance engaging said dispensing outlet,

35 and wherein, with said locking flap lying in said recess, application of a downward force to the portion of the locking flap over said second protuberance displaces the free end of the locking flap in an

(27)



14

upward direction without releasing said hook portion from its locking engagement with said locking shoulder, and inward deformation of said radial end wall cams the free end of the locking flap upwardly out of said recess sufficient to release said hook portion from said locking shoulder and to permit said free end to be engaged by the fingers and lifted to remove said second protuberance from said dispensing opening.

2. The safety closure of claim 1 wherein said dispensing opening is defined by a depending annular wall having an internal rib engageable by the end of said second protuberance.

3. A safety closure for a necked container comprising:

(1) a body member molded from a resilient plastic and having a circular top panel portion and an integral depending annular sidewall;

(2) means on said annular sidewall for securing the closure to a container neck;

(3) a locking flap connected by an integral hinge to a peripheral portion of said top panel portion;

(4) a recess in said top panel portion corresponding in configuration to said locking flap and having a radial end wall, remote from said integral hinge, which is inwardly deformable by finger compression;

(5) means in said recess defining a dispensing opening for the container contents;

(6) a depending protuberance on said locking flap sealingly engageable with said dispensing opening;

(7) two sets of co-operating surfaces provided



on said panel portion and said locking flap
for holding the locking flap in the recess,

wherein said locking flap is foldable about
said integral hinge to lie snugly in said recess
5 with no edge portion of the locking flap
projecting out of said recess, with the free
end of said locking flap overlying a portion of the
side wall and abutting said radial end wall, said free end
of said locking flap and said radial end wall with which it
10 is in abutment comprising one of said two sets of
co-operating surfaces, with the protuberance
engaging said dispensing opening, and with the
two sets of surfaces in abutment and co-operating
to hold the locking cap in the recess,

15 and wherein, with said locking flap lying
in said recess, application of downward pressure
on a selected portion of said locking flap
causes said one of the sets of surfaces to
move out of abutment, and inward deformation
20 of said radial end wall causes the other set of
surfaces to move out of abutment whereby the
locking flap may be removed from the recess.

4. A safety closure in accordance with claim
3, wherein that portion of the side wall
25 underlying the free end of the locking flap is
provided with an upwardly open recess to
facilitate the inward depression of said
radial end wall.

5. A safety closure as claimed in claim 1,
30 substantially as described with reference to
the drawings.

The text of the specification has been reproduced by photocopying the applicants original
typescript. It may contain a few amendments which are difficult to read. The original
typescript containing these amendments may be inspected on the premises of the Patent Office