



(51) International Patent Classification:

B23K 35/00 (2006.01) *B23K 35/365* (2006.01)
B23K 35/02 (2006.01) *C22C 19/00* (2006.01)

(21) International Application Number:

PCT/EP2013/056544

(22) International Filing Date:

27 March 2013 (27.03.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

12161742.7 28 March 2012 (28.03.2012) EP

(71) Applicant: **ALFA LAVAL CORPORATE AB** [SE/SE];
Box 73, S-221 00 Lund (SE).

(72) Inventor: **SJÖDIN, Per**; Östra Vallgatan 37 A, 4 tr, S-223
61 Lund (SE).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A NOVEL COATING CONCEPT

(57) Abstract: The present invention relates to composition comprising a blend of at least one boron source and at least one silicon source, and the composition further comprises particles selected from particles having wear resistance properties, particles having surface enhancing properties, particles having catalytic properties or combinations thereof, wherein the blend comprises boron and silicon in a weight ratio boron to silicon within a range from about 3:100 wt:wt to about 100:3 wt:wt, wherein silicon and boron are present in the blend in at least 25 wt%, and wherein the at least one boron source and the at least one silicon source are oxygen free except for inevitable amounts of contaminating oxygen, and wherein the blend is a mechanical blend of particles in and the particles have an average particle size less than 250 µm. The present invention relates further to a method for providing a coated product and a coated product obtained by the method.

