CLAIMS

1. An industrial control device comprising:

a display;

a unitary body including a facia wall, an inner shroud, and an outer shroud, the facia wall including a window, wherein the window is a transparent material and aligned with the display to permit the display to be viewed through the window, wherein the inner shroud extends in a rearward direction from a rear side of the facia wall, wherein the outer shroud is disposed about the inner shroud and extends in the rearward direction from the rear side of the facia wall and is spaced apart from the inner shroud to define a cavity;

a seal member disposed in the cavity and configured to form a seal with a facia plate disposed about the inner shroud;

a first sensor configured to detect contact with a front surface of the facia wall; and

a controller coupled to an output of the first sensor for electrical communication therewith, the controller being coupled to the display and configured to control the display.

2. The industrial control device according to Claim 1, wherein the first sensor is a capacitive slider sensor.

3. The industrial control device according to Claim 1, wherein the facia wall includes an input graphic overlapping the first sensor.

4. The industrial control device according to Claim 1, wherein the unitary body is a molded body and the first sensor is in-molded in the facia wall.

5. The industrial control device according to Claim 4, wherein the unitary body includes a first input graphic that is in-molded in the facia wall and overlaps the first sensor.

6. The industrial control device according to Claim 5, wherein the unitary body further includes a second input graphic and a second sensor, wherein the second sensor is discrete from the first sensor and the second input graphic is in-molded in the facia wall and overlaps the second sensor.

7. The industrial control device according to Claim 4, wherein the output of the first sensor includes a plurality of electrical traces in-molded in the facia wall and the industrial control device further includes a plurality of connector pins directly connected to the plurality of electrical traces, the connector pins coupling the electrical traces to the controller for electrical communication therewith.

8. The industrial control device according to Claim 1 further comprising a carrier including a carrier plate and a plurality of board supports extending from a back side of the carrier plate, wherein the display is coupled to a front side of the carrier plate, wherein the controller includes a first circuit board and a plurality of second circuit boards, the first circuit board is coupled to the back side of the carrier plate and each second circuit board is received in a slot defined by a corresponding pair of board supports of the plurality of board supports.

9. The industrial control device according to Claim 8, wherein one of the unitary body and the carrier plate includes a plurality of locating ridges and the other of the unitary body and the carrier plate defines a plurality of alignment grooves, each locating ridge being received in a corresponding alignment groove.

10. The industrial control device according to Claim 1, wherein the controller is configured to adjust a set point value based on input from the first sensor.

11. The industrial control device according to Claim 10, wherein the controller is configured to change the set point value an amount proportional to a speed of a user activating the first sensor via a sliding contact along the front surface of the facia wall.

12. The industrial control device according to Claim 1 further comprising a housing coupled to the unitary body, wherein the controller is disposed within the housing, wherein the housing includes a plurality of retaining clips and the unitary body defines a plurality of retention apertures, each retaining clip resiliently snapping into a corresponding one of the retention apertures to couple the housing to the unitary body.

13. The industrial control device according to Claim 1, wherein the inner shroud is disposed about the display.

14. The industrial control device according to Claim 1 further comprising the facia plate, wherein the facia plate defines an aperture through which the inner shroud extends, the outer shroud and the seal being disposed about the aperture.

15. The industrial control device according to Claim 1 further comprising a housing, a front collar, a rear collar, a plurality of tightening members, and a pair of retaining clips, wherein the housing is coupled to the unitary body and the controller is disposed within the housing, wherein the inner shroud defines a pair of retention apertures, the front collar being disposed about the inner shroud between the rear collar and the facia plate, the rear collar being disposed about the housing, each retaining clip extending from the rear collar in a direction toward the facia plate and being received in a corresponding one of the retention apertures, and each tightening member being configured to engage the rear collar and the front collar such that actuation of the tightening members translates the front collar toward the facia plate.

16. The industrial control device according to Claim 15, wherein each tightening member is a screw, wherein the front collar defines a plurality of abutment surfaces and each screw is threadably engaged to the rear collar and abutts a corresponding one of the abutment surfaces such that rotation of each screw in a predetermined rotational direction causes each screw to translate the front collar toward the facia plate.

17. The industrial control device according to Claim 1, wherein the controller is configured to control the display to visually output a numeric value of a current

process, the controller being configured to adjust a font size of the numeric value based on an amount of digits of the numeric value.