

Description

Field of the invention

This invention relates to an electronic printer, and more particularly to a printer which may be connected electrically to an electronic scale used in a department store or supermarket etc. and the desired data printed on a printing sheet and issued under an instruction from the electronic scale.

Description of the prior art

The conventional type of electronic scale printer is used in a store such as supermarket for direct face-to-face selling between the customer and the store personnel and it sometimes arises that in the one case the receipt should be issued and in the other case that the label should be issued in accordance with the object of use of the unit.

However, the conventional type of printer may be classified into two units comprising a label printer and a receipt printer for use in printing in the desired printing mode on the desired printing sheet, that is, the weight of the article is weighed by an electronic scale, the price of the article is calculated by reference to the result of weighing and to the unit price (price per unit weight) and either one of the label or receipt issued in view of the result of calculation.

Although the two units have similar functions, a manufacturer must produce two types of printers merely because of the fact that different objects have to be printed, with the result that they are quite inefficient in their operation.

Also, the customer must replace the electronic scale itself or printer when he wishes to replace the receipt printer already in use by the label printer as the size of the store expands, which is inconvenient. Further, for example, when a daily totalization is to be performed with the label printer, a separate exclusive totalization printer must be connected or the roll of used label sheet must be removed upon completion of the daily work to replace it with the roll of receipt sheet and print out the accumulated data, which is a troublesome operation. Resetting of the roll of label sheet upon printing-out of the accumulated data caused an issuing of useless labels, resulting in waste.

Since the printer was quite thin in view of its function and design, it was hard to perform a replacement of a roll of printing sheet upon completion of the roll of the printing sheet. Therefore, if the roll was completely used during meeting with a consumer, the store personnel must keep the consumer waiting for the replacement of the roll.

A way of displaying in the label to be attached to an item packed is defined under a rule of the Food Sanitation Act or the Food Fair Competition Rule etc. and the character of item name to be printed on the label is defined more than the desired size. In turn, the character of item name to be printed on the receipt (usually Japanese KANA

character) is quite small in a usual ECR (electronic register) due to complicated printing item data or a sheet width of printing sheet applied. Thus, in the above-mentioned printer are applied characters in reference to the size of the sheet width. Fig. 39(a) shows one example of a label and (b) illustrates one example of receipt. As shown in the figure, the item name character N1 in the label is substantially larger than the item name character N2 in the receipt normally used, and therefore it is practically impossible to issue the receipt having characters for label or to issue the label having characters for receipt. In the conventional type of the printer, only one kind of item name was defined in correspondence with one item and thus it was impossible to issue both label and receipt.

US-A-4 351 403 describes a conventional electronic scale printer including a label printing facility and suggests modifications to record weighing transactions without disclosing a technical solution.

Summary of the invention

It is an object of the present invention to provide a printer in which disadvantages of the prior art printer described above are eliminated and both label and receipt can be issued with only one printing means, and more particularly an electronic scale printer in which a cassette storing a printing sheet for a label is replaceable by a cassette storing a printing sheet for a receipt, whereby either a label or a receipt corresponding to the kind of printing sheet in the cassette is printed and then issued.

This object is met by a printer as specified in Claim 1.

It is another object of the present invention to enable the item name characters to be printed under the same condition as that of the prior art label printer or receipt printer and to provide a practical electronic scale printer in which the item name code for label and the item name code for receipt stored in response to each of the item names are stored in the memory in advance, and in case of issuing label where the cassette storing a label sheet is installed in the main body of the printer, the label is printed with the item name character pattern corresponding to the item name code for label and in turn in case of issuing receipt where the cassette storing a receipt is installed, the receipt is printed with the item name character pattern corresponding to the item name code for receipt.

A preferred embodiment of the printer of the present invention described above consists in an electronic scale printer in which the main body of the printer is electrically connected to the electronic scale, the desired data are printed on the printing sheet under an instruction from the electronic scale and issued, a cassette for storing the printing sheet for label or receipt is provided, the main body of the printer is provided with a mounting part where the cassette is removably arranged and also each of the label printing

control means and the receipt printing control means is provided as a printing control means, the above-mentioned control means can be selected in response to the kind of printing sheet stored in the installed cassette, and more practical arrangement is constructed such that it may be provided with:

a first memory having the item name code for a label and the item name code for a receipt stored in correspondence with each of the items in advance,

a second memory having several kinds of character patterns:

control means for reading out the above-mentioned item name code for label in response to an issuing instruction, transforming the read item name code for label into the character pattern through said second memory and outputting it to a printing part when the cassette storing said label sheet is installed in said cassette installing part, and in turn when the cassette storing said receipt sheet is installed at said cassette installing part, said item name code for said receipt is read out in response to the issuing instruction, the read item name code for receipt is transformed into a character pattern through said second memory and then outputted, and

a printing part for printing said label sheet or receipt sheet.

The arrangement in which the replacement of the label sheet and the receipt sheet is performed under an installation of the cassette as described above has some mechanical and electrical problems to be solved in the sheet sensing means for detecting the position or presence or absence of the label or detecting the presence or absence of the receipt which are not reviewed in the conventional type of the label printer or receipt printer.

The mechanical and technical problems consist in the structure of the label position sensor.

In the conventional type of the label printer, as shown in Fig. 11, a label position sensor 70 having a transparent type photoelectric sensor is applied, said sensor is constructed such that a light emitting element 71 and a light receiving element 72 are stored and arranged at one end of the substantial π -shaped prism 73, a label sheet L before printing is passed through a groove 74 formed at the other end of said prism 73, thereby either the front end or rear end of the label L2 is detected and the printing position of the label is controlled.

In case that the above-mentioned detector 70 is arranged at the cassette installing part of the main body of the printer of the present invention, if the cassette is slid along the installing part to perform its installation, the presence of the cassette may hinder the installation of the cassette. Thus, if the cassette is fitted over the installing part, an insertion and arrangement of the detector 70 in the cassette may be theoretically possible under an arrangement of opening at the bottom part of the cassette. However, in this case, it is difficult to perform a positive insertion of the label sheet L in respect to the groove 74 having the width 1 to be

set at a quite small value under consideration of attenuation of light and it is not practical process.

Thus, it is yet another object of embodiments of the present invention to eliminate the above-mentioned mechanical problems and to provide an electronic scale printer having a structure of label position sensing part without any troubles in installing and operation of the cassette and showing a superior practical and operative characteristic.

It is optional that the above-mentioned label position sensor has a function for detecting the presence or absence of the receipt when the receipt is to be issued.

Embodiments of the present invention which should accomplish the above-mentioned objects are characterized in that a sensing element composed of a light emitting element and a light receiving element is arranged at the cassette installing part of the main body of the printer in the above-mentioned fundamental or practical constitution, a sensing part through which the printing sheet before printing is passed is arranged at the position in said cassette where it faces against said sensing element, and the sensing part is provided with a reflection means for causing the light from said light emitting element to be crossed with a running passage of the printing sheet at one side thereof and then reflecting the light in such a direction as incidental to the light receiving element.

The electrical and technical problems found in the sheet sensing means are based upon the fact that the electronic scale printer of the present invention deals with both the label sheet and the receipt sheet and further the position, presence and absence of the label and the presence and absence of the receipt are detected by one sheet sensing means.

In order to clarify the technical problems more, one example of the receipt sheet and label sheet is shown in Fig. 7, wherein Fig. 7a illustrates one example of the receipt sheet R in which a thermosensitive sheet having a desired width is wound as a roll, Fig. 7b illustrates a part near terminal end of the label sheet L in which the thermosensitive labels L2, L2 ... are adhered on the base sheet L1 and wound as a roll.

Between each of the labels L2 is formed a sensing slit m having a width of about 2 mm ... and at the rear part of the final label L2 is also arranged a terminal end m' having no adhered part thereon.

When the label L2 is to be printed, it is necessary to confirm the position of each of the labels L2. The check of the position is usually performed by sensing the thickness of sheet due to the fact that the part of label L2 is overlapped on the base sheet L1 to make a double sheet and the part of the slit m is occupied by the base sheet L1 only.

For example, as a sheet sensing means the above-mentioned passing-through type photoelectric sensor is applied and the label sheet L is passed between the light emitting element and

the light receiving element, resulting in that the amount of passing-through light is decreased at the part of the label L2 and the amount of passing light is increased at the slit *m*, thus it is possible to judge the position of the label L2. That is, since the output of the light receiving element becomes "Low" level when the label L2 is sensed and the output becomes "High" level when the slit *m* and the terminal end *m'* are detected, it is possible to judge the presence or absence of the label by assigning "0"/"1" signals to these levels.

In turn, when the receipt sheet R is passed through said photoelectric sensor, an amount of passing-through light is decreased when the receipt sheet R is present and in turn increased when the sheet is not present, so that the presence or absence of the receipt sheet R may also be judged by this operation.

However, in this case, since the thickness of the base sheet L1 and the receipt sheet L or an amount of passing-through light is substantially coincided, it is difficult to detect the label position and to detect the receipt sheet by one photoelectric sensor.

Fig. 29 is a view for illustrating the reason for the above case. Fig. 29a illustrates a condition of either the label sheet L or the receipt sheet R, Fig. 29b illustrates the output of the photoelectric sensor when these sheets L and R pass through said photoelectric sensor, Figs. 29c and 29d illustrate a level of two-value signal got when the slice level (a reference voltage of comparator: hereinafter called as a reference voltage) is defined as E1 and E2, respectively.

As just apparent from these figures, the output levels of the photoelectric sensor when the base sheet L1 and the receipt sheet R are passed are substantially coincided to each other (Figs. 29a and 29b). When the label L2 is passed, the value is decreased lower than this level, and when the receipt sheet R is not present, it is increased more than this level. Therefore, the output level of the photoelectric sensor becomes a low (when the label L2 is passed), medium (when the base sheet L1 or the receipt sheet R is passed) and high (when the sheets R and L are not present) levels, respectively. When the reference voltage is set to E1 under the presence or absence of label L2 so as to cause the signal level to be changed over to "0"/"1", the signal becomes "1" signal irrespective of the presence or absence of the receipt sheet R (Fig. 29c), and in turn when the reference voltage is set for example to E2 so as to cause the signal level to be changed over to "0"/"1" under the presence or absence of the receipt sheet R, the signal becomes "0" signal irrespective of the presence or absence of the label L2 in case of applying label sheet L (Fig. 29d), resulting in that only either the position sensing of label L2 or the presence or absence of the receipt sheet R may be detected.

It is a still further object of embodiments of the present invention to overcome the above-mentioned technical problems, provide a printer in which the sensing of label sheet and the sensing

of receipt sheet can be performed with one sheet sensing means (sensor) and improve a practical characteristic of the electronic scale printer in which the label sheet is replaced with the receipt sheet.

Embodiments of the present invention to accomplish the above-mentioned objects are characterized in that under the above-mentioned fundamental arrangement or practical constitution an output level of the sensor is varied in response to a condition whether the sheet installed in the main body of the printer is the label sheet or the receipt sheet or not.

Another electrical and technical problem found in the sheet sensing means consists in that there are several kinds of label sheets, thickness and rate of transparency are also versatile, so that the output level of the sheet sensing means (label position sensor) is varied in reference to the kind of label sheet.

Fig. 33 shows a wave-form illustrating this condition, wherein the wave-form shown by a symbol *a* is aligned in respect to the reference voltage E1, and in turn if the label L2 and the base sheet L1 are thin, its level is increased too much as shown by the wave-form *b* and if they are thick, it is decreased as shown by the wave-form *c*, so in both cases it is not possible to discriminate the label L2 from the slit *m*.

It is a still further object of embodiments of the present invention to overcome the above-mentioned technical problems and to provide an electronic scale printer in which the output level of the level position sensor (sensor) is automatically adjusted in response to the label sheet, the sensing of the label position may always be positively performed and a high accuracy is maintained.

Embodiments of the present invention to accomplish such objects as above have a change-over means for varying the output level of the sensor in a step-wise manner and a comparator for comparing the output signal from this sensor with the reference value under the above-mentioned fundamental arrangement or the practical constitution and has as its object to set the output level of said sensor in reference to the output of said comparator when said output level is varied in sequence.

Brief description of the drawings

Fig. 1 is a perspective view for illustrating an outer appearance construction of an electronic scale assembled with the printer of the present invention.

Fig. 2 is a top plan view of a main body of the printer with its substantial part being enlarged.

Fig. 3 is a side elevational view of Fig. 12.

Fig. 4 is a perspective view for showing a cassette.

Fig. 5a is a sectional view for showing a receipt cassette.

Fig. 5b is a rear view of Fig. 5a.

Fig. 6a is a sectional view for showing a label cassette.

Fig. 6b is a rear view of Fig. 6a.

Fig. 7a is a perspective view for showing a receipt sheet.

Fig. 7b is a perspective view for showing a label sheet.

Fig. 8 is a sectional view for showing a fixing structure for a sensor 21.

Fig. 9 is a sectional view for showing a modified form of the sensing part 21a of the sensor.

Fig. 10 is a sectional view for showing an adjusting means for a guide roller G_2 .

Fig. 11 is a sectional view for showing the conventional type of structure of the sensor.

Fig. 12 is a sectional view for showing a modified form of means for sensing the kind of cassette.

Fig. 13 is a rear view of Fig. 12.

Figs. 14 and 15 are a front elevational view for showing one example of means for displaying the kind of printing sheet.

Figs. 16 to 21 illustrate some modified forms of the main body of the printer.

Fig. 16 is a top plan view of an installing part.

Fig. 17 is a sectional view of Fig. 16 with a part being broken away.

Fig. 18 is a sectional top plan view of a cassette.

Fig. 19 is a longitudinal section of the cassette.

Fig. 20 is a sectional view in top plan for showing an installing part where the cassette is installed.

Fig. 21 is a side elevational view of Fig. 20 with a part being broken away.

Fig. 22 is a sectional view for showing a modified form of a platen roller and means for driving a take-up reel.

Fig. 23 is a block diagram for showing an electrical arrangement of the electronic scale.

Fig. 24 is a block diagram for showing an electrical arrangement of the main body of the printer.

Fig. 25 is a circuit diagram for showing in detail a thermal head of the main body of the printer and the driving circuit therefor.

Fig. 26 is a circuit diagram for showing the sensors S1 to S3 and their peripheral circuit arrangements.

Fig. 27 is a view for illustrating the operation of the output level adjusting circuit 62.

Fig. 28a is a view for showing a condition of the label sheet and the receipt sheet.

Fig. 28b is a view for showing an output level of the sensor S3 when the output level is not adjusted.

Fig. 28c is a view for showing the output level of the sensor S3 after the output level is adjusted.

Fig. 28d is a view for showing the wave-form of a signal KS3 produced from the comparator 62.

Fig. 29a is a view for showing a condition of the label sheet and the receipt sheet.

Fig. 29b is a view for showing an output wave-form of said sensor when each of the sheets is passed through a photoelectric sensor.

Fig. 29c is a wave-form when said output wave-form is sliced by the voltage E1 shown in Fig. 2g.

Fig. 29d is a wave-form when said output wave-

form is sliced with the voltage E2 shown in Fig. 29b.

Fig. 30 is a view for showing an example of variation in level of the output voltage V_o of the sensor S3 when the value SD is modified.

Fig. 31 is a flow chart for illustrating an operation for adjusting the output level of the sensor S3 automatically in reference to a difference in thickness of label sheet.

Fig. 32a is a view for showing a condition of level of the output voltage V_o before an automatic level adjusting operation is performed.

Fig. 32b is a view for showing a condition of a level of the output voltage V_o after the automatic level adjusting operation is performed.

Fig. 33 is a view for showing a variation of the output level of the sensor S3 in reference to the thickness of the label sheet.

Fig. 34 is a view for showing an area arrangement of ROM 58.

Fig. 35 is a view for showing one example of a character pattern.

Fig. 36 is a view for showing an area arrangement of RAM 59.

Fig. 37 is a view for showing memory data of PLU memory area EA2 in Fig. 36.

Fig. 38 is a view for showing memory data in data register area EA3 and a total register area EA4.

Fig. 39a and Fig. 39b are a view for showing one example of a label and a receipt, respectively.

Fig. 40 is a flow chart for illustrating a printing control of an electronic scale.

Description of the preferred embodiments

Fig. 1 is an outer appearance view for showing an electronic scale in which a printer of the present invention is integrally assembled, wherein 1 designates the main body of the printer, 3 designates a cassette installing part and 11 designates a weighing pan to which a weighing sensor (not shown) such as a load cell is connected to form a weighing part 51 (see Fig. 23).

12 designates a displaying part for displaying various data such as weight, unit price and selling price etc. of the weighed item, 13 designates an operating part comprising preset keys 14, ten keys 15 and function keys 16. The preset keys 14 are a key for use in calling up preset data such as preset unit price for each of the items, the ten keys 15 are a key for use in inputting various numerical data and the function keys 16 are a key for use in correcting operation.

4 denotes a cassette for storing receipt sheet R or label sheet L shown in Fig. 7 and the cassette is removably attached to the cassette installing part 3 of the main body 1 of said printer. For convenience of description, the receipt cassette for storing the receipt sheet R is designated as 4a, the label cassette for storing the label sheet L as 4b and they are totally called as a cassette 4.

The receipt cassette 4a is formed with an opening of sheet issuing port 17 at one corner of a shallow box as shown in Fig. 5, and a platen roller

5 for use in printing and feeding the sheet is arranged at the inside of the issuing port 17 and also a cutter 18 for use in cutting the receipt sheet having printing operation completed is arranged near the issuing port 17.

In the cassette 4a is arranged a set shaft 20 for supporting a roll R' having a receipt sheet R wound therein, and a sensing part 21a and a guide roller G1 are arranged along a transporting direction of the receipt sheet ranging from the set shaft to the issuing port 17. The plate on the upper surface of the cassette 4a is a cap plate 22 arranged to be opened or closed. Upon opening of this cap plate 22, the roll R' is set on the set shaft 20, the receipt sheet R is pulled out and then loaded in such a way as the sheet may pass through the sensing part 21a, guide roller G1, platen roller 5 and the cutter 18 and finally through the issuing opening 17.

The sensing part 21a cooperates with a sensing element part S3 arranged at the installing part 3 of the main body 1 of the printer so as to construct the sensor 21 and to detect the presence or absence of the receipt sheet R, and their details will be described in detail later.

The shaft 5a of the platen roller 5 is projected downward of the cassette 4a and is provided with a gear (not shown) to be engaged with a power transmitting gear 23 of the installing part 3.

The label cassette 4b is applied for storing a label sheet L in a shallow box as shown in Fig. 6, and within the cassette 4b is arranged a label peeling-off dispenser 19 in place of the cutter 18 of the above-mentioned cassette 4a and also there are arranged in it a take-up reel 6 for winding up the base sheet L1 having the label peeled off and an adjusting guide roller G2 capable of being moved along an elongated hole 29 and fixed at any position.

Within the cassette 4b is also arranged a sensing part 21a having the same structure as that of the sensing part 21a for the cassette 4a, and the presence or absence of the label L2 and the position of the label are detected by this sensing part 21a and the sensing element part S3 (their details will be described later).

In case that the label L2 having a different length is to be applied, the guide roller G2 is moved along the elongated hole 29, thereby the distance from the sensing part 21a to the platen roller 5 can be varied in response to the length of the label.

The shaft 5a of the platen roller 5 is projected out of the cassette 4b and is provided with a gear (not shown) to be engaged with the gear 28 for use in transmitting a power at the installing part 3. Similarly, the shaft 6a of the take-up reel 6 is projected out of the cassette 4b and is provided with a rubber wheel (not shown) to be press contacted with a friction wheel 30 of the installing part 3.

Figs. 2 and 3 illustrate an installing part 3 for installing the cassette 4. When the cassette 4 is installed at the installing part 3, the thermal head 2 is arranged at a position corresponding to the

platen roller 5 and arranged such that it may be rotated around the fulcrum shaft 2a by a certain amount. The thermal head 2 is of a structure in which it may be pushed against the platen roller 5 with the desired printing pressure under an action of spring (not shown) etc.

Below the installing part 3 is arranged a stepping motor M and the motor shaft Ma is projected out of the upper surface of the installing part 3 and then is provided with a gear 26 and the friction wheel 30. The gear 25 is engaged with a gear of the platen roller 5 when the gears 26, 27 and 28 are engaged and the cassette 4b is installed and then the platen roller 5 may be rotated by the desired number of rotation. The friction wheel 30 is abutted against the rubber wheel of the cassette 4b to cause the take-up reel 6 to be rotated and to take-up the base sheet.

In case of the receipt cassette 4a, the platen roller 5 is driven only with a gear 28.

The installing part 3 of the main body 1 of the printer is provided with a sensing element part S3 which is oppositely faced against the sensing part 21a of the cassette when the cassette 4 is installed.

The sensing element part S3 is composed of a light emitting element 23 and a light receiving element 24, the light emitting element 23 and the light receiving element 24 being composed of a semiconductor element, respectively, and the former being composed of a light emitting diode and the latter being formed of a phototransistor. They are arranged in parallel and buried in the bottom wall and connected to a control unit (not shown) for controlling the driving of the stepping motor M.

The sensing part 21a of the cassette 4 which constitutes the sensor 21 along with the sensing element part S3 will be described in detail in reference to Figs. 8 to 10.

The sensing part 21a is provided with a pair of raised walls 34 and 35 which are raised from the bottom wall 33 of the cassette 4. The raised walls 34 and 35 are bent at an angle 45° in a direction crossing with each other, and the label sheet L or the receipt sheet (for a sake of convenience of description, the label sheet will be described) will pass through between these raised walls 34 and 35. To the upper end of one of the raised walls 34 and 35, for example, the raised wall 35 is connected a vertical raised guide wall 36 integrally, and the label base sheet L1 is guided by this guide wall 36.

Within the sensing part 21a is arranged a reflecting means for reflecting a light from the light emitting element 23 across the passing path of the label sheet L at one side thereof and in a direction incident to the light receiving element 24. The reflecting means is composed of a prism having a shape to be fitted in the sensing part 21a. The prism 37 is provided with a groove 38 for passing the label sheet L at its intermediate part, its lower end is fitted to the opening hole 39 of the bottom wall 33 of the cassette and is flush with the outer surface of the bottom wall 33.

The sensing part 21a is operated such that when the cassette 4 is installed in the main body 1 of the printer during its use, one label L2 subsequent to the proceeding label L2 positioned at the printing part (between the platen roller 5 and the thermal head 2) is positioned in the sensing part 21a, a light from the light emitting element 23 is reflected against a reflection means in the sensing part 21a, i.e. a prism 37 and incident to the light receiving element 24 after crossing the passing path of the label L2, an intensity of light incident to the light receiving element 24 is varied in response to the presence or absence of the label L2, thereby either the front end or rear end of the label L2 is detected and the sensing of the label position is performed. The sensing sensitivity can be improved by a method wherein the opposed surface of the prism 37 facing to both sides of the groove 38 acting as the passing path of the label L2 is made narrow. That is, a narrow width of the opposed surfaces may cause a converged part therein to enable the intensity of light to be increased.

The above-mentioned light reflecting means is not limited to the prism 37 above, but, for example, as shown in Fig. 9, it may be constructed such that the inner surfaces of the bent parts 34a and 35a of the raised walls 34 and 35 in the sensing part 21a are of a mirror surface.

In turn, in case that a displacement of the printing position of the label L2 is detected by sensing the position of the label, the printing position of the label L2 is modified. In order to modify the printing position, the number of steps of the stepping motor M for driving the platen roller 5 is varied or the length of the passing path of the label 1 is elongated or shortened by displacing the guide roller G2 as described above, and so in the present preferred embodiment, the latter means is employed as described above. Detailed illustration of the guide roller G2 is given in Fig. 10, wherein the guide roller G2 has its fulcrum shaft 45 slidably fitted in the elongated hole 29 in the cassette bottom wall 33 and engaged in the bottom wall 33 through screw 40 and washer 41.

In Fig. 10, the unit is constructed such that the kind of label L2 being used at present can be recognized by detecting the position of the guide roller G2.

That is, the bottom wall 33 of the installing part 3 of the main body 1 of the printer below the elongated hole 29 is provided with the number of sensing elements corresponding to the kind of label L2, for example, if the length of the label has three kinds, three sensing elements 42, 43 and 44 are arranged. These sensing elements 42, 43 and 44 are applied to detect the screw 40 for the guide roller G2, the sensing element being of a reflection type sensor, a microswitch and a magnetic switch such as hole element etc., and the elements are connected to a display means (not shown) and the result of sensing operation is displayed in the display means.

In case that a magnetic switch is applied as the

elements 42, 43 and 44, the screw 40 for the guide roller G2 is made as a magnet.

In the above description concerning the sensor 21, the sensing of label position has been described, wherein the label sheet L or the receipt sheet R is sensed for its presence or absence and the completion of these sheets is sensed.

As found in the above-mentioned preferred embodiment, the sensor 21 is divided into the sensing part 21a and the sensing element part S3. The sensing part 21a is arranged in the cassette 4 and the sensing element part S3 is arranged at the installing part 3 of the main body 1 of the printer and when the label sheet L or the receipt sheet R is installed at the cassette 4, the sheet L or R is passed through the sensing part 21a, so that merely the installation of the cassette 4 enables the sheet L or R to be set in the sensor 21. Therefore, the unit may provide an effective attaching or removal of the cassette 4 as well as its replacement and also no projecting member of the cassette 4 may provide such an effect as the installing direction of the cassette is not restricted.

Sensing means for sensing it if the printing sheet loaded in the cassette 4 is of a label sheet or receipt sheet will be described.

This sensing means is operated such that the sensor S1 is arranged in advance at the installing part 3 of the main body 1 of the printer, the kind of the cassette 4 is detected by the sensor and thereby the sheet is judged if it is the label sheet or the receipt sheet R. For this reason, the cassette 4a and the cassette 4b are provided with different marks, e.g. openings therein. In the preferred embodiment, a hole 46 is made at the rear surface of the label cassette 4b and the receipt cassette 4a is not provided with any openings (see Figs. 6 and 5).

The above-mentioned sensor S1 is of a reflection type sensor which is installed at the abutting portion 3' of the installing part 3 to detect the presence or absence of the hole 46 when the cassette 4 is installed and judges if the cassette is the label cassette 4b or the receipt cassette 4a by the presence or absence of the hole.

If the cassette 4b is detected, the printing sheet is a label sheet L and in turn if the cassette 4a is detected, the loading of the receipt sheet R in the main body 1 of the printer is electrically detected.

The sensor S2 provided in the installing part senses if the cassette 4 is positively installed in the installing part 3 or not (Figs. 2 and 3).

Thus, when the cassette 4 is inserted at the opening of the installing part 3 and up to the abutting position of the installing part 3, it may be fixed by a leaf spring (not shown). The thermal head 2 is abutted against the platen roller 5 and pressed with a desired pressure and at the same time it may be engaged with the driving gear of the platen roller 5 and the driving rubber wheel of the take-up reel 6 is abutted against the friction wheel 30. The sensor S2 detects if the cassette is positively installed or not and the sensor recognizes the kind of printing sheet in the cassette 4.

In the preferred embodiment of the present invention, since the two kinds of printing sheets, i.e. a label sheet and a receipt sheet are applied, the kind of the sheet can be detected by the presence or absence of the hole 46, and if there are more than three kinds of printing sheets to be sensed, two holes 46 are made and a combination of the presence or absence of each of the holes may detect the kind of sheet.

That is, the kind of the printing sheet is defined for each of the combinations of hole:hole, hole:non-hole, non-hole:hole, non-hole:non-hole etc.

In case of the sensing means applied with an opening 46 made in the cassette 4, a compatibility of the cassette is not assured.

Thus, as shown in Figs. 12 and 13, a sliding plate 47 is arranged at the hole 46 of the cassette 4 to open and close the hole 46, resulting in that a compatibility of the cassette can be improved and no trouble is found in storing of the receipt sheet R in the label cassette 4b and in storing of the label sheet L in the receipt cassette 4b.

Some modified forms of means for detecting the kind of sheet are as follows:

(1) Sensing is performed by the presence or absence of the projection by arranging it in place of the hole 46;

(2) Arranging of a reflection plate in place of the hole 46, arranging the light emitting and light receiving sensors at the installing part and the detecting operation is performed by the presence or absence of the reflection plate;

(3) Bar code label having storing content printed on it is adhered on the surface of the cassette and at the same time a scanner is arranged at the installing part to detect the bar code. The sensing not by the cassette but by the direct sensing of the sheet may also be available.

(4) The light transmitting type sensors are arranged to hold the sheet therebetween which is pulled out of the roll in the cassette, the desired amount of sheet is fed when the cassette is installed, the sheet is sensed by a variation in output in the sensor if the sheet is for a label or a receipt and at the same time the kind of printing sheet is detected in reference to the rate of light transmittance.

The kind of the printing sheet in the cassette 4 sensed in this way is display as shown in Figs. 14 and 15 by indicating the kind by an arrow or illuminating it. The display is not limited to the display part 12, but it may be arranged at a place where it may easily be seen or it may be indicated by sound.

Some modified forms of driving means for the above-mentioned platen roller 5 and the take-up reel 6 are illustrated in Figs. 16 to 22 and for the sake of convenience of description, the same component elements as that of the above-mentioned members are designated by the similar reference symbols and their description will be eliminated.

Figs. 16 to 21 illustrate a system in which the platen roller 5 is driven and the take-up reel 6 is driven by a power from the platen roller 5.

In the figures, the installing part 3 has a stepping motor M' below it, a shaft Ma' of the motor M' is projected out of the upper surface of the installing part 3, a gear 8 for use in transmitting a power force is mounted and at the same time a gear 9 is engaged with the gear 8. A shaft 9a of the gear 9 is slidably installed in an arcular groove 10 around the motor shaft Ma' and biased in one direction by a spring (not shown).

The cassette 4b is constructed such that the shaft 5a of the platen roller 5 is projected out of the cassette, a pulley 48 and a gear 49 are coaxially attached to the shaft 5a and at the same time the shaft 6a of the take-up reel 6 is similarly projected out of the cassette, a pulley 48' is fixed to the shaft 6a, a rubber belt 50 is wound around both pulleys 48 and 48' so as to transmit a power force from the shaft 5a to the shaft 6a.

The gear 49 is engaged with the gear 9 at the installing part 3 to accept the power force from the stepping motor M'.

The cassette 4b is slid and installed at the side opening in the installing part 3. In case that the gear 49 of the cassette 4b is not engaged with the gear 9 of the installing part 3, the gear 9 is moved along the arcular groove 10 while being rotated around the outer circumference of the gear 8, so that the installation of the cassette 4b causes the gear 9 to be engaged with the gear 49. Since the direction of escaping of the gear 9 is opposite to the rotational direction of the motor M', the rotation of the motor M' causes the gear 9 to be pressed against the gear 49, resulting in that a positive transmitting of power force can be assured.

The preferred embodiment of the present invention is constructed such that the platen roller 5 is driven, so that the printing can be performed by feeding the printing sheet even in case that the take-up reel is required and also in case that the take-up reel is not required.

If the cutter required for the receipt sheet and the dispenser required for the label sheet are arranged at the main body 1 of the printer or the cassette 4, the cassette may be of the same construction, the cost is not expensive and it is possible to provide a quite convenient product.

Fig. 22 illustrates a structure in which a driving source is connected to each of the platen roller 5 and the take-up reel 6. The stepping motor M1 and the DC motor M2 are mounted in the main body 1 of the printer, and the gears 28' and 30' are rotatably drive by and attached to the shafts M1' and M2' of the motors M1 and M2.

In the figure, a gear 31 engaging with the gear 28' is mounted on the shaft 5a of the platen roller 5 of the cassette 4b, and a gear 32 engaging with the gear 30' is mounted on the shaft 6a of the take-up reel 6.

Then, an electrical arrangement of an electronic scale having the main body 1 of the present invention will be described in reference to Figs. 23 to 26.

In Fig. 23, each of the weighing part 51, the main body 1 of the printer, operating part 13 and

the display part 12 having the above-mentioned constitution is connected to a bus 56 and CPU 57 through interface circuits 52, 53, 54 and 55.

58 in the figure denotes ROM (read-only-memory) for storing programs and 59 designates RAM (random-access-memory) to be applied in various calculations.

The main body 1 of the printer is, as shown in Fig. 24, composed of the following component elements:

(1) the thermal head 2 and the head driving circuit 60 for driving the thermal head;

(2) stepping motor M and a motor driving circuit 61 for controlling its driving;

(3) sensors S1 and S2 for discriminating the receipt cassette 4a and the label cassette 4b;

(4) sensor S3 for checking the receipt sheet R or the label sheet L and sensing their presence or absence and label position, and an output level adjusting circuit 62 and D/A (analogue/digital) converter circuit 63.

The thermal head 2 and its driving circuit 60 described in the above item (1) of the component elements are illustrated in detail in Fig. 25, wherein the thermal head 2 is composed of the heating resistors r_1 to r_n of 127 dots, the shift register 64 is comprised of a dot pattern corresponding to one line, the printer interface circuit 53 generates in reference to the control data fed from the CPU 57 a printing instruction signal DP to the driving circuit 60, a clock pulse CP for shifting the printing data to the shift register 64 and the printing data (serial dot data), respectively.

The fundamental circuits for the sensor S3, output level adjusting circuit 62 and D/A converter circuit 63 of the above-mentioned component element (4) are illustrated in Fig. 26. (In this figure, the sensors S1 and S2 are also shown in addition to these elements).

In Fig. 26, D/A converter circuit 63 is applied for converting SD0 to SD3 of four-bit signals fed from the printer interface circuit 53 to the analogue signal SA, and is composed of an adder circuit mainly having a calculation amplifier (hereinafter called as OP amp) OP1. To the resistors R0 to R3 for adder are applied said signal SD0 to SD3 through the voltage followers VF0 to VF3. The values of resistors R0 to R3 are, for example, weighted by 8K, 4K, 2K and 1K Ω , correspond to sixteen SD values defined by four bit signals SD0 to SD3 and thus the analogue signal SA of sixteen levels can be outputted. In the figure, the resistor Rf is a resistor for use in feeding-back operation, the resistor Rc is a resistor for accommodation and the resistor Rp is a resistor for pull-up operation.

Then, the output level adjusting circuit 62 is composed of the transistor Q1 and an equivalent resistance between the collector and emitter of the transistor Q1 is varied. The collector of the transistor Q1 is connected to the emitter of the light receiving element (phototransistor) of the sensor S3, and this connecting point is connected to the inverted input terminal of the comparator

65. As a result, the voltage at the inverted input terminal of the comparator 65, i.e. the output voltage Vo of the sensor S3 is, as shown in Fig. 27, determined by a ratio between an equivalent resistor Ra of the light receiving element 24 and the equivalent resistance Rb between the collector of the transistor Q1 and the ground (this value is a sum of an equivalent resistance value between the collector and the emitter of the transistor Q1 and the resistance value of the resistor Re between the emitter and the ground). That is, if the resistance Rb is constant, light receiving amount of the light receiving element 24 is increased, as the resistance Ra is decreased, the output voltage Vo is increased, and if the light receiving amount of the light receiving element 24 is constant (at this time, the resistance value Ra is constant), the more the resistance Rb, the more the output voltage Vo.

In the present invention, when the label sheet L is used, the light receiving amount is decreased, so that the resistance value Rb is increased to raise up the level of the output voltage Vo, and in turn when the receipt sheet 1 is used, the light receiving amount is increased and so the resistance value Rb is decreased and the level of the output voltage Vo is decreased. For example, in case of applying the label sheet L, all the signals SD0 to SD3 are applied as "1" signal, and the output signal SA of the D/A converter circuit 63 is decreased (since the OP amp OP1 forms an inverted adder, the more the values of SD0 to SD3, the less the output SA), thereby the resistance value Ro is increased. When the receipt sheet R is used, all the signals SD0 to SD3 are set to "0" signal to increase the signal SA and then the resistance value Ra is decreased. In this way, the level of the output voltage Vo is adjusted approximately constant (see Fig. 28(c)) and approaches to the upper and lower values of the reference voltage Es fed to the non-inverted input terminal of the comparator 65. Then, the comparator 65 produces the signal KS3 which becomes "High" level ("1" signal) when a relation of $V_o < E_s$ is found and in turn becomes "Low" levels ("0" signal) when a relation of $V_o > E_s$ is found (see Fig. 28(d)).

The outputs from the sensors S1 and S2 are inverted by the invertors 56 and 57 to become the signals KS1 and KS2. As a result, the signals KS1 and KS2 become "1" signal ("High" level) when the light receiving elements of the sensors S1 and S2 accept the light, and in turn become "0" signal when they do not accept the light.

Then, the operation of the preferred embodiment of the present invention will be described.

At first, when the cassette 4 is installed in the installing part 3, the cassette is judged if it is a receipt cassette 4a or a label cassette 4b. That is, if it is a receipt cassette 4a, the light receiving elements of the sensors S1 and S2 receive the light, the signals KS1 and KS2 become "1" signal and if it is a label cassette 4b, only the sensor S1 receives the light, the signal KS1 becomes "1" and the signal KS2 becomes "0" signal.

these signals KS1 and KS2 are supplied to CPU57 through the printer interface circuit 53 and the bus 56, CPU57 discriminates the cassette 4, and sets all the signals SD0 to SD3 to "0" signal when it is a receipt cassette 4a, and sets all the signals SD0 to SD3 to "1" signal when it is a label cassette 4b. With this arrangement, as described above, when the cassette is a receipt sheet R cassette, the output level of the sensor S3 is decreased and if it is a label sheet L cassette, the above-mentioned output level is increased and it is adjusted such that both levels are substantially equal. That is, in case of no output level adjusting circuit 62, the output of the sensor S3 kept at the level shown in Fig. 28b is transferred to the level shown in Fig. 28c by the output level adjusting circuit 62 in correspondence with the label sheet 1 and the receipt sheet R shown in Fig. 28a, the "High" level of the output voltage V_o of the sensor S3 becomes sufficiently higher than the reference voltage E_s and the "Low" level becomes sufficiently lower than the reference voltage E_s . As a result, the signal KS3 becomes "1" signal when the label L2 is detected in case of the label sheet L and becomes "0" signal when the base sheet L1 (i.e. slit m and terminal end m') is detected, and in turn in case of the receipt sheet R, it becomes "1"/"0" signal in response to the presence/absence of the receipt sheet R. In this way, it is possible to detect the presence or absence of and the position of the label L2 and the presence or absence of the receipt sheet R by the sensor S3.

Returning now to Fig. 26, the resistance value R_b is increased as the level of the analogue signal SA is decreased, and the level of the signal SA is decreased as the value SDs of the signals SD0 to SD3 are increased, so that these relations are as follows:

$$SD \downarrow \rightarrow SA \downarrow \rightarrow R_b \uparrow \rightarrow V_o \uparrow$$

in turn,

$$SD \downarrow \rightarrow SA \uparrow \rightarrow R_b \downarrow \rightarrow V_o \downarrow$$

When the thick label sheet L is used under a condition that the installation of the label cassette 4b is confirmed by the sensors S1 and S2, the value SD is increased to raise the output voltage V_o and in turn when the thin label sheet L is used, the value SD is decreased and the output voltage V_o is decreased and these voltages V_o are oscillated between the values over and below the reference voltage E_s (see Fig. 32b). If the output voltage V_o is adjusted as above, the output signal KS3 of the comparator 65 becomes "High" level ("1" signal) when a relation of $V_o < E_s$ is found and in turn it becomes "Low" level ("0" signal) when a relation of $V_o > E_s$ is found.

Therefore, when the cassette 4b is installed at the installing part 3, the CPU57 judges that this cassette is a label cassette at first in reference to the signals KS1 and KS2, and then automatically adjusts the value SD of the signals SD0 to SD3 in response to the thickness of the label sheet L in

such a way as the output voltage V_o of the sensor S3 is oscillated between the values of over and below the reference voltage E_s when the base sheet L1/label L2 are detected.

Fig. 30 is a view for showing how the level of the output voltage V_o is varied and illustrates each of the cases, i.e. (i) the sensor S3 has no sheet at its sensing point, (ii) the label L2 is found (iii) the base sheet L1, i.e. either the slit m or the terminal end m' is found, (iv) item completely shielding light, respectively.

As apparent from this figure, if the value SD is set to a proper value, a relation between the output voltage V_o and the reference voltage E_s can be defined as $V_o < E_s$ when the label L2 is found, and in turn as $V_o > E_s$ when the base sheet L1 is found. For example, in case of this arrangement shown in this figure, if the value SD equals to 6, the relation can be assured. The CPU57 may be perform the following process in order to set the value SD as above.

(1) the value SD is decreased in sequence from 15, 14, 13 ... and the value when the signal KS3 is changed from "0" to "1" signal, i.e. the initial value SD showing a relation of $V_o < E_s$ is stored as the value SDa (flow chart in Fig. 31, the steps SP1 to SP2). In this case, the sensing point of the sensor S3 has a label L2 or base sheet L1, so that $SD=8$ (in case of label L2) or $SD=3$ (in case of base sheet L1) in Fig. 30 is stored as SDa under the above-mentioned process;

(2) then, the label sheet L is fed by the desired length (more than the width of the slit m), the label L2 comes to the sensing point when the slit m is placed at the sensing point, the same process as that of the step (1) is performed and the initial value SD having a relation of $V_o < E_s$ is stored as SDb (steps SP3 to SP5). Also, in this case, for example, the above-mentioned value $SD=8$ or $SD=3$ is set as the value SDb in response to a condition whether the label L2 is positioned at the sensing point or the base sheet L1 is positioned at the sensing point;

(3) the value SDa and the value SDb are compared and the higher value is set as a temporary reference value SDc (steps SP6 to SP8). Thereby, the value in case of label L2 becomes a temporary reference value SDc. For example, SDc equals to 8 in case of that shown in Fig. 30. In case that the terminal end m' of the label sheet L is initially positioned at the sensing point, the value found in case of the label L1 becomes a temporary reference value SDc, and in this case an error is detected in the step SP12 described later;

(4) then, CPU57 rotates the platen roller 5 in step-by-step and feeds the label sheet L to find out the slit m . That is, the number of steps for one label L2 is initially set in a counter in the CPU57 (step SP9), the label sheet L is fed by one step while the value in this counter is decremented (steps SP10 to SP11) to search the point where the signal KS3 is changed from "1" signal to "0" signal and to detect the slit m (step SP13). In this case, if the signal KS3 is not varied even if the value in the counter becomes 0, it is judged that

the terminal end m' is sensed, the process is transferred from the step SP12 to the step SP14 to perform an error processing such as producing alarm output;

(5) thus if the presence of the slit m is confirmed, the value SD is decreased again in sequence from 15, 14, 13, ... and the value SD when the signal KS3 is changed from "0" to "1" is stored as a new temporary value SDd (steps SP15 to SP16). This process is performed in order that the level adjustment is performed again at the slit m having no printed matter due to the fact that the printed names such as store name or frame are printed in advance at the label L12 and the temporary reference value SDc set at the label L2 is not stable. In this way, if the value SD is set as SDd (in the above example, SDd equals to 3) which is found when the signal KS3 at the slit m is varied from "0" to "1", i.e. the output voltage V_o is varied from a relation of $V_o > E_s$ to a relation of $V_o < E_s$, a constant n (for example, 3) is added to the value SDd and this value becomes a reference value SDs. In the above example, a relation of $SDs = 3 + 3 = 6$ is attained.

In this way, the level of the output voltage V_o of the sensor S3 is automatically adjusted in response to the thickness of the label sheet L and the level of V_o is adjusted in such a way as it may show substantially a constant value. That is, in case that the output level adjusting circuit 62 is not present, as shown in Fig. 32a, the level of output voltage V_o which is varied in response to the thickness of the label sheet L is changed to the level shown in Fig. 32b after adjustment of level, "High" level of the output voltage V_o becomes sufficiently higher than the reference voltage E_s and "Low" level becomes sufficiently lower than the value E_s . As a result, the signal KS3 is positively changed over to "1"/"0" in response to the presence or absence of the label L2 and a positive sensing can always be performed.

Thus, when the value SD is set at the proper value SDs, similar operation is performed in the same manner as that of the conventional system, the printing and issuing of the label 4 are performed.

In the above description, the level adjustment is performed when the cassette is installed, and the level adjustment may also be performed after the key operation at the operating part, for example, the feed key in the function key is performed. With this arrangement, it is possible to prevent the label from being uselessly applied under a level adjustment for every installation of cassette.

Then, ROM58 and RAM59 in a block diagram of Fig. 23 will be described in detail.

ROM58 has areas E1 to E4 as shown in Fig. 34, each of the areas E1 to E3 has a label printing program, a receipt printing program and a control program stored therein, and the area E4 has various characters (numbers, symbols etc. are contained) and patterns (dot-patterns) stored therein. Figs. 35 (a) to (c) illustrate one example of character pattern, and the area E4 has Japanese kana characters (46 characters) of 16×8 dots

configuration shown in Fig. 35(a), numbers (ten characters) of 16×8 dots configuration, Japanese kana characters (46 characters) of 16×8 dots configuration, Chinese characters (100 characters) of 16×16 dots configuration shown in Fig. 35(b), Japanese kana characters (46 characters) of 7×5 dots configuration shown in Fig. 35(c) and numbers (ten characters) of 7×5 dots configuration and various character patterns. In this case, the character patterns of 16×9 dots and 16×16 dots are mainly applied for a label printing operation and the character pattern of 7×5 dots configuration is mainly for a receipt printing operation. Each of the character patterns is assigned with each of the character codes, and each of the character patterns is read out in reference to the character code. RAM59 is provided with a buffer area EA1 PLU (Price Look Up) memory area EA2, data register area EA3 and a total register area EA4 as shown in Fig. 36, respectively, and at the same time a working area EA5 is arranged in it. In this case, the printing buffer area EA1 is an area where character pattern to be printed on the label or receipt is written and this area has a capacity corresponding to the printing section of the maximum label. PLU memory area EA2 is an area where item number, unit price and appreciation period of each of the products and item name for label printing and item name for receipt printing are set, respectively and area for storing 100 items is kept. In this case, the item name to be printed is stored by a character code for each of the characters in the item name column for a label printing and the item name column for a receipt printing, respectively. For example, if the item name for the label printing for the item number "0152" is "roaf steak" and the item name for the receipt printing is "beef roaf", the character codes of Chinese character "ushi (beef)" of 16×16 dots, Japanese kana "O", "—" and "λ" of 16×8 dots are stored in sequence. In turn, in the item name column for the receipt printing are stored in sequence each of the character codes of the Japanese kana " ", " ", " " of 7×5 dots. The writing in the PLU memory area EA2 is performed by, for example, a host computer or key operation at the operating part 13.

The data register area EA3 is an area in which data concerning the product purchased by a consumer and as shown in data of 50 items can be written. The total register area EA4 has, as shown in Fig. 38, an area EA4-1 and an area EA4-2 where the number of items and total price of the items purchased by a consumer are written.

The input operation for the above-mentioned RAM59 will be described in reference to an example of a face-to-face selling.

The face-to-face selling used herein is a selling process in which sales personnel moves along with the consumer while the consumer moves in a selling spot, the sales personnel utilizes a nearby electronic scale everytime the consumer purchases the product and issues a label indicating a price, adhering the label on the package of the

product (at this time, money is not exchanged) and lastly the product is checked at the checkout counter to receive the money.

(1) In case that the label cassette 4b is utilized

In this case, the sales personnel sets the label cassette 4b at the installing part 3 of the main body of the printer and then a correct installation of the cassette is confirmed by the display lamp 80 of the display part 12. The label cassette 4b sensed by the sensor S1 is written into the working area EA5 of RAM59 through CPU57 for its cassette data. Then, the sales personnel mounts the product on the weighing pan 11 and inputs the item number of the product through the operating part 13. When the product is mounted on the weighing pan 11, the weight data WD corresponding to the weight of the product are outputted from the weighing part 51 (Fig. 23). When the item number is inputted, CPU57 reads out from the PLU data area EA2 of RAM59 shown in Fig. 37 PLU data corresponding to the inputted number (i.e. unit price, appreciation period, label printing item name and receipt printing item name), then transmits them to the working area EA5 and transfers the weight data WD to the working area EA5. Then, the CPU57 calculates the price of the product in reference to the weight data WD and the unit price data in the working area EA5 and stores the calculated price data in the working area EA5. Then, the CPU57 outputs the weight data WD, unit price data and price data in the working area EA5 to the display part 12. Thereby, each of the above-mentioned data is displayed in the display part 12 (Fig. 1).

In case that the single item label (one item label) is to be issued, the sales personnel depresses the print key 81 at the operating part 13. In turn, in case that a total label (label having a total price of several items printed thereon) is to be issued, the sales personnel depresses the plus key 82 at the operating part 13. When this plus key 82 is depressed, each of the PLU data, weight data W and price data in the working area EA5 is transferred to the data register area EA3 (Fig. 38) of RAM 59, the data in the area EA4-1 (initially reset) of total register area (Fig. 38) are incremented and the price data transferred from the working area EA5. Then, the sales personnel demounts the product from the weighing pan 11, puts the next product on the weighing pan 11 and then inputs the item number. Thereby, in the same manner as described above, weight data etc. are displayed at the display part 12. When sales personnel depresses the plus key 82, each of the data concerning the second product is stored, the data in the area EA4-1 of the total register area EA4 (in this case "1") are incremented and the price data are added to the data in the area EA4-2. Similar processing will be repeated in sequence. The sales personnel performs operation of the plus key 82 for the last item and then depresses the print key 81.

Thereafter, the print key 81 is depressed and the operation shown in Fig. 40 will be performed.

(2) In case that the receipt cassette 4a is to be used

In this case, when the sales personnel installs correctly the receipt cassette 4a on the installing part 3 of the main body 1 of the printer, the cassette data are written into the working area EA5 of RAM59 through CPU57 in the same manner as described above. Then, the sales personnel puts the first item on the weighing pan 11 in a quite same manner as above for the total label printing, inputs the item number, depresses the plus key 82 and then puts the second item on the weighing pan 11, inputs the item number, depresses the plus key 82 and then repeats process subsequently and finally depresses the plus key 81 upon completion of the operation of depressing plus key for the final item (n-th item). The processing performed by the CPU57 corresponding to each of the above operations is the same as that of the total label printing operation described above.

Thereafter, when the print key 81 is depressed, the processing of the CPU57 is the same as that shown in Fig. 40.

Thus, the case in which the printer of the present invention shown in Fig. 40 issues the label or receipt will be described. Prior to the starting of the printer, the feed key 83 in the function keys 16 shown in Fig. 1 is depressed in advance, and the sensor S3 of the main body 1 of the printer detects the position of the label and detects the presence or absence of the label sheet L and the receipt sheet R in advance.

(1) In case that the label is to be issued

When the sales personnel depresses the print key 81, the CPU57 advances to the step SP1 shown in Fig. 40 and checks that the above-mentioned data in the working area EA5 are a label cassette 4b and then advances to the step SP2. In the step SP2, the CPU57 judges if the plus key 82 is depressed or not. If the plus key 82 is not depressed (in the case of a single item label), the CPU57 advances to the step SP3, and performs a writing operation for the single item label data into the printing buffer area EA1.

That is, the unit price data, appreciation period data and the label printing item name data in the working area EA5 are read out, and each of the read data is transformed into the character pattern with the character patterns in the area EA4 of ROM58 which is written into the printing buffer area EA1 under the same arrangement as that of the characters when the label printing is to be performed. In turn, when the result of judgement in the step SP2 is "YES" (when the plus key is depressed), the CPU57 advances to the step SP4 to perform a writing of total label data into the printing buffer area EA1. That is, the total data in the total register area EA4-2 are transformed into the character pattern and written into the printing buffer area EA1. In this case, the writing of the unit price and the item name are not written into it.

Then, the CPU57 advances to the step SP5, the content in printing buffer area EA1 is outputted in

sequence at the main body 1 of the printer. Thereby, the label printing is performed at the main body 1 of the printer, and for example, the label (single item label in this example) shown in Fig. 39a is automatically issued. Upon completion of the label printing operation, the feeding of the label sheet is performed (step SP6) and the processing is completed upon reaching of the next label to the specified position, i.e. detecting of the slit width m by the sensor S3 (sensing of label position step SP7).

In the step SP7 described above, when the position of the label is not detected, that is, the slit m is not detected even if the desired amount of sheet is fed, the terminal end m' of the label sheet L is detected and no label condition is detected (step SP8).

When the condition of no label is detected in the step SP8, "YZS" displays it by illuminating the cassette empty light 84 of the display part 12 (step SP9).

(2) In case that the receipt is to be issued

When the sales personnel depresses the above-mentioned print key 81, the result of judgement in the step SP1 in this case is "NO" and therefore the CPU advances to the step SP10. In the step SP10, the presence or absence of the receipt sheet R is detected by the sensor S3, and when no receipt is found (step SP10-YES), the cassette empty light 84 in the display part 12 is illuminated (step SP11).

In the step SP10, when the presence of the receipt sheet is confirmed (SP10-NO), the CPU advances to the step 12, and in the step SP12, each of the data stored in the total register area EA4-1 and EA4-2 is transformed into the character pattern and then written into the printing buffer area EA1.

Then, the CPU advances to the step SP13, the content in the printing buffer area EA1 is outputted in sequence to the main body 1 of the printer. Thereby, both the total number of items and the total price are printed in the receipt sheet.

Then the CPU advances to the step SP14, the unit price data in the n -th line, receipt item name data, weight data, and price data in the data register area EA3 shown in Fig. 38 are read out in sequence and transformed into the character pattern and written into the printing buffer area EA1. Then, the CPU advances to the step SP15, and the content of the printing buffer area EA1 is outputted in sequence to the main body 1 of the printer. Thereby, the unit price, item name, weight and price of the product of the n -th order are printed on the receipt sheet.

Then, the CPU advances to the step SP16, it is judged if the printing of all items written into the data register area EA3 is completed or not. If the result of this judgement is "NO", the CPU returns back to the step SP14, a printing for the item of the $(n-1)$ th order is performed and the above-mentioned process is repeated. When the result of judgement in the step SP16 becomes "YES", the CPU advances to the step SP17. In the step SP17, the store name, date etc. are transformed

into the character pattern and written into the printing buffer area EA1 and in the step SP18 the content in the printing buffer is outputted at the main body 1 of the printer and then in the step SP19 the receipt sheet is fed. During feeding of the sheet in the step SP19, the presence or absence of the sheet is detected by the sensor S3 (in the step SP20) and when the condition of no sheet is detected (in the step SP20-YES), the CPU advances to the above-mentioned step SP11 to illuminate the cassette empty light 84 in the display part 12 and in turn when the presence of the sheet is detected (in the step SP20-NO), the desired amount of sheet is fed (in the step SP21), then the processing operation will be finished.

The above-mentioned sheet issuing operation is similarly applied to one item or a plurality of items. When the receipt is to be printed in the above-mentioned preferred embodiment, the system in which the total number of items and the total price are printed in advance compared with that of the item data is employed. The printing order is opposite to that of the receipt which is issued by a usual ECR, and this is employed in relation with the label printing control operation and it is apparent that this invention is not limited to such arrangement as above.

The cassette empty light in the display part 12 is also illuminated when the cassette 4 is not installed at the installing part 3, and is not correctly installed even if it is set in it, i.e. no output signal is produced through the sensor S2.

The above-mentioned preferred embodiment is described and illustrated in reference to the case in which the printer is integrally assembled in the electronic scale and it is apparent that the printer of the present invention can be constructed separate from the electronic scale and that they may be electrically connected to each other.

Claims

1. An electronic printer (1) suitable for connection to an electronic scale in which the desired data is printed on a printing sheet and issued comprising:

(a) a cassette installing part (3) arranged at the main body (1) of the printer such that either a receipt cassette (4a) for storing a receipt printing sheet (R) or a label cassette (4b) for storing a label printing sheet (L) may be removably attached thereto;

(b) means (51, 52) for discriminating whether the printing sheet stored in the cassette installed in said installing part is the receipt sheet (R) or the label sheet (L);

(c) printing control means (57, 58, 59) comprised of a receipt printing control means and a label printing control means in which either one of said receipt or label control means is selectable in accordance with the output of the discriminating means and

(d) a printing means (2, 5) for printing on said receipt sheet (R) or on said label sheet (L) as appropriate.

sequence at the main body 1 of the printer. Thereby, the label printing is performed at the main body 1 of the printer, and for example, the label (single item label in this example) shown in Fig. 39a is automatically issued. Upon completion of the label printing operation, the feeding of the label sheet is performed (step SP6) and the processing is completed upon reaching of the next label to the specified position, i.e. detecting of the slit width m by the sensor S3 (sensing of label position step SP7).

In the step SP7 described above, when the position of the label is not detected, that is, the slit m is not detected even if the desired amount of sheet is fed, the terminal end m' of the label sheet L is detected and no label condition is detected (step SP8).

When the condition of no label is detected in the step SP8, "YZS" displays it by illuminating the cassette empty light 84 of the display part 12 (step SP9).

(2) In case that the receipt is to be issued

When the sales personnel depresses the above-mentioned print key 81, the result of judgement in the step SP1 in this case is "NO" and therefore the CPU advances to the step SP10. In the step SP10, the presence or absence of the receipt sheet R is detected by the sensor S3, and when no receipt is found (step SP10-YES), the cassette empty light 84 in the display part 12 is illuminated (step SP11).

In the step SP10, when the presence of the receipt sheet is confirmed (SP10-NO), the CPU advances to the step 12, and in the step SP12, each of the data stored in the total register area EA4-1 and EA4-2 is transformed into the character pattern and then written into the printing buffer area EA1.

Then, the CPU advances to the step SP13, the content in the printing buffer area EA1 is outputted in sequence to the main body 1 of the printer. Thereby, both the total number of items and the total price are printed in the receipt sheet.

Then the CPU advances to the step SP14, the unit price data in the n -th line, receipt item name data, weight data, and price data in the data register area EA3 shown in Fig. 38 are read out in sequence and transformed into the character pattern and written into the printing buffer area EA1. Then, the CPU advances to the step SP15, and the content of the printing buffer area EA1 is outputted in sequence to the main body 1 of the printer. Thereby, the unit price, item name, weight and price of the product of the n -th order are printed on the receipt sheet.

Then, the CPU advances to the step SP16, it is judged if the printing of all items written into the data register area EA3 is completed or not. If the result of this judgement is "NO", the CPU returns back to the step SP14, a printing for the item of the $(n-1)$ th order is performed and the above-mentioned process is repeated. When the result of judgement in the step SP16 becomes "YES", the CPU advances to the step SP17. In the step SP17, the store name, date etc. are transformed

into the character pattern and written into the printing buffer area EA1 and in the step SP18 the content in the printing buffer is outputted at the main body 1 of the printer and then in the step SP19 the receipt sheet is fed. During feeding of the sheet in the step SP19, the presence or absence of the sheet is detected by the sensor S3 (in the step SP20) and when the condition of no sheet is detected (in the step SP20-YES), the CPU advances to the above-mentioned step SP11 to illuminate the cassette empty light 84 in the display part 12 and in turn when the presence of the sheet is detected (in the step SP20-NO), the desired amount of sheet is fed (in the step SP21), then the processing operation will be finished.

The above-mentioned sheet issuing operation is similarly applied to one item or a plurality of items. When the receipt is to be printed in the above-mentioned preferred embodiment, the system in which the total number of items and the total price are printed in advance compared with that of the item data is employed. The printing order is opposite to that of the receipt which is issued by a usual ECR, and this is employed in relation with the label printing control operation and it is apparent that this invention is not limited to such arrangement as above.

The cassette empty light in the display part 12 is also illuminated when the cassette 4 is not installed at the installing part 3, and is not correctly installed even if it is set in it, i.e. no output signal is produced through the sensor S2.

The above-mentioned preferred embodiment is described and illustrated in reference to the case in which the printer is integrally assembled in the electronic scale and it is apparent that the printer of the present invention can be constructed separate from the electronic scale and that they may be electrically connected to each other.

Claims

1. An electronic printer (1) suitable for connection to an electronic scale in which the desired data is printed on a printing sheet and issued comprising:

(a) a cassette installing part (3) arranged at the main body (1) of the printer such that either a receipt cassette (4a) for storing a receipt printing sheet (R) or a label cassette (4b) for storing a label printing sheet (L) may be removably attached thereto;

(b) means (51, 52) for discriminating whether the printing sheet stored in the cassette installed in said installing part is the receipt sheet (R) or the label sheet (L);

(c) printing control means (57, 58, 59) comprised of a receipt printing control means and a label printing control means in which either one of said receipt or label control means is selectable in accordance with the output of the discriminating means and

(d) a printing means (2, 5) for printing on said receipt sheet (R) or on said label sheet (L) as appropriate.



2. An electronic printer as set forth in claim 1 in which the main body of the printer is integrally assembled with an electronic scale and electrically connected to the scale.

3. An electronic printer as set forth in claim 1 in which the main body of the printer is made separate from an electronic scale and is electrically connected to the electronic scale.

4. An electronic printer as set forth in any one of the preceding claims in which the printing control means is composed of the following elements;

(a) a first memory (EA3) storing a receipt item name code and a label item name code corresponding to each of the items in advance;

(b) a second memory (EA4) storing plural kinds of character patterns; and

(c) control means (57) for reading out said receipt item name code in response to an issuing instruction when the printing sheet in the cassette is a receipt sheet, transforming the read receipt item name code to a character pattern through the second memory and outputting it to the printing part, and in turn reading out said label item name code in response to an issuing instruction when the printing sheet is a label sheet, and transforming the read label item name code to a character pattern through said second memory and outputting it to the printing part.

5. An electronic printer as set forth in claim 1 or 4 in which the kind of printing sheet stored in the cassette installed at the installing part is detected by discriminating the kind of cassette installed in the installing part.

6. An electronic printer as set forth in claim 5 in which through-pass holes are made at either one of the label cassette or receipt cassette, the presence or absence of through-pass holes is detected by reflection type photoelectric sensors to discriminate the kind of cassette.

7. An electronic printer as set forth in claim 6 comprising means for opening or closing the through-pass holes opened in the cassette.

8. An electronic printer as set forth in claims 1 or 4 in which a sensor comprising a light emitting element and a light receiving element is arranged at the cassette installing part of the main body of the printer, and in turn a sensing part through which a printing sheet before its printing passes is arranged at a position in the cassette facing to said sensor, the sensing part is provided with a reflection means for reflecting a light from said light emitting element at one side of a passing path of the printing sheet across the path toward the direction incident to a light receiving element, and a sheet sensing means is composed of the sensing part and said sensor.

9. An electronic printer as set forth in claim 8 in which said reflection means is composed of a prism.

10. An electronic printer as set forth in claim 8 in which said reflection means is composed of two inner mirror surfaces crossing at 90° to each other.

11. An electronic printer as set forth in claim 8 in which the sheet sensing means has a change-over means for automatically varying an output level of

the sensor in response to whether the printing sheet installed in the main body of the printer is a printing sheet or a label sheet or not, and said sheet sensing means under an operation of the change-over means detects the position of the label and the presence or absence of the receipt sheet.

12. An electronic printer as set forth in claim 8 in which the sheet sensing means has a change-over means for varying an output level of the sensor in a step-wise manner and a comparator for comparing an output signal from the sensor with a reference value, the output level of the sensor is set in reference to an output from said comparator when said output level is varied in sequence under a discrimination of the printing sheet installed in the main body of the printer as a label sheet, and thereby said output level is automatically adjusted to a substantial constant value in response to the thickness of the label sheet.

13. An electronic printer as set forth in claim 11 in which the output level adjustment of the sensor is performed when the cassette is installed.

14. An electronic printer as set forth in claim 12 in which the output level adjustment of the sensor is performed in reference to the key operation at the operating part.

15. An electronic printer as set forth in any one of claims 1, 4 or 8 in which a source of driving is arranged below the installing part of the main body of the printer, the upper surface of the installing part is provided with driving means to be driven by said source of driving, a platen roller is rotatably installed in the cassette, a power driven means for rotating said roller is arranged at outside of the cassette, a driving force of said driving means is transmitted to the platen roller through said driving means and driven means when the cassette is installed at said installing part, and a transferring of the printing sheet at a specified speed is performed under the rotation of the platen roller.

16. An electronic printer as set forth in claim 15 in which the cassette is removably attached to the installing part by sliding the cassette transversely into the installing part of the main body of the printer.

17. An electronic printer as set forth in claim 15 in which a driving motor is mounted below the cassette installing part of the main body of the printer, a motor shaft of said motor is projected out of the upper surface of said installing part, a first driving wheel is coaxially attached to the motor shaft, a second driving wheel is arranged through a gear mechanism in a properly spaced relation, the receipt cassette is provided with a driven means engaged with said second driving means at the shaft of the platen roller, the label cassette is provided with a first driven wheel engaged with said first driving wheel at the shaft of take-up reel, and is provided with a second driven wheel engaged with said second driving wheel at the shaft of the platen roller, respectively.

18. An electronic printer as set forth in claim 15 in which a driving motor is mounted below the



cassette installing part of the main body of the printer, the motor shaft of said motor is projected out of the upper surface of the installing part, a driving wheel is attached to the motor shaft, the receipt cassette is provided with a driven wheel engaged with said driving wheel at the shaft of the platen roller, the label cassette is provided with a driven wheel engaged with said driving wheel at the shaft of the platen roller, and a power transmitting means is arranged between said shaft and a take-up reel.

19. An electronic printer as set forth in claim 17 or 18 in which the driving motor is a stepping motor.

20. An electronic printer as set forth in claim 19 in which the driving wheel arranged at the main body of the printer is composed of a first gear coaxially attached to the motor shaft of the driving motor and a second gear engaged with the first gear, and the second gear is slidably arranged along the arcular groove around said motor shaft.

21. An electronic printer as set forth in claim 15 in which the stepping motor and DC motor are arranged side-by-side below the cassette installing part of the main body of the printer, motor shafts of both motors are projected out of the upper surface of the installing part, a first driving wheel and a second driving wheel are attached to each of the motor shafts, the receipt cassette is provided with a driven wheel engaged with said first driving wheel at the shaft of the platen roller, the label cassette is provided with a first driven wheel engaged with said first driving wheel at the shaft of the platen roller and is provided with a second driven wheel engaged with said second driving wheel at the shaft of the take-up reel.

22. An electronic printer as set forth in claim 8 in which the label cassette is provided with a guide roller capable of varying an installing position along an elongated hole between a sensing part through which the label sheet passes and the platen roller, the length of the passing passage of the label sheet is varied under a displacement of position of the guide roller and a sensing means for sensing the position of said guide roller.

Patentansprüche

1. Elektronischer Drucker (1), der zum Verbinden mit einer elektronischen Waage geeignet ist, in welchem die gewünschten Daten auf einem Druckblatt gedruckt und ausgegeben werden, enthaltend:

(a) einen kassetteninstallierenden Teil (3), der an dem Hauptkörper (1) des Druckers derart angeordnet ist, daß entweder eine Quittungskassette (4a) zum Speichern eines Quittungsdruckblattes (R) oder ein Etikettenkassette (4b) zum Speichern eines Etikettendruckblattes (L) an diesem entferntbar anzubringen ist;

(b) Mittel (51, 52) zum Unterscheiden, ob das in der in dem installierenden Teil installierten Kassette gespeicherte Druckblatt das Quittungsblatt (R) oder das Etikettenblatt (L) ist;

(c) Drucksteuermittel (57, 58, 59), die Quittungsdrucksteuermittel und Etikettendrucksteuermittel einschließen, in welchen entweder die Quittungs- oder Etikettensteuermittel entsprechend der Ausgangsgröße der Unterscheidungsmittel wählbar sind; und

(d) Druckmittel (2, 5) zum Drucken jeweils auf das Quittungsblatt (R) oder auf das Etikettenblatt (L).

2. Elektronischer Drucker nach Anspruch 1, bei welchem der Hauptkörper des Druckers einstückig mit einer elektronischen Waage zusammenge stellt und mit der Waage elektrisch verbunden ist.

3. Elektronischer Drucker nach Anspruch 1, bei welchem der Hauptkörper des Druckers getrennt von einer elektronischen Waage und mit der elektronischen Waage elektrisch verbunden ist.

4. Elektronischer Drucker nach einem der vorhergehenden Ansprüche, in welchem die Drucksteuermittel aus den folgenden Elementen bestehen:

(a) einem ersten Speicher (EA3), der einen Quittungsstücknamencode und einen Etikettenstücknamencode im voraus speichert, die jedem der Stücke entsprechen;

(b) einem zweiten Speicher (EA4), der eine Vielzahl Arten von Zeichenmustern speichert, und

(c) Steuermittel (57) zum Auslesen des Quittungsstücknamencodes im Ansprechen auf einen Ausgabebefehl, wenn das Druckblatt in der Kassette ein Quittungsblatt ist, zum Umwandeln des Lesequittungsstücknamencodes in ein Zeichenmuster durch den zweiten Speicher und zum Ausgeben desselben auf den Druckteil, und der Reihe nach zum Auslesen des Etikettenstücknamencodes im Ansprechen auf einen Ausgabebefehl, wenn das Druckblatt ein Etikettenblatt ist, und zum Umwandeln des Leseetikettenstücknamencodes in ein Zeichenmuster durch den zweiten Speicher und zum Ausgeben desselben auf den Druckteil.

5. Elektronischer Drucker nach Anspruch 1 oder 4, bei welchem die Art des Druckblatts, das in der an dem installierenden Teil installierten Kassette gespeichert ist, durch Unterscheiden der Art der Kassette, die in dem installierenden Teil installiert ist, festgestellt ist.

6. Elektronischer Drucker nach Anspruch 5, bei welchem Durchgangslöcher in eine der Etikettenkassetten oder Quittungskassetten eingebracht sind, wobei die Anwesenheit oder Abwesenheit von Durchgangslöchern durch reflektierend photoelektrischen Sensoren erfaßt wird, um die Art der Kassette zu unterscheiden.

7. Elektronischer Drucker nach Anspruch 6 enthaltend Mittel zum Öffnen oder Schließen der in der Kassette geöffneten Durchgangslöcher.

8. Elektronischer Drucker nach Anspruch 1 oder 4, bei welchem ein lichtabgebendes Element und ein lichtempfindendes Element enthaltend ein Sensor an dem kassetteninstallierenden Teil des Hauptkörpers des Druckers angeordnet ist, um ein Erfassungsteil, durch welches ein Druckblatt vor seinem Druck läuft, seinerseits an einer Stelle



in der Kassette gegenüber dem Detektor angeordnet ist, das Erfassungsteil mit Reflexionsmitteln zum Reflektieren von Licht von dem lichtabgebenden Element auf einer Seite eines Durchlaufwegs des Druckblatts über den Weg in die Richtung auffallend auf ein lichtempfindendes Element vorgesehen ist, und Blatterfassungsmittel aus dem Erfassungsteil und dem Sensor besteht.

9. Elektronischer Drucker nach Anspruch 8, bei welchem die Reflexionsmittel aus einem Prisma bestehen.

10. Elektronischer Drucker nach Anspruch 8, bei welchem die Reflexionsmittel aus zwei inneren Spiegelflächen bestehen, die einander unter 90° kreuzen.

11. Elektronischer Drucker nach Anspruch 8, bei welchem die Blatterfassungsmittel Umwechslungsmittel zum automatischen Variieren eines Ausgangspegel des Sensors im Ansprechen darauf aufweisen, ob das in dem Hauptkörper des Druckers installierte Druckblatt ein Druckblatt oder ein Etikettenblatt oder nicht ist, und die Blatterfassungsmittel unter Betrieb der Umwechslungsmittel die Position des Etiketts und die Anwesenheit oder Abwesenheit des Quittungsblatts erfassen.

12. Elektronischer Drucker nach Anspruch 8, bei welchem die Blatterfassungsmittel Umwechslungsmittel zum schrittweisen Variieren eines Ausgangspegels des Sensors in einer und einen Komparator zum Vergleichen eines Ausgangssignal von dem Sensor mit einem Bezugswert aufweisen, wobei der Ausgangspegel des Sensors in Bezug auf eine Ausgangsgröße des Komparators eingestellt wird, wenn der Ausgangspegel sequentiell unter einer Unterscheidung des in dem Hauptkörper des Druckers installierten Druckblatts als ein Etikettenblatt variiert wird und dadurch der Ausgangspegel automatisch auf einen im wesentlichen konstanten Wert im Ansprechen auf die Dicke des Etikettenblatts eingestellt wird.

13. Elektronischer Drucker nach Anspruch 11, bei welchem die Einstellung des Ausgangspegels des Sensors durchgeführt wird, wenn die Kassette installiert ist.

14. Elektronischer Drucker nach Anspruch 12, bei welchem die Einstellung des Ausgangspegels des Sensors unter Bezug auf die Tastenbetätigung am Betriebsteil durchgeführt wird.

15. Elektronischer Drucker nach einem der Ansprüche 1, 4 oder 8, bei welchem eine Antriebsquelle unterhalb des installierenden Teils des Hauptkörpers des Druckers angeordnet ist, die obere Oberfläche des installierenden Teils mit Antriebsmitteln versehen ist, die von der Antriebsquelle angetrieben sind, eine Plattenrolle in der Kassette drehbar installiert ist, kraftangetriebene Mittel zum Drehen der Rolle außerhalb der Kassette angeordnet sind, eine Antriebskraft der Antriebsmittel auf der Plattenrolle durch die Antriebsmittel und die kraftangetriebenen Mittel übertragen wird, wenn die Kassette an dem installierenden Teil installiert ist, und eine Über-

tragung des Druckblatts bei einer spezifizierten Geschwindigkeit unter der Rotation der Plattenrolle durchgeführt wird.

16. Elektronischer Drucker nach Anspruch 15, bei welchem die Kassette mit dem installierenden Teil durch Verschieben des Kassette quer in den installierenden Teil des Hauptkörpers des Druckers entfernbar verbunden wird.

17. Elektronischer Drucker nach Anspruch 15, bei welchem ein Antriebsmotor unterhalb des kassetteninstallierenden Teils des Hauptkörpers des Druckers angeordnet ist, eine Motorwelle des Motors aus der oberen Oberfläche des installierenden Teils herausragt, ein erstes Antriebsrad mit der Motorwelle koaxial angeordnet ist, ein zweites Antriebsrad durch einen Getriebemechanismus in einem richtigen Abstand angeordnet ist, die Quittungskassette mit Antriebsmitteln versehen ist, die mit den zweiten Antriebsmitteln auf der Welle der Plattenrolle in Eingriff stehen, die Etikettenkassette jeweils mit einem ersten angetriebenen Rad versehen ist, das mit dem ersten Antriebsrad auf der Welle der Aufwickelspule in Eingriff steht, und mit einem zweiten angetriebenen Rad versehen ist, das mit dem zweiten Antriebsrad auf der Welle der Plattenrolle in Eingriff steht.

18. Elektronischer Drucker nach Anspruch 15, bei welchem ein Antriebsmotor unterhalb des kassetteninstallierenden Teils des Hauptkörpers des Druckers angeordnet ist, die Motorwelle des Motors aus der oberen Oberfläche des installierenden Teils herausragt, ein Antriebsrad mit der Motorwelle verbunden ist, die Quittungskassette mit einem angetriebenen Rad versehen ist, das mit dem Antriebsrad auf der Welle der Plattenrolle in Eingriff steht, die Etikettenkassette mit einem angetriebenen Rad versehen ist, das mit einem Antriebsrad auf der Welle der Plattenrolle in Eingriff steht und Übertragungsmittel zwischen der Welle und einer Aufwickelspule angeordnet sind.

19. Elektronischer Drucker nach Anspruch 17 oder 18, bei welchem der Antriebsmotor ein Schrittmotor ist.

20. Elektronischer Drucker nach Anspruch 19, bei welchem das an dem Hauptkörper des Druckers angeordnete Antriebsrad aus einem ersten zu der Motorwelle des Antriebsmotors koaxial angeordneten Getrieberad und einem zweiten, mit dem ersten Getrieberad in Eingriff stehenden Getrieberad besteht, und das zweite Getrieberad entlang der bogenförmigen Rille um die Motorwelle verschiebbar angeordnet ist.

21. Elektronischer Drucker nach Anspruch 15, bei welchem der Schrittmotor und der Gleichspannungsmotor nebeneinander unterhalb des kassetteninstallierenden Teils des Hauptkörpers des Druckers angeordnet sind, die Motorwellen von beiden Motoren aus der oberen Oberfläche des installierenden Teils herausragen, ein erstes Antriebsrad und ein zweites Antriebsrad mit jeder der Motorwellen verbunden sind, die Quittungskassette mit einem Antriebsrad versehen ist, das mit dem ersten Antriebsrad auf der Welle der



Plattenrolle in Eingriff steht, die Etikettenkassette mit einem ersten Abtriebsrad versehen ist, das mit dem ersten Antriebsrad auf der Welle der Plattenrolle in Eingriff steht und mit einem zweiten Abtriebsrad versehen ist, das mit dem zweiten Antriebsrad auf der Welle der Aufwickelspule in Eingriff steht.

22. Elektronischer Drucker nach Anspruch 8, bei welchem die Etikettenkassette mit einer Führungsrolle versehen ist, die eine installierende Position entlang eines Langloches zwischen einem Erfassungsteil, dadurch welches das Etikettenblatt läuft, und der Plattenrolle variieren kann, die Länge des Durchlaufkanals des Etikettenblatts unter einer Verschiebung der Position der Führungsrolle und Erfassungsmitteln zum Erfassen der Position der Führungsrolle variiert wird.

Revendications

1. Une imprimante électronique (1) appropriée pour une connexion à une balance électronique dans laquelle la donnée désirée est imprimée sur une feuille d'impression et éditée comprenant:

(a) une partie d'installation de cassette (3) disposée au niveau du corps principal de (1) de l'imprimante de sorte que soit une cassette de reçu (4a) servant à stocker une feuille d'impression de reçu (R), soit une cassette d'étiquette (4b) servant à stocker une feuille d'impression d'étiquette (L) peut être fixée de manière amovible à celle-ci;

(b) un moyen (51, 52) servant à distinguer si la feuille d'impression stockée dans la cassette installée dans ladite partie d'installation est la feuille de reçu (R) ou la feuille d'étiquette (L);

(c) un moyen de commande d'impression (57, 58, 59) constitué d'un moyen de commande d'impression de reçu et d'un moyen de commande d'impression d'étiquette dans lequel l'un desdits moyen de commande de reçu ou d'étiquette et sélectionnable en conformité avec la sortie du moyen de discrimination;

(d) un moyen d'impression (2, 5) pour impression sur ladite feuille de reçu (R) ou sur ladite feuille d'étiquette (L) de manière appropriée.

2. Une imprimante électronique selon la revendication 1, dans laquelle le corps principal de l'imprimante est monté de manière solidaire à une balance électronique et est reliée électroniquement à la balance.

3. Une imprimante électronique selon la revendication 1, dans laquelle le corps principal de l'imprimante est fabriqué de manière séparée d'une balance électronique et est électriquement reliée à la balance électronique.

4. Une imprimante électronique selon l'une quelconque des revendications précédentes, dans laquelle le moyen de commande d'impression est composé des éléments suivants:

(a) une première mémoire (EA3) mémorisant un code de désignation d'article de reçu et un code de désignation d'article d'étiquette correspondant à l'avance à chacun des articles;

(b) une deuxième mémoire (EA4) mémorisant plusieurs sortes de formes de caractère;

(c) un moyen de commande (57) servant à extraire ledit code de désignation d'article de reçu en réponse à une instruction d'édition lorsque la feuille d'impression dans la cassette est une feuille de reçu, transformant le code de désignation d'article de reçu extrait en une forme de caractère par l'intermédiaire de la deuxième mémoire et sortant celui-ci vers la partie d'impression, et à son tour, extrayant ledit code de désignation d'article d'étiquette en réponse à une instruction d'édition lorsque la feuille d'impression est une feuille d'étiquette, et transformant le code de désignation d'article d'étiquette extrait en une forme de caractère par l'intermédiaire de ladite deuxième mémoire et sortant celui-ci vers la partie d'impression.

5. Une imprimante électronique selon la revendication 1 ou 4, dans laquelle la sorte de feuille d'impression stockée dans la cassette installée dans la partie d'installation est détectée en discriminant le genre de cassette installée dans la partie d'installation.

6. Une imprimante électronique selon la revendication 5, dans laquelle des trous de passage sont prévus sur l'une ou l'autre des cassette d'étiquette ou cassette de reçu, la présence ou l'absence des trous de passage est détectée par des détecteurs photoélectriques de type à réflexion pour discriminer le genre de cassette.

7. Une imprimante électronique selon la revendication 6, comprenant un moyen servant à ouvrir ou à fermer les trous de passage ouverts dans la cassette.

8. Une imprimante électronique selon la revendication 1 ou 4, dans laquelle un détecteur comprenant un élément émetteur de lumière et un élément de réception de lumière est disposé au niveau de la partie d'installation de la cassette du corps principal de l'imprimante, et à son tour une partie de détection par l'intermédiaire de laquelle une feuille d'impression passe avant son impression est disposée en un emplacement de la cassette faisant face audit détecteur, la partie de détection est pourvue d'un moyen de réflexion servant à réfléchir la lumière provenant dudit élément émetteur de lumière sur un côté d'un trajet de passage de la feuille d'impression à travers le chemin vers la direction incidente à un élément de réception lumière, et un moyen de détection de feuille est composé de la partie de détection et dudit détecteur.

9. Une imprimante électronique selon la revendication 8, dans laquelle ledit moyen de réflexion est constitué d'un prisme.

10. Une imprimante électronique selon la revendication 8, dans laquelle ledit moyen de réflexion est constitué de deux surfaces de miroir interne se croisant l'une l'autre à 90°.

11. Une imprimante électronique selon la revendication 8, dans laquelle le moyen de détection de feuille comporte un moyen de commutation servant à changer automatiquement un niveau de sortie du détecteur en réponse à ce que la feuille d'impression installée dans le corps principal 1 de l'imprimante est soit une feuille d'impression, soit



une feuille d'étiquette, ou non, et ledit moyen de détection de feuille, sous l'action du moyen de commutation, détecte la position de l'étiquette et la présence ou l'absence de la feuille de reçu.

12. Une imprimante électronique selon la revendication 8, dans laquelle le moyen de détection de feuille comporte un moyen de commutation servant à modifier un niveau de sortie du détecteur de manière graduelle et un comparateur servant à comparer un signal de sortie provenant du détecteur avec une valeur de référence, le niveau de sortie du détecteur est établi en référence à une sortie provenant dudit comparateur lorsque le niveau de sortie est modifié en séquence par une discrimination de la feuille d'impression installée dans le corps principal de l'imprimante sous la forme d'une feuille d'étiquette, et de la sorte ledit niveau de sortie est automatiquement ajusté à une valeur pratiquement constant en réponse à l'épaisseur de la feuille d'étiquette.

13. Une imprimante électronique selon la revendication 11, dans laquelle l'ajustement du niveau de sortie du détecteur est effectué lorsque la cassette est installée.

14. Une imprimante électronique selon la revendication 12, dans laquelle l'ajustement du niveau de sortie du détecteur est effectué en référence à l'actionnement de touche dans la partie fonctionnelle.

15. Une imprimante électronique selon l'une quelconque des revendications 1, 4 ou 8, dans laquelle une source d'entraînement est disposée en-dessous de la partie d'installation du corps principal de l'imprimante, la surface supérieure de la partie d'installation est pourvue d'un moyen d'entraînement destiné à être entraîné par ladite source d'entraînement, un cylindre d'impression est installé de manière rotative dans la cassette, un moyen commandé par moteur servant à mettre en rotation ledit cylindre et disposé à l'extérieur de la cassette, une force d'entraînement dudit moyen d'entraînement est transmise au cylindre d'impression par l'intermédiaire dudit moyen d'entraînement et un moyen entraîné lorsque la cassette est installée au niveau de ladite partie d'installation, et un déplacement de la feuille d'impression à une vitesse spécifique est effectué par rotation du cylindre d'impression.

16. Une imprimante électronique selon la revendication 15, dans laquelle la cassette est fixée de manière amovible à la partie d'installation en faisant glisser la cassette transversalement dans la partie d'installation du corps principal 1 de l'imprimante.

17. Une imprimante électronique selon la revendication 15, dans laquelle un moteur d'entraînement est monté en-dessous de la partie d'installation de la cassette du corps principal 1 de l'imprimante, un arbre de moteur dudit moteur dépasse de la surface supérieure de ladite partie d'installation, une première roue d'entraînement est fixée de manière coaxiale à l'arbre de moteur, une deuxième roue d'entraînement est disposée par l'intermédiaire d'un mécanisme d'engrenage

dans une relation proprement espacée, la cassette de reçu est pourvue d'un moyen entraîné mis en prise avec ledit deuxième moyen d'entraînement au niveau de l'arbre du cylindre d'impression, la cassette d'étiquette est pourvue d'une première roue entraînée mise en prise avec ladite première roue d'entraînement au niveau de l'arbre de la bobine d'enroulement, et est pourvue d'une deuxième roue entraînée mise en prise avec ladite deuxième roue d'entraînement au niveau de l'arbre du cylindre d'impression, respectivement.

18. Une imprimante électronique selon la revendication 15, dans laquelle un moteur d'entraînement est monté en dessous de la partie d'installation de cassette du corps principal de l'imprimante, l'arbre de moteur dudit moteur dépasse de la surface supérieure de la partie d'installation, une roue d'entraînement est fixée à l'arbre de moteur, la cassette de reçu est pourvue d'une roue entraînée mise en prise avec ladite roue d'entraînement au niveau de l'arbre du cylindre d'impression, la cassette d'étiquette est pourvue d'une roue entraînée mise en prise avec ladite roue d'entraînement au niveau de l'arbre du cylindre d'impression, et un moyen de transmission de puissance est disposée entre ledit arbre et une bobine d'enroulement.

19. Une imprimante électronique selon la revendication 17 ou 18, dans laquelle le moteur d'entraînement est un moteur pas à pas.

20. Une imprimante électronique selon la revendication 19, dans laquelle la roue d'entraînement disposée au niveau du corps principal 1 de l'imprimante est composée d'un premier engrenage fixé coaxialement à l'arbre du moteur d'entraînement et un deuxième engrenage mis en prise avec le premier engrenage, et le deuxième engrenage est disposé de manière coulissante le long de la rainure en forme d'arc autour dudit arbre de moteur.

21. Une imprimante électronique selon la revendication 15, dans laquelle le moteur pas à pas et le moteur à courant continu sont disposés côte à côte en-dessous de la partie d'installation de cassette du corps principal 1 de l'imprimante, les arbres de moteur des deux moteurs dépassent de la surface supérieure de la partie d'installation, une première roue d'entraînement et une deuxième roue d'entraînement sont fixées à chacun des arbres de moteur, la cassette de reçu est pourvue d'une roue entraînée mise en prise avec ladite première roue d'entraînement au niveau de l'arbre du cylindre d'impression, la cassette d'étiquette est pourvue d'une première roue entraînée mise en prise avec ladite première roue d'entraînement au niveau de l'arbre du cylindre d'impression et est pourvue d'une deuxième roue entraînée mise en prise avec ladite deuxième roue d'entraînement au niveau de l'arbre de la bobine d'enroulement.

22. Une imprimante électronique selon la revendication 8, dans laquelle la cassette d'étiquette est pourvue d'un rouleau de guidage propre à faire varier une position d'installation



suivant un trou de forme allongée situé entre une partie de détection entre laquelle passe la feuille d'étiquette et le cylindre d'impression, la longueur du passage de traverse de la feuille d'éti-

quette est amené à varier par un déplacement d'une position du rouleau de guidage et un moyen de détection servant à détecter la position dudit rouleau de guidage.

5

10

15

20

25

30

35

40

45

50

55

60

65

19



* C L M S *