

METHOD OF ENHANCING THE OPERATION OF DIESEL FUEL COMBUSTION SYSTEMS

Field of the Invention

The present invention relates to the use of a fuel additive for protecting and improving operation of diesel fuel combustion systems. The additive contains one or more manganese compounds. The additive can be introduced into a combustion chamber as part of the fuel. The additive will then enhance the operation of diesel fuel combustion systems by improving, for example, wear inhibition, lubricant oil life, and fuel economy.

Description of the Prior Art

It is well known in the automobile industry, or any industry where hydrocarbonaceous fuels are burned, to reduce tailpipe (or smokestack) emissions by using various strategies. For example, the most common method for reducing emissions from spark ignition engines is by careful control of the air-fuel ratio and ignition timing. Retarding ignition timing from the best efficiency setting reduces HC and NO_x emissions, while excessive retard of ignition increases the output of CO and HC. Increasing engine speed reduces HC emissions, but NO_x emissions increase with load. Increasing coolant temperature tends to reduce HC emissions, but this results in an increase in NO_x emissions.

Diesel systems raise a further set of challenges for emissions control. Strategies for reducing particulate and HC include optimizing fuel injection and air motion, effective fuel atomization at varying loads, control of timing of fuel injection, minimization of parasitic losses in combustion chambers, low sac volume or valve cover orifice nozzles for direct injection, reducing lubrication oil contributions, and rapid engine warm-up.

New diesel fuel combustion systems have been and are being engineered to improve various performance attributes. Some new types of technology to be employed may include one or more of the following: improved turbochargers, fuel injections systems, electronic engine controls, low friction coatings on engine surfaces, and exhaust gas recirculation apparatuses. Many of these systems in turn result in new performance requirements and trade-offs in the overall engine operation. For example, exhaust gas recirculation (EGR) systems result in increased combustion byproduct blowby which means increased soot in engine oils. In other words, a trade-off in the use of EGR systems is that diesel engine lubricants can be expected to have a relatively higher soot content. Other types of technologies likewise result in diesel engine lubricating oils having relatively high soot content.

Summary

In one aspect, there is provided a method of enhancing the operation of a diesel fuel combustion system, the method comprising: supplying a diesel fuel comprising an additive that includes an inorganic manganese compound to a diesel fuel combustion chamber in a diesel fuel combustion system; combusting the fuel in the combustion chamber to produce at least one byproduct comprising the manganese-containing compound; the manganese-containing compound being supplied in an amount effective to complex with the at least one combustion byproduct, wherein the diesel fuel combustion system comprises an engine oil and at least 3% mass, soot loading; whereby the diesel fuel combustion system performance is enhanced.

In another aspect, there is provided a method of enhancing the operation of a diesel fuel combustion system, the method comprising: supplying a diesel fuel comprising an additive that includes a manganese-containing compound to a diesel fuel combustion chamber in a diesel fuel combustion system; combusting the fuel in the combustion chamber to produce at least one byproduct comprising the manganese-containing compound; the manganese-containing compound being supplied in an amount effective to complex with the at least one combustion byproduct; wherein the diesel fuel combustion system comprises one or more of the following components: exhaust gas recirculation systems, either hot or cooled; variable-scroll turbochargers/variable geometry turbochargers; common-rail fuel injection systems; hydraulically-activated electronically-controlled unit injectors; turbocharged and after cooled combustion air systems; elevated mean fuel injection pressure and injection rate shaping capable systems; electronic engine control systems for combustion air, fuel and exhaust; variable valve actuation systems; homogenous charge compression ignition systems; and low friction coatings on engine surfaces, whereby the diesel fuel combustion system performance is enhanced.

Detailed Description

The additives used in the methods described herein are inorganic or organometallic manganese-containing compounds soluble in fuels. This fuel is then combusted in a diesel fuel combustion system to produce combustion byproducts including the manganese compound.

A method of enhancing the operation of a diesel fuel combustion system comprises supplying a diesel fuel comprising an additive that includes a manganese-containing compound to a diesel fuel combustion chamber in a diesel fuel combustion system, combusting the fuel in the combustion chamber to produce at least one byproduct comprising the manganese-containing compound, the manganese-containing compound being supplied in an amount effective to complex with the at least one combustion byproduct, wherein the diesel fuel combustion system comprises an engine oil and at least 3% mass, soot loading, whereby the diesel fuel combustion system performance is enhanced.

The diesel fuel combustion systems that may benefit from the present invention include all combustion engines that burn diesel fuels. By "combustion system" herein is meant any and all internal and external combustion devices, machines, engines, turbine engines, boilers, incinerators, evaporative burners, stationary burners and the like which can combust or in which can be combusted a diesel fuel. In one example, the diesel fuel combustion system requires an engine oil

formulated to accommodate at least 3% mass, soot loading. (Heavy-duty engine oils formulated to meet the API CH-4 must prevent wear in the presence of at least 3% mass, soot loading.) In another example, the engine oil is formulated to accommodate at least about 5% mass, soot loading.

Diesel fuel combustion systems are being engineered to incorporate one or more new components which may result in the accumulation of new, high mass levels of soot loading in engine lubricating oils. The new components may also demand increased engine wear, lubricant performance. These diesel fuel combustion system components include, but are not limited to, the following: exhaust gas recirculation systems, either hot or cooled; variable-scroll turbochargers/variable geometry turbochargers; common-rail fuel injection systems; hydraulically-activated electronically-controlled unit injectors; turbocharged and after cooled combustion air systems; elevated mean fuel injection pressure and injection rate shaping capable systems; electronic engine control systems for combustion air, fuel and exhaust; variable valve actuation systems; homogenous charge compression ignition systems; and low friction coatings (e.g., carbon-based and PTFE) on engine surfaces.

The new components for diesel fuel combustion systems each contribute in their own unique way to the efficiencies and performance of

the overall system. Several tradeoffs resulting from their use may include increased soot loading in the engine lubricant oil and increased lubricant performance with respect to engine wear (and new component wear).

By "diesel fuel" herein is meant one or more fuels selected from the group consisting of diesel fuel, biodiesel, biodiesel-derived fuel, synthetic diesel, diesel fuel treated with oxygenates for particulate control, and mixtures thereof and other products meeting the definitions of ASTM D975. In one example, the sulfur content of the diesel fuel would be less than about 100 ppm, and in a further example, the sulfur content would be less than about 30 ppm.

The metal disclosed herein includes elemental and ionic manganese, precursors thereof, and mixtures of metal compounds including manganese. These manganese-containing compounds may be either inorganic or organic. Also effective is the generation, liberation or production *in situ* of manganese or manganese ions.

Inorganic manganese-containing compounds of the present invention can include by example and without limitation fluorides, chlorides, bromides, iodides, oxides, nitrates, sulfates, phosphates, nitrides, hydrides, hydroxides, carbonates and mixtures thereof. Manganese sulfates and phosphates will be operative and may, in certain fuels and combustion applications, not present unacceptable additional

sulfur and phosphorus combustion byproducts. Organometallic compounds include manganese compounds with alcohols, aldehydes, ketones, esters, anhydrides, sulfonates, phosphonates, chelates, phenates, crown ethers, naphthanates, carboxylic acids, amides, acetyl acetonates, and mixtures thereof as part of the ligand systems.

In one example, manganese-containing organometallic compounds are manganese tricarbonyl compounds. Such compounds are taught, for example, in US Patent Nos. 4,568,357; 4,674,447; 5,113,803; 5,599,357; 5,944,858 and European Patent No. 466 512 B1.

Suitable manganese tricarbonyl compounds which can be used include cyclopentadienyl manganese tricarbonyl, methylcyclopentadienyl manganese tricarbonyl, dimethylcyclopentadienyl manganese tricarbonyl, trimethylcyclopentadienyl manganese tricarbonyl, tetramethylcyclopentadienyl manganese tricarbonyl, pentamethylcyclopentadienyl manganese tricarbonyl, ethylcyclopentadienyl manganese tricarbonyl, diethylcyclopentadienyl manganese tricarbonyl, propylcyclopentadienyl manganese tricarbonyl, isopropylcyclopentadienyl manganese tricarbonyl, tert-butylcyclopentadienyl manganese tricarbonyl, octylcyclopentadienyl manganese tricarbonyl, dodecylcyclopentadienyl manganese tricarbonyl, ethylmethylcyclopentadienyl manganese tricarbonyl, indenyl manganese tricarbonyl, and the like, including mixtures of two or more such

compounds. One example includes the cyclopentadienyl manganese tricarbonyls which are liquid at room temperature such as methylcyclopentadienyl manganese tricarbonyl, ethylcyclopentadienyl manganese tricarbonyl, liquid mixtures of cyclopentadienyl manganese tricarbonyl and methylcyclopentadienyl manganese tricarbonyl, mixtures of methylcyclopentadienyl manganese tricarbonyl and ethylcyclopentadienyl manganese tricarbonyl, etc.

Preparation of such compounds is described in the literature, for example, U.S. Pat. No. 2,818,417, the disclosure of which is incorporated herein in its entirety.

When formulating additives to be used in the methods and systems of the present invention, the manganese-containing compounds are employed in amounts sufficient to enhance the operation of diesel fuel combustion systems like those described herein. The amount or concentration of the additive may be selected based on the specific components incorporated into the particular combustion system and how those components affect, for instance, the amount of soot that the components cause to be loaded into the lubricating oil used in the operation of the combustion system. The amount or concentration of the additive may also be selected based on the concentration of sulfur in the diesel fuel. Exemplary treatment rates of the manganese compound can be in excess of 100 mg of manganese/liter, up to about 50mg/liter,

and in one example about 5 to about 30mg/liter.

The additive disclosed herein results in reduced total mass of soot produced. Additionally, however, the additive improves the quality of the soot particles, at least with respect to the soot particles' effect on diesel engine lubricating oils. Manganese-containing additives reduce the proportion of elemental carbon (EC) relative to the soluble organic fraction (SOF). This ratio of EC to SOF is believed to affect the hardness of soot particles, thereby affecting film strength. Reducing the proportion of EC to SOF appears to improve the quality of lubricant loaded with the soot. The effects of soot properties on the formation of boundary films and thus on the ability of soot-laden lubricant to prevent wear has been described in SAE 2002-01-2793 (Devlin et al, " Film Formation Properties of Polymers in the Presence of Abrasive Contaminants"). In this paper the wear in heavy-duty diesel engines is correlated to the formation of boundary layer films, whose presence is detected using a High Frequency Reciprocating Rig (HFRR).

The additive described herein improves soot particle quality as evidenced by the measure of boundary-layer film thickness in a first comparative study. Lubricating oils containing different amounts of soot generated with and without the manganese-containing additive (MMT) were tested in the HFRR. The treat rate of manganese-containing additive in these tests was 10 mg-Mn/liter. The results were as follows:

Table I: Effect of Soot on Boundary Film Formation Properties of Lubricants (1)

Lubricant	+ 3% Soot Formed from fuel without MMT	+3% Soot Formed from fuel with MMT	+6% Soot Formed from fuel without MMT	+6% Soot Formed from fuel with MMT
Group II Base Oil + ZDDP	41 +/- 15	69 +/- 8	3 +/- 2	33 +/- 3
Group II Base Oil + Low Molecular Weight Functionalized Olefin Copolymer (2)	37 +/- 5	71 +/- 2	21 +/- 5	55 +/- 4
Group II Base Oil + High Molecular Weight Functionalized Olefin Copolymer (3)	42 +/- 4	75 +/- 4	37 +/- 3	79 +/- 5

1. These fluids were examined since the additives in these fluids are those that form boundary films (see 2003-01-2793). The higher the test result the better the ability of the fluid to form a boundary film in the presence of soot.
2. See US Patent 5,075,383
3. See US Patent 6,107,257

In a second comparative test, lubricating oils containing equal amounts of soot but varying treat rates of manganese-containing additive were tested in the HFRR. The soot load in the test samples was 6% mass. The results were as follows:

Table II: Effect of Soot formed by fuels containing different amounts of Mn on Boundary Film Formation Properties of Lubricants (1)

Lubricant	+ 6% Soot Formed from fuel without MMT	+6% Soot Formed from fuel containing 3 mg-Mn/L	+6% Soot Formed from fuel containing 10 mg-Mn/L	+6% Soot Formed from fuel containing 20 mg-Mn/L
Group II Base Oil + ZDDP	4 +/- 2	39 +/- 2	39 +/- 5	42 +/- 10
Group II Base Oil + Low Molecular Weight Functionalized Olefin Copolymer (2)	30 +/- 1	62 +/- 8	60 +/- 2	68 +/- 1
Group II Base Oil + High Molecular Weight Functionalized Olefin Copolymer (3)	12 +/- 4	71 +/- 3	59 +/- 3	68 +/- 1

1. These fluids were examined since the additives in these fluids are those that form boundary films (see 2003-01-2793). The higher the test result the better the ability of the fluid to form a boundary film in the presence of soot.
2. See US Patent 5,075,383
3. See US Patent 6,107,257

As can be seen in the tables, the film thickness was improved (higher) in every case when the MMT additive was used. Accordingly, the operation of diesel fuel combustion engines using the fuel additive is enhanced with lower fuel consumption, lower friction (enhanced wear inhibition), and enhanced lubricant oil life (extended length of time

between oil changes).

The terms "complex" or "complexing" are intended herein to describe the combination of or reaction by the manganese containing compound with the combustion byproduct(s) such as poisons, soot and other particulates. The combination includes covalent or ionic reactions or any other binding of the metal compound with the combustion byproduct. Further, the term "combustion byproduct" includes, but is not limited to, particulates, soot, unburned soot, uncombusted hydrocarbons, partially-combusted hydrocarbons, combusted hydrocarbons, oxides of nitrogen and sulfur, and any other gas, vapor, particle or compound that results from the combustion of a fuel.

Reference is also made throughout of the term "enhanced" in the context of operation of diesel fuel combustion systems. The term "enhanced" means an improvement in the operation of the diesel fuel combustion system relative to the operation of a similar system that does not have a manganese compound combusted in it. "Enhanced" operation includes, but is not limited to, increased diesel engine lubricating oil life, and reduced engine wear and fuel consumption.

It is to be understood that the reactants and components referred to by chemical name anywhere in the specification or claims hereof, whether referred to in the singular or plural, are identified as they exist prior to coming into contact with another substance referred to by

chemical name or chemical type (e.g., base fuel, solvent, etc.). It matters not what chemical changes, transformations and/or reactions, if any, take place in the resulting mixture or solution or reaction medium as such changes, transformations and/or reactions are the natural result of bringing the specified reactants and/or components together under the conditions called for pursuant to this disclosure. Thus the reactants and components are identified as ingredients to be brought together either in performing a desired chemical reaction (such as formation of the organometallic compound) or in forming a desired composition (such as an additive concentrate or additized fuel blend). It will also be recognized that the additive components can be added or blended into or with the base fuels individually per se and/or as components used in forming preformed additive combinations and/or sub-combinations. Accordingly, even though the claims hereinafter may refer to substances, components and/or ingredients in the present tense ("comprises", "is", etc.), the reference is to the substance, components or ingredient as it existed at the time just before it was first blended or mixed with one or more other substances, components and/or ingredients in accordance with the present disclosure. The fact that the substance, components or ingredient may have lost its original identity through a chemical reaction or transformation during the course of such blending or mixing operations or immediately thereafter is thus wholly immaterial for an

accurate understanding and appreciation of this disclosure and the claims thereof.

At numerous places throughout this specification, reference has been made to a number of U.S. Patents, published foreign patent applications and published technical papers. All such cited documents are expressly incorporated in full into this disclosure as if fully set forth herein.

This invention is susceptible to considerable variation in its practice. Therefore the foregoing description is not intended to limit, and should not be construed as limiting, the invention to the particular exemplifications presented hereinabove. Rather, what is intended to be covered is as set forth in the ensuing claims and the equivalents thereof permitted as a matter of law.

Applicant does not intend to dedicate any disclosed embodiments to the public, and to the extent any disclosed modifications or alterations may not literally fall within the scope of the claims, they are considered to be part of the invention under the doctrine of equivalents.

WHAT IS CLAIMED IS:

1. A method of enhancing the operation of a diesel fuel combustion system, the method comprising:

supplying a diesel fuel comprising an additive that includes an inorganic manganese compound to a diesel fuel combustion chamber in a diesel fuel combustion system;

combusting the fuel in the combustion chamber to produce at least one byproduct comprising the manganese-containing compound;

the manganese-containing compound being supplied in an amount effective to complex with the at least one combustion byproduct,

wherein the diesel fuel combustion system comprises an engine oil and at least 3% mass, soot loading;

whereby the diesel fuel combustion system performance is enhanced.

2. The method described in claim 1, wherein the diesel fuel is selected from the group consisting of diesel fuel, biodiesel, biodiesel - derived fuel, and synthetic diesel fuel, and mixtures thereof.

3. The method described in claim 1, wherein the diesel fuel contains less than about 30 ppm of sulfur.

4. The method described in claim 1, wherein the inorganic manganese compound is selected from the group consisting of fluorides, chlorides, bromides, iodides, oxides, nitrates, sulfates, phosphates, nitrides, hydrides, hydroxides, carbonates and mixtures thereof.

5. The method described in claim 1, wherein the inorganic manganese compound is an organometallic compound.

6. The method described in claim 5, wherein the organometallic compound is selected from the group consisting of alcohols, aldehydes, ketones, esters, anhydrides, sulfonates, phosphonates, chelates, phenates, crown ethers, naphthenates, carboxylic acids, amides, acetyl acetonates and mixtures thereof.

7. The method described in claim 1, wherein the inorganic manganese compound comprises about 5 to about 30 mgMn/liter of the fuel.

8. The method described in claim 5, wherein the organometallic

compound comprises methylcyclopentadienyl manganese tricarbonyl.

9. The method described in claim 1, wherein the inorganic manganese compound is selected from the following group: cyclopentadienyl manganese tricarbonyl, methylcyclopentadienyl manganese tricarbonyl, dimethylcyclopentadienyl manganese tricarbonyl, trimethylcyclopentadienyl manganese tricarbonyl, tetramethylcyclopentadienyl manganese tricarbonyl, pentamethylcyclopentadienyl manganese tricarbonyl, ethylcyclopentadienyl manganese tricarbonyl, diethylcyclopentadienyl manganese tricarbonyl, propylcyclopentadienyl manganese tricarbonyl, isopropylcyclopentadienyl manganese tricarbonyl, tert-butylcyclopentadienyl manganese tricarbonyl, octylcyclopentadienyl manganese tricarbonyl, dodecylcyclopentadienyl manganese tricarbonyl, ethylmethylcyclopentadienyl manganese tricarbonyl, indenyl manganese tricarbonyl, and the like, including mixtures of two or more such compounds.

10. The method described in claim 1, wherein the combustion byproduct is selected from the group consisting of particulates, soot, unburned soot, uncombusted hydrocarbons, partially-combusted hydrocarbons, combusted hydrocarbons, and oxides of nitrogen and

sulfur.

11. The method described in claim 1, wherein the diesel fuel combustion system comprises one or more of the following components:

exhaust gas recirculation systems, either hot or cooled; variable-scroll turbochargers/variable geometry turbochargers; common-rail fuel injection systems; hydraulically-activated electronically-controlled unit injectors; turbocharged and after cooled combustion air systems; elevated mean fuel injection pressure and injection rate shaping capable systems; electronic engine control systems for combustion air, fuel and exhaust; variable valve actuation systems; homogenous charge compression ignition systems; and low friction coatings on engine surfaces.

12. A method as described in claim 1, wherein the engine oil is formulated to accommodate at least 3% mass, soot loading.

13. A method as described in claim 1, wherein the engine oil is formulated to prevent wear in the presence of at least 3% mass, soot loading as categorized by API CH-4 engine tests.

14. A method as described in claim 1, wherein the engine oil has at least 6% mass, soot loading.

15. A method as described in claim 1, wherein the operation of the diesel fuel combustion system is enhanced as compared to the operation of the same system without the additive that includes a manganese-containing compound.

16. A method of enhancing the operation of a diesel fuel combustion system, the method comprising:

supplying a diesel fuel comprising an additive that includes a manganese-containing compound to a diesel fuel combustion chamber in a diesel fuel combustion system;

combusting the fuel in the combustion chamber to produce at least one byproduct comprising the manganese-containing compound;

the manganese-containing compound being supplied in an amount effective to complex with the at least one combustion byproduct;

wherein the diesel fuel combustion system comprises one or more of the following components:

exhaust gas recirculation systems, either hot or cooled; variable-scroll turbochargers/variable geometry turbochargers; common-rail fuel injection systems; hydraulically-activated electronically-controlled unit

injectors; turbocharged and after cooled combustion air systems; elevated mean fuel injection pressure and injection rate shaping capable systems; electronic engine control systems for combustion air, fuel and exhaust; variable valve actuation systems; homogenous charge compression ignition systems; and low friction coatings on engine surfaces.

whereby the diesel fuel combustion system performance is enhanced.