

Description**BACKGROUND OF THE INVENTION****5 FIELD OF THE INVENTION**

The present invention relates to a new use of a trap selector which is used when, among various traps, an appropriate trap must be selected for automatically exhausting condensed water or condensate (drainage), which is produced in steam, compressed air, or at a gas piping system to which said trap is attached.

For example, a steam trap is naturally used as a self-actuated valve which automatically discharges only condensate without losing steam from the steam piping system or steam equipment. Such a steam trap is classified into a mechanical type, a thermostatic type, a thermodynamic type and the like according to its operation principle. There are steam trap types in which the condensate is continuously discharged and those in which it is intermittently discharged. The steam trap may be further classified into various types, such as a trap for low pressure or a trap for high pressure, and a trap with small capacity or a trap with large capacity.

Upon the selection of steam trap, an optimum one has to be selected so as to meet various working conditions such as steam pressure, steam temperature, condensation rate, the class or the operating state of the device to which the trap in question is attached, or the presence of the condensate for recovery.

DESCRIPTION OF THE PRIOR ART

One of the conventional trap selectors is disclosed in the Japanese unexamined patent publication (Kokai) Heisei 1-207817 (1989). This trap selector is designed to select an optimum trap which has various uses in such a way that certain data required for the selection of a trap is sequentially inputted in accordance with the indication of a display and program which is previously memorized, the selection of a trap is executed by a microcomputer.

Although the optimum trap can be automatically selected only by inputting the required data into the conventional trap selector, it has a great inconvenience in that the memory inevitably has to be enormous. This problem is caused because one of the most fundamental conditions in the selection of a steam trap or a gas trap resides in selecting a trap provided with enough discharging capability to discharge actual condensate volume and, therefore, all discharging characteristics for every pressure or temperature and the like of various kinds of traps are memorized in the trap selector mentioned above. Thus, a memory with an extremely large capacity is needed. Depending on the temperature of the discharged condensate in the steam trap, degree of reevaporation in the condensate is varied and the discharging characteristics is also changed. As described above, since all the discharging characteristics must be memorized for respective types of conditions in the conventional trap selectors, memory capacity must be further increased. The increase of memory capacity unavoidably causes the cost of the trap selector itself to be raised.

40 SUMMARY OF THE INVENTION

Accordingly, it is a primary object of the present invention to provide a trap selector capable of selecting an optimum trap in spite of small memory capacity in which the above mentioned defects and disadvantages of the conventional trap selector can be substantially eliminated.

In accordance with the present invention, this object can be attained by the following new use of a trap selector for selecting an optimum trap meeting various uses which selector comprises a keyboard to sequentially input in case of selection required data for selecting the trap, a display, a memory and a microprocessor unit to execute previously memorized trap selecting programs wherein the geometrical conditions of various kinds of traps are contained in the memory of the selector, the thermodynamical working conditions such as pressure thereof are subsequently inputted, when the optimum trap must be selected, and the microprocessor unit is calculating the discharging flow rate (capacity), comparing it to the actually required discharging flow rate and then selecting the optimum trap.

The function of the trap selector according to the present invention will be described in the following.

The geometrical conditions of a trap, that is, the diameter of an orifice, the figure of a passage and the like, are inherent in each trap and univocally determined. The discharging flow rates of the several traps are respectively calculated from the geometrical conditions and the thermodynamical working conditions such as pressure, which are different in accordance with working conditions. Accordingly, the discharging flow

rates for the respective working conditions of the several traps had not previously been put into memory. The calculated discharging flow rates of the various kinds of traps are compared with the flow rate necessary for the actual use, as a result of which, an optimum trap capable of discharging the desired flow rate can be selected.

5 According to the present invention, since it is not necessary to memorize the discharging flow rates for the respective working conditions of the various traps, the memory capacity prior to the selection can be significantly reduced and the optimum trap can be selected based on the use of the small memory.

These objects and advantages of the present invention will become apparent upon reference to the following explanation, attendant claims and drawings.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a general front view showing an embodiment of a trap selector according to the present invention,

15 Fig. 2 is a block diagram of a main circuit according to the present invention and

Fig. 3 is a functional block diagram in the embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

20 An embodiment of the present invention showing a form of the aforementioned technical improvement will be explained hereafter.

Referring to Fig. 1 showing one embodiment of a trap selector according to the present invention, a trap selector 1 has a housing 2 into which various circuits are built, as well as a control panel 3 provided on surface thereof. On the control panel 3 are arranged a keyboard 4 and a display 6. The various circuits built
25 into housing 2, as shown in Fig. 2, consist of a power source 10, a memory 11, an MPU 12, a communication control part 13, an interface 14 and the keyboard 4 and the display 6 connected thereto. In the memory 11, a selection logic for selecting an optimum steam trap, and various engineering expressions associated with the selection logic are memorized, and, in addition thereto, geometrical conditions concerning the diameter of an orifice, the figure of a passage, etc., in a variety of steam traps are also
30 memorized. The geometrical conditions: C_v may be represented by the following expression:

$$C_v = W/w_1$$

where W indicates the measured value of the discharging flow rate of a trap, and w_1 is represented by the
35 flow rate in the case of $C_v = 1$. This w_1 can be obtained by a relational expression mentioned below.

The contents of the selection logic and the various engineering expressions, which are indicated in Fig. 3, are sequentially indicated on the display and an optimum trap can be selected while various kinds of engineering calculations are executed if required. This operation will be explained in detail hereinafter.

For instance, when the optimum steam trap employed for a steam main pipe is selected, "1. trap selection" should be designated from [Main Menu] indicated on the left side of Fig. 3. When the [Main Menu] is selected, the indication on the display 6 is changed to changed to [Trap Selection] indicated in the central and upper part of Fig. 3, so that "1. steam trap" should be designated therefrom. When the [Trap Selection] is selected, the indication is changed to [Steam Trap] shown in the upper part of the right side of Fig. 3, "1. steam main" should be similarly designated. In this step, the thermodynamical conditions such
45 as primary steam pressure, the secondary steam pressure and the fluid temperature of the steam trap are inputted and the discharging flow rate for the respective working conditions of the steam trap is obtained from the product of the thermodynamical conditions and the geometrical conditions of the steam trap. This will be explained by using the following expression in accordance with the standard of INSTRUMENT SOCIETY OF AMERICA.

50

$$F_s = C_v \times f(P_1, P_2, \Delta t)$$

where F_s indicates discharging flow rate under a certain condition of a steam trap, C_v indicates the geometrical conditions of the trap, P_1 indicates the primary steam pressure of the trap, P_2 indicates the
55 secondary steam pressure of the trap and Δt indicates the difference between fluid temperature and saturation temperature.

The above mentioned $f(P_1, P_2, \Delta t)$ is represented by the following expression:

$$f(P_1, P_2, \Delta t) = 856 F_L ((P_1 - F_F P_V) G_s)^{1/2}$$

where

$$F_L = ((P_1 - P_2) / (P_1 - P_{VC}))^{1/2}$$

$$F_F = 0,96 - 0,28 (P_V / P_C)^{1/2}$$

P_V indicates saturation pressure corresponding to the temperature of condensate on the primary side of the trap,

P_{VC} indicates the minimum value of pressure in contraction flow immediately behind the orifice,
 G_s indicates specific weight of the condensate.

After the above mentioned procedure, other data required for the selection of the optimum trap including condensation rate or the safety factor of a trap is inputted and the discharging flow rate of the steam trap is compared with the actual condensation rate, the optimum steam trap thereby being determined. The safety factor may be previously programmed and possibly replaced by another one. Further, trap type, trap body material, trap size, trap model and trap material may be selected from among a group of steam traps roughly sorted as a result of the input described above so as to select the optimum steam trap.

The relation between other functions and input items in the trap selection shown in Fig. 3 will be designated as follows in Table 1:

Table 1

function		input items
steam trap	steam insulation	steam pressure, steam temperature, trap back pressure, condensation rate, ambient temperature, etc.
	steam equipment	max. working steam pressure, steam temperature, trap back pressure, condensation rate, etc.
	heater	steam pressure, trap back pressure, estimated condensation rate
	flash tank	condition of condensate for recovery, set pressure for flash tank
	nuclear power plant	max. working steam pressure, steam temperature, trap back pressure, condensation rate, etc.
gas (air) trap		inlet pressure, back pressure, temperature of water
engineering of discharging liquid flow rate		inlet pressure, back pressure, degree of subcooling condensate etc.

In case the actual condensation rate is not obvious, "3. calculation for steam consumption" should be specified from [Calculation for Steam] indicated in the central part of the right side of Fig. 3 and it should be obtained according to the procedure mentioned below.

In order to calculate the condensation rate produced in a steam main pipe when heat insulation is not made, data to be inputted will be listed below:

pipe size: A (mm)

schedule number: Sch

pipe material: STPG, SGP, etc.

length of pipe: L (m)

steam pressure: P (kg/cm² G)

ambient temperature: T_o (°C)

Data memorized in the memory of the trap selector is described in the following:

weight per unit length for the size of each pipe, schedule number and each material

specific heat for each pipe material

corresponding relation of tables for saturated steam and for superheated steam.

From the inputted data and the memorized data, the following data is calculated:

Initially, from the relation illustrated in the table for steam by steam pressure P, the following data can be obtained:

1. steam temperature: T_s ($^{\circ}\text{C}$)
2. latent heat of steam: r (Kcal/kg)

Furthermore, from the diameter of pipe size A, schedule number Sch and pipe material, the following data can be obtained:

3. weight per unit length of pipe: G_U (kg/m)
4. specific heat of pipe: C

From the above mentioned data, the condensation rate Q (kg) can be calculated from the following expression:

$$Q = C \times L \times G_U (T_s - T_0) / r$$

As shown in Fig. 3, other engineering calculations associated with the trap selection, for instance, calculation on merit of condensate for recovery or steam piping design and the like can be properly selected and thus executed by the use of a well-known relational expression.

As apparent from the above description, according to the present invention, since the geometrical conditions of the trap are previously memorized, the thermodynamical conditions such as pressure, temperature, etc. are subsequently inputted and the discharging flow rate, in other words, the discharging flow capacity of the trap, is calculated. An optimum trap can be selected by the use of a memory with small capacity without memorizing the discharging flow capacity for various working conditions of various traps. This is an excellent effect that cannot be attained by the conventional technique.

Claims

1. The use of a trap selector for selecting an optimum trap meeting various uses which selector comprises a keyboard to sequentially input in case of selection required data for selecting the trap, a display, a memory and a microprocessor unit to execute previously memorized trap selecting programs wherein the geometrical conditions of various kinds of traps are contained in the memory of the selector, the thermodynamical working conditions such as pressure thereof are subsequently inputted, when the optimum trap must be selected, and the microprocessor unit is calculating the discharging flow rate capacity, comparing it to the actually required discharging flow rate and then selecting the optimum trap.
2. The use according to claim 1, wherein the condensation rate is calculated by inputting data in accordance with input items which are automatically instructed by said trap selector.
3. The use according to claim 1 or 2, wherein a program for executing various kinds of engineering calculations which are associated with the trap is further contained in the memory.
4. The use according to any of the aforementioned claims, wherein various engineering expressions associated with the selection logic are further contained in the memory.
5. The use according to any of the aforementioned claims, wherein the geometrical conditions concern with the diameter of an orifice, the figure of a passage, etc., in a variety of steam traps.
6. The use according to any of the aforementioned claims, wherein the contents of the selection logic and the various engineering expressions are sequentially indicated on the display.
7. The use according to any of the aforementioned claims, wherein the selection logic displays a menu of items and each calculation process in said sequence is successively executed by selecting either the item of the menu or by inputting the numerical value of the required parameter.
8. The use according to any of the aforementioned claims, wherein the steam flow rate of the trap can be expressed by the product of the thermodynamical conditions and the geometrical conditions of the steam trap.



From the inputted data and the memorized data, the following data is calculated:

Initially, from the relation illustrated in the table for steam by steam pressure P, the following data can be obtained:

1. steam temperature: T_s ($^{\circ}\text{C}$)
2. latent heat of steam: r (Kcal/kg)

Furthermore, from the diameter of pipe size A, schedule number Sch and pipe material, the following data can be obtained:

3. weight per unit length of pipe: G_U (kg/m)
4. specific heat of pipe: C

From the above mentioned data, the condensation rate Q (kg) can be calculated from the following expression:

$$Q = C \times L \times G_U (T_s - T_0) / r$$

As shown in Fig. 3, other engineering calculations associated with the trap selection, for instance, calculation on merit of condensate for recovery or steam piping design and the like can be properly selected and thus executed by the use of a well-known relational expression.

As apparent from the above description, according to the present invention, since the geometrical conditions of the trap are previously memorized, the thermodynamical conditions such as pressure, temperature, etc. are subsequently inputted and the discharging flow rate, in other words, the discharging flow capacity of the trap, is calculated. An optimum trap can be selected by the use of a memory with small capacity without memorizing the discharging flow capacity for various working conditions of various traps. This is an excellent effect that cannot be attained by the conventional technique.

Claims

1. The use of a trap selector for selecting an optimum trap meeting various uses which selector comprises a keyboard to sequentially input in case of selection required data for selecting the trap, a display, a memory and a microprocessor unit to execute previously memorized trap selecting programs wherein the geometrical conditions of various kinds of traps are contained in the memory of the selector, the thermodynamical working conditions such as pressure thereof are subsequently inputted, when the optimum trap must be selected, and the microprocessor unit is calculating the discharging flow rate capacity, comparing it to the actually required discharging flow rate and then selecting the optimum trap.
2. The use according to claim 1, wherein the condensation rate is calculated by inputting data in accordance with input items which are automatically instructed by said trap selector.
3. The use according to claim 1 or 2, wherein a program for executing various kinds of engineering calculations which are associated with the trap is further contained in the memory.
4. The use according to any of the aforementioned claims, wherein various engineering expressions associated with the selection logic are further contained in the memory.
5. The use according to any of the aforementioned claims, wherein the geometrical conditions concern with the diameter of an orifice, the figure of a passage, etc., in a variety of steam traps.
6. The use according to any of the aforementioned claims, wherein the contents of the selection logic and the various engineering expressions are sequentially indicated on the display.
7. The use according to any of the aforementioned claims, wherein the selection logic displays a menu of items and each calculation process in said sequence is successively executed by selecting either the item of the menu or by inputting the numerical value of the required parameter.
8. The use according to any of the aforementioned claims, wherein the steam flow rate of the trap can be expressed by the product of the thermodynamical conditions and the geometrical conditions of the steam trap.



9. The use according to claim 8, wherein a measured value is used as the valve flow coefficient C_v .
10. The use according to claim 8, wherein the valve flow coefficient C_v is determined by using the measured steam flow rate of the trap.

Patentansprüche

1. Verwendung eines Kondensatableiter-Wählers zum Selektieren eines optimalen Kondensatwasser-Ableiters, der mehrere Verwendungen erfüllt, wobei der Wähler eine Tastatur zur sequentiellen Eingabe, falls selektionsbedingt Daten für die Selektion des Kondensatwasser-Ableiters erforderlich sind, ein Display, einen Speicher und eine Mikroprozessoreinheit für die Ausführung von zuvor eingespeicherten Kondensatwasserableiter-Selektionsprogrammen umfaßt, wobei die geometrischen Bedingungen verschiedener Typen von Kondensatwasser-Ableitern im Speicher des Wählers enthalten sind, und die thermodynamischen Arbeitsbedingungen wie dessen Druck nachfolgend eingegeben werden, wenn der optimale Kondensatwasser-Ableiter gewählt werden muß, und die Mikroprozessoreinheit die Abfluß-Flußgeschwindigkeits-Kapazität berechnet und sie mit der tatsächlich erforderlichen Abfluß-Flußgeschwindigkeit vergleicht und dann den optimalen Kondensatwasser-Ableiter selektiert.
2. Verwendung nach Anspruch 1, wobei die Kondensationsgeschwindigkeit durch Eingabe von Daten entsprechend Eingabepositionen berechnet wird, die automatisch durch den Kondensatableiter-Wähler angegeben werden.
3. Verwendung nach Anspruch 1 oder 2, wobei im Speicher ferner ein Programm zur Ausführung verschiedener Arten von technischen Berechnungen enthalten ist, die mit dem Kondensatableiter in Zusammenhang stehen.
4. Verwendung nach einem der vorstehenden Ansprüche, wobei im Speicher ferner verschiedene technische Formeln enthalten sind, die mit der Selektionslogik in Zusammenhang stehen.
5. Verwendung nach einem der vorstehenden Ansprüche, wobei die geometrischen Bedingungen bezüglich des Durchmessers einer Auslaßöffnung, der Auslegung eines Durchlaufs, etc. in verschiedenen Dampfkondensat-Ableitern betreffen.
6. Verwendung nach einem der vorstehenden Ansprüche, wobei die Inhalte der Selektionslogik und die verschiedenen technischen Formeln sequentiell auf dem Display angegeben werden.
7. Verwendung nach einem der vorstehenden Ansprüche, wobei die Selektionslogik ein Menü von Positionen anzeigt und jeder Berechnungsvorgang in der Sequenz nacheinander ausgeführt wird, entweder durch Selektion der Position aus dem Menü oder durch Eingabe des numerischen Wertes des erforderlichen Parameters.
8. Verwendung nach einem der vorstehenden Ansprüche, wobei die Dampf-Flußgeschwindigkeit des Kondensatwasser-Ableiters durch das Produkt aus den thermodynamischen Bedingungen und den geometrischen Bedingungen des Dampfkondensatwasserableiters ausgedrückt werden kann.
9. Verwendung nach Anspruch 8, wobei ein gemessener Wert als Ventil-Flußkoeffizient C_v verwendet wird.
10. Verwendung nach Anspruch 8, wobei der Ventil-Flußkoeffizient C_v durch Verwendung der gemessenen Dampf-Flußgeschwindigkeit des Kondensatwasser-Ableiters festgestellt wird.

Revendications

1. L'utilisation d'un sélecteur de purgeur destiné à sélectionner un purgeur optimal répondant à différentes utilisations, sélecteur qui comprend un clavier pour l'entrée en séquence, en cas de sélection, des données requises pour la sélection du purgeur, un dispositif d'affichage, une mémoire et une unité de microprocesseur pour l'exécution des programmes de sélection de purgeur préalablement mémorisés, dans laquelle les conditions géométriques de différents types de purgeurs sont contenues dans la mémoire du sélecteur, les conditions de service thermodynamiques, telles que la pression, sont



entrées ultérieurement, lorsque le purgeur optimal doit être sélectionné, et l'unité de microprocesseur calcule la capacité de débit de décharge, la compare au débit de décharge réellement requis et ensuite sélectionne le purgeur optimal.

- 5 2. L'utilisation suivant la revendication 1, dans laquelle le taux de condensation est calculé en entrant des données selon les données d'entrées pour lesquelles ledit sélecteur de purgeur donne automatiquement des instructions.
3. L'utilisation suivant la revendication 1 ou 2, dans laquelle un programme pour l'exécution de différents types de calculs d'ingénierie qui sont associés au purgeur est, en outre, contenu dans la mémoire.
- 10 4. L'utilisation suivant l'une quelconque des revendication précédentes, dans laquelle différentes expressions d'ingénierie associées à la logique de sélection sont, en outre, contenues dans la mémoire.
- 15 5. L'utilisation suivant l'une quelconque des revendication précédentes, dans laquelle les conditions géométriques concernent le diamètre d'un orifice, la figure d'un passage, etc. dans une variété de purgeurs à vapeur.
- 20 6. L'utilisation suivant l'une quelconque des revendication précédentes, dans laquelle le contenu de la logique de sélection et les différentes expressions d'ingénierie sont indiquées en séquence au dispositif d'affichage.
- 25 7. L'utilisation suivant l'une quelconque des revendication précédentes, dans laquelle la logique de sélection affiche un menu de données et chaque opération de calcul dans ladite séquence est réalisée successivement soit en sélectionnant la donnée du menu, soit en entrant la valeur numérique du paramètre requis.
- 30 8. L'utilisation suivant l'une quelconque des revendication précédentes, dans laquelle le débit de vapeur du purgeur peut être exprimé par le produit des conditions thermodynamiques et des conditions géométriques du purgeur à vapeur.
9. L'utilisation suivant la revendication 8, dans laquelle une valeur mesurée est utilisée comme coefficient de débit de soupape C_v .
- 35 10. L'utilisation suivant la revendication 8, dans laquelle le coefficient de débit de soupape C_v est déterminé à l'aide d'un débit de vapeur mesuré du purgeur.

40

45

50

55