



(51) International Patent Classification:
F16K 37/00 (2006.01)

(21) International Application Number:
PCT/US2013/058553

(22) International Filing Date:
6 September 2013 (06.09.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
13/606,499 7 September 2012 (07.09.2012) US

(71) Applicant: PENTAIR VALVES & CONTROLS US LP
[US/US]; 5500 Wayzata Boulevard, Ste. 800, Golden Valley, MN 55416 (US).

(72) Inventor; and

(71) Applicant : MINERVINI, Leo [US/US]; 230 Diane Place, Paramus, NJ 07652 (US).

(74) Agents: DAUGHERTY, Raye, Lynn et al.; Quarles & Brady LLP, 411 E. Wisconsin Avenue, Ste. 2350, Milwaukee, WI 53202 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

(54) Title: VIRTUAL LIMIT SWITCH

(57) Abstract: A method associated with a valve package having a process valve, an actuator and a controller. The method includes obtaining a baseline signature corresponding to opening or closing the valve as the valve moves from a first position to a second position. The method also includes obtaining an operating signature corresponding to values associated with the baseline signature each time the valve moves from the first position to the second position. In addition, the operating signature is compared to the baseline signature. The method further includes determining if one or more of the values associated with the operating signature is within an acceptable range from the corresponding one or more values in the baseline signature.



WO 2014/039852 A2