

【DESCRIPTION】**【Invention Title】**

STEREOSCOPIC IMAGE PROJECTING SYSTEM USING CIRCULARLY POLARIZED FILTER
MODULE

【Technical Field】

<1> The present invention relates to a stereoscopic image projection system, and more particularly, to a stereoscopic image projection system using a circular polarized filter module according to a single projector circular polarization method.

【Background Art】

<2> A general method for implementing stereoscopic images (or 3D images) is to emit different images to two human eyes. Stereoscopic displays are mainly divided into glasses stereoscopic displays and glassless (naked-eye) stereoscopic displays according to whether or not it is necessary for the viewer to wear glasses in order to emit different images to their two eyes, respectively.

<3> Especially, projection of stereoscopic images implemented through a large screen as in a movie theater typically uses a polarization method in which left and right images separately pass through polarized glasses having left and right polarized lenses with orthogonal polarization directions. This method implements stereoscopic image projection in the following manner. First, images are captured using two cameras. The images are given orthogonal polarization directions through polarizers and their overlapping images are then displayed on a screen. Then, the viewer views the images captured using the two cameras with their two eyes through polarized glasses.

<4> FIG. 1 illustrates the structure of a conventional dual projector system for stereoscopic image projection.

<5> To provide stereoscopic image projection according to the polarization method, the conventional dual projector system uses two conventional two-dimensional (2D) projectors 1 and 2. One of the 2D projectors 1 emits left images and the other 2D projector 2 emits right images. The left and right

images are then projected on a screen 5 after passing through polarized filters 3 and 4 with orthogonal polarization directions. The left and right images overlapping on the screen 5 are then viewed separately by the two eyes of the viewer through left and right image lenses 7 and 8 of polarized glasses 6 worn by the viewer, so that the viewer feels as if they view 3D images.

<6> The conventional dual projector stereoscopic image projection system is very expensive since it uses two 2D image projectors and two polarized plates as described above and also includes peripheral devices. The number of projectors required to project stereoscopic films in a theater is twice the number of the movies since two projectors are required for each movie. The positions of left and right images projected on the screen vary depending on the positions of the two projectors. Therefore, incorrect adjustment of the positions of the two projectors reduces the conformity of stereoscopic images.

<7> Thus, there has been a need to provide a single-projector system for stereoscopic image projection. Systems based on a method of dividing the area of the single projector LCD module and a method of using an LCD shutter has been developed to meet the need.

<8> FIG. 2 illustrates the structure of the conventional system for stereoscopic image projection based on the method of dividing the LCD module.

<9> The conventional stereoscopic image projection system shown in FIG. 2 operates in the following manner. First, light generated by a light source 201 is reflected using a reflecting mirror 202. The reflected light passes through an LCD module 203, which then outputs left and right images with different polarization directions. The left and right images are projected on a screen 205 through a condenser lens 204. The left and right images projected on the screen 205 are separated by passing through left and right image lenses 206a and 206b of polarized glasses 206 worn by the viewer, respectively, so that the viewer feels as if they view 3D images.

<10> The following is a detailed description of how left and right images

come to have different polarization directions as light passes through the LCD module 203.

<11> The LCD module 203 includes two polarized films 209 and 210. Each of the polarized films 209 and 210 includes pairs of two regions with orthogonal polarization directions that are alternately arranged in a vertical direction. Specifically, the polarized film 209 includes pairs of two regions, first polarized regions 209a and second polarized regions 209b, and the polarized film 210 includes pairs of two regions, third polarized regions 210a and fourth polarized regions 210b. A beam displaying left images included in the light reflected by the reflecting mirror 202 passes through the first polarized regions 209a of one of the polarized films 209 included in the LCD module 203, while a beam displaying right images included in the light reflected by the reflecting mirror 202 passes through the second polarized regions 209b of the same polarized film 209, which have a phase different of 90 degrees with the first polarized regions 209a, so that the reflected beams displaying left and right images come to have orthogonal polarization directions. Then, as the liquid crystal is driven according to whether or not each image is to be displayed, the emitted left images pass through the third polarized regions 210a included in the other polarized film 210, which have a phase difference of 90 degrees with the first polarized regions 209a, while the emitted right images pass through the fourth polarized regions 210b included in the other polarized film 210, which have a phase difference of 90 degrees with the second polarized regions 209b, so that the left and right images come to have orthogonal polarization directions. Then, the beams of left and right images are projected on the screen 205 after passing through the condenser lens 204. As a result, left and right images with orthogonal polarization directions are alternately arranged on the screen 205. The viewer separately recognizes the left and right images through the polarized glasses 206.

<12> The method of projecting stereoscopic images through division of the area of the LCD module 203 has a problem that the overall resolution is

reduced since the projected area is divided into left image projected regions and right image projected regions. That is, as the total area of each of the left and right images projected on the screen decreases, the resolution of each image, which has passed through each lens of the polarized glasses, must be reduced, which limits its application to movie theaters with large screens.

<13> In addition, left and right images must correctly pass through their defined regions. Otherwise, the stereoscopic image quality will be reduced. It is difficult to avoid this problem when left and right images are processed separately in space. When stereoscopic images are projected on a large screen as in a movie theater, it is not easy to adjust the positions of left and right images projected on the screen since small position mismatching at the projector will significantly reduce the conformity of stereoscopic images at the viewer.

<14> FIG. 3 illustrates the structure of a conventional LCD-shutter-based system for stereoscopic image projection.

<15> To overcome the problem that may occur when left and right images are spatially divided in the single projector method, the method shown in FIG. 3 produces stereoscopic image content including alternating left and right images. An LCD shutter 302 is used to cause the left and right images to have different polarization directions.

<16> Specifically, in the method of FIG. 3, left and right images are alternately stored in the content. When a projector 301 emits images according to the content, the LCD shutter 302 is driven to have the same polarization direction as that of left images at the times when the projector 301 emits the left images and is driven to have a polarization direction different from that of the left images at the times when the projector 301 emits the right images. This operation can be performed by a shutter driver 303 which drives the LCD shutter 302.

<17> However, this stereoscopic image projection system using the LCD shutter has a problem that the response delay of the LCD shutter when it is

driven causes crosstalk between left and right images. Especially, the time during which alternating left and right images are switched must be short enough to not be noticed by a human. The slow response time of the LCD shutter will be a serious problem when left and right images are quickly switched.

<18> In addition, there is a need to provide a technology for replacing the LCD shutter with different means for increasing the polarization ratio, since the polarization ratio of left and right images of the LCD shutter is not so high.

<19>

【Disclosure】

【Technical Problem】

<20> An object of the present invention devised to solve the problem lies on providing a stereoscopic image projector system, an apparatus for stereoscopic image projection, and a stereoscopic image projection system including the stereoscopic image projector system and the apparatus, wherein single projector type stereoscopic image projection is implemented using a circular polarized filter module so that the number of projectors required for stereoscopic image projection is reduced and left and right images are also divided in time so as not to cause crosstalk between the images.

<21> Another object of the present invention devised to solve the problem lies on providing a system which uses a circular polarized filter module that rotates to selectively polarize left and right images, wherein the synchronization of rotation of the circular polarized filter module is controlled taking into consideration the sizes of left and right images, thereby achieving stereoscopic image projection with a higher quality.

<22>

【Technical Solution】

<23> An embodiment of the present invention to achieve the above objects provides a stereoscopic image projector system for a stereoscopic image projection system using a polarization method, the stereoscopic image

projector system including a projector for sequentially emitting left and right images; a circular polarized filter module including a left image polarized filter and a right image polarized filter; and a filter driver for rotating and driving the circular polarized filter module according to timing synchronization of left and right image emissions of the projector.

<24> In this embodiment, the stereoscopic image projector system may further include a synchronizer for acquiring timing synchronization of left and right image emissions of the projector and providing the timing synchronization to the filter driver and a frame for fixing and adjusting positions of the projector and the circular polarized filter module.

<25> The frame may control the positions of the projector and the circular polarized filter module to control two-dimensional (2D) or three-dimensional (3D) image projection. Preferably, the circular polarized filter module further includes a light shielding region at a boundary between the left image polarized filter and the right image polarized filter.

<26> The projector may receive stereoscopic image content, including the left and right images sequentially stored in the stereoscopic image content, and continuously emits the content. By rotating the circular polarized filter module, the circular polarized filter module may be controlled such that the left image polarized filter is located at an emission hole of the projector when the projector emits left images and the right image polarized filter is located at the emission hole of the projector when the projector emits right images.

<27> The circular polarized filter module may further include a sensor for detecting whether or not the left image polarized filter is located at the emission hole of the projector when the projector emits left images and whether or not the right image polarized filter is located at the emission hole of the projector when the projector emits right images. In this case, a position of the sensor is preferably determined taking into consideration the size of a left and right image emitted by the projector. In a preferred embodiment of the invention, the circular polarized filter module may further

include measurement means for measuring the size of a left and right image emitted by the projector; and position determination means for determining the position of the sensor according to the measurement of the measurement means.

<28> Another embodiment of the invention provides a polarization-based stereoscopic image projection system using a projector for sequentially emitting left and right images, the stereoscopic image projection system including a circular polarized filter module including a left image polarized filter and a right image polarized filter; and a filter driver for rotating and driving the circular polarized filter module according to timing synchronization of left and right image emissions of the projector.

<29> Also in this embodiment, the stereoscopic image projection system may further include a synchronizer for acquiring timing synchronization of left and right image emissions of the projector and providing the timing synchronization to the filter driver and a frame for fixing and adjusting positions of the projector and the circular polarized filter module.

<30> The frame may control the positions of the projector and the circular polarized filter module to control two-dimensional (2D) or three-dimensional (3D) image projection. Preferably, the circular polarized filter module further includes a light shielding region at a boundary between the left image polarized filter and the right image polarized filter.

<31> In addition, by rotating the circular polarized filter module, the circular polarized filter module may be controlled such that the left image polarized filter is located at an emission hole of the projector when the projector emits left images and the right image polarized filter is located at the emission hole of the projector when the projector emits right images.

<32> Another embodiment of the invention provides a stereoscopic image projection system including a stereoscopic image projector system for emitting left and right images according to a polarization method; a screen on which the left and right images are projected; and polarized glasses through which the left and right images selectively pass, the stereoscopic

image projector system including a projector for sequentially emitting left and right images; a circular polarized filter module including a left image polarized filter and a right image polarized filter; and a filter driver for rotating and driving the circular polarized filter module according to timing synchronization of left and right image emissions of the projector.

【Advantageous Effects】

<33> According to the embodiments of the invention, the system uses only one projector to increase its utilization in viewing rooms of a movie theater or the like and to reduce installation costs and can project stereoscopic images with a high conformity of left and right images and a wide viewing angle while reducing crosstalk compared to the LCD-shutter-based system.

<34> In addition, the position of the circular polarized filter module is changed using the frame not only to allow 3D image projection but also to allow general 2D image projection and the light shielding region is inserted between the left and right image filters of the circular polarized filter module, thereby further reducing crosstalk.

<35> Further, the sensor is used to efficiently detect the rotation position of the circular polarized filter module at the times when left and right images are switched. Especially, the position of the sensor is set taking into consideration the sizes of images, thereby further improving the stereoscopic image quality.

<36> Furthermore, it is easy to use the stereoscopic image projector system according to the embodiments of the invention since it is easily installed at the front of the existing projector.

<37>

【Description of Drawings】

<38> The accompanying drawings, which are included to provide a further understanding of the invention, illustrate embodiments of the invention and together with the description serve to explain the principle of the invention.

<39> In the drawings:

<40> FIG. 1 illustrates the structure of a conventional dual projector system for stereoscopic image projection;

<41> FIG. 2 illustrates the structure of a conventional system for stereoscopic image projection based on a method of dividing the area of an LCD module;

<42> FIG. 3 illustrates the structure of a conventional LCD-shutter-based system for stereoscopic image projection;

<43> FIG. 4 illustrates the structure of a stereoscopic image projector system used in a single projector circular filter type system according to an embodiment of the invention;

<44> FIG. 5 illustrates a preferable structure of a circular polarized filter module used in a single projector circular polarized filter type system according to an embodiment of the invention;

<45> FIG. 6 illustrates the operation and position of a sensor used for a circular polarized filter module according to a preferred embodiment of the invention;

<46> FIG. 7 is a drawing for explaining in detail a method for determining the position of a sensor used in a circular polarized filter module taking into consideration the sizes of images according to a preferred embodiment of the invention;

<47> FIG. 8 illustrates a structure for efficiently determining the size of an image and the position of the sensor based on the image size according to a preferred embodiment of the invention;

<48> FIG. 9 illustrates comparisons of the extents of crosstalk occurring between left and right images according to the conventional LCD shutter method and according to the single projector circular polarized filter methods of the embodiments of the invention; and

<49> FIG. 10 illustrates an overall structure of a single-projector circular polarized filter type stereoscopic image projection system according to an embodiment of the invention.

【Mode for Invention】

<50> Reference will now be made in detail to the preferred embodiments of the present invention with reference to the accompanying drawings. The detailed description, which will be given below with reference to the accompanying drawings, is intended to explain exemplary embodiments of the present invention, rather than to show the only embodiments that can be implemented according to the invention.

<51> The following detailed description includes specific details in order to provide a thorough understanding of the present invention. However, it will be apparent to those skilled in the art that the present invention may be practiced without such specific details. In some instances, known structures and devices are omitted or are shown in block diagram form, focusing on important features of the structures and devices, so as not to obscure the concept of the present invention. The same reference numbers will be used throughout this specification to refer to the same or like parts.

<52> The present invention suggests that a method of sequentially emitting left and right images be used to allow single projector stereoscopic image projection and a circular polarized filter module be used to polarize left and right images differently. Using the circular polarized filter module to polarize left and right images can reduce the crosstalk problem in the LCD shutter method. Using the circular polarized filter also has an advantage in that it can increase the viewing angle of stereoscopic images, compared to when linearly polarized filters are used.

<53> FIG. 4 illustrates the structure of a stereoscopic image projector system used in a single projector circular filter type system according to an embodiment of the invention.

<54> As shown in FIG. 4, the stereoscopic image projector system according to the embodiment of the invention includes a single projector 401, a circular polarized filter module 402, and a filter driver 403. The projector 401 sequentially emits left and right images. The circular polarized filter module 402 includes a left image polarized filter and a right image polarized

filter. The filter driver 403 rotates and drives the circular polarized filter module 402 according to timing synchronization of the left image emission and right image emission of the projector 401. The stereoscopic image projector system may further include a synchronizer 404 for acquiring timing synchronization of the left image emission and right image emission of the projector 401 and transferring the timing synchronization to the filter driver 403 as shown in FIG. 4. Reference will now be made to detailed operations of the stereoscopic image projector system.

<55> First, the projector 401 receives stereoscopic image content, including left images and right images sequentially (or alternately) stored in the stereoscopic image content, and continuously emit the content. This indicates that a conventional projector for projecting 2D images can be directly used as the projector 401. That is, the projector 401 sequentially emits left images and right images according to information of the received stereoscopic image content.

<56> By rotating the circular polarized filter module 402 which includes a left image polarized filter and a right image polarized filter as described above, the circular polarized filter module 402 is controlled such that the left image polarizing filter is located at an emission hole of the projector 401 at the time when the projector 401 emits left images and the right image polarized filter is located at the emission hole of the projector 401 at the time when the projector 401 emits right images. To accomplish this, the synchronizer 404 must be able to acquire the timing of switching between left and right images in the stereoscopic image content input to the projector 401. The synchronizer 404 controls the filter driver 403 to adjust the timing of driving the circular polarized filter module 402 according to the acquired timing information. The timing synchronization can be set to detect a synchronization signal containing the timing synchronization information from a High Definition-Serial Digital Interface (HD-SDI) port for transmission of stereoscopic image content, a GPIO port, or any other corresponding port.

<57> The stereoscopic image projector system may further include a frame (not shown) for fixing and adjusting the positions of the projector 401 and the circular polarized filter module 402. The frame can control the position of the projector 401 and/or the circular polarized filter module 402 to control 2D or 3D image projection. For example, in the case of 2D image projection, the frame lowers the position of the circular polarized filter module 402 to control images emitted by the projector 401 not to pass through the circular polarized filter module 402.

<58> Since a conventional projector can be directly used as the projector 401 in the stereoscopic image projector system described above, the circular polarized filter module 402 and the filter driver 403, preferably together with the synchronizer 404 and/or the frame (not shown), can constitute an apparatus for stereoscopic image projector systems according to another embodiment of the invention. This apparatus for stereoscopic image projection systems can be easily mounted on the front side of an existing projector. Thus, the apparatus for stereoscopic image projection systems can be compatible with a variety of projectors.

<59> The following is a description of a preferable structure of the circular polarized filter module 402.

<60> FIG. 5 illustrates a preferable structure of the circular polarized filter module used in the single projector circular polarized filter type system according to an embodiment of the invention.

<61> As shown in FIG. 5, the circular polarized filter module 402 according to the embodiment of the invention includes a left image polarized filter for left image polarization (denoted by "L" in FIG. 5) and a right image polarized filter for right image polarization (denoted by "R" in FIG. 5) and preferably further includes a light shielding region 402a.

<62> Generally, the circular polarized filter includes a linear polarization filter and a quarter phase difference plate to convert incident light into right-handed or left-handed circularly polarized light. Stereoscopic display using circular polarized filters has an advantage over that using linearly

polarized filters in that the viewer can view projected images in 3D even when they significantly tilt their head to the left or right as described above. However, stereoscopic display using circular polarized filters also has a problem in that crosstalk easily occurs between colors of left and right images of stereoscopic pictures.

<63> Thus, the light shielding region 402a is inserted as shown in FIG. 5 to reduce crosstalk between left and right images emitted by the projector at the time when the left and right images are switched. To accomplish this, it is preferable that the light shielding region 402a be located at the emission hole of the projector at the time when left and right images of the projector are switched.

<64> Although FIG. 5 shows that one circular polarized filter module 402 includes one left image filter L and a right image filter R, the circular polarized filter module 420 may include a plurality of left image filters and a plurality of right image filters. For example, when the circular polarized filter module includes two left image filters and two right image filters, the speed at which the filter driver drives the circular polarized filter module can be reduced to half of that of the case of FIG. 5.

<65> It is preferable that each filter be in the form of a fan with a decreasing central angle at the center of the circular polarized filter module as the number of left image filters and the number of right image filters increase as in the above embodiment. If the central angles of the left image filter L and the right image filter R are large, the stereoscopic image quality may be reduced due to mismatching between the polarization angles of the circular polarized filter module and the polarized glasses as the circular polarized filter module rotates. Accordingly, a preferred embodiment of the invention suggests that the circular polarized filter module include an appropriate number of left image polarized filters L and right image polarized filters R with the same fan shape to reduce the central angle, thereby minimizing the reduction of the stereoscopic image quality due to mismatching between the polarization angles.

<66> One method of increasing the numbers of left image polarized filters L and right image polarized filters R is to repeatedly arrange left image polarized filters L and right image polarized filters R alternately, for example in the order of L, R, L, R, and another method is to repeat the same-side image filters and then to repeat the opposite-side image filters, for example in the order of L, L, L, , R, R, R, , R. Repeating left image filters L and right image filters R in this manner can also prevent the reduction of the stereoscopic image quality due to the mismatching between the polarization angles of the circular polarized filter module and the polarized glasses. Although any number of left or right image filters can be repeated, it is preferable that the left image filter region L be divided into 6 equal sections and the right image filter region R be divided into 6 equal sections taking into consideration flickering due to the interval between each filter section in the circular polarized filter module. The present invention is not necessarily limited to this example and can set any appropriate number of filter sections which reasonably balances the polarization direction mismatching problem with the flickering problem.

<67> In an embodiment of the invention, the circular polarized filter module may further include a sensor for detecting whether or not a left image polarized filter is located at the emission hole of the projector at the time when the projector emits left images and whether or not a right image polarized filter is located at the emission hole of the projector at the time when the projector emits right images. The concept of this sensor for the circular polarized filter module will now be described in more detail with reference to the drawings.

<68> FIG. 6 illustrates the operation and position of a sensor used for a circular polarized filter module according to a preferred embodiment of the invention.

<69> In FIG. 6, it is assumed that the projector emits an image 601a at the timing of switching from left to right images (L->R). The circular polarized filter module 402 can be set to rotate such that its region located at the

emission hole of the projector is switched from the left image polarized filter region L to the right image polarized filter region R at the time when the image is switched from left to right images. In the case of this setting of the circular polarized filter module 402, the sensor can be set to detect whether or not the boundary between the left and right polarization regions of the circular polarized filter module 402 is located at a position a-a shown in FIG. 6 at the time.

<70> However, as can be seen from FIG. 6, if the boundary between the left and right polarization regions of the circular polarized filter module 402' is located at a position a-a shown in FIG. 6 at the time when the image 601a emitted by the projector is switched from left to right images, the circular polarized filter module 402 cannot properly polarize a right image during a duration in which the projector emits the right image. That is, additional crosstalk may occur if the position of the boundary between the left and right polarization regions of the circular polarized filter module 402 at the timing of switching between left and right images is set without taking into consideration the size of the image 601a.

<71> Thus, a preferred embodiment of the invention suggests that the circular polarized filter boundary position at the timing of switching between left and right images be set taking into consideration the size of the images. Specifically, in the above example, the boundary between the left and right polarization regions of the circular polarized filter module 402 can be set to be located at a position b-b rather than the position a-a shown in FIG. 6 at the time when the image 601a emitted by the projector is switched from left to right images. This embodiment also suggests that the sensor 402b for detecting the rotation position of the circular polarized filter module 402 be set to be located at the position b or b'. This setting of the position of the sensor 402b can prevent crosstalk caused during a period of time corresponding to the size of the image 601a.

<72> While it is assumed in the example of FIG. 6 that images have a uniform size, images may have various sizes according to the type of the projector or

the like, which is described below.

<73> FIG. 7 is a drawing for explaining in detail a method for determining the position of a sensor used in a circular polarized filter module taking into consideration the sizes of images according to a preferred embodiment of the invention.

<74> Specifically, FIG. 7 illustrates that the projector can emit various images such as an image 601a, an image 601b, and an image 601c. The setting of the position of the boundary between a left image polarized filter region L and a right image polarized filter region R of a circular polarized filter module 402 at the time when images are switched from left to right images can be changed according to the size of the images. It is preferable that the position of a sensor 402b be also adjusted according to the changed boundary position. For example, it is preferable in FIG. 7 that the sensor be located at a position b or b when the image 601a is emitted, the sensor be located at a position c or c when the image 601b is emitted, and the sensor be located at a position d or d when the image 601c is emitted. A preferred embodiment of the invention suggests that the position of the sensor be adjusted according to the various image sizes in this manner.

<75> FIG. 8 illustrates a structure for efficiently determining the size of an image and the position of the sensor based on the image size according to a preferred embodiment of the invention.

<76> As described above with reference to FIG. 7, it is preferable that, when the size of the images is changed, the position of the sensor be adjusted according to the changed image size. However, when the position of a sensor is roughly adjusted on a projector used in movie theaters, the adjusted position may be incorrect, thereby reducing the stereoscopic image quality.

<77> Accordingly, a more preferred embodiment of the invention suggests that a circular polarized filter module 402 further include measurement means 801 for measuring the size of an image and position determination means 802 for determining the position of a sensor 402b according to the measurement of the

measurement means 801 as shown in FIG. 8. Specifically, in the example of FIG. 8, if image sizes 0, 1, 2, 3, 4, 5, are measured through the measurement means, the sensor 402b can be located at positions 0, 1, 2, 3, 4, 5, corresponding to the measured image sizes, respectively.

<78> Although FIG. 8 shows a method in which the image size and the corresponding sensor position are quantitatively set using a type of scale to illustrate the preferred embodiment of the invention, any means for determining the image size and the corresponding sensor position can be used as the measurement means and the position determination means in the invention.

<79> The above methods according to the embodiments of the invention will now be described in comparison with the conventional LCD shutter method.

<80> FIG. 9 illustrates comparisons of the extents of crosstalk occurring between left and right images according to the conventional LCD shutter method and according to the single projector circular polarized filter methods of the embodiments of the invention.

<81> Left and Right in the top of FIG. 9 denote time intervals during which the projector emits left and right images, respectively. It can be seen from FIG. 9 that, when left and right images are emitted alternately in this manner, relatively great crosstalk occurs at the timings of switching between left and right images if each image is polarized using the LCD shutter as shown in FIG. 3. Generally, the LCD shutter responds more slowly at falling times than at rising times. In the example of FIG. 9, left images are projected during rising cycles of the LCD and right images are projected during falling cycles so that greater crosstalk occurs at the timings of switching from left to right images than at the timings of switching from right to left images. Different images from those shown in FIG. 9 may also be projected during the cycles. On the other hand, as shown in FIG. 9, almost no crosstalk occurs at the timings of switching between left and right images if the circular polarized filter module according to the embodiment of the invention is used. Setting the light shielding region as shown in FIG. 5

can further reduce the possibility of occurrence of crosstalk.

<82> As shown in FIG. 9, in the case of the method using the LCD shutter, crosstalk occurring in cycles during which left images are emitted and cycles during which right images are emitted, other than the switching cycles, is also greater than in the case of the method using the circular polarized filter module according to the embodiment of the invention since the LCD shutter method has a lower polarization ratio of images for one of the left or right sides than the circular polarization method according to the invention.

<83> Accordingly, using the single projector according to the invention, it is possible to maximize the utilization of the projector in viewing rooms of a movie theater or the like and to reduce the installation costs for stereoscopic image projection and also to reduce crosstalk between left and right images, compared to the conventional LCD shutter method, thereby realizing more excellent stereoscopic images.

<84> The following table shows comparisons of the stereoscopic image projection system using the single-projector circular polarized filter module according to the above embodiments of the invention with other systems.

<85> **【Table 1】**

Classification		Advantages	Problems
DUAL PROJECTOR	linearly polarized filter	Easy construction in short time. Implementation of excellent stereoscopic quality.	Low utilization in theater. Increase in projector installation costs. Left and right image conformity problem. Limited viewing angle.
	circular polarized filter	Easy construction in short time. Implementation of excellent stereoscopic quality. Improvement in viewing angle.	Low utilization in theater. Increase in projector installation costs. Left and right image conformity problem.
SINGLE PROJECTOR	LCD shutter	Improvement in utilization in theater. Improvement in left and right image conformity. Improvement in viewing angle.	Occurrence of crosstalk. Lowest stereoscopic quality.
	circular polarized filter	Improvement in utilization in theater. Improvement in left and right image conformity. Improvement in viewing angle. Reduction in occurrence of crosstalk	Possibility of occurrence of crosstalk compared to dual projector method.

<86>

<87> As shown in Table. 1, the circular polarized filter method according to the invention overcomes the problem of utilization in viewing rooms of a movie theater and the problem of conformity of left and right images in the single projector method and overcomes the limited viewing angle problem in the method using linearly polarized filters and also significantly reduces the problem of crosstalk that seriously occurs in the LCD shutter method.

<88> Although the circular polarized filter method according to the invention has a problem of the possibility of occurrence of crosstalk in contrast to the dual projector method since circular polarized filters are used, its crosstalk problem is much less serious than that in the LCD shutter method and the crosstalk problem can be overcome to some extent by setting the light shielding region between the left and right image filters as shown in FIG. 5.

<89> FIG. 10 illustrates an overall structure of a single-projector circular polarized filter type stereoscopic image projection system according to an embodiment of the invention.

<90> As shown in FIG. 10, the single projector circular polarized filter type stereoscopic image projection system according to the embodiment of the invention includes a stereoscopic image projector system 705, a screen 706, and polarizing glasses 707 as described above. The stereoscopic image projector system 705 emits left and right images according to the polarization method. The left and right images are projected on the screen 706. The left and right images selectively pass through the polarized glasses 707.

<91> The stereoscopic image projector system 705 is characterized by including a single projector 701, a circular polarized filter module 702, and a filter driver 703 as described above. The single projector 701 sequentially emits left and right images. The circular polarized filter module 702 includes a left image polarized filter and a right image polarized filter. The filter driver 703 rotates and drives the circular polarized

filter module 702 according to the timing synchronization of left and right image emissions of the projector. Accordingly, with only one projector, it is possible to project stereoscopic images with high conformity of left and right images and a wide viewing angle, while significantly reducing crosstalk compared to the LCD shutter method.

<92> The detailed description of the preferred embodiments of the present invention has been given to enable those skilled in the art to implement and practice the invention. Although the invention has been described with reference to the preferred embodiments, those skilled in the art will appreciate that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention described in the appended claims. Accordingly, the invention should not be limited to the specific embodiments described herein, but should be accorded the broadest scope consistent with the principles and novel features disclosed herein.

<93>

【Industrial Applicability】

<94> The stereoscopic image projection system using the circular polarized filter module according to the invention increases its utilization in viewing rooms of a movie theater or the like and decreases installation costs since it uses only one projector and can also project stereoscopic images with high conformity of left and right images and a wide viewing angle while reducing crosstalk compared to the LCD shutter method. Thus, the stereoscopic image projection system according to the invention is suitable for use as a system for stereoscopic image projection in movie theaters.

<95> The stereoscopic image projection system according to the invention can not only be used in its entirety but a stereoscopic image projector system including a projector, a circular polarized filter module, and a filter driver, included in the stereoscopic image projection system, can also be used standalone. In addition, since a conventional projector can be directly used for the stereoscopic image projection system, the circular polarized

filter module and the filter driver can be used as standalone apparatuses for the stereoscopic image projection system.

<96>

【CLAIMS】**【Claim 1】**

A stereoscopic image projector system for a stereoscopic image projection system using a polarization method, the stereoscopic image projector system comprising:

a projector for sequentially emitting left and right images;

a circular polarized filter module including a left image polarized filter and a right image polarized filter; and

a filter driver for rotating and driving the circular polarized filter module according to timing synchronization of left and right image emissions of the projector.

【Claim 2】

The stereoscopic image projector system according to claim 1, further comprising a synchronizer for acquiring the timing synchronization of left and right image emissions of the projector and providing the timing synchronization to the filter driver.

【Claim 3】

The stereoscopic image projector system according to claim 1, further comprising a frame for fixing and adjusting positions of the projector and the circular polarized filter module.

【Claim 4】

The stereoscopic image projector system according to claim 3, wherein the frame controls the positions of the projector and the circular polarized filter module to control two-dimensional (2D) or three-dimensional (3D) image projection.

【Claim 5】

The stereoscopic image projector system according to claim 1, wherein the circular polarized filter module further includes a light shielding region at a boundary between the left image polarized filter and the right image polarized filter.

【Claim 6】

The stereoscopic image projector system according to claim 1, wherein the projector receives stereoscopic image content, including the left and right images sequentially stored in the stereoscopic image content, and sequentially emits the content.

【Claim 7】

The stereoscopic image projector system according to claim 1, wherein, by rotating the circular polarized filter module, the circular polarized filter module is controlled such that the left image polarized filter is located at an emission hole of the projector when the projector emits left images and the right image polarized filter is located at the emission hole of the projector when the projector emits right images.

【Claim 8】

The stereoscopic image projector system according to claim 7, wherein the circular polarized filter module further includes a sensor for detecting whether or not the left image polarized filter is located at the emission hole of the projector when the projector emits left images and whether or not the right image polarized filter is located at the emission hole of the projector when the projector emits right images.

【Claim 9】

The stereoscopic image projector system according to claim 8, wherein a position of the sensor is determined taking into consideration the size of a left and right image emitted by the projector.

【Claim 10】

The stereoscopic image projector system according to claim 9, wherein the circular polarized filter module further includes:

measurement means for measuring the size of a left and right image emitted by the projector; and

position determination means for determining the position of the sensor according to the measurement of the measurement means.

【Claim 11】

The stereoscopic image projector system according to claim 1, wherein

the circular polarized filter module include a plurality of the left image polarized filters and a plurality of the right image polarized filters.

【Claim 12】

The stereoscopic image projector system according to claim 11, wherein each of the left image polarized filters and the right image polarized filters has a form with a decreasing central angle as a number of the left image filters and a number of the right image filters increase.

【Claim 13】

A single projector type stereoscopic image projection system for sequentially emitting left and right images, the stereoscopic image projection system comprising:

a circular polarized filter module including a left image polarized filter and a right image polarized filter; and

a filter driver for rotating and driving the circular polarized filter module according to timing synchronization of left and right image emissions of the projector.

【Claim 14】

The single projector type stereoscopic image projection system according to claim 13, further comprising a synchronizer for acquiring timing synchronization of left and right image emissions of the projector and providing the timing synchronization to the filter driver.

【Claim 15】

The single projector type stereoscopic image projection system according to claim 13, further comprising a frame for fixing and adjusting positions of the projector and the circular polarized filter module.

【Claim 16】

The single projector type stereoscopic image projection system according to claim 15, wherein the frame controls the positions of the projector and the circular polarized filter module to control two-dimensional (2D) or three-dimensional (3D) image projection.

【Claim 17】

The single projector type stereoscopic image projection system according to claim 13, wherein the circular polarized filter module further includes a light shielding region at a boundary between the left image polarized filter and the right image polarized filter.

【Claim 18】

The single projector type stereoscopic image projection system according to claim 13, wherein, by rotating the circular polarized filter module, the circular polarized filter module is controlled such that the left image polarized filter is located at an emission hole of the projector when the projector emits left images and the right image polarized filter is located at the emission hole of the projector when the projector emits right images.

【Claim 19】

A stereoscopic image projection system comprising:

a stereoscopic image projector system for emitting left and right images according to a polarization method;

a screen on which the left and right images are projected; and

polarized glasses through which the left and right images selectively pass,

wherein the stereoscopic image projector system comprises:

a projector for sequentially emitting left and right images;

a circular polarized filter module including a left image polarized filter and a right image polarized filter; and

a filter driver for rotating and driving the circular polarized filter module according to timing synchronization of left and right image emissions of the projector.