REPLACED SHEETS SG
☑ Description : paged ...1.... to paged ...10.....
☑ Claim(s) : paged ...11.... to paged ...13.....
☑ Drawing(s) : paged ...14... to paged ...15....
☑ Abstract : paged ...16... to paged ...-.....
DATE OF RECEIPT .....

OPTICAL PICK-UP HEAD APPARATUS

This invention relates to optical pick-up head apparatus, for use, for example, in a recording and/or reproducing apparatus which records and/or reproduces a so-called optical disc such as a magneto-optical disc.

An optical disc recording and/or reproducing apparatus for recording and/or reproducing an optical disc such as a magneto-optical disc may include a linear motor system to translate an objective lens. For example, US patent specifications US-A-4 545 046 and US-A-4 607 913 describe such optical pick-up head apparatus. In such an apparatus, if two parallel guide rods of the apparatus are not supported very accurately, then this will impair smooth movement of a movable member to which the objective lens is attached. Moreover, in this type of optical pick-up head apparatus, the bearings attached to the movable member are expensive. Also, if the bearings are not identical in their properties, movement of the movable member will be impaired.

Our US patent specification US-A-4 864 170 describes a linear motor which can be applied to such an optical pick-up head apparatus, and this will now be described with reference to Figures 1 and 2. Figure 1 is a perspective view of the linear motor, and Figure 2 is a transverse sectional view taken on the line I – I in Figure 1.

Referring to Figures 1 and 2, two permanent stator magnets 1 and 4 are each magnetized in the thickness direction thereof. A base plate 2 is made of a magnetizable material, for example, iron, and has secured on it two outer stator yokes 3 and 5. The stator magnet 1 is attached to the inner side of the stator yoke 3, and the stator magnet 4 is similarly attached to the inner side of the stator yoke 5, leaving a predetermined clearance. Enclosing the stator magnets 1 and 4, inner stator yokes 6 and 7 are secured to the base plate 2, such that they form closed magnetic paths together with the outer stator yokes 3 and 5.

A frame or bobbin 8 has at least the outer peripheral portion thereof made of a non-magnetic material. A pair of coils 9a and 9b are wound around two end portions of the bobbin 8, and through-holes 10 and 11 are formed through the bobbin 8 so that they intersect each other in the front and rear direction as well as the upper and lower direction.

This Sheet Has Been Replaced

The bobbin 8 also has formed therethrough a pair of apertures 12 and 13 which penetrate the pair of coils 9a and 9b. The inner stator yokes 6 and 7 are inserted into the pair of apertures 12 and 13.

Guide grooves 14, 15 and 16, 17 are formed on the inside surfaces of the apertures 12 and 13 and on the inner surfaces of the inner stator yokes 6 and 7. As shown in Figure 2, pairs of shafts 18 and 19 are attached to the guide grooves 14 and 15, and balls 21a and 21b are supported by supporting members 20a and 20b within these guide grooves 14, 15 and 16, 17. Therefore, the bobbin 8 is supported on the inner stator yokes 6 and 7 via the balls 21a and 21b, whereby the bobbin 8 can move freely in the longitudinal direction of the inner stator yokes 6 and 7.

A reflecting mirror 22 for changing a light path is secured where the holes 10 and 11 intersect. An optical pick-up 25 having an objective lens 24 is attached to the exit side of the vertically-elongated hole 11 by a mount 23. The optical pick-up 25 faces an optical disc D, and includes a focusing motor 26 to move the objective lens 24 in the optical axis direction of the objective lens 24.

As shown in Figure 1, a read-out optical system 27 is located in the direction in which the hole 10 formed through the bobbin 8 in the front and rear direction extends rearward. The read-out optical system 27 comprises a laser diode 28, a beam splitter 29, a collimator lens 30, a light receiving system 31, and a photo-diode 32. With the read-out optical system 27, a light beam emitted from the laser diode 28 travels over a light path formed of the collimator lens 30, the mirror 22, the objective lens 24 of the optical pick-up 25, the optical disc D, the objective lens 24, the mirror 22, the collimator lens 30, the beam splitter 29 and the light receiving system 31, in that order, and is incident on the photo-diode 32.

In this optical pick-up head apparatus, when both the coils 9a and 9b are energized, the bobbin 8 is acted on by a driving force according to Fleming's left-hand rule, due to the reaction between the current and the magnetic field produced by the magnets 1 and 4 and the yokes 3, 6 and 5, 7, that is, a linear motor is formed, whereby the optical pick-up 25 is moved in the radial direction of the optical disc D. During this operation of the optical pick-up 25 the objective lens 24 of the optical pick-up 25 is driven by the focusing motor 26, so

This Sheet Has Been Replaced

that the focus of the objective lens 24 is adjusted.

In this optical pick-up head apparatus, the linear motor for moving the optical pick-up 25 is compact, because the bobbin 8 supporting the optical pick-up 25 utilizes the inner stator yokes 6 and 7 as guides. However, the optical pick-up 25 is provided with the focusing motor 26 which moves the objective lens 24, and the focusing motor 26 and the feed linear motor form different magnetic circuits, which are liable to interfere with each other. Thus, there may be a magnetically neutral zone which interferes with the movement of the optical pick-up 25, that is, the bobbin 8.

Moreover, the bobbin 8 is loaded with the weight of the magnetic circuit of the focusing motor 26, so that the moving mass is increased, which results in a lower accessing speed. Also, the number of magnets forming the magnetic circuits is increased, which increases the cost.

According to the present invention there is provided an optical pick-up head apparatus having a tracking error signal generating device for generating a tracking error signal on the basis of a detected output from a photo-detecting device, and a tracking control device for performing a tracking servo by rotating a mirror portion in response to the tracking error signal supplied thereto, the apparatus comprising:

a yoke facing a magnet;

a movable member having an aperture into which said yoke is inserted and around which a first coil is wound facing said magnet; and

objective lens supporting means for supporting an objective lens to be movable in the direction parallel to an optical axis of said objective lens and having a plurality of second coils to move said objective lens in the direction parallel to the optical axis of said objective lens;

wherein said objective lens supporting means is secured to said member, said movable member is supported by said yoke so that it can move freely, and at least one side of said first and second coils is located within a common magnetic gap.

According to the present invention there is also provided an optical pick-up head apparatus comprising:

a stationary optical system formed of a laser light source, photo-detecting means, and tracking control means for performing a tracking control so that a beam spot formed on an optical disc by a light beam emitted from said laser light source follows tracks on said optical

This Sheet Has Been Replaced



disc; and

a movable optical system formed of an objective lens freely movable in the radial direction of said optical disc and controlled to focus the light beam emitted from said laser light source on said optical disc, and light path changing means for changing the path of the light beam emitted from said laser light source so that said light beam becomes incident on said objective lens;

wherein said stationary optical system and said movable optical system are located in the same plane.

An embodiment of optical pick-up head apparatus according to the invention having a tracking error signal generating device for generating a tracking error signal on the basis of a detected output from a photo-detecting device and a tracking control device for performing a tracking servo by rotating a mirror portion in response to the tracking error signal supplied thereto, may comprise yokes provided in an opposing relation to a magnet, a movable member having apertures into which the yokes are inserted and around which a first coil is wound in an opposing relation to the magnets, and an objective lens supporting device having a plurality of second coils to support an objective lens such that the objective lens can be moved in the direction parallel to an optical axis of the objective lens, and which moves the objective lens in the direction parallel to the optical axis of the objective lens, wherein the objective lens supporting device is secured to the movable member, the movable member is supported by the yokes so that is can move freely, and at least one side of the first and second coils is provided within a common magnetic gap.

An embodiment of optical pick-up head apparatus according to the invention may comprise a stationary optical system formed of a laser light source, a photo-detecting device, and a tracking control device for performing a tracking control, so that a beam spot formed on an optical disc by a light beam emitted from the laser light source follows tracks on the optical disc, and a movable optical system formed of an objective lens controlled to focus the light beam emitted from the laser light source on the optical disc, and a light path changing device for changing a light path of the light beam emitted from the laser light source so that the light beam becomes incident on the objective lens, wherein the stationary optical system and the movable

This Sheet Has Been Replaced



optical system are provided on the same plane.

The invention will now be described by way of example with reference to the accompanying drawings, throughout which like parts are referred to by like references, and in which:

Figure 1 is a perspective view of an example of a previously-proposed optical pick-up apparatus;

Figure 2 is a transverse sectional view taken on the line I - I in Figure 1;

Figure 3 is a perspective view of an embodiment of optical pick-up apparatus according to the present invention;

Figure 4 is an enlarged transverse sectional view taken on the line II - II in Figure 3;

Figure 5 is an enlarged longitudinal sectional view of the embodiment; and

Figure 6 is an exploded perspective view of part of the embodiment.

Referring to Figures 3 to 6, there is shown a base plate 41 of a rectangular shape which is made of a rigid material. Outer yokes 42 and 43 of substantially U-shape are secured to the two side portions of the base plate 41 in the longitudinal direction of the surface of the base plate 41 in facing relation. Magnets 44 and 45, each magnetized in the thickness direction, are attached to the inside surfaces of the outer yokes 42 and 43, respectively.

Inner yokes 46 and 47 are respectively coupled to the outer yokes 42 and 43 at two inner end faces 42a, 42b and 43a, 43b, whereby the magnets 44 and 45 are respectively encircled by the yokes 42, 43, 46 and 47 to form closed magnetic paths. More specifically, the inner yokes 46 and 47 are held on stepped surfaces 42a1, 42b1, 43a1 and 43b1 of predetermined height formed on the inner ends of the outer yokes 42 and 43. Thus, magnetic gaps g of a predetermined width are respectively formed between the magnets 44 and 45 and the inner yokes 46 and 47, and the inner yokes 46 and 47 are supported on the surface of the base plate 42 at a predetermined spacing.

A movable member 48 has formed therethrough apertures 49 and 50 intersecting each other in the front and rear direction and in the upper and lower direction. A bobbin 51 made of a non-magnetic material is engaged with the rear half portion of the movable member 48 such

This Sheet Has Been Replaced



that a pair of through-holes 51a and 51b are respectively formed between two side surfaces 48a and 48b of the movable member 48 and the bobbin 51. A slide drive coil 52 is wound around the outer peripheral surface of the bobbin 51 as a first coil.

An objective lens supporting member 53 which is shaped as a rectangular frame is supported on the first half portion of the movable member 48 by parallel plate springs 54 and 55 so as to be freely movable in the upper and lower direction. An objective lens 56 is attached to the objective lens supporting member 53 in facing relation to the exit side of the hole 50 extending in the upper and lower direction of the movable member 48.

Flat coils 57a, 57b, 57c and 57d are moulded in L-shape and are secured to four corners of the objective lens supporting member 53, respectively, whereby horizontal portions of the respective flat coils in the two side surfaces of the supporting member 53 form a focusing coil 57 which might be referred to as a second coil. The flat coils 57a, 57b, 57c and 57d are respectively energized by bonding flexible printed circuit boards 58a and 58b to the plate springs 54 and 55. When the circuit boards 58a and 58b are bonded to the plate springs 54 and 55, resonance of the plate springs 54 and 55 can be suppressed, no improving the silencing. Preferably, the plate springs 54 and 55 are each made of a non-magnetic material such as helium bronze or phosphor bronze. The focusing coil 57 may be formed by bending wound wires of square shape in an L-shape as described above. Alternatively, the focusing coil 57 may be formed by using a flexible printed circuit board. When the focusing coil 57 is formed by using a flexible printed circuit board, the focusing coil 57 can easily be coupled to the flexible printed circuit board secured to the plate springs 54 and 55.

A reflecting mirror 59 for changing a light path is secured to a portion in which the front and rear direction hole 49 and the upper and lower direction hole 50 of the movable member 48 intersect, so that the optical axes of light beams travelling through the apertures 49 and 50 are set at a right angle by the mirror 59.

The inner yokes 46 and 47 are inserted into the pair of holes 51a and 51b through a hollow portion of the objective lens supporting member 53.

Guide grooves 48a1, 48b1, 46a1 and 47a1 of U-shape cross-section

This Sheet Has Been Replaced



are respectively formed on the inner surfaces of the holes 51a and 51b, that is, on the side surfaces 48a and 48b of the movable member 48 and magnet-non-opposing surfaces 46a and 47a of the inner yokes 46 and 47 opposing the side surfaces 48a and 48b. A shaft 60 is respectively provided at each of the corners of the guide grooves 48a1, 48b1, 46a1 and 47a1.

Each of the shafts 60 is formed by grinding an outer surface of a rod moulded, for example, from ceramic or stainless steel. The shafts 60 are secured to the corners of the guide grooves 48a1, 48b1, 46a1, and 47a1 by a bonding agent (not shown). Accordingly, four shafts 60 are provided at each side of the movable member 48 in facing relation to each other. Respective balls 61 are interposed between each group of four shafts 60. The balls 61 are each made of non-magnetic material such as, stainless steel, ceramic, ruby or sapphire.

In this way, the movable member 48 is supported on the inner yokes 46 and 47 via the balls 61 so as to freely movable along the inner yokes 46 and 47. During the movement of the movable member 48, the ball 61 rotates between the shafts 60, the outer surfaces of which are ground, whereby the movable member 48 can move stably and accurately. Stops 62 and 63 are formed on the front and rear ends of the surface of the base plate 41 to stop the movable member 48 at predetermined positions. The stops 62 and 63 are each made, for example, of acrylonitrile butadience styrene copolymer or rubber.

As shown in Figure 3, there is provided a galvanomirror 64 located at an angle of substantially 45° to the direction in which the front and rear direction hole 49 of the movable member 48 extends rearwards. A read-out optical system 65 is located at an angle of substantially 45° to the galvanomirror 64. The read-out optical system 65 comprises a laser diode 65a, a photo-diode 65b and a beam splitter 65c.

In this embodiment, the read-out optical system 65 and the galvanomirror 64 form a stationary optical systems and the mirror 59 and the objective lens 56 form a movable optical system. These stationary and movable optical systems are located in the same plane, whereby the thickness of the whole optical pick-up head apparatus can be reduced.

More precisely, the stationary optical system formed of the read-

This Sheet Has Been Replacec



out optical system 65 and the galvanomirror 64, and the movable optical system formed of the mirror 59 and the objective lens 56 are respectively located such that the optical axis of the light path through which a light beam emitted from the laser diode 65a reaches the mirror 59, and the optical axis of the light path in which a reflected-back laser beam from the optical disc D reaches the photo 65c from the mirror 59 are provided in the same plane. The mirror 59 is located such that the optical axis of the light path over which the laser beam emitted from the laser diode 65a reaches the optical disc D via the mirror 59 and the optical axis of the light path over which the reflected-back laser beam from the optical disc D reaches the mirror 59 are perpendicular to the above plane.

In accordance this embodiment, however, the light path over which the laser beam reaches the mirror 59 via the beam splitter 65c and the galvanomirror 64, and the light path between the mirror 59 and the optical disc D are made common to the light beam from the laser diode 65a and the reflected-back light beam from the optical disc D. Therefore, the emitted light beam and the reflected-back light beam are distributed by the beam splitter 65c such that the emitted light beam reaches the galvanomirror 64, while the reflected-back light beam reaches the photo-diode 65c.

As described above, the laser beam emitted from the laser diode 65a is introduced into the photo-diode 65b via the galvanomirror 64, the mirror 59, the objective lens 56, the optical disc D, the objective lens 56, the mirror 59 and the galvanomirror 64, in that order. A focusing error signal and a tracking error signal are generated on the basis of the detected output from the photo-diode 65b. As will be described later, the focusing error signal is supplied to the focusing coil 57, and the tracking error signal is supplied to the galvanomirror 64. The galvanomirror 64 performs the tracking servo by rotating the mirror thereof on the basis of the tracking error signal, so that the light beam spot on the optical disc D moves across the tracks formed on the optical disc D.

Turning to Figure 3, there is shown a spindle motor 66 which rotates the optical disc D. The spindle motor 66 is coupled to a disc table 66a on which there is chucked the optical disc D.

As described above, the movable member 48 is supported by the

This Sheet Has Been Replaced



inner yokes 46 and 47 via the balls 61, and the respective side portions of the slide drive coil 52 wound around the bobbin 51 and the horizontal portions of the side surface sides of the deflection coils 57a and 57d secured to the objective lens supporting member 53, that is, the focusing coil 57 is placed within the magnetic gaps g between the magnets 44 and 45 and the inner yokes 46 and 47, whereby the magnetic circuits of the slide motor and the focusing motor are made common.

Moreover, the inner yokes 46 and 47 form a closed magnetic path with the outer yokes 42 and 43 attached to the base plate 41, and also serve as the guide shafts for guiding the movable member 48 so that a guide shaft and a slidable base plate are not needed additionally.

In the thus constructed optical pick-up head apparatus, when the slide driving coil 52 wound around the bobbin 51 of the movable member 48 is energized on the basis of an access command or the like from, for example, a control circuit (not shown), the movable member 48 is given a driving force by the action of the magnetic field within the magnetic gaps g and the current, whereby the movable member 48 can be moved in the front or rear direction along the inner yokes 46 and 47 which serve as the guide shafts, that is, the movable member 48 can be moved in the radial direction of the optical disc D by a linear motor system.

Furthermore, when the focusing error signal generated on the basis of the detected output from the photo-diode 65b is supplied to the flat coils 57a to 57d fixed to the objective lens supporting members 53, the objective lens supporting member 53 is moved by the parallel plate springs 54 and 55 in the upper or lower direction parallel to the optical axis of the objective lens 56, due to the reaction between the current flowing through the horizontal portions of the respective coils located within the magnetic gaps g and the magnetic field produced within the magnetic gaps g, whereby the focusing of the objective lens 56 relative to the optical disc D is adjusted. In this way, the read-out optical system 65 reads (that is, reproduces) the optical disc D.

The movable member 48 can, for example, be unitarily formed with the bobbin 51 as one body. Moreover, either the guide grooves 48a1, 48b1, or 46a1, 47a1 or both of the guide grooves 48a1, 48b1 and 46a1, 47a1 of the inner yokes 46 and 47, and the movable member 48 can be

This Sheet Has Been Replaced



shaped to have a cross-section of V-shape. If the two guide grooves are V-shaped, then the shafts can be omitted. Also, the number of balls interposed between the guide grooves can be increased and/or decreased, if necessary.

Furthermore, the lay out of the read-out optical system 65 and the like can be freely modified in dependence on the arrangement of the optical disc recording and/or reproducing apparatus.

In addition, by applying such an optical pick-up head apparatus to a magneto-optical disc recording and/or reproducing apparatus, it is possible to reduce the thickness of the recording and/or reproducing apparatus considerably, which has been a very difficult problem to solve, because an external magnetic field generating apparatus must be provided at the disc surface side opposite to the recording and/or reproducing apparatus across the magneto-optical disc, in prior-art magneto-optical disc recording and/or reproducing apparatus.

As set out above, in an embodiment of the present invention, since the magnetic circuits of the slide drive motor which moves the objective lens in the radial direction of the optical disc of the focusing motor which moves the objective lens in its optical axis direction can be made common, the movable member does not need a heavy magnet, so that the mass of the movable member can be reduced. Also, mutual interference can be avoided between the magnetic circuits of the two motors, and a magnetically neutral portion can be prevented from being produced in the movement of the objective lens, thus making it possible stably to move the objective lens at high speed. Therefore, the reliability of the optical pick-up head apparatus can be increased. Furthermore, the assembly is simplified, and the assembly cost reduced.

This Sheet Has Been Replaced



* C L M S *

CLAIMS

1. An optical pick-up head apparatus having a tracking error signal generating device for generating a tracking error signal on the basis of a detected output from a photo-detecting device (65b), and a tracking control device for performing a tracking servo by rotating a mirror portion (64) in response to the tracking error signal supplied thereto, the apparatus comprising:
a yoke (46, 47) facing a magnet (44, 45);
a movable member (48) having an aperture (49, 50) into which said yoke (46, 47) is inserted and around which a first coil (52) is wound facing said magnet (44, 45); and
objective lens supporting means (53) for supporting an objective lens (56) to be movable in the direction parallel to an optical axis of said objective lens (56) and having a plurality of second coils (57) to move said objective lens (56) in the direction parallel to the optical axis of said objective lens (56);
wherein said objective lens supporting means (53) is secured to said member (48), said movable member (48) is supported by said yoke (46, 47) so that it can move freely, and at least one side of said first and second coils (52, 57) is located within a common magnetic gap.

2. Apparatus according to claim 1 wherein said objective lens supporting means (53) comprises an objective lens supporting member (53) with said objective lens (56) and said plurality of second coils (57) attached thereto, and a pair of leaf springs (54, 55) to one ends of which said objective lens supporting member (53) is attached, and whose other ends are secured to said movable member (48).

3. Apparatus according to claim 1 wherein each of said second coils (57) is shaped as a substantially square coil of L-shape, and one side of a pair of sides perpendicular to the optical axis of said objective lens (56) is located within said common magnetic gap.

4. Apparatus according to claim 1 wherein guide portions (46a1, 47a1, 48a1, 48b1) for ball members (61) are respectively provided in apertures (51a, 51b) of said yoke (46, 47) and said movable member

This Sheet Has Been Replaced

(48), and said movable member (48) is supported in said yoke (46, 47) by said ball members (61).

5. Apparatus according to claim 4 wherein said guide portions (46a1, 47a1, 48a1, 48b1) are provided with shafts (60) which contact said ball members (61).

6. An optical pick-up head apparatus comprising:
a stationary optical system (64, 65) formed of a laser light source (65a), photo-detecting means (65b), and tracking control means (64) for performing a tracking control so that a beam spot formed on an optical disc by a light beam emitted from said laser light source (65a) follows tracks on said optical disc; and
a movable optical system (56, 59) formed of an objective lens (56) freely movable in the radial direction of said optical disc and controlled to focus the light beam emitted from said laser light source (65a) on said optical disc, and light path changing means (59) for changing the path of the light beam emitted from said laser light source (65a) so that said light beam becomes incident on said objective lens (56);
wherein said stationary optical system (64, 65) and said movable optical system (56, 59) are located in the same plane.

7. Apparatus according to claim 6 wherein the optical axis of the light path through which the light beam emitted from said laser light source (65a) reaches said light path changing means (59), and the optical axis of the light path through which a reflected-back light beam from said optical disc reaches said photo-detecting means (65b) from said light path changing means (59) are located in the same plane.

8. Apparatus according to claim 6 wherein said light path changing means (59) changes the light path of the light beam emitted from said laser light source (65a) such that said light path is located at a right angle to said plane.

9. Apparatus according to claim 6 wherein said movable optical system (56, 59) comprises objective lens supporting means (53) for

This Sheet Has Been Replaced

* C L M S *

supporting said objective lens (56) such that said objective lens (56) can move freely in the direction parallel to the optical axis thereof, a movable member (48) on which said objective lens supporting means (53) is attached, and slide means (60) for sliding said movable member (48) in the radial direction of said optical disc.

This Sheet Has Been Replaced

ABSTRACT

OPTICAL PICK-UP HEAD APPARATUS

An optical pick-up head apparatus comprises a yoke (46, 47) provided in an opposing relation to a magnet (44, 45), a movable member (48) having therethrough an aperture (51a, 51b) into which the yoke (46, 47) is inserted and around which a first coil (52) is wound in facing relation to the magnet (44, 45), an objective lens supporting device (53) having a pair of leaf springs (54, 55) for supporting the objective lens (56) such that the objective lens (56) can move in the direction parallel to the optical axis thereof, a plurality of second coils (57) of substantially square shape for moving the objective lens (56) in the direction parallel to the optical axis thereof, and a tracking control device (64) for rotating a mirror portion so that a beam spot focused on the optical disc by the objective lens (56) follows a track on the optical disc. The objective lens supporting device (53) is secured to the movable member (48), the movable member (48) is movably supported by the yoke (46, 47), and one side of each of the second coils (57) and of the first (52) are located within a common magnetic gap.

This Sheet Has Been Replaced




FIG. 1

This Sheet Has Been Replaced

This Sheet Has Been Replaced

FIG. 2






FIG. 4




This Sheet Has Been Replaced

FIG. 3




This Sheet Has Been Replaced

FIG. 5



This Sheet Has Been Replaced

FIG. 6



9608040-9 3103

REPLACED SHEETS SG
☐ Description : paged ..... to paged .....
☑ Claim(s) : paged ...11... to paged ...13.....
☐ Drawing(s) : paged ..... to paged .....
☑ Abstract : paged ...14... to paged ...15.....
DATE OF RECEIPT .....

REPLACEMENT SHEETS SG
☑ Description : paged 1... to paged 10..
☑ Claim(s) : paged 11... to paged 13..
☑ Drawing(s) : paged 14.. to paged 15..
☑ Abstract : paged 14.. to paged 15...
DATE OF RECEIPT 3/12/96

OPTICAL PICK-UP HEAD APPARATUS

This invention relates to optical pick-up head apparatus, for use, for example, in a recording and/or reproducing apparatus which records and/or reproduces a so-called optical disc such as a magneto-optical disc.

An optical disc recording and/or reproducing apparatus for recording and/or reproducing an optical disc such as a magneto-optical disc may include a linear motor system to translate an objective lens. For example, US patent specifications US-A-4 545 046 and US-A-4 607 913 describe such optical pick-up head apparatus. In such an apparatus, if two parallel guide rods of the apparatus are not supported very accurately, then this will impair smooth movement of a movable member to which the objective lens is attached. Moreover, in this type of optical pick-up head apparatus, the bearings attached to the movable member are expensive. Also, if the bearings are not identical in their properties, movement of the movable member will be impaired.

Our US patent specification US-A-4 864 170 describes a linear motor which can be applied to such an optical pick-up head apparatus, and this will now be described with reference to Figures 1 and 2. Figure 1 is a perspective view of the linear motor, and Figure 2 is a transverse sectional view taken on the line I - I in Figure 1.

Referring to Figures 1 and 2, two permanent stator magnets 1 and 4 are each magnetized in the thickness direction thereof. A base plate 2 is made of a magnetizable material, for example, iron, and has secured on it two outer stator yokes 3 and 5. The stator magnet 1 is attached to the inner side of the stator yoke 3, and the stator magnet 4 is similarly attached to the inner side of the stator yoke 5, leaving a predetermined clearance. Enclosing the stator magnets 1 and 4, inner stator yokes 6 and 7 are secured to the base plate 2, such that they form closed magnetic paths together with the outer stator yokes 3 and 5.

A frame or bobbin 8 has at least the outer peripheral portion thereof made of a non-magnetic material. A pair of coils 9a and 9b are wound around two end portions of the bobbin 8, and through-holes 10 and 11 are formed through the bobbin 8 so that they intersect each other in the front and rear direction as well as the upper and lower direction.

This is the replacement sheet

0 - 0 6 0 8 0 4 0 - 9

Date: 03 DEC 1996

The bobbin 8 also has formed therethrough a pair of apertures 12 and 13 which penetrate the pair of coils 9a and 9b. The inner stator yokes 6 and 7 are inserted into the pair of apertures 12 and 13.

Guide grooves 14, 15 and 16, 17 are formed on the inside surfaces of the apertures 12 and 13 and on the inner surfaces of the inner stator yokes 6 and 7. As shown in Figure 2, pairs of shafts 18 and 19 are attached to the guide grooves 14 and 15, and balls 21a and 21b are supported by supporting members 20a and 20b within these guide grooves 14, 15 and 16, 17. Therefore, the bobbin 8 is supported on the inner stator yokes 6 and 7 via the balls 21a and 21b, whereby the bobbin 8 can move freely in the longitudinal direction of the inner stator yokes 6 and 7.

A reflecting mirror 22 for changing a light path is secured where the holes 10 and 11 intersect. An optical pick-up 25 having an objective lens 24 is attached to the exit side of the vertically-elongated hole 11 by a mount 23. The optical pick-up 25 faces an optical disc D, and includes a focusing motor 26 to move the objective lens 24 in the optical axis direction of the objective lens 24.

As shown in Figure 1, a read-out optical system 27 is located in the direction in which the hole 10 formed through the bobbin 8 in the front and rear direction extends rearward. The read-out optical system 27 comprises a laser diode 28, a beam splitter 29, a collimator lens 30, a light receiving system 31, and a photo-diode 32. With the read-out optical system 27, a light beam emitted from the laser diode 28 travels over a light path formed of the collimator lens 30, the mirror 22, the objective lens 24 of the optical pick-up 25, the optical disc D, the objective lens 24, the mirror 22, the collimator lens 30, the beam splitter 29 and the light receiving system 31, in that order, and is incident on the photo-diode 32.

In this optical pick-up head apparatus, when both the coils 9a and 9b are energized, the bobbin 8 is acted on by a driving force according to Fleming's left-hand rule, due to the reaction between the current and the magnetic field produced by the magnets 1 and 4 and the yokes 3, 6 and 5, 7, that is, a linear motor is formed, whereby the optical pick-up 25 is moved in the radial direction of the optical disc D. During this operation of the optical pick-up 25 the objective lens 24 of the optical pick-up 25 is driven by the focusing motor 26, so

This is the replacement sheet

Date: 0 3 DEC 1996

that the focus of the objective lens 24 is adjusted.

In this optical pick-up head apparatus, the linear motor for moving the optical pick-up 25 is compact, because the bobbin 8 supporting the optical pick-up 25 utilizes the inner stator yokes 6 and 7 as guides. However, the optical pick-up 25 is provided with the focusing motor 26 which moves the objective lens 24, and the focusing motor 26 and the feed linear motor form different magnetic circuits, which are liable to interfere with each other. Thus, there may be a magnetically neutral zone which interferes with the movement of the optical pick-up 25, that is, the bobbin 8.

Moreover, the bobbin 8 is loaded with the weight of the magnetic circuit of the focusing motor 26, so that the moving mass is increased, which results in a lower accessing speed. Also, the number of magnets forming the magnetic circuits is increased, which increases the cost.

According to the present invention there is provided an optical pick-up head apparatus having a tracking error signal generating device for generating a tracking error signal on the basis of a detected output from a photo-detecting device, and a tracking control device for performing a tracking servo by rotating a mirror portion in response to the tracking error signal supplied thereto, the apparatus comprising:
a yoke facing a magnet;
a movable member having an aperture into which said yoke is inserted and around which a first coil is wound facing said magnet; and
objective lens supporting means for supporting an objective lens to be movable in the direction parallel to an optical axis of said objective lens and having a plurality of second coils to move said objective lens in the direction parallel to the optical axis of said objective lens;
wherein said objective lens supporting means is secured to said member, said movable member is supported by said yoke so that it can move freely, and at least one side of said first and second coils is located within a common magnetic gap.

According to the present invention there is also provided an optical pick-up head apparatus comprising:
a stationary optical system formed of a laser light source, photo-detecting means, and tracking control means for performing a tracking control so that a beam spot formed on an optical disc by a light beam emitted from said laser light source follows tracks on said optical

This is the replacement sheet
03 DEC 1996
Date:

disc; and

a movable optical system formed of an objective lens freely movable in the radial direction of said optical disc and controlled to focus the light beam emitted from said laser light source on said optical disc, and light path changing means for changing the path of the light beam emitted from said laser light source so that said light beam becomes incident on said objective lens;

wherein said stationary optical system and said movable optical system are located in the same plane.

An embodiment of optical pick-up head apparatus according to the invention having a tracking error signal generating device for generating a tracking error signal on the basis of a detected output from a photo-detecting device and a tracking control device for performing a tracking servo by rotating a mirror portion in response to the tracking error signal supplied thereto, may comprise yokes provided in an opposing relation to a magnet, a movable member having apertures into which the yokes are inserted and around which a first coil is wound in an opposing relation to the magnets, and an objective lens supporting device having a plurality of second coils to support an objective lens such that the objective lens can be moved in the direction parallel to an optical axis of the objective lens, and which moves the objective lens in the direction parallel to the optical axis of the objective lens, wherein the objective lens supporting device is secured to the movable member, the movable member is supported by the yokes so that is can move freely, and at least one side of the first and second coils is provided within a common magnetic gap.

An embodiment of optical pick-up head apparatus according to the invention may comprise a stationary optical system formed of a laser light source, a photo-detecting device, and a tracking control device for performing a tracking control, so that a beam spot formed on an optical disc by a light beam emitted from the laser light source follows tracks on the optical disc, and a movable optical system formed of an objective lens controlled to focus the light beam emitted from the laser light source on the optical disc, and a light path changing device for changing a light path of the light beam emitted from the laser light source so that the light beam becomes incident on the objective lens, wherein the stationary optical system and the movable

This is the replacement sheet

0 3 DEC 1996

Date:

optical system are provided on the same plane.

The invention will now be described by way of example with reference to the accompanying drawings, throughout which like parts are referred to by like references, and in which:

Figure 1 is a perspective view of an example of a previously-proposed optical pick-up apparatus;

Figure 2 is a transverse sectional view taken on the line I - I in Figure 1;

Figure 3 is a perspective view of an embodiment of optical pick-up apparatus according to the present invention;

Figure 4 is an enlarged transverse sectional view taken on the line II - II in Figure 3;

Figure 5 is an enlarged longitudinal sectional view of the embodiment; and

Figure 6 is an exploded perspective view of part of the embodiment.

Referring to Figures 3 to 6, there is shown a base plate 41 of a rectangular shape which is made of a rigid material. Outer yokes 42 and 43 of substantially U-shape are secured to the two side portions of the base plate 41 in the longitudinal direction of the surface of the base plate 41 in facing relation. Magnets 44 and 45, each magnetized in the thickness direction, are attached to the inside surfaces of the outer yokes 42 and 43, respectively.

Inner yokes 46 and 47 are respectively coupled to the outer yokes 42 and 43 at two inner end faces 42a, 42b and 43a, 43b, whereby the magnets 44 and 45 are respectively encircled by the yokes 42, 43, 46 and 47 to form closed magnetic paths. More specifically, the inner yokes 46 and 47 are held on stepped surfaces 42a1, 42b1, 43a1 and 43b1 of predetermined height formed on the inner ends of the outer yokes 42 and 43. Thus, magnetic gaps g of a predetermined width are respectively formed between the magnets 44 and 45 and the inner yokes 46 and 47, and the inner yokes 46 and 47 are supported on the surface of the base plate 42 at a predetermined spacing.

A movable member 48 has formed therethrough apertures 49 and 50 intersecting each other in the front and rear direction and in the upper and lower direction. A bobbin 51 made of a non-magnetic material is engaged with the rear half portion of the movable member 48 such

This is the replacement sheet

Date: 03 DEC 1996

that a pair of through-holes 51a and 51b are respectively formed between two side surfaces 48a and 48b of the movable member 48 and the bobbin 51. A slide drive coil 52 is wound around the outer peripheral surface of the bobbin 51 as a first coil.

An objective lens supporting member 53 which is shaped as a rectangular frame is supported on the first half portion of the movable member 48 by parallel plate springs 54 and 55 so as to be freely movable in the upper and lower direction. An objective lens 56 is attached to the objective lens supporting member 53 in facing relation to the exit side of the hole 50 extending in the upper and lower direction of the movable member 48.

Flat coils 57a, 57b, 57c and 57d are moulded in L-shape and are secured to four corners of the objective lens supporting member 53, respectively, whereby horizontal portions of the respective flat coils in the two side surfaces of the supporting member 53 form a focusing coil 57 which might be referred to as a second coil. The flat coils 57a, 57b, 57c and 57d are respectively energized by bonding flexible printed circuit boards 58a and 58b to the plate springs 54 and 55. When the circuit boards 58a and 58b are bonded to the plate springs 54 and 55, resonance of the plate springs 54 and 55 can be suppressed, no improving the silencing. Preferably, the plate springs 54 and 55 are each made of a non-magnetic material such as helium bronze or phosphor bronze. The focusing coil 57 may be formed by bending wound wires of square shape in an L-shape as described above. Alternatively, the focusing coil 57 may be formed by using a flexible printed circuit board. When the focusing coil 57 is formed by using a flexible printed circuit board, the focusing coil 57 can easily be coupled to the flexible printed circuit board secured to the plate springs 54 and 55.

A reflecting mirror 59 for changing a light path is secured to a portion in which the front and rear direction hole 49 and the upper and lower direction hole 50 of the movable member 48 intersect, so that the optical axes of light beams travelling through the apertures 49 and 50 are set at a right angle by the mirror 59.

The inner yokes 46 and 47 are inserted into the pair of holes 51a and 51b through a hollow portion of the objective lens supporting member 53.

Guide grooves 48a1, 48b1, 46a1 and 47a1 of U-shape cross-section

This is the replacement sheet
0 3 DEC 1996
Date:

are respectively formed on the inner surfaces of the holes 51a and 51b, that is, on the side surfaces 48a and 48b of the movable member 48 and magnet-non-opposing surfaces 46a and 47a of the inner yokes 46 and 47 opposing the side surfaces 48a and 48b. A shaft 60 is respectively provided at each of the corners of the guide grooves 48a1, 48b1, 46a1 and 47a1.

Each of the shafts 60 is formed by grinding an outer surface of a rod moulded, for example, from ceramic or stainless steel. The shafts 60 are secured to the corners of the guide grooves 48a1, 48b1, 46a1, and 47a1 by a bonding agent (not shown). Accordingly, four shafts 60 are provided at each side of the movable member 48 in facing relation to each other. Respective balls 61 are interposed between each group of four shafts 60. The balls 61 are each made of non-magnetic material such as, stainless steel, ceramic, ruby or sapphire.

In this way, the movable member 48 is supported on the inner yokes 46 and 47 via the balls 61 so as to freely movable along the inner yokes 46 and 47. During the movement of the movable member 48, the ball 61 rotates between the shafts 60, the outer surfaces of which are ground, whereby the movable member 48 can move stably and accurately. Stops 62 and 63 are formed on the front and rear ends of the surface of the base plate 41 to stop the movable member 48 at predetermined positions. The stops 62 and 63 are each made, for example, of acrylonitrile butadience styrene copolymer or rubber.

As shown in Figure 3, there is provided a galvanomirror 64 located at an angle of substantially 45° to the direction in which the front and rear direction hole 49 of the movable member 48 extends rearwards. A read-out optical system 65 is located at an angle of substantially 45° to the galvanomirror 64. The read-out optical system 65 comprises a laser diode 65a, a photo-diode 65b and a beam splitter 65c.

In this embodiment, the read-out optical system 65 and the galvanomirror 64 form a stationary optical systems and the mirror 59 and the objective lens 56 form a movable optical system. These stationary and movable optical systems are located in the same plane, whereby the thickness of the whole optical pick-up head apparatus can be reduced.

More precisely, the stationary optical system formed of the read-

This is the replacement sheet

Date: 03 DEC 1996

out optical system 65 and the galvanomirror 64, and the movable optical system formed of the mirror 59 and the objective lens 56 are respectively located such that the optical axis of the light path through which a light beam emitted from the laser diode 65a reaches the mirror 59, and the optical axis of the light path in which a reflected-back laser beam from the optical disc D reaches the photo 65c from the mirror 59 are provided in the same plane. The mirror 59 is located such that the optical axis of the light path over which the laser beam emitted from the laser diode 65a reaches the optical disc D via the mirror 59 and the optical axis of the light path over which the reflected-back laser beam from the optical disc D reaches the mirror 59 are perpendicular to the above plane.

In accordance this embodiment, however, the light path over which the laser beam reaches the mirror 59 via the beam splitter 65c and the galvanomirror 64, and the light path between the mirror 59 and the optical disc D are made common to the light beam from the laser diode 65a and the reflected-back light beam from the optical disc D. Therefore, the emitted light beam and the reflected-back light beam are distributed by the beam splitter 65c such that the emitted light beam reaches the galvanomirror 64, while the reflected-back light beam reaches the photo-diode 65c.

As described above, the laser beam emitted from the laser diode 65a is introduced into the photo-diode 65b via the galvanomirror 64, the mirror 59, the objective lens 56, the optical disc D, the objective lens 56, the mirror 59 and the galvanomirror 64, in that order. A focusing error signal and a tracking error signal are generated on the basis of the detected output from the photo-diode 65b. As will be described later, the focusing error signal is supplied to the focusing coil 57, and the tracking error signal is supplied to the galvanomirror 64. The galvanomirror 64 performs the tracking servo by rotating the mirror thereof on the basis of the tracking error signal, so that the light beam spot on the optical disc D moves across the tracks formed on the optical disc D.

Turning to Figure 3, there is shown a spindle motor 66 which rotates the optical disc D. The spindle motor 66 is coupled to a disc table 66a on which there is chucked the optical disc D.

As described above, the movable member 48 is supported by the

This is the replacement sheet

Date: 03 DEC 1996

inner yokes 46 and 47 via the balls 61, and the respective side portions of the slide drive coil 52 wound around the bobbin 51 and the horizontal portions of the side surface sides of the deflection coils 57a and 57d secured to the objective lens supporting member 53, that is, the focusing coil 57 is placed within the magnetic gaps g between the magnets 44 and 45 and the inner yokes 46 and 47, whereby the magnetic circuits of the slide motor and the focusing motor are made common.

Moreover, the inner yokes 46 and 47 form a closed magnetic path with the outer yokes 42 and 43 attached to the base plate 41, and also serve as the guide shafts for guiding the movable member 48 so that a guide shaft and a slidable base plate are not needed additionally.

In the thus constructed optical pick-up head apparatus, when the slide driving coil 52 wound around the bobbin 51 of the movable member 48 is energized on the basis of an access command or the like from, for example, a control circuit (not shown), the movable member 48 is given a driving force by the action of the magnetic field within the magnetic gaps g and the current, whereby the movable member 48 can be moved in the front or rear direction along the inner yokes 46 and 47 which serve as the guide shafts, that is, the movable member 48 can be moved in the radial direction of the optical disc D by a linear motor system.

Furthermore, when the focusing error signal generated on the basis of the detected output from the photo-diode 65b is supplied to the flat coils 57a to 57d fixed to the objective lens supporting members 53, the objective lens supporting member 53 is moved by the parallel plate springs 54 and 55 in the upper or lower direction parallel to the optical axis of the objective lens 56, due to the reaction between the current flowing through the horizontal portions of the respective coils located within the magnetic gaps g and the magnetic field produced within the magnetic gaps g, whereby the focusing of the objective lens 56 relative to the optical disc D is adjusted. In this way, the read-out optical system 65 reads (that is, reproduces) the optical disc D.

The movable member 48 can, for example, be unitarily formed with the bobbin 51 as one body. Moreover, either the guide grooves 48a1, 48b1, or 46a1, 47a1 or both of the guide grooves 48a1, 48b1 and 46a1, 47a1 of the inner yokes 46 and 47, and the movable member 48 can be

This is the replacement sheet

Date: 0 3 DEC 1996

shaped to have a cross-section of V-shape. If the two guide grooves are V-shaped, then the shafts can be omitted. Also, the number of balls interposed between the guide grooves can be increased and/or decreased, if necessary.

Furthermore, the lay out of the read-out optical system 65 and the like can be freely modified in dependence on the arrangement of the optical disc recording and/or reproducing apparatus.

In addition, by applying such an optical pick-up head apparatus to a magneto-optical disc recording and/or reproducing apparatus, it is possible to reduce the thickness of the recording and/or reproducing apparatus considerably, which has been a very difficult problem to solve, because an external magnetic field generating apparatus must be provided at the disc surface side opposite to the recording and/or reproducing apparatus across the magneto-optical disc, in prior-art magneto-optical disc recording and/or reproducing apparatus.

As set out above, in an embodiment of the present invention, since the magnetic circuits of the slide drive motor which moves the objective lens in the radial direction of the optical disc of the focusing motor which moves the objective lens in its optical axis direction can be made common, the movable member does not need a heavy magnet, so that the mass of the movable member can be reduced. Also, mutual interference can be avoided between the magnetic circuits of the two motors, and a magnetically neutral portion can be prevented from being produced in the movement of the objective lens, thus making it possible stably to move the objective lens at high speed. Therefore, the reliability of the optical pick-up head apparatus can be increased. Furthermore, the assembly is simplified, and the assembly cost reduced.

This is the replacement sheet

Date: 03 DEC 1996

* C L M S *

CLAIMS

1. An optical pick-up head apparatus having a tracking error signal generating device for generating a tracking error signal on the basis of a detected output from a photo-detecting device (65b), and a tracking control device for performing a tracking servo by rotating a mirror portion (64) in response to the tracking error signal supplied thereto, the apparatus comprising:

a yoke (46, 47) facing a magnet (44, 45);

a movable member (48) having an aperture (49, 50) into which said yoke (46, 47) is inserted and around which a first coil (52) is wound facing said magnet (44, 45); and

objective lens supporting means (53) for supporting an objective lens (56) to be movable in the direction parallel to an optical axis of said objective lens (56) and having a plurality of second coils (57) to move said objective lens (56) in the direction parallel to the optical axis of said objective lens (56);

wherein said objective lens supporting means (53) is secured to said member (48), said movable member (48) is supported by said yoke (46, 47) so that it can move freely, and at least one side of said first and second coils (52, 57) is located within a common magnetic gap.

2. Apparatus according to claim 1 wherein said objective lens supporting means (53) comprises an objective lens supporting member (53) with said objective lens (56) and said plurality of second coils (57) attached thereto, and a pair of leaf springs (54, 55) to one ends of which said objective lens supporting member (53) is attached, and whose other ends are secured to said movable member (48).

3. Apparatus according to claim 1 wherein each of said second coils (57) is shaped as a substantially square coil of L-shape, and one side of a pair of sides perpendicular to the optical axis of said objective lens (56) is located within said common magnetic gap.

4. Apparatus according to claim 1 wherein guide portions (46a1, 47a1, 48a1, 48b1) for ball members (61) are respectively provided in apertures (51a, 51b) of said yoke (46, 47) and said movable member

This Sheet Has Been Replaced

This is the replacement sheet

Date: 03 DEC 1996

* C L M S *

(48), and said movable member (48) is supported in said yoke (46, 47) by said ball members (61).

5. Apparatus according to claim 4 wherein said guide portions (46a1, 47a1, 48a1, 48b1) are provided with shafts (60) which contact said ball members (61).

6. An optical pick-up head apparatus comprising:
a stationary optical system (64, 65) formed of a laser light source (65a), photo-detecting means (65b), and tracking control means (64) for performing a tracking control so that a beam spot formed on an optical disc by a light beam emitted from said laser light source (65a) follows tracks on said optical disc; and
a movable optical system (56, 59) formed of an objective lens (56) freely movable in the radial direction of said optical disc and controlled to focus the light beam emitted from said laser light source (65a) on said optical disc, and light path changing means (59) for changing the path of the light beam emitted from said laser light source (65a) so that said light beam becomes incident on said objective lens (56);
wherein said stationary optical system (64, 65) and said movable optical system (56, 59) are located in the same plane.

7. Apparatus according to claim 6 wherein the optical axis of the light path through which the light beam emitted from said laser light source (65a) reaches said light path changing means (59), and the optical axis of the light path through which a reflected-back light beam from said optical disc reaches said photo-detecting means (65b) from said light path changing means (59) are located in the same plane.

8. Apparatus according to claim 6 wherein said light path changing means (59) changes the light path of the light beam emitted from said laser light source (65a) such that said light path is located at a right angle to said plane.

9. Apparatus according to claim 6 wherein said movable optical system (56, 59) comprises objective lens supporting means (53) for

This Sheet Has Been Replaced

This is the replacement sheet

Date: 03 DEC 1996

* C L M S *

supporting said objective lens (56) such that said objective lens (56) can move freely in the direction parallel to the optical axis thereof, a movable member (48) on which said objective lens supporting means (53) is attached, and slide means (60) for sliding said movable member (48) in the radial direction of said optical disc.

This Sheet Has Been Replaced

This is the replacement sheet

Date: 03 DEC 1996

ABSTRACT

OPTICAL PICK-UP HEAD APPARATUS

An optical pick-up head apparatus comprises a yoke (46, 47) provided in an opposing relation to a magnet (44, 45), a movable member (48) having therethrough an aperture (51a, 51b) into which the yoke (46, 47) is inserted and around which a first coil (52) is wound in facing relation to the magnet (44, 45), an objective lens supporting device (53) having a pair of leaf springs (54, 55) for supporting the objective lens (56) such that the objective lens (56) can move in the direction parallel to the optical axis thereof, a plurality of second coils (57) of substantially square shape for moving the objective lens (56) in the direction parallel to the optical axis thereof, and a tracking control device (64) for rotating a mirror portion so that a beam spot focused on the optical disc by the objective lens (56) follows a track on the optical disc. The objective lens supporting device (53) is secured to the movable member (48), the movable member (48) is movably supported by the yoke (46, 47), and one side of each of the second coils (57) and of the first (52) are located within a common magnetic gap.

FIGURE 3

This Sheet Has Been Replaced

This is the replacement sheet

Date: 03 DEC 1996




FIG. 1

This is the replacement sheet

0 3 DEC 1996

Date:

FIG. 2






FIG. 4



This is the replacement sheet

Date: 03 DEC 1996


FIG. 3



This is the replacement sheet

Date: 03 DEC 1996


FIG. 5



This is the replacement sheet

Date: 03 DEC 1996

FIG. 6



This is the replacement sheet

Date: 03 DEC 1996

REPLACEMENT SHEETS 30
☐ Description : paged ..... to paged .....
☑ Claim(s) : paged 11 to paged 12
☐ Drawing(s) : paged ..... to paged .....
☑ Abstract : paged 13 to paged 13
DATE OF RECEIPT 3/8/98

CLAIMS:

1. An optical pickup head apparatus having a tracking error signal generating device for a tracking error signal on the basis of a detected output a photodetecting device and a tracking control device for performing a tracking servo by rotating a mirror in response to the tracking error signal supplied thereto, which apparatus comprises:

a magnet;

yoke means provided in an opposing relation to said magnet;

a movable member having an aperture into which said yoke means is inserted;

a first coil wound around said movable member in opposing relation to said magnet.;

an objective lens having an optical axis; and

objective lens supporting means for supporting said objective lens to be movable in a direction parallel to said optical axis and having a plurality of second coils to move said objective lens in said direction, wherein said supporting means is secured to said movable member, said movable member is supported by said yoke means so that it can freely move in a direction perpendicular to said optical axis, and at least one side of said first and second coils is located within a common magnetic gap;

wherein each of said second coils has four sides and is formed as a substantially square coil of L-letter shape, a pair of sides of each of said second coils being perpendicular to the optical axis of said objective lens and one side of each of said second coils being located within said common magnetic gap.

2. An optical head apparatus comprising:

a fixed optical system including a light beam source, a photodetector, and a beam splitter for splitting a light beam emitted from said light beam source, so that a portion of the light beam is irradiated on said photodetector;

a movable optical system having an objective lens, a first coil, a focussing actuator for supporting said objective lens and for moving said objective lens in a direction parallel to an optical axis of said objective lens using at least one of a plurality of second coils, each having four sides and being formed as a substantially square coil of L-letter shape, a pair of sides of each of the plurality of second coils

This is the replacement sheet

Date: 03 AUG 1998

* C L M S *

being formed perpendicular to the optical axis of said objective lens, one side of each of the plurality of second coils being formed parallel to the optical axis of the objective lens, a member provided on said actuator, a linear motor including magnets provided to face said first coil and said sides of said plurality of second coils parallel to said optical axis, whereby said sides of said plurality of second coils parallel to said optional axis are within a common magnetic gap formed by said magnets of said linear motor, guiding means for guiding said member in a direction perpendicular to the axis of said objective lens, and a yoke, said movable optical system being provided in a plane that is parallel to the direction perpendicular to the axis of the objective lens and said fixed optical system being provided in said same plane; and

a tracking means provided between said fixed optical system and said movable optical system and including a mirror for changing a path of the light beam emitted from said light beam source and the light beam irradiated on said photodetector.

3. Apparatus according to claim 1 whererin each said second coils is shaped as a substantially square coil of L-shaped, and one side of a pair of sides prependicular to the optical axis of said objective lens is located within said common magnetic gap.

4. Apparatus according to claim 1 wherein guide portions for ball members are respetively provided in apertures of said yoke and said movable member, and said movable member is supported in said yoke by said ball members.

5. Apparatus according to claim 4 wherein said guide portions are provided with shafts which contact said ball members.

This is the replacement sheet

Date: 03 AUG 1998

ABSTRACT

OPTICAL PICK-UP HEAD APPARATUS

An optical pick-up head apparatus comprises a yoke (46, 47) provided in an opposing relation to a magnet (44, 45), a movable member (48) having therethrough an aperture (51a, 51b) into which the yoke (46, 47) is inserted and around which a first coil (52) is wound in facing relation to the magnet (44, 45), an objective lens supporting device (53) having a pair of leaf springs (54, 55) for supporting the objective lens (56) such that the objective lens (56) can move in the direction parallel to the optical axis thereof, a plurality of second coils (57) of substantially square shape for moving the objective lens (56) in the direction parallel to the optical axis thereof, and a tracking control device (64) for rotating a mirror portion so that a beam spot focused on the optical disc by the objective lens (56) follows a track on the optical disc. The objective lens supporting device (53) is secured to the movable member (48), the movable member (48) is movably supported by the yoke (46, 47), and one side of each of the second coils (57) and of the first (52) are located within a common magnetic gap.

FIGURE 3

This is the replacement sheet

Date: 03 AUG 1998