

DESCRIPTION

Title of the Invention:

MOBILE COMMUNICATION METHOD, MOBILE STATION, AND WIRELESS
5 ACCESS NETWORK APPARATUS

Technical Field

[0001]

The present invention relates to a mobile communication
10 method, a mobile station, and a radio access network apparatus
with which a mobile station camping on a system of a first
communication scheme starts circuit switched communications
in a mobile communication system in which there coexist the
system of the first communication scheme not capable of
15 supporting circuit switched communications, and a system of
a second communication scheme capable of supporting circuit
switched communications.

Background Art

20 [0002]

Referring to Fig. 5, operations for starting
communications in a system of conventional LTE (Long Term
Evolution) scheme is described.

[0003]

25 As shown in Fig. 5, in step S3000, the mobile station
UE performs location registration processing (Attach/TAU
(Tracking Area Update)) to the exchange MME of the LTE scheme.

[0004]

In step S3001A, an application function AP of the mobile
30 station UE transmits "Primitive" to the function EMM
performing processing related to the EMM protocol, in

response to a calling operation by a user.

[0005]

Alternatively, the exchange MME in the LTE scheme transmits "S1 Paging" to the radio base station eNB of the
5 LTE scheme in step S3001B, and also transmits "Paging" to the function EMM in step S3001C.

[0006]

Consequently, in step S3002, the function EMM transmits "Primitive" to the function AS performing processing related
10 to the AS protocol.

[0007]

In step S3003, the function AS transmits "RRC Connection Request" to the radio base station eNB.

[0008]

15 In step S3004, the radio base station eNB transmits "RRC Connection Setup" to the function AS.

[0009]

In steps S3005 to S3007, the function EMM transmits "NAS Service Request" to the function AS. The function AS
20 includes the received "NAS Service Request" in "RRC Connection Setup Complete", and transmits the "NAS Service Request" to the radio base station eNB. The radio base station eNB extracts "S-TMSI" from the received "RRC Connection Request", and also extracts "NAS Service Request"
25 from the received "RRC Connection Setup Complete". The radio base station eNB includes the extracted "S-TMSI" and "NAS Service Request" in "S1 Initial UE Message", and transmits the "S1 Initial UE Message" to the exchange MME.

[0010]

30 In step S3008, the exchange MME transmits "S1 Initial UE Context Setup" including "UE capability (capability

information of mobile station)" to the radio base station eNB.

[0011]

In step S3009, the radio base station eNB transmits "RRC Security Mode Command" to the function AS, and in step S3010, the function AS transmits "Primitive" to the function EMM.

[0012]

In step S3011, the radio base station eNB transmits "RRC Connection Reconfiguration" to the function AS, and in step S3012, the function AS transmits "Primitive" to the function EMM.

[0013]

The function AS transmits "RRC Security Mode Complete" to the radio base station eNB in step S3013, and transmits "RRC Connection Reconfiguration Complete" to the radio base station eNB in step S3014.

[0014]

In step S3015, the radio base station eNB transmits "S1 Setup Complete" to the exchange MME.

[0015]

In step S3016, "U-Plane" is established to communicate between the mobile station UE and the network.

Disclosure of the Invention

Problem to be Solved by the Invention

[0016]

However, since a system of the conventional LTE scheme does not support circuit switched (CS: Circuit Switch) communications, there is a problem in that the mobile station UE cannot perform circuit switched communications (for both transmission and reception) when the mobile station UE is

camping on a system of the LTE scheme.

[0017]

Thus, the present invention is made in view of the above-mentioned problem, and it is an object of the present invention to provide a mobile communication method, a mobile station, and a radio access network apparatus that allows circuit switched communications (for both transmission and reception) even when the mobile station UE is camping on a system of the LTE scheme.

10 **Solution to Problem**

[0018]

A first aspect of the present invention is summarized as a mobile communication method in which a mobile station camping on a system of a first communication scheme starts circuit switched communications in a mobile communication system in which there coexist the system of the first communication scheme not capable of supporting circuit switched communications, and a system of a second communication scheme capable of supporting circuit switched communications, wherein the mobile station includes: a first protocol processor unit configured to perform processing related to a first protocol terminated between the mobile station and a core network apparatus of the first communication scheme; a second protocol processor unit configured to perform processing related to a second protocol terminated between the mobile station and the core network apparatus of the second communication scheme; and a third protocol processor unit configured to perform processing related to a third protocol terminated between the mobile station and a radio access network apparatus; the method includes the steps of: (A) transmitting, at a radio access

network apparatus of the first communication scheme,
instruction information to the third protocol processor unit
when receiving predetermined information which indicates its
relevancy to a start of circuit switched communications, the
5 instruction information instructing to select a cell in the
second communication scheme; (B) instructing, at the third
protocol processor unit, to start the circuit switched
communications to the first protocol processor unit when
receiving the instruction information; (C) instructing, at
10 the first protocol processor unit, to start the circuit
switched communications to the second protocol processor
unit when receiving the instruction from the third protocol
processor unit; (D) selecting, at the third protocol
processor unit, a cell in the second communication scheme
15 when receiving the instruction information; and (E) setting
up, at the second protocol processor unit has receiving the
instruction from the first protocol processor unit, a link
for the circuit switched communications via the cell in the
second communication scheme selected by the third protocol
20 processor unit.

[0019]

In the first aspect, in the step (A), when receiving,
from the third protocol processor unit, a setup complete
response of a radio link between the radio access network
25 apparatus of the first communication scheme and the mobile
station as the predetermined information, the radio access
network apparatus of the first communication scheme can
transmit, to the third protocol processor unit, the
instruction information based on identification information
30 of the mobile station and capability information of the mobile
station, after acquiring the identification information of

the mobile station and capability information of the mobile station from the core network apparatus of the first communication scheme.

[0020]

5 In the first aspect, the method can further include the step of: transmitting, at the core network apparatus of the first communication scheme, setup information to the radio access network apparatus of the first communication scheme when receiving a service request of the first communication
10 scheme from first protocol processor unit via the radio access network apparatus of the first communication scheme, the setup information which indicates its relevancy to a start of circuit switched communications; and in the step (A), the radio access network apparatus of the first communication
15 scheme can transmit the instruction information to the third protocol processor unit when receiving the setup information from the core network apparatus of the first communication scheme as the predetermined information.

[0021]

20 In the first aspect, the method can further include the steps of: transmit, at the core network apparatus of the first communication scheme, a paging signal including the identification information of the mobile station; receiving,
at the core network apparatus of the first communication
25 scheme, initial information including the identification information of the mobile station from the radio access network apparatus of the first communication scheme;
transmitting, at the core network apparatus of the first communication scheme, the setup information to the radio
30 access network apparatus of the first communication scheme when the identification information of the mobile station

included in the paging signal is same as the identification information of the mobile station included in the initial information, the setup information indicating its relevancy to a start of circuit switched communications.

5 [0022]

A second aspect of the present invention is summarized as a mobile station which can start circuit switched communications when camping on a system of a first communication scheme starts circuit switched communications in a mobile communication system in which there coexist the system of the first communication scheme not capable of supporting circuit switched communications, and a system of a second communication scheme capable of supporting circuit switched communications, including: a first protocol processor unit configured to perform processing related to a first protocol terminated between the mobile station and a core network apparatus of the first communication scheme; a second protocol processor unit configured to perform processing related to a second protocol terminated between the mobile station and the core network apparatus of the second communication scheme; and a third protocol processor unit configured to perform processing related to a third protocol terminated between the mobile station and a radio access network apparatus; wherein the third protocol processor unit is configured to instruct to start the circuit switched communications to the first protocol processor unit when receiving the instruction information which instructs to select a cell in the second communication scheme; the first protocol processor unit is configured to instruct to start the circuit switched communications to the second protocol processor unit when receiving the instruction from the third

protocol processor unit; the third protocol processor unit is configured to select a cell in the second communication scheme when receiving the instruction information; and the second protocol processor unit has receiving the instruction
5 from the first protocol processor unit is configured to set up a link for the circuit switched communications via the cell in the second communication scheme selected by the third protocol processor unit.

[0023]

10 A third aspect of the present invention is summarized as a radio access network apparatus of a first communication scheme used in a mobile communication system in which there coexist a system of the first communication scheme not capable of supporting circuit switched communications, and a system
15 of a second communication scheme capable of supporting circuit switched communications, wherein, when receiving, from the third protocol processor unit, a setup complete response of a radio link between the radio access network apparatus of the first communication scheme and the mobile
20 station as the predetermined information, the radio access network apparatus of the first communication scheme is configured to transmit, to the third protocol processor unit, the instruction information based on identification information of the mobile station and capability information
25 of the mobile station, after acquiring the identification information of the mobile station and capability information of the mobile station from the core network apparatus of the first communication scheme.

[0024]

30 A fourth aspect of the present invention is summarized as a radio access network apparatus of a first communication

scheme used in a mobile communication system in which there
coexist a system of the first communication scheme not capable
of supporting circuit switched communications, and a system
of a second communication scheme capable of supporting
5 circuit switched communications, wherein the radio access
network apparatus of the first communication scheme is
configured to transmit the instruction information to the
third protocol processor unit when receiving the setup
information from the core network apparatus of the first
10 communication scheme as the predetermined information, the
setup information indicating its relevancy to a start of
circuit switched communications.

[0025]

A fifth aspect of the present invention is summarized
15 as a mobile communication including: a system of a first
communication scheme not capable of supporting circuit
switched communications, and a system of a second
communication scheme capable of supporting circuit switched
communications, wherein, the system of the first
20 communication scheme includes: a radio access network
apparatus of the first communication scheme, and a core
network apparatus of the first communication scheme; the
system of the second communication scheme includes: a radio
access network apparatus of the second communication scheme,
25 and a core network apparatus of the second communication
scheme; the mobile station includes: a first protocol
processor unit configured to perform processing related to
a first protocol terminated between the mobile station and
a core network apparatus of the first communication scheme;
30 a second protocol processor unit configured to perform
processing related to a second protocol terminated between

the mobile station and the core network apparatus of the second communication scheme; and a third protocol processor unit configured to perform processing related to a third protocol terminated between the mobile station and the radio access network apparatus of the first communication scheme as well as between the mobile station and the radio access network apparatus of the second communication scheme; the first protocol processor unit is configured to transmit a service request signal to the core network apparatus of the first communication scheme when the mobile station is camping on the system of the first communication scheme, the service request signal including predetermined information which indicates its relevancy to a start of circuit switched communications; the core network apparatus of the first communication scheme is configured to transmit setup information to the radio access network apparatus of the first communication scheme in response to the service request signal transmitted by the first protocol processor unit, the setup information including predetermined information which indicates its relevancy to a start of circuit switched communications; the radio access network apparatus of the first communication scheme is configured to transmit instruction information to the third protocol processor unit in response to the setup information transmitted by the core network apparatus of the first communication scheme, the instruction information instructing to select a cell in the system of the second communication scheme; the third protocol processor unit is configured to select the cell in the system of the second communication scheme in accordance with the instruction information transmitted by the radio access network apparatus of the first communication scheme; and the

second protocol processor unit is configured to set up circuit switched communications via the cell in the system of the second communication scheme selected by the third protocol processor unit.

5 [0026]

In the fifth aspect, the core network apparatus of the first communication scheme can be configured to transmit a paging signal to the mobile station via the radio access network apparatus of the first communication scheme when
10 receiving an incoming signal relevant to circuit switched communications addressed to the mobile station, the paging signal including identification information of the mobile station and predetermined information which indicates its relevancy to a start of circuit switched communications; and
15 the first protocol processor unit can be configured to transmit the service request signal to the core network apparatus of the first communication scheme in response to the paging signal transmitted by the core network apparatus of the first communication scheme when the mobile station
20 is camping on the system of the first communication scheme.
[0027]

In the fifth aspect, the service request signal can be NAS Service Request.

[0028]

25 In the fifth aspect, the radio access network apparatus of the first communication scheme can be configured to transmit the instruction information to the third protocol processor unit using a handover command signal; and the third protocol processor unit can be configured to select a cell
30 in the system of the second communication scheme, the cell being designated with the cell ID included in the instruction

information transmitted by the radio access network apparatus of the first communication scheme using the handover command signal.

[0029]

5 In the sixth aspect, the radio access network apparatus of the first communication scheme can be configured to transmit the instruction information to the third protocol processor unit by using a connection release signal; and the third protocol processor unit can be configured to select
10 the cell in the system of the second communication scheme designated by system information and frequency of a cell including in the instruction information transmitted by the radio access network apparatus of the first communication scheme by using the connection release signal.

15 [0030]

 That is to say, in the sixth aspect, the instruction information instructing to select a cell in the system of the second communication scheme can be RRC Connection Release; and the RRC Connection Release can designate a
20 frequency of the cell in the system of the second communication scheme.

[0031]

 A sixth aspect of the present invention is summarized as a mobile communication method including the steps of:
25 transmitting, at a mobile station, a service request signal to a core network apparatus of a first communication scheme included in a system of the first communication scheme when camping on the system of the first communication scheme not capable of supporting circuit switched communications, the
30 service request signal including predetermined information which indicates its relevancy to a start of circuit switched

communications; transmitting, at the core network apparatus of the first communication scheme, setup information to a radio access network apparatus of the first communication scheme included in the system of the first communication
5 scheme in response to the service request signal transmitted by the mobile station, the setup information including predetermined information which indicates its relevancy to a start of circuit switched communications; transmitting, at the radio access network apparatus of the first
10 communication scheme, instruction information to the mobile station in response to the setup information transmitted by the core network apparatus of the first communication scheme, the instruction information instructing to select a cell in a system of a second communication scheme capable of
15 supporting circuit switched communications; selecting, at the mobile station, the cell in the system of the second communication scheme in accordance with the instruction information transmitted by the radio access network apparatus of the first communication scheme; and setting up,
20 at the mobile station, circuit switched communications via the selected cell in the system of the second communication scheme.

[0032]

A seventh aspect of the present invention is summarized
25 as a mobile station capable of starting circuit switched communications in a mobile communication system including a system of a first communication scheme not capable of supporting circuit switched communications and a system of a second communication scheme capable of supporting circuit
30 switched communications even when the mobile station is camping on the system of the first communication scheme, the

mobile station including: a first protocol processor unit configured to perform processing related to a first protocol terminated between the mobile station and a core network apparatus of the first communication scheme; a second
5 protocol processor unit configured to perform processing related to a second protocol terminated between the mobile station and a core network apparatus of the second communication scheme; and
a third protocol processor unit configured to perform
10 processing related to a third protocol terminated between the mobile station and a radio access network apparatus of the first communication scheme, and between the mobile station and a radio access network apparatus of the second communication scheme, wherein the first protocol processor
15 unit is configured to transmit a service request signal to the core network apparatus of the first communication scheme when the mobile station is camping on the system of the first communication scheme, the service request signal including predetermined information which indicates its relevancy to
20 a start of circuit switched communications; the third protocol processor unit is configured to select a cell in the system of the second communication scheme in accordance with instruction information transmitted by the radio access network apparatus of the first communication scheme, the
25 instruction information instructing to select the cell in the system of the second communication scheme; and the second protocol processor unit is configured to set up circuit switched communications via the cell in the system of the second communication scheme selected by the third protocol
30 processor unit.

[0033]

A eighth aspect of the present invention is summarized as a radio access network apparatus of a first communication scheme not capable of supporting circuit switched communications, the radio access network apparatus including: a function configured to include a service request signal in initial information and to transmit the initial information including the service request signal to a core network apparatus of the first communication scheme when receiving the service request signal from a mobile station that is camping on the system of the first communication scheme, the service request signal including predetermined information which indicates its relevancy to a start of circuit switched communications; and a function configured to transmit instruction information to the mobile station when receiving setup information including predetermined information which indicates its relevancy to a start of circuit switched communications from a core network apparatus of the first communication scheme, the instruction information instructing to select a cell in a system of a second communication scheme capable of supporting circuit switched communications.

[0034]

A ninth aspect of the present invention is summarized as a core network apparatus of a first communication scheme not capable of supporting circuit switched communications, the core network apparatus including: a function configured to transmit setup information to a radio access network apparatus of the first communication scheme when receiving initial information including predetermined information which indicates its relevancy to a start of circuit switched communications of a mobile station from the radio access

network apparatus of the first communication scheme, the setup information including capability information of the mobile station and the initial information including the predetermined information which indicates its relevancy to a start of circuit switched communications.

[0035]

In the ninth aspect, the core network apparatus can be configured to transmit a paging signal to the mobile station via the radio access network apparatus of the first communication scheme when receiving an incoming signal relevant to circuit switched communications for the mobile station, the paging signal including identification information of the mobile station and predetermined information which indicates its relevancy to a start of circuit switched communications.

Advantageous Effects of Invention

[0036]

As described above, the present invention can provide a mobile communication method, a mobile station, and a radio access network apparatus that allows circuit switched communications (for both transmission and reception) even when the mobile station UE is camping on a system of the LTE scheme.

25

Brief Description of the Drawings

[0037]

[Fig. 1] Fig. 1 is an entire configuration diagram of a mobile communication system according to a first embodiment of the present invention.

[Fig. 2] Fig. 2 is a diagram showing a protocol

configuration of a mobile station according to the first embodiment of the present invention.

[Fig. 3] Fig. 3 is a sequence diagram showing operations at the time of transmission and reception in the mobile communication system according to the first embodiment of the present invention.

[Fig. 4] Fig. 4 is a sequence diagram showing operations at the time of transmission and reception in a mobile communication system according to a second embodiment of the present invention.

[Fig. 5] Fig. 5 is a sequence diagram showing operations at the time of transmission and reception in a conventional mobile communication system.

Best Modes for Carrying out the Invention

[0038]

(Configuration of Mobile Communication System according to First Embodiment of the Present Invention)

Referring to Figs. 1 and 2, a configuration of a mobile communication system according to a first embodiment of the present invention is described.

[0039]

As shown in Fig. 1, in the mobile communication system according to the present embodiment, there coexist a system of the LTE scheme (a first communication scheme) not capable of supporting circuit switched communications, and a system of the WCDMA/GSM (a second communication scheme) capable of supporting circuit switched communications.

[0040]

Specifically, the system of the LTE scheme (the first communication scheme) includes an exchange MME (core network

apparatus of the first communication scheme), and a radio base station eNB (radio access network apparatus of the first communication scheme).

[0041]

5 The system of the WCDMA/GSM (the second communication scheme) includes an exchange MSC for circuit switched communications (a core network apparatus of the second communication scheme), an exchange SGSN for packet communications (a core network apparatus of the second communication scheme), a radio control apparatus RNC/BSC (a radio access network apparatus of the second communication scheme), and a radio base station NodeB/BTS (a radio access network apparatus of the second communication scheme).

[0042]

15 As shown in Fig. 2, the mobile station UE includes a function EMM (a first protocol processor) that performs processing related to an EMM protocol (a first protocol) terminated between the mobile station UE and the exchange MME (core network apparatus of the first communication scheme), a function MM (a second protocol processor) that performs processing related to an MM protocol (a second protocol) terminated between the mobile station UE and the exchange MSC/SGSN (core network apparatus of the second communication scheme), and a function AS (a third protocol processor) that performs processing related to an AS protocol (a third protocol) terminated between the mobile station UE and the radio base station eNB/radio control apparatus RNC/BSC (radio access network apparatus).

[0043]

30 The AS protocol is originally classified into three AS protocols: a first AS protocol to be terminated between the

mobile station UE and the radio base station eNB; a second AS protocol to be terminated between the mobile station UE and the radio control apparatus RNC (radio control apparatus in WCDMA); and a third AS protocol to be terminated between
5 the mobile station UE and the radio control apparatus BSC (radio control apparatus in GSM). These protocols are independent of each other.

[0044]

For convenience, these three protocols are
10 collectively referred to as "AS protocol" herein; however, in particular, the function to perform "cell selection of the second communication scheme" in the following embodiments is achieved by the second AS protocol or the third AS protocol according to the second communication scheme (the
15 WCDMA scheme or the GSM system).

[0045]

Other functions in the following embodiments are all achieved by the first AS protocols.

[0046]

20 (Operations of Mobile Communication System according to First Embodiment of the Present Invention)

Referring to Fig. 3, operations of the mobile communication system according to the first embodiment of the present invention is described.

25 [0047]

As shown in Fig. 3, in step S1000, the mobile station UE performs location registration processing (Attach/TAU) to the exchange MME of the LTE scheme, and the exchange MSC of the WCDMA/GSM scheme. The mobile station UE, after
30 performing such location registration processing in step S1000, is camping on a system of the LTE scheme.

[0048]

In step S1001A, an application function AP of the mobile station UE transmits "Primitive" to the function EMM performing processing related to the EMM protocol, in response to a calling operation by a user.

[0049]

Alternatively, the exchange MSC of the WCDMA/GSM scheme transmits, to the exchange MME of the LTE scheme, "Paging (paging signal)" addressed to the mobile station UE in step S1001B, and also transmits, to the radio control apparatus RNC/BSC of the WCDMA/GSM system, the "Paging (paging signal)" addressed to the mobile station UE in step S1001C.

[0050]

The exchange MME of the LTE scheme transmits, to the radio base station eNB of the LTE scheme, "S1 Paging (paging signal)" addressed to the mobile station UE in step S1001D, and also transmits, to the mobile station UE, the "Paging (paging signal)" addressed to the mobile station UE in step S1001E.

[0051]

The "Paging (paging signal)" of step S1001E is transmitted after being included in the "S1 Paging (paging signal)" of step S1001D.

[0052]

Consequently, in step S1002, the function EMM transmits "Primitive" to the function AS performing processing related to the AS protocol.

[0053]

In step S1002A, the function AS transmits "RRC Connection Request" to the radio base station eNB.

[0054]

Here, the "RRC Connection Request" includes "S-TMSI (SAE-Temporary Mobile Subscriber Identity)" which is identification information of the mobile station UE.

[0055]

5 In step S1003, the radio base station eNB transmits "RRC Connection Setup" to the function AS.

[0056]

In step S1004, the function AS transmits "RRC Connection Setup Complete" to the radio base station eNB.

10 [0057]

Here, the "RRC Connection Setup Complete (setup information)" is assumed to include information "CSFB (Circuit Switch FallBack)" which indicates its relevancy to a start of circuit switched communications.

15 [0058]

In step S1005, the radio base station eNB transmits "S1 UE Capability Request" including the "S-TMSI" included in the "RRC Connection Request" to the exchange MME.

[0059]

20 In step S1006, the exchange MME extracts the "S-TMSI" from the "S1 UE Capability Request", and notifies, to the radio base station eNB, the "capability information of mobile station (UE Capability)" identified by the extracted "S-TMSI" by "S1 UE Capability Transfer".

25 [0060]

In step S1008, the radio base station eNB transmits "S1 UE Capability Transfer Complete" to the exchange MME.

[0061]

30 In step S1007, the radio base station eNB makes a reference to the "capability information of mobile station (UE Capability)" included in the "S1 UE Capability Transfer"

to determine that target communication scheme to be used by the mobile station UE to perform circuit switched communications is the WCDMA or GSM system (the second communication scheme), and transmits "RRC HO from EUTRA" or
5 "RRC Connection Release" to the mobile station UE.

[0062]

Here, the "Redirection Information" is included in the "RRC HO from EUTRA" or the "RRC Connection Release".

[0063]

10 The "Redirection Information" is instruction information that instructs to selection of the WCDMA/GSM (the second communication scheme).

[0064]

In addition, the "Redirection Information" may include
15 the frequency of the second communication scheme, the cell ID, and system information of the cell.

[0065]

Further, the "Redirection Information" may include information "CSFB" which indicates its relevancy to a start
20 of circuit switched communications.

[0066]

That is, when the radio base station eNB receives the "RRC Connection Setup Complete" as predetermined information from the function AS, the radio base station eNB, after
25 acquiring the "UE Capability (capability information of mobile station)" from the exchange MME, transmits the "Redirection Information (instruction information)" to the function AS based on the acquired "UE Capability (capability information of mobile station)". The "RRC Connection Setup
30 Complete" is a setup complete response of a radio link (RRC link) between the radio base station eNB and the mobile

station UE

[0067]

In step S1009, the function AS, when receiving the "RRC
HO from EUTRA" or the "RRC Connection Release", transmits
5 "Primitive" for instructing to start circuit switched
communications to the function EMM.

[0068]

In step S1010, the function EMM transmits "Primitive"
for instructing to start circuit switched communications to
10 the function MM.

[0069]

In step S1011, the function AS, when receiving the
"Redirection Information", selects the cell of the WCDMA/GSM
scheme (the second communication scheme).

15 [0070]

In step S1012, the function MM sets up a link for circuit
switched (CS) communications via the cell of the WCDMA/GSM
scheme selected by the function AS, and in step S1013,
"U-Plane" is established to communicate between the mobile
20 station UE and the exchange MSC.

[0071]

(Operations and Effects of Mobile Communication System
according to First Embodiment of the Present Invention)

According to the mobile communication system according
25 to the first embodiment of the present invention, when a
paging signal for circuit switched communications is
transmitted to a mobile station UE camping on a system of
the LTE scheme, and the mobile station UE calls circuit
switched communications, the mobile station UE can be
30 instructed to forcibly start circuit switched communications
in a system of the WCDMA/GSM scheme. Thus, even when the

mobile station UE is camping on the system of the LTE scheme, circuit switched communications may be performed (for both transmission and reception).

[0072]

5 According to the mobile communication system of the first embodiment of the present invention, less time is required to start communications compared with the case where S1 connection is established between the radio base station eNB and the exchange MME.

10 [0073]

(Mobile Communication System according to Second Embodiment of the Present Invention)

 In the following, referring to Fig. 4, a mobile communication system according to a second embodiment of the present invention is described by focusing on its difference from the above-mentioned mobile communication system according to the first embodiment.

[0074]

 As shown in Fig. 4, operations in steps S2001 to S2004 are the same as those in steps S1001 to S1003 shown in Fig. 3.

[0075]

 In steps S2005 to S2007, the function EMM transmits "NAS Service Request" to the function AS. The function AS includes the received "NAS Service Request" in the "RRC Connection Setup Complete", and transmits the "RRC Connection Setup Complete" to the radio base station eNB. The radio base station eNB extracts "S-TMSI (identification information of the mobile station UE)" from the received "RRC Connection Request", and also extracts the "NAS Service Request" from the received "RRC Connection Setup Complete".

The radio base station eNB includes the extracted "S-TMSI" and "NAS Service Request" in "S1 Initial UE Message (initial information)", and transmits the "S1 Initial UE Message" to the exchange MME.

5 [0076]

Here, the "NAS Service Request (service request for the first protocol)" is assumed to include information "CSFB" which indicates its relevancy to a start of circuit switched communications.

10 [0077]

In step S2008, the exchange MME transmits "S1 Initial UE Context Setup (setup information)" including "UE capability (capability information of mobile station)" to the radio base station eNB.

15 [0078]

Here, the "S1 Initial UE Context Setup (setup information)" includes information "CSFB" which indicates its relevancy to a start of circuit switched communications.

[0079]

20 The exchange MME is configured to transmit the "S1 Initial UE Context Setup" including the "UE capability (capability information of mobile station)" to the radio base station eNB in step S2008, in the case where information "CSFB" is not included in the "NAS Service Request (service request for the first protocol)", and the "S-TMSI (identification information of mobile station UE)" included in the "Paging (paging signal)" in step S2001B is same as the "S-TMSI" extracted from identification information of the mobile station UE included in the "S1 Initial UE Message (initial information)".

30

[0080]

In step S2009, the radio base station eNB makes a reference to the "the capability information (UE Capability) of a mobile station" included in the "S1 Initial UE Context Setup", and transmits "Redirection Information" such as "RRC
5 HO from EUTRA" or "RRC Connection Release" to the mobile station UE.

[0081]

In step S2010, the function EMM, when receiving the "Redirection Information", transmits "Primitive" for
10 instructing to start circuit switched communications to the function EMM.

[0082]

In step S2011, the function EMM transmits "Primitive" for instructing to start circuit switched communications to
15 the function MM.

[0083]

In step S2012, the function AS, when receiving the "Redirection Information", selects the cell of the WCDMA/GSM scheme (the second communication scheme).

20 [0084]

In step S2013, the radio base station eNB transmits "S1 Setup Complete" to the exchange MME. In step S2014, the exchange MME transmits "S1 Release" to the radio base station eNB. In step S2015, the radio base station eNB transmits "S1
25 Release Complete" to the exchange MME.

[0085]

In step S2016, the function MM sets up a link for circuit switched (CS) communications via the cell of the WCDMA/GSM scheme (the second communication scheme) selected by the
30 function AS, and in step S2017, "U-Plane" is established to communicate between the mobile station UE and the exchange

MSC.

[0086]

The present embodiment is described by focusing on a procedure followed by the mobile station UE in an Idle state to perform transmission and reception; however, the present invention may be applied to a case where the mobile station is already in a Connected state in the first communication scheme.

[0087]

10 In such a case, the "RRC Connection Request" and the "RRC Connection Setup" may be omitted, and the "RRC Connection Setup Complete" may be replaced by other message.

[0088]

Note that operation of the above described mobile station UE, the radio base station eNB, and the exchange MME may be implemented by means of hardware, a software module executed by a processor, or a combination of both.

[0089]

The software module may be provided in any type of storage medium such as an RAM (Random Access Memory), a flash memory, a ROM (Read Only Memory), an EPROM (Erasable Programmable ROM), an EEPROM (Electrically Erasable and Programmable ROM), a register, a hard disk, a removable disk, or a CD-ROM.

25 [0090]

The storage medium is connected to the processor so that the processor can read and write information from and to the storage medium. Also, the storage medium may be integrated into the processor. Also, the storage medium and the processor may be provided in an ASIC. The ASIC may be provided in the mobile station UE, the radio base station eNB, and

the exchange MME. Also, the storage medium and the processor may be provided in the mobile station UE, the radio base station eNB, and the exchange MME as a discrete component.
[0091]

5 Hereinabove, the present invention has been described in detail using the above embodiment; however, it is apparent to those skilled in the art that the present invention is not limited to the embodiment described herein. Modifications and variations of the present invention can
10 be made without departing from the spirit and scope of the present invention defined by the description of the scope of claims. Thus, what is described herein is for illustrative purpose, and has no intention whatsoever to limit the present invention.

Claims

- [1] A mobile communication system comprising: a system of a first communication scheme not capable of supporting circuit switched communications, a system of a second communication scheme capable of supporting circuit switched communications, and a mobile station capable of communicating with each of the first communication system and the second communication system, wherein:
- 10 the system of the first communication scheme includes:
- a radio access network apparatus of the first communication scheme, and
- a core network apparatus of the first communication scheme;
- 15 the system of the second communication scheme includes:
- a radio access network apparatus of the second communication scheme, and
- a core network apparatus of the second communication scheme;
- 20 the mobile station includes:
- a first protocol processor unit configured to perform processing related to a first protocol terminated between the mobile station and the core network apparatus of the first communication scheme,
- 25 a second protocol processor unit configured to perform processing related to a second protocol terminated between the mobile station and the core network apparatus of the second communication scheme, and
- a third protocol processor unit configured to
- 30 perform processing related to a third protocol terminated between the mobile station and the radio access network

apparatus of the first communication scheme as well as between the mobile station and the radio access network apparatus of the second communication scheme;

the first protocol processor unit is configured to
5 transmit a service request signal to the core network apparatus of the first communication scheme when the mobile station is camping on the system of the first communication scheme, the service request signal including predetermined information which indicates its relevancy to a start of
10 circuit switched communications;

the core network apparatus of the first communication scheme is configured to transmit setup information to the radio access network apparatus of the first communication scheme in response to the service request signal transmitted
15 by the first protocol processor unit, the setup information including predetermined information which indicates its relevancy to a start of circuit switched communications;

the radio access network apparatus of the first communication scheme is configured to transmit instruction
20 information to the third protocol processor unit in response to the setup information transmitted by the core network apparatus of the first communication scheme, the instruction information instructing to select a cell in the system of the second communication scheme;

25 the third protocol processor unit is configured to select the cell in the system of the second communication scheme in accordance with the instruction information transmitted by the radio access network apparatus of the first communication scheme; and

30 the second protocol processor unit is configured to set up circuit switched communications via the cell in the system

of the second communication scheme selected by the third protocol processor unit.

[2] The mobile communication system according to claim 1,
5 wherein

the core network apparatus of the first communication scheme is configured to transmit a paging signal to the mobile station via the radio access network apparatus of the first communication scheme when receiving an incoming signal
10 relevant to circuit switched communications addressed to the mobile station, the paging signal including identification information of the mobile station and predetermined information which indicates its relevancy to a start of circuit switched communications; and

15 the first protocol processor unit is configured to transmit the service request signal to the core network apparatus of the first communication scheme in response to the paging signal transmitted by the core network apparatus of the first communication scheme when the mobile station
20 is camping on the system of the first communication scheme.

[3] The mobile communication system according to claim 1, wherein the service request signal is NAS Service Request.

25 [4] The mobile communication system according to claim 1, wherein

the radio access network apparatus of the first communication scheme is configured to transmit the instruction information to the third protocol processor unit
30 using a handover command signal; and

the third protocol processor unit is configured to

select a cell in the system of the second communication scheme,
the cell being designated with the cell ID included in the
instruction information transmitted by the radio access
network apparatus of the first communication scheme using
5 the handover command signal.

[5] The mobile communication system according to claim 1,
wherein

the instruction information instructing to select a
10 cell in the system of the second communication scheme is RRC
Connection Release; and

the RRC Connection Release designates a frequency of
the cell in the system of the second communication scheme.

15 [6] A mobile communication method comprising the steps of:
transmitting, at a mobile station, a service request
signal to a core network apparatus of a first communication
scheme included in a system of the first communication scheme
when camping on the system of the first communication scheme
20 not capable of supporting circuit switched communications,
the service request signal including predetermined
information which indicates its relevancy to a start of
circuit switched communications;

transmitting, at the core network apparatus of the
25 first communication scheme, setup information to a radio
access network apparatus of the first communication scheme
included in the system of the first communication scheme in
response to the service request signal transmitted by the
mobile station, the setup information including
30 predetermined information which indicates its relevancy to
a start of circuit switched communications;

transmitting, at the radio access network apparatus of the first communication scheme, instruction information to the mobile station in response to the setup information transmitted by the core network apparatus of the first communication scheme, the instruction information instructing to select a cell in a system of a second communication scheme capable of supporting circuit switched communications;

selecting, at the mobile station, the cell in the system of the second communication scheme in accordance with the instruction information transmitted by the radio access network apparatus of the first communication scheme; and

setting up, at the mobile station, circuit switched communications via the selected cell in the system of the second communication scheme.

[7] A mobile station capable of starting circuit switched communications in a mobile communication system including a system of a first communication scheme not capable of supporting circuit switched communications and a system of a second communication scheme capable of supporting circuit switched communications even when the mobile station is camping on the system of the first communication scheme, the mobile station comprising:

a first protocol processor unit configured to perform processing related to a first protocol terminated between the mobile station and a core network apparatus of the first communication scheme;

a second protocol processor unit configured to perform processing related to a second protocol terminated between the mobile station and a core network apparatus of the second

communication scheme; and

a third protocol processor unit configured to perform processing related to a third protocol terminated between the mobile station and a radio access network apparatus of the first communication scheme, and between the mobile station and a radio access network apparatus of the second communication scheme, wherein

the first protocol processor unit is configured to transmit a service request signal to the core network apparatus of the first communication scheme when the mobile station is camping on the system of the first communication scheme, the service request signal including predetermined information which indicates its relevancy to a start of circuit switched communications;

the third protocol processor unit is configured to select a cell in the system of the second communication scheme in accordance with instruction information transmitted by the radio access network apparatus of the first communication scheme, the instruction information instructing to select the cell in the system of the second communication scheme; and

the second protocol processor unit is configured to set up circuit switched communications via the cell in the system of the second communication scheme selected by the third protocol processor unit.

[8] A radio access network apparatus of a first communication scheme not capable of supporting circuit switched communications, the radio access network apparatus comprising:

a function configured to include a service request

signal in initial information and to transmit the initial information including the service request signal to a core network apparatus of the first communication scheme when receiving the service request signal from a mobile station
5 that is camping on the system of the first communication scheme, the service request signal including predetermined information which indicates its relevancy to a start of circuit switched communications; and
a function configured to transmit instruction
10 information to the mobile station when receiving setup information including predetermined information which indicates its relevancy to a start of circuit switched communications from a core network apparatus of the first communication scheme, the instruction information
15 instructing to select a cell in a system of a second communication scheme capable of supporting circuit switched communications.

[9] A core network apparatus of a first communication
20 scheme not capable of supporting circuit switched communications, the core network apparatus comprising:

a function configured to transmit setup information to a radio access network apparatus of the first communication scheme when receiving initial information including
25 predetermined information which indicates its relevancy to a start of circuit switched communications of a mobile station from the radio access network apparatus of the first communication scheme, the setup information including capability information of the mobile station and the initial
30 information including the predetermined information which indicates its relevancy to a start of circuit switched

communications.

[10] The core network apparatus according to claim 9,
wherein

5 the core network apparatus is configured to transmit
a paging signal to the mobile station via the radio access
network apparatus of the first communication scheme when
receiving an incoming signal relevant to circuit switched
communications for the mobile station, the paging signal
10 including identification information of the mobile station
and predetermined information which indicates its relevancy
to a start of circuit switched communications.