

## DESCRIPTION

## IMAGE DATA PROCESSING SYSTEM

5

## Technical Field

The entire contents of Japanese Patent Application No. 8-346201 filed on December 25, 1996 are incorporated herein by reference.

10

## Background Art

Recently, digital cameras (electronic cameras) for electrically storing photographed images instead of using films have been widely used. In such a digital camera, when the shutter release is depressed to issue an instruction of fetching an image of a subject, the image is electrically fetched by use of a solid state imaging device such as a CCD, the fetched image is compressed by the compression processing technique such as JPEG, and the compressed still image is stored in a solid state memory such as a flash memory.

20

The digital camera has a function of permitting a photographed image to be recognized on the spot and is excellent in quick adaptability in comparison with a conventional camera which uses a film for photographing and in which the photographed image cannot be observed until it is developed and printed.

25

Further, recently, a device obtained by attaching the above digital camera function to a device having a

PDA (Personal Digital Assistant) function such as a personal digital assistant is also commercialized and it is possible to transmit photographed image data to another place via a telephone line.

5           However, in the digital camera with the image data transmitting function, the photographed data is transmitted to a personal computer at user's home and then the image data is processed by use of the personal computer, but since the image data processing is  
10           largely dependent on the image data processing capability of the personal computer, an added value of image data purposely photographed cannot be fully utilized in some cases.

#### Disclosure of Invention

15           An object of this invention is to provide an image data processing system capable of utilizing the function of transmitting photographed image data and permitting anybody to fully utilize the added value of the image data.

20           According to a first aspect of this invention, an image data processing system comprises a photographing unit including photographing means for photographing a subject to create image data; and transmission means for transmitting the image data via a communication  
25           line; and a center unit including reception means for receiving image data transmitted from the photographing unit via the communication line; storage means for

storing image data received by the reception means;  
editing means for editing image data stored in the  
storage means; and output means for outputting image  
data edited by the editing means.

5           According to a second aspect of this invention, an  
image data processing device comprises communication  
means for transmitting and receiving data with respect  
to a terminal unit connected to a network; storage  
means for storing image data received via the  
10 communication means; editing means for editing image  
data stored in the storage means; and output means for  
outputting image data edited by the editing means.

          According to this invention, the image data  
processing system receives and stores photographed  
15 image data from a terminal unit such as a PDA connected  
via the network. After the stored image data is edited  
according to a request, the image data is output to an  
output unit such as a printer.

          Therefore, the image data and the like created in  
20 the photographing unit can be edited according to an  
output format which the user desires and output in a  
preset output format, thus the output format is not  
influenced by the function of the terminal unit of the  
user unlike the conventional case, and the added value  
25 of photographed image data can be fully utilized.

          Further, for example, when the user makes a  
journey and if the user previously transmits

photographed image data and the like to a center  
(having a center unit) near the user's home and  
designates an output in a desired output format, it  
becomes possible for the user to drop in the center on  
5 the way home from the journey and take an output  
material (for example, album) home, and thus it becomes  
unnecessary for the user to edit the image data and the  
like by himself, it becomes convenient and the user can  
immediately see the output result.

10 Further, since the image data and the like  
photographed by the photographing unit can be  
transmitted to the terminal unit and reedited after  
they were edited by the center unit, for example, the  
user can remove unnecessary image data, or change or  
15 add text information such as a comment or title by use  
of a terminal unit provided at his home or the like and  
he can edit the photographed image data to his  
satisfaction.

Further, according to this invention, noted places,  
20 buildings, place names and the like are stored in  
connection with position data in a data base on the  
server side. Therefore, it becomes possible to receive  
information of position and information of azimuth  
measured by use of a GPS or azimuth sensor provided in  
25 the PDA together with photographing data and display  
information (noted place, building, place name and the  
like) associated with the photographing place based on

corresponding information of photographing position, photographing azimuth and the like by referring to the data base. Therefore, an album with large added value can be made.

5

#### Brief Description of Drawings

FIG. 1 is a system block diagram of an image data processing system according to an embodiment of this invention;

10

FIG. 2 is a block diagram showing the construction of a main portion of a PDA 2;

FIG. 3 is a block diagram showing the construction of a main portion of an image data processing unit 3;

FIG. 4 is a block diagram showing the construction of a main portion of a personal computer 4;

15

FIG. 5 is a flowchart showing the content of a process for photographing a subject in the PDA 2;

FIG. 6 is a flowchart showing the content of a comment input process in the PDA 2;

20

FIG. 7 is a flowchart showing the content of a data transmission process for transmitting data from the PDA 2 to the image data processing unit 3;

FIG. 8 is a flowchart showing the content of an image data process in the image data processing unit 3;

25

FIG. 9 is a flowchart showing the contents of communication and editing processes for image data and the like effected by the personal computer 4 and image data processing unit 3;

FIG. 10 is a flowchart showing the content of an album data communication processes effected by the personal computer 4 and image data processing unit 3;

FIG. 11 is a diagram showing the memory  
5 configuration of a data storage unit 34 of the image data processing unit 3;

FIG. 12 is a diagram showing the data memory configuration of the data storage unit 34 of the image data processing unit 3;

10 FIGS. 13A and 13B are diagrams schematically showing one format of output result of image data and the like by an image data processing system 1;

FIG. 14 is a system block diagram of an image processing unit according to another embodiment of this  
15 invention;

FIG. 15 is a system block diagram showing a PDA shown in FIG. 14;

FIG. 16 is a diagram showing the memory configuration of a server in the embodiment shown in  
20 FIG. 14;

FIGS. 17 and 18 are diagrams showing the internal configuration of a data base shown in FIG. 14;

FIG. 19 is a flowchart showing the reception process of the server in the above embodiment of this  
25 invention;

FIG. 20 is a flowchart showing the content of a process which the server executes in response to

various requests from the PC in the above embodiment of this invention;

FIG. 21 is a flowchart showing a process effected when the PC issues various requests to the server in the above embodiment of this invention; and

FIGS. 22A to 22C are diagrams showing screen display examples of image data and related information thereof in the PC.

#### Best Mode of Carrying Out the Invention

There will now be described an embodiment of an image data processing system according to this invention in detail with reference to FIGS. 1 to 22C.

First, the construction is explained.

FIG. 1 is a system block diagram of an image data processing system according to an embodiment of this invention.

In FIG. 1, an image data processing system 1 is constructed by a PDA (Personal Digital Assistant) 2 used as a photographing unit, an image data processing unit 3 used as a center unit, a personal computer 4 used as a terminal unit and the like and the above portions are connected via a communication line a. Further, a printer 5 is connected to the image data processing unit 3.

FIGS. 2 and 3 are block diagrams respectively showing the constructions of the main portions of the PDA 2 and image data processing unit 3.

As shown in FIG. 2, the PDA 2 is constructed by a CPU (Central Processing Unit) 11, image input unit 12, display unit 13, input unit 14, vertical/horizontal sensor 15, communication unit 16, RAM (Random Access Memory) 17, ROM (Read Only Memory) 18, memory 19, timer 20, GPS (Global Positioning System) measuring unit 21, counter 22 and others and the above portions are connected via a bus 23.

The CPU 11 effects operation processes necessary for various operations corresponding to an input via the input unit 14 with respect to the RAM 17 according to various control programs stored in the ROM 18 and creates and outputs various control signals for controlling the respective portions of the PDA 2 based on the operation processes.

The image input unit 12 is constructed by a CCD (Charge Coupled Device), lens, A/D converter, driving circuit, timing generator and others although they are not shown in the drawing, and it receives light of the image of a subject formed by the lens in the CCD, stores charges of an amount proportional to the amount of received light in each of transfer electrodes arranged on the light receiving surface of the CCD and sequentially converts the stored charges stored in each of the transfer electrodes treated as an electrical signal (analog signal) into digital image data for each electrode in response to a driving signal supplied from

the driving circuit in the A/D converter.

The display unit 13 is constructed by a liquid crystal display panel or the like to display an image based on photographed image data and display the content of a command input from the CPU 11 or a comment or title input via the input unit 14.

Although not shown in the drawing, the input unit 14 is a unit for outputting a depression signal to the CPU 11 when a key on a keyboard having a cursor key, numeral input keys, various function keys and the like is depressed and it is used to input a title and comment for image data and determine the output format. Further, the input unit 14 may be of a so-called tablet type which has a transparent position detecting tablet superposed on a liquid crystal display (not shown) and detects the XY coordinate of a pressurized point by contact of a finger tip based on a pressure-sensitive system and outputs the same to the CPU 11.

The vertical/horizontal sensor 15 is a sensor for detecting whether the photograph is taken with the PDA 2 set in the horizontal position or in the vertical position and the PDA 2 has a pendulum provided therein to detect the position based on the rotation of the pendulum.

The communication unit 16 has a function of executing the communication protocol for transmitting and receiving image data and the like with respect to

the image data processing unit 3 or terminal unit 4 via the communication line a and has a terminal which can be connected to the communication line a.

5 The RAM 17 has a storage area for temporarily storing image data and the like and a work area for the CPU 11 and data can be rewritten according to the input via the input unit 14.

10 The ROM 18 stores various control programs (for example, part of the programs shown in the flowcharts of FIGS. 5 to 7, and FIGS. 9, 10) executed in the PDA 2 and data and the like used in the program processing.

15 The memory 19 is a unit for storing photographed image data. The memory 19 has a storage medium 19a in which programs, data and others are previously stored and the storage medium 19a is formed of a magnetic, optical storage medium or semiconductor memory. The storage medium 19a includes a medium fixedly provided in the memory 19 or a medium which can be removably  
20 mounted. The program, data and others to be stored in the storage medium 19a may be supplied from another device connected via the communication line and stored therein.

25 The timer 20 has a time counting function, counts the photographing time and outputs time data to the CPU 11.

The GPS (Global Positioning System) measuring

unit 21 has a function of measuring a place at which the user took a photograph of image data, specifies the place at which the image data was photographed based on a difference between the arrival times of radio waves transmitted to a plurality of artificial satellites (for example, four or more satellites) from a control station on the ground and the arrival times of radio waves transmitted from the artificial satellites to the PDA 2 and outputs the coordinate data of the place, place name and others to the CPU 11.

Although not shown in the drawing, the counter 22 is constructed by a counter and the like, counts the number of photographs taken after preset photographing start time and outputs the obtained result to the CPU 11.

The PDA 2 transmits image data, data of time at which the image data was photographed, GPS data, vertical/horizontal data, number-of-images data, comment, title and a command signal of a desired output format to the image data processing unit 3 according to a transmission command by the user.

FIG. 3 is a block diagram showing the construction of the main portion of the image data processing unit 3 in the above embodiment to which this invention is applied.

The image data processing unit 3 shown in FIG. 3 has a CPU 31, RAM 32, program memory 33, data storage

unit 34, communication unit 35 and others provided therein.

The CPU 31 fetches image data and related data (image data and the like) thereof stored in the data storage unit 34 and subjects the image data to the editing process, and stores the result of the process into the data storage unit 34 again or outputs the same to the printer 5 or the like according to various control programs stored in the program memory 33.

The RAM 32 forms a work area used for the image data editing process executed by the CPU 31.

The program memory 33 has a storage medium 33a in which a program (for example, a program shown in FIG. 8), data and others are previously stored and the storage medium is formed of a magnetic, optical storage medium or semiconductor memory. The storage medium 33a includes a medium fixedly provided in the memory 19 or a medium which can be removably mounted. Further, in order to obtain the program, data and others stored in the storage medium 33a, it is possible to provide a memory having the above storage medium on another device side connected via the communication line a and use the program and data stored in the storage medium 33a via the communication line a.

The data storage unit 34 is constructed by a format memory 34a, data memory 34b, album memory 34c and others as shown in FIG. 11 and image data and data

related to the image data transmitted from the PDA 2 or image data obtained after editing and data related to the image data are stored therein.

5 The communication unit 35 is connected to the PDA 2 or personal computer 4 via the communication line a (for example, telephone line) and has a communicating function of executing the communication protocol for transmitting and receiving image data and the like via the communication line a.

10 The image data processing unit 3 receives image data received from the PDA 2 and data related thereto or a command signal of output format at the communication unit 35 and stores the received image data and the like in the data storage unit 34. Then,  
15 it fetches image data and the like from the data storage unit 34 via the CPU 31 based on the command signal of output format, subjects the image data and the like to the editing process, and outputs the result of the process to the personal computer 4 or printer 5.  
20 Further, the image data processing unit 3 receives image data reedited in the personal computer 4 and image data-related information and stores them into the data storage unit 34.

25 FIG. 4 is a block diagram showing the construction of the main portion of the personal computer 4 in the above embodiment to which this invention is applied.

The personal computer 4 shown in FIG. 4 is

constructed by a CPU 41, RAM 42, ROM 43, hard disk 44, keyboard 45, display unit 46, communication unit 47, audio output unit 48 and others.

5 The CPU 41 fetches image data and image data-related information stored in the hard disk 44, subjects them to the image data editing process, and stores the result of the process into the hard disk 44 again or outputs the same to the image data processing unit 3 according to various control programs stored in  
10 the ROM 43. Further, the CPU 41 also effects the control operation to convert the image data-related information into an audio signal.

The RAM 42 forms a work area for the image data editing process effected by the CPU 41.

15 Various control programs necessary for editing image data are stored in the ROM 43.

In the hard disk 44, image data transmitted from the PDA 2 and data related to the image data, or image data obtained after editing and data related to the  
20 image data are stored.

Although not shown in the drawing, the keyboard 45 is a unit for outputting a depression signal to the CPU 41 when a key on a keyboard having a cursor key, numeral input keys, various function keys and the like  
25 is depressed and it is used to input a title and comment for image data and determine the output format.

The display unit 46 is constructed by a CRT

(Cathode Ray Tube) or the like and displays an image display signal input via the CPU 41 in a specified color.

5       The communication unit 47 is connected to the PDA 2 or image data processing unit 3 via the communication line a (for example, telephone line) and has a communicating function of executing the communication protocol for transmitting or receiving image data via the communication line a.

10       The audio output unit 48 is constructed by a speaker which is not shown or the like and outputs image data-related information which is converted into an audio output as a voice.

15       The personal computer 4 fetches image data edited in the image data processing unit 3 or the like via the communication line a by use of the communication unit 47, displays the fetched image data and the like on the display screen of the display unit 46, reedits the image data and the like and outputs the image data to the image data processing unit 3 again. At this  
20       time, the output format can also be determined.

      The printer 5 is connected to the image data processing unit 3 and outputs the edited image data and the like in a preset format.

25       Next, the operation is explained.

      FIG. 5 is a flowchart showing the content of a process for photographing a subject in the PDA 2.

When a key of the input unit 14 which corresponds to the shutter release of a camera is depressed, the photographing process is started. In the step S1, image data of a photographed subject is created in the image input unit 12 and the image data is stored into the memory 19.

In the step S2, a process for reading the time at the image data creation time from the timer 20 and storing the time data into the memory 19 is effected.

In the step S3, the measuring place (the coordinate indicating the north latitude and the east longitude) at the image data creation time is read from the GPS measuring unit 21 and the GPS data is stored into the memory 19.

In the step S4, information that the photographed image data is a vertical type or horizontal type is read from the vertical/horizontal sensor 15 and the vertical/horizontal data is stored into the memory 19.

In the step S5, the number of the photographed image data counted from the preset photographing start time is read from the counter 22 and the number-of-images data is stored in the memory 19, and then the present photographing process is completed.

FIG. 6 is a flowchart showing the content of the comment input process in the PDA 2.

In the comment input process, a process for reading out photographed image data from the memory 19

is effected in the step S11.

In the step S12, a comment for the fetched image data is input by use of a keyboard (not shown) of the input unit 14.

5 In the step S13, a category (for example, which is used for grouping the same type of data) according to the user's request for the fetched image data.

In the step S14, a process for storing the input comment and category in correspondence to the readout  
10 image data into the memory 19 is effected and the present comment input process is terminated.

FIG. 7 is a flowchart showing the content of a data transmission process for transmitting data from the PDA 2 to the image data processing unit 3.

15 The PDA 2 can transmit a photographed image and transmit an output request of the image to the image data processing unit. In the data transmission process, whether an output request for requesting the image data processing unit 3 to output data is present or not is  
20 determined in the step S21, and if it is detected as the result of the above determination that the output request is present, an output request signal is transmitted (step S23) from the communication unit 16 of the PDA 2 to the communication unit 35 of the image  
25 data processing unit 3 after the output format designating process (step S22) is effected, and then the present data transmission process is terminated,

and if it is detected as the result of the above determination in the step S21 that no output request is present, the step S24 is effected.

5 In the step S24, whether a data transmission command is present or not is determined, and if it is detected as the result of the above determination that no data transmission command is present, the present process is returned to the step S21 and is repeated, and if the data transmission command is present, a  
10 process for transmitting image data specified to be transmitted and related data thereof from the communication unit 16 of the PDA 2 to the communication unit 35 of the image data processing unit 3 is effected and the present data transmission process is terminated.

15 In this case, the output format designating process effected in the step S22 is a process for designating a way of printing the image received by and stored in the image data processing unit 3. More specifically, the output format can be previously  
20 selectively set in the time unit, place unit, vertical/horizontal unit, category unit, number-of-images unit, that is, the output selection can be made in the unit of related data of the image data and the output format can be determined by selecting one of  
25 them by the user's operation. The arrangement of an image with album size shown in FIG. 13 as will be described later is determined by designation of the

output format.

Next, an image data processing on the center side effected in the image data processing unit 3 based on an output request signal or image data and the like  
5 output from the PDA 2 is explained with reference to the flowchart of FIG. 8. A program for realizing various functions of the center described in the flowchart is stored in the storage medium 33a in the form of program code which can be read out by the  
10 CPU 31.

In the image data processing unit 3, first, whether image data and related data thereof transmitted from the PDA 2 in the step S25 of FIG. 7 are received by the communication unit 35 or not is determined in  
15 the step S31. If it is detected as the result of the above determination that the image data and related data thereof are received, the step S32 is effected to store the image data and related data thereof in the data memory 34b (for example, related data (time 51,  
20 place 52, comment 53, number of images 54, category 55) is stored in correspondence to image data 50 as shown in FIG. 12). If it is determined in the step S31 that no image data or the like is received, the step S33 is effected to determine whether an output request signal  
25 in the step S23 is received by the communication unit 35 or not. If the output request signal is received, the output format designated in the step S34

is stored in the format memory 34a and a printout  
(for example, the output result as shown in FIGS. 13A  
and 13B) is issued from the printer 5 in the step S35  
to terminate the process. Further, if the output  
5 request is not received, the step S31 is effected again  
and the process is repeated.

Next, the flow of the process for communicating  
and editing image data and the like effected between  
the personal computer 4 and the image data processing  
10 unit 3 of the center is explained with reference to  
FIG. 9.

The personal computer 4 can designate an output  
destination and issue an output request for outputting  
an image with respect to the center. First, if an  
15 output request of image data and the like is  
transmitted (step S41) from the personal computer 4 to  
the image data processing unit 3, the image data  
processing unit 3 determines in the step S42 whether  
the output request is issued for an output to the  
20 personal computer 4 or an output to the printer 5. If  
an output to the printer 5 is determined as the result  
of the above determination, the step S43 is effected to  
output the image data and the like in the designated  
format. On the other hand, in the case of an output to  
25 the PC 4, the image data and the like are edited in the  
designated output format (step S44) and the edited  
image data and the like are transmitted from the

communication unit 35 to the communication unit 47 of the personal computer 4 (step S45).

5 In the personal computer 4, image data and the like transmitted from the image data processing unit 3 of the center is received in the step S46 and the received image data and the like are displayed on the display unit 46. On the display screen, the user effects the reediting process (step S47) such as removal of an unnecessary photograph by use of the  
10 keyboard 45. At this time, a process for converting text data into a voice can be specified, and if the specification is made, text data is converted into voice data and an acoustic icon is attached to the image instead of display of the text.

15 In the step S48, a process for transmitting the reedited image data and the like to the image data processing unit 3 is effected.

In the step S49, the image data processing unit 3 receives the reedited image data and the like  
20 transmitted from the personal computer 4 at the communication unit 35, effects a process for storing the received reedited image data and the like into the album memory 34c in the data storage unit 34 (step S50) and the present image data communicating and editing  
25 process is terminated.

Next, the processing flow of the album data communicating process effected by the image data

processing unit 3 of the center and the personal computer 4 is explained with reference to FIG. 10.

If an output request for album data or the like stored in the album memory 334c of the data storage unit 34 is transmitted from the personal computer 4 to the image data processing unit 3 (step S51), the image data processing unit 3 reads out album data stored in the album memory 34c and transmits the same to the personal computer 4 via the communication unit 35 in the step S52.

The personal computer 4 receives the album data transmitted from the image data processing unit 3 at the communication unit 47 in the step S52 and displays the received album data on the display unit 46 (for example, on the CRT screen) (step S54). In the step S55, whether the acoustic icon on the display screen of the displayed album data is specified or not is determined, and if it is detected as the result of the above determination that the acoustic icon is not specified, the step S54 is effected to repeatedly display the data, and if the acoustic icon is specified, text data is converted into a voice and output by the audio output unit 48 in the step S56.

Since the image data processing system 1 described above is formed with the above construction, the following image data processing can be attained, for example.

First, the user who makes a journey with the PDA 2 takes photographs of scenery, person, or the like on the journey. Thus, photograph data is created in the image input unit 12, and at the same time, 5 photographing time is determined by the timer 20, the photographing place is determined by the GPS measuring unit 21, whether the photograph is taken in the vertical position or in the horizontal position is determined by the vertical/horizontal sensor 15, the 10 number of the photographed image data counted from the preset photographing start time is determined by the counter 22, and the image data and the related data thereof are stored in the memory 19.

Then, the user fetches each photographed image 15 data from the memory 19, displays the same on the display unit 13 and inputs a comment or title for the image data via the input unit 14. At this time, the user inputs a category to categorize scenery images and person images. Then, the image data and the related 20 data thereof are transmitted to the communication unit 35 of a center having the image data processing unit 3 and existing near the user's home via the communication line a by use of the communication unit 16.

25 The image data processing unit 3 of the center stores the received image data and related data thereof in the data storage unit 34.

Then, the user inputs an output request for printing of images and the like based on the image data and related data thereof in time-sequential order, for example, via the input unit 14 and transmits the output request signal to the image data processing unit 3 of the center on the final day of the journey.

The image data processing unit 3 of the center outputs an album of images and the like based on the image data and the related data thereof to the printer 5 thereof according to the received output request signal. More specifically, as shown in FIG. 13B, images (photographs) 57 are printed together with time 58, place 59, comment 60, title 61 and the like in time-sequential order as an album.

Then, the user will drop in the center on the way back home from the journey and take an output album home.

Therefore, the image data and the like created in the PDA 2 (photographing unit) can be edited according to the output format which the user desires and output in the preset output format and the added value of the photographed image data can be fully utilized while the output format is not influenced by the function of the personal computer 4 (terminal unit) of the user unlike the conventional case.

Further, since an output in the desired output format can be attained by previously transmitting

photographed image data and the like to a center near the user's home, it becomes unnecessary for the user to edit the image data and the like by himself, it becomes convenient and the user can immediately see the output  
5 result.

In this case, the personal computer at the user's home and the image data processing unit 3 are connected to each other via the communication line a.

Therefore, the user can fetch the image data and  
10 image data-related information edited in the image data processing unit 3 into the personal computer 4 and perform the reediting process such as removal of unnecessary image data, re-arrangement, or addition or modification of the comment or title so as to edit the  
15 photographed image data to his satisfaction.

In this case, image data and image data-related information subjected to the reediting process can be transmitted to the image data processing unit 3 again and output from the printer 5.

20 Therefore, the user can determine the output format by use of either the photographing unit or the terminal unit and it becomes a further convenient image data processing system.

Further, in this case, text information such as  
25 the comment and title can be specified to be output as a voice by the personal computer 4.

Therefore, when an electronic album is reproduced

by use of a personal computer or the like, text information can be output as a voice and the image data editing with larger added value can be attained.

Next, another embodiment of this invention is explained with reference to FIGS. 14 to 22C.

FIG. 14 is a system block diagram of an image processing unit according to another embodiment of this invention. In FIG. 14, a personal computer (which is hereinafter referred to as a PC) 51, portable terminal unit (which is hereinafter referred to as a PDA) 53 and server 55 are connected to one another via a communication network 57. A data base 59 is connected to the server 55. The data base 59 stores position information (physical information such as a geographical coordinate) and information (social information such as a place name) related to the position.

FIG. 15 is a system block diagram of the PDA 53 shown in FIG. 14. As shown in FIG. 15, the PDA 53 is constructed by a CPU 59, keyboard 61, photographing unit 63, display unit 65, GPS 67, ROM 69, RAM 71, communication unit 73, and azimuth sensor 75 and the above units are connected to one another via a system bus 77. Since the CPU 59, keyboard 61, photographing unit 63, display unit 65, GPS 67, ROM 69, RAM 71 and communication unit 73 among the above units have constructions equivalent to those of the CPU 11, input

unit 14, image input unit 12, display unit 13, GPS 21, ROM 18, RAM 71 and communication unit 73, the explanation therefor is omitted. The azimuth sensor 75 measures the azimuth when photographing is made by use  
5 of the photographing unit 63 (that is, a direction in which photographing is made).

FIG. 16 shows the memory configuration in the server 55. The memory configuration shown in FIG. 16 has areas for storing information of azimuth and other  
10 information in addition to the memory configuration shown in FIG. 12. As the information of azimuth, information of azimuth measured by the azimuth sensor 75 of the PDA 53 is stored. Further, as the other information, for example, an electronic mail address of  
15 a person whom the user came to know on the journey is stored by transmitting the electronic mail address from the PDA 53 to the server 55 after the user photographed him and heard his electronic mail address. As a result, the photographed image can be transmitted later to the  
20 electronic mail address.

FIGS. 17 and 18 are diagrams showing the internal configuration of the data base 58 shown in FIG. 14. The first data base shown in FIG. 17 previously stores position information (information of coordinates  
25 measured by the GPS 67) 83 and place name information (such as the names of noted sightseeing resorts) 85 corresponding to the position information. The second

data base shown in FIG. 18 has position information (information of coordinates measured by the GPS 67) 87, azimuth information and geographical information 91 corresponding to the azimuth. For example, the place  
5 names of respective places existing on the north side, south side, west side and east side of a certain position coordinate (indicating the north latitude and the east longitude) are previously stored.

FIG. 19 is a flowchart showing the reception  
10 process of the server. The server 55 receives image data and position data from the PDA 53 via the communication network 57 in the step S93. Then, it stores the received image information and position information into a specified area in the data base 58  
15 assigned to the sender in the step S95.

FIG. 20 is a flowchart showing the content of a process which the server 55 executes in response to various requests from the PC 51 and FIG. 21 is a flowchart showing a process effected when the PC 51  
20 issues various requests to the server 55. In the step S117 of FIG. 21, the PC 51 transmits an output request of desired image data to the server 55 via the communication network 57. The server 55 receives the image output request from the PC 51 in the step S97 of  
25 FIG. 20. Then, in the step S99, it reads out specified image data and related information (FIG. 16) thereof among the stored image data from a specified area of

the data base 58 which is assigned to the user in response to the output request and transmits the same to the PC 51. The PC 51 displays the image data and related information thereof transmitted from the server 55 on the display unit 65 as shown in FIG. 22A in the step S119 of FIG. 21. The user can specify further related information (geographical information) of the image data displayed on the display unit 65 in the step S121. For example, in a case the user wants to know the name of a sightseeing resort in a corresponding place based on position information measured by the GPS 67, the user moves the cursor to a position corresponding to a position information field (133 in FIG. 22A) thereof and clicks the mouse 61. Alternatively, if the user wants to know the name of a place at which the photograph was taken based on the azimuth measured by the azimuth sensor 75, the user moves the cursor to a position corresponding to an azimuth field 135 shown in FIG. 22A and clicks the mouse. As a result, the PC 51 transmits the clicked position information and azimuth information to the server 55 in the step S123. The server 55 determines the content of the request from the PC 51 in the step S101 of FIG. 20, searches the data base 58 to read out specified information (a place name corresponding to the position information or a place name corresponding to the azimuth information) in the step S109, and

outputs the information to the PC 51 in the step S111.

The PC 51 receives place name information corresponding to the position information and azimuth information from the server 55 and displays "KOFU" and  
5 "Mt. FUJI" as shown in FIG. 22B in the step S125.

Further, if the user wants to transmit image data displayed on the display unit 65 to the address of the electronic mail displayed as shown in FIG. 22C, he moves the cursor to a position corresponding to the  
10 electronic mail address and clicks the mouse so as to permit the PC to transmit a mail transmission request together with the electronic mail address to the server.

The server determines in the step S127 of FIG. 21 that an image data transmission request by the  
15 electronic mail is issued from the PC and transmits the image data to the electronic mail address in the step S129.

Further, if the user wants to print image data displayed on the display unit 65, he clicks a print  
20 button (not shown) on the display unit 65 by use of the mouse in the display screen of FIG. 16 so as to permit the PC to transmit a print request to the server via the communication network 57.

The server 55 determines the print request from  
25 the PC in the step S127 of FIG. 21 and prints the specified image data in the step S131.

Further, the user sometimes wants to input some

comment for the displayed image data. In such a case,  
a comment is input by use of the keyboard unit 61 and  
the PC 51 transmits the input comment to the server 55.  
The server 55 determines the comment input request from  
5 the PC in the step S127 and writes the comment into the  
corresponding comment field 54 shown in FIG. 16 in the  
step S129.

Related data of the image data is not limited to  
the type described in the above embodiments and may be  
10 any type of information if it is related to the image  
data.

Further, the preset output format includes an  
output by a printing unit, output by a display unit,  
output by an audio unit and the like.

15 Further, the output format is determined based on  
the related data of the image data in the above  
embodiments but may be determined based on data  
different from the related data of the image data.

This Sheet Has Been Replaced



## C L A I M S

1. An image data processing system comprising:  
a photographing unit (2) including photographing means (12) for photographing a subject to create image data; and transmission means (16) for transmitting the  
5 image data via a communication line; and  
a center unit (3) including reception means (35) for receiving image data transmitted from said photographing unit via the communication line; storage means (34) for storing image data received by said  
10 reception means; editing means (31) for editing image data stored in said storage means; and output means (5) for outputting image data edited by said editing means.
2. A system according to claim 1, wherein said  
15 photographing unit further includes additional information creating means (20, 21) for creating information added to the image data, said transmission means includes means for transmitting the image data and additional information, said receiving means  
20 includes means for receiving image data and additional information transmitted via the communication line, said storage means includes storing means for storing image data and additional information received by said receiving means, and said editing means includes means  
25 for editing the image data stored in said storing means based on the additional information.

3. A system according to claim 2, wherein said



photographing unit includes designating means (11) for designating an output format, and said editing means of said center unit includes means for editing data into a format designated by said designating means.

5           4. A system according to claim 3, wherein said additional information creating means includes at least one of position measuring means (21) for measuring a position at which the image data was photographed and timer means (20) for counting time at which the image  
10 data was photographed, and said designating means includes means for designating an output in the unit of photographing place or time.

          5. A system according to claim 3, wherein said additional information creating means includes means  
15 for inputting a category of image data and said designating means includes means for designating an output according to the category of image data.

          6. A system according to claim 3, wherein said center unit further includes a data base (58) which  
20 stores information related to additional information, and additional information outputting means (55) for fetching information related to additional information received from said photographing unit from said data base and outputting the information.

25           7. A system according to claim 6, wherein said additional information creating means includes position measuring means for measuring the position at which the





image data was photographed, said data base includes means for storing a geographical name related to position information as a data base, and said additional information outputting means includes means  
5 for outputting a geographical name corresponding to a position when information of the position is received as additional information.

8. A system according to claim 7, wherein said additional information creating means further includes  
10 azimuth measuring means (75) for measuring the azimuth in which the image data was photographed, said data base further includes means for storing a geographical name related to a combination of the position information and azimuth information, and said  
15 additional information outputting means includes means for outputting a geographical name corresponding to a position and azimuth when information of the position and information of the azimuth are received as additional information.

20 9. A system according to claim 1, wherein said photographing unit includes means for adding an electronic mail address to photographed image data, and said center unit includes means for transmitting the image data to the added electronic mail address.

25 10. A system according to claim 1, wherein said outputting means includes means for outputting data to a terminal unit connected via a communication line (a).





11. An image data processing device comprising:  
communication means for transmitting and receiving  
data with respect to a terminal unit (53) connected to  
a network (57);

5 storage means (58) for storing image data received  
via said communication means;

editing means (55) for editing image data stored  
in said storage means; and

10 output means (55) for outputting image data edited  
by said editing means.

12. A device according to claim 11, wherein said  
storage means includes means for storing image data and  
additional information received via said communication  
means, and said editing means includes means for  
15 editing the image data stored in said storage means  
based on the additional information.

13. A device according to claim 12, wherein said  
editing means includes means for editing data into a  
format designated by said terminal unit via said  
20 communication means.

14. A device according to claim 13, wherein  
additional information stored in said storage means  
includes at least one of information of position at  
which the image data was photographed and information  
25 of time at which the image data was photographed, and  
said editing means includes means for editing data to  
output the data in the unit of photographing place or





time.

15. A device according to claim 14, wherein said output means includes a printer (5) for printing out edited image data.

5 16. A device according to claim 12, further comprising a data base which stores information related to additional information; and additional information outputting means for fetching information related to the received additional information from said data base  
10 and outputting the information.

17. A device according to claim 16, wherein the additional information contains position information of information at which the image data is photographed, said data base includes means for storing a  
15 geographical name related to the position information as a data base, and said additional information outputting means includes means for outputting a geographical name corresponding to a position when information of the position is received as additional  
20 information.

18. A device according to claim 11, wherein said output means includes means for outputting edited image data to a terminal unit connected via a network.

19. A device according to claim 18, further  
25 comprising means for receiving image data reedited by the terminal unit; and means for printing out received image data.

This Sheet Has Been Replaced





20. A device according to claim 11, further comprising means for transmitting image data by electronic mail to a mail address when the electronic mail address is added to the image data.

---

This Sheet Has Been Replaced

