

BLOCKCHAIN CONSENSUS METHOD AND DEVICE AND ELECTRONIC EQUIPMENT

TECHNICAL FIELD

5 [0001] This specification relates to the field of blockchain technology, and in particular, to a blockchain consensus method, a blockchain consensus device, and an electronic equipment.

BACKGROUND

[0002] With the development of information technologies, the blockchain technology has
10 become people's focus because of its advantages such as openness, inalterability, decentralization, etc. In current blockchain technology, a transaction initiated by a client can be chained only after all consensus nodes in the blockchain reach a consensus. A proposal of the consensus is initiated by a consensus master node of the blockchain. The consensus master node sends transaction information of a pending-consensus transaction to a consensus
15 backup node. After receiving the transaction information, the consensus backup node performs a consensus check on the pending-consensus transaction to decide whether to reach a proposal.

[0003] At present, when there are many pending-consensus transactions in a consensus proposal, the data amount of transaction information that the consensus master node needs to
20 send will increase accordingly, thereby consuming much time for transmission and analysis, which in turn seriously affects the consensus efficiency. In view of the above, a technical solution for improving the consensus efficiency of the blockchain is urgently desired.

SUMMARY

[0004] One object of the embodiments of this specification is to provide a blockchain
25 consensus method, a blockchain consensus device, and an electronic equipment, which can improve the consensus execution efficiency of the blockchain.

[0005] To achieve the above-described object, the embodiments of this specification are implemented as follows.

[0006] In a first aspect, a blockchain consensus method is provided, comprising:
30 initiating, by a consensus master node of a blockchain, a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the consensus proposal carries a transaction hash list, and the transaction hash list comprises

a transaction hash of the at least one pending-consensus transaction; matching and selecting, by a target consensus backup node of the blockchain from a transaction pool of the target consensus backup node, the at least one pending-consensus transaction corresponding to the transaction hash list, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and obtaining, by the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on the transaction information.

[0007] In a second aspect, a blockchain consensus device is provided, comprising: a consensus initiation module, configured to initiate, based on a consensus master node of a blockchain, a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the consensus proposal carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus transaction; a transaction matching module, configured to match and select, based on a target consensus backup node of the blockchain, the at least one pending-consensus transaction corresponding to the transaction hash list from a transaction pool of the target consensus backup node, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and a consensus execution module, configured to obtain, based on the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on the transaction information.

[0008] In a third aspect, an electronic equipment is provided, comprising: a memory, a processor, and a computer program stored on the memory and capable of running on the processor, wherein the computer program is executed by the processor to: initiate, based on a consensus master node of a blockchain, a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the consensus proposal carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus transaction; match and select, based on a target consensus backup node of the blockchain, the at least one pending-consensus transaction corresponding to the transaction hash list from a transaction pool of the target consensus backup node, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and obtain, based on the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the

transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on the transaction information.

[0009] In a fourth aspect, a computer-readable storage medium having a computer program stored thereon is provided, wherein when the computer program is executed by a processor, the following steps are implemented: initiating, based on a consensus master node of a blockchain, a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the consensus proposal carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus transaction; matching and selecting, based on a target consensus backup node of the blockchain, the at least one pending-consensus transaction corresponding to the transaction hash list from a transaction pool of the target consensus backup node, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and obtaining, based on the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on the transaction information.

[0010] In the solutions of the embodiments of this specification, a consensus master node sends to a consensus backup node a transaction hash of a pending-consensus transaction in a consensus stage, replacing the original method of sending transaction information of the pending-consensus transaction to the consensus backup node. All transaction backup nodes may autonomously match and select transaction information of the pending-consensus transaction from respective transaction pools based on the transaction hash, thereby completing a consensus process flow. Since the data amount of the transaction hash is smaller than that of transaction information, the solutions of the embodiments of this specification may significantly reduce the time for data transmission and data analysis in the consensus process, thereby improving the consensus efficiency.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] In order to more clearly describe the technical solutions of the embodiments of this specification or the current technologies, the accompanying drawings used for the description of the embodiments or the current technologies are briefly described below. Apparently, the accompanying drawings described below are only some embodiments recorded in this specification. One of ordinary skill in the art may obtain other drawings according to these accompanying drawings without creative efforts.

[0012] FIG. 1 is a first process flow diagram of a blockchain consensus method according to the embodiments of this specification.

[0013] FIG. 2 is a second process flow diagram of a blockchain consensus method according to the embodiments of this specification.

5 [0014] FIG. 3 is a structural diagram of a blockchain consensus device according to the embodiments of this specification.

[0015] FIG. 4 is a structural diagram of an electronic equipment according to the embodiments of this specification.

DETAILED DESCRIPTION

10 [0016] For a better understanding of the technical solutions of this specification by those skilled in the art, a clear and complete description of the technical solutions of the embodiments of this specification is made below in conjunction with the accompanying drawings in the embodiments of this specification. Apparently, only some, not all of the embodiments of this specification are described. All other embodiments obtained by one of
15 ordinary skill in the art without creative efforts based on the embodiments of this specification shall fall within the protection scope of this specification.

[0017] As mentioned earlier, in current blockchain technology, a transaction initiated by a client can be chained only after all consensus nodes in the blockchain reach a consensus. In the consensus process, a consensus master node needs to send transaction information of a
20 pending-consensus transaction to consensus backup nodes for a consensus check. At present, when there are many pending-consensus transactions in a consensus proposal, the data amount of transaction information that the consensus master node needs to send will increase accordingly, thereby consuming much time for transmission and analysis, which in turn seriously affects the consensus efficiency.

25 [0018] For this problem, one object of this specification is to provide a technical solution which may achieve a highly efficient consensus execution.

[0019] FIG. 1 is a process flow diagram of a blockchain consensus method according to the embodiments of this specification. The method shown in FIG. 1 may be executed by corresponding device below, comprising the following steps:

30 [0020] S102: initiating, by a consensus master node of a blockchain, a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the consensus proposal carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus

transaction.

[0021] Note that the original consensus proposal carries a transaction information list, and the transaction information list carries transaction information of all pending-consensus transactions in this consensus proposal. In general, when the number of the pending-
5 consensus transactions reaches 1,000, the data amount of the transaction information list is as high as about 2 M, which for a blockchain, is a relatively large data amount.

[0022] In this step, the consensus master node uses the transaction hash list instead of a traditional transaction information list, which means that the consensus master node informs a consensus backup node of a pending-consensus transactions of this consensus proposal
10 through a transaction hash. It should be appreciated that the data amount corresponding to the transaction hash is much smaller than that corresponding to transaction information.

[0023] S104: matching and selecting, by a target consensus backup node of the blockchain from a transaction pool of the target consensus backup node, the at least one pending-consensus transaction corresponding to the transaction hash list, wherein all
15 consensus nodes of the blockchain have the same transaction hash calculation logic.

[0024] It should be appreciated that all consensus nodes of the blockchain having the same transaction hash calculation logic means that the transaction hashes calculated by all consensus nodes for the same transaction are consistent. As a result, all consensus backup nodes may match and select a pending-consensus transaction consistent with the consensus
20 master node based on the transaction hash of the transaction hash list.

[0025] S106: obtaining, by the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on transaction information.

[0026] Note that under normal circumstances, all consensus nodes of the blockchain will independently initiate a legality check on a transaction initiated by a client, and add the transaction passing the legality check to the transaction pool thereof. As a result, the consensus backup node has the ability to obtain transaction information of a pending-consensus transaction from the transaction pool thereof, instead of having the consensus
25 master node sending transaction information to the consensus backup node.

[0027] It is clear from the blockchain consensus method shown in FIG. 1 that: in the solutions of the embodiments of this specification, the consensus master node sends to the consensus backup node a transaction hash of a pending-consensus transaction in the consensus stage, replacing the original method of sending to the consensus backup node

transaction information of the pending-consensus transaction. All transaction backup nodes may autonomously match and select transaction information of the pending-consensus transaction from respective transaction pools based on the transaction hash, thereby completing a consensus process flow. Since the data amount of the transaction hash is smaller than that of transaction information, the solutions of the embodiments of this specification may significantly reduce the time for data transmission and data analysis in the consensus process, thereby improving the consensus efficiency.

5 [0028] In practical use, the client will access a node in the blockchain to initiate a transaction. After this node performs a successful legality check on the transaction, the node will add the transaction to the transaction pool thereof, and then forward the transaction to other nodes, causing other nodes to perform a legality check on the transaction. Similarly, after performing a successful legality check on the transaction, other nodes will add the transaction to respective transaction pools.

10 [0029] Thus, the transactions in the transaction pools of all nodes in the blockchain are not all synchronous. It means that in a very rare case, after a consensus master node initiates a consensus proposal for a pending-consensus transaction in the transaction pool thereof, the pending-consensus transaction may not yet be added to the transaction pools of some consensus backup nodes. Thus, even if a transaction hash list sent by the consensus master node is obtained, a consensus backup node would still fail to match and select the pending-consensus transaction from the transaction pool thereof, nor would it be able to obtain transaction information of the pending-consensus transaction, which makes a consensus flow unable to proceed.

20 [0030] To solve this problem, in the above-described Step S104, if a target consensus backup node fails to match and select, from a transaction pool of the target consensus backup node, a target pending-consensus transaction (not limited to one) corresponding to the transaction hash list, the target consensus backup node waits until the transaction pool of the target consensus backup node is updated based on a preset delay strategy, and then rematches and reselects, from the transaction pool of the target consensus backup node, the target pending-consensus transaction corresponding to the transaction hash list.

30 [0031] Here, the delay strategy may include, but is not limited to: a rematch count and a rematch time interval. As an example for illustration: assuming that the rematch count is 3 and the rematch time interval is 10 ms. Then the target consensus backup node waits for 10 ms after failing to match and select, from the transaction pool of the target consensus backup node, the target pending-consensus transaction corresponding to the transaction hash list, and

then retries to match and select the target pending-consensus transaction from the transaction pool of the target consensus backup node. If the matching still fails, the target consensus backup node waits for another 10 ms and retries to match and select the target pending-consensus transaction from the transaction pool of the target consensus backup node until the rematch count reaches 3.

[0032] In order to further ensure successful execution of the consensus proposal, if the target consensus backup node still fails to match and select, based on the delay strategy, the target pending-consensus transaction corresponding to the transaction hash list from the transaction pool of the target consensus backup node, the target consensus backup node may certainly actively request to obtain transaction information of the target pending-consensus transaction from the consensus master node. It should be appreciated here that the consensus master node will only initiate a consensus proposal for a transaction in a transaction pool of the consensus master node. The scenario in which the consensus master node does not have transaction information of the target pending-consensus transaction does not exist.

[0033] For example, when the target consensus backup node needs to request transaction information of the target pending-consensus transaction from the consensus master node, the target consensus backup node may send a transaction synchronization request message to the consensus master node. The transaction synchronization request message carries the transaction hash of the target pending-consensus transaction that the target consensus backup node fails to match and select from the transaction pool of the target consensus backup node.

[0034] Then, the consensus master node searches for the transaction information of the target pending-consensus transaction in the transaction pool of the consensus master node based on the transaction hash in the transaction synchronization request, and feeds back transaction information of the target pending-consensus transaction to the target consensus backup node through a transaction synchronization response message.

[0035] After receiving the transaction synchronization response message, the target consensus backup node first performs an account legality check on the target pending-consensus transaction based on the transaction information of the target pending-consensus transaction in the transaction synchronization response message (in some embodiments, the IP address of a client that initiates the transaction is verified, etc.). After the account legality check is performed and successful, adds the transaction information of the target pending-consensus transaction to the transaction pool of the target consensus backup node. Then, the target consensus backup node matches and selects the target pending-consensus transaction from the transaction pool of the target consensus backup node. It needs to be explained here

that the match should not be deemed as a successful match when the target consensus backup node does not match and select the pending-consensus transaction corresponding to the transaction hash list from its own transaction pool.

[0036] It should be appreciated that the above-described target pending-consensus transaction does not refer to all pending-consensus transactions of this consensus proposal. Therefore, even if the consensus master node sends transaction information of the target pending-consensus transaction to the consensus backup node, the consumed time for transmission and analysis is less than that for sending transaction information of all pending-consensus transactions to the target consensus backup node.

[0037] Apparently, since one object of the embodiments of this specification is to reach a consensus more quickly for the blockchain, the technology of the above-described solution may be improved to further increase the consensus efficiency.

[0038] As an example: when the target consensus backup node fails to match and select all pending-consensus transactions corresponding to the transaction hash list from its own transaction pool at one try, the target consensus backup node may mark the transaction hash of the matched pending-consensus transaction in the transaction hash list. In subsequent rematch, the target consensus backup node only performs matching and selecting, from the transaction pool of the target consensus backup node, for a pending-consensus transaction corresponding to an unmarked transaction hash in the transaction hash list, thereby achieving the goal of saving the matching time.

[0039] As another example: after adding a new transaction to a transaction pool of a target consensus backup node, the target consensus backup node may pre-calculate a transaction hash of the new transaction based on a transaction hash calculation logic, and store a mapping relationship between the new transaction and the corresponding transaction hash. In subsequent execution of a consensus process flow for the new transaction, a target consensus backup node may directly match and select, from a transaction pool of the target consensus backup node, the new transaction corresponding to the transaction hash list based on the pre-stored mapping relationship, thereby achieving the goal of saving the matching time. Optionally, after the new transaction is successfully chained, the target consensus backup node may delete the pre-stored mapping relationship between the new transaction and corresponding transaction hash, in order to clear up the storage space.

[0040] The method according to the embodiments of this specification is described below as an example in conjunction with different implementation manners.

Implementation manner 1

[0041] In implementation manner 1, replica nodes (also referred to as copies, which are nodes that establish a blockchain distributed system, including a consensus master node and consensus backup nodes) of a blockchain performs consensus based on Practical Byzantine Fault Tolerance (PFBT) (or performs consensus based on other algorithms, which are not limited to PFBT). A consensus process flow corresponding to PFBT is shown in FIG. 2, including:

[0042] A pre-prepare stage:

[0043] The consensus master node of the blockchain initiates a consensus proposal, enters a pre-prepare stage of PFBT, and broadcasts a pre-prepare message to all consensus backup nodes, wherein the pre-prepare message carries information such as a sequence number (Sequence): n of this proposal, a view value (View): v, a transaction hash list, etc. Here, the transaction hash list includes the transaction hashes of all pending-consensus transactions in this consensus proposal. In implementation manner 1, it is assumed that the pending-consensus transactions include: transaction a, transaction b and transaction c.

[0044] A prepare stage:

[0045] After receiving the pre-prepare message, the target consensus backup node (representing any consensus backup node) of the blockchain first determines whether Sequence: n and View: v in the pre-prepare message are recognized.

[0046] If not, the consensus proposal is rejected.

[0047] If so, the pre-prepare message is accepted, and the process flow proceeds to the following steps.

[0048] The target consensus backup node matches and selects transaction a, transaction b, and transaction c from a transaction pool of the target consensus backup node based on the transaction hashes of transaction a, transaction b, and transaction c in the transaction hash list.

[0049] For example, in the matching process, the target consensus backup node may respectively perform reverse calculation of the transaction hashes in the transaction hash list based on a transaction hash calculation logic agreed by the replica nodes, and obtain summary information of transaction a, transaction b, and transaction c. Afterwards, based on summary information of transaction a, transaction b, and transaction c, the target consensus backup node searches its own transaction pool in order to match and select transaction a, transaction b, and transaction c from the transaction pool.

[0049] After matching transaction a, transaction b, and transaction c from the transaction pool of the target consensus backup node, the target consensus backup node extracts transaction information of transaction a, transaction b, and transaction c from the transaction

pool. Then, the target consensus backup node performs a consensus check on transaction information of transaction a, transaction b, and transaction c based on a consensus check rule. It should be understood that the consensus check method may be set flexibly, which will not be elaborated further with examples herein.

5 **[0050]** If the consensus check succeeds, the target consensus backup node enters the prepare stage, determines that the state on replica nodes is prepared, and adds the pre-prepare message to local Log, and sends a prepare message to other replica nodes.

[0051] A commit stage:

[0052] After all replica nodes enter the prepared state, each replica node sends a commit
10 message to other replica nodes, and adds the commit message it sends to local Log
(representing its recognition). When a replica node finds that a quorum (a quorum is a set of a
certain number of replicas required to ensure the consistency requirement and fault tolerance
requirement of all replica data) agrees on the assignment of Sequence: n, the replica node will
broadcast a commit message to all other replica nodes. At the same time, the replica node will
15 also receive the commit messages from other replica nodes. If a replica node receives $2f+1$ (f
is the number of evil nodes in a union chain) commit messages (including the one it sends,
and the commit messages from different nodes carrying the same Sequence: n and View: v),
then the replica node possesses a certificate named committed certificate, and the consensus
proposal reaches a committed state on this replica node. Now, it can be confirmed, only
20 through this replica node, that the request already reaches a prepared state in a quorum,
namely, all replica nodes of the same quorum agree on the assignment of Sequence: n. When
a replica node is in the committed state, it accepts the consensus proposal.

Implementation manner 2

[0053] In implementation manner 2, the replica nodes of a blockchain reach a consensus
25 based on PFBT, and a consensus process flow corresponding to PFBT includes:

[0054] A pre-prepare stage:

[0055] A consensus master node of the blockchain initiates a consensus proposal, enters a
pre-prepare stage of PFBT, and broadcasts a pre-prepare message to each consensus backup
node, wherein the pre-prepare message carries the information such as Sequence: n, View: v,
30 and a transaction hash list. Here, the transaction hash list includes the transaction hashes of
all pending-consensus transactions in this consensus proposal. In the implementation manner
1, it is assumed that the pending-consensus transactions include: transaction a, transaction b.
and transaction c.

[0056] A prepare stage:

[0057] After receiving the pre-prepare message, a target consensus backup node of the blockchain first determines whether the Sequence: n and View: v in the pre-prepare message are recognized.

[0058] If not, the consensus proposal is rejected.

5 **[0059]** If so, the pre-prepare message is accepted, and the process flow proceeds to the following steps.

[0060] Based on the transaction hashes of transaction a, transaction b, and transaction c in the transaction hash list, the target consensus backup node only matches and selects transaction a from a transaction pool of the target consensus backup node. At this point, it

10 means that transaction b and transaction c have not yet been synchronized to the transaction pool of the target consensus backup node, then the target consensus backup node may wait for 3 ms, and rematch and reselect transaction b and transaction c from the transaction pool of the target consensus backup node.

[0061] Assuming that transaction b is re-matched and selected from the transaction pool

15 of the target consensus backup node, but transaction c is still not matched and selected, then the target consensus backup node may wait for another 3 ms, and try again to match and select transaction c from the transaction pool of the target consensus backup node.

[0062] If transaction c is still not matched and selected, the target consensus backup node sends the transaction hash of the matched transaction c in the transaction hash list to the

20 consensus master node; and the consensus master node matches and obtains transaction information of transaction c from a transaction pool of the consensus master node based on the transaction hash of transaction c, and feeds back transaction information of transaction c to the target consensus backup node.

[0063] After obtaining transaction information of transaction c through the consensus

25 master node, the target consensus backup node performs account legality check based on transaction information of transaction c. This account legality check is different from subsequent consensus check of a consensus node, and is only intended to verify whether transaction c can be added to the transaction pool; and if transaction c passes the account legality check from the target consensus backup node, the target consensus backup node adds

30 transaction c to the transaction pool of the target consensus backup node. Then, the target consensus backup node re-matches the transaction hash corresponding to transaction c in the transaction hash list with the transaction pool of the target consensus backup node.

[0064] After matching and selecting transaction a, transaction b, and transaction c from the transaction pool of the target consensus backup node, the target consensus backup node

further extracts transaction information of transaction a, transaction b, and transaction c from the transaction pool. Then, the target consensus backup node performs a consensus check on transaction information of transaction a, transaction b, and transaction c based on its consensus check rules, and determines whether transaction a, transaction b, and transaction c are legal at a transaction level.

[0065] If the consensus check is successful, the target consensus backup node enters the prepare stage, determines that the state on replica is prepared, and adds the pre-prepare message to local Log, and sends a prepare message to other replica nodes.

[0066] A commit stage:

[0067] After all replica nodes enter the prepared state, each replica node sends a commit message to other replica nodes, and adds the commit message it sends to local Log (representing its recognition). When a replica node finds that a quorum (a quorum is a set of a certain number of replicas required to ensure the consistency requirement and fault tolerance requirement of all replica data) agrees on the assignment of Sequence: n, the replica node will broadcast a commit message to all other replica nodes. At the same time, the replica node will also receive the commit messages from other replica nodes. If a replica node receives $2f+1$ (f is the number of evil nodes in a union chain) commit messages (including the one it sends, and the commit messages from different nodes carrying the same Sequence: n and View: v), then the replica node possesses a certificate named committed certificate, and the consensus proposal reaches a committed state on this replica node. Now, it can be confirmed, only through this replica node, that the request already reaches a prepared state in a quorum, namely, all replica nodes of the same quorum agree on the assignment of Sequence: n. When a replica node is in the committed state, it accepts the consensus proposal.

[0068] The above-described implementation manners are only used for the description of the method according to the embodiments of this specification. It should be understood that appropriate changes may be made without departing from the above-described principles, and these changes shall also be considered to be within the protection scope of the embodiments of this specification. In some embodiments, after obtaining a hash list from the pre-prepare message, the consensus backup node may also obtain transaction information of the pending-consensus transaction from local transaction pool in the pre-prepare stage or the committed stage, and complete relevant consensus check.

[0069] Corresponding to the above-described method, as shown in FIG. 3, the embodiments of this specification also provide a blockchain consensus device 300, comprising:

[0070] a consensus initiation module 310, configured to initiate, based on a consensus master node of a blockchain, a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the consensus proposal carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus transaction;

[0071] a transaction matching module 320, configured to match and select, based on a target consensus backup node of the blockchain, the at least one pending-consensus transaction corresponding to the transaction hash list from a transaction pool of the target consensus backup node, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and

[0072] a consensus execution module 330, configured to obtain, based on the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on the transaction information.

[0073] It can be known from the blockchain consensus device shown in FIG. 3 that in the solutions of the embodiments of this specification, the consensus master node sends the transaction hash of the pending-consensus transaction to a consensus backup node in a consensus stage, replacing the original method of sending transaction information of the pending-consensus transaction to the consensus backup node. All transaction backup nodes may autonomously match and select transaction information of the pending-consensus transaction from respective transaction pools based on the transaction hash, thereby completing a consensus process flow. Since the data amount of the transaction hash is smaller than that of transaction information, the solutions of the embodiments of this specification may significantly reduce the time for data transmission and data analysis in the consensus process, thereby improving the consensus efficiency.

[0074] Optionally, before the step of executing a processing logic of the consensus proposal based on the transaction information, if the transaction matching module 320 fails to match and select, based on a target consensus backup node, a target pending-consensus transaction corresponding to the transaction hash list from a transaction pool of the target consensus backup node, it may wait until the transaction pool of the target consensus backup node is updated based on a preset delay strategy, and rematch and reselect the target pending-consensus transaction corresponding to the transaction hash list from the transaction pool of the target consensus backup node.

[0075] Optionally, before the step of executing a processing logic of the consensus

proposal based on the transaction information, if the transaction matching module 320 still fails to match and select, based on the target consensus backup node and the delay strategy, the target pending-consensus transaction corresponding to the transaction hash list from the transaction pool of the target consensus backup node, it may request to obtain the information
5 of the target pending-consensus transaction from the consensus master node based on the target consensus backup node. For example, the transaction matching module 320 may send a transaction synchronization request message to the consensus master node based on the target consensus backup node, wherein the transaction synchronization request message carries the transaction hash of the target pending-consensus transaction that fails to be matched and
10 selected from the transaction pool of the target consensus backup node. Then, the transaction matching module 320 receives, based on the target consensus backup node, a transaction synchronization response message fed back by the consensus master node, wherein the transaction synchronization response message carries transaction information of the target pending-consensus transaction provided by the consensus master node. Then, the transaction
15 matching module 320 performs a legality check on the target pending-consensus transaction based on the target consensus backup node and transaction information of the target pending-consensus transaction in the transaction synchronization response message. After the legality check is performed and successful, transaction information of the target pending-consensus transaction is added to the transaction pool of the target consensus backup node. Finally, the
20 transaction matching module 320 matches and selects, based on a consensus backup node of the blockchain, the target pending-consensus transaction corresponding to the transaction hash list from the transaction pool of the target consensus backup node.

[0076] Here, the above-described delay strategy may include, but is not limited to: a rematch count and a rematch time interval.

25 **[0077]** Optionally, the transaction matching module 320 may mark, based on the target consensus backup node, the transaction hash of the matched pending-consensus transaction in the transaction hash list. Here, the transaction matching module 320 only matches and selects, based on the target consensus backup node, a pending-consensus transaction corresponding to an unmarked transaction hash in the transaction hash list from the transaction pool of the
30 target consensus backup node.

[0078] Optionally, after the target consensus backup node adds a new transaction to the transaction pool of the target consensus backup node, the transaction matching module 320 may calculate a transaction hash of the new transaction based on the transaction hash calculation logic, and stores a mapping relationship between the new transaction and the

corresponding transaction hash, to directly match and select, based on the pre-stored mapping relationship, the at least one pending-consensus transaction corresponding to the transaction hash list from the transaction pool of the target consensus backup node.

5 [0079] Optionally, the transaction hash list is sent to the target consensus backup node by the consensus master node through a pre-prepare message in a pre-prepare stage of the consensus proposal.

[0080] Apparently, the blockchain consensus device of the embodiments of this specification may serve as an execution entity of the blockchain consensus method shown in FIG. 1, and thus can achieve the functions of the blockchain consensus method shown in
10 FIGs. 1 and 2. As the principles are identical, the blockchain consensus device will not be elaborated further herein.

[0081] FIG. 4 is a structural diagram of an electronic equipment according to an embodiment of this specification. Referring to FIG. 4, at a hardware level, the electronic equipment includes a processor, and optionally further includes an internal bus, a network
15 interface, and a memory. Here, the memory may include an internal memory such as a high-speed Random-Access Memory (RAM), and may also include a non-volatile memory such as at least one disk memory. The electronic equipment may certainly also include the hardware required by other transactions.

[0082] The processor, the network interface, and the memory may be connected to each
20 other through an internal bus, wherein the internal bus may be an ISA (Industry Standard Architecture) bus, a PCI (Peripheral Component Interconnect) bus or an EISA (Extended Industry Standard Architecture) bus, etc. The bus may be classified into an address bus, a data bus, a control bus, etc. For ease of presentation, only a double-headed arrow is used in FIG. 4, which, however, does not mean that there is only one bus or one type of bus.

25 [0083] The memory is used to store programs. For example, the programs may include program codes, and the program codes include computer operation instructions. The memory may include an internal memory and a non-volatile memory, and provides instructions and data to the processor.

[0084] The processor reads corresponding computer program from the non-volatile
30 memory to the internal memory and then runs the computer program to form a blockchain consensus device at a logical level. The processor executes the programs stored in the memory, and is used to perform the following operations:

[0085] initiating, based on a consensus master node of a blockchain, a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master

node, wherein the consensus proposal carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus transaction;

[0086] matching and selecting, based on a target consensus backup node of the blockchain, the at least one pending-consensus transaction corresponding to the transaction hash list from a transaction pool of the target consensus backup node, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and

[0087] obtaining, based on the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on the transaction information.

[0088] It can be known from the electronic equipment shown in FIG. 4 that in the solutions of the embodiments of this specification, the consensus master node sends the transaction hash of the pending-consensus transaction to the consensus backup node in a consensus stage, replacing the original method of sending transaction information of the pending-consensus transaction to the consensus backup node. All transaction backup nodes may autonomously match transaction information of the pending-consensus transaction from respective transaction pools based on the transaction hash, thereby completing a consensus process flow. Since the data amount of the transaction hash is smaller than that of transaction information, the solutions of the embodiments of this specification may significantly reduce the time for data transmission and data analysis in the consensus process, thereby improving the consensus efficiency.

[0089] The above-mentioned blockchain consensus method disclosed by the embodiment shown in FIG. 1 of this specification is applicable on a processor or is implemented by the processor. The processor may be an integrated circuit chip with signal processing capability. During implementation, the steps of the above-described method may be completed by an integrated logic circuit of hardware in the processor or by instructions in a software form. The above-described processor may be a general-purpose processor, including CPU (Central Processing Unit), NP (Network Processor), etc, and may also be DSP (Digital Signal Processor), ASIC (Application Specific Integrated Circuit), FPGA (Field-Programmable Gate Array) or other programmable logic devices, discrete gate or transistor logic devices, discrete hardware components. The method, steps and logical block diagrams disclosed in the embodiments of this specification may be implemented or executed. The general-purpose processor may be a microprocessor or any conventional processor, etc. The steps of the method disclosed by the embodiments of this specification may be directly executed

completely by a hardware decoding processor, or by a combination of hardware and software modules in the decoding processor. The software module may be located in a mature storage medium in the field, such as a random access memory, a flash memory, a read-only memory, a programmable read-only memory, an electrically erasable programmable memory and a register. The storage medium is located in the memory, and the processor reads information in the memory and implements the steps of the above-described method in conjunction with its hardware.

5 [0090] It should be appreciated that the electronic equipment according to the embodiments of this specification may achieve the functions of the above-mentioned blockchain consensus device embodiments shown in FIGs. 1 and 2, which will not be elaborated further herein.

[0091] Of course, in addition to the implementation manner by software, the electronic equipment in this specification does not exclude other implementation manners, such as by a logic device or a combination of software and hardware, etc. That is to say, the execution entity for the following process flow is not limited to various logic units, and may also be a hardware or logic device.

15 [0092] In addition, the embodiments of this specification also provide a computer-readable storage medium having one or more programs stored thereon, wherein the one or more programs include instructions; and when the instructions are executed by a portable electronic device comprising a plurality of applications, the portable electronic device may be caused to execute the method according to the embodiment shown in FIG. 1, and is used to implement the following steps:

[0093] initiating, based on a consensus master node of a blockchain, a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the consensus proposal carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus transaction;

25 [0094] matching and selecting, based on a target consensus backup node of the blockchain, the at least one pending-consensus transaction corresponding to the transaction hash list from a transaction pool of the target consensus backup node, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and

30 [0095] obtaining, based on the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on the transaction information.

[0096] It should be appreciated that when the above-described instructions are executed by a portable electronic device comprising a plurality of applications, the above-described blockchain consensus device may be caused to achieve the functions according to the embodiments shown in FIGs. 1 and 2, which will not be repeated herein.

5 [0097] Those skilled in the art should understand that the embodiments of this specification may be provided as a method, a system or a computer program product. Therefore, this specification may adopt a form of complete hardware embodiments, complete software embodiments or embodiments described in conjunction with software and hardware. In addition, this specification may adopt a form of a computer program product implemented
10 on one or more computer-usable storage media (including but not limited to disk memories, CD-ROM, optical memories, etc.) comprising computer-usable program codes.

[0098] Some embodiments of this specification are described above. Other embodiments fall within the protection scope of the appended claims. In some cases, the actions or steps stated in the claims may be performed in a sequence different from those in the embodiments
15 and the desired result may still be achieved. In addition, the processes described in the accompanying drawings do not necessarily require the specific order or sequential order shown to achieve the desired result. In some implementation manners, multitasking and parallel processing are also feasible or may be advantageous.

[0099] What described above are just embodiments of this specification, and are not
20 intended to limit this specification. For those skilled in the art, there may be various modifications and changes to this specification. Any modification, equivalent replacement, improvement and the like made within the spirit and principle of this specification shall fall within the protection scope of the claims of this specification.

What is claimed is:

1. A blockchain consensus method performed by a target consensus backup node of a blockchain, comprising:

receiving, from a consensus master node of the blockchain, a pre-prepare message in a pre-prepare stage of a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the pre-prepare message carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus transaction;

matching and selecting, from a transaction pool of the target consensus backup node, the at least one pending-consensus transaction corresponding to the transaction hash list, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and

obtaining, from the transaction pool of the target consensus backup node, transaction information of the matched at least one pending-consensus transaction, thereby executing a process flow of the consensus proposal based on the transaction information,

characterized in that the method further comprises:

after adding, by the target consensus backup node, a new transaction to the transaction pool of the target consensus backup node, calculating a transaction hash of the new transaction based on the transaction hash calculation logic, and storing a mapping relationship between the new transaction and a corresponding transaction hash thereof; and

the step of matching and selecting the at least one pending-consensus transaction corresponding to the transaction hash list comprises:

matching and selecting, from the transaction pool of the target consensus backup node, the at least one pending-consensus transaction corresponding to the transaction hash list based on the pre-stored mapping relationship.

2. The method according to claim 1, wherein before executing a processing logic of the consensus proposal based on the transaction information, the method further comprises:

if the target consensus backup node fails to match and select, from the transaction pool of the target consensus backup node, the target pending-consensus transaction corresponding to the transaction hash list, waiting until the transaction pool of the target consensus backup node is updated based on a preset delay strategy, and rematch and reselecting again, from the transaction pool of the target consensus backup node, the target pending-consensus

transaction corresponding to the transaction hash list.

3. The method according to claim 2, wherein before the step of executing a consensus logic for the pending-consensus transaction based on the transaction information, the method further comprises:

if the target consensus backup node still fails to match and select, from the transaction pool of the target consensus backup node, the target pending-consensus transaction corresponding to the transaction hash list based on the delay strategy, sending to the consensus master node a transaction synchronization request message, wherein the transaction synchronization request message carries a transaction hash of the target pending-consensus transaction not matched and selected from the transaction pool of the target consensus backup node;

receiving, by the target consensus backup node, a transaction synchronization response message fed back by the consensus master node, wherein the transaction synchronization response message carries transaction information of the target pending-consensus transaction provided by the consensus master node;

performing, by the target consensus backup node, a validity check on the target pending-consensus transaction based on the transaction information of the target pending-consensus transaction in the transaction synchronization response message, and after the validity check is performed and successful, adding the transaction information of the target pending-consensus transaction to the transaction pool of the target consensus backup node; and

matching and selecting, by the consensus backup node of the blockchain from the transaction pool of the target consensus backup node, the target pending-consensus transaction corresponding to the transaction hash list.

4. The method according to claim 2,
wherein the delay strategy comprises: a rematch count and a rematch time interval.

5. The method according to claim 2, further comprising:

marking, by the target consensus backup node, a transaction hash of a matched and selected pending-consensus transaction in the transaction hash list, wherein the target consensus backup node only matches and selects, from the transaction pool of the target consensus backup node, a pending-consensus transaction corresponding to an unmarked transaction hash in the transaction hash list.

6. The method according to any one of claims 1-5,
wherein the consensus proposal reaches a consensus based on the Practical Byzantine Fault Tolerance algorithm.

7. A blockchain target consensus device, comprising:
a consensus initiation module, configured to receive, from a consensus master node of a blockchain, a pre-prepare message in a pre-prepare stage of a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master node, wherein the pre-prepare message carries a transaction hash list, and the transaction hash list comprises a transaction hash of the at least one pending-consensus transaction;

a transaction matching module, configured to match and select, based on a target consensus backup node of the block, the at least one pending-consensus transaction corresponding to the transaction hash list from a transaction pool of the target consensus backup node, wherein all consensus nodes of the blockchain have the same transaction hash calculation logic; and

a consensus execution module, configured to obtain, based on the target consensus backup node, transaction information of the matched at least one pending-consensus transaction from the transaction pool of the target consensus backup node, thereby executing a process flow of the consensus proposal based on the transaction information,

characterized in that, once a new transaction is added to the transaction pool of the target consensus backup device, the transaction matching module is further configured to:

calculate a transaction hash of the new transaction based on the transaction hash calculation logic, and store a mapping relationship between the new transaction and a corresponding transaction hash thereof; and

match and select, from the transaction pool of the target consensus backup device, the at least one pending-consensus transaction corresponding to the transaction hash list based on the pre-stored mapping relationship.

8. A blockchain-based system comprising:
a blockchain target consensus device according to claim 7; and
a consensus master device configured to initiate a consensus proposal for at least one pending-consensus transaction in a transaction pool of the consensus master device.

9. A computer-readable storage medium having a computer program stored thereon, wherein the computer program is executed by a processor to implement the method according to any one of claims 1 to 6.