

Description

The invention relates to a display device comprising two supporting plates, a plurality of picture elements which are formed by the crossing areas of strip-shaped electrodes on the facing surfaces of the supporting plates, orienting layers on the electrodes and the exposed surface of the supporting plates, a layer of cholesteric liquid crystal between the supporting plates, said liquid crystal, upon applying an electric field across the layer, having a focal-conic texture below a given field strength E_1 and having a homeotropic-nematic texture above a given field strength E_2 , and having one of the said textures for a field strength between E_1 and E_2 , the facing surfaces of the supporting plates furthermore comprising first ridges at the edges of each picture element, on which ridges the distance between the opposed electrodes is such as to maintain a field strength above E_2 and thus to maintain the liquid crystal in the homeotropic-nematic texture, if a field strength between E_1 and E_2 prevails in the central part of the picture element.

A cholesteric liquid crystal is to be understood to mean herein a nematic liquid crystal to which a certain quantity of cholesteric liquid crystal has been added and which mixture has a cholesteric texture.

Such a display device is known from US-A-4,264,149 and may be used for displaying alphanumeric or picture information. In this known device the bistability effect is used which cholesteric liquid crystals show. In this effect there is a substantially transparent cholesteric texture in which the axes of the helices are at right angles to the surfaces of the supporting plates. Above a given threshold value E_m of the field strength, the substantially transparent cholesteric texture changes into a light-scattering focal-conic texture in which the axes of the helices extend parallel to the surfaces of the supporting plates. When the field strength increases the helices uncoil and the light-scattering focal-conic texture changes into a transparent homeotropic-nematic texture above a field strength E_2 . As a result of the hysteresis in the transmission versus field strength characteristic the transparent homeotropic-nematic texture changes back into the light-scattering focal-conic texture only at a field strength E_1 smaller than the field strength E_2 . This focal-conic texture is maintained for a longer period of time in the field-free state.

As a result of the said hysteresis, the liquid crystal layer, at a field strength between E_1 and E_2 , may be either in the transparent homeotropic-nematic texture or in the light-scattering focal-conic texture dependent on whether the field strength started from a value higher than E_2 or a value lower than E_1 .

In the matrix display device described in the said Patent Specification the said bistability effect is used as follows. The electrodes are provided on the supporting plates in the form of parallel strips. The electrodes on one supporting plate cross the

electrodes on the other supporting plate. The electrodes on one supporting plate constitute the so-called rows and the electrodes on the other supporting plate constitute the so-called columns of the matrix. The picture elements are present at the crossings of the two and column electrodes. All picture elements of the matrix are brought into the transparent homeotropic-nematic texture by a sufficiently high voltage at the electrodes which results in a field strength above E_2 across the liquid crystal layer. A voltage which results in a field strength E_m between E_1 and E_2 is then applied across all elements. The liquid crystal layer now has the property of remaining in the transparent homeotropic-nematic state for some time. The rows are successively driven and the information is written on the columns per row. For the elements which have to change into the scattering state the voltage is made zero until the homeotropic-nematic texture changes into the focal-conic texture. The remaining elements of a row during writing are kept at a voltage which results in a field strength larger than or equal to E_m and consequently remain in the transparent homeotropic-nematic texture. A voltage which results in a field strength E_m across the liquid crystal layer is then applied again across all elements of a row.

During the time in which a transparent homeotropic-nematic state of a line remains stable, other lines can be driven. The stability of the transparent homeotropic-nematic texture at a field strength E_m , however, is restricted in that the surroundings of a picture element are in the focal-conic state. The focal-conic texture as a matter of fact has the property of growing into parts of the liquid crystal which have the homeotropic-nematic texture, which results in disturbing light-scattering effects. In order to prevent the growth of the focal-conic texture into the homeotropic-nematic texture, the edges of each picture element are maintained above a field strength E_2 if a field strength between E_1 and E_2 prevails in the central part of the picture element. In the known device this is realized in that ridges separated by grooves are provided on the facing surfaces of the supporting plates. The grooves in one supporting plate are oriented at right angles to the grooves in the other supporting plate. The strip-shaped electrodes are provided in the grooves and extend onto the ridges and on the ridges are separate from each other by a narrow strip.

It has been found, however, that the homeotropic-nematic texture at a field strength between E_1 and E_2 can be disturbed not only by the focal-conic texture growing-in from the surroundings of a picture element, but also by the focal-conic texture starting to grow from within a picture element. This is caused by unevennesses and damage to the electrodes and by dust particles which form growth nuclei for the formation of the focal-conic texture. It is to be noted that this phenomenon is known *per se* from the article "Nucleation of Focal-Conic Domains in the Field-Induced Nematic Texture of a Cholesteric Liquid

Crystal", Japanese Journal of Applied Physics, Vol 17, No. 2, February 1978, pp. 391—394.

It is therefore the object of the invention to provide a display device with which disturbing effects caused by the formation of the focal-conic texture within a picture element are prevented as much as possible. For that purpose, a display device of a kind mentioned in the opening paragraph is characterized according to the invention in that the facing surfaces of the supporting plates also comprise second ridges which extend through each picture element thus forming the edges of a number of sub-elements within the picture element, on which second ridges the distance between the opposed electrodes is such as to maintain a field strength above E_2 and thus to maintain the edges of each sub-element in the homeotropic-nematic texture if a field strength between E_1 and E_2 prevails at the area of the picture element. By dividing each picture element into many smaller sub-elements surrounded by an edge where a field strength prevails larger than E_2 , the growth of the focal-conic texture resulting from surface-inhomogeneities is restricted to one or a few sub-elements. The focal-conic texture, as a result of this, cannot expand over the whole picture element and thus remains substantially unnoticeable.

A first embodiment of a display device in accordance with the invention is characterized in that on each supporting plate the first ridges are separated from each other by grooves, the height of the first ridges above the bottom of the grooves being substantially equal to half the maximum thickness of the layer of liquid crystal, that second ridges are provided in each groove, and that the electrode strips are provided in the grooves extending continuously from each one of the first ridges over the second ridges of this groove onto the next one of the first ridges, adjacent electrode strips being separated from each other by an electrodeless strip on the first ridges. The picture elements are each divided into many sub-elements by the second ridges. If the liquid crystal in a sub-element at a field strength between E_1 and E_2 is in the homeotropic-nematic or in the focal-conic state, such a high field strength prevails at the area of the second ridges that the liquid crystal at the area is in the stable homeotropic-nematic state above a field strength E_2 .

A second embodiment is characterized in that the height of the second ridges is substantially equal to the height of the first ridges. The second ridges as well as the first ridges serve as spacing elements for the supporting plates.

In the first and second embodiments the liquid crystal orienting layer provided on the electrodes and on the exposed surface of supporting plates may be electrically insulating so as to prevent short-circuit between the electrodes of the supporting plates. Instead of an insulating orienting layer the orienting layer may alternatively be provided on an electrically insulating intermediate layer. This intermediate layer may also serve

to improve the adhesion of the orienting materials.

A third embodiment of a display device in accordance with the invention is characterized in that a boss is present at the area of the electrodeless strip between two electrodes on the first ridges. The supporting plates engage each other with the bosses. As a result of this the orienting layer need no longer be electrically insulating.

The invention will now be described in greater detail with reference to the accompanying drawing, of which

Figure 1 illustrates the operating principle of a display device embodying the invention,

Figure 2 shows a first embodiment of a display device partly broken away, and

Figure 3 is a cross-sectional view of a part of the device according to a second embodiment.

Figure 1a shows a field strength versus transmission characteristic of a display device using the bistability effect of a cholesteric liquid crystal. The longitudinal axes of the liquid crystal molecules at the interface with the electrodes are oriented at right angles to the electrode surface. For that purpose the electrode surface has been subjected in known manner to a surface treatment. Initially the liquid crystal has a transparent planar-conic texture in which the axes of the helices are at right angles to the surface of the supporting plates as is shown diagrammatically in Fig. 1b.

The pitch of the helices depends on the composition of the nematic-cholesteric liquid crystal mixture and on the cholesteric liquid crystal used. Upon applying a voltage across the electrodes the transparent planar-conic texture changes into a light-scattering focal-conic texture, as is shown in Fig. 1c, at a field strength dependent on the liquid crystal used. The axes of the helices rotate into a direction parallel to the plates. When the field strength increases above a given value E_2 the helices uncoil and a transparent homeotropic-nematic texture is formed as is shown in Fig. 1d. When the field strength decreases the transparent homeotropic-nematic texture is maintained until a field strength $E_1 < E_2$, below which field strength the light-scattering focal-conic texture is again formed. The focal-conic texture is maintained when the field strength across the electrodes decreases. In the field-free state the focal-conic texture changes only slowly into the planar-conic texture. The times required for this purpose, however, are large as compared with the switching times which are usual in a matrix control so that the planar-conic texture does not occur in an operating matrix display device. At a field strength $E_1 < E_2 < E_2$ the liquid crystal layer is in a transparent homeotropic-nematic state when the field strength is initially higher than E_2 or is in a light-scattering focal-conic state when the field strength is initially lower than E_1 .

The above-mentioned effects also occur in the case in which the liquid crystal molecules are not oriented at right angles to but parallel to the

electrodes. The transparent cholesteric texture in which the axes of the helices are at right angles to the surfaces of the supporting plates, however, is termed Grand-Jean texture instead of planar-conic texture.

Figure 2 is a first embodiment of a display device partly broken away. The display device comprises two glass supporting plates 1 and 2 between which a layer of cholesteric liquid crystal is present. The facing surfaces of the supporting plates 1 and 2 have first ridges 3 having a largest width of 300 μm which are present at a mutual pitch of 1.20 mm. A number of second ridges 4 having a largest width of 20 μm are present at a mutual pitch of 100 μm between two first ridges 3. The height of the first and second ridges 3 and 4 is 6 μm . At the given dimensions, each time nine second ridges 4 are present between two first ridges 3 but only a few are shown in the Figure for the sake of clarity.

The first and second ridges 3 and 4 are provided by coating a glass plate first with a nickel-phosphorus layer and providing thereon in known manner a mask for forming the ridges 3 and 4 by means of a photolacquer. Etching is then carried out with a solution of ammonium fluoride and hydrogen fluoride. The depth of the grooves present between the first and second ridges 3 and 4 is controlled by the duration of etching and the concentration of the etching liquid. This manner of etching results in grooves the depth of which is well homogeneous throughout the glass plate. Grooves having a depth of approximately 4–15 μm can be obtained by etching. The first and second ridges 3 and 4 may also be provided by means of silk-screen printing on a glass plate. The first and second ridges 3 and 4 may also be manufactured from a photolacquer. In that case a layer of photolacquer is provided on each of the supporting plates and is exposed via a mask. The non-exposed parts are dissolved and the remaining exposed parts form the ridges. Electrodes 5 which extend across the second ridges 4 onto the first ridges 3 are provided on the glass plates 1 and 2.

The electrodes 5 are separated from each other by a 100 μm wide strip on the first ridges 3. The electrodes 5 are provided by first covering the entire glass plates 1 and 2 provided with the ridges 3 and 4 with an approximately 0.1 μm thick layer of indium oxide and/or tin oxide. After providing a mask the electrode pattern is etched by means of a solution of ferricchloride and hydrochloric acid ($\text{FeCl}_3 + \text{HCl}$). The electrodes 5 on glass plate 1, for example, constitute in this manner the rows and the electrodes 5 on the glass plate 2 constitute the columns of a matrix of picture elements. An insulating layer 7 of SiO_2 is sputtered on the whole surface of the glass plates 1 and 2 in a thickness of 0.5 μm . In order to obtain a homeotropic orientation of the liquid crystal at the surface of the supporting plates, the insulating layer 7 is treated, for example, with a solution of perfluorosilane in hexane. Instead of providing an orienting layer on an insulating intermediate

layer, it is also possible to directly provide an insulating orienting layer. The first and second ridges 3 and 4 of the supporting plates 1 and 2 contact each other at the crossings and hence ensure that the supporting plates are kept at the correct distance from each other throughout the surface of the device. The picture elements of the matrix are present at the crossings of the electrodes 5 on the supporting plates 1 and 2. Each picture element has four edges which are formed by the parts of the electrode 5 present on the ridges 3. At the area of said edges the thickness of the layer of liquid crystal is twice as small as the maximum thickness of the layer in a picture element. As a result of this the edges of a picture element are in the homeotropic-nematic texture at a field strength above E_2 if the picture element itself is in the homeotropic-nematic or in the focal-conic texture at a field strength between E_1 and E_2 . Herewith it is prevented that the focal-conic texture with which a picture element is surrounded grows into the homeotropic-nematic texture of the picture element.

The nine ridges 4 in the example described divide each picture element into 100 sub-elements. The edges of the sub-elements are formed by the ridges 4. At the area of the ridges 4 the layer of liquid crystal is twice as thin as at the area of the central part of the sub-elements. If within a sub-element the focal-conic texture is formed as a result of an inhomogeneity in or contamination of the surface of the electrodes, said structure cannot expand over the whole picture element. The focal-conic structure is restricted to one single sub-element by the field strength higher than E_2 which prevails at the edges of the sub-element.

In the embodiment shown the two ridges 4 have the same height as the first ridges 3. The second ridges 4 however, may also be lower than the first ridges 3 if only the field strength at the edges of a sub-element is higher than E_2 .

A second embodiment will be described with reference to Figure 3 which is a sectional view of a part of the device and in which the same components are referred to by the same reference numerals as in Figure 2. The supporting plates 1 and 2 again comprise first ridges 3 and second ridges 4 on which electrodes 5 are provided. However, a boss 10 having a width of 40 μm and a height of 2.5 μm is present on the strip between the electrodes 5 on the ridges 3. The height of the second ridges 4 is 3.5 μm . The further dimensions of the ridges are the same as in Fig. 2. An orienting layer is provided on each one of the supporting plates 1 and 2, which layer need not be electrically insulating since the supporting plates 1 and 2 engage each other with the bosses 10. At the area of the edges of the picture elements and at the area of the edges of the sub-elements the layer of liquid crystal has a smaller thickness than in the central parts of the sub-elements. These edges are in the homeotropic-nematic texture at a field strength above E_2 if the central parts of the sub-elements are in the

homeotropic-nematic texture at a field strength between E_1 and E_2 . Herewith the growing-in of the focal-conic texture from adjacent picture elements is again prevented and the formation of the focal-conic texture as a result of inhomogeneities at the surface is restricted to one single sub-element.

Claims

1. A display device comprising two supporting plates, a plurality of picture elements which are formed by the crossing areas of strip-shaped electrodes on the facing surfaces of the supporting plates, orienting layers on the electrodes and the exposed surface of the supporting plates, a layer of cholesteric liquid crystal between the supporting plates, said liquid crystal, upon applying an electric field across the layer, having a focal-conic texture below a given field strength E_1 and having a homeotropic-nematic texture above a given field strength E_2 , and having one of the said textures for the field strength between E_1 and E_2 , the facing surfaces of the supporting plates furthermore comprising first ridges at the edges of each picture element, on which ridges the distance between the opposed electrodes is such as to maintain a field strength above E_2 and thus to maintain the liquid crystal in the homeotropic-nematic texture, if a field strength between E_1 and E_2 prevails in the central part of the picture element, characterized in that the facing surfaces of the supporting plates also comprise second ridges which extend through each picture element thus forming the edges of a number of sub-elements within the picture element, on which second ridges the distance between the opposed electrodes is such as to maintain a field strength above E_2 and thus to maintain the edges of each sub-element in the homeotropic-nematic texture if a field strength between E_1 and E_2 prevails at the area of the picture element.

2. A display device as claimed in Claim 1, characterized in that on each supporting plate the first ridges are separated from each other by grooves, the height of the first ridges above the bottom of the grooves being substantially equal to half the maximum thickness of the layer of liquid crystal, that second ridges are provided in each groove, and that the electrode strips are provided in the grooves extending continuously from each one of the first ridges over the second ridges of this groove onto the next one of the first ridges, adjacent electrode strips being separated from each other by an electrodeless strip on the first ridges.

3. A display device as claimed in Claim 2, characterized in that the height of the second ridges is substantially equal to the height of the first ridges.

4. A display device as claimed in Claim 2 or 3, characterized in that a boss is present at the area of the electrodeless strip between two electrodes on the first ridges.

5. A display device as claimed in Claim 1, 2, 3 or

4, characterized in that the orienting layers on the electrodes and on the exposed surface of the supporting plates are electrically insulating layers.

6. A display device as claimed in Claim 1, 2, 3 or 4, characterized in that the orienting layers are provided on an electrically insulating intermediate layer which is provided on the electrodes and on the exposed surface of the supporting plates.

Patentansprüche

1. Anzeigevorrichtung mit zwei Trägerplatten, einer Anzahl von Bildelementen, die durch die sich kreuzenden Bereiche streifenförmiger Elektroden auf den einander zugewandten Oberflächen der Trägerplatten, gebildet werden mit orientierenden Schichten auf den Elektroden den freiliegenden Oberfläche der Trägerplatten, mit einer cholesterischen Flüssigkristallschicht zwischen der Trägerplatten, wobei der Flüssigkristall nach dem Anlegen eines elektrischen Feldes über die Schicht unter einer gegebenen Feldstärke E_1 eine fokalkonische Textur und über einer gegebenen Feldstärke E_2 eine homeotropisch-nematische Textur besitzt, und für eine Feldstärke zwischen E_1 und E_2 eine der erwähnten Texturen besitzt, wobei die einander zugewandten Oberflächen der Trägerplatten weiter erste Ränder an den Kanten jedes Bildelements besitzen, auf welchen Rändern der Abstand zwischen den einander gegenüberliegenden Elektroden einen derartigen Wert hat, dass eine Feldstärke über E_2 aufrechterhalten und so der Flüssigkristall in der homeotropisch-nematischen Textur erhalten wird, wenn eine Feldstärke zwischen E_1 und E_2 im zentralen Teil des Bildelements vorherrscht, dadurch gekennzeichnet, dass die einander zugewandten Oberflächen der Trägerplatten ebenfalls zweite Rändern enthalten, die sich durch jedes Bildelement erstrecken und so die Kanten einer Anzahl von Unterelementen innerhalb des Bildelements bilden, auf welchen zweiten Rändern der Abstand zwischen den einander gegenüberliegenden Elektroden einen derartigen Wert hat, dass eine Feldstärke über E_2 aufrechterhalten und so die Kanten jedes Unterelements in der homeotropisch-nematischen Textur erhalten wird, wenn eine Feldstärke zwischen E_1 und E_2 im Bereich des Bildelements vorherrscht.

2. Anzeigevorrichtung nach Anspruch 1, dadurch gekennzeichnet, dass auf jeder Trägerplatte die ersten Ränder durch Rillen voneinander getrennt sind, wobei die Höhe der ersten Ränder über dem Boden der Rillen im wesentlichen gleich der halben maximalen Dicke der Flüssigkristallschicht beträgt, dass in jeder Rille zweite Ränder vorgesehen sind, und dass sich die Elektrodenstreifen in den Rillen von jedem der ersten Ränder über die zweiten Ränder dieser Rille zum folgenden der ersten Ränder erstrecken, wobei benachbarte Elektrodenstreifen durch einen elektrodenfreien Streifen auf den ersten Rändern voneinander getrennt sind.

3. Anzeigevorrichtung nach Anspruch 2, dadurch gekennzeichnet, dass die Höhe der zweiten

homeotropic-nematic texture at a field strength between E_1 and E_2 . Herewith the growing-in of the focal-conic texture from adjacent picture elements is again prevented and the formation of the focal-conic texture as a result of inhomogeneities at the surface is restricted to one single sub-element.

Claims

1. A display device comprising two supporting plates, a plurality of picture elements which are formed by the crossing areas of strip-shaped electrodes on the facing surfaces of the supporting plates, orienting layers on the electrodes and the exposed surface of the supporting plates, a layer of cholesteric liquid crystal between the supporting plates, said liquid crystal, upon applying an electric field across the layer, having a focal-conic texture below a given field strength E_1 , and having a homeotropic-nematic texture above a given field strength E_2 , and having one of the said textures for the field strength between E_1 and E_2 , the facing surfaces of the supporting plates furthermore comprising first ridges at the edges of each picture element, on which ridges the distance between the opposed electrodes is such as to maintain a field strength above E_2 and thus to maintain the liquid crystal in the homeotropic-nematic texture, if a field strength between E_1 and E_2 prevails in the central part of the picture element, characterized in that the facing surfaces of the supporting plates also comprise second ridges which extend through each picture element thus forming the edges of a number of sub-elements within the picture element, on which second ridges the distance between the opposed electrodes is such as to maintain a field strength above E_2 and thus to maintain the edges of each sub-element in the homeotropic-nematic texture if a field strength between E_1 and E_2 prevails at the area of the picture element.

2. A display device as claimed in Claim 1, characterized in that on each supporting plate the first ridges are separated from each other by grooves, the height of the first ridges above the bottom of the grooves being substantially equal to half the maximum thickness of the layer of liquid crystal, that second ridges are provided in each groove, and that the electrode strips are provided in the grooves extending continuously from each one of the first ridges over the second ridges of this groove onto the next one of the first ridges, adjacent electrode strips being separated from each other by an electrodeless strip on the first ridges.

3. A display device as claimed in Claim 2, characterized in that the height of the second ridges is substantially equal to the height of the first ridges.

4. A display device as claimed in Claim 2 or 3, characterized in that a boss is present at the area of the electrodeless strip between two electrodes on the first ridges.

5. A display device as claimed in Claim 1, 2, 3 or

4, characterized in that the orienting layers on the electrodes and on the exposed surface of the supporting plates are electrically insulating layers.

6. A display device as claimed in Claim 1, 2, 3 or 4, characterized in that the orienting layers are provided on an electrically insulating intermediate layer which is provided on the electrodes and on the exposed surface of the supporting plates.

Patentansprüche

1. Anzeigevorrichtung mit zwei Trägerplatten, einer Anzahl von Bildelementen, die durch die sich kreuzenden Bereiche streifenförmiger Elektroden auf den einander zugewandten Oberflächen der Trägerplatten, gebildet werden mit orientierenden Schichten auf den Elektroden den freiliegenden Oberfläche der Trägerplatten, mit einer cholesterischen Flüssigkristallschicht zwischen der Trägerplatten, wobei der Flüssigkristall nach dem Anlegen eines elektrischen Feldes über die Schicht unter einer gegebenen Feldstärke E_1 eine fokalkonische Textur und über einer gegebenen Feldstärke E_2 eine homeotropisch-nematische Textur besitzt, und für eine Feldstärke zwischen E_1 und E_2 eine der erwähnten Texturen besitzt, wobei die einander zugewandten Oberflächen der Trägerplatten weiter erste Ränder an den Kanten jedes Bildelements besitzen, auf welchen Rändern der Abstand zwischen den einander gegenüberliegenden Elektroden einen derartigen Wert hat, dass eine Feldstärke über E_2 aufrechterhalten und so der Flüssigkristall in der homeotropisch-nematischen Textur erhalten wird, wenn eine Feldstärke zwischen E_1 und E_2 im zentralen Teil des Bildelements vorherrscht, dadurch gekennzeichnet, dass die einander zugewandten Oberflächen der Trägerplatten ebenfalls zweite Rändern enthalten, die sich durch jedes Bildelement erstrecken und so die Kanten einer Anzahl von Unterelementen innerhalb des Bildelements bilden, auf welchen zweiten Rändern der Abstand zwischen den einander gegenüberliegenden Elektroden einen derartigen Wert hat, dass eine Feldstärke über E_2 aufrechterhalten und so die Kanten jedes Unterelements in der homeotropisch-nematischen Textur erhalten wird, wenn eine Feldstärke zwischen E_1 und E_2 im Bereich des Bildelements vorherrscht.

2. Anzeigevorrichtung nach Anspruch 1, dadurch gekennzeichnet, dass auf jeder Trägerplatte die ersten Ränder durch Rillen voneinander getrennt sind, wobei die Höhe der ersten Ränder über dem Boden der Rillen im wesentlichen gleich der halben maximalen Dicke der Flüssigkristallschicht beträgt, dass in jeder Rille zweite Ränder vorgesehen sind, und dass sich die Elektrodenstreifen in den Rillen von jedem der ersten Ränder über die zweiten Ränder dieser Rille zum folgenden der ersten Ränder erstrecken, wobei benachbarte Elektrodenstreifen durch einen elektrodenfreien Streifen auf den ersten Rändern voneinander getrennt sind.

3. Anzeigevorrichtung nach Anspruch 2, dadurch gekennzeichnet, dass die Höhe der zweiten



Ränder im wesentlichen gleich der Höhe der ersten Ränder ist.

4. Anzeigevorrichtung nach Anspruch 2 oder 3, dadurch gekennzeichnet, dass im Bereich des elektrodenfreien Streifens zwischen zwei Elektroden auf den ersten Rändern eine Erhöhung vorgesehen ist.

5. Anzeigevorrichtung nach Anspruch 1, 2, 3 oder 4, dadurch gekennzeichnet, dass die orientierenden Schichten auf den Elektroden und auf der freien Oberfläche der Trägerplatten elektrisch isolierende Schichten sind.

6. Anzeigevorrichtung nach Anspruch 1, 2, 3 oder 4, dadurch gekennzeichnet, dass die orientierenden Schichten auf einer elektrisch isolierenden Zwischenschicht vorgesehen sind, die auf den Elektroden und auf der freien Oberfläche der Trägerplatten vorgesehen ist.

Revendications

1. Dispositif d'affichage comportant deux plaques de support, une pluralité d'éléments d'image qui sont formés aux zones de croisement d'électrodes en forme de bande sur les faces situées vis-à-vis des plaques de support, des couches d'orientation sur les électrodes et la surface exposée des plaques de support, une couche de cristal liquide cholestérique entre les plaques de support, ledit cristal liquide présentant, après application d'un champ électrique dans la couche, une texture focale-conique au-dessous d'une certaine intensité de champ E_1 et une texture homéotropique-nématique au-dessus d'une certaine intensité de champ E_2 , et présentant l'une desdites textures pour une intensité de champ comprise entre E_1 et E_2 , les surfaces situées vis-à-vis des plaques de support comportant en outre des premières nervures aux bords de chaque élément d'image, nervures auxquelles la distance comprise entre les électrodes situées vis-à-vis est telle qu'une intensité de champ est maintenue au-dessus de E_2 afin de maintenir ainsi le cristal liquide dans la texture homéotropique-nématique si une intensité de champ entre E_1 et E_2 règne dans la partie centrale de l'élément d'image, caractérisé en ce que les surfaces si-

tuées vis-à-vis des plaques de support comportent également des deuxième nervures qui s'étendent à travers chaque élément d'image, formant ainsi les bords de plusieurs sous-éléments dans l'élément d'image, nervures auxquelles la distance comprise entre les électrodes situées vis-à-vis est telle qu'une intensité de champ supérieure à E_2 est maintenue et que les bords de chaque sous-élément dans la texture homéotropique-nématique sont maintenus si une intensité de champ comprise entre E_1 et E_2 règne dans la zone de l'élément d'image.

2. Dispositif d'affichage selon la revendication 1, caractérisé en ce que sur chaque plaque de support, les premières nervures sont séparées les unes des autres par des rainures, la hauteur des premières nervures au-dessus du fond des rainures étant pratiquement égale à la moitié de l'épaisseur maximale de la couche de cristal liquide, que des deuxième nervures sont appliquées dans chaque rainure, et que les bandes d'électrode sont appliquées dans les rainures s'étendant de façon continue à partir de chacune des premières nervures sur les deuxième nervures de cette rainure jusqu'à la nervure prochaine des premières rainures, des bandes d'électrode adjacentes étant séparées les unes des autres par une bande sans électrodes sur la première nervure.

3. Dispositif d'affichage selon la revendication 2, caractérisé en ce que la hauteur des deuxième nervures est pratiquement égale à la hauteur des premières nervures.

4. Dispositif d'affichage selon la revendication 2 ou 3, caractérisé en ce qu'une saillie est présente dans la zone de la bande sans électrodes entre deux électrodes sur la première nervure.

5. Dispositif d'affichage selon la revendication 1, 2, 3 ou 4, caractérisé en ce que les couches d'orientation sur les électrodes et sur la surface exposée des plaques de support sont des couches électro-isolantes.

6. Dispositif d'affichage selon la revendication 1, 2, 3 ou 4, caractérisé en ce que la couche d'orientation est appliquée sur une couche intermédiaire électro-isolante qui est appliquée sur les électrodes et sur la surface exposée des plaques de support.

