

SYSTEMS AND METHODS FOR INTERACTIONS BETWEEN TICKET HOLDERS AND SELF SERVICE FUNCTIONS

This invention relates to automated interactions with passenger services such as baggage
5 handling. In particular, but not exclusively, it is concerned with the handling of baggage at
airports, seaports, railways, other mass transport locations, venues, stadiums and arenas.

In the airport environment, checking-in of baggage can be a time consuming and stressful
experience for passengers. At busy times long queues can form caused partly by the slow,
manned check-in process which includes ground staff printing bag tags for each item of
10 baggage and fixing those tags to the baggage item.

The baggage check-in process represents a high cost overhead to airports and airlines due
to ongoing operational and maintenance costs of the bag tagging equipment together with
staff costs associated with the check-in process and maintenance.

In recent years some steps have been taken to reduce these costs and to streamline the
15 check-in process and reduce queueing times for passengers. For example many airlines
now provide on-line check-in services which require passengers only to drop their bags when
they arrive at the airport. More recently some airlines have introduced semi-automated self-
service bag drops where a bag tag is generated from a scan of a boarding pass and affixed
by the passenger. Some airlines have adopted a hybrid approach using a combined self-
20 service and ground staff assisted facility. Although these measures have gone some way
to alleviate the problems discussed above they all require some sort of interaction between
a passenger and a ground agent, kiosk or other computerised equipment. These solutions
themselves generate further problems as they require significant modifications to the check-
in counters at airports and considerable investment in the self-service equipment. Both of
25 these are costly and operationally complex.

In addition to the above issues there is an increasing awareness of the needs of disabled
passengers. Many countries have legislated to ensure that disabled and reduced mobility
passengers are adequately supported at airports. An example is EU regulation 1107/2006
which identifies the check-in and baggage registration and drop off processes as areas where
30 the airport is responsible for the provision of assistance to disabled or reduced mobility
passengers. Existing or future legislation requires access to any automated or self-service
bag drop solution and may require, for example, specified maximum height of touch access

for wheelchair access and specified additional control devices for visually impaired passengers.

The invention aims to address and to ameliorate these problems.

According to one aspect of the invention there is provided a method of facilitating
5 interaction between a ticket holder and a self-service function related to the ticket,
comprising the steps of: detecting by a mobile device proximity to a self-service function,
the mobile device having stored thereon information relating to the ticket and the self-
service function being related to the ticket; on detection by the mobile device of proximity to
10 the location, activating an application on the mobile device, the application being related to
the self-service function; and communicating to the mobile device via the application,
information about the self-service function including directional information.

The invention also provides a system for facilitating interaction between a ticket holder and
a self-service function related to the ticket, comprising: a self-service function; a mobile
device, the mobile device having stored thereon information relating to the ticket; at least
15 geolocation device; wherein the mobile device is configured to detect the geolocation
device at a location proximate a self-service function, and at least one server having stored
thereon computer software for performing the steps of: on detection by the mobile device of
the geolocation device proximate the location, activating an application on the mobile
device, the application being related to the self-service function; and communicating to the
20 mobile device via the application, information about the self-service function including
directional information.

A second aspect of the invention provides a method of facilitating interaction between a
ticket holder and a self-service function related to the ticket, comprising the steps of: at a
location proximate a self-service function related to the ticket activating an application on
25 the mobile device, the application being related to the self-service function and the mobile
device having stored thereon information relating to the ticket; and communicating to the
mobile device via the application, information about the self-service function including
directional information.

Embodiments of the invention may have the advantage of simplifying interaction between
30 ticket holders and self service functions. In one preferred embodiment the self-service
function is a bag drop system, for example for use in an airport. Embodiments of the
invention may have the advantage of making interactions with the bag drop more simple,
and enabling airline or other service providers to reduce the amount of human interaction

required in the bag drop, and other self-service processes and so reduce cost and overheads.

In one embodiment of the invention the ticket relates to a passenger journey and includes passenger and journey identification. The ticket information may comprise a boarding
5 pass. In one embodiment the presence of the mobile device at the location may be detected using a geolocation device, for example a Bluetooth beacon.

In one embodiment the application queries ticket information stored on the mobile device and communicates the ticket information to a remote server. The remote server, in response to receipt of the ticket information provides information relating to the self-service
10 function to the application for presentation to the user of the mobile device.

In one embodiment the self-service function is a bag drop and the information relating to the ticket is a boarding pass, passenger information in the boarding pass is communicated to a departure control system. The departure control system may determine whether baggage relating to the boarding pass is eligible for bag drop and communicates the
15 eligibility to the mobile device.

In one embodiment of the invention, on deposit of a bag at a bag drop, the bag is weighed and a determination made as to whether the weight exceeds an allowable weight and, if the weight exceeds an allowable weight arrangements are made for payment of an excess baggage fee via the application.

20 In one embodiment a bag tag is printed at the bag drop and instructions for fixing the bag tag to a bag are communicated for presentation to the user to the mobile device via the application.

In one embodiment, on receipt of a bag by the bag drop, information about boarding and routing to a departure gate is communicated to the application.

25 Embodiments of the invention will now be described, by way of example only, and with reference to the accompanying drawings, in which:

Figure 1 is a schematic overview of an embodiment of the invention;

Figure 2 is a flow chart illustrating the steps in an embodiment of the invention;

Figure 3 shows an overview of a system embodying the invention;

Figure 4 shows the logical architecture of the system;

Figure 5 illustrates the logical architecture of the Cloud service;

Figure 6 is a class diagram showing a service model indicating available interfaces;

Figure 7 schematically illustrates the Bag Unit Controller;

5 Figure 8 illustrates the high level interactions occurring at the mobile device application;

Figure 9 is a process flow diagram for the mobile app; and

Figure 10 is a process flow diagram for the overall system.

Description of Preferred Embodiments

10 In the examples given below the bag drop sequence is initiated from a passenger smart phone, tablet, laptop or similar mobile computing device. Geo-location technology such as Bluetooth beacons or other location sensors are used to enable an app on a mobile device to detect when it is proximate a given beacon or other device. However, automatic location detection is not essential to the invention. Although described in relation to bag drop, 15 embodiments of the invention may also be used in conjunction with other passenger interactions such as passenger processing kiosks for printing bag tags, boarding passes, scanning passports and other functions, interactions with mobile enabled payments via the passengers smartphone or other device, and interactions with other airport facilities including, but not limited to self-service checkpoints and gates, for example automated passport control gates or barriers. Embodiments are described with specific reference to 20 airports but the invention has broader applicability to any travel environment in which a passenger is required to check-in or drop baggage and so includes sea ports and railways. Embodiments of the invention may also be used for mass ticketing events to assist in directing spectators and audiences, for example sporting venues and entertainments such as concerts and festivals.

25 In the embodiments shown in the Figures, which relate specifically to an airport solution, location technology such as Bluetooth beacons distributed around an airport is used to enable a passenger's mobile device such as a smart phone, tablet, laptop or other device to identify the presence of a given beacon. Any other indoor or outdoor geo-location technology may be used to enable the device to identify its relative location. However, as will become 30 clear, although preferred, Bluetooth beacons or other location technology is not essential to

the invention. The mobile device has a bag drop application which is downloaded by the passenger. This application may be a unique bag drop app or a bag drop module of an airline or airport app. The mobile device 10 detect the presence of the location devices, for example when it enters the airport and passes proximate to a first beacon 12. As the passenger passes through the airport toward the bag drop area, the second beacon 14 is detected by the device 10 which initiates the bag drop application on the device. The detection by the passenger's mobile device of the first beacon on entry to the airport is not essential but is advantageous as detection of beacons by the device enables interaction with other services that are provided in the airport.

10 The use of beacon detection to track the movement of a passenger through an airport or similar environment is described in WO2013117723.

Once the application has been initiated it either queries the passengers booking details from their mobile boarding pass stored on the phone, for example using Apple® wallet or similar apps, or, where there is no stored boarding pass, asks the passenger to scan their printed boarding pass either using their device's camera or a scanner provided at the bag drop.

Where a mobile boarding pass is stored on the device, the app will identify from the stored passenger related data whether or not the passenger has checked in a bag and, if so, how many. Where a bag has been checked in the app then causes instructions to be displayed to the passenger on how to proceed with the bag drop process. Where no check-in bag is detected, the app may give the passenger the option of amending their booking to permit check-in.

Where the interaction is with a different self-service function the process functions in a similar manner. For example where the function is self-service passport control the app, which is again a unique app or a module of an airline or airport app, detects the presence of the device in a passport check area and presents instructions to the user via the device display as to how to proceed and how to negotiate the passport scanner.

Thus, in one embodiment, the system uses a passenger Smartphone or other mobile device, and, optionally, any indoor or outdoor geo-location technology such as Bluetooth beacons or other types of sensors and mapping applications, to automate the Bag Drop process or any other passenger process which requires interaction with a system at an airport or other associated locations. When in the proximity of a Bag Drop area, a Passenger Processing kiosk or station, a checkpoint or e-gate, a mobile app on the passenger's Smartphone or other mobile device activates, and the passenger and their

booking details are identified. The passenger device "pairs" with the Bag Drop unit and further instructions on how to manage the Bag Drop are all executed electronically/wirelessly via the Smartphone or mobile device. The system comprises a mobile application on, for example, a smartphone, a processing unit (controller) connected to the bag drop unit, and a cloud based API service which mediates, or "proxies" the interaction between the mobile application and the bag drop unit as is described in more detail below.

Although the embodiment described below uses Bluetooth as a trigger mechanism to pair a mobile device with the baggage system, other methods are possible. For example another type of automatic pairing such as another Near Field Communication (NFC), WIFI or BLE beacons could be used or a manual method such as a QR or another barcode which is scanned by the mobile device owner to launch the application, or a voice activation command such as Amazon Alexa TM. Where barcodes are used the passenger may scan a 2-D barcode on a sticker at a check in desk or photograph the code in known manner. In order to address security concerns barcodes may be produced using e-ink and changed regularly. For the sake of clarity communications between the mobile device and the baggage handling system is via an API service as described below using WIFI or another communications protocol.

The process in relation to bag drop is shown in more detail in Figure 2 which is presented from the perspective of the passenger. The process is shown generally at 100. At step 102 the passenger checks-in on-line via their smartphone or other mobile device. As mentioned above this could be via a specific application or via a check in module on the airlines website. As part of the check-in process a mobile boarding pass is created which includes various passenger information including passenger ID and baggage allowance. The boarding pass is stored in a suitable storage location on the mobile device. An example of a suitable storage location is the Apple wallet application on devices running Apple IOS or Google PassWallet on devices running Android. Other storage options are possible.

Each airline may decide between offering a two-stop self-bag drop process and a one-stop process. The example of Figure 2 is a two-stop process in which, at step 106, the passenger prints a bag tag and affixes the tag to their baggage. This printing may take place in the user's home or office environment or at a kiosk in the airport. The kiosk may be dedicated to bag tag printing or provide other function such as on-line check in. In the one-stop process step 106 is omitted and the passenger proceeds straight to the bag drop.

On entry into the airport the passenger's mobile device detects a beacon arranged near the airport entrance (12, Figure 1). The mobile device detects again a second beacon when the passenger is in proximity of that second beacon 14 on entry into a bag drop area of the airport. This detection instantiates an intent in the user's mobile device application. An API
5 call is made to get details of the bagdrop represented by the beacon and a session request made to the cloud service using the bagdrop id from the API call, and a mobile device id. This is described in more detail below.

As an alternative to messaging via passenger's smart device, the relevant portion of the airport may be provided with signage instructing passengers to open the bag-drop app or to
10 visit the website. A QR code or other barcode could be provided which, when scanned with the device's camera would open the app or website automatically or initiate the bag-drop process if that app is already open. This option has the advantage to the airline that they know which self-bag drop (SBD) a given passenger is using as the barcodes may include an individual code that broadly corresponds to location within the airport. This assists the airline
15 in monitoring usage and controlling passenger through flow.

In one preferred option, both messaging to passengers' devices and signage is used to improve reliability and to ensure that passengers can use the system, for example if they have forgotten to switch on Bluetooth.

In one embodiment the signage includes a braille instruction for blind or visually impaired
20 passengers and the app may include voice instructions.

With the bag drop app opened the passenger proceeds to the designated bag drop at step 110. The app may instruct the passenger to present themselves to a particular one or group of self-bag drop terminals. At this stage, the bag drop application or module has retrieved boarding pass data that is stored on the device. This may include baggage allowance
25 information or that information may be retrieved, using the passenger identification, from the airlines departure control system (DCS). An eligibility check may be performed, for example to determine whether the passenger is too early to drop their bags, or too late or whether the mobile device bag drop option is not available for their particular flight.

At step 112 the passenger presents themselves at the bag drop area and the application
30 displays a message asking them to place their bag on the luggage belt or static scale. As with any conventional bag drop, the bag is weighed to check that it is within permitted allowances. The weight is communicated back to the app which can check the received

weight against allowances that are either stored as part of the boarding card or can be retrieved from the DCS.

5 If the bag fails the weight check the passenger is asked to pay for the excess baggage. This may be via a credit or debit card already stored in the airline application or via a regular online transaction. The transaction is of the “card not present” type and will be unique to each airline, each of which have their own excess baggage fees.

10 Assuming that the weight is within permitted limits, or that an excess has been paid for, at step 114 a bag tag is now printed. In the case of the two-step process mentioned above this step is not necessary as the bag tag already exists. The app then displays to the passenger information regarding how to affix the bag tag to the bag.

15 Once the bag tag has been attached, the LPC barcode may be read via the device’s camera. This is helpful where a bag does not arrive at the intended destination or where the passenger does not present themselves for the flight or a claim for compensation is made. In one embodiment a 3D scan of the bag may be performed to check that the bag is within permitted dimensions and is suitable rigorously constructed to be conveyed.

20 At step 116 a passenger verification step is performed. As the app has access to the airline DCS, it can retrieve the PNR (passenger name record) and compare the data on the tag with that record. The app may instruct the passenger to take a selfie or use one or more other forms of verification offered by the mobile device such as biometric identification or finger print recognition. Data collected in this manner may be stored for later reference. Passenger verification may take place before bag tag printing.

25 At step 118, if the identity of the passenger is verified, the bag is accepted by the departure control system (DCS) and a claim tag is shown to the passenger on the smart phone. This tag is stored in the application and/or on the mobile device. The bag is then handed over to the baggage handling system, this step being performed automatically or with the assistance of an airline agent.

30 With the bag now handed over, the app may supply the passenger with further information regarding their flight, such as, but not limited to, the boarding time and gate. At this point the app may automatically close or may return the passenger to a way finding application of the type disclosed in WO2013/117723 which directs the passenger to the departure gate using near field beacons distributed around the airport.

Figure 3 shows the essential hardware components used in the process described above. The Passengers mobile device is shown at 200 and is loaded with the app which consists of the logic to check a passenger's bag in. As mentioned above the app may be, for example, a module of an airline app or a standalone app. Device 200 communicates with the airline departure control system (DCS) 210 and a cloud service 220, which hosts a set of APIs and associated logic. A baggage check in system includes a baggage check in unit 230 and a controller 235 which may be either a hardware controller associated with the baggage check-in unit (BCIU) 230 which contains software and/or firmware to communicate with the BCIU 230, or a CUTE/CUSS module which does the same. CUTE (Common Use Terminal Equipment) and CUSS (Common Use Self Service). CUTE and CUSS are well known standards which enable hardware to be used by multiple airlines or service companies. The controller also communicates with the cloud service 220. Although not essential, a beacon 240 is provided for automatic identification of the bag drop area which communicates with the mobile device via Bluetooth TM or another communication protocol. Where beacons are used the mobile device 200 also communicates with a beacon registry 250 to retrieve a bag drop identifier. Even where beacons are used, the beacon registry 250 may not be essential as the service may be supported by the cloud service 220.

Figure 4 shows the logical architecture of the system. In general, the Cloud Service (220 Figure 3) acts as a broker between the mobile device 200 and the baggage unit controller. The service exposes a single connection endpoint to the mobile device, mitigates any network related complexities, allows for multiple device over the air protocols, manages bag drop service availability, and creates an abstraction for any controller specific messaging. A Web socket connection 400 is established between the mobile device 200 and the Cloud Service, and between the Cloud Service and the Baggage Unit Controller. The latter connection will be established by the Baggage Unit Controller, and maintained for the duration of the controller's time in service. It is the responsibility of the controller to assure that the connection is up. If the connection is terminated, the controller must re-establish the connection. The cloud service will consider the bag drop unit unavailable if the web socket connection is not active. Although described as a websocket, other asynchronous or bi-synchronous methods may be used.

Similarly, the mobile device 200 is responsible for establishing a connection with the Cloud Service 220, and to maintain the connection for the life of the session. As with the controller, discovery of the service from each mobile device streamlines the process.

The end to end session is mapped via binding the id's of both the mobile device and bag unit controller.

The logical architecture of the cloud service 220 is shown in Figure 5. The Cloud service consists of a set of microservices hosted on a distributed reactive platform. Each service endpoint registers an address by which events, based on *operator (op)*, will be routed across the event bus. The web socket service is the external facing service which directly communicates with controllers and mobile devices.

Figure 6 is a class diagram 600 that depicts a service model reflecting the interfaces available, and is coarser grained in nature than the service platform model. The services are as follows:

BagDropSvc 602

This service comprises the interfaces used in a session between the mobile device and the controller. Some interfaces may “pass through” to additional services, such as session, however, most if not all basic interfaces will be managed here. These include bag induction, bag tag printing, scale services, etc.

BagDropMngntSvc 604

This service handles the management of controllers. When a controller is booted for the first time, a registration request is sent. The service will interact with the *ConfigurationSvc* 606 to validate the request and store the new configuration for the controller. It also handles the availability status of the controller.

TimerSvc 608

A session has a predetermined inactivity period. The *TimerSvc* manages this, and interacts with the *sessionSvc* to handle overall session state.

ConfigurationSvc 606

As stated, this service interacts with the *BagDropMngmtSvc* to register and deregister controllers. In addition, each controller *may* have unique attributes, which can be uploaded and stored. Controllers may be enabled and disabled via the interface.

SessionSvc 610

This service manages a session between the mobile device and the controller. It interacts with the AuthSvc to authenticate users on start_session and to validate tokens, and with the timerSvc to invalidate a session after a period of inactivity.

AuthSvc 612

This service interface acts as a facade to one or more implementations of Authentication and Authorization. An initial implementation will provide for a local userid/password authentication scheme, and JWT (JSON Web Tokens) for authorization.

Figure 7 shown the logical architecture of the Bag Unit Controller 235 in Figure 3. A workstation 702 which may be any suitable computing device hosts the hardware service 704 and bag drop controller service 706. The Workstation is, in a preferred embodiment, configured as a common use terminal, for example running a Windows TM operating system, as discussed above. The bag drop controller service acts as a communication layer between the cloud service and the hardware service via web socket 708 and hardware communication layer 710. It also manages the state of the machine and registers to the cloud service. The hardware service 704 connects to an IO server 710 and other hardware peripherals. Alternatively the hardware service may connect to a Common Use Self-Service module.

The IO Server 710 includes a programmable logic control PLC 712 to control one or more baggage belt setups 714 and to other hardware 716. It is connected either to the airport Baggage Handling System or directly to the hardware.

Figure 8 shows the architecture of the mobile device application (app) 800. The app has two main components, a software development kit SDK 802 and user written event handlers 804. The mobile device architecture is designed to push as much of the applicable processing into the SDK 802. This makes it easier for the app developer, which is a specific airline or an external vendor to implement the service. Applicable processing includes workflow as well as socket communications between the mobile device and cloud service.

To achieve this, the app developer implements a set of documented event listeners, or handlers 804. These listeners, or observers, are registered to accept callbacks from the SDK, at which time the handler executes logic predefined to achieve a certain result. The

handler 804 may also be required to call the SDK 802 with the result, or simply to inform the SDK 802 of its completion. Figure 8 shows the high level interactions between the UX (User Experience layer) 806, application logic 808, and SDK 802.

5 Table 1 below is a list of event handlers that an app developer will implement.

Operator	Description
no_session	Called if start_session fails, due e.g. to bag drop unit not available
session_ready	Session is ready, app should inform user to place bag on scale. This is also a trigger to fetch airline rules, if not already cached in app.
scale_result	Result from scale delivered to handler. Included in result is airport rules. If either airline or airport rules check fails, handler informs passenger as to options.
bagtag_printed	Handler is informed that the bag is ready to be inducted. The app may want to communicate with passenger first before calling induct_bag. If bagtag already printed (in which case print_bagtag would not be called), app would call sdk induct_bag directly)
bag_inducted	Handler to clean up and end session.
end_session	Alternative to bag inducted

Table 1

Table 2 a list of method calls to the sdk which are implemented by the app.

10

Method	Description
start_session	Request to initiate session with bag drop. Most likely called as the result of an external trigger (e.g. beacon, NFC) from a close-by bag drop unit.
print_bagtag	The app would have made a call to its DCS to check bag. The successful result (image, pectab, etc) would be included in this call.
induct_bag	Request to induct the bag into the BHS system.
print_receipt	Request to print bagtag receipt.
end_session	Request to end this session.

Table 2

15 Figure 9 is a process flow diagram showing the end to end interaction between the SDK 802, airline mobile app components, and the UX 806. In the example of figure 9, the bag tag has not yet been printed. If the bag tag has already been printed, a different path would be taken to support this.

Figure 10 shows the end to end interactions between the major system actors, mobile device app, cloud service, and self bag drop unit. The DCS (Departure Control System) interaction with the app is also shown. Similarly to the Figure 9 example the bag tag has not yet been printed. If the bag tag has already been printed, a different path would be taken.

Security may be achieved by ensuring that all communications, for all sessions, between the mobile device and cloud service, and between the cloud service and bag drop unit controller, are over secure, cryptographic protocols. Secure web socket protocol (WSS) presently preferred. JSON web tokens (JWT) are used to authenticate and authorize transactions across all layers. JWT is a compact, URL-safe means of representing claims between parties by encoding them as JSON objects which can be digitally signed or encrypted.

In the mobile device app, HMAC (Hash-based Message Authentication Code) algorithms are used between the mobile device and cloud service. Each client (e.g. an airline) receives a single user id and password combination. On *session_start*, these credentials are passed to the cloud service, which validates them. A JWT is generated using a private key. The mobile device is responsible for sending the JWT with each request. A new JWT may be generated at any time by the cloud service. It is the responsibility of the mobile client to save the JWT on each event received from the cloud service, and to pass the latest version back on subsequent requests.

HMAC algorithms are also used between the bag drop unit controller and cloud service. Each Bag drop unit controller is pre-configured with a unique id, username and password. When the module first boots, the controller registers with the cloud service, passing its unique credentials with the registration request. On successful registration, the cloud service response contains a JWT, which will be required in each message from the controller to the cloud service.

As an alternative, RSA public/private key encryption may be used.

The API handles interactions between the Cloud service 220 and the controller 235, between the Cloud service 220 and mobile device 200, and between the Cloud service 220 and both the controller and mobile device (in a proxy mode).

Each API event, or operation is conveyed in a JSON payload over a secure web socket connection (wss), and contains an event operator (op). The type operator type is used to route the message to an appropriate handler.

- 5 A session between the mobile app and Bag Drop unit, is initiated during start_session, propagated by use of JsonWebToken, and ended with either an end session call or timeout. The mobile app client is responsible for passing the token with each call made to the cloud service. This may be the responsibility of the SDK, as only it communicates with the cloud service via the web socket connection.

10

1. Cloud Service - Mobile Device

A basic command is sent in the following format:

```
15 {
    "token": "<service-supplied token>",
    "op": "<command>",
    "txid": "<generated transaction id>",
    "args": [{
20         "key1": "val1",
        "key2": "val2",
        "key3": "val3"
    }]
25 }
```

This format is valid for all API calls except start_session, in which the application's user id and password will be sent. The resulting token returned indicates successful authentication, and an active session with the bag drop unit. Transaction id is optional for the requestor. If a transaction id is received, it is preferred, but not mandatory, to return it in a response payload.

30

reply

reply is a generic response sent by either the cloud service or mobile device. The message carries information pertaining to a previous request, and (optional) transaction id. It may be used to acknowledge a request with no specific response payload. This API is bi-directional.

35

Field Description

Key	Value	required
op	<i>reply</i>	yes
token	Service provided session token	yes
txid	Transaction id	no
for	{the request api}	yes
result	ok or failed	yes
reason_code	Reason for failure	cond

5

Example

```
10  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
    "op": "reply",
    "txid": "<generated transaction id>",
    "args": [{
15    "for": "mark_available",
        "result": "ok",
    }]
}

20  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
    "op": "reply",
    "txid": "<generated transaction id>",
    "args": [{
25    "for": "mark_available",
        "result": "failed",
        "reason_code": "NO_RESPONSE"
    }]
30 }
```

Reason Codes (tbd)

Code	Description
NO_RESPONSE	The service has not responded within the timeout period
NOT_SUPPORTED	Generic response to a request. Examples include print bagtag, print receipt.

5

Start_session

start_session requests that a session with the bag drop denoted by id is started with the client. Credentials are passed in the request. Each client of the system will have a unique set of credentials. Credentials are not unique to each app user. This is a one way, asynchronous request. The client will receive either a session_ready or no_session event as the result of this call. The direction is generally from mobile app to cloud service.

10

Field Description

Key	Value	required
op	session_start	yes
txid	Transaction id	no
uid	The client provided user id	yes
pwd	The client provided password	yes
bagdrop_id	The id of the bag drop unit as provided during discovery	yes

Example

```
{
  "op": "start_session",
  "args": [{
    "uid": "myClientId",
    "pwd": "myClientPwd",
    "bagdrop_id": "ID105211"
  }]
}
```

session_ready

20

25

session_ready is one of two events that result from a *start_session* request. It notifies the client that the session with the bag drop unit has been started. The response includes capabilities of the bag drop unit, e.g. bag tag and receipt printing is available or not. Direction is generally from cloud service to mobile app.

5 Field Description

Key	Value	required
op	<i>session_ready</i>	yes
txid	Returned transaction id	no
token	Service provided session token	yes
bag drop _id	The id of the bag drop unit we are in session with	yes
config	Key value pair of configured capabilities of the bag drop unit. Values TBD.	no

Example

```

10  {
      "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
      "op": "session_ready",
      "args": [{
15    "bagdrop_id": "ID105211"
      "config": [{
          "print_bagtag": true,
          "print_receipt": true
      }],
20  }]
    }

```

no_session

25 *no_session* is one of two events that result from a *start_session* request. It notifies the client that the session with the bag drop unit did not start successfully. A reason code will be attached to the response. Direction is generally from cloud service to mobile app.

Field Description

Key	Value	required
op	<i>no_session</i>	yes

txid	Transaction id	no
reason_code	Valid reason code (see table)	no
bagdrop_id	The bag drop unit id	yes

Example

```

5  {
    "op": "no_session",
    "args": [{
        "bagdrop_id": "ID105211",
        "reason_code": "OUT_OF_SERVICE"
    }]
10 }

```

Reason Codes

Code	Description
OUT_OF_SERVICE	The bag drop unit is out of service.
IN_USE	The bag drop unit is being used, there is an existing session.

15

end_session

end_session is sent by either party to signify that the sender wishes to end the session.

20 While generally sent from the mobile app, in order for both sides to clean up, it may be sent by the cloud service for a number of reasons. Direction is generally from mobile app to cloud service. May be sent from cloud service.

Field Description

25

Key	Value	required
op	<i>end_session</i>	yes
token	Service provided session token	yes
txid	Transaction id	no
bag drop_id	The id of the bag drop unit we are in session with	yes

reason_code	Reason for ending session	no
-------------	---------------------------	----

Example

```

5  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
    "op": "end_session",
    "args": [{
        "bagdrop_id": "ID105211",
        "reason_code": "PROCESS_COMPLETE"
    }]
10 }

```

Reason Codes

Code	Description
PROCESS_COMPLETE	Either side considers that the check in workflow is complete.
USER_REQUESTED	The user (passenger) has requested to stop the process
UNIT_ERROR	The bag drop unit has detected some error or malfunction and can no longer continue.
SESSION_TIMEOUT	The session has timed out
BAGGAGE_ERROR	There is some problem with continuing to check this bag(s) in

scale_result

20 *scale_result* is sent by the cloud service, forwarding from the bag drop unit, to relay the results of the weighing of the bag by the bag drop unit scale. The response includes a set of airport or baggage handling system restrictions on weight/size. Direction is from cloud service to mobile app.

Field Description

Key	Value	required
op	<i>scale_result</i>	yes
token	Service provided session token	yes
txid	Transaction id	no
bag drop _id	The id of the bag drop unit we are in session with	yes

weight	Weight of bag	yes
dimension	Bag dimensions	yes
weight_unit	Unit used (K=kilo, P=pounds)	yes
dimension_unit	Unit used (I=inches, M=millimeters)	yes
bhs_rules	Array of bhs rules	no
bhs_rules.weight	Weight restriction	no
bhs_rules.dimension	Size restriction	no
bhs_rules.weight_unit	Unit used	cond
bhs_rules.dimension_unit	Unit used	cond
result	An enumerated advisory (see reason codes section)	yes

Example

```

5  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2...",
    "op": "scale_result",
    "args": [{
10      "bagdrop_id": "ID105211",
        "weight": 20,
        "dimension": 10,
        "weight_unit": "K",
        "dimension_unit": "I",
        "bhs_rules": [{
15          "weight": 50,
          "dimension": 20,
          "weight_unit": "K",
          "dimension_unit": "I"
        }],
        "result": "PASSED"
20    }]
  }

```

Reason Codes

Code	Description
PASSED	weight/size passed all requirements
FAILED_WEIGHT_AIRLINE	failed airline weight restriction
FAILED_WEIGHT_BHS	failed BHS weight restriction
FAILED_SIZE_AIRLINE	failed airline size restriction

FAILED_SIZE_BHS	failed BHS size restriction
PLACE_IN_TUB_RETEST	advisory code to place bag in a tub and place on scale

print_bagtag

- 5 *print_bagtag* is sent by the mobile device to the cloud service. As the request is delivered to the bag drop unit, it is considered a proxy call. The request contains the image to be printed, e.g. in pectab format. Direction is from mobile app to cloud service.

Field Description

10

Key	Value	required
op	<i>print_bagtag</i>	yes
token	Service provided session token	yes
txid	Transaction id	no
bag drop_id	The id of the bag drop unit we are in session with	yes
image	The image to be printed	yes
format	The format of the image (e.g. PECTAB)	yes

Example

15 {
 "token": "eyJpc3MiOiJ0b3B0YWwY2....",
 "op": "print_bagtag",
 "args": [{
 20 "bagdrop_id": "ID105211",
 "image": "<image to print>",
 "format": "PECTAB"
 25 }]
 }

Formats

25

Code	Description
PECTAB	Parametric Table

induct_bag

- 5 *induct_bag* is sent by the mobile device to the cloud service. As the request is delivered to the bag drop unit, it is considered a proxy call. The request, as implied, is for the bag drop unit to initiate injecting the bag into the baggage handling system. This call may be optional based on configuration. For example, some configurations may call for the bag to be automatically inducted after some certain step, particularly if the bag tag has been pre-printed, and is attached to the bag. Direction is from mobile app to cloud service.
- 10

Field Description

Key	Value	required
op	<i>induct_bag</i>	yes
token	Service provided session token	yes
txid	Transaction id	no
bag drop _id	The id of the bag drop unit we are in session with	yes

Example

15 {
 "token": "eyJpc3MiOiJ0b3B0YWwuY2...",
 "op": "induct_bag",
 "args": [{
20 "bagdrop_id": "ID105211"
 }]
}

print_receipt

- 25 *print_receipt* is sent by the mobile device to the cloud service. As the request will be delivered to the bag drop unit, it is considered a proxy call. The request contains the image to be printed, e.g. in pectab format.
- 30 Direction is from mobile app to cloud service. A reply is to be expected.

Field Description

Key	Value	required
-----	-------	----------

op	<i>print_receipt</i>	yes
token	Service provided session token	yes
txid	Transaction id	no
bag drop _id	The id of the bag drop unit we are in session with	yes
image	The image to be printed	yes
format	The format of the image (e.g. PECTAB)	yes

Example

```

5  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
    "op": "print_receipt",
    "args": [{
10      "bagdrop_id": "ID105211",
        "image": "<image to print>",
        "format": "PECTAB"
    }]
  }

```

Formats

Code	Description
PECTAB	Parametric Table

2. Cloud Service - Controller

20 A basic command is sent in the following format:

```

{
    "token": "<server-supplied token>",
    "op": "<command>",
25  "txid": "<generated transaction id>",
    "args": [{
        "key1": "val1",
        "key2": "val2",
        "key3": "val3"
30    }]
  }

```

This format is valid for all API calls except *register*, in which the baggage handling unit's unique id, username and password will be sent. Transaction id is optional for the requestor. If a transaction id is received, it is preferred, but not mandatory, to return it in a response payload.

5

reply

reply is a generic response sent by either the cloud service or controller. The message carries information pertaining to a previous request, and (optional) transaction id. It may be used to acknowledge a request with no specific response payload. This API is bi-directional.

10

Field Description

Key	Value	required
Op	<i>reply</i>	yes
Token	Service provided session token	yes
Txid	Transaction id	no
For	{the request api}	yes
Result	ok or failed	yes
reason_code	Reason for failure	cond

15

Examples

```
{
  "token": "eyJpc3MiOiJ0b3B0YWwuY2...",
  "op": "reply",
  "txid": "<generated transaction id>",
  "args": [{
    "for": "mark_available",
    "result": "ok",
  }]
}
```

20

25

30

```
{
  "token": "eyJpc3MiOiJ0b3B0YWwuY2...",
  "op": "reply",
}
```

```

"txid": "<generated transaction id>",
  "args": [{
    "for": "mark_available",
      "result": "failed",
5      "reason_code": "NO_RESPONSE"
    }]
  }

```

10 Reason Codes

Code	Description
NO_RESPONSE	The service has not responded within the timeout period

register

15

register is sent by the bag drop controller (CUTE, CUSS module or other) to the cloud service. This is a one-time message, sent the first time the controller is brought online. The controller receives one of two events as a result of the register request, *registered*, or *registration_failed*. Direction is from controller to cloud service.

20

Field Description

Key	Value
Op	<i>register</i>
bag drop _id	The unit's preconfigured id
username	The unit's preconfigured username
password	The unit's preconfigured password

Example

25

```

{
  "op": "register",
  "args": [{
    "bagdrop_id": "ID105211",
30    "username": "9e83a024-c374-4c3e-bd4e-ead758282513",
  }]
}

```

```

    "password": "bfdfdb7-4cd2-4b33-ae17-a11c45ae1802"
  }
}

```

registered

registered is sent by the cloud service to the controller. The message indicates successful registration, and that a session has been started. Direction is from cloud service to controller.

Field Description

Key	Value
op	<i>registered</i>
token	Service provided session token

Example

```

{
  "token": "eyJpc3MiOiJ0b3B0YWwuY2...",
  "op": "registered"
}

```

registration_failed

registration_failed is sent by the cloud service to the controller. The message indicates that there was an issue in attempting to register the controller. Direction is from cloud service to controller.

Field Description

Key	Value
op	<i>registration_failed</i>

Example

```
{  
  "op": "registration_failed",  
  "reason_code": "BAD_CREDENTIALS"  
}
```

Reason Codes

Code	Description
UNKOWN_UNIT_ID	The bag drop unit is not found in the database (must be preconfigured in cloud service).
BAD_CREDENTIALS	Username and/or password incorrect

deregister

deregister is sent by the bag drop controller (CUTE, CUSS module or other) to the cloud service. The API request informs the cloud service that the controller has been decommissioned, and to remove its record from the system. Direction is from controller to cloud service.

Field Description

Key	Value
op	<i>deregister</i>
token	Service provided session token
bag drop_id	The unit's preconfigured id
username	The unit's preconfigured username
password	The unit's preconfigured password

Example

```
{  
  "token": "eyJpc3MiOiJ0b3B0YWwuY2....",  
  "op": "register",  
  "args": [{  
    "bagdrop_id": "ID105211",  
  }]
```

```

        "username": "9e83a024-c374-4c3e-bd4e-ead758282513",
        "password": "bfdfdc7-4cd2-4b33-ae17-a11c45ae1802"
    }
}

```

mark_available

mark_available is sent by the bag drop controller (CUTE, CUSS module or other) to the cloud service. The API request informs the cloud service that the controller is now available to accept sessions. If the controller is already available, the request will be ignored by the cloud service. In all cases, an acknowledgement will be sent back. Direction is from controller to cloud service.

Field Description

Key	Value
op	<i>mark_available</i>
token	Service provided session token

Example

```

{
  "token": "eyJpc3MiOiJ0b3B0YWwY2....",
  "op": "mark_available",
}

```

mark_unavailable

mark_unavailable is sent by the bag drop controller (CUTE, CUSS module or other) to the cloud service. The API request informs the cloud service that the controller is unavailable to accept sessions. If the controller is already marked unavailable, the request will be ignored by the cloud service. In all cases, an acknowledgement will be sent back. Direction is from controller to cloud service.

Field Description

Key	Value
Op	<i>mark_unavailable</i>

Token	Service provided session token
-------	--------------------------------

Example

```

5  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
    "op": "mark_unavailable",
    "args": [{
        "reason_code": "MAINTENANCE"
10 }

```

Reason Codes

Code	Description
MAINTENANCE	The controller is taken offline for maintenance
MODE_CHANGE	The bag drop unit is changing modes e.g. switching to manual

15

scale_result

scale_result is sent by the bag drop unit, to the cloud service. The response includes a set of airport or baggage handling system restrictions on weight/size. Direction is from controller to cloud service.

20

Field Description

Key	Value
op	<i>scale_result</i>
token	Service provided session token
weight	Weight of bag
dimension	Bag dimensions
weight_unit	Unit used (K=kilo, P=pounds)
dimension_unit	Unit used (I=inches, M=millimeters)
bhs_rules	Array of bhs rules
bhs_rules.weight	Weight restriction

bhs_rules.dimension	Size restriction
bhs_rules.weight_unit	Unit used
bhs_rules.dimension_unit	Unit used
result	An enumerated advisory (see reason codes section)

Example

```

5  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2...",
    "op": "scale_result",
    "args": [{
10      "weight": 20,
        "dimension": 10,
        "weight_unit": "K",
        "dimension_unit": "I",
        "bhs_rules": [{
15          "weight": 50,
            "dimension": 20,
            "weight_unit": "K",
            "dimension_unit": "I"
        }],
        "result": "PASSED"
    }]
20 }

```

Reason Codes

Code	Description
PASSED	weight/size passed all requirements
FAILED_WEIGHT_AIRLINE	failed airline weight restriction
FAILED_WEIGHT_BHS	failed BHS weight restriction
FAILED_SIZE_AIRLINE	failed airline size restriction
FAILED_SIZE_BHS	failed BHS size restriction
PLACE_IN_TUB_RETEST	advisory code to place bag in a tub and place on scale

print_bagtag

print_bagtag is sent by the cloud service to the controller. As the request originated from the mobile device, it is considered a proxy call. The request contains the image to be

printed, e.g. in pectab format. Direction is from cloud service to cloud controller. A response from the controller is expected.

Field Description

5

Key	Value	required
op	<i>print_bagtag</i>	yes
token	Service provided session token	yes
Transaction id	Transaction id	no
image	The image to be printed	yes
format	The format of the image (e.g. PECTAB)	yes

Example

```
10 {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
    "op": "print_bagtag",
    "args": [{
15         "bagdrop_id": "ID105211",
        "image": "<image to print>",
        "format": "PECTAB"
    }]
}
```

20 Formats

Code	Description
PECTAB	Parametric Table

induct_bag

25

induct_bag is sent by the cloud service to the controller. As the request originated at the mobile device, it is considered a proxy call. The request, as implied, is for the bag drop unit to initiate injecting the bag into the baggage handling system. This call may be considered optional based on configuration. For example, some configurations may call for the bag to

be automatically inducted after some certain step, particularly if the bag tag has been pre-printed, and is attached to the bag. Direction is from cloud service to controller. A reply is expected.

5 Field Description

Key	Value	required
op	<i>induct_bag</i>	yes
token	Service provided session token	yes
txid	Transaction id	no

Example

```

10  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
    "op": "induct_bag"
  }

```

```

15  print_receipt

```

print_receipt is sent by the cloud service to the controller. As the request originates from the mobile device, it is considered a proxy call. The request contains the image to be printed, e.g. in pectab format. Direction is from mobile app to cloud service. A reply is expected.

Field Description

Key	Value	required
op	<i>print_receipt</i>	yes
token	Service provided session token	yes
txid	Transaction id	no
image	The image to be printed	yes
format	The format of the image (e.g. PECTAB)	yes

Example

```
5  {
    "token": "eyJpc3MiOiJ0b3B0YWwuY2....",
    "op": "print_receipt",
    "args": [{
        "image": "<image to print>",
        "format": "PECTAB"
10  }]
}
```

Formats

Code	Description
PECTAB	Parametric Table

15

As described, the system comprises a front end application which is either a unique application or a module on an airline/airport website. This is the interface through which airlines and/or airports present the bag drop service to their passengers. A back-end software engine hosts the logic for the self-bag drop process and drives the process. An API enabled communication between the App, the backend software engine and the baggage handling system hardware and self-bag drop peripherals such as the printer and weigher. Other speedy peripherals may include automated readers and baggage assessment devices for example the BHS hardware may comprise new or existing conveyor belts and weighing scales.

25

Embodiments of the invention may also be used where printed boarding passes are required for use by the passenger instead of mobile boarding passes and with any type of bag tag including temporary and permanent bag tags, tag-less baggage handling systems and self-printed bag tags.

30

Embodiments of the invention have many advantages. The interaction between the passenger and the self-service location is made more simple for the passenger and enables operators to reduce overheads such as the staffing of traditional check-in and other facilities while requiring only relatively small modifications to existing check-in systems and other systems such as passport gates etc. From the perspective of the passenger, it provides convenience and time savings so enhancing the passenger's experience of the airport.

Although described in respect of a bag drop system, embodiments of the invention may be used in conjunction with other airport self-service functions such as e-gates, providing electronic passport and/or boarding pass checks, final boarding checks and kiosks for checking in and/or generation and printing of bag tags. In one embodiment the passenger's mobile device connects to a baggage handling system on arrival at an airport and the passenger is directed to the correct carousel and their baggage is also directed to that carousel.

Embodiments of the invention may be used with similar services at other ports, railways of mass transit locations as well as at venues, sports grounds etc. where individuals interact with services such as ticket checks.

Embodiments of the invention may also be advantageous for passengers with certain disabilities. For example by using the audio capabilities of a smart device a blind or partially sighted passenger's experience of the bag drop, passport control and other airport functions can be greatly improved. Embodiments of the invention also enable the integration of passenger information on the smart device with payment services that an airline or airport may already provide via existing mobile applications.

CLAIMS

1. A method of facilitating interaction between a ticket holder and a self-service function related to the ticket, comprising the steps of:

5 detecting by a mobile device proximity to a self-service function, the mobile device having stored thereon information relating to the ticket and the self-service function being related to the ticket;

on detection by the mobile device of proximity to the location, activating an application on the mobile device, the application being related to the self-service function;
10 and

communicating to the mobile device via the application, information about the self-service function including directional information.

2. A method according to claim 1, wherein the ticket relates to a passenger journey and includes passenger and journey identification.

15 3. A method according to claim 2, wherein the ticket information comprises a boarding pass.

4. A method according to claim 1, wherein the mobile device detects geolocation device indicating proximity to the self-service function.

20 5. A method according to claim 5, wherein the geolocation device is a Bluetooth beacon.

6. A method according to claim 1, wherein the application queries the ticket information stored on the mobile device and communicates the ticket information to a remote server.

25 7. A method according to claim 6, wherein the remote server, in response to receipt of the ticket information provides information relating to the self-service function to the application for presentation to the user of the mobile device.

8. A method according to claim 1, wherein the self-service function is a bag drop and the information relating to the ticket is a boarding pass, comprising communicating passenger information in the boarding pass to a departure control system.

5 9. A method according to claim 8, comprising determining by the departure control system whether baggage relating to the boarding pass is eligible for bag drop and communicating the eligibility to the mobile device.

10 10. A method according to claim 8, comprising on deposit of a bag at a bag drop, weighing the bag, determining whether the weight exceeds an allowable weight and, if the weight exceeds an allowable weight arranging for payment of an excess baggage fee via the application.

11. A method according to claim 1, comprising printing a bag tag at the bag drop and communicating instructions for fixing the bag tag to a bag for presentation to the user to the mobile device via the application.

15 12. A method according to claim 8, comprising, on receipt of a bag by the bag drop, communicating to the application information about boarding and routing to a departure gate.

13. A method of facilitating interaction between a ticket holder and a self-service function related to the ticket, comprising the steps of:

20 at a location proximate a self-service function related to the ticket, activating an application on the mobile device, the application being related to the self-service function and the mobile device having stored thereon information relating to the ticket;

communicating to the mobile device via the application, information about the self-service function including directional information.

25 14. A method according to claim 13, wherein the application is activated by scanning or imaging a barcode using the mobile device.

15. A system for facilitating interaction between a ticket holder and a self-service function related to the ticket, comprising:

A self-service function;

A mobile device, the mobile device having stored thereon information relating to the ticket;

at least geolocation device; wherein the mobile device is configured to detect the geolocation device at a location proximate a self-service function, and

5 at least one server having stored thereon computer software for performing the steps of:

on detection by the mobile device of the geolocation device proximate the location, activating an application on the mobile device, the application being related to the self-service function; and

10 communicating to the mobile device via the application, information about the self-service function including directional information.

16. A system according to claim 15, wherein the ticket relates to a passenger journey and includes passenger and journey identification.

15 17. A system according to claim 15, wherein the ticket information comprises a boarding pass.

18. A system according to claim 17, wherein the at least one geolocation device is a Bluetooth beacon.

20 19. A system according to claim 15, wherein the application queries the ticket information stored on the mobile device and communicates the ticket information to the server.

20. A system according to claim 19, wherein the server, in response to receipt of the ticket information provides information relating to the self-service function to the application for presentation to the user of the mobile device.

25 21. A system according to claim 15, comprising a departure control system, wherein the self-service function is a bag drop comprising a baggage handling system and a bag drop controller and the information relating to the ticket is a boarding pass, comprising communicating passenger information in the boarding pass to a departure control system.

22. A system according to claim 21, wherein the departure control system is arranged to determine whether baggage relating to the boarding pass is eligible for bag drop and to communicate the eligibility to the mobile device.

5 24. A system according to claim 22, wherein the baggage handling system comprises a weighing device for weighing a bag on deposit at the bag drop, for determining whether the weight exceeds an allowable weight and, if the weight exceeds an allowable weight arranging for payment of an excess baggage fee via the application.

10 25. A system according to claim 22, wherein the baggage handling system comprises a printer for printing a bag tag and the bag drop controller is configured to communicate instructions for fixing the bag tag to a bag for presentation to the user to the mobile device via the application.

26. A system according to claim 15, on receipt of a bag by the bag drop, the system is configured to communicate to the application information about boarding and routing to a departure gate.

15

Abstract

SYSTEMS AND METHODS FOR INTERACTIONS BETWEEN TICKET HOLDERS AND SELF SERVICE FUNCTIONS

- 5 Ticket information, such as an airline boarding pass may be stored on a mobile device. The presence of a geolocation device such as a Bluetooth beacon is detected by the mobile device in a departure location such as an airport. On detection by the mobile device of a further geolocation device when the mobile device is proximate a self-service function an application on the mobile device is triggered which directs the mobile device to a self-
- 10 service function such as a bag drop and instructs the mobile device user how to use the self-service function.