

NETWORK TRAFFIC REDIRECTION (NTR) IN LONG TERM EVOLUTION (LTE)

Related Applications

5

This application claims priority to US Provisional Patent application No. 61/504,977 titled "Roaming VAS in LTE", filed on July 6, 2011. This patent application is incorporated herein by this reference in its entirety.

10 Field of the Invention

The present invention generally relates to telecommunication. More specifically, the invention relates to method and system for redirecting roaming traffic to preferred operators across multiple telecommunication networks.

15

Background of the Invention

As telecommunication technology has progressed, numerous mobile communication standards have been developed. These standards are broadly
20 categorized into second generation (2G), third generation (3G) and the future, fourth generation (4G) technologies. Examples of 2G/3G technologies include Global System for Mobile communications (GSM), General Packet Radio Service (GPRS), Enhanced Data rates for GSM Evolution (EDGE), Universal Mobile Telecommunications System (UMTS), and the like. The UMTS standard further
25 evolved to LTE technology under the Third Generation Partnership Project (3GPP).

LTE technology offers a wireless broadband system with higher data rates, lower latency, and higher spectrum efficiency.

To keep up with the competition, more and more operators are adapting the
5 newer LTE technology standard. These network operators provide voice and data
services to their own subscribers and to subscribers from other networks. When the
network operator provides service to a subscriber from a foreign country, it is referred
to as "international roaming". When the network operator provides service to a
subscriber from another network in the same country, it is referred to as "domestic
10 roaming".

An operator always has a preference for one or more operators over another
set of operators. Various network operators have partnership agreements with each
other that include more favorable roaming charges than non-partners receive. Partner
15 networks are "preferred" networks for the network operator's subscriber to register
with when roaming. Non-partner networks are "non-preferred" networks to the
subscriber. Network operators can maximize their margins and the roamers can get
more attractive roaming rates and services if roamers roam on their home mobile
operator's preferred partner networks.

20

Over the last few years, the revenues to network operators from home
subscribers have consistently declined due to increased competition and resulting
pricing pressures. On the other hand, revenues from roamers have consistently grown
in the same period due to increased mobile penetration in local markets and an

increase in travel. Hence, protecting the existing roaming revenues and growing them further has become an important priority for the network operators worldwide.

Some operators also own networks in various countries. These operators
5 would like to make sure their out-roamers stay within the group properties, or stay on preferred networks, in order to gain the best service experience even when roaming. They will also be able to offer geography based price plans (for example, a single rate all across Western Europe or South East Asia) to users who have subscribed to such plans. In addition, as new technologies like LTE keep rolling out, operators can
10 control the rollout schedule across their own properties and also make sure interoperability issues are taken care of. Keeping roaming subscribers on preferred networks gives the best service experience to the subscriber. However, current methods of controlling which network a subscriber registers on when roaming have disadvantages.

15

One previous patent from the inventors of this application was directed towards a method and system for facilitating redirection of network traffic towards a preferred network. However, that patent was focusing on GSM network. Considering the current scenario where LTE is widely getting adapted, there is a need in the art for
20 a system and method facilitating redirection of network traffic across multiple networks including LTE and GSM.

Summary

The present invention is directed towards a method and system for redirecting
5 roaming network traffic in an LTE network. The method includes observing a
registration process of a subscriber in a visited network. The method further includes
upon successful registration, sending one or more messages to the visited network to
induce a re-registration attempt by the subscriber to another visited network.

10 The present invention in another embodiment also provides a method for
redirecting roaming network traffic in an LTE network. The method includes
intercepting a Diameter registration request of a subscriber in a visited network. The
method further includes sending a Diameter Update Location Answer (Reject)
message to the visited network, where the Diameter Update Location Answer (Reject)
15 message results in an error code.

The present invention in another embodiment also provides a method for
redirecting roaming network traffic in one or more telecommunication networks. The
method includes observing a registration process of a subscriber in a visited network.
20 The method further includes identifying the subscriber's registration on at least one of
an LTE network or a GSM network. In case the subscriber is registered at the GSM
network, then the it is identified whether the registration is due to loss of LTE
coverage or CSFB. If registration is due to loss of LTE coverage, then the method
includes sending one or more messages to the visited network to induce a re-
25 registration attempt by the subscriber to another visited network.

The present invention in another embodiment also provides a system for redirecting roaming network traffic in a telecommunication network. The system includes an NTR module that observes a registration process of a subscriber in a visited network. The NTR module further sends one or more messages to the visited network to induce a re-registration attempt by the subscriber to another visited network.

In accordance with various embodiments of the present invention, the NTR module is capable of steering roamers across LTE and non-LTE (GSM) networks. This solution of implementing NTR is hereinafter, interchangeably, referred to as NTR LTE or NTR solution.

Brief Description of Drawings

15

In the drawings, the same or similar reference numbers identify similar elements or acts.

FIG. 1 illustrates a system for implementing the NTR in LTE solution, in accordance with an embodiment of the present invention;

20 FIG. 2 represents a flowchart for redirecting roaming network traffic in a telecommunication network, in accordance with an embodiment of the present invention;

FIG. 3 represents a flow diagram for implementing NTR solution in monitoring mode using an ISD message, in accordance with an embodiment of the present invention;

25

FIG. 4 represents a flow diagram for implementing NTR solution in monitoring mode using a Cancel Location message, in accordance with an embodiment of the present invention; and

FIG. 5 represents a flow diagram for implementing NTR solution in an in-path mode, in accordance with an embodiment of the present invention;

Detailed Description

In the following description, for purposes of explanation, specific numbers, materials and configurations are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, to one having ordinary skill in the art that the present invention may be practiced without these specific details. In some instances, well-known features may be omitted or simplified, so as not to obscure the present invention. Furthermore, reference in the specification to "one embodiment" or "an embodiment" means that a particular feature, structure or characteristic, described in connection with the embodiment, is included in at least one embodiment of the present invention. The appearance of the phrase "in an embodiment", in various places in the specification, does not necessarily refer to the same embodiment.

The present invention provides a system and a method for redirecting roaming traffic across multiple telecommunication networks. The general idea of this invention is to allow an operator to apply NTR solution across LTE and non-LTE (GSM) networks. The HPMN operator deploys an NTR module to implement the solution as described in the present invention. This module enables the operator to steer away its

subscribers from a non-preferred VPMN to a preferred VPMN. The preferred VPMN may be another LTE network or a GSM network.

In accordance with another embodiment of the present invention, a group of operators may deploy the NTR solution to steer their subscribers to a set of preferred operators. In such an embodiment, the NTR module is deployed at a centralized location that is connected to a host network. In its various implementation of the present invention, the NTR solution is implemented in monitoring mode or in-signaling mode

FIG. 1 illustrates a system 100 that implements the NTR in LTE solution, in accordance with an embodiment of the present invention. NTR module 102 is deployed in HPMN 104 to apply traffic steering on its subscriber 106, who is roaming in a VPMN 108. This enables the operator in HPMN to be able to steer its subscribers to preferred operators in VPMN 108. For sake of representation, system 100 represents network elements from both LTE and GSM networks. HPMN 104 includes an HSS 110 that connects via a DEA / DRA 112 in HPMN 104 and a DEA / DRA 114 in VPMN 108 to an MME 116 in VPMN 108. The MME 116 is further connected to an MSC-R / VLR-R 118 in VPMN 108 via BSSAP+ protocol.

HPMN 105 further includes an MSC-H / VLR-H 120, an SGSN-H 122, a GGSN-H 124, an SMSC-H 126 and an STP-H 128. These network elements communicate with each other over a Signaling System 7 (SS7) link. System 100 further includes in VPMN 108 an SGSN-R 130, a GMSC-R 132, and an STP-R 134 that connects to STP-H 128 over SS7 link.

It will also be apparent to a person skilled in the art that HPMN 104 and VPMN 108 may also include various other network components (not shown in FIG. 1), depending on the architecture under consideration.

5

NTR module 102 connects with various components within HPMN 104 and VPMN 108 to implement the NTR solution for its roaming subscriber, like roamer 106. The primary objective of NTR module 102 is to be able to do SoR across multiple telecommunication networks like LTE and GSM.

10

FIG. 2 represents a flowchart for redirecting roaming network traffic in a telecommunication network, in accordance with an embodiment of the present invention. It will be apparent to a person skilled in the art that various steps of the flowchart would be executed by the NTR module 102. At step 202, a registration of a subscriber in a visited network is observed. In an embodiment of the invention, NTR module 102 observes the registration of roamer 106 in VPMN 108. Thereafter, once the registration is successful, at step 204, the NTR module 102 sends one or more messages to VPMN 108 to induce a re-registration attempt by roamer 106. In one embodiment of the present invention, roamer 106 registers to an LTE network and the messages are Diameter messages. In one embodiment of the present invention, NTR module 102 sends these messages, while being deployed in monitoring mode. In another embodiment of the present invention, NTR module 102 sends these messages, while being deployed in in-signaling mode. In another embodiment of the present invention, at step 206, NTR module 102 sends a list of preferred visited networks to the roamer 106 while being in VPMN 108 to induce a re-registration attempt by the

roamer 106 to another visited network. These messages are sent directly to roamer 106's SIM card.

FIG. 3 represents a flow diagram for implementing NTR solution in monitoring mode using an ISD message, in accordance with an embodiment of the present invention. In order to initiate registration to VPMN 108, roamer 106 sends an EMM Attach request to MME 116 in VPMN 108. MME 116 further sends a Diameter – Update Location Request towards HSS 110 of HPMN 104. In response, HSS 110 sends a Diameter - Update Location Accept to MME 116. Thereafter, MME 116 confirms the registration roamer 106 by sending EMM Attach accept message to roamer 106. Now, when roamer 106 is successfully registered in VPMN 108, NTR module 102 attempts SoR to redirect the roamer 106 to another preferred LTE operator.

Therefore, NTR module 102 sends a Diameter ISD request to MME 116, with ODB as the parameter. The MME 116 acknowledges the message and returns Diameter ISD accept to NTR module 102. Thereafter, MME 116 sends a EMM Detach request with an error code #19 for ESM failure. The roamer 106 acknowledges and sends EMM Detach accept message to MME 116. Hence, the roamer 106 is successfully steered away from VPMN 108.

FIG. 4 represents a flow diagram for implementing NTR solution in monitoring mode using a Cancel Location message, in accordance with an embodiment of the present invention. The call flow for this embodiment, is identical to Fig. 3 embodiment, except that NTR module 102 sends a Diameter Cancel

Location Request to MME 116 with cancellation type as subscription withdrawn to force the roamer 106 to steer away from VPMN 106. Also, in this case when MME 116 sends an EMM Detach request it sends with an error code # 7 for EPS not allowed.

5

As mentioned above, the NTR solution can be deployed both in monitoring and in-path mode. FIG. 5 represents a flow diagram for implementing NTR solution in an in-path mode, in accordance with an embodiment of the present invention. In this case, when roamer 106 sends the EMM Attach request to MME 116 and subsequently the MME 116 sends a Diameter UL request, this message is received by NTR module 102 as it is deployed in signaling path. Now, in order to apply SoR, NTR module 102 sends a Diameter UL Answer (Reject) that results in an error code.

The Diameter LTE steering enables to control the radio access technology. In other words, it enables the deploying operator of favoring preferred partner or controlling the traffic distribution between networks but also between Radio Access Technologies (RAT).

The rejection of the Diameter Registration procedures results in various error codes in the radio interface of the mobile of roamer 106. In accordance with various embodiments of the present invention, the NTR module 102 is able to induce the following new error codes on the radio interfaces:

1. Cause #15 (no suitable cells in Tracking Area), #12 "tracking area not allowed", #13 "roaming not allowed in this tracking area and it forces

the UE to reselect another RAT in the same PMN. The location area is added to the list of "forbidden LAs for roaming" which is stored in the mobile.

2. Cause #14 "EPS services not allowed in this PLMN" is received by the UE, the chosen PLMN identity shall be stored in the "forbidden PLMNs for GPRS service".

3. Cause #19, "ESM failure", the UE may set the attach attempt counter to 5 and directly attempt to register on another network.

The NTR module 102 also follows the usual rejection principles available in SS7 steering. For example,

- Cause #11 (PMN Not Allowed)

It forces the mobile UE (User Equipment) to perform a PMN reselection. The mobile UE shall store the PMN identity in the "forbidden PMN list" in the card and the UE shall no more reselect this PMN.

- Cause #17 (Network Failure) -- leading to additional registration re-attempts (up to 5 attempts) from the mobile before changing network.

Since the NTR solution intercepts the DIAMETER Update Location Request, it can respond with the correct Diameter Update Location Answer (Reject) leading to the expected radio error code and handset behavior.

The mapping table to be applied is as follows:

Diameter Reject Cause	Radio Error cause
DIAMETER_ERROR_UNKNOWN_EPS_SUBSCRIPTION	#15 "No suitable cells in tracking area"
DIAMETER_AUTHORIZATION_REJECTED (5003)	#15 "No suitable cells in tracking area"
DIAMETER_ERROR_RAT_NOT_ALLOWED (5421)	#15 "No suitable cells in tracking area", or #13 "Roaming not allowed in this tracking area", or #12 "Tracking area not allowed" Note – the cause selection is an operator's choice
DIAMETER_ERROR_ROAMING_NOT_ALLOWED (5004)	#11 "PLMN not allowed"
DIAMETER_UNABLE_TO_COMPLY (5012), DIAMETER_INVALID_AVP_VALUE (5004)	#17 "Network failure"
DIAMETER - Roaming restricted in MME due to unsupported feature, in of the Subscription-Data, part of the Update Location Answer	#14 "EPS services not allowed in this PLMN"
OPERATOR_DETERMINED_BARRING is received in the Subscriber-Status AVP, part of the Update Location Answer	#19 "ESM failure"

In yet another embodiment of the present invention, the NTR module 102
5 performs OTA based steering in LTE environment. There are some mobile devices
which do not maintain an SMS stack in LTE networks. Hence, they need an applet to
open an IP channel for specific events. For example, the SIM card in the handset may
detect the entry in a new PMN or handset may restart. In such a scenario, the SIM
card may open an IP channel with OTA server. The OTA server may then request for
10 a dynamic preference list. This request is intercepted by the NTR module 102. At this
stage, the NTR module 102 sends the list of preferred networks where it wants to steer

its subscriber. Upon receiving the list, the OTA server sends relevant EF files to the handset.

In accordance with various other embodiment of the present invention, the
5 NTR module 102 is also able to redirect network traffic across multiple networks from different RAT. E.g. NTR solution can steer a roamer from LTE to GSM or vice versa.

In the context of coexistence of LTE with pre-LTE technology, the mobility
10 management of outbound roamers may happen in different fashions, from a core network perspective:

- EPS only registration i.e. the registration is entirely happening between the MME and HSS.
- 15 • EPS and non-EPS registration for CSFB and/or Single Radio Voice Call Continuity (SRVCC) i.e. the registration happens between the MME-HSS and MSC/VLR-HLR.
- non-EPS registration i.e. the registration happens between the MSC/VLR – HLR and the SGSN-HLR.

20

It should be noted that while CSFB makes the call happen on the CS-domain, an advantage of the SRVCC is to provide the possibility of a Voice over LTE to fall back to 2G/3G without disruption to the CS-domain, or loss of conversation, in case of an LTE loss of radio coverage. One challenge of the previous steering solution is
25 to identify the current registration status of the subscriber. In other words, the NTR

solution determines whether the subscriber is attached to an E-UTRAN or UTRAN/GERAN network access.

This information is required to correctly apply the rejection principles linked to the observed GSM UL. In some cases, GSM UL may happen for combined
5 EPS/Non-EPS registration but also as a standalone scenario, in case of MO/MT call occurring under a new coverage area. It is therefore required to identify in the scenario of the subscriber as a GSM UL does not provided any information.

In specific scenario of 'Circuit-Switched Fallback' (CSFB), the legacy (GSM)
10 and evolved core network protocol (LTE), MAP and Diameter, respectively coexist. When a registration process including CSFB happens, the order of messages observed at HSS/HLR is fully determined. The GSM UL registration only happens after a successful Diameter UL procedure (ULR/ULA).

In other words, observed messages will follow the sequence:

15

1. Diameter ULR
2. Diameter ULA (assumed successful)
3. GSM UL
4. ISD/ISD ACK
- 20 5. GSM UL ACK

Now if standard SoR is applied on MAP it would mark the Diameter registration as successful but with failure on non-EPS domain. This would lead to ineffective SoR or new steering attempts but with counter rules associated with the
25 EPS domain and not the GSM domain. This misleads the NTR module that would assume a possible manual registration of the subscriber. The observed behavior will

vary on handset type (data- or voice-centric), but would be likely to end up in an ineffective steering of roaming action.

It should be obvious for a person skilled in the art that an independent MAP
5 based NTR platform is likely to interfere with the MAP message as it would be
unaware of a previous Diameter registration. This would affect negatively the user
experience at a time of a call activity. Hence, the NTR solution of the present
invention is enhanced with Diameter-handling capabilities like the NTR solution must
have information about the two sets of registration procedures (Diameter and MAP).

10

In accordance with an embodiment of the present invention, the NTR module
102 in such case performs SoR by first observing a registration process of the
subscriber in VPMN 108. Thereafter, the NTR module 102 identifies the subscriber's
registration on either an LTE network or a GSM network. In case of registration at
15 GSM network, NTR module 102 further identifies whether the roamer's registration is
due to loss of LTE coverage or due to CSFB. If registration is due to loss of LTE
coverage, then NTR module 102 sends messages to the MME 116 to induce a re-
registration attempt by the subscriber to another visited network.

20 However, in order to check for above-mentioned conditions, the NTR module
gains some knowledge about the registration.

Firstly, the NTR module 102 determines whether roamer 106 is attached to an
LTE or pre-LTE network. For this, if NTR module 102 observes Diameter ULR (and
25 the corresponding interface S6a), then it can be deduced that roamer 106 is on LTE

network. Similarly, if NTR module 102 observes GPRS UL or a Diameter message on the S6d SGSN-HSS interface, then the roamer 106 is on pre-LTE (or GSM) network.

Secondly, the NTR module 102 identifies whether observed MAP messages
5 are related to CSFB activity (i.e., initial registration or at MO/MT call activity) or a regular registration in a legacy (i.e. 2G/3G) network due to a lack of LTE radio coverage or LTE roaming agreement.

Different approaches may be used for identify these cases – their application
10 will depend on the information found in the MAP/Diameter signaling, which depends on the Release implemented.

A first set of parameter that is maintained by the system:

- A timer (T-ULR) will be started after each allowed Diameter ULR on
15 S6a. The timer is maintained per subscriber.
- A timer (T-GPRS-UL) will be started after each allowed GPRS UL (or Diameter ULR on S6d). The timer is maintained per subscriber.
- A timer (T-GSM-UL) will be started after each allowed GSM UL. The timer is maintained per subscriber.

20

A second set of information is based on the observation of specific fields in the MAP message e.g. CSMO flag GSM UL, CSMT flag in GSM UL, EPS info in GPRS UL, etc.

A third set of information is based on active subscriber state polling. The NTR solution of the present invention sends MAP PSI message to the last known VLR or Diameter InsertSubscriberData Request (IDR) to the last known MME for determining the current subscriber state.

5

The NTR solution of the present invention is also able to check content of Cancellation message (Diameter CancelLocation Request (CLR) or MAP CancelLocation (CL), and more precisely the Cancellation Type.

10 In case the NTR module finds that roamer is within the LTE network, it then validates via a timing condition or message content whether the registration is expected to be related to a CSFB or an actual loss of coverage.

- If the timer value is below a configurable threshold, it can be expected
15 the GSM UL relates to a CSFB registration.
- If the timer value is above a configuration, it can be expected the GSM
UL related to loss of coverage. However, the timing condition may be
overruled by specific messaging fields (e.g. CSMO flag) or by
implementing a polling mechanism which informs that the subscriber
20 is currently busy in a call or still attached to the EPS domain.

With above intelligence, an operator can deploy the NTR solution in multiple combinations, as shown in the table below.

		Diameter Module	
		Passive	In-Path
MAP Module	Passive	Yes	Yes
	In-Path	Yes	Yes

It will be apparent to a person skilled in the art, that the present invention can also be applied to Code Division Multiple Access (CDMA)/ American National Standards Institute # 41D (ANSI-41D), and various other technologies such as, but not limited to, VoIP, WiFi, 3GSM and inter-standard roaming. In one exemplary case, a CDMA outbound roamer travels with an HPMN CDMA handset. In another exemplary case, the CDMA outbound roamer travels with an HPMN GSM SIM and a GSM handset. In yet another exemplary case, GSM outbound roamer travels with an HPMN CDMA RUIM and a CDMA handset. To support these variations, system 100 will have a separate SS7 and network interfaces, corresponding to both the HPMN and VPMN networks. It will also be apparent to a person skilled in the art that these two interfaces in different directions may not have to be the same technologies. Moreover, there could be multiple types of interface in both directions.

An exemplary list of the mapping between GSM MAP and ANSI-41D is described in the table below as a reference.

GSM MAP	ANSI-41D
Location Update/ISD	REGNOT
Cancel Location	REGCAN
RegisterSS	FEATUREREQUEST
InterrogateSS	FEATUREREQUEST
SRI-SM	SMSREQ
SRI	LOCATION REQUEST
ForwardSMS	SMSDPP
ReadyForSMS	SMSNOTIFICATION
AlertServiceCenter	SMSNOTIFICATION
ReportSMSDelivery	SMDPP
ProvideRoamingNumber	ROUTING REQUEST

The present invention can take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment containing both hardware and software elements. In accordance with an embodiment of the present invention, software, including but not limited to, firmware, resident software, and microcode,
5 implements the invention.

Furthermore, the invention can take the form of a computer program product, accessible from a computer-usable or computer-readable medium providing program code for use by, or in connection with, a computer or any instruction execution
10 system. For the purposes of this description, a computer-usable or computer readable medium can be any apparatus that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

15 The medium can be an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system (or apparatus or device) or a propagation medium. Examples of a computer-readable medium include a semiconductor or solid state memory, magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk and an optical disk. Current
20 examples of optical disks include compact disk – read only memory (CDROM), compact disk – read/write (CD-R/W) and Digital Versatile Disk (DVD).

The components of present system described above include any combination of computing components and devices operating together. The components of the
25 present system can also be components or subsystems within a larger computer

system or network. The present system components can also be coupled with any number of other components (not shown), such as other buses, controllers, memory devices, and data input/output devices, in any number of combinations. In addition, any number or combination of other processor-based components may be carrying out
5 the functions of the present system.

It should be noted that the various components disclosed herein may be described using computer aided design tools and/or expressed (or represented), as data and/or instructions embodied in various computer-readable media, in terms of their
10 behavioral, register transfer, logic component, transistor, layout geometries, and/or other characteristics. Computer-readable media in which such formatted data and/or instructions may be embodied include, but are not limited to, non-volatile storage media in various forms (e.g., optical, magnetic or semiconductor storage media) and carrier waves that may be used to transfer such formatted data and/or instructions
15 through wireless, optical, or wired signaling media or any combination thereof.

Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise," "comprising," and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in a
20 sense of "including, but may not be limited to." Words using the singular or plural number also include the plural or singular number respectively. Additionally, the words "herein," "hereunder," "above," "below," and words of similar import refer to this application as a whole and not to any particular portions of this application. When the word "or" is used in reference to a list of two or more items, it covers all of the

following interpretations: any of the items in the list, all of the items in the list and any combination of the items in the list.

The above description of illustrated embodiments of the present system is not
5 intended to be exhaustive or to limit the present system to the precise form disclosed.
While specific embodiments of, and examples for, the present system are described
herein for illustrative purposes, various equivalent modifications are possible within
the scope of the present system, as those skilled in the art will recognize. The
teachings of the present system provided herein can be applied to other processing
10 systems and methods. They may not be limited to the systems and methods described
above.

The elements and acts of the various embodiments described above can be
combined to provide further embodiments. These and other changes can be made in
15 light of the above detailed description.

Other Variations

Provided above for the edification of those of ordinary skill in the art, and not
20 as a limitation on the scope of the invention, are detailed illustrations of a scheme for
proactive roaming tests, discoveries of roaming partner services and discoveries of
frauds in roaming using simulated roaming traffic. Numerous variations and
modifications within the spirit of the present invention will of course occur to those of
ordinary skill in the art in view of the embodiments that have been disclosed. For
25 example, the present invention is implemented primarily from the point of view of

GSM mobile networks as described in the embodiments. However, the present invention may also be effectively implemented on GPRS, 3G, CDMA, WCDMA, WiMax etc., or any other network of common carrier telecommunications in which end users are normally configured to operate within a "home" network to which they normally subscribe, but have the capability of also operating on other neighboring networks, which may even be across international borders.

The examples under the system of present invention detailed in the illustrative examples contained herein are described using terms and constructs drawn largely from GSM mobile telephony infrastructure. However, use of these examples should not be interpreted as limiting the invention to those media. The system and method can be of use and provided through any type of telecommunications medium, including without limitation: (i) any mobile telephony network including without limitation GSM, 3GSM, 3G, CDMA, WCDMA or GPRS, satellite phones or other mobile telephone networks or systems; (ii) any so-called WiFi apparatus normally used in a home or subscribed network, but also configured for use on a visited or non-home or non-accustomed network, including apparatus not dedicated to telecommunications such as personal computers, Palm-type or Windows Mobile devices; (iii) an entertainment console platform such as Sony Playstation, PSP or other apparatus that are capable of sending and receiving telecommunications over home or non-home networks, or even (iv) fixed-line devices made for receiving communications, but capable of deployment in numerous locations while preserving a persistent subscriber id such as the eye2eye devices from Dlink; or telecommunications equipment meant for voice over IP communications such as those provided by Vonage or Packet8.

In describing certain embodiments of the system under the present invention, this specification follows the path of a telecommunications call, from a calling party to a called party. For the avoidance of doubt, such a call can be a normal voice call, in
5 which the subscriber telecommunications equipment is also capable of visual, audiovisual or motion-picture display. Alternatively, those devices or calls can be for text, video, pictures or other communicated data.

In the foregoing specification, specific embodiments of the present invention
10 have been described. However, one of ordinary skill in the art will appreciate that various modifications and changes can be made without departing from the scope of the present invention as set forth in the claims below. Accordingly, the specification and the figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of present
15 invention. The benefits, advantages, solutions to problems, and any element(s) that may cause any benefit, advantage, or solution to occur, or to become more pronounced, are not to be construed as a critical, required, or essential feature or element of any or all of the claims.

APPENDIX

Acronym	Description
3G	Third generation of mobile
ACM	ISUP Address Completion Message
ANM	ISUP Answer Message
ANSI-41	American National Standards Institute #41
ATI	Any Time Interrogation
BCSM	Basic Call State Model
BSC	Base Station Controller
BOIC	Barring Outgoing International Calls
BOIC-EX-Home	Barring Outgoing International Calls except to home country
CAMEL	Customized Application for Mobile Enhanced Logic
CAP	Camel Application Part
CB	Call Barring
CC	Country Code
CDMA	Code Division Multiplexed Access
CdPA	Called Party Address
CDR	Call Detail Record
CF	Call Forwarding
CgPA	Calling Party Address
CIC	Circuit Identification Code
CLI	Calling Line Identification
CSD	Circuit Switched Data
CSI	Camel Subscription Information
DPC	Destination Point Code
DSD	Delete Subscriber Data
DEA	Diameter Edge Agent
DRA	Diameter Routing Agent
DTMF	Dual Tone Multi-Frequency
ERB	CAP Event Report Basic call state model
EU	European Union
FPMN	Friendly Public Mobile Network
FTN	Forward-To-Number
GLR	Gateway Location Register
GGSN	Gateway GPRS Support Node
GMSC	Gateway MSC
GMSC-F	GMSC in FPMN
GMSC-H	GMSC in HPMN
GPRS	General Packet Radio System
GSM	Global System for Mobile
GSMA	GSM Association
GSM SSF	GSM Service Switching Function
GsmSCF	GSM Service Control Function
GT	Global Title
GTP	GPRS Tunnel Protocol

HLR	Home Location Register
HPMN	Home Public Mobile Network
IN	Intelligent Network
IOT	Inter-Operator Tariff
GTT	Global Title Translation
IAM	Initial Address Message
IDP	Initial DP IN/CAP message
IDD	International Direct Dial
IMSI	International Mobile Subscriber Identity
IMSI-H	HPMN IMSI
IN	Intelligent Network
INAP	Intelligent Network Application Part
INE	Interrogating Network Entity
IP	Internet Protocol
IREG	International Roaming Expert Group
IRS	International Revenue Share
ISC	International Service Carrier
ISD	MAP Insert Subscriber Data
ISG	International Signal Gateway
IST	Immediate Service Termination
ISTP	International STP
ISTP-F	ISTP connected to FPMN STP
ISTP-H	ISTP connected to HPMN STP
ISUP	ISDN User Part
ITPT	Inbound Test Profile Initiation
ITR	Inbound Traffic Redirection
IVR	Interactive Voice Response
LU	Location Update
LUP	MAP Location Update
MAP	Mobile Application Part
MCC	Mobile Country Code
MCC	Mobile Country Code
MD	Missing Data
ME	Mobile Equipment
MGT	Mobile Global Title
MMS	Multimedia Message Service
MMSC	Multimedia Message Service Center
MMSC-F	FPMN MMSC
MMSC-H	HPMN MMSC
MNC	Mobile Network Code
MNP	Mobile Number Portability
MO	Mobile Originated
MOS	Mean Opinion Score
MS	Mobile Station
MSC	Mobile Switching Center
MSISDN	Mobile Station International Subscriber Directory Number
MSISDN-F	FPMN MSISDN

MSISDN-H	HPMN MSISDN
MSRN	Mobile Station Roaming Number
MSRN-F	FPMN MSRN
MSRN-H	HPMN MSRN
MT	Mobile Terminated
MTP	Message Transfer Part
NDC	National Dialing Code
NP	Numbering Plan
NPI	Numbering Plan Indicator
NRTRDE	Near Real Time Roaming Data Exchange
O-CSI	Originating CAMEL Subscription Information
OCN	Original Called Number
ODB	Operator Determined Barring
OPC	Origination Point Code
OR	Optimal Routing
ORLCF	Optimal Routing for Late Call Forwarding
OTA	Over The Air
OTPI	Outbound Test Profile Initiation
PDP	Protocol Data Packet
PDN	Packet Data Network
PDU	Packet Data Unit
PRN	MAP Provide Roaming Number
PSI	MAP Provide Subscriber Information
QoS	Quality of Service
RAEX	Roaming Agreement EXchange
RI	Routing Indicator
RIS	Roaming Intelligence System
RDN	Redirecting Number
RNA	Roaming Not Allowed
RR	Roaming Restricted due to unsupported feature
RRB	CAP Request Report Basic call state model
RSD	Restore Data
RTP	Real-Time Transport Protocol
SAI	Send Authentication Info
SC	Short Code
SCA	Smart Call Assistant
SCCP	Signal Connection Control part
SCP	Signaling Control Point
SF	System Failure
SG	Signaling Gateway
SGSN	Serving GPRS Support Node
SGSN-F	FPMN SGSN
SIM	Subscriber Identity Module
SIGTRAN	Signaling Transport Protocol
SME	Short Message Entity
SM-RP-UI	Short Message Relay Protocol User Information
SMS	Short Message Service
SMSC	Short Message Service Center

SMSC-F	FPMN SMSC
SMSC-H	HPMN SMSC
SoR	Steering of Roaming
SPC	Signal Point Code
SRI	MAP Send Routing Information
SRI-SM	MAP Send Routing Information For Short Message
SS	Supplementary Services
SS7	Signaling System #7
SSN	Sub System Number
SSP	Service Switch Point
STK	SIM Tool Kit Application
STP	Signal Transfer Point
STP-F	FPMN STP
STP-H	HPMN STP
TADIG	Transferred Account Data Interchange Group
TAP	Transferred Account Procedure
TCAP	Transaction Capabilities Application Part
VT-CSI	Visited Terminating CAMEL Service Information
TP	SMS Transport Protocol
TR	Traffic Redirection
TS	Traffic Steering
TT	Translation Type
UD	User Data
UDH	User Data Header
UDHI	User Data Header Indicator
USSD	Unstructured Supplementary Service Data
VAS	Value Added Service
VIP	Very Important Person
VLR	Visited Location Register
VLR-F	FPMN VLR
VLR-H	HPMN VLR
VLR-V	VPMN VLR
VMSC	Visited Mobile Switching Center
VoIP	Voice over IP
VPMN	Visited Public Mobile Network
ATI	Access Transport Information
UDV	Unexpected Data Value
USI	User Service Information
WAP	Wireless Access Protocol

Technical references

Between AS and HSS	3GPP TS 29.328 & TS 29.329
Between AS and SLF	3GPP TS 29.328 & TS 29.329
Between AS and OFCS	RFC 4006, 3GPP TS 32.225 & TS 32.299
Between AS and OCS	RFC 4006, 3GPP TS 32.225 & TS 32.299
Between OCF and Rating function	3GPP TS 32.296
Between CSCF and HSS	3GPP TS 29.228 & TS 29.229
Between CSCF and SLF	3GPP TS 29.228 & TS 29.229
Between PCRF and SPR	3GPP TS 23.203, TS 29.328 & TS 29.329
Between AF and the PCRF	3GPP TS 23.203 & TS 29.214
Rx reference point for EPC	3GPP TS 32.820, 3GPP TS 23.203 & TS 29.214
Between PCEF and the PCRF	3GPP TS 29.212 & TS 23.203
Between OCS and PCEF	3GPP TS 32.29, TS 32.251 & RFC 4006
Between PCEF and OFCS	3GPP TS 32.240, TS 32.295
Between AF and PDF	3GPP TS 29.209
Between Packet Domain and an external packet data network	3GPP TS 29.061
between the EPC based PLMN and the packet data network	3GPP TS 29.061
Between BSF and HSS	3GPP TS 29.109 & TS 33.220
Between BSF and SLF	3GPP TS 29.109 & TS 33.220
Between BSF and NAF	3GPP TS 29.109 & TS 33.220
Between BSF and Zn Proxy	3GPP TS 29.109 & TS 33.220

Between the 3GPP AAA Server and an SLF	3GPP TS 29.234
Between the WLAN AN and the 3GPP AAA Proxy	3GPP TS 29.234
Between the 3GPP AAA Proxy and 3GPP AAA Server	3GPP TS 29.234
Between the 3GPP AAA Server and the HSS	3GPP TS 29.234
Between the 3GPP AAA Server and the PDG	3GPP TS 29.234
Between the 3GPP AAA Server/Proxy and the WAG	3GPP TS 29.234
Between the 3GPP AAA Server and the PNA	3GPP TS 29.234
Between the 3GPP AAA Server and the PDG	3GPP TS 29.234
Between GGSN and BM-SC	3GPP TS 29.061
Mz is the roaming variant of the Gmb reference point with the same functionality	3GPP TS 29.061
CCF to BS	3GPP TS TS 32.225
Multimedia Messaging Service (MMS)	OMA MM10 interface
Between AGW and PCRF	3GPP2 TSG-X X.S0013-014
Between AF and PCRF	3GPP2 TSG-X X.S0013-013
Between MME and HSS	3GPP TS 29.272
Between the 3GPP AAA Server/Proxy and the PDN GW	3GPP TS 23402
Between MME and HSS	3GPP TS 29.272
Transfer of (QoS) policy information from PCRF to the S-GW.	3GPP TS 32820, TS 23402
Between PCRF in the HPLMN (H PCRF) and a PCRF in the VPLMN (V PCRF)	3GPP TS 23.203 & TS 29.215
Between MME and EIR	3GPP TS 29.272
PCRF and the BBERF	3GPP TS 23.203
Between ePDG and vPCRF	3GPP TS 23.203
PCRF and the BBERF	3GPP TS 23.203
Between an un-trusted non-3GPP IP access and the 3GPP AAA Server/Proxy	3GPP TS 23402
Between the 3GPP AAA Proxy and 3GPP AAA Server	3GPP TS 23402
Between Untrusted Non-3GPP IP Access and ePDG	3GPP TS 23402

Between the 3GPP AAA Server/Proxy and the ePDG	3GPP TS 23402
Between the 3GPP AAA Server and the HSS	3GPP TS 23402
Between a trusted non-3GPP IP access and the 3GPP AAA Server/Proxy	3GPP TS 23402
Between the 3GPP AAA Server and the HA	3GPP TS 23402

CLAIMS

1. A method for redirecting roaming network traffic in an LTE network, the method being executed by a network traffic redirection, NTR, module and comprising:
 - observing (202) a registration process of a subscriber in a visited network (108);
 - upon successful registration, sending (204) one or more messages to the visited network (108) to induce a re-registration attempt by the subscriber to another visited network, wherein the one or more messages are one of Diameter Insert Subscriber Data Request, IDR, message and Diameter Cancel Location Request, CLR, message,
 - and wherein said sending one or more messages to the visited network (108) comprises:
 - identifying the subscriber's registration on at least one of an LTE network or a GSM network;
 - for registration at the GSM network, identifying whether the registration is due to loss of LTE coverage or Circuit-Switched Fallback, CSFB; and
 - if registration is due to loss of LTE coverage, then sending said one or more messages to the visited network to induce a re-registration attempt by the subscriber to another visited network.
2. The method of claim 1, wherein said sending one or more messages comprises sending (206) a list of preferred visited networks to the subscriber while being in the visited network (108), to induce a re-registration attempt by the subscriber to another visited network, optionally, wherein the list of preferred visited networks (108) is sent in response to an applet on subscriber's handset i) being able to detect one of roaming, network registration change, handset start, and activation timer, and ii) opening a communication channel to get the list of networks.
3. The method of claim 1, wherein the registration process is executed between an MME (116) in the visited network (108), and HSS (110) of a home network (104) of the subscriber.
4. The method of claim 1, wherein the one or more messages are sent to an MME (116) corresponding to the subscriber's visited network (108).
5. The method of claim 1, further comprising one of:

rejecting the subscriber's registration invoking a radio technology change from LTE to GSM; and

discriminating between subscriber's dual registration or consecutive registration, by analyzing the signalling pattern.

6. The method of claim 1, wherein the subscriber's registration is dual registration for CSFB, over LTE network for data access and GSM network for voice access.

7. A system for redirecting roaming network traffic in a LTE network, the system comprising:

a network traffic redirection, NTR module (102) configured to observe a registration process of a subscriber in a visited network (108); the NTR module (102) further configured to send one or more messages to the visited network (108) to induce a re-registration attempt by the subscriber to another visited network, wherein the one or more messages are one of Diameter Insert Subscriber Data Request, IDR, message and Diameter Cancel Location Request, CLR, message,

and wherein the NTR module (102) is configured to:

identify the subscriber's registration on at least one of an LTE network or a GSM network;

for registration at the GSM network, identify whether the registration is due to loss of LTE coverage or Circuit-Switched Fallback, CSFB; and

if registration is due to loss of LTE coverage, then send said one or more messages to the visited network to induce a re-registration attempt by the subscriber to another visited network (108).

8. The system of claim 7, wherein the NTR module (102) is configured to send one of:

one or more messages post successful registration of the subscriber in the visited network (108); and

a list of preferred visited networks to the subscriber while being in the visited network (108), to induce a re-registration attempt by the subscriber to another visited network.

9. The system of claim 7, wherein the NTR module is configured to observe the registration process executed between an MME (116) in the visited network, and HSS (110) of a home network (104) of the subscriber.

10. The system of claim 7, wherein the NTR module (102) is configured to send the one or more messages to an MME (116) corresponding to the subscriber's visited network (108).