What is claimed is:

1. A gas generator, comprising:

    a water tank, having a first hollow portion for containing electrolyzed water, and a pipe; and

    an electrolysis device, disposed inside the first hollow portion of the water tank, the electrolysis device comprising an electrolysis tank separating an inner space of the electrolysis device from the first hollow portion, the electrolysis tank having an opening for passing the electrolyzed water from the first hollow portion of the water tank to the inner space of the electrolysis device, the electrolysis device being arranged to electrolyze the electrolyzed water to generate a gas comprising hydrogen;

    wherein the gas generator is arranged for the pipe to refill the electrolyzed water into the first hollow portion of the water tank, such that the level of water for the electrolyzed water in the first hollow portion of the water tank is higher than 90% of a full level of water of the water tank.

2. The gas generator of claim 1, arranged for, after the electrolysis device electrolyzed the electrolyzed water, the electrolyzed water to be filled into the first hollow portion of the water tank and the electrolysis device for allowing the level of water thereof to be between 90% of the full level of water and 99.99% of the full level of water.

3. The gas generator of claim 1, arranged for the pipe output the gas comprising hydrogen.

4. The gas generator of claim 1, further comprising:

    a water pump, coupled with the first hollow portion of the water tank for circulating the electrolyzed water in the first hollow portion of the water tank.

5. The gas generator of claim 4, wherein the water pump comprises an inlet pipe and an outlet pipe, the water tank comprises an outlet opening and an inlet opening, the outlet pipe of the water pump being arranged for coupling with the inlet opening of the water

tank, and the inlet pipe of the water pump being arranged for coupling with the outlet opening of the water tank.

6. The gas generator of claim 1, further comprising a nebulized gas mixing tank, wherein the nebulized gas mixing tank is arranged to receive the gas comprising hydrogen, and the nebulized gas mixing tank is arranged to generate a nebulized gas to be mixed with the gas comprising hydrogen to form a healthy gas for users to breathe, wherein the nebulized gas is selected from a group consisting of water vapor, nebulized medicinal liquid, evaporated essential oil, and the combination thereof.

7. The gas generator of claim 4, further comprising:

   a cooling device, for coupling to the electrolysis device, for cooling down the electrolyzed water;

   wherein, gas generator is arranged for the water pump to be coupled between the cooling device and the electrolysis device.

8. The gas generator of claim 7, further comprising a microcomputer controller, the microcomputer controller being arranged to control the water pump and to detect the temperature of the electrolyzed water and control an inputting flow rate and an outputting flow rate of the water pump according to the detected temperature of the electrolyzed water.

9. The gas generator of claim 8, wherein the microcomputer controller comprises a temperature sensor for detecting the temperature of the electrolyzed water.

10. The gas generator of claim 9, wherein the cooling device comprises a radiator and a fan, the radiator comprises a box and a radiating tube, the radiating tube is disposed in the box, and the fan is fixed on an outer surface of the box of the radiator.

11. The gas generator of claim 7, arranged for the temperature of the electrolyzed water contained in the electrolysis device to be between 55℃ and 65℃.