

1. Field of the Invention

This invention relates to a hydroisomerization process for the production, from paraffin feeds, of high purity paraffinic solvent compositions characterized as mixtures of C_8 - C_{20} n-paraffins and isoparaffins, with the isoparaffins containing predominantly methyl branching and an isoparaffin:n-paraffin ratio sufficient to provide products having superior low temperature properties and low viscosities.

2. Background

Paraffinic solvents provide a variety of industrial uses. For example, NORPAR solvents, several grades of which are marketed by Exxon Chemical Company, e.g., are constituted almost entirely of C_{10} - C_{15} linear, or normal paraffins (n-paraffins). They are made by the molecular sieve extraction of kerosene via the ENSORB process. These solvents, because of their high selective solvency, low reactivity, mild odor and relatively low viscosity, are used in aluminum rolling oils, as diluent solvents in carbonless copy paper, and in spark erosion machinery. They are used successfully in pesticides, both in emulsifiable concentrates and in formulations to be applied by controlled droplet application, and can even meet certain FDA requirements for use in food-related applications. The NORPAR solvents, while having relatively low viscosity, unfortunately have relatively high pour points; properties which cannot be improved in the ENSORB process by a wider n-paraffin cut because the $C_{15}+$ n-paraffins have low melting points. Thus, the addition of $C_{15}+$ paraffins will only worsen the pour point.

Three typical grades of NORPAR solvents are NORPAR 12, NORPAR 13, and NORPAR 15; the numerals 12, 13, and 15 respectively, designating the average carbon number of the paraffins contained in the paraffinic mixture. Solvents with an average

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced


carbon number of 14 rarely meet the specifications of the specialty solvent market, and consequently such solvents are generally downgraded and sold as fuel. The NORPAR 15 solvent, while it generally meets the specifications of the specialty solvent market, has a relatively high melting point and must be stored in heated tanks.

Solvents constituted of mixtures of highly branched paraffins, or isoparaffins, with very low n-paraffin content, are also commercially available. For example, several grades of ISOPAR solvents, i.e., isoparaffins or highly branched paraffins, are supplied by Exxon Chemical Company. These solvents, derived from alkylate bottoms (typically prepared by alkylation), have many good properties; e.g., high purity, low odor, good oxidation stability, low pour point, and are suitable for many food-related uses. Moreover, they possess excellent low temperature properties. Unfortunately however, the ISOPAR solvents have high viscosities, e.g., as contrasted with the NORPAR solvents. Despite the need, a solvent which possesses substantially the desirable properties of both the NORPAR and ISOPAR solvents, but particularly the low viscosity of the NORPAR solvents and the low temperature properties of the ISOPAR solvents is not available.

3. The Invention

The present invention, to meet these and other needs, relates to a process which comprises contacting and reacting, with hydrogen, a feed characterized as a mixture of paraffins, predominantly n-paraffins, having from about 8 to about 20 carbon atoms per molecule, i.e., about C₈-C₂₀, preferably about C₁₀-C₁₆, over a dual function catalyst at conditions sufficient to hydroisomerize and convert the feed to a mixture of isoparaffins of substantially the same carbon number, i.e., C₈-C₂₀, or C₁₀-C₁₆, which contain greater than fifty percent, 50%, mono-methyl species, e.g., 2-methyl, 3-methyl, 4-methyl, ≥5-methyl or the like, with minimum formation of branches with substituent

groups of carbon number greater than 1, i.e., ethyl, propyl, butyl or the like, based on the total weight of isoparaffins in the mixture. Preferably, the isoparaffins of the product mixture contain greater than 70 percent of the mono-methyl species, based on the total weight of the isoparaffins in the mixture. The product solvent composition has an isoparaffin:n-paraffin ratio ranging from about 0.5:1 to about 9:1, preferably from about 1:1 to about 4:1. The product solvent composition boils within a range of from about 320°F to about 650°F, and preferably within a range of from about 350°F to about 550°F. To prepare different solvent grades, the paraffinic solvent mixture is generally fractionated into cuts having narrow boiling ranges, i.e., 100°F, or 50°F boiling ranges.

In the ensuing hydroisomerization reaction a major concentration of the paraffinic feed is thus converted into isoparaffins which contain one or more methyl branches, with little or no cracking of the molecules. The carbon number distribution of the molecular constituents of the product is essentially the same as that of the feed. A feed constituted of an essentially C₈-C₂₀ paraffinic mixture of n-paraffins will produce a product rich in C₈-C₂₀ isoparaffins which contain greater than 50 percent mono-methyl paraffins, and preferably greater than 70 percent mono-methyl paraffins, based on the weight of the product. A feed constituted of an essentially C₁₀-C₁₆ paraffinic mixture of n-paraffins will produce a product constituted essentially of a C₁₀-C₁₆ paraffinic mixture of isoparaffins which contains greater than 50 percent mono-methyl paraffins, and preferably greater than 70 percent mono-methyl paraffins, based on the weight of the product. The solvent product has an isoparaffin:n-paraffin ratio ranging from about 0.5:1 to about 9:1, preferably about 1:1 to about 4:1, and boils within a range of from about 320°F to about 650°F, preferably from about 350°F to about 550°F.

The properties of these solvents e.g., viscosity, solvency and density, are similar to NORPAR solvents of similar volatility but have significantly improved low

temperature properties (e.g., lower pour or lower freeze points). These solvents also have significantly lower viscosities than ISOPAR solvents of similar volatility. In fact, these solvents combine many of the most desirable properties found in the NORPAR and ISOPAR solvents. The solvents made by the process of this invention have the good low temperature properties of ISOPAR solvents and the low viscosities of the NORPAR solvent; and yet maintain most of the other important properties of these solvents.

The C₈-C₂₀ paraffinic feed, or C₁₀-C₁₆ paraffinic feed, is preferably one obtained from a Fischer-Tropsch process; a process known to produce substantially n-paraffins having negligible amounts of aromatics, sulfur and nitrogen compounds. The Fischer-Tropsch liquid, and wax, is characterized as the product of a Fischer-Tropsch process wherein a synthetic gas, or mixture of hydrogen and carbon monoxide, is processed at elevated temperature over a supported catalyst comprised of a Group VIII metal, or metals, of the Periodic Table Of The Elements (Sargent-Welch Scientific Company, Copyright 1968), e.g., cobalt, ruthenium, iron, etc., especially cobalt which is preferred. A distillation showing the fractional make up (± 10 wt.% for each fraction) of a typical Fischer-Tropsch reaction product is as follows:

<u>Boiling Temperature Range</u>	<u>Wt.% of Fraction</u>
IBP - 320°F	13
320 - 500°F	23
500 - 700°F	19
700 - 1050°F	34
1050°F+	<u>11</u>
	100

The NORPAR solvents, which are predominantly n-paraffins, can be used as feeds and upgraded to solvents having lower pour points. A solvent with an average

carbon number of 14 is, e.g., a suitable and preferred feed, and can be readily upgraded to solvents having considerably lower pour points, without loss of other important properties.

The paraffinic feed is contacted, with hydrogen, at hydroisomerization conditions over a bifunctional catalyst, or catalyst containing a metal, or metals, hydrogenation component and an acidic oxide support component active in producing hydroisomerization reactions. Preferably, a fixed bed of the catalyst is contacted with the feed at temperature ranging from about 400°F to about 850°F, preferably from about 550°F to about 700°F, and at pressures ranging generally from about 100 pounds per square inch gauge (psig) to about 1500 psig, preferably from about 250 psig to about 1000 psig sufficient to hydroisomerize, but avoid cracking, the feed. Hydrogen treat gas rates range from about 1000 SCFB to about 10,000 SCFB, preferably from about 2000 SCFB to about 5000 SCFB, with negligible hydrogen consumption. Space velocities range generally from about 0.5 W/Hr/W to about 10 W/Hr/W, preferably from about 1.0 W/Hr/W to about 5.0 W/Hr/W.

The active metal component of the catalyst is preferably a Group VIII metal, or metals, of the Periodic Table Of The Elements (Sargent-Welch Scientific Company Copyright 1968), suitably in sulfided form, in amount sufficient to be catalytically active for dehydrogenation of the paraffinic feed. The catalyst may also contain, in addition to the Group VIII metal, or metals, a Group IB and/or a Group VIB metal, or metals, of the Periodic Table. Generally, metal concentrations range from about 0.05 percent to about 20 percent, based on the total weight of the catalyst (wt.%), preferably from about 0.1 wt. percent to about 10 wt. percent. Exemplary of such metals are such non-noble Group VIII metals as nickel and cobalt, or mixtures of these metals with each other or with other metals, such as copper, a Group IB metal, or molybdenum, a Group VIII metal. Palladium and platinum are exemplary of suitable Group VIII noble metals. The metal, or metals, is incorporated with the support component of the

catalyst by known methods, e.g., by impregnation of the support with a solution of a suitable salt or acid of the metal, or metals, drying and calcination.

The catalyst support is constituted of metal oxide, or metal oxides, components at least one component of which is an acidic oxide active in producing olefin cracking and hydroisomerization reactions. Exemplary oxides include silica, silica-alumina, clays, e.g., pillared clays, magnesia, titania, zirconia, halides, e.g., chlorided alumina, and the like. The catalyst support is preferably constituted of silica and alumina, a particularly preferred support being constituted of up to about 35 wt.% silica, preferably from about 2 wt.% to about 35 wt.% silica, and having the following pore-structural characteristics:

<u>Pore Radius, Å</u>	<u>Pore Volume</u>
0-300	>0.03 ml/g
100-75,000	<0.35 ml/g
0-30	<25% of the volume of the pores with 0-300 Å radius
100-300	<40% of the volume of the pores with 0-300 Å radius

The base silica and alumina materials can be, e.g., soluble silica containing compounds such as alkali metal silicates (preferably where $\text{Na}_2\text{O}:\text{SiO}_2 = 1:2$ to $1:4$), tetraalkoxy silane, orthosilic acid ester, etc.; sulfates, nitrates, or chlorides of aluminum alkali metal aluminates; or inorganic or organic salts of alkoxides or the like. When precipitating the hydrates of silica or alumina from a solution of such starting materials, a suitable acid or base is added and the pH is set within a range of about 6.0 to 11.0. Precipitation and aging are carried out, with heating, by adding an acid or base under reflux to prevent evaporation of the treating liquid and change of pH. The remainder of the support producing process is the same as those commonly employed, including filtering, drying and calcination of the support material. The support may

also contain small amounts, e.g., 1-30 wt.%, of materials such as magnesia, titania, zirconia, hafnia, or the like.

Support materials and their preparation are described more fully in U.S. Patent No. 3,843,509 incorporated herein by reference. The support materials generally have a surface area ranging from about 180-400 m²/g, preferably 230-375 m²/g, a pore volume generally of about 0.3 to 1.0 ml/g, preferably about 0.5 to 0.95 ml/g, bulk density of generally about 0.5-1.0 g/ml, and a side crushing strength of about 0.8 to 3.5 kg/mm.

The hydroisomerization reaction is conducted in one or a plurality of reactors connected in series, generally from about 1 to about 5 reactors; but preferably the reaction is conducted in a single reactor. The paraffinic feed is fed, with hydrogen, into the reactor, or first reactor of a series, to contact a fixed bed of the catalyst at hydroisomerization reaction conditions sufficient to hydroisomerize and convert at least a portion of the feed to products suitable as high purity paraffinic solvent compositions, as previously described.

If desired, the hydroisomerized product can be hydrotreated to remove trace amounts of impurities, if any, olefins, etc. This type of treatment may be sometimes desirable to render the product suitable to meet FDA specifications, or the like.

The following exemplifies the more salient features of the invention. All parts, and percentages, are given in terms of weight unless otherwise specified.

Example

A vaporous feed containing 87.7 wt.% nC₁₄ was passed, with hydrogen at 1800 SCF/B into a reactor and hydroisomerized over a fixed bed of a Pd catalyst (0.3 wt.% Pd on an amorphous silica-alumina support consisting of about 20 wt.% bulk SiO₂ + 80 wt.% Al₂O₃), with minimal cracking of the feed, to produce a product having substantially the same carbon number distribution as the feed, but with considerably lower viscosities, and better low temperature properties than that of the feed. The carbon distribution numbers (C-No.) of the feed are given as follows:

nC ₁₂	0.045 wt.%
nC ₁₃	4.444 wt.%
nC ₁₄	87.697 wt.%
nC ₁₅	7.639 wt.%
nC ₁₆	0.175 wt.%

The reaction was conducted with gradual increase of the space velocity of the entering feed, and temperature, to produce liquid products having the freeze points, and C₁₂+ yields given below:

<u>Space Velocity</u> <u>V/H/V</u>	<u>Temp,</u> <u>°F</u>	<u>%nC₁₄ In</u> <u>Product</u>	<u>Freeze</u> <u>Point, °C</u>	<u>C₁₂+ Yield</u> <u>wt.% on Feed</u>
34.3	636	51.5	-4	99.1
34.8	646	39.1	-6.5	98.2
35.0	656	28.1	-11.5	96.6
37.1	666	21.1	-15.5	92.1
34.0	667	15.6	-20	89.3
40.2	677	12.3	-23.5	87.0

A complete yield workup of the liquid product obtained at a freeze point of -20°C is given in Table 1A.

TABLE 1A
YIELD WORKUP

		Feed, wt.% n-par	TLP, wt.% n-par
		C-No	
Conditions V/H/V	34	1	0.002
		2	0.012
		3	0.234
		4	0.433
		5	0.373
Temp., F	667	6	0.505
Psig	400	7	0.496
H ₂ Treat, SCF/B	1800	8	0.461
		9	0.420
		10	0.335
H ₂ Uptake, SCF/B	70	11	0.110
		12	0.045
TLP Freeze, C	-20	13	4.444
		14	87.697
		15	7.639
		16	0.175
		Sum	100
			24.520
TLP 15/5 Distillation	wt.%	Yield, wt.% FF	
i-320 F	5.79		
320/425 F	2.43	C4-minus	1.123
425/460 F	15.17	C5/320 F	5.947
460 F+	76.61	320/425 F	2.400
Total	100	425/460 F	14.987
		460 F+	75.680
		Total	100.137

⁽¹⁾ n-C₁₃ G.C. peak contains some i-C₁₄ overlap

A workup of the product fractions obtained from the 15/5 distillation described above is given in Table 1B.

TABLE 1B
PRODUCT FRACTIONS

		i-320 F			320-425 F			425-460 F			460 F+	
		nor	other		nor	other		nor	other		nor	other
C-No.												
4		1.086	0.923		0.114	0.185		0.013	0.027			
5		4.420	5.435		0.105	0.218		0.005	0.011			
6		6.660	9.014		0.096	0.135		0.002	0.004			
7		6.659	13.384		0.322	0.429		0.009	0.009			
8		5.761	16.794		1.437	2.816		0.071	0.116			
9		3.898	16.405		3.526	9.263		0.288	0.665			
10		0.807	8.297		6.288	22.410		0.659	2.150			0.007
11		0.004	0.446		1.696	14.741		0.368	2.017			0.028
12			0.007		0.955	8.587		0.877	4.037		0.086	0.171
13					0.547	18.258		4.574	32.690		2.804	8.622
14					0.035	7.837		1.462	49.930		20.543	61.789
15									0.016		1.079	4.768
16											0.013	0.090
Total		29.295	70.705		15.121	84.879		8.328	91.672		24.525	75.475

Table 1B continued

		i-320 F			320-425 F			425-460 F			460 F+	
		nor	other		nor	other		nor	other		nor	other
Freeze, C												
Pred						-68		-45				
Meas											-12.5	
Br Index											40	
cST@100C											0.901	
API											52.5	
Flash, F											225	
D-93												

It is apparent that various minor modifications and changes can be made without departing the spirit and scope of the invention.



CLAIMS:

1. A process for the production of high purity paraffinic solvent compositions having superior low temperature properties and low viscosities which comprises

contacting a feed constituted predominantly of n-paraffins of carbon number ranging from about C₈ to about C₂₀, with hydrogen, over a dual function catalyst at conditions sufficient to hydroisomerize and convert the feed to a mixture of isoparaffins which contains greater than 50 percent of mono-methyl species, with minimum formation of branches with substituent groups of carbon number greater than 1, based on the total weight of isoparaffins in the mixture, and

recovering a high purity paraffinic solvent composition of carbon number ranging from about C₈ to about C₂₀ rich in isoparaffins which contain greater than 50 percent of said mono-methyl species, and having a molar ratio of isoparaffins:n-paraffins ranging from about 0.5:1 to about 9:1.

2. The process of Claim 1 wherein the feed is constituted predominantly of n-paraffins of carbon number ranging from about C₁₀ to about C₁₆, and the product high purity paraffinic solvent composition has carbon numbers ranging from about C₁₀ to about C₁₆.

3. The process of Claim 1 wherein the feed is converted to a product high purity paraffinic solvent composition rich in isoparaffins which contains greater than 70 percent of the mono-methyl species.



4. The process of Claim 1 wherein the high purity paraffinic solvent composition that is recovered has a molar ratio of isoparaffins:n-paraffins ranging from about 1:1 to about 4:1.

5. The process of Claim 1 wherein the feed is converted to a product high purity paraffinic solvent composition rich in isoparaffins which contains greater than 70 percent of the mono-methyl species, and has a molar ratio of isoparaffins:n-paraffins ranging from about 1:1 to about 4:1.

6. The process of Claim 1 wherein the product high purity paraffinic solvent composition boils at a temperature ranging from about 320°F to about 650°F.

7. The process of Claim 6 wherein the product high purity paraffinic solvent composition boils at a temperature ranging from about 350°F to about 550°F.

8. The process of Claim 1 wherein the high purity solvent composition product is characterized as a mixture of paraffins of carbon number ranging from about C₁₀ to about C₁₆, has a molar ratio of isoparaffins:n-paraffins ranging from about 1:1 to about 4:1 and the isoparaffins of the mixture contain greater than 70 percent of the mono-methyl species, based on the weight of the mixture.

9. The process of Claim 1 wherein the feed is hydroisomerized at temperature ranging between about 400°F and about 800°F, at pressures ranging between about 100 psig and about 1500 psig, hydrogen treat gas rates ranging between about 1000 SCFB and about 10,000 SCFB, and at space velocities ranging between about 0.5 W/Hr/W to about 10 W/Hr/W.



- 16 -

10. The process of Claim 9 wherein the feed is hydroisomerized at temperature ranging between about 550°F and about 700°F, at pressures ranging between about 250 psig and about 1000 psig, hydrogen treat gas rates ranging between about 2000 SCFB and about 5000 SCFB, and at space velocities ranging between about 1.0 W/Hr/W and about 5.0 W/Hr/W.