

(51) International Patent Classification:
H04L 1/16 (2006.01)(21) International Application Number:
PCT/SE2008/051427(22) International Filing Date:
9 December 2008 (09.12.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/076,899 30 June 2008 (30.06.2008) US(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET L M ERICSSON (PUBL)** [SE/SE]; S-164 83 Stockholm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ASTELY, David** [SE/SE]; Stobaevägen 22, SE-168 56 Bromma (SE). **HU, Yang** [CN/CN]; Ming guang building, Beijing University of Post and Telecom, Beijing, 100876 (CN). **WAN, Lei** [CN/CN]; No. 703, Building 4, Shui Qing Mu Hua Yuan, Beijing, 100080 (CN). **LARSSON, Daniel** [SE/SE]; Storgatan 50, S-SE-171 52 Solna (SE).(74) Agent: **HASSELGREN, Joakim**; Ericsson AB, Patent Unit LTE, S-164 80 Stockholm (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD AND ARRANGEMENT IN A TELECOMMUNICATION SYSTEM




Fig. 3a




Fig. 3b




Fig. 3c

(57) **Abstract:** A method in a terminal for providing an ACK/NAK message to a base station is provided. The terminal counts the number of assigned downlink subframes detected from the base station resulting in k . The terminal then establishes whether each of a number of transport blocks comprised in the counted k downlink subframes is correctly received or not. In the case when each one of the transport blocks, comprised in the k downlink subframes is estimated as correctly received the terminal provides to the base station an encoded ACK message for the k subframes, which comprises k , the number of subframes.