

“SYSTEM AND METHOD OF LOADING AND UNLOADING CONTAINERS”

Field of the Invention

The present invention relates to a system and method of loading and
5 unloading shipping containers onto and off a tilt-tray truck and relates
particularly, though not exclusively, to an ejector assembly for assisting in
unloading such a container from a tilt-tray truck.

Background to the Invention

Cargo or sea containers are commonly used for transporting goods either on
10 land by rail or road transport, or at sea on container ships. Such shipping
containers are generally of a rectangular parallelepiped configuration so as to
enable the containers to be stacked one on top of the other or to enable the
containers to be supported on a deck of a ship or on a tray of a transport
vehicle such as a railcar or road vehicle. Shipping containers are usually
15 provided with doors on at least one end to provide access to the interior of
the container. Corner fittings or sockets are provided at each external corner
of the container for engagement by connecting devices to secure the
container to the deck of a ship or tray of a vehicle or to secure containers
together. The corner fittings include elongate apertures on the lower side of
20 the container for receipt of rotatable cleats or lugs of the connecting devices
which are receivable within the apertures and which are rotatable to lock the
containers in position. Apertures are also provided in the corner fittings on
the top, side and end faces of the container so that containers stacked upon
each other can be locked together or adjacent containers locked together by
25 similar connecting devices in an end-to-end or side-by-side configuration.

A particular difficulty occurs when a shipping container which is on the
ground is to be loaded onto a road vehicle having a flat bed or tray, but no
crane or hoist to lift the container onto the tray. With this type of vehicle the
bed or tray (which is often slidably mounted on the vehicle chassis) is tilted to
30 an inclined position and moved into longitudinal alignment with and adjacent

to an end of the container. A winch cable, attached to a winch provided centrally at a front end of the tilt-tray, is coupled to the container. When the winch is operated, the intention is for the container to be drawn onto the tray. However it is not uncommon for the end of the container to abut the rear end
5 of the tray and to become jammed against the rear end of the tray, thereby preventing the container from being winched onto the tray of the vehicle. The result is that a substantial load is then placed on the winch producing high tension in the cable, with the potential for catastrophic failure of either the winch or the cable. If the cable should break it may result in severe injury and
10 even death for any person in the vicinity who may be struck by the cable.

To help avoid this situation and to make it easier to load a container onto a vehicle flat-bed tilt-tray, commonly-owned Australian Patent No 2006900175 describes a method and apparatus for loading containers which involves the use of a specially designed elongated drawbar assembly. The method and
15 apparatus of AU2006900175 has been very successful in overcoming the problems associated with loading a container onto a flat-bed tray. However there are also problems associated with the reverse process of unloading a container from a flat-bed tray. For example, when the container is ready to be unloaded, the gravitational forces acting on the container by tilting the tray
20 may not be sufficient to overcome the frictional forces between the bottom of the container and the tray. There is a risk that the container may slide backwards off the tray in an uncontrolled manner.

The present invention was developed with a view to providing a system and method of both loading and unloading a shipping container more safely from
25 a flat-bed tray. The invention also relates to an ejector assembly for assisting in unloading a shipping container from a vehicle tray, and relates more particularly to a vehicle with a tilt-tray which is fitted with such an ejector assembly.

References to prior art in this specification are provided for illustrative
30 purposes only and are not to be taken as an admission that such prior art is part of the common general knowledge in Australia or elsewhere.

Summary of the Invention

According to one aspect of the present invention there is provided a method of loading and unloading a shipping container onto and off a tilt-tray vehicle, the method comprising the steps of:

- 5 releasably attaching a drawbar assembly to opposite corner connectors provided on the container such that the drawbar assembly extends transversely of the container adjacent a lower edge of the container and forwardly of the container;

- inclining the vehicle tray and positioning a rear edge of the tray adjacent the
10 drawbar assembly on the lower edge of the container;

applying traction to the drawbar assembly to draw the container onto the vehicle tray and to facilitate loading of the container onto the tray wherein, in use, the drawbar assembly cooperates with the inclined tray to lift the lower edge of the container onto the tray;

- 15 when it is desired to unload the container releasably engaging the drawbar assembly attached to the container on the tray with an ejector assembly; and, moving the ejector assembly towards the rear of the tray to move the container partially off the vehicle to facilitate unloading of the container off the vehicle tray.

- 20 Preferably when it is desired to unload the container the method further comprises the steps of inclining the vehicle tray and moving the tray until a rear edge of the container rests on the ground at a designated drop-off point.

- Typically when the ejector assembly has moved to its fully extended position the container, attached to the drawbar assembly, hangs about 600 mm over
25 the rear of the tray.

Preferably when it is desired to unload the container the method further comprises the steps of releasing the drawbar assembly from the container and, with the ejector assembly, returning it to a rest position. Preferably at the

same time as, or subsequent to, the step of returning the drawbar assembly to the rest position, the vehicle is slowly driven forward so that the remainder of the container slides off the tray and comes to rest on the designated drop-off point.

- 5 According to another aspect of the present invention there is provided a system of loading and unloading a shipping container onto and off a tilt-tray vehicle, the system comprising:

a drawbar assembly adapted to be releasably attached to opposite corner connectors provided on the container such that the drawbar assembly
10 extends transversely of the container adjacent a lower edge of the container and forwardly of the container;

means for applying traction to the drawbar assembly to draw the container onto the vehicle tray and to facilitate loading of the container onto the tray wherein, in use, when the vehicle tray is inclined and positioned with the back
15 of the tray adjacent the drawbar assembly, the drawbar assembly cooperates with the inclined tray to lift the lower edge of the container onto the tray; and,

an ejector assembly adapted to releasably engage the drawbar assembly when the container has been loaded onto the tray wherein, in use, when it is desired to unload the container the ejector assembly is moved towards the
20 rear of the tray to move the container partially off the tray to facilitate unloading of the container off the vehicle.

Preferably the ejector assembly is provided in connection with the vehicle tray and is movable between a fully retracted and fully extended position on the tray. Advantageously the ejector assembly comprises an ejector head
25 which is movable between a raised position in which it extends upwards from an upper surface of the vehicle tray and a lowered position in which it is concealed below the upper surface of the vehicle tray whereby, in use, in the raised position the ejector head can engage with the drawbar assembly whereas in the lowered position it disengages from the drawbar assembly.

30 Preferably the ejector assembly further comprises an hydraulic cylinder for

moving the ejector assembly between the fully retracted and fully extended positions.

Typically the means for applying traction comprises a winch provided on the vehicle tray and a winch cable which can be attached to the drawbar
5 assembly.

The described system and method of loading and unloading containers may be employed with any ISO standard size shipping container, from 8 foot to 48 foot in length. Typically it may be used with a 20 foot container. More typically the invention may provide for a system and method of loading and
10 unloading a shipping container, wherein the container is a 40 foot container.

According to a further aspect of the present invention there is provided an ejector assembly for moving a container partially off a tilt-tray vehicle, the ejector assembly being movable between a fully retracted and fully extended position on the tray to facilitate unloading of the container off the vehicle tray.

15 Preferably the ejector assembly is provided in connection with the vehicle tray. Advantageously the ejector assembly comprises an ejector head which is movable between a raised position, in which it extends upwards from an upper surface of the vehicle tray, and a lowered position in which it is concealed below the upper surface of the vehicle tray. Preferably the ejector
20 head is adapted to releasably engage a drawbar assembly attached to the container. Preferably in the raised position the ejector head can engage with the drawbar assembly whereas in the lowered position it disengages from the drawbar assembly. The ejector assembly typically further comprises an hydraulic cylinder for moving the ejector assembly between the fully retracted
25 and fully extended positions.

Throughout the specification, unless the context requires otherwise, the word "comprise" or variations such as "comprises" or "comprising", will be understood to imply the inclusion of a stated integer or group of integers but not the exclusion of any other integer or group of integers. Likewise the word
30 "preferably" or variations such as "preferred", will be understood to imply that

a stated integer or group of integers is desirable but not essential to the working of the invention.

Brief Description of the Drawings

- 5 The nature of the invention will be better understood from the following detailed description of a specific embodiment of the system and method of loading and unloading shipping containers, given by way of example only, with reference to the accompanying drawings, in which:

10 Figure 1 is a front elevation of a preferred embodiment of a drawbar assembly according to the present invention;

Figure 2 is a plan view of the drawbar assembly of Figure 1;

Figure 3 is a rear elevation of the drawbar assembly of Figure 1;

Figure 4 is a cross-section view through the line A-A in Figure 2 illustrating a locking mechanism of the drawbar assembly of Figure 1;

15 Figure 5 illustrates the method of releasably attaching the drawbar assembly of Figure 1 to a shipping container;

Figure 6 is a side elevation partial section view of a preferred embodiment of an ejector assembly according to the present invention showing the ejector assembly in a fully retracted position;

20 Figures 7 (a) and (b) are a side elevation and a section view respectively of the ejector assembly of Figure 6 showing the ejector assembly in a fully extended position;

Figure 8 is a plan view of the ejector assembly of Figure 7 showing the ejector assembly in a fully extended position;

25 Figures 9 to 10 illustrate the method of loading a shipping container onto a tray of a vehicle using the ejector assembly of Figure 6;

Figures 11 to 13 illustrate the method of unloading a shipping container from a tray of a vehicle using the ejector assembly of Figure 6; and,

Figures 14 to 23 illustrate each of the steps in a preferred embodiment of the method of loading and unloading a shipping container from the tray of a vehicle according to the present invention.

5 Detailed Description of Preferred Embodiments

A preferred embodiment of the system of loading and unloading a shipping container onto and off a tilt-tray vehicle in accordance with the invention, as illustrated in Figures 1-13, comprises a drawbar assembly 10. The drawbar assembly 10 is adapted to be releasably attached to opposite corner
10 connectors 12 provided on a shipping container 14 such that the drawbar assembly 10 extends transversely of the container 14 adjacent a lower edge of the container and forwardly of the container (see Figure 5). The drawbar assembly 10 is similar to the draw bar assembly described in commonly-owned Australian Patent No 2006900175, the contents of which are
15 incorporated herein by reference.

The drawbar assembly 10 comprises an elongated hollow beam 16 of rectangular cross-section which is typically fabricated of bisalloy, but may be made of any suitably strong and rigid material. The hollow beam 16 is preferably formed with a plurality of holes 17 at spaced intervals along its
20 length, the holes 17 passing through both upper and lower walls of the beam 16. The holes 17 reduce the overall weight of the beam 16 without compromising its mechanical integrity. A slot 19 is provided centrally of the hollow beam 16, the slot passing through both upper and lower walls of the beam. The slot 19 is provided to enable the drawbar assembly 10 to
25 cooperate with an ejector assembly 60, as will be described below.

The respective ends of the beam 16 are bevelled such that the beam has a shorter length at its front face 18 relative to its rear face 20. The bevelled ends of the beam 16 are provided with guide members in the form of end plates 22 secured to the respective ends of the beam 16 by welding. The end
30 plates 22 thus converge towards each other. The guide members further

comprise flanges 24 which extend from the end plates 22, the flanges 24 extending forwardly of the front face 18 of the beam 16 and also converging towards each other at a greater extent than the convergence of the end plates 22. Skid members 26 are also provided at the respective ends of the beam 16 but welded to the underside of the beam at right angles to the guide members. The skid members 26 also have forwardly extending flanges 28, which are angled upwards to facilitate sliding movement of the drawbar assembly 10 in a forwards direction.

Container attachment devices 30 are provided at the respective ends of the beam 16, each attachment device 30 including a locking bar 32, as can be seen most clearly in Figure 4. The locking bar 32 is in the form of a cylindrical rod rotatably received in a bearing-like manner within the hollow beam 16 and extending between the front and rear faces of the beam 16. A radially extending handle 34 is fixed to one end of the locking bar 32 at the front face 18 of the beam by respective castellated retaining nuts 35. The opposite end of the locking bar 32 is provided with a cam-like off-centre engagement lug 36 fixed for rotation with the locking bar 32. The engagement lugs 36 are adapted to be received in the respective corner connectors 12 of the shipping container 14. Handles 34 can be pivoted through 90° to rotate the locking bars 32 so that the engagement lugs 36 move between an engaged and disengaged position.

A draw plate 40, as shown in Figures 1 and 2, is fixed at a central position to the front face 18 of the beam 16 by welding through a stiffening plate 42. Spacer blocks 44 are provided at each end of the beam 16 on the rear face 20, to enable the drawbar assembly 10 to be connected to the container. Sometimes there are protruding parts along the front and/or rear edge of a container; spacer blocks 44 are designed to allow the rear face 20 of the beam 16 to sit in front of such protruding parts. The spacer blocks 44 are welded to the rear face 20 of the beam 16 in the region of the locking bar 32 of the container attachment devices 30.

The drawbar assembly 10 is designed for use with a vehicle 50 of the type having a flat-bed tray 52 mounted for tilting and/or tilt-slide movement relative to a chassis of the vehicle 50. The tray 52 is provided with means for applying traction to the drawbar assembly 10 in the form of a winch 54
5 arranged centrally of and at a front end of the tray, as shown in Figures 9 to 23. The winch 54 has a cable 56 which can be coupled to the draw plate 40 of the drawbar assembly 10 to draw the container 14 onto the vehicle tray 52 and to facilitate loading of the container 14 onto the tray 52. A rear edge of the tray 52 is preferably provided with a small ramp 58 to assist in guiding a
10 container 14 onto the tray (see Figures 14 and 15). In use, when the vehicle tray 52 is inclined and positioned with the rear edge of the tray adjacent the drawbar assembly 10, the drawbar assembly cooperates with the inclined tray 52 to lift the lower edge of the container 14 onto the tray. This will be described in more detail below.

15 The system of loading and unloading a shipping container further comprises an ejector assembly 60 adapted to releasably engage the drawbar assembly 10 when the container 14 has been loaded onto the tray 52. In the illustrated embodiment the ejector assembly 60 is provided in connection with the vehicle tray 52, as can be seen most clearly in Figures 9 to 23. As illustrated
20 in Figures 6 to 8, the ejector assembly 60 is movable between a fully retracted and fully extended position on the tray 52. Advantageously the ejector assembly 60 comprises an ejector head 62 which is movable between a raised position, in which it extends upwards from an upper surface of the vehicle tray 52 as shown in Figure 7, and a lowered position in which it is
25 concealed below the upper surface of the vehicle tray 52 as shown in Figure 6. In use, in the raised position the ejector head 62 can engage with the drawbar assembly 10 whereas in the lowered position it disengages from the drawbar assembly 10. Preferably the ejector head 62 engages with the slot
30 19 provided for this purpose in the beam 16 of the drawbar assembly 10. The ejector assembly 60 further comprises an hydraulic cylinder 64 for moving the ejector assembly 60 between the fully retracted and fully extended positions.

As can be seen most clearly in Figures 6 to 8, the ejector assembly 60 is mounted longitudinally within the floor of the flat-bed tray 52 within a rectangular housing 66. The rectangular housing 66 is welded to the frame of the flat-bed tray 52 and forms an integral part of the tray 52. An elongate guide channel 68 extends the full length of the housing 66 and guides the ejector head 62 while it is moving between the fully retracted and fully extended positions. The hydraulic cylinder 64 is fixed to and extends from the rear end of the rectangular housing 66 towards the rear of the tray 52. The ejector head 62 is L-shaped and is preferably pivotally attached to the free end of the piston rod of the hydraulic cylinder 62. A remotely controlled activator (not visible) is provided to pivot the ejector head 62 from the lowered to the raised position, and vice versa. As will be described in more detail below, in use, when it is desired to unload the container 14 the ejector assembly 60 is moved towards the rear of the tray 52 to slide the container 14 in a controlled manner partially off the tray 52 to facilitate unloading of the container off the vehicle.

The vehicle tray 52 is preferably also provided with longitudinally extending upstanding guides 70 along the respective side edges of the tray 52 (see Figure 14). The guides 70 are adapted to cooperate with the end plates 22 and flanges 24 of the guide members, together with the skid members 26 and their forwardly extending flanges 28 on the respective ends of the drawbar assembly 10, to guide the container 14 as it is drawn onto the tray 52.

A preferred method of loading and unloading a shipping container onto and off a tilt-tray vehicle in accordance with the invention will now be described with reference to Figures 9 to 23.

To load a container 14 onto the tray 52 using the drawbar assembly 10, the vehicle 50 is first operated to incline the vehicle tray 52 and position the rear edge of the tray 52 adjacent the drawbar assembly 10 on the lower edge of the container 14, as shown in Figure 14. The drawbar assembly 10 is then manually slid from its secured position near the winch 54 down the vehicle

tray 52 close to the container 14. A tool (not illustrated) may be used to perform this manual operation. The tool is approximately 1m long with a handle at one end and a hook at the other. The operator simply hooks the drawbar assembly 10 with the tool and draws it down the tray 52. By using a
5 tool of this nature the operator's posture is maintained in an upright position during this manual operation. The draw bar assembly 10 is then releasably attached to opposite corner connectors 12 provided on the container 14 using the container attachment devices 30. The hollow beam 16 of the drawbar assembly 10 thus extends transversely of the container 14 with the
10 draw plate 40 extending in a forwards direction.

If not already connected, the drawbar assembly 10 then has its draw plate 40 connected via a coupling such as a shackle to the winch cable 56. The transmission of the vehicle 50 is put in neutral and the brake released. Traction is then applied to the drawbar assembly 10 by operating the winch
15 54 to apply tension to the cable 56 and to draw the container 14 onto the vehicle tray 52.

Since the drawbar assembly 10 is at the lower edge of the container 14 it will firstly engage the ramp 58, and as it is pulled up the ramp 58 it will elevate the front edge of the container 14 as shown in Figure 15. This provides a
20 smooth transition of the front edge of the container 14 onto the tray 52. At the same time, the respective flanges 24 and 28 on the ends of the drawbar assembly will engage and cooperate with the guides 70 along the respective sides on the upper surface of the tray 52. Any misalignment of the container 14 relative to the tray 52 during loading will be corrected by the cooperation
25 between the guides 70 and the angled end plates 22 and their flanges 24 and the skid members 26 and their flanges 28 which serve to centralise the drawbar assembly 10 and the container 14 relative to the tray 52. Thus, even if the vehicle 50 and the container 14 are not quite aligned, the cooperation between the guides 70 and the angled end plates 22 and their flanges 24 and
30 the skid members 26 and their flanges 28 perform a self-centring function. The driver of the vehicle simply turns the vehicle steer wheels, via the

steering wheel, as the vehicle 50 is drawn backwards to align it with the container 14.

Continued operation of the winch 54 will cause the drawbar assembly 10 and the attached container 14 to be drawn further onto the tray 52 as shown in
5 Figure 16 (see also Figure 9). Throughout this operation, the rear end of the container 14 remains stationary on the ground, whilst the vehicle 50 and tray 52 is drawn under the container. When the container 14 has been drawn wholly onto the tray 52, the winch 54 continues to operate until the container reaches the position shown in Figure 17 (see also Figure 10). In this position
10 the container corner connectors 12 are typically aligned with corresponding fittings on the tray 52 so that the container can be secured to the tray. The tray 52 can then be pivoted back to its horizontal position as shown in Figure 18. The container 14 is locked onto the tray 52 via the corner connectors and is then fully loaded on the vehicle 50. The drawbar assembly 10 can then be
15 detached from the container 14 and stowed in the vehicle 50, or it can be left attached to the container 14 during transport.

In order to unload the container 14, the drawbar assembly is first reattached to the respective corner connectors 12 provided on the front lower edge of the container 14, (see Figure 5). All four bottom corner connectors 12 on the
20 container 14 are released from the flat-bed tray 52. The drawbar assembly 10 may then be releasably engaged by the ejector assembly 60. The ejector head 62 is pivoted to the raised position so that it engages with the slot 19 in the drawbar assembly 10 as shown in Figures 11 and 19. At the same time, or subsequently, the tray 52 is tilted to an inclined position. When it is desired
25 to unload the container 14, the ejector assembly 60 is moved towards the rear of the tray 52. Hydraulic cylinder 64 is operated to begin moving the ejector head 62, with the drawbar assembly 10 and container 14 attached, towards the rear of the tray 52, as shown in Figures 12, 13 and 20, to move the container 14 in a controlled manner partially off the vehicle to facilitate
30 unloading of the container off the vehicle tray.

When the ejector assembly 60 has moved to its fully extended position the container 14 (attached to the drawbar assembly 10) hangs about 600 mm over the rear of the tray 52. The tilt-tray 52 is then lowered so that the rear lower edge of the container 14 makes purchase with a designated drop-off point, as shown in Figure 21, cushioned by blocks (not illustrated) to protect the surface of the designated drop-off point.

The drawbar assembly 10 is then released from the container 14 and, with the ejector assembly 60, returned to the rest position using the remote control. At the same time, or subsequently, the vehicle 50 is slowly driven forward so that the remainder of the container 14 slides off the tray 52 and comes to rest on the designated drop-off point, as shown in Figures 22 and 23. When drawbar assembly 10 has returned to its rest position, the ejector head 62 is disengaged from the drawbar assembly 10 and returned to its lowered position beneath the upper surface of the tilt-tray 52. The drawbar assembly 10 is then secured in a locked position on the tray 52.

The described system and method of loading and unloading containers can be employed with any ISO standard size shipping container, from 8 foot to 48 foot in length. Typically it is used with 20 foot containers. More typically it is used with 40 foot containers. It can also be used with two containers that are joined end-to-end.

Now that a preferred embodiment of the system and method of loading and unloading shipping containers has been described in detail, it will be apparent that the described embodiment provides a number of advantages over the prior art, including the following:

- (i) The system and method enables a container to be quickly, safely and efficiently loaded and unloaded from a tilt-tray vehicle without the need for a crane or hoist.
- (ii) The drawbar assembly and ejector assembly ensure the loading and unloading operation is as smooth and safe as possible without resulting in the container getting stuck at any point, and avoiding unacceptable delays and hazards.

(iii) The ejector assembly provides an effective means of unloading the container which cooperates with the drawbar assembly.

It will be readily apparent to persons skilled in the relevant arts that various
5 modifications and improvements may be made to the foregoing
embodiments, in addition to those already described, without departing from
the basic inventive concepts of the present invention. For example, whilst
the described ejector assembly is designed to operate with the drawbar
assembly it will be apparent that with minor modifications it may also be used
10 independently of the drawbar assembly to assist with unloading a container
and other ejectable loads. Therefore, it will be appreciated that the scope of
the invention is not limited to the specific embodiments described.

Claims

1. A method of loading and unloading a shipping container onto and off a
5 tilt-tray vehicle, the method comprising the steps of:
- releasably attaching a drawbar assembly to opposite corner connectors
provided on the container such that the drawbar assembly extends
transversely of the container adjacent a lower edge of the container and
forwardly of the container;
- 10 inclining the vehicle tray and positioning a rear edge of the tray adjacent the
drawbar assembly on the lower edge of the container;
- applying traction to the drawbar assembly to draw the container onto the
vehicle tray and to facilitate loading of the container onto the tray wherein, in
use, the drawbar assembly cooperates with the inclined tray to lift the lower
15 edge of the container onto the tray;
- when it is desired to unload the container releasably engaging the drawbar
assembly attached to the container on the tray with an ejector assembly;
and,
- moving the ejector assembly towards the rear of the tray to move the
20 container partially off the vehicle to facilitate unloading of the container off
the vehicle tray.
2. A method of loading and unloading a shipping container as defined in
claim 1, wherein when it is desired to unload the container the method
further comprises the steps of inclining the vehicle tray and moving the tray
25 until a rear edge of the container rests on the ground at a designated drop-
off point.
3. A method of loading and unloading a shipping container as defined in
claim 1 or claim 2, wherein when the ejector assembly has moved to its fully
extended position the container, attached to the drawbar assembly, hangs
30 about 600 mm over the rear of the tray.

4. A method of loading and unloading a shipping container as defined in claim 2, wherein when it is desired to unload the container the method further comprises the steps of releasing the drawbar assembly from the container and, with the ejector assembly, returning it to a rest position.

- 5 5. A method of loading and unloading a shipping container as defined in claim 4, wherein at the same time as, or subsequent to, the step of returning the drawbar assembly to the rest position, the vehicle is slowly driven forward so that the remainder of the container slides off the tray and comes to rest on the designated drop-off point.

- 10 7. A system of loading and unloading a shipping container onto and off a tilt-tray vehicle, the system comprising:

a drawbar assembly adapted to be releasably attached to opposite corner connectors provided on the container such that the drawbar extends transversely of the container adjacent a lower edge of the container and

- 15 forwardly of the container;

means for applying traction to the drawbar assembly to draw the container onto the vehicle tray and to facilitate loading of the container onto the tray wherein, in use, when the vehicle tray is inclined and positioned with the back of the tray adjacent the drawbar assembly, the drawbar assembly
20 cooperates with the inclined tray to lift the lower edge of the container onto the tray; and,

an ejector assembly adapted to releasably engage the drawbar assembly when the container has been loaded onto the tray wherein, in use, when it is desired to unload the container the ejector assembly is moved towards the
25 rear of the tray to move the container partially off the vehicle to facilitate unloading of the container off the vehicle tray.

8. A system of loading and unloading a shipping container as defined in claim 7, wherein the ejector assembly is provided in connection with the vehicle tray and is movable between a fully retracted and fully extended
30 position on the tray.

9. A system of loading and unloading a shipping container as defined in claim 8, wherein the ejector assembly comprises an ejector head which is movable between a raised position in which it extends upwards from an upper surface of the vehicle tray and a lowered position in which it is
5 concealed below the upper surface of the vehicle tray whereby, in use, in the raised position the ejector head can engage with the drawbar assembly whereas in the lowered position it disengages from the drawbar assembly.
10. A system of loading and unloading a shipping container as defined in claim 9, wherein the ejector assembly further comprises an hydraulic
10 cylinder for moving the ejector assembly between the fully retracted and fully extended positions.
11. A system of loading and unloading a shipping container as defined in any one of claims 7 to 10, wherein the means for applying traction comprises a winch provided on the vehicle tray and a winch cable which can
15 be attached to the drawbar assembly.
12. A system of loading and unloading a shipping container as defined in any one of claims 7 to 11, wherein the container is a 40 foot container.
13. An ejector assembly for moving a container partially off a tilt-tray vehicle, the ejector assembly being movable between a fully retracted and fully
20 extended position on the tray to facilitate unloading of the container off the vehicle tray.
14. An ejector assembly as defined in claim 13, wherein the ejector assembly is provided in connection with the vehicle tray.
15. An ejector assembly as defined in claim 14, wherein the ejector
25 assembly further comprises an ejector head which is movable between a raised position, in which it extends upwards from an upper surface of the vehicle tray, and a lowered position in which it is concealed below the upper surface of the vehicle tray.

16. A system of loading and unloading a shipping container as defined in claim 15, wherein the ejector head is adapted to releasably engage a drawbar assembly attached to the container.

17. A system of loading and unloading a shipping container as defined in
5 claim 16, wherein in the raised position the ejector head can engage with the drawbar assembly whereas in the lowered position it disengages from the drawbar assembly.

18. A system of loading and unloading a shipping container as defined in
10 any one of claims 13 to 17, wherein the ejector assembly further comprises an hydraulic cylinder for moving the ejector assembly between the fully retracted and fully extended positions.