

Description

Title of Invention

COMMUNICATION CONTROL DEVICE, COMMUNICATION CONTROL
5 METHOD, RADIO COMMUNICATION SYSTEM, AND TERMINAL DEVICE

Technical Field

[0001]

The present disclosure relates to a communication control device, a
10 communication control method, a radio communication system, and a terminal
device.

Background Art

[0002]

15 Recent radio communication environments have faced problems of
depletion of frequency resources caused due to a rapid increase in data traffic.
Accordingly, to increase network density and improve resource efficiency, network
configurations in which a plurality of cells including macro cells and small cells are
disposed in an overlapping manner can be adopted. For example, heterogeneous
20 networks are networks that are formed in such a manner that various cells in which
radio access technologies, cell sizes, or frequency bands differ coexist.

[0003]

Small cells may, for example, be provided to cover a hot spot, where a
significant amount of traffic occurs. Note that hot spots change dynamically, and
25 therefore, it is not always easy to provide a small cell at a location suitable for a hot
spot. When a plurality of overlapping cells are provided, it is also important to
prevent the cells from adversely interfering with each other. Patent Literature 1
describes a technique for preventing such adverse interference from occurring in a
radio communication system. In the technique, a device that will secondarily use a
30 frequency channel senses a state of communication in a primary system or collects
sensed data, and based on the communication state, determines whether or not the

secondary use is allowed, in advance.

Citation List

Patent Literature

5 [0004]

Patent Literature 1: JP 2010-193433A

Summary of Invention

Technical Problem

10 [0005]

However, the new introduction of an arrangement for sensing the communication state requires correspondingly high cost. If the adverse interference can be prevented by using an existing arrangement at low cost instead of the above sensing, the secondary use of a frequency channel can be promoted, resulting in an increase in network efficiency.

15 [0006]

Under the above circumstances, it is an object of the technology according to the present disclosure to prevent the adverse interference by using an existing arrangement when a frequency channel is secondarily used.

20

Solution to Problem

[0007]

According to the present disclosure, there is provided a communication control device including: an obtaining unit configured to, in a radio communication system including a primary base station to which a primary terminal is connected, and a secondary base station to which a secondary terminal is connected by secondarily using a frequency channel for the primary base station, obtain at least one of a quality report containing a communication quality indicator measured by the primary terminal and a quality report containing a communication quality indicator measured by the secondary terminal; and an interference control unit configured to instruct the secondary base station to reduce transmission power, when it is

25
30

determined that adverse interference is present in the radio communication system, based on the communication quality indicator contained in the quality report obtained by the obtaining unit.

[0008]

5 According to the present disclosure, there is provided a communication control method executed by a communication control device in a radio communication system including a primary base station to which a primary terminal is connected, and a secondary base station to which a secondary terminal is connected by secondarily using a frequency channel for the primary base station, the
10 communication control method including: obtaining at least one of a quality report containing a communication quality indicator measured by the primary terminal and a quality report containing a communication quality indicator measured by the secondary terminal; determining whether or not adverse interference is present in the radio communication system, based on the communication quality indicator
15 contained in the obtained quality report; and instructing the secondary base station to reduce transmission power, if determining that the adverse interference is present.

[0009]

 According to the present disclosure, there is provided a radio communication system including: a primary base station to which a primary terminal
20 is connected; a secondary base station to which a secondary terminal is connected by secondarily using a frequency channel for the primary base station; and a cooperation manager configured to instruct the secondary base station to reduce transmission power, if it is determined that adverse interference is present in the system, based on a communication quality indicator contained in at least one of a quality report
25 containing the communication quality indicator measured by the primary terminal and a quality report containing the communication quality indicator measured by the secondary terminal.

[0010]

 According to the present disclosure, there is provided a terminal device
30 operable in a radio communication system including a primary base station to which a primary terminal is connected, and a secondary base station to which a secondary

terminal is connected by secondarily using a frequency channel for the primary base station, the terminal device including: a control unit configured to generate a quality report containing a communication quality indicator used by a control node configured to determine whether or not adverse interference is present in the radio communication system, the communication quality indicator being used for the determination; and a radio communication unit configured to transmit the quality report generated by the control unit to a base station to which the terminal device is connected.

10 Advantageous Effects of Invention

[0011]

The technology according to the present disclosure provides an arrangement that can prevent the adverse interference when a frequency channel is secondarily used, at low cost.

15

Brief Description of Drawings

[0012]

[FIG. 1] FIG. 1 is an explanatory diagram for explaining an overview of a radio communication system according to an embodiment.

20 [FIG. 2A] FIG. 2A is an explanatory diagram for explaining first example secondary use of a frequency channel.

[FIG. 2B] FIG. 2B is an explanatory diagram for explaining second example secondary use of a frequency channel.

25 [FIG. 2C] FIG. 2C is an explanatory diagram for explaining third example secondary use of a frequency channel.

[FIG. 2D] FIG. 2D is an explanatory diagram for explaining fourth example secondary use of a frequency channel.

[FIG. 3A] FIG. 3A is a first explanatory diagram for explaining a duty ratio in the TDD scheme.

30 [FIG. 3B] FIG. 3B is a second explanatory diagram for explaining a duty ratio in the TDD scheme.

[FIG. 4A] FIG. 4A is a first explanatory diagram for explaining transmission of a measurement report.

[FIG. 4B] FIG. 4B is a second explanatory diagram for explaining transmission of a measurement report.

5 [FIG. 5A] FIG. 5A is an explanatory diagram for explaining a first example and a second example of introduction of a cooperation manager.

[FIG. 5B] FIG. 5B is an explanatory diagram for explaining a third example of introduction of a cooperation manager.

[FIG. 6] FIG. 6 is a block diagram showing an example configuration of a terminal
10 device according to an embodiment.

[FIG. 7] FIG. 7 is a block diagram showing an example configuration of a cooperation manager according to an embodiment.

[FIG. 8] FIG. 8 is an explanatory diagram showing a relationship between a base station and a terminal in a first interference scenario.

15 [FIG. 9] FIG. 9 is a flowchart showing an example flow of a communication control process that is performed by a cooperation manager in the first interference scenario.

[FIG. 10] FIG. 10 is an explanatory diagram showing a relationship between a base station and a terminal in a second interference scenario.

[FIG. 11] FIG. 11 is an explanatory diagram showing a relationship between a base
20 station and a terminal in a third interference scenario.

[FIG. 12] FIG. 12 is a flowchart showing an example flow of a communication control process that is performed by a cooperation manager in the third interference scenario.

[FIG. 13] FIG. 13 is an explanatory diagram showing a relationship between a base
25 station and a terminal in a fourth interference scenario.

[FIG. 14] FIG. 14 is a flowchart showing an example flow of a communication control process that is performed by a cooperation manager in the fourth interference scenario.

[FIG. 15] FIG. 15 is an explanatory diagram showing a relationship between a base
30 station and a terminal in a fifth interference scenario.

[FIG. 16] FIG. 16 is a flowchart showing an example flow of a communication

control process that is performed by a cooperation manager in the fifth interference scenario.

[FIG. 17] FIG. 17 is an explanatory diagram for explaining one variation of the communication control process performed in the fifth interference scenario.

5 [FIG. 18] FIG. 18 is an explanatory diagram showing a relationship between a base station and a terminal in a sixth interference scenario.

[FIG. 19] FIG. 19 is a flowchart showing an example flow of a communication control process that is performed by a cooperation manager in the sixth interference scenario.

10 [FIG. 20] FIG. 20 is an explanatory diagram for explaining one variation of the communication control process performed in the sixth interference scenario.

Description of Embodiments

[0013]

15 Hereinafter, preferred embodiments of the present disclosure will be described in detail with reference to the appended drawings. Note that, in the present description and the drawings, elements that have substantially the same function and structure are denoted with the same reference signs, and repeated explanation is omitted.

20 [0014]

Description will be provided in the following order.

1. Overview of system
2. Example configuration of terminal device
3. Example configuration of cooperation manager
- 25 4. Example interference scenarios
 - 4-1. First interference scenario
 - 4-2. Second interference scenario
 - 4-3. Third interference scenario
 - 4-4. Fourth interference scenario
 - 30 4-5. Fifth interference scenario
 - 4-6. Sixth interference scenario

5. Conclusion

[0015]

<1. Overview of system>

FIG. 1 is an explanatory diagram for explaining an overview of a radio communication system 1 according to an embodiment of the technology according to the present disclosure. Referring to FIG. 1, the radio communication system 1 includes a primary base station 10, a primary terminal 20, a secondary base station 30, and secondary terminals 40a and 40b.

[0016]

The primary base station 10 is a base station to which one or more primary terminals are connected. The primary base station 10 manages a primary cell 11 using a frequency channel for which the primary base station 10 is, for example, legally allowed, or authorized to use. The primary base station 10 is connected to a core network 5. The primary terminal 20, which is located in the primary cell 11, is connected to the primary base station 10. When the primary base station 10 manages the primary cell 11 using the frequency division duplex (FDD) scheme, a frequency channel from the primary terminal 20 to the primary base station 10 is called an uplink (UL) channel, and a frequency channel from the primary base station 10 to the primary terminal 20 is called a downlink (DL) channel. When the primary base station 10 manages the primary cell 11 using the time division duplex (TDD) scheme, the link direction of a frequency channel between the primary terminal 20 and the primary base station 10 is switched at time intervals, such as, for example, a sub-frame or the like.

[0017]

The secondary base station 30 is a base station to which one or more secondary terminals are connected. The secondary base station 30 manages a secondary cell 31 by secondarily using a frequency channel for the primary base station 10. The secondary terminals 40a and 40b, which are located in the secondary cell 31, are connected to the secondary base station 30. As an example, the secondary cell 31 may be a small cell. As used herein, small cells encompass femtocells, nanocells, picocells, microcells, and the like. There is a communication

link between the secondary base station 30 and the primary base station 10. The communication link between the primary base station 10 and the secondary base station 30 may be a wired link or a wireless link. Also, the secondary base station 30 may be connected to the primary base station 10 through the core network 5 and the Internet 7.

[0018]

The primary base station 10 and the secondary base station 30 may each operate as an evolved Node B (eNB) according to the Long Term Evolution (LTE) standard or the LTE-Advanced (LTE-A) standard, for example. Alternatively, the primary base station 10 and the secondary base station 30 may operate according to other cellular communication standards, such as the Wideband-Code Division Multiple Access (W-CDMA) standard, the CDMA2000 standard, and the like.

[0019]

The primary terminal 20, the secondary terminal 40a, and the secondary terminal 40b may each, for example, operate as user equipment (UE) according to the LTE standard or the LTE-A standard. Alternatively, the primary terminal 20, the secondary terminal 40a, and the secondary terminal 40b may operate according to other cellular communication standards, such as the W-CDMA scheme, the CDMA2000 standard, and the like. The primary terminal 20, the secondary terminal 40a, and the secondary terminal 40b may be any radio communication terminal, such as, for example, a smartphone, tablet terminal, personal computer (PC), personal digital assistant (PDA), portable navigation device (PNA), game console, or the like. Note that, herein, when it is not necessary to distinguish the secondary terminals 40a and 40b from each other, these secondary terminals are collectively referred to as the secondary terminals 40 by removing the alphabet letter at the end of the reference character. The same applies to the other components.

[0020]

In the FDD scheme, different frequency channels are used for transmission and reception. Therefore, transmission and reception can be performed at the same timing, and interference does not occur between transmission time slots and reception time slots. Because of such advantages, it is believed that the FDD

scheme is suitable for the case where a large region should be covered by a plurality of macrocells. A number of macrocells may be managed according to the FDD scheme. The primary cell 11 illustrated in FIG. 1 may typically be a macrocell. On the other hand, it is becoming difficult to accommodate recently rapidly increasing data traffic using only macrocells. Therefore, a small cell is provided in a hot spot, where a significant amount of traffic occurs locally. If a small cell base station covers terminals located in a hot spot, not only the traffic load is distributed, but also communication quality in the hot spot is improved, and as a result, the system capacity may also be improved by the effect of link adaptation. The secondary cell 31 illustrated in FIG. 1 may typically be such a small cell. In hot spots, the ratio of uplink traffic and downlink traffic may change dynamically. In the TDD scheme, such dynamically changing traffic can be efficiently processed by controlling a duty ratio (the ratio of the time amount of UL time slots and the time amount of DL time slots). Therefore, small cells as an example may be managed according to the TDD scheme. Note that when there are a plurality of overlapping cells managed according to the TDD scheme, it is necessary for the cells to be highly precisely synchronized together and have the same duty ratio in order to avoid interference between UL time slots and DL time slots, and therefore, the above advantages of the TDD scheme are reduced. Therefore, in the radio communication system 1, for example, while a hot spot in the primary cell 11 managed according to the FDD scheme may be covered by the secondary cell 31 managed according to the TDD scheme, the secondary cell 31 may be provided without overlapping any other secondary cell. In this case, interference between the primary cell 11 and the secondary cell 31 is the only interference that can occur in the radio communication system 1.

[0021]

FIGS. 2A–2D are each an explanatory diagram for explaining example secondary use of a frequency channel. An upper portion of FIG. 2A shows two frequency channels (primary channels) FC11 and FC12 that are used by the primary cell 11. The frequency channel FC11 is, for example, an uplink channel that occupies a band ranging from a frequency F11 to a frequency F12. The frequency

channel FC12 is, for example, a downlink channel that occupies a band ranging from a frequency F21 to a frequency F22. A lower portion of FIG. 2A shows a secondary channel that is secondarily used by the secondary cell 31. In the example of FIG. 2A, the frequency channel FC11 is secondarily used as a secondary channel.

5 [0022]

An upper portion of FIG. 2B shows the same two frequency channels FC11 and FC12 as those of FIG. 2A again. The frequency channels FC11 and FC12 are a primary channel that is used by the primary cell 11. In a lower portion of FIG. 2B, the frequency channels FC11 and FC12 are both secondarily used. For example, 10 the frequency channel FC11 may be used by the secondary cell 31, and the frequency channel FC12 may be used by another secondary cell (and vice versa).

[0023]

An upper portion of FIG. 2C shows four frequency channels CC11, CC12, CC13, and CC14. These frequency channels are each a component carrier (CC) in 15 the LTE-A carrier aggregation technology. The frequency channel CC11 is an uplink CC that occupies a band ranging from a frequency F11 to a frequency F12. The frequency channel CC12 is an uplink CC that occupies a band ranging from the frequency F12 to a frequency F13. The frequency channels CC11 and C12 may be aggregated by the carrier aggregation technology to form an uplink aggregated 20 channel. Also, the frequency channel CC13 is a downlink CC that occupies a band ranging from a frequency F21 to a frequency F22. The frequency channel CC14 is a downlink CC that occupies a band ranging from the frequency F22 to a frequency F23. The frequency channels CC13 and C14 may be aggregated by the carrier aggregation technology to form a downlink aggregated channel. A lower portion of 25 FIG. 2C shows a secondary channel that is secondarily used by the secondary cell 31. In the example of FIG. 2C, the frequency channel CC11 is secondarily used as a secondary channel.

[0024]

An upper portion of FIG. 2D shows the same four frequency channels CC11, 30 CC12, CC13, and CC14 as those of FIG. 2C. The frequency channels CC11 and C12 may be aggregated by the carrier aggregation technology to form an uplink

aggregated channel for the primary cell 11. Also, the frequency channels CC13 and C14 may be aggregated by the carrier aggregation technology to form a downlink aggregated channel for the primary cell 11. A lower portion of FIG. 2D shows two secondary channels that are secondarily used by the secondary cell 31. In the example of FIG. 2D, the frequency channels CC12 and CC13 are a secondary channel. The frequency channels CC12 and C13 may be aggregated by the carrier aggregation technology to form an aggregated channel (e.g., may be managed by the TDD scheme) for the secondary cell 31.

[0025]

Note that resource allocation information (for resource block allocation or PUSCH allocation, etc.) may be distributed on each of a plurality of component carriers included in an aggregated channel or on a component carrier having lowest observed interference. For example, the secondary terminal 40 transmits a quality report containing a communication quality indicator for each component carrier of an aggregated channel, to the secondary base station 30. Thereafter, the secondary base station 30 may select a component carrier that is to be used in transmitting resource allocation information to the secondary terminal 40, using the communication quality indicator for each component carrier. As a result, a reduction in performance due to transmission error of resource allocation information can be reduced. The amount of interference for each component carrier may be estimated using various techniques described below.

[0026]

FIGS. 3A and 3B are explanatory diagrams for explaining a duty ratio in the TDD scheme. In a first example of FIG. 3A, secondary terminals 40a and 40b have uplink traffic while a secondary terminal 40c has downlink traffic. In this case, in the entire system, the amount of uplink traffic is greater than the amount of downlink traffic, and therefore, a duty ratio having a larger number of UL time slots may be selected. As an example, FIG. 3A shows a configuration of 10 sub-frames included in a radio frame having a time length of 10 msec. Here, one radio frame includes six UL sub-frames (labeled with the letter "U"), two DL sub-frames (labeled with the letter "D"), and two special sub-frames (labeled with the letter "S"). Note that

special sub-frames are a sub-frame including a guard interval, that is inserted when the link is switched from downlink to uplink.

[0027]

In contrast to this, in a second example of FIG. 3B, a secondary terminal 40a
5 has uplink traffic while secondary terminals 40b and 40c have downlink traffic. In this case, in the entire system, the amount of downlink traffic is greater than the amount of uplink traffic, and therefore, a duty ratio having a larger number of DL time slots may be selected. As an example, a radio frame shown in FIG. 3B includes two UL sub-frames, six DL sub-frames, and two special sub-frames. By
10 thus changing the duty ratio applied to the secondary cell 31, depending on the state of traffic in a cell, the secondary base station 30 can efficiently process traffic in a hot spot that changes dynamically.

[0028]

It is important to prevent adverse interference in the radio communication
15 system 1 no matter whether the primary cell 11 and the secondary cell 31 are managed according to the FDD scheme or according to the TDD scheme. According to the technique disclosed in Patent Literature 1, a secondary base station or a secondary terminal senses communication states therearound or collects sensed data in advance before determining whether or not a frequency channel protected for
20 a primary cell can be secondarily used. For example, when a radio signal of a primary system has been detected as a result from sensing, it may be determined that secondary use is not to be performed, in order to prevent adverse interference from occurring in the primary system. However, the new introduction of an arrangement for sensing a communication state requires correspondingly high cost. Therefore, in
25 this embodiment, instead of such sensing, an existing quality report arrangement is used to determine the occurrence of adverse interference or the risk thereof. The quality report that may be herein used may be, for example, a measurement report or a channel quality indicator (CQI) report.

[0029]

30 The measurement report is a report containing a determination indicator used in determining handover, which is transmitted from a terminal to a base station.

The measurement report typically contains a received power indicator for a reference signal, such as reference signal received power (RSRP). For example, a measurement report that is transmitted from the primary terminal 20 to the primary base station 10 contains RSRP for a reference signal from the primary base station 10, which is a serving base station, and RSRP for a reference signal from one or more neighboring base stations (e.g., the secondary base station 30). In this embodiment, in addition to this, it is assumed that a terminal incorporates a communication quality indicator into a measurement report. The communication quality indicator may be, for example, a signal-to-interference and noise power ratio (SINR) or a signal-to-interference power ratio (SIR). Most existing terminals have an application programming interface (API) for measuring the SINR or SIR, and therefore, a measurement report can be modified to contain such a communication quality indicator, at less implementation cost. Note that the term “reference signal” as used herein may be replaced with another term, such as a pilot signal, beacon signal, or the like, depending on the communication scheme to which the technology according to the present disclosure is applied.

[0030]

FIG. 4A and FIG. 4B are explanatory diagrams for explaining transmission of a measurement report. FIG. 4A shows a signal sequence in an UMTS terrestrial radio access network (UTRAN). A radio network controller (RNC) is a control node that is located in a core network. An RNC initially transmits a measurement control message to a terminal (UE) through a base station (NodeB) (step S11). The measurement control message indicates reporting criteria with which the UE determines a timing at which a measurement report is to be transmitted. The reporting criteria may be, for example, periodic criteria, or event-triggered criteria (e.g., based on threshold comparison of a measured indicator). If the UE determines that the reporting criteria indicated by the measurement control message are satisfied, the UE transmits a measurement report to the RNC through the NodeB (step S12). Such reporting criteria determination and measurement report transmission may be repeatedly performed.

[0031]

FIG. 4B shows a signal sequence in an E-UTRAN. Initially, a base station (eNodeB) transmits an RRC connection reconfiguration message to a terminal (UE) (step S21). The RRC connection reconfiguration message indicates reporting criteria with which the UE determines a timing at which the measurement report is to be transmitted. The reporting criteria may be, for example, periodic criteria, or event-triggered criteria (e.g., based on threshold comparison of measured indicators). If the periodic criteria are employed, a reporting period may be specified within the range of, for example, 120 ms to 3600 ms. If the event-triggered criteria are employed, a suitable threshold may be specified for each of a plurality of events that are categorized. The RRC connection reconfiguration message may also indicate the type of an indicator that is to be reported. If the UE determines that the reporting criteria indicated by the RRC connection reconfiguration message are satisfied, the UE transmits a measurement report to the eNodeB (step S22). Such reporting criteria determination and measurement report transmission may be repeatedly performed.

[0032]

A measurement report may contain, in addition to the above RSRP, SINR and SIR, an indicator, such as CPICH received signal code power (RSCP), CPICH energy per chip divided by the power density (E_c/N_o), pilot power, energy per chip per interference density measured on the pilot channel (E_c/I_o), reference signal received quality (RSRQ), an signal to noise ratio (SNR), or the like.

[0033]

In this embodiment, introduced is a cooperation manager 100 that is a functional entity for determining the occurrence of adverse interference in the radio communication system 1. The cooperation manager 100 obtains at least one of a quality report containing a communication quality indicator measured by a primary terminal and a quality report containing a communication quality indicator measured by a secondary terminal, and based on the communication quality indicator contained in the obtained quality report, determines the occurrence of adverse interference (or the risk thereof).

[0034]

FIG. 5A is an explanatory diagram for explaining a first example and a second example of the introduction of a cooperation manager. In the first example, a cooperation manager 100a is provided on a control node 52 in the core network 5. The control node 52 may be a node of any type, such as, for example, the Mobility Management Entity (MME), PDN-Gateway (P-GW), Serving-Gateway (S-GW), or the like. The cooperation manager 100a can obtain a measurement report generated by a primary terminal or a secondary terminal, from the primary base station 10 and the secondary base station 30, through a core network-base station interface, such as, for example, the S1 interface or the like.

10 [0035]

In the second example, a cooperation manager 100b is provided on the primary base station 10. The cooperation manager 100b can directly receive a measurement report from a primary terminal, or can receive a measurement report generated by a primary terminal or a secondary terminal from another base station through an inter-base station interface, such as the X2 interface or the like.

15 [0036]

FIG. 5B is an explanatory diagram for explaining a third example of the introduction of a cooperation manager. In the third example, a cooperation manager 100c is provided as a new dedicated control node in the core network 5. The cooperation manager 100c can obtain a measurement report from another control node 52, the primary base station 10, or the secondary base station 30, through a newly implemented interface.

20 [0037]

<2. Example configuration of terminal device>

FIG. 6 is a block diagram showing an example configuration of a terminal device according to this embodiment. A terminal device 90 shown in FIG. 6 is dealt with as the primary terminal 20 when the terminal device 90 is connected to the primary base station 10, and is dealt with as the secondary terminal 40 when the terminal device 90 is connected to the secondary base station 30. The terminal device 90 can be handed over from the primary base station 10 to the secondary base station 30 or from the secondary base station 30 to the primary base station 10.

25

30

Referring to FIG. 6, the terminal device 90 includes a radio communication unit 91, a storage unit 92, an input unit 93, a display unit 94, and a control unit 95.

[0038]

The radio communication unit 91 is a radio communication interface that
5 has one or more antennas, and operates according to the FDD scheme or the TDD
scheme. The radio communication unit 91 detects a cell that is managed in the
vicinity of the terminal device 90, by a cell search procedure, and connects to one of
connectable base stations that is expected to have best communication quality (e.g.,
highest received power of a reference signal). A base station to which a terminal is
10 connected is referred to as a serving base station for the terminal. The radio
communication unit 91 transmits an uplink signal to a serving base station, and
receives a downlink signal from a serving base station. The maximum transmission
power of an uplink signal transmitted from the radio communication unit 91 is set to
be greater as the transmission power of a reference signal set from a serving base
15 station increases.

[0039]

The storage unit 92 stores a program and data for operating the terminal
device 90, using a storage medium, such as a hard disk, semiconductor memory, or
the like.

20 [0040]

The input unit 93, which includes, for example, a touch sensor for detecting
a touch on the screen of the display unit 94, a keypad, a keyboard, a button, or a
switch, or the like, receives an operation or information input by the user.

[0041]

25 The display unit 94, which has a screen, such as a liquid crystal display
(LCD), organic light emitting diode (OLED) display, or the like, displays an output
image of the terminal device 90.

[0042]

The control unit 95 controls all operations of the terminal device 90 using a
30 central processing unit (CPU) or a system on chip (SoC). In this embodiment, the
control unit 95 includes a power measurement unit 96, a quality measurement unit 97,

and a report generation unit 98.

[0043]

The power measurement unit 96 measures the power of a received signal received by the radio communication unit 91 to generate a received power indicator.

5 For example, when the terminal device 90 is connected to the primary base station 10, the power measurement unit 96 may measure the received power of a reference signal of the primary base station 10 received by the radio communication unit 91 to generate RSRP indicating the measured value as a received power indicator. Also, when the terminal device 90 is connected to the secondary base station 30, the power
10 measurement unit 96 may measure received power of a reference signal of the secondary base station 30 received by the radio communication unit 91 to generate RSRP indicating the measured value as a received power indicator. Thereafter, the power measurement unit 96 outputs the generated received power indicator to the quality measurement unit 97 and the report generation unit 98.

15 [0044]

The quality measurement unit 97 measures communication quality of a received signal received by the radio communication unit 91 to generate a communication quality indicator. For example, when the terminal device 90 is connected to the primary base station 10, the quality measurement unit 97 may
20 measure communication quality for a frequency channel between the primary base station 10 and the terminal device 90 to generate an SINR indicating the measured value as a communication quality indicator. Also, when the terminal device 90 is connected to the secondary base station 30, the quality measurement unit 97 may measure communication quality for a frequency channel between the secondary base
25 station 30 and the terminal device 90 to generate an SINR indicating the measured value as a communication quality indicator. During the measurement of communication quality, the quality measurement unit 97 may use a received power indicator input from the power measurement unit 96. Thereafter, the quality measurement unit 97 outputs the generated communication quality indicator to the
30 report generation unit 98.

[0045]

The report generation unit 98 determines whether or not the reporting criteria indicated by the measurement control message described with reference to FIG. 4A or the RRC connection reconfiguration message described with reference to FIG. 4B are satisfied. Also, the report generation unit 98 generates a measurement
 5 report containing the received power indicator input from the power measurement unit 96 and the communication quality indicator input from the quality measurement unit 97. Thereafter, if the reporting criteria are satisfied, the report generation unit 98 transmits the generated report from the radio communication unit 91 to a serving base station on an uplink channel or uplink time slot(s). Note that, instead of a
 10 measurement report, the report generation unit 98 may generate a CQI report containing the above received power indicator and communication quality indicator, and transmits the generated CQI report from the radio communication unit 91 to a serving base station.

[0046]

15 <3. Example configuration of cooperation manager>

FIG. 7 is a block diagram showing an example configuration of the cooperation manager 100 according to this embodiment. Referring to FIG. 7, the cooperation manager 100 includes a communication unit 110, a storage unit 120, and a control unit 130.

20 [0047]

The communication unit 110 is a communication interface for allowing the cooperation manager 100 to communicate with other nodes in the radio communication system 1. When the cooperation manager 100 is provided on a control node (an existing or new one) in the core network 5, the communication unit
 25 110 may, for example, be provided with the S1 interface between the primary base station 10 and the secondary base station 30. When the cooperation manager 100 is provided on a primary base station, the communication unit 110 may, for example, be provided with the X2 interface between itself and other base stations.

[0048]

30 The storage unit 120 stores a program and data for operating the cooperation manager 100, using a storage medium, such as a hard disk, semiconductor memory,

or the like.

[0049]

The control unit 130 controls all operations of the cooperation manager 100 using a CPU or SoC. In this embodiment, the control unit 130 includes a data
5 obtaining unit 132 and an interference control unit 134.

[0050]

The data obtaining unit 132 obtains at least one of a quality report generated by the primary terminal 20 and a quality report generated by the secondary terminal 40. When the cooperation manager 100 is provided on a control node in the core
10 network 5, the data obtaining unit 132 may obtain, through the communication unit 110, a quality report generated by the primary terminal 20 from the primary base station 10, and a quality report generated by the secondary terminal 40 from the secondary base station 30. When the cooperation manager 100 is provided on the primary base station 10, the data obtaining unit 132 may obtain a quality report
15 generated by the primary terminal 20 connected to the primary base station 10 from the primary terminal 20, and quality reports generated by other terminals from other base stations. A quality report obtained by the data obtaining unit 132 may be a measurement report or CQI report as described above. The quality report, which contains a received power indicator and a communication quality indicator, is used to
20 determine whether or not adverse interference is present in the radio communication system 1.

[0051]

The data obtaining unit 132 may also obtain additional information that may be optionally used in determining interference, such as a current transmission power
25 value of each base station, a list of terminals currently connected, and the like. In scenarios described below, interference is determined based on location information of a base station. Therefore, the data obtaining unit 132 may also obtain location information of the primary base station 10 and the secondary base station 30. The location information may be stored in the storage unit 120 in advance, or may be
30 dynamically measured by each base station using some known positioning technique (e.g., GPS positioning, etc.).

[0052]

The interference control unit 134 determines whether or not adverse interference is present in the radio communication system 1, based on a communication quality indicator contained in a quality report obtained by the data
5 obtaining unit 132. Thereafter, if the interference control unit 134 determines that adverse interference is present, the interference control unit 134 instructs the secondary base station 30 involved in the interference, to reduce transmission power. The interference control unit 134 may transmit a control message for instructing to
10 reduce transmission power, from the communication unit 110 to the secondary base station 30 through, for example, the above S1 interface or X2 interface. Here, the control message transmitted may contain a label having only the meaning “reduce transmission power,” or a specific target value of transmission power.

[0053]

The secondary base station 30 includes a radio communication unit that has
15 one or more antennas, and performs radio communication with one or more secondary terminals 40 by secondarily using a frequency channel for the primary base station 10, and a communication unit that transfers a quality report generated by the secondary terminal 40 to the cooperation manager 100, and receives a control message from the cooperation manager 100. The secondary base station 30, when
20 receiving a control message that instructs to reduce transmission power from the cooperation manager 100, reduces transmission power set in the radio communication unit. The secondary base station 30 may set transmission power to a target value indicated by the control message.

[0054]

25 In this embodiment, the determination of interference by the interference control unit 134 based on a communication quality indicator roughly includes two techniques. In the first technique, the interference control unit 134 estimates a distance between a first terminal and a first base station to which the first terminal is connected, from a received power indicator. Thereafter, when the communication
30 quality indicator does not satisfy allowable quality depending on the estimated distance, the interference control unit 134 determines that adverse interference is

present. In the second technique, the interference control unit 134 estimates a path loss between a second terminal and a second base station to which the second terminal is not connected, from an interference component of the communication quality indicator. Also, the interference control unit 134 estimates interference power in the second base station that is caused by the transmission power of the second terminal, based on the estimated path loss. Thereafter, when the estimated interference power does not satisfy allowable interference power, the interference control unit 134 determines that adverse interference is present. Note that, in the first technique, the SNR may be used as a communication quality indicator instead of the SINR or SIR.

[0055]

Incidentally, when the primary terminal 20 is provided in or in the vicinity of the secondary cell 31, a downlink signal transmitted from the secondary base station 30 acts as an interference component in a communication quality indicator of the primary terminal 20. Specifically, a downlink signal from the secondary base station 30 decreases communication quality that is experienced by the primary terminal 20. The decrease is transmitted from the primary terminal 20 to the cooperation manager 100 through a quality report. Therefore, in the above second technique, the interference control unit 134 can estimate a path loss between the primary terminal 20 and the secondary base station 30 to which the primary terminal 20 is not connected, from an interference component of a communication quality indicator of a quality report generated by the primary terminal 20. Similarly, the interference control unit 134 can estimate a path loss between the secondary terminal 40 and the primary base station 10 to which the secondary terminal 40 is not connected, from an interference component of a communication quality indicator of a quality report generated by the secondary terminal 40.

[0056]

In the next section, six interference scenarios in the radio communication system 1 of how the interference control unit 134 can determine the occurrence of adverse interference will be described.

[0057]

<4. Example interference scenarios>

[4-1. First interference scenario]

In a first interference scenario, the interference control unit 134 determines the occurrence of adverse interference according to the above first technique. The
 5 first terminal is the primary terminal 20, and the first base station is the primary base station 10. Specifically, the interference control unit 134 estimates a distance between the primary terminal 20 and the primary base station 10 to which the primary terminal 20 is connected, from a received power indicator. Thereafter, the interference control unit 134 determines that adverse interference is present, if
 10 allowable quality depending on the estimated distance is not satisfied by a communication quality indicator contained in a quality report obtained from the primary terminal 20.

[0058]

FIG. 8 is an explanatory diagram showing a relationship between a base
 15 station and a terminal in the first interference scenario. In FIG. 8, a desired signal is indicated by a thick line, and an interfering signal is indicated by a dashed line. In the first interference scenario, a downlink channel from the primary base station 10 to the primary terminal 20 is secondarily used by the secondary base station 30. Also, a downlink signal from the secondary base station 30 to the secondary terminal
 20 40 acts as an interfering signal on a desired signal received by the primary terminal 20.

[0059]

The received power P_{REF1_1} [W] of a reference signal that is received by the primary terminal 20 from the primary base station 10 is represented by the following
 25 formula, where P_{REF1} is the transmission power of the reference signal, and L_{1_1} is a path loss between the primary base station 10 and the primary terminal 20. Note that, here, it is assumed that the antenna does not have directivity.

[0060]

[Math 1]

$$P_{\text{REF1_1}} = L_{1_1} \cdot P_{\text{REF1}} \quad (1)$$

[0061]

Similarly, the received power $I_{\text{REF2_UE1}}$ [W] of a reference signal that is received by the primary terminal 20 from the secondary base station 30 is represented by the following formula, where P_{REF2} is the transmission power of the reference signal, and L_{2_1} is a path loss between the secondary base station 30 and the primary terminal 20.

[0062]

[Math 2]

$$I_{\text{REF2_UE1}} = L_{2_1} \cdot P_{\text{REF2}} \quad (2)$$

10

[0063]

Overall interference power $I_{\text{DL2_UE1}}$ from the secondary base station 30 that is observed by the primary terminal 20 is represented by the following formula, where $I_{\text{REF2_UE1}}$ is received power (interference power) of a reference signal from the secondary base station 30 that is observed by the primary terminal 20, and $M_{\text{REF2}}/M_{\text{ALL2}}$ is the power ratio of all signal components to the reference signal component. Note that M_{ALL2} and M_{REF2} represent the total number of resource blocks in the secondary cell 31 and the number of resource blocks used for the reference signal, respectively.

20 [0064]

[Math 3]

$$I_{\text{DL2_UE1}} = \frac{M_{\text{ALL2}}}{M_{\text{REF2}}} \cdot I_{\text{REF2_UE1}} \quad (3)$$

[0065]

Moreover, the $\text{SINR}_{\text{REF1}}$ of a reference signal from the primary base station

10 that is observed by the primary terminal 20 is represented by the following formula, where M_{ALL1}/M_{REF1} is the power ratio of all signal components to a reference signal component from the primary base station 10 in the primary cell 11, where $N(d_1)$ is a noise component (thermal noise, and noise in a receiver) depending
 5 on a distance d_1 from the primary base station 10. Note that M_{ALL1} and M_{REF1} represent the total number of resource blocks in the primary cell 11 and the number of resource blocks used for the reference signal, respectively.

[0066]

[Math 4]

$$SINR_{REF1} = \frac{P_{REF1_1}}{N(d_1) + \frac{M_{REF1}}{M_{ALL1}} \cdot I_{DL2_UE1}} \quad (4)$$

10

[0067]

Note that when the code division multiple access (CDMA) scheme is employed, the noise component $N(d_1)$ may be obtained through a correlation with codes assigned to a pilot signal. When the orthogonal frequency division multiple
 15 access (OFDMA) scheme is employed, the noise component $N(d_1)$ may represent noise in a band of resource blocks allocated to a reference signal.

[0068]

Formula (4) is derived by assuming that an interference component of an SINR measured in the primary terminal 20 is caused by the transmission power of the secondary base station 30. A control target value P_{REF2_TGT} of the transmission power of a reference signal of the secondary base station 30 may be calculated by substituting minimum allowable quality $SINR_{ALW1}$ for the $SINR_{REF1}$ in Formula (4) and modifying the formula. Note that P_{margin} is backoff power that is set in order to compensate for an error that may occur due to various causes.

25

[0069]

[Math 5]

$$P_{REF2_TGT} = \frac{M_{REF2}}{M_{REF1} \cdot L_{2_1}} \cdot \left\{ \frac{P_{REF1_1}}{SINR_{ALW1}} - N(d_1) \right\} - P_{margin} \quad (5)$$

[0070]

Here, the distance d_1 may be represented by the following formula, where c [m/s] is the light speed, and f_1 [Hz] is a frequency of a reference signal of the primary base station 10.

[0071]

[Math 6]

$$d_1 = \frac{c}{4\pi f_1} \cdot \sqrt{\frac{P_{REF1}}{P_{REF1_1}}} \quad (6)$$

[0072]

Moreover, a path loss L_{1_2} can be represented by the following formula, based on Formula (2), Formula (3), and Formula (4).

[0073]

[Math 7]

$$L_{1_2} = \frac{M_{ALL1} \cdot M_{REF2}}{M_{REF1} \cdot M_{ALL2} \cdot P_{REF2}} \cdot \left\{ \frac{P_{REF1_1}}{SINR_{REF1}} - N(d_1) \right\} \quad (7)$$

[0074]

Note that a power correction coefficient k_1 may be added to Formula (5) as follows. The power correction coefficient k_1 may, for example, be the ratio of the transmission power of another downlink signal to the transmission power of a reference signal.

[0075]

[Math 8]

$$P_{REF2_TGT} = \frac{M_{REF2}}{k_1 \cdot M_{REF1} \cdot L_{2_1}} \cdot \left\{ \frac{P_{REF1_1}}{SINR_{ALW1}} - N(d_1) \right\} - P_{margin} \quad (8)$$

[0076]

Also, the following power correction coefficient k_2 depending on the duty ratio of the secondary cell 31 may be used instead of or in addition to the power correction coefficient k_1 . When the secondary cell 31 is managed according to the TDD scheme, the power correction coefficient k_2 is used to change the control target value P_{REF2_TGT} of the transmission power of a reference signal from the secondary base station 30, depending on the ratio of UL time slots and DL time slots. Note that, for example, T_{DL} may correspond to the number of DL sub-frames (or DL sub-frames and special sub-frames) in one radio frame, and T_{UL} may correspond to the number of UL sub-frames in one radio frame.

[0077]

[Math 9]

$$k_2 = \frac{T_{DL}}{T_{UL} + T_{DL}} \quad (9)$$

15 [0078]

FIG. 9 is a flowchart showing an example flow of a communication control process that is performed by the cooperation manager 100 in the first interference scenario. The communication control process described here may be repeatedly performed at regular or variable intervals, or may be performed according to a request from any terminal or base station.

[0079]

Referring to FIG. 9, initially, the interference control unit 134 selects a primary terminal that is to be protected from interference (step S111). Next, the interference control unit 134 obtains a measurement report from the selected primary terminal (step S112). Next, the interference control unit 134 estimates a distance between a primary base station and a primary terminal according to Formula (6),

from RSRP and the transmission power of a corresponding reference signal that are contained in the obtained measurement report (step S113). Next, the interference control unit 134 obtains an allowable value $\text{SINR}_{\text{ALW1}}$ of SINR corresponding to the estimated distance (step S114). Note that a table in which various distances are associated with corresponding allowable values of SINR, may be stored in the storage unit 120 in advance. Next, the interference control unit 134 determines whether or not an SINR contained in a measurement report from the selected primary terminal satisfies allowable quality (i.e., whether or not the SINR exceeds the allowable value $\text{SINR}_{\text{ALW1}}$) (step S115). Here, if it is determined that the measured SINR does not satisfy allowable quality, the interference control unit 134 instructs a secondary base station to reduce transmission power (step S116). Such a process is repeated for each of primary terminals that are to be protected from interference (step S117). Thereafter, if the interference determination has been ended for all primary terminals, the communication control process shown in FIG. 9 is ended.

[0080]

Note that, instead of instructing a secondary base station to reduce transmission power after the interference determination has been performed for each primary terminal as in the example of FIG. 9, a secondary base station may be instructed to reduce transmission power only once after the interference determination has been performed for all primary terminals. In the latter case, the interference control unit 134 may select a lowest control target value of transmission power, and notify the secondary base station of the selected control target value.

[0081]

[4-2. Second interference scenario]

In a second interference scenario, the interference control unit 134 determines the occurrence of adverse interference according to the above first technique. The first terminal is the primary terminal 20, and the first base station is the primary base station 10. Note that, in the second interference scenario, an interference factor is not the secondary base station 30, but rather the secondary terminal 40. A communication control process performed in the second interference scenario may be similar to that shown in FIG. 9.

[0082]

FIG. 10 is an explanatory diagram showing a relationship between a base station and a terminal in the second interference scenario. In the second interference scenario, a downlink channel from the primary base station 10 to the primary terminal 20 is secondary used by the secondary base station 30. Also, an uplink signal from the secondary terminal 40 to the secondary base station 30 acts as an interfering signal on a desired signal received by the primary terminal 20.

[0083]

One or more terminals connected to a base station each transmit an uplink signal with transmission power that allows the base station to receive equal received power of an uplink signal. This means that transmission power from a terminal is set to be greater as a path loss between the terminal and a base station increases. A relationship between the received power of a reference signal that is received by the secondary terminal 40 from the secondary base station 30, the transmission power of the reference signal, and a path loss between the secondary base station 30 and the secondary terminal 40, is represented by the following formula.

[0084]

[Math 10]

$$P_{\text{REF2_2}} = L_{2_2} \cdot P_{\text{REF2}} \quad (27)$$

20 [0085]

The transmission power P_{UL2} of an uplink signal transmitted by the secondary terminal 40 is represented by the following formula, where P_{REF2} is the transmission power of a reference signal, and L_{2_2} is a path loss.

[0086]

25 [Math 11]

$$P_{\text{UL2}} = \frac{P_{\text{BAS2}}}{L_{2_2}} = b_2 \cdot \frac{P_{\text{REF2}}}{L_{2_2}} \quad (10)$$

[0087]

In Formula (10), P_{BAS2} represents base power on which transmission power from the secondary terminal 40 depends. The base power P_{BAS2} may have a variable value that is signaled to the secondary terminal 40, or may have a predefined
 5 fixed value. Alternatively, instead of the base power P_{BAS2} , the ratio b_2 of the base power P_{BAS2} to the transmission power P_{REF2} of a reference signal may be signaled or fixedly defined.

[0088]

Overall interference power $I_{\text{UL2_UE1}}$ of uplink signals from N_{UE2} secondary
 10 terminals 40 that is observed in the primary terminal 20, is represented by the following formula based on Formula (10). Note that L_{2i_1} represents a path loss between the i -th secondary terminal 40 and the primary terminal 20, and L_{2_2i} represents a path loss between the secondary base station 30 and the i -th secondary terminal 40.

15 [0089]

[Math 12]

$$I_{\text{UL2_UE1}} = P_{\text{REF2}} \cdot \sum_i^{N_{\text{UE2}}} \frac{L_{2i_1}}{L_{2_2i}} \quad (11)$$

[0090]

According to a meaning similar to that of Formula (4), the $\text{SINR}_{\text{REF1}}$ of a
 20 reference signal from the primary base station 10 that is observed in the primary terminal 20 in the second interference scenario is represented by the following formula, where M_{ALL2} is the total number of resource blocks in the secondary cell 31.

[0091]

[Math 13]

$$SINR_{REF1} = \frac{P_{REF1_1}}{N(d_1) + \frac{M_{REF1}}{M_{ALL2}} \cdot I_{UL2_UE1}} \quad (12)$$

[0092]

Here, the following relationship formula is derived from Formula (11) and Formula (12).

5 [0093]

[Math 14]

$$\sum_i^{N_{UE2}} \frac{L_{2i_1}}{L_{2_2i}} = \frac{M_{ALL2}}{M_{REF1} \cdot P_{REF2}} \cdot \left\{ \frac{P_{REF1_1}}{SINR_{REF1}} - N(d_1) \right\} \quad (13)$$

[0094]

The instruction to the secondary base station 30 to reduce the transmission power of a reference signal in step S116 of FIG. 9 leads to a shrinkage of the secondary cell 31, and therefore, a decrease in the number N_{UE2} of secondary terminals 40 located in the secondary cell 31. Specifically, when adverse interference is caused by an uplink signal transmitted to the secondary base station 30, the interference control unit 134 hands over one or more secondary terminals 40 from the secondary base station 30 to the primary base station 10. As a result, the overall interference power I_{UL2_UE1} of Formula (11) is reduced, and the communication quality $SINR_{REF1}$ of Formula (12) is improved.

[0095]

As an example, if the transmission power P_{REF2} of a reference signal of the secondary base station 30 is reduced to P_{REF2}' , the secondary terminal 40 that does not satisfy the following condition may perform handover to the primary base station 10. Note that P_{TH1} is a threshold for determining handover. The threshold P_{TH1} may vary depending on an operation mode (an active mode, an idle mode, etc.) of a terminal at that time.

[0096]

[Math 15]

$$P_{TH1} < P_{REF2_2i} = L_{2_2i} \cdot P_{REF2} \quad (14)$$

[0097]

5 [4-3. Third interference scenario]

In a third interference scenario, the interference control unit 134 determines the occurrence of adverse interference according to the above first technique. The first terminal is the secondary terminal 40, and the first base station is the secondary base station 30. Specifically, the interference control unit 134 estimates a distance
 10 between the secondary terminal 40 and the secondary base station 30 to which the secondary terminal 40 is connected, from a received power indicator. Thereafter, the interference control unit 134 determines that adverse interference is present, if allowable quality depending on the estimated distance is not satisfied by a communication quality indicator contained in a quality report obtained from the
 15 secondary base station 30.

[0098]

FIG. 11 is an explanatory diagram showing a relationship between a base station and a terminal in the third interference scenario. In the third interference scenario, an uplink channel from the primary terminal 20 to the primary base station
 20 10 is secondarily used by the secondary base station 30. The uplink signal from the primary terminal 20 to the primary base station 10 acts as an interfering signal on a desired signal received from the secondary terminal 40.

[0099]

Overall interference power I_{UL1_UE2} of uplink signals from N_{UE1} primary
 25 terminal 20 that is observed in the secondary terminal 40, is represented by the following formula, where P_{UL1j} is the transmission power of the j-th primary terminal 20, and L_{1i_2} is a path loss between the j-th primary terminal 20 and the secondary terminal 40.

[0100]

[Math 16]

$$I_{UL1_UE2} = \sum_j^{N_{UE1}} L_{1i_2} \cdot P_{UE1j} \quad (15)$$

[0101]

An $SINR_{REF2}$ of a reference signal from the secondary base station 30 that is
 5 observed in the secondary terminal 40 in the third interference scenario, is represented by the following formula.

[0102]

[Math 17]

$$SINR_{REF2} = \frac{P_{REF2_2}}{N(d_2) + \frac{M_{REF2}}{M_{ALL1}} \cdot I_{UL1_UE2}} \quad (16)$$

10 [0103]

Note that $N(d_2)$ represents a noise component (thermal noise, and noise in a receiver) that depends on a distance d_2 from the secondary base station 30. When the CDMA scheme is employed, the noise component $N(d_2)$ is obtained through a correlation with codes assigned to a pilot signal. When the OFDMA scheme is
 15 employed, the noise component $N(d_2)$ may represent noise in the band of resource blocks allocated to a reference signal.

[0104]

The instruction to the secondary base station 30 to reduce the transmission power of a reference signal in the third interference scenario leads to a shrinkage of
 20 the secondary cell 31, and therefore, a handover of the secondary terminal 40 whose measured communication quality does not satisfy allowable quality to the primary base station 10 (or such a secondary terminal 40 is connected to the primary base station 10 after selection of a cell or reselection of a cell). As a result, adverse interference that is present in the secondary terminal 40 may be eliminated.

[0105]

As an example, if the transmission power P_{REF2} of a reference signal of the secondary base station 30 is reduced to P_{REF2}'' , the secondary terminal 40 that does not satisfy the following condition may perform handover to the primary base station 10. Note that P_{TH2} is a threshold for determining handover. The threshold P_{TH2} may vary depending on an operation mode of a terminal at that time.

[0106]

[Math 18]

$$P_{TH2} < L_{2_2i} \cdot (P_{REF2}'' + P_{margin}) \quad (17)$$

10 [0107]

FIG. 12 is a flowchart showing an example flow of a communication control process that is performed by the cooperation manager 100 in the third interference scenario. The communication control process described here may be repeatedly performed at regular or variable intervals, or may be performed according to a request from any terminal or base station.

[0108]

Referring to FIG. 12, initially, the interference control unit 134 selects a secondary terminal (step S131). Next, the interference control unit 134 obtains a measurement report from the selected secondary terminal (step S132). Next, the interference control unit 134 estimates a distance between a secondary base station and a secondary terminal, from RSRP and the transmission power of a corresponding reference signal that are contained in the obtained measurement report (step S133). Next, the interference control unit 134 obtains an allowable value $SINR_{ALW2}$ of SINR corresponding to the estimated distance (step S134). Note that a table in which various distances are associated with corresponding allowable values of SINR, may be stored in the storage unit 120 in advance. Next, the interference control unit 134 determines whether or not an SINR contained in a measurement report from the selected secondary terminal satisfies allowable quality (i.e., whether or not the SINR exceeds the allowable value $SINR_{ALW2}$) (step S135). Here, if it is determined that

the measured SINR does not satisfy allowable quality, the interference control unit 134 instructs a secondary base station to reduce transmission power (step S136). Such a process is repeated for each of secondary terminals (step S137). Thereafter, if the interference determination has been ended for all secondary terminals, the communication control process shown in FIG. 12 is ended.

[0109]

Note that, instead of instructing a secondary base station to reduce transmission power after the interference determination has been performed for each secondary terminal as in the example of FIG. 12, a secondary base station may be instructed to reduce transmission power only once after the interference determination has been performed for all secondary terminals. In the latter case, the interference control unit 134 may select a lowest control target value of transmission power, and notify the secondary base station of the selected control target value.

[0110]

15 [4-4. Fourth interference scenario]

In a fourth interference scenario, the interference control unit 134 determines the occurrence of adverse interference using location information of the primary base station 10 and the secondary base station 30. More specifically, the interference control unit 134 determines that adverse interference is present, if interference power that is calculated using the transmission power of a reference signal of the secondary base station 30, and a path loss estimated from the above location information, does not satisfy allowable interference power of the primary base station 10.

[0111]

FIG. 13 is an explanatory diagram showing a relationship between a base station and a terminal in the fourth interference scenario. In the fourth interference scenario, an uplink channel from the primary terminal 20 to the primary base station 10 is secondarily used by the secondary base station 30. Also, a downlink signal from the secondary base station 30 to the secondary terminal 40 acts as an interfering signal on a desired signal received by the primary base station 10.

[0112]

When the secondary base station 30 is a stationary device, location information of the secondary base station 30 may be stored in the storage unit 120 in advance, and may be obtained by the data obtaining unit 132. When the secondary base station 30 is a mobile device, the secondary base station 30 may measure a location of the secondary base station 30, and the data obtaining unit 132 may obtain location information indicating the measured location. The location information may indicate an absolute topographical location, such as a latitude, longitude, and altitude, or the like, or a relative location (or a relative distance) from any reference location, such as a location of a specific primary base station.

10 [0113]

FIG. 14 is a flowchart showing an example flow of a communication control process that is performed by the cooperation manager 100 in the fourth interference scenario. The communication control process described here may be repeatedly performed at regular or variable intervals, or may be performed according to a request from any terminal or base station.

15

[0114]

Referring to FIG. 14, initially, the interference control unit 134 selects a secondary base station (step S141). Next, the interference control unit 134 obtains the location information of a primary base station and the selected secondary base station (step S142). Next, the interference control unit 134 uses the obtained location information to estimate interference power in the primary base station that is caused by downlink transmission from the selected secondary base station (step S143). Next, the interference control unit 134 obtains the allowable value of interference power in the primary base station (step S144). Note that the allowable value of interference power of each primary base station may be stored in the storage unit 120 in advance. The allowable value of interference power of a primary base station may be a value obtained by multiplying a minimum reception sensitivity by a certain coefficient. Next, the interference control unit 134 determines whether or not the estimated interference power is lower than the allowable value (step S145). Here, if the interference control unit 134 determines that the interference power is not lower than the allowable value, the interference control unit 134 instructs the

20

25

30

secondary base station to reduce transmission power (step S146). Such a process is repeated for each secondary base station located in the primary cell (step S147). Thereafter, if the interference determination has been ended for all secondary base stations, the communication control process shown in FIG. 14 is ended.

5 [0115]

Note that when interference power estimated for a certain secondary base station is much lower than the allowable value, the interference control unit 134 may instruct that secondary base station to increase transmission power.

[0116]

10 [4-5. Fifth interference scenario]

In a fifth interference scenario, the interference control unit 134 determines the occurrence of adverse interference according to the above second technique. The second terminal is the primary terminal 20, and the second base station is the secondary base station 30. Specifically, the interference control unit 134 estimates
 15 a path loss between the primary terminal 20 and the secondary base station 30 to which the primary terminal 20 is not connected, from an interference component of a communication quality indicator contained in a quality report obtained from the primary terminal 20. Also, the interference control unit 134 estimates interference power in the secondary base station 30 that is caused by the transmission power of
 20 the primary terminal 20, based on the estimated path loss. Thereafter, if the estimated interference power does not satisfy allowable interference power, the interference control unit 134 determines that adverse interference is present.

[0117]

FIG. 15 is an explanatory diagram showing a relationship between a base
 25 station and a terminal in the fifth interference scenario. In the fifth interference scenario, an uplink channel from the primary terminal 20 to the primary base station 10 is secondarily used by the secondary base station 30. Also, an uplink signal from the primary terminal 20 to the primary base station 10 acts as an interfering signal on a desired signal received by the secondary base station 30.

30 [0118]

The fifth interference scenario is further divided into two sub-scenarios. In

a first sub-scenario, the secondary base station 30 secondarily uses not only an uplink channel of the primary cell 11, but also a downlink channel of the primary cell 11. In this case, a reference signal transmitted from the secondary base station 30 is received as an interfering signal by the primary terminal 20, and therefore, the use of
 5 the above second technique is advantageous. On the other hand, in a second sub-scenario, a downlink channel of the primary cell 11 is not secondary used. Interference determination in the second sub-scenario will be described below.

[0119]

In the first sub-scenario, the interference power I_{DL2_UE1} of a reference
 10 signal from the secondary base station 30, that is observed by the primary terminal 20, is represented by the following formula.

[0120]

[Math 19]

$$I_{DL2_UE1} = \frac{M_{ALL1}}{M_{ALL2}} \cdot L_{BS2_UE1} \cdot P_{REF2} \quad (18)$$

15 [0121]

Here, L_{BS2_UE1} in Formula (18) is an unknown path loss from the secondary base station 30 to the primary terminal 20. If the interference power I_{REF2_UE1} of Formula (18) is an interference component of an SINR contained in a quality report obtained from the primary terminal 20, the unknown path loss L_{BS2_UE1} can be
 20 derived by substituting the interference component into Formula (18). Note that a path loss L_{UE1_BS2} from the primary terminal 20 to the secondary base station 30 (specifically, in the opposite direction), may be obtained by converting the path loss L_{BS2_UE1} , taking into consideration that a frequency f_{DL1} of a downlink channel and a frequency f_{UL1} of an uplink channel, of the primary cell 11, are different from each
 25 other.

[0122]

[Math 20]

$$L_{UE1_BS2} = \left(\frac{f_{DL1}}{f_{UL1}} \right)^2 \cdot L_{BS2_UE1} \quad (19)$$

[0123]

Interference power I_{UL1_BS2} of an uplink signal from the primary terminal 20, that is observed in the secondary base station 30, is represented by the following formula.

[0124]

[Math 21]

$$I_{UL1_BS2} = L_{UE1_BS2} \cdot P_{UL1} = L_{UE1_BS2} \cdot \frac{P_{BAS1}}{L_{1_1}} \quad (20)$$

[0125]

In Formula (20), P_{BAS1} represents base power on which transmission power from the primary terminal 20 depends. The interference control unit 134 estimates, in this manner, interference power in the secondary base station 30 that is caused by the transmission power of the primary terminal 20. Thereafter, if the greatest value of the interference power estimated for all primary terminals 20 does not satisfy the allowable interference power of the secondary base station 30, the interference control unit 134 determines that adverse interference is present. If an estimated SINR calculated from the estimated interference power does not satisfy the allowable quality of the secondary base station 30, the interference control unit 134 may determine that adverse interference is present.

[0126]

FIG. 16 is a flowchart showing an example flow of a communication control process that is performed by the cooperation manager 100 in the fifth interference scenario. The communication control process described here may be repeatedly performed at regular or variable intervals, or may be performed according to a request from any terminal or base station.

[0127]

Referring to FIG. 16, initially, the interference control unit 134 obtains an allowable value of SINR of a secondary base station (step S150). Next, the interference control unit 134 selects one primary terminal (step S151). Next, the interference control unit 134 obtains a measurement report from the selected primary terminal (step S152). Next, the interference control unit 134 estimates a path loss between the primary terminal and the secondary base station, from an SINR contained in the obtained measurement report (step S153). Next, the interference control unit 134 uses the estimated path loss to estimate interference power in the secondary base station that is caused by uplink transmission from the primary terminal (step S154).

[0128]

Next, the interference control unit 134 selects one secondary terminal (step S155). Next, the interference control unit 134 uses received power from the selected secondary terminal and the interference power estimated in step S154 to calculate an SINR in the secondary base station (step S156). Next, the interference control unit 134 determines whether or not the SINR calculated in step S156 exceeds the allowable value obtained in step S150 (step S157). Here, if the interference control unit 134 determines that the calculated SINR does not exceed the allowable value, the interference control unit 134 calculates the coverage of the secondary cell based on the transmission power of a reference signal of the secondary base station (step S158). Next, the interference control unit 134 determines whether or not the selected secondary terminal is located within the coverage of the secondary cell (step S159). Thereafter, if the interference control unit 134 determines that the selected secondary terminal is located within the coverage of the secondary cell, the interference control unit 134 instructs the secondary base station to reduce transmission power (step S160).

[0129]

Such a process is repeated for each pair of a secondary terminal and a primary terminal (steps S161 and S162). Thereafter, when the interference determination has been ended for all pairs, the communication control process shown

in FIG. 16 is ended.

[0130]

Note that, instead of instructing a secondary base station to reduce transmission power after the interference determination has been performed for each pair of a secondary terminal and a primary terminal as in the example of FIG. 16, a secondary base station may be instructed to reduce transmission power only once after the interference determination has been performed for all pairs.

[0131]

In the second sub-scenario, the primary base station 10 and the primary terminal 20 operate according to the FDD scheme, and the secondary base station 30 and the secondary terminal 40 secondarily use only uplink channels of the primary base station 10. In this case, when the primary terminal 20 performs measurement, the secondary base station 30 does not transmit a reference signal. Therefore, it is difficult to estimate a path loss between the primary terminal 20 and the secondary base station 30, from an interference component of a communication quality indicator measured by the primary terminal 20. Therefore, the interference control unit 134 assumes a worst case where the primary terminal 20 is located at a cell edge of the secondary cell 31. Thereafter, on this assumption, the interference control unit 134 estimates interference power in the secondary base station 30 that is caused by the transmission power of the primary terminal 20, and determines whether or not the estimated interference power satisfies allowable interference power.

[0132]

FIG. 17 is an explanatory diagram for explaining one variation of the communication control process performed in the fifth interference scenario. In the second sub-scenario of the fifth interference scenario, it is assumed that the primary terminal 20 is not present at an actual location PT1, but rather at a location PT2 on a cell edge of the secondary cell 31.

[0133]

Here, there is the following relationship between a path loss L_{UE1_BS1} from the primary terminal 20 to the primary base station 10 and a path loss L_{BS1_UE1} from the primary base station 10 to the primary terminal 20.

[0134]

[Math 22]

$$L_{UE1_BS1} = \left(\frac{f_{DL1}}{f_{UL1}} \right)^2 \cdot L_{BS1_UE1} \quad (21)$$

[0135]

5 Also, there is the following relationship between a path loss $L_{UE1'_BS2}$ from a virtual primary terminal 20' to the secondary base station 30 and a path loss $L_{BS2_UE1'}$ from the secondary base station 30 to the virtual the primary terminal 20'.

[0136]

[Math 23]

$$L_{UE1'_BS2} = \left(\frac{f_{DL1}}{f_{UL1}} \right)^2 \cdot L_{BS2_UE1'} \quad (22)$$

10

[0137]

From Formula (21) and Formula (22), interference power I_{UL1_BS2} in the secondary base station 30 that is caused by uplink transmission from the primary terminal 20' can be represented by the following formula.

15 [0138]

[Math 24]

$$I_{UL1_BS2} = L_{UE1'_BS2} \cdot P_{UL1} = L_{UE1'_BS2} \cdot \frac{P_{BAS1}}{L_{1_1'}} \quad (23)$$

[0139]

20 Received power P_{UL2_BS2} of a desired signal received by the secondary base station 30 is represented by the following formula.

[0140]

[Math 25]

$$P_{UL2_BS2} = L_{UE2_BS2} \cdot P_{UL2} \quad (24)$$

$$L_{UE2_BS2} = \left(\frac{f_{DL1}}{f_{UL1}} \right)^2 \cdot L_{2_2} \quad (25)$$

[0141]

5 The interference control unit 134 can calculate an SINR or SIR in the secondary base station 30 using the interference power I_{UL1_BS2} of Formula (23) and the received power P_{UL2_BS2} of Formula (24). Thereafter, the interference control unit 134 may compare the calculated SINR or SIR with an allowable value to determine whether or not adverse interference is present, and if determining that
10 adverse interference is present, may instruct the secondary base station 30 to reduce transmission power.

[0142]

[4-6. Sixth interference scenario]

 In a sixth interference scenario, the interference control unit 134 determines
15 the occurrence of adverse interference according to the above second technique. The second terminal is the secondary terminal 40, and the second base station is the primary base station 10. Specifically, the interference control unit 134 estimates a path loss between the secondary terminal 40 and the primary base station 10 to which the secondary terminal 40 is not connected, from an interference component of a
20 communication quality indicator contained in a quality report obtained from the secondary terminal 40. Also, the interference control unit 134 estimates interference power in the primary base station 10 that is caused by the transmission power of the secondary terminal 40, based on the estimated path loss. Thereafter, if the estimated interference power does not satisfy allowable interference power, the
25 interference control unit 134 determines that adverse interference is present.

[0143]

FIG. 18 is an explanatory diagram showing a relationship between a base station and a terminal in the sixth interference scenario. In the sixth interference scenario, an uplink channel from the primary terminal 20 to the primary base station 10 is secondarily used by the secondary base station 30. Also, an uplink signal from the secondary terminal 40 to the secondary base station 30 acts as an interfering signal on a desired signal received by the primary base station 10.

[0144]

The sixth interference scenario is further divided into two sub-scenarios. In a first sub-scenario, the secondary base station 30 secondarily uses not only an uplink channel of the primary cell 11, but also a downlink channel of the primary cell 11. In this case, a reference signal transmitted from the primary base station 10 is received as an interfering signal by the secondary terminal 40, and therefore, the use of the above second technique is advantageous. On the other hand, in a second sub-scenario, a downlink channel of the primary cell 11 is not secondarily used. Interference determination in the second sub-scenario will be described below.

[0145]

In the first sub-scenario, the transmission power P_{DL1} of a downlink transmitted from the primary base station 10 is represented by the following formula.

[0146]

[Math 26]

$$P_{DL1} = \frac{M_{ALL1}}{M_{REF1}} \cdot P_{REF1} \quad (26)$$

[0147]

Interference power I_{DL1_UE2} of a downlink signal from the primary base station 10, that is observed in the secondary terminal 40, is represented by the following formula. Note that L_{BS1_UE2} represents a path loss from the primary base station 10 to the secondary terminal 40.

[0148]

[Math 27]

$$I_{DL1_UE2} = L_{BS1_UE2} \cdot P_{DL1} \quad (27)$$

[0149]

An $SINR_{REF2}$ of a reference signal from the secondary base station 30 that is observed in the secondary terminal 40 is represented by the following formula.

5 [0150]

[Math 28]

$$SINR_{REF2} = \frac{P_{REF2_2}}{N(d_2) + \frac{M_{REF2}}{M_{ALL2}} \cdot I_{DL1_UE2}} \quad (28)$$

[0151]

Here, L_{BS1_UE2} in Formula (27) is an unknown path loss from the primary
 10 base station 10 to the secondary terminal 40. If the interference power I_{DL1_UE2} of
 Formula (27) is an interference component of an SINR contained in a quality report
 obtained from the secondary terminal 40, the unknown path loss L_{BS1_UE2} can be
 derived by substituting the interference component into Formula (27). Note that a
 path loss L_{UE2_BS1} from the secondary terminal 40 to the primary base station 10
 15 (specifically, in the opposite direction), may be obtained by converting the path loss
 L_{BS1_UE2} , taking into consideration that a frequency f_{DL1} of a downlink channel and a
 frequency f_{UL1} of an uplink channel, of the primary cell 11, are different from each
 other.

[0152]

20 [Math 29]

$$L_{UE2_BS1} = \left(\frac{f_{UL1}}{f_{DL1}} \right)^2 \cdot L_{BS1_UE2} \quad (29)$$

[0153]

Interference power I_{UL2_BS1} of an uplink signal from the secondary terminal 40, that is observed in the primary base station 10, is represented by the following
5 formula.

[0154]

[Math 30]

$$I_{UL2_BS1} = L_{UE2_BS1} \cdot P_{UL2} = L_{UE2_BS1} \cdot \frac{P_{BAS2}}{L_{2_2}} \quad (30)$$

[0155]

10 In Formula (30), P_{BAS2} represents base power on which transmission power from the secondary terminal 40 depends. The interference control unit 134 estimates, in this manner, interference power in the primary base station 10 that is caused by the transmission power of the secondary terminal 40. Thereafter, if the greatest value of the interference power estimated for all secondary terminals 40 does
15 not satisfy the allowable interference power of the primary base station 10, the interference control unit 134 determines that adverse interference is present. If an estimated SINR calculated from the estimated interference power does not satisfy the allowable quality of the primary base station 10, the interference control unit 134 may determine that adverse interference is present.

20 [0156]

FIG. 19 is a flowchart showing an example flow of a communication control process that is performed by the cooperation manager 100 in the sixth interference scenario. The communication control process described here may be repeatedly performed at regular or variable intervals, or may be performed according to a

request from any terminal or base station.

[0157]

Referring to FIG. 19, initially, the interference control unit 134 obtains an allowable value of SINR of a primary base station (step S170). Next, the interference control unit 134 selects one secondary terminal (step S171). Next, the interference control unit 134 obtains a measurement report from the selected secondary terminal (step S172). Next, the interference control unit 134 estimates a path loss between the secondary terminal and the primary base station, from an SINR contained in the obtained measurement report (step S173). Next, the interference control unit 134 uses the estimated path loss to estimate interference power in the primary base station that is caused by uplink transmission from the secondary terminal (step S174).

[0158]

Next, the interference control unit 134 selects one primary terminal (step S175). Next, the interference control unit 134 uses received power from the selected primary terminal and the interference power estimated in step S174 to calculate an SINR in the primary base station (step S176). Next, the interference control unit 134 determines whether or not the SINR calculated in step S176 exceeds the allowable value obtained in step S170 (step S177). Here, if the interference control unit 134 determines that the calculated SINR does not exceed the allowable value, the interference control unit 134 calculates the coverage of the secondary cell based on the transmission power of a reference signal of the secondary base station (step S178). Next, the interference control unit 134 determines whether or not the selected secondary terminal is located within the coverage of the secondary cell (step S179). Thereafter, if the interference control unit 134 determines that the selected secondary terminal is located within the coverage of the secondary cell, the interference control unit 134 instructs the secondary base station to reduce transmission power (step S180).

[0159]

Such a process is repeated for each pair of a primary terminal and a secondary terminal (steps S181 and S182). Thereafter, when the interference

determination has been ended for all pairs, the communication control process shown in FIG. 19 is ended.

[0160]

Note that, instead of instructing a secondary base station to reduce transmission power after the interference determination has been performed for each pair of a primary terminal and a secondary terminal as in the example of FIG. 19, a secondary base station may be instructed to reduce transmission power only once after the interference determination has been performed for all pairs.

[0161]

In the second sub-scenario, the primary base station 10 and the primary terminal 20 operate according to the FDD scheme, and the secondary base station 30 and the secondary terminal 40 secondarily use only uplink channels of the primary base station 10. In this case, when the secondary terminal 40 performs measurement, the primary base station 10 does not transmit a reference signal. Therefore, it is difficult to estimate a path loss between the secondary terminal 40 and the primary base station 10, from on an interference component of a communication quality indicator measured by the secondary terminal 40. Therefore, the interference control unit 134 assumes a worst case where the secondary terminal 40 is located at a cell edge closest to the primary base station 10 in the secondary cell 31. Thereafter, on this assumption, the interference control unit 134 estimates interference power in the primary base station 10 that is caused by the transmission power of the secondary terminal 40, and determines whether or not the estimated interference power satisfies allowable interference power.

[0162]

FIG. 20 is an explanatory diagram for explaining one variation of the communication control process performed in the sixth interference scenario. In the second sub-scenario of the sixth interference scenario, it is assumed that the secondary terminal 40 is not present at an actual location PT3, but rather at a location PT4 on a cell edge of the secondary cell 31.

[0163]

Interference power I_{UL2_BS1} in the primary base station 10 that is caused by

uplink transmission from the secondary terminal 40', is represented by the following formula.

[0164]

[Math 31]

$$I_{UL2_BS1} = L_{UE2'_BS1} \cdot P_{UL2} = L_{UE2'_BS1} \cdot \frac{P_{BAS2}}{L_{2_2'}} \quad (31)$$

5

[0165]

A distance between the primary base station 10 and the secondary base station 30 is calculated from location information. Also, a distance between the secondary base station 30 and the secondary terminal 40' is calculated as a radius of the secondary cell 31 from the transmission power of a reference signal from the secondary base station 30. Therefore, by substituting the values of path losses corresponding to these distances into Formula (31), the interference power I_{UL2_BS1} can be estimated. The interference control unit 134 can use the interference power I_{UL2_BS1} thus estimated to calculate an SINR or SIR in the primary base station 10. Thereafter, the interference control unit 134 may compare the calculated SINR or SIR with an allowable value to determine whether or not adverse interference is present, and if determining that adverse interference is present, may instruct the secondary base station 30 to reduce transmission power.

15

[0166]

20 <5. Conclusion>

In the foregoing, embodiments of the technology according to the present disclosure have been described with reference to FIGS. 1–20. According to the above embodiments, in an environment where a frequency channel for a primary base station is secondarily used by a secondary base station, it is determined whether or not adverse interference is present, based on a communication quality indicator contained in a quality report generated by a primary terminal or a secondary terminal. Thereafter, if it is determined that adverse interference is present, the secondary base station is instructed to reduce transmission power. As a result, adverse interference

25

can be prevented and the secondary use of a frequency channel can be safely performed, without the need of an arrangement for sensing a communication state. Here, a quality report may be a measurement report or a CQI report. Therefore, the determination of adverse interference can be assisted by slightly modifying a reporting function possessed by an existing terminal.

[0167]

According to a certain technique, a quality report contains a received power indicator for a reference signal. Also, a distance between a first terminal and a first base station to which the first terminal is connected is estimated from the received power indicator, and the occurrence of interference is determined based on comparison between allowable quality depending on the estimated distance and the above communication quality indicator. Therefore, adverse interference experienced by a primary terminal or a secondary terminal, or the risk thereof, can be accurately determined using the above quality report, irrespective of the location of the terminal in a cell.

[0168]

According to another technique, a path loss between a second terminal and a second base station to which the second terminal is not connected is estimated from an interference component of a communication quality indicator. Thereafter, based on the estimated path loss, interference power in the second base station that is caused by the transmission power of the second terminal is estimated, and based on the estimated interference power, the occurrence of interference is determined. Therefore, adverse interference experienced by a primary base station or a secondary base station, or the risk thereof, can be determined using the above quality report.

[0169]

Further, a series of control processes by the respective devices described in the present description may be implemented using any one of software, hardware, and a combination of hardware and software. For example, a program configuring software is stored in a storage medium (a non-transitory medium) installed inside or outside each device. Further, for example, each program is read onto a Random Access Memory (RAM) at the time of execution and executed by a processor such as

a Central Processing Unit (CPU). The technology according to the present disclosure may be implemented as a one-chip module in which a processor that executes such a program, a memory that stores the program, and related circuits are integrated together.

5 [0170]

Further, the processes described using the flowcharts in the present description may not necessarily be executed in the order indicated by the flowchart. Some process steps may be executed in parallel. Further, additional process steps may be employed, and some process steps may be omitted.

10 [0171]

The preferred embodiment(s) of the present disclosure has/have been described above with reference to the accompanying drawings, whilst the present disclosure is not limited to the above examples, of course. A person skilled in the art may find various alterations and modifications within the scope of the appended claims, and it should be understood that they will naturally come under the technical scope of the present disclosure.

[0172]

Additionally, the present technology may also be configured as below.

(1)

20 A communication control device including:

an obtaining unit configured to, in a radio communication system including a primary base station to which a primary terminal is connected, and a secondary base station to which a secondary terminal is connected by secondarily using a frequency channel for the primary base station, obtain at least one of a quality report containing a communication quality indicator measured by the primary terminal and a quality report containing a communication quality indicator measured by the secondary terminal; and

an interference control unit configured to instruct the secondary base station to reduce transmission power, when it is determined that adverse interference is present in the radio communication system, based on the communication quality indicator contained in the quality report obtained by the obtaining unit.

30

(2)

The communication control device according to (1),
wherein the quality report is a measurement report or a channel quality indicator (CQI) report.

5 (3)

The communication control device according to (1) or (2),
wherein the quality report contains a received power indicator for a reference signal,

wherein the interference control unit estimates a distance between a first
10 terminal and a first base station to which the first terminal is connected, from the received power indicator, and determines that the adverse interference is present, if the communication quality indicator does not satisfy allowable quality depending on the estimated distance.

(4)

15 The communication control device according to (1) or (2),
wherein the interference control unit estimates a path loss between a second terminal and a second base station to which the second terminal is not connected, from an interference component of the communication quality indicator, estimates interference power in the second base station caused by transmission power of the
20 second terminal, based on the estimated path loss, and determines that the adverse interference is present, if the estimated interference power does not satisfy allowable interference power.

(5)

25 The communication control device according to (3),
wherein the first terminal is the primary terminal, and
wherein the first base station is the primary base station.

(6)

The communication control device according to (5),
wherein the interference control unit assumes that an interference
30 component of the communication quality indicator contained in the quality report of the primary terminal is caused by the transmission power of the secondary base

station, and calculates a control target value of the transmission power of the secondary base station.

(7)

The communication control device according to (6),

5 wherein the secondary terminal and the secondary base station operate according to a time division duplex scheme, and

wherein the interference control unit changes the control target value, depending on a ratio of uplink slots and downlink slots of the secondary base station.

(8)

10 The communication control device according to (6) or (7),

wherein, when the adverse interference is caused by an uplink signal transmitted to the secondary base station, the interference control unit hands over one or more secondary terminals from the secondary base station to the primary base station to reduce the adverse interference.

15 (9)

The communication control device according to (3),

wherein the first terminal is the secondary terminal, and

wherein the first base station is the secondary base station.

(10)

20 The communication control device according to any one of (1) to (9),

wherein the obtaining unit further obtains location information of the primary base station and the secondary base station, and

wherein, when interference power calculated using transmission power of a reference signal of the secondary base station and a path loss estimated from the location information does not satisfy allowable interference power of the primary base station, the interference control unit determines that the adverse interference is present.

25

(11)

The communication control device according to (4),

30 wherein the second terminal is the primary terminal, and

wherein the second base station is the secondary base station.

(12)

The communication control device according to any one of (1) to (10),
wherein the primary terminal and the primary base station operate according
to a frequency division duplex scheme,

5 wherein the secondary terminal and the secondary base station secondarily
use an uplink channel of the primary base station, and

 wherein, when interference power in the secondary base station caused by
transmission power of the primary terminal does not satisfy allowable interference
power on an assumption that the primary terminal is located at a cell edge of the
10 secondary base station, the interference control unit determines that the adverse
interference is present.

(13)

 The communication control device according to (4),
 wherein the second terminal is the secondary terminal, and
15 wherein the second base station is the primary base station.

(14)

 The communication control device according to any one of (1) to (12),
 wherein the primary terminal and the primary base station operate according
to a frequency division duplex scheme,

20 wherein the secondary terminal and the secondary base station secondarily
use an uplink channel of the primary base station, and

 wherein, when interference power in the primary base station caused by
transmission power of the secondary terminal does not satisfy allowable interference
power on an assumption that the secondary terminal is located at a cell edge of the
25 secondary base station, the interference control unit determines that the adverse
interference is present.

(15)

 The communication control device according to any one of (1) to (14),
 wherein maximum transmission power of the secondary terminal is set to be
30 greater as transmission power of a reference signal of the secondary base station
increases.

(16)

The communication control device according to any one of (1) to (15),
wherein the primary terminal and the primary base station operate according
to a frequency division duplex scheme, and

5 wherein the secondary terminal and the secondary base station operate
according to a time division duplex scheme, using an aggregated channel formed by
aggregating one or more component carriers on an uplink channel of the primary
base station and one or more component carriers on a downlink channel of the
primary base station.

10 (17)

The communication control device according to (16),
wherein the quality report of the secondary terminal contains the
communication quality indicator of each component carrier of the aggregated
channel, and

15 wherein the secondary base station uses the communication quality indicator
of each component carrier to select a component carrier for transmitting resource
allocation information to the secondary terminal.

(18)

20 A communication control method executed by a communication control
device in a radio communication system including a primary base station to which a
primary terminal is connected, and a secondary base station to which a secondary
terminal is connected by secondarily using a frequency channel for the primary base
station, the communication control method including:

25 obtaining at least one of a quality report containing a communication quality
indicator measured by the primary terminal and a quality report containing a
communication quality indicator measured by the secondary terminal;

 determining whether or not adverse interference is present in the radio
communication system, based on the communication quality indicator contained in
the obtained quality report; and

30 instructing the secondary base station to reduce transmission power, if
determining that the adverse interference is present.

(19)

A radio communication system including:

a primary base station to which a primary terminal is connected;

a secondary base station to which a secondary terminal is connected by
 5 secondarily using a frequency channel for the primary base station; and

a cooperation manager configured to instruct the secondary base station to
 reduce transmission power, if it is determined that adverse interference is present in
 the system, based on a communication quality indicator contained in at least one of a
 quality report containing the communication quality indicator measured by the
 10 primary terminal and a quality report containing the communication quality indicator
 measured by the secondary terminal.

(20)

A terminal device operable in a radio communication system including a
 primary base station to which a primary terminal is connected, and a secondary base
 15 station to which a secondary terminal is connected by secondarily using a frequency
 channel for the primary base station, the terminal device including:

a control unit configured to generate a quality report containing a
 communication quality indicator used by a control node configured to determine
 whether or not adverse interference is present in the radio communication system, the
 20 communication quality indicator being used for the determination; and

a radio communication unit configured to transmit the quality report
 generated by the control unit to a base station to which the terminal device is
 connected.

25

Reference Signs List

[0173]

- | | |
|--------|----------------------------|
| 1 | radio communication system |
| 10 | primary base station |
| 20, 90 | primary terminal |
| 30 | secondary base station |
| 40, 90 | secondary terminal |

	91	radio communication unit
	95	control unit
	100	cooperation manager (communication control device)
	132	data obtaining unit
5	134	interference control unit

CLAIMS

Claim 1

A communication control device comprising:

an obtaining unit configured to, in a radio communication system including
5 a primary base station to which a primary terminal is connected, and a secondary
base station to which a secondary terminal is connected by secondarily using a
frequency channel for the primary base station, obtain at least one of a quality report
containing a communication quality indicator measured by the primary terminal and
a quality report containing a communication quality indicator measured by the
10 secondary terminal; and

an interference control unit configured to instruct the secondary base station
to reduce transmission power, when it is determined that adverse interference is
present in the radio communication system, based on the communication quality
indicator contained in the quality report obtained by the obtaining unit.

15

Claim 2

The communication control device according to claim 1,

wherein the quality report is a measurement report or a channel quality
indicator (CQI) report.

20

Claim 3

The communication control device according to claim 1,

wherein the quality report contains a received power indicator for a
reference signal,

25 wherein the interference control unit estimates a distance between a first
terminal and a first base station to which the first terminal is connected, from the
received power indicator, and determines that the adverse interference is present, if
the communication quality indicator does not satisfy allowable quality depending on
the estimated distance.

30

Claim 4

The communication control device according to claim 1,
wherein the interference control unit estimates a path loss between a second terminal and a second base station to which the second terminal is not connected, from an interference component of the communication quality indicator, estimates
5 interference power in the second base station caused by transmission power of the second terminal, based on the estimated path loss, and determines that the adverse interference is present, if the estimated interference power does not satisfy allowable interference power.

10 Claim 5

The communication control device according to claim 3,
wherein the first terminal is the primary terminal, and
wherein the first base station is the primary base station.

15 Claim 6

The communication control device according to claim 5,
wherein the interference control unit assumes that an interference component of the communication quality indicator contained in the quality report of the primary terminal is caused by the transmission power of the secondary base
20 station, and calculates a control target value of the transmission power of the secondary base station.

Claim 7

The communication control device according to claim 6,
25 wherein the secondary terminal and the secondary base station operate according to a time division duplex scheme, and
wherein the interference control unit changes the control target value, depending on a ratio of uplink slots and downlink slots of the secondary base station.

30 Claim 8

The communication control device according to claim 6,

wherein, when the adverse interference is caused by an uplink signal transmitted to the secondary base station, the interference control unit hands over one or more secondary terminals from the secondary base station to the primary base station to reduce the adverse interference.

5

Claim 9

The communication control device according to claim 3,
wherein the first terminal is the secondary terminal, and
wherein the first base station is the secondary base station.

10

Claim 10

The communication control device according to claim 1,
wherein the obtaining unit further obtains location information of the
primary base station and the secondary base station, and

15

wherein, when interference power calculated using transmission power of a
reference signal of the secondary base station and a path loss estimated from the
location information does not satisfy allowable interference power of the primary
base station, the interference control unit determines that the adverse interference is
present.

20

Claim 11

The communication control device according to claim 4,
wherein the second terminal is the primary terminal, and
wherein the second base station is the secondary base station.

25

Claim 12

The communication control device according to claim 1,
wherein the primary terminal and the primary base station operate according
to a frequency division duplex scheme,

30

wherein the secondary terminal and the secondary base station secondarily
use an uplink channel of the primary base station, and

wherein, when interference power in the secondary base station caused by transmission power of the primary terminal does not satisfy allowable interference power on an assumption that the primary terminal is located at a cell edge of the secondary base station, the interference control unit determines that the adverse
5 interference is present.

Claim 13

The communication control device according to claim 4,
wherein the second terminal is the secondary terminal, and
10 wherein the second base station is the primary base station.

Claim 14

The communication control device according to claim 1,
wherein the primary terminal and the primary base station operate according
15 to a frequency division duplex scheme,
wherein the secondary terminal and the secondary base station secondarily use an uplink channel of the primary base station, and
wherein, when interference power in the primary base station caused by transmission power of the secondary terminal does not satisfy allowable interference
20 power on an assumption that the secondary terminal is located at a cell edge of the secondary base station, the interference control unit determines that the adverse interference is present.

Claim 15

25 The communication control device according to claim 1,
wherein maximum transmission power of the secondary terminal is set to be greater as transmission power of a reference signal of the secondary base station increases.

30 Claim 16

The communication control device according to claim 1,

wherein the primary terminal and the primary base station operate according to a frequency division duplex scheme, and

wherein the secondary terminal and the secondary base station operate according to a time division duplex scheme, using an aggregated channel formed by aggregating one or more component carriers on an uplink channel of the primary
5 base station and one or more component carriers on a downlink channel of the primary base station.

Claim 17

10 The communication control device according to claim 16,
wherein the quality report of the secondary terminal contains the communication quality indicator of each component carrier of the aggregated channel, and
wherein the secondary base station uses the communication quality indicator
15 of each component carrier to select a component carrier for transmitting resource allocation information to the secondary terminal.

Claim 18

A communication control method executed by a communication control
20 device in a radio communication system including a primary base station to which a primary terminal is connected, and a secondary base station to which a secondary terminal is connected by secondarily using a frequency channel for the primary base station, the communication control method comprising:

obtaining at least one of a quality report containing a communication quality
25 indicator measured by the primary terminal and a quality report containing a communication quality indicator measured by the secondary terminal;

determining whether or not adverse interference is present in the radio communication system, based on the communication quality indicator contained in the obtained quality report; and

30 instructing the secondary base station to reduce transmission power, if determining that the adverse interference is present.

Claim 19

A radio communication system comprising:
a primary base station to which a primary terminal is connected;
5 a secondary base station to which a secondary terminal is connected by
secondarily using a frequency channel for the primary base station; and
a cooperation manager configured to instruct the secondary base station to
reduce transmission power, if it is determined that adverse interference is present in
the system, based on a communication quality indicator contained in at least one of a
10 quality report containing the communication quality indicator measured by the
primary terminal and a quality report containing the communication quality indicator
measured by the secondary terminal.

Claim 20

15 A terminal device operable in a radio communication system including a
primary base station to which a primary terminal is connected, and a secondary base
station to which a secondary terminal is connected by secondarily using a frequency
channel for the primary base station, the terminal device comprising:
a control unit configured to generate a quality report containing a
20 communication quality indicator used by a control node configured to determine
whether or not adverse interference is present in the radio communication system, the
communication quality indicator being used for the determination; and
a radio communication unit configured to transmit the quality report
generated by the control unit to a base station to which the terminal device is
25 connected.