

TOWBARLESS AIRPLANE TUG

FIELD OF THE INVENTION

The present invention relates generally to systems for airplane ground movement, and more particularly to control methods of ground vehicles of such systems.

BACKGROUND OF THE INVENTION

5 Airplane tugs are often provided for towing airplanes between ground locations at an airport, thus obviating the need for the airplane to move itself under its own power, saving jet fuel. The tugs may be provided with a towbar, which connects a landing gear with the tug, or towbarless, in which a towbar is not provided, in which, typically, the landing gear sits directly on the chassis of the tug.

10 SUMMARY OF THE INVENTION

According to one aspect of the present invention, there is provided a towbarless airplane tug configured for receiving a landing gear of an airplane and towing it thereby, the tug comprising:

- a chassis configured for receiving thereon at least a portion of the landing gear;
- 15 • a propulsion arrangement configured to move the tug in a direction along a trajectory and comprising a variable angle swash plate hydraulic pump coupled to a variable angle swash plate hydraulic motor and to a controllable bypass path valve, configured such that a hydraulic fluid circulates between the pump and the motor so as to activate the propulsion arrangement to increase at least one of the speed and the traction force of the tug when the bypass path is in a closed state, and at least most of the hydraulic fluid circulates across the motor via the bypass path valve so as to reduce at least one of a rotational speed and traction force of the tug when the bypass path is in an opened state;
- 20 • at least one force sensor configured to measure, directly or indirectly, a force exerted by the chassis on the landing gear in at least the direction due to a speed differential between the tug and the airplane; and
- 25 • a controller in communication with the force sensor and being configured to alter one or more parameters of movement of the tug such that the force exerted by the chassis on the

landing gear is maintained (for example, during movement of the tug) below a predetermined value by regulating at least the power available to the propulsion arrangement, the pump and motor swash-plates, and the state of the bypass path valve.

It will be appreciated that the term "towbarless" as used herein the specification and claims relates to a class of airplane tugs without a towbar (i.e., a bar or other connecting device which couples between the chassis of a tug and the landing gear of the airplane). In a towbarless airplane tug, the landing gear typically sits directly on the chassis, or its weight is directed to an area within the chassis.

It will further be appreciated that the term "controller" as used herein the specification and claims is to be understood in its broadest terms, including, but not being limited to, two or more controllers, for example each one performing a specific function.

The towbarless airplane tug may further comprise a hydraulic motor cross valve to allow a free flow of hydraulic fluid across the motor, for free tug movement, when the bypass path is closed.

The bypass path may be associated with a brake period following opening of the bypass path wherein hydraulic fluid is diverted from the swash plate pump, the controller being further configured to control the state of the bypass path, the valve being characterized by a response period that is much smaller than the brake period.

The propulsion driving module may further comprise a valve which controls the state of the bypass path, the valve being characterized by a response period that is much smaller than a resonance period of the swash plates of the hydraulic pump and motor.

The controller may be configured to regulate displacement of the hydraulic motor.

The controller may be configured to regulate a control angle of the swash plate pump. In this way, it may control the speed of the tug and the force applied on the landing gear of the airplane thereby.

The controller may be configured to induce fast changes in the control angle of the swash plate pump. This allows it to prevent a force applied on the landing gear of the airplane from exceeding a force threshold.

The controller may be configured to induce slow changes in the control angle of the swash plate pump. For example, this may be useful to bring the towbarless airplane tug to a desired speed.

The controller may be configured to utilize a feed-forward process (i.e., a form of control in which upsets in inputs to the system can be used to adjust the system devices in anticipation of or simultaneously with the arrival of those upsets) to regulate the control angle of the swash plate pump.

The towbarless airplane tug may further comprise energy absorbers arranged to absorb energy between the landing gear and the chassis.

The altering of the one or more parameters of movement may have an effect so as to and/or be directed to cause the tug to reduce its speed and/or traction force.

5 The chassis may comprise a support assembly configured for the receiving of the portion of the landing gear and being mounted on the chassis such that it is moveable thereon at least in the direction. In such a case, the force sensor may be configured to measure the force exerted by the support assembly on the chassis in at least the direction.

10 The parameters of movement may be selected from a group comprising speed, direction, acceleration, and deceleration.

The controller may be configured to calculate a (predicted) resultant force exerted by the chassis on the landing gear at least based on one or more external factors. The external factors may be selected from a group comprising:

- 15 • data relating to slopes at various locations along an airplane travel surface to be traversed by the tug;
- data relating to wind forces affecting the airplane and tug;
- data relating to rolling friction forces of the airplane and or tug at various locations along the airplane travel surface; and
- data relating to obstacles.

20 The data relating to slopes may be provided by an inclination sensing functionality.

The data relating to slopes may be predetermined and stored as slope data in a database, the controller being further configured to determine the position of the tug on the airplane travel surface and to relate the slope data to the position.

25 The data relating to rolling friction forces may be predetermined and stored as friction data in a database, the controller being further configured to determine the position of the tug on the airplane travel surface and to relate the friction data to the position.

The tug may be configured to detect obstacles along the airplane path.

The controller may be configured to communicate wirelessly with a remote command center, for example via an electronic flight bag.

30 The towbarless airplane tug may further comprise an electronic flight bag configured to communicate wirelessly with a similar device within the airplane.

According to another aspect of the present invention, there is provided a method for towing an airplane, the method comprising providing a towbarless airplane tug comprising:

- 35 • a chassis configured for receiving thereon at least a portion of a landing gear of the airplane; and

- a propulsion arrangement configured to move the tug in a direction along a trajectory and comprising a variable angle swash plate hydraulic pump coupled to a variable angle swash plate hydraulic motor and to a controllable bypass path valve, configured such that a hydraulic fluid circulates between the pump and the motor so as to activate the propulsion arrangement to increase at least one of the speed and the traction force of the tug when the bypass path is in a closed state, and at least most of the hydraulic fluid circulates across the motor via the bypass path valve so as to reduce at least one of a rotational speed and traction force of the tug when the bypass path is in a opened state;

the method further comprising causing the tug to tow the airplane while altering one or more parameters of movement of the tug such that a force exerted by the chassis on the landing gear is maintained below a predetermined value by regulating at least the power available to the propulsion arrangement, the pump and motor swash-plates, and the state of the bypass path valve.

The tug may be provided as described above.

According to a further aspect of the present invention, there is provided a towbarless airplane tug configured for receiving a landing gear of an airplane and towing it thereby, the tug comprising:

- a chassis configured for receiving thereon at least a portion of the landing gear;
- a propulsion arrangement configured to move the tug in a direction along a trajectory;
- and
- a controller configured to compare between an actual speed of a towbarless airplane tug and a predetermined desired speed thereof, and to direct the propulsion arrangement to maintain the actual speed of the towbarless airplane tug if:
 - the actual speed is lower than the desired speed; and
 - the actual speed was maintained within a predefined speed range during a predefined period that preceded the comparing.

The controller may be further configured to detect airplane pilot-controlled braking and deceleration of the airplane, and is further configured to direct the propulsion arrangement to maintain the actual speed if:

- the actual speed is higher than the desired speed; and
- at least one of an airplane pilot-controlled braking and deceleration of the airplane is detected.

The controller may be further configured to direct the propulsion arrangement to change the actual speed of the towbarless airplane tug to match the desired speed if an airplane pilot-controlled braking is detected.

The towbarless airplane tug may be further configured to apply a positive traction force at all times during a towing of the airplane.

The towbarless airplane tug may be further configured to protect in real time the landing gear from exceeding its maximum allowed fatigue load.

5 The controller may be further configured to calculate the desired speed.

The controller may be further configured to calculate a desired traction force corresponding to the desired speed.

The controller may be further configured to calculate the desired speed at least based upon a location of the tug.

10 The controller may be further configured to calculate the desired speed at least based upon a location of the tug and a location of at least one other tug.

The controller may be further configured to calculate the desired speed at least based upon a location of the tug and a location and a speed of at least one other tug that shares at least one path therewith.

15 The controller may be further configured to calculate the desired speed at least based upon a location of the tug and a desired time of arrival thereof at an end of towing location.

The controller may be further configured to calculate the desired speed at least based upon a location of the tug, an estimated time of arrival of another tug at an end of towing point, and a desired time of arrival of the tug at the end of towing location.

20 The towbarless airplane tug may further comprise a transmitter configured to transmit information relating to speed and location of the tug. This information may be transmitted, e.g., to an airplane cockpit, to at least one other tug, or a remote command center.

The towbarless airplane tug may further comprise a receiver configured to receive information relating to speed and location of at least one other tug from a remote command center.

25 The towbarless airplane tug may further comprise a detector configured to detect a speed and a location of at least one other tug by utilizing a sensor; the controller being configured to calculate the desired speed at least based upon the speed and location of the other tug.

The controller may be further configured to calculate the desired speed based upon a desired time of arrival at an end of towing location and an estimated time of arrival of the other tug at an end of towing point.

30 According to a still further aspect of the present invention, there is provided a method for controlling a towbarless airplane tug, the method comprising:

- obtaining information relating to speed and location of at least one other tug that is expected to share at least a portion of a towing path with the tug; and

35

- calculating the desired speed of the tug at least based upon the speed and location thereof and the information.

The method may further comprise calculating the desired speed based upon desired time of arrival of the tug at an end of towing location.

5 The method may further comprise calculating the desired speed of the towbarless airplane tug based upon an estimated time of arrival of the one other tug at an end of towing point.

The method may further comprise transmitting information relating to speed and location of the tug to the other tug.

10 The method may further comprise transmitting information relating to speed and location of the tug to a remote command center and receiving there from information relating to speed and location information of the other tug.

The tug may obtain the information relating to speed and location of at least one other tug utilizing a sensor.

15 According to a still further aspect of the present invention, there is provided a towbarless airplane tug configured for receiving a landing gear of an airplane and towing it thereby, the tug comprising:

- a chassis configured for receiving thereon at least a portion of the landing gear;
- a propulsion arrangement configured to move the tug in a direction along a trajectory;
- 20 and
- a controller configured to operate as per the above.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description, taken in conjunction with the drawings in which:

25 **Fig. 1A** is a pictorial illustration of a towbarless airplane tug;

Fig. 1B is a cross-sectional view of the towbarless airplane tug illustrated in Fig. 1A, taken along the lines 1B-1B;

Fig. 1C is a top view of the towbarless airplane tug illustrated in Fig. 1A;

Figs. 2A through 2J are perspective views of various stages of pre-pushback and pushback operations of the towbarless airplane tug illustrated in Fig. 1A;

30 **Figs. 3A through 3E** illustrate various stages of pilot controlled taxiing operation of the towbarless airplane tug illustrated in Fig. 1A;

Figs. 4A through 4E illustrate various stages of autonomous taxiing operation of the towbarless airplane tug illustrated in Fig. 1A;

Figs. 5A through 5E illustrate various stages of the autonomous return operation of the towbarless airplane tug illustrated in Fig. 1A;

Figs. 6A through 6C diagrammatically illustrate steering functionality of the towbarless airplane tug illustrated in Fig. 1A;

5 **Figs. 7A through 7D** illustrate an energy absorption system that reacts to pilot-controlled braking of the airplane in order to control the load on the landing gear;

Fig. 8A is a block diagram of inputs and outputs of a force control loop and speed control loop which are part of a controller of the tug illustrated in Fig. 1;

10 **Fig. 8B** is a block diagram of a Multi Input/Multi Output (MIMO) force control loop and speed control loop which are part of the controller;

Fig. 9 illustrates a dynamic model of the towbarless tug and the airplane and forces applied on the plane and on the towbarless airplane tug illustrated in Fig. 1A;

Fig. 10 illustrates various control loops;

Fig. 11 illustrates a method for towing an airplane;

15 **Fig. 12** illustrates towbarless tug and airplane cockpit Electronic Flight Bag (EFB) units according;

Fig. 13 illustrates towbarless airplane tugs having two cameras;

Fig. 14 illustrates the movement of several towbarless tugs in an airport;

Fig. 15 illustrates a method for towing an airplane;

20 **Fig. 16** are plots of speed, pilot brake, traction force, and motor RPM, each as function of time, and related to desired and actual speed of towbarless airplane tugs; and

Fig. 17 illustrates a method for controlling a towbarless airplane tug.

DETAILED DESCRIPTION

25 A control system for a robotic or a semi-robotic tug for taxiing airplanes from an airport gate to a take-off runway is provided. The tug is designed for taxiing the airplane without using the airplane's jet engines, in order to save fuel consumption and minimize pollution. The controller thus has a dual function, namely controlling in real time and at all times the tug towing speed (thus replacing the airplane engine), and regulating the tug traction force (thus protecting the airplane's landing gear, e.g., the nose landing gear, or NLG, by not exceeding its static and

30 fatigue load limits, and thus not impacting its life cycle. Accordingly, a multi input, multi output (MIMO) control concept, where some controlling and controlled variables are interconnected and dependent, is provided in order to direct operation of the controller.

The description provided herein relates to robotic or semi-robotic tugs for taxiing airplanes from a gate to a take-off runway without using the aircraft jet engines. The tugs may

operate in an airplane pilot-controlled taxi mode, wherein the airplane pilot steers and brakes as if the airplane were moving under its own power, and the tug speed is controlled by its controller. Upon completion of taxiing, the tug may return autonomously to a pre-pushback location at the gate, controlled by an airport command and control system. A tug driver may perform the pushback operation, after which he leaves the tug and the airplane pilot controls the tug during taxi. The tug may operate in an autonomous mode of operation during airplane taxi. The term "autonomous" is used throughout in a broad sense to include operation under the control of an airport command, control and communication system, which may be subject to airplane pilot override.

Reference is now made to Figs. 1A, 1B, and 1C, which illustrate a towbarless airplane tug **100**. International publication WO 2008/139440, which is assigned to the assignee of the present application, teaches many principles which are applicable to the present disclosure, and the full content thereof are hereby incorporated by reference herein where appropriate for appropriate teachings of additional or alternative details, features and/or technical background. As seen in Figs. 1A, 1B, and 1C, the towbarless airplane tug **100** comprises a chassis **102** supported on six wheels, including forward steerable wheels **104** and **106**, rearward steerable wheels **108** and **110** and intermediate non-steerable wheels **112** and **114**. It is appreciated that wheels **112** and **114** may alternatively be steerable as well. The centers of rotation of steerable wheels **104**, **106**, **108**, and **110**, respectively indicated by reference numerals **115**, **116**, **117**, and **118**, may define vertices of a rectangle, whose length A is defined by the separation between the centers of rotation of respective forward and rearward wheels on the same side of the tug **100**, and whose width B is defined by the separation between the centers of rotation **115** and **116** of respective forward wheels **104** and **106** and between the centers of rotation **117** and **118** of respective rearward wheels **108** and **110**.

Each of wheels **104**, **106**, **108**, **110**, **112**, and **114** may be controllably driven by a corresponding hydraulic motor (not shown) powered by a corresponding hydraulic pump (not shown) driven by a vehicle diesel motor (not shown) in response to speed and torque control signals from a controller **119**. Each of the steerable wheels **104**, **106**, **108**, and **110** may be steerable by one or more steering pistons (not shown) in response to steering control signals from controller **119**. The wheels, hydraulic pump, and diesel motor constitute portions of a propulsion arrangement which is configured to move the tug in a direction along a trajectory.

A driver control interface assembly, which may include a steering wheel **120**, brakes (not shown), and optionally other controls as necessary, may interface with controller **119** to enable a driver to govern the operation of the towbarless airplane tug **100** prior to and during pushback, and/or in the event of an emergency or a tug control system malfunction. The towbarless airplane

tug **100** may operate in a “airplane pilot-in-control” (PIC) mode, via controller **119** to taxi to or near a take-off point. Near the take-off point, the controller **119** automatically or manually (by the safety driver) disengages the tug **100** from the airplane, in response to a command received from an airport Command and Control Center or from a tug location sensor **121**, such as a GPS sensor or any other suitable tug location sensor, and the tug **100** operates under control of controller **119**, to return autonomously or manually driven by a safety driver from the take-off point to a desired pre-push back location. Tug **100** may also be equipped with a wind sensor **122**, one or more obstacle detection sensors **123**, such as radar and/or laser sensors, for example as sold under the name HDL-64E by Velodyne®, which output to controller **119**, and one or more driving cameras **124**, which enable remote driving of tug **100**, such as by a remote command and control center. Driving cameras **124** may be rotatable to have selectable pan and tilt so as to enable an operator to view various locations on or near the tug **100**.

A rotatable airplane landing gear wheel support assembly **125** is pivotably and rotatably mounted on a horizontal base assembly **126**. The steady state center of rotation of the support assembly **125**, designated by reference numeral **127**, may be at the geometrical center of the rectangle defined by the centers of rotation **115**, **116**, **117**, and **118** of respective steerable wheels **104**, **106**, **108**, and **110**.

Horizontal base assembly **126** is connected to the chassis **102** in a manner which allows a limited amount of freedom of movement thereof relative to the chassis, and is engaged by an energy absorber assembly which may comprise a plurality of energy absorbing pistons **128**, each of which is pivotably coupled to the chassis **102** and to horizontal base assembly **126**. Force sensors **129**, which may be load cells, may be associated with each of energy absorbing pistons **128**, which output to controller **119**, and are used thereby in controlling vehicle acceleration and deceleration.

Horizontal base assembly **126** may comprise a circumferential base element **130**, which is pivotably mounted onto chassis **102** by being suspended from a transversely extending support rod **131** on a pair of forward hanging supports **132**, and suspended on a pair of rearward hanging supports **132** which are pivotably mounted onto chassis **102**. Hanging supports **132** are engaged by pivotably mounted energy absorbing pistons **128**. Mounting of circumferential base element **130** onto hanging supports **132** may be by means of pivotable axles **133**, which may or may not be integrally formed with circumferential base element **130**.

The support assembly **125** may be pivotably and rotatably mounted onto base **126** by a pair of pivot rods **134** extending outwardly therefrom into engagement with high load capacity bearings **135**, which in turn, engage a 360° circumferential bearing race **136** formed in base **126**.

This arrangement provides both relatively low friction rotatability and tiltability of the support

assembly **125** relative to the base element **130**, the horizontal base assembly **126**, and the chassis **102**.

An upstanding frame **140** is fixedly mounted onto the support assembly **125** for aligning the airplane landing gear wheel on the support assembly. An airplane landing gear wheel stop bar **142** may be selectably positioned with respect to upstanding frame **140** by a stop bar positioning piston **144**, anchored on the support assembly **125**, for adapting the support assembly to different sizes of airplane landing gear wheels. The rotational orientation of the support assembly **125** may be sensed by a rotation sensor **145**, such as a potentiometer, which provides a support assembly rotational orientation input to controller **119**. Rotational orientation of the support assembly **125** may be governed by a support assembly rotation motor **146**.

A selectably positionable clamp assembly **147** may be mounted on the support assembly **125** and connected to upstanding frame **140**. The clamp assembly **147** is operative to selectably clamp airplane landing gear wheels onto the support assembly **125** such that the center of rotation of the airplane landing gear wheels lies, insofar as possible, exactly at the center of rotation **127** of the support assembly, which, as noted above, lies at the geometrical center of the rectangle defined by the centers of rotation of steerable wheels **104**, **106**, **108**, and **110**.

Force sensors **148**, such as load cells, are mounted onto a forward facing surface of the clamp assembly **147** and onto a rearward facing surface of stop bar **142**, so as to engage the airplane landing gear wheels to sense forces in the horizontal plane which are applied to airplane landing gear wheels and thus to the airplane landing gear, such as due to differences in acceleration, deceleration, and/or speed of the tug **100** relative to acceleration, deceleration, and/or speed of an airplane being towed thereby.

An inclined airplane landing gear wheel ramp **150** may be mounted onto base element **130**. A pair of airplane landing gear wheel engaging piston assemblies **152** may be provided for pushing and lifting the airplane landing gear and positioning the airplane landing gear wheels onto the support assembly **125**.

The force sensors **148** may be operative to sense forces applied to the landing gear in at least one generally horizontal direction along a trajectory of movement of the tug. This force may be the result of airplane pilot-controlled braking of the airplane, which produces tug deceleration, or of tug acceleration. The controller **119** is operative at least partially in response to an output of a force sensor indicating, *inter alia*, airplane pilot-controlled braking, resulting in deceleration of the airplane to provide speed and torque control signals to the hydraulic motors which drive the wheels of the tug **100**. The control is such as to reduce and limit the force applied to the landing gear of the airplane, to a maximum allowed force which will not damage

the landing gear of the airplane as a result of airplane pilot-controlled braking resulting in tug deceleration and/or acceleration.

The rotation sensor **145** may be operative to sense rotation of the support assembly **125** relative to base assembly **126**, which is produced by airplane pilot steering via the landing gear of the airplane, and the controller **119** is operative to control steering of steerable wheels **104**, **106**, **108**, and **110** based on the output of rotation sensor **145** and thus in response to airplane pilot steering commands.

The force sensors **129** and **148** may be operative to sense forces applied to the landing gear in at least one generally horizontal direction resulting such that the controller **119** is operative to control acceleration and deceleration of the tug by employing at least one force feedback loop utilizing an output of at least one force sensor, sensing pilot-controlled braking and at least one of the following inputs:

- an indication of force induced by known slopes at various locations along an airplane travel surface traversed by the tug **100**, the locations being identified to the controller by location sensing functionality;
- an indication of wind forces applied to the airplane, information regarding the wind forces being supplied to the controller from airport and/or tug mounted wind sensors; and
- an indication of known tug and airplane rolling friction forces at various locations along the airplane travel surface traversed by the tug, the locations being identified to the controller by location sensing functionality.

The controller **119** may further be operative to control the speed of the tug **100** by employing at least one speed feedback loop based on known speed limits along a travel path traversed by the tug and the airplane, for example by utilizing a suitable airport map embedded in the controller **119**, and an output of a tug location sensor, indicating the position of the tug **100** along the travel path of the tug **100** and the airplane.

A single or pair of laser range finders **154** may be mounted on the chassis **102** of the tug **100** for ascertaining the angular relationship between the longitudinal axis of the airplane and the longitudinal axis of the tug **100**. The angular relationship between the longitudinal axis of the airplane and the longitudinal axis of the tug **100** may be employed in an autonomous taxiing mode of operation such as that described herein below in Figs. 4A through 4E.

As seen in Fig. 2A, the tug **100** is moved, under the control of a tug driver, in a direction indicated by an arrow **200**, towards an airplane **202** awaiting pushback. Fig. 2B illustrates the landing gear wheels **204** located on ramp **150**. Fig. 2C illustrates landing gear wheel engaging piston assemblies **152** positioned in engagement with landing gear wheels **204** for pushing and lifting the airplane landing gear and positioning the airplane landing gear wheels onto the

support assembly **125**. Fig. 2D illustrates suitable positioning of airplane landing gear wheel stop bar **142** with respect to upstanding frame **140** by a stop bar positioning piston **144** to accommodate the specific airplane landing gear wheels **204** of the specific airplane **202**. Fig. 2E illustrates landing gear wheels **204** being pushed onto the support assembly **125**.

Fig. 2F illustrates the airplane landing gear wheels **204** pushed by piston assemblies **152** against suitably positioned stop bar **142**, such that the axis of rotation of the airplane landing gear wheels **204** may lie insofar as possible exactly at the center of rotation **127** of the support assembly **125**, which, as noted above, lies at or close to the geometrical center of the rectangle defined by the centers of rotation of steerable wheels **104**, **106**, **108**, and **110**.

Figs. 2G and 2H illustrate a sequence of retraction of individual piston assemblies **152** out of engagement with airplane landing gear wheels **204** and engagement of individual clamps of the clamp assembly **147** with airplane landing gear wheels **204** to clamp airplane landing gear wheels onto the support assembly **125** such that the center of rotation of the airplane landing gear wheels lies insofar as possible exactly at the center of rotation **127** of the support assembly **125**.

Fig. 2I illustrates pushback of the airplane **202** by tug **100** under control of the driver of the tug. Fig. 2J illustrates the tug driver leaving the tug **100** following completion of pushback. The driver may remain on the tug **100** during all or part of taxiing, and may participate in disengagement of the tug from the airplane following engine start up.

Fig. 3A illustrates rotation of the airplane landing gear wheels **204** by the airplane pilot using the conventional airplane steering tiller **206** or pedals (not shown), producing corresponding rotation of the support assembly **125** relative to base element **130**. Rotation of the support assembly **125** is immediately sensed by rotation sensor **145** which provides an output to controller **119** resulting in immediate rotation of steerable wheels **104**, **106**, **108**, and **110** of tug **100**, as described hereinbelow in greater detail with reference to Figs. 6A through 6B.

Controller **119** may perform steering of tug **100** in accordance with a feedback control loop which receives an input from rotation sensor **145** indicating an angle α between the direction of the wheels **204** of the landing gear as steered by the airplane pilot, and thus of the support assembly **125**, with the longitudinal axis of the tug **100**, here designated by reference numeral **210**. The controller **119** rotates tug steerable wheels **104**, **106**, **108**, and **110** at respective angles β_1 , β_2 , β_3 and β_4 , as described hereinbelow with reference to Figs. 6A through 6C, and drives tug **100** such that angle α goes to zero.

Fig. 3B illustrates an intermediate stage during movement of the tug **100** during which is it oriented such that the airplane **202** is pulled thereby in the direction indicated by the airplane pilot. At this stage the angle α between the support assembly **125** and the longitudinal axis **210** of the tug **100** is shown to be one-half of that shown in Fig. 3A. An angle γ is indicated between the

longitudinal axis **210** of the tug **100** and the longitudinal axis of the airplane **202** being towed thereby, here designated by reference numeral **220**, due to turning of the tug **100** relative to the airplane **202**.

Fig. 3C illustrates the tug **100** oriented with respect to the wheels **204** of the landing gear of the airplane **202** such that α is zero. It is noted that the angles β_1 , β_2 , β_3 and β_4 of the tug steerable wheels **104**, **106**, **108**, and **110**, respectively, are typically not zero. At this stage the angle γ between the longitudinal axis **210** of the tug **100** and the longitudinal axis **220** of the airplane **202** being towed by tug **100** is less than γ in Fig. 3B, inasmuch as the airplane **202** has begun to turn.

Fig. 3D illustrates braking of the airplane **202**, by the airplane pilot pressing on pedals **222**. Braking of the airplane **202** is performed by brakes on the main landing gear (not shown) of the airplane **202**, causing the airplane to decelerate and thus immediately causing the application of a force sensed by the force sensors **148** on clamps **147**, the output of which is received by controller **119**, which immediately decelerates the tug **100** accordingly. Inasmuch as there is a time lag between braking of the airplane **202** and corresponding deceleration of the tug **100**, forces are applied to rearward energy absorbing pistons **128** which are immediately sensed by force sensors **129**. Rearward energy absorbing pistons **128** absorb the energy produced by braking of the airplane **202** relative to the tug **100**. At this stage force sensors **129** serve as a back up to force sensors **148**.

Fig. 3E illustrates controlled acceleration of the tug **100** governed by controller **119** in response, *inter alia*, to inputs received from force sensors **148** and **129**, to provide airplane taxi velocity which is within predetermined speed limits at predetermined locations along an airplane travel path and to ensure that forces applied to the landing gear do not exceed predetermined limits, taking into account one or more of the following factors:

- force induced by known slopes at various locations along an airplane travel surface traversed by the tug **100**, the locations being identified to the controller **119** by location sensing functionality, such as GPS functionality, here provided by a tug mounted tug location sensor **121**;
- wind forces applied to the airplane **202**, information regarding the wind forces being supplied to the controller **119** from airport or tug-mounted wind sensors, such as tug mounted wind sensor **122**, and optionally also via airport command and control functionality; and
- tug **100** and airplane **202** rolling friction forces at various locations along the airplane travel surface traversed by the tug **100**, the locations being identified to the controller **119**

by the location sensing functionality provided by tug location sensor **121**, and optionally also via airport command and control functionality.

The controller **119** may also decelerate of the tug **100** responsive not only to airplane pilot braking of the airplane **202**, but also to detection of an obstacle sensed by an obstacle sensor **123**. The tug deceleration is governed by controller **119** in response, *inter alia*, to inputs received from force sensors **148** and **129**, to ensure a coordinated deceleration ratio between the airplane and the tug, thereby to limit the forces applied to landing gear of the airplane **202** to within predetermined force limits.

In order to distinguish between normal traction forces on the landing gear and forces applied by the pilot braking, the controller **119** may take into account one or more of the factors described above, which are indicated by data from the various sensors, such as sensors **120**, **121**, **122**, and **123** and cameras **124**.

Controller **119** may be operative to govern acceleration and deceleration of tug **100** so as to maintain a desired tug speed by employing a speed control feedback loop. The controller **119** may be provided with, or given access to, an embedded map of the airport indicating relevant tug speed limits at various regions of the tug travel path. This speed limit information is coordinated with information indicating instantaneous location of the tug **100**, which may be provided by tug location sensor **121**. The controller **119** may further include a navigation system which indicates the instantaneous speed of the tug **100**. The feedback loop operates to cause the actual speed to be as close as possible to and not to exceed the speed limit for the instantaneous location of the tug **100**.

Controller **119** may also be operative to govern acceleration and deceleration of tug **100** so as to limit the horizontal forces applied to the landing gear of the airplane **202** to an acceptable limit, for example 4% of the airplane gross weight, for example by employing a force control feedback loop. Controller **119** receives inputs from force sensors **148** and **129**, which indicate the sum of the forces applied to the landing gear of the airplane **202**, resulting from, *inter alia*, wind, slopes, rolling friction, and acceleration or deceleration of the airplane **202** and/or the tug **100**. The force feedback loop is operative to accelerate or decelerate the tug **100** such as to maintain the forces sensed by force sensors **148** and **129** below the acceptable limit, optionally leaving a margin for unexpected accelerations or decelerations of either the airplane **202** or the tug **100**.

Reference is now made to Figs. 4A, 4B, 4C, 4D, and 4E, illustrate various stages in autonomous taxiing operation of the towbarless airplane tug **100**. The autonomous taxiing operation may be initiated by a driver of the tug **100** or automatically in response to a command from the airport command and control center following completion of pushback.

In autonomous taxiing operation, a function of the support assembly **125** is to reduce the forces which are applied to the landing gear in the horizontal plane, specifically torque, to zero, by maintaining the position of the landing gear wheels **204** in the position last selected by the airplane pilot, typically parallel to the longitudinal axis **220** of the airplane. As a result the landing gear remains in that position while the tug **100** changes its heading along its travel path. This means that in most of the steering maneuvers of the tug **100** the support assembly will be turned in a direction opposite to that of the tug **100**.

Autonomous tug control may be overridden immediately by the airplane pilot by operating the airplane brakes on the main landing gear, which is immediately sensed by force sensors **148** and **129**.

Autonomous taxiing may employ enhanced C4 (Command, Control, Communications, and Computers) functionality of an airport command and control center which coordinates and optimizes the taxi travel path and speed of all of the taxiing airplane in the airport, for example utilizing some or all of the following inputs:

- Positions of all the airplanes taxiing in the airport;
- Calculation of all airplane taxi clearances and taxi travel pathways; and
- Airfield meteorological conditions and taxiway ground travel conditions.

This enhanced C4 functionality may provide some or all of the following functions:

- avoidance of runway incursions;
- calculating optimal taxiing speeds for all the airplanes to insure minimal starts and stops during taxiing;
- minimizing traffic jams on the taxiways; and
- enabling immediate pilot control in the event of a malfunction or emergency.

Fig. 4A illustrates an initial orientation of the tug **100** and the airplane **202** at the beginning of autonomous taxiing operation. The airplane landing gear wheels **204** lie parallel to the longitudinal axis **210** of the tug **100** and to the longitudinal axis **220** of the airplane. The steerable wheels **104**, **106**, **108**, and **110** of the tug **100** also lie parallel to axes **210** and **220**.

Fig. 4B illustrates initial turning of the tug **100** under control of controller **119**, for example responsive to traffic control instructions received from an airport command and control system **250** based on a C4 system. As seen in Fig. 4B, the airplane pilot does not use conventional airplane steering tiller **206** or pedals (not shown), except for emergency braking. Desired steering of the tug **100** is produced in response to suitable instructions from controller **119** by rotation of steerable wheels **104**, **106**, **108**, and **110** of tug **100**. In order to avoid application of torque to the landing gear of the airplane **202**, the support assembly **125** is rotated by a support assembly rotation motor **146** by an angle $-\alpha$, which is equal in magnitude and

opposite in direction to the angle α between the longitudinal axis **210** of the tug and the longitudinal axis **220** of the airplane. Rotation of the support assembly **125** is sensed by rotation sensor **145** which provides a feedback output to controller **119**.

Controller **119** may steer the tug **100** by steering steerable wheels **104**, **106**, **108**, and **110** and rotating the support assembly **125** by support assembly rotation motor **146** in accordance with two feedback control loops. One feedback loop ensures that the heading of the tug **100** follows a predetermined travel path established by the airport command and control system **250**. The second feedback loop employs laser range finders **154** to ensure that the landing gear wheels **204** are aligned parallel to the longitudinal axis **220** of the airplane. The laser range finders **154** ascertain the angle α between the longitudinal axis **210** of the tug **100** and the longitudinal axis **220** of the airplane **202**. Controller **119** ensures that the support assembly **125** is rotated relative to the longitudinal axis **210** by an angle $-\alpha$, so as to ensure that the landing gear wheels **204** remain aligned with the longitudinal axis **220** of the airplane at all times.

Fig. 4C illustrates a further stage of rotation of the tug **100**. At this stage the angle α between the longitudinal axis **210** of the tug **100** and the longitudinal axis **220** of the airplane **202** and the angle $-\alpha$ between the support assembly **125** and the longitudinal axis **210** of tug **100** are shown to be twice the angles shown in Fig. 4B.

Fig. 4D illustrates an overriding of the autonomous mode of operation by the airplane pilot, for example by the airplane pilot pressing on braking pedals **222**. This overriding may be, e.g., for emergency braking and/or to enable the airplane pilot to control steering of the tug **100**, as described above with reference to Figs. 3A through 3E. Braking of the airplane **202** is performed by brakes on the main landing gear (not shown) of the airplane **202**, causing the airplane to decelerate and thus immediately causing the application of a force sensed by the force sensors **148** on clamps **147**, the output of which is received by controller **119**, which immediately decelerates the tug **100**.

Controller **119** terminates the pushback operation mode of the tug **100** and transfers the tug mode to airplane pilot control operation, as described above with reference to Figs. 3A through 3E.

Inasmuch as there is a time lag between braking of the airplane **202** and corresponding deceleration of the tug **100**, forces are applied to rearward energy absorbing pistons **128** which are immediately sensed by the force sensors **129**. Rearward energy absorbing pistons **128** absorb the energy produced by braking of the airplane **202** relative to the tug **100**. At this stage the force sensors **129** serve as a back up to force sensors **148**.

A return to autonomous mode operation typically requires an input from the airport command and control system **250** or a pilot command transmitted via an Electronic Flight Bag (EFB), such as commercially available from Astronautics Ltd. of Israel.

Fig. 4E illustrates a controlled acceleration of the tug **100** in the autonomous mode of operation, governed by controller **119** in response, *inter alia*, to inputs received from airport command and control center **250** and from force sensors **148** and **129**, to provide airplane taxi velocity which is within predetermined speed limits at predetermined locations along an airplane travel path, and to ensure that forces applied to the landing gear do not exceed predetermined limits, taking into account one or more of the following factors:

- force induced by known slopes at various locations along an airplane travel surface traversed by the tug **100**, the locations being identified to the controller **119** by location sensing functionality, such as GPS functionality, here provided by a tug mounted tug location sensor **121**;
- wind forces applied to the airplane **202**, information regarding the wind forces being supplied to the controller **119** from airport or tug-mounted wind sensors, such as tug mounted wind sensor **122**, and via airport command and control functionality; and
- tug and airplane rolling friction forces at various locations along the airplane travel surface traversed by the tug **100**, the locations being identified to the controller **119** by the location sensing functionality provided by tug location sensor **121**, and via airport command and control functionality.

The controller **119** may decelerate the tug **100** responsive not only to airplane pilot braking of the airplane **202**, but also to detection of an obstacle sensed by an obstacle sensor **123** or one of driving cameras **124** or to control instructions received from airport command and control center **250**. The tug deceleration is governed by controller **119** in response, *inter alia*, to inputs received from force sensors **148** and **129**, to ensure a coordinated deceleration ratio between the airplane and the tug, thereby to limit the forces applied to landing gear of the airplane **202** to within predetermined force limits.

In order to distinguish between normal traction forces on the landing gear and forces applied by the pilot braking, the controller **119** takes into account one or more of the factors described above, which are indicated by data from the various sensors, such as sensors **120**, **121**, **122**, and **123**.

Controller **119** may be operative to govern acceleration and deceleration of tug **100** so as to maintain a desired tug speed by employing a speed control feedback loop. The controller **119** may be provided with, or given access to, an embedded map of the airport indicating relevant tug speed limits at various regions of the tug travel path. This speed limit information is coordinated

with information indicating instantaneous location of the tug **100**, which may be provided by tug location sensor **121**. The controller **119** may further include a navigation system which indicates the instantaneous speed of the tug **100**. The feedback loop operates to cause the actual speed to be as close as possible to and not to exceed the speed limit for the instantaneous location of the tug.

Controller **119** may also be operative to govern acceleration and deceleration of tug **100** to as to limit the horizontal forces applied to the landing gear of the airplane **202** to an acceptable limit, for example 4% of the airplane gross weight, for example by employing a force control feedback loop. Controller **119** receives inputs from force sensors **148** and **129**, which indicate the sum of the forces applied to the landing gear of the airplane, resulting from, *inter alia*, wind, slopes, rolling friction and acceleration or deceleration of the airplane **202** and/or the tug **100**. The force feedback loop is operative to accelerate or decelerate the tug **100** such as to maintain the forces sensed by force sensors **148** and **129** sufficiently below the acceptable landing gear force limit, optionally leaving a margin for unexpected accelerations or decelerations of either the airplane **202** or the tug **100**.

When the tug **100** is operative in the autonomous taxiing mode of operation illustrated in Figs. 4A through 4E, where the taxi speeds of tug **100** and the towed airplane **202** are typically those of the airplane pilot controlled taxiing mode of operation, the airplane pilot may be able to override the autonomous system to switch to an airplane pilot-controlled mode of operation by applying the airplane brakes and resuming tug steering by the airplane tiller **206**. The airplane pilot may also apply the airplane brakes in emergency situations.

Efficient taxiing operation is provided in the autonomous taxiing mode of operation due to the fact that the ground movements of all airplanes in the airport are managed by the command and control system **250** in an integrated manner, thus avoiding lines of airplanes waiting to take off. As seen in Fig. 4E, the command and control system **250** integrates the movement of all airplanes such that airplanes maintain desired spacing between them during taxiing and avoid start and stop movements, insofar as possible.

Reference is now made to Figs. 5A, 5B, 5C, 5D and 5E, which are respective pictorial illustrations of various stages in the autonomous mode of operation of the towbarless airplane tug **100** under the control of a command and control system in the airport tower, via controller **119** for tug taxiing movement and for return of the tug **100** from the take-off area to a pre-pushback location.

Figs. 5A, 5B and 5C illustrate disengagement of the tug **100** from the airplane landing gear wheels **204**. It is appreciated that disengagement of the tug **100** from the airplane is typically carried out after the engines of the airplane have been started by the airplane pilot. The

command and control system **250** may command the tug **100** to perform disengagement. Alternatively, disengagement by the tug may be automatically actuated by the sensed location of the tug at a predetermined disengagement location adjacent the take off point. The disengagement instructions may be communicated wirelessly to the controller **119**. In response to an instruction to disengage the tug, the clamp assembly **147** is disengaged from clamping engagement with the airplane landing gear wheels **204** and tug **100** is moved forward, while the airplane pilot brakes the airplane **202** and controls the airplane tiller **206**, allowing the airplane landing gear wheels to roll down the ramp **150** and keeping the landing gear parallel to the longitudinal axis of the airplane **220**, as the ramp **150** is moved forward relative thereto.

A safety driver may be present on the tug **100**, in which case the disengagement can be carried out by the safety driver in a conventional manner and is usually accompanied by disconnection of a voice communications cord, by the safety driver.

Fig. 5D illustrates a controlled acceleration and steering of the tug governed by controller **119** to provide tug travel speed which is within predetermined speed limits at predetermined locations along a predetermined tug autonomous travel path from the take off area to a pre-pushback location, taking into account one or more of the following factors:

- instantaneous location of the tug **100** as indicated by tug location sensor **121**;
- obstacle detection information received from sensors **123** or cameras **124**;
- real time information on the locations of other vehicles along the tug travel path which is provided by the airport command and control system **250**; and
- information indicating one or more predetermined travel paths of the tug **100** from the take-off location to the pre-pushback location; this information may be stored in controller **119** or provided in real time by the airport command and control system **250**.

Fig. 5E illustrates controlled deceleration and parking of the tug governed by controller **119** at a pre-pushback location.

Reference is now made to Figs. 6A, 6B and 6C, which are respective diagrammatical illustrations of steering functionality of the towbarless airplane tug **100**, which provides Ackerman steering of the airplane **202**.

Turning to Fig. 6A, which illustrates the airplane **202** with its landing gear wheels **204** steered straight ahead along the longitudinal axis **220** of the airplane **202**, the following designations of parameters are noted:

- L = distance along the longitudinal axis **220** of the airplane **202** between the axis of rotation **302** of the landing gear wheels **204**, and a line **304** joining the main landing gear, here designated by reference numerals **306** and **308**;

- A = Longitudinal distance between a line **310** connecting the centers of back steerable wheels **108** and **110** and a line **312** connecting the centers of front steerable wheels **104** and **106** of the tug **100**;
- B = Transverse distance between centers of wheels **108** and **110** and between centers of wheels **104** and **106** of the tug **100**; and
- C = Distance between main landing gear **306** and **308** along line **304**.

Fig. 6B illustrates airplane **202** with its landing gear wheels **204** turned by an angle α , in response to airplane pilot steering using tiller **206** producing corresponding rotation of the support assembly **125** relative to the chassis **102** of tug **100**. Controller **119** causes rotation of tug steerable wheels **104**, **106**, **108** and **110** in order to cause reorientation of the tug **100** such that α goes to zero, as described hereinabove with reference to Figs. 3A through 3E. Controller **119** also controls the motion of the tug **100** such that Ackerman steering of the airplane **202** is produced, as illustrated in Fig. 6B, in accordance with the following parameters:

- $R + C/2$ = instantaneous radius of rotation of airplane **202**;
- α = angle of rotation of the landing gear wheels **204** relative to the longitudinal axis **220** of the airplane **202**; and
- β_i = Steering angle of the wheels of tug **100** ($i = 104, 106, 108, \text{ and } 110$).

The calculation of β_i as a function of α may be as follows:

- $L/[R + C/2] = \tan \alpha \gg R = L/\tan \alpha - C/2$
- $\tan(\beta_{108}) = [L - A/2 \cos \alpha - B/2 \sin \alpha]/[L/\tan \alpha + A/2 - B/2 \sin \alpha]$
- $\tan(\beta_{110}) = [L - A/2 \cos \alpha + (A/2 \tan \alpha + B/2) \sin \alpha]/[L/\tan \alpha + (A/2 \tan \alpha + B/2) \cos \alpha]$
- $\tan(\beta_{104}) = [L - A/2 \cos \alpha + B/2 \sin \alpha]/[L/\tan \alpha - A/2 + B/2 \sin \alpha]$
- $\tan(\beta_{106}) = [L - A/2 \cos \alpha - (A/2 \tan \alpha + B/2) \sin \alpha]/[L/\tan \alpha - (A/2 \tan \alpha + B/2) \cos \alpha]$

Fig. 6C illustrates the operation of tug **100** in accordance with a tug steering algorithm whereby the tug **100** is reoriented relative to the airplane **202** such that α is zero. As noted above with reference to Figs. 3A through 3E, controller **119** reorients the tug **100** by rotating steerable tug wheels **104**, **106**, **108**, and **110** as described hereinabove so as to reduce the angle α , sensed by rotation sensor **145**, to zero. Controller **119** may be operative to cause orientation of the tug **100** such that the instantaneous radius of rotation, $R + C/2$, of the tug-towed airplane **202** is identical to the instantaneous radius of rotation $R + C/2$ of the airplane **202**, itself, such that in the example illustrated in Figs. 3A through 3E, the pilot of the airplane steers the airplane in the same way whether or not it is pulled by the tug **100** or proceeds under its own power.

Reference is now made to Figs. 7A and 7B, which illustrate a portion of the towbarless airplane tug, while Fig. 7C illustrates a portion of the variable angle swash plate motor. A hydrostatic drive system pressure (P_S) provides the traction force and will be used to control the

load on the landing gear of the airplane during acceleration, deceleration and stopping, through a force control loop. Traction force target will be derived from the speed control loop, and the force control loop will define the acceleration required to reach desired speed. Speed and Force control loops output are the RPM of diesel motor **160** and the desired control angle Φ of variable angle swash plate pump **161**. Speed control input (feedback) is wheels odometer signal (θ'), force control input (feedback) is the force sensor signal (ΣF) and hydraulic system pressure (P_s), motor torque – vehicle traction force. System pressure will be limited so that the landing gear load limits will not be exceeded, at all times and in real time.

Diesel motor **160** controls hydrostatic variable displacement pumps flow rate, and motor torque controls pump pressure. The motor has a dynamic response, roughly modeled as a first order system $N_d/(\tau_d S + 1)$ with time constant τ_d . The revolution speed of the hydraulic motor **162** is denoted N_d . Hydraulic pump constant is K_p , the control angle of variable angle swash plate pump variable angle swash plate pump **161** is Φ and can be controlled by a valve (not shown). Hydraulic motor **162** constant is D_m providing the traction torque – force F_t . Hydraulic system damping viscous friction is B_h , and vehicle mass M_2 that can be translated into an equivalent inertia J_2 as seen by the motor. There is no spring effect in the system (continuous rotation).

In order to increase bandwidth (improve speed of response) of the speed and force control loops, servo-valve **164** is installed in the hydraulic system, between motor high and low pressure lines. Servo-valve **164**, a fast response valve, controls the speed and the amount of energy dissipated (absorbed). Controlled opening of the servo-valve **164** is practically “causing to leakage” through a narrowed pass **165** that slows down the vehicle, up to a complete stop (no flow through the motor – all flow dumped through the servo-valve **164**). During a fast pilot braking (deceleration $0.4g - 0.5g$), the energy absorption system may bottom-up and then the vehicle impact (40 ton) is taken by the landing gear. However, even the highest possible deceleration $0.5g$ will cause to $F = 40,000 \times 0.5g = 20$ ton on the landing gear (maximum allowed $0.15 W = 60$ ton for B747 for example).

Fig. 7A illustrates the flow of hydraulic fluid **167** during a non-brake period. For example it can occur when the airplane is accelerated or moves at a substantially constant speed. In this situation, the servo-valve **164** (controlling bypass path **166**) is closed, so that all hydraulic fluid **167** flows between the variable angle swash plate pump **161** and the hydraulic motor **162**, thus rotating the tug wheel.

Fig. 7B illustrates the flow of hydraulic fluid **167** during a brake period. Once the airplane pilot brakes the airplane, servo-valve **164** is opened, causing a leakage of hydraulic fluid **167** through a bypass path **166** entering a narrowed pass **165** that slows down the vehicle.

Fig. 7C illustrates the angle of variable angle swash plate that controls the vehicle speed. The diesel motor controls variable angle swash plate pump 161. A smaller angle will lower the pressure of the hydraulic pump, thus lowering the liquid flow and slows down the wheel.

Fig. 7D illustrates that an additional bypass path 181 can be connected in parallel to the variable angle swash plate pump 161. The additional bypass path includes a servo-valve 181 and can be opened in response to either a higher than desired hydraulic fluid pressure, or in response to an output of at least one force sensor indicating airplane pilot-controlled braking of the airplane. It can be controlled by controller 119 and/or by hydraulic pressure sensing elements (not shown).

It is noted that both bypass paths can be opened when sensing a braking of the airplane, that they can be opened in parallel or in a serial manner. One of the bypass pathes can be opened when sensing braking forces that exceed a first threshold, while the other is opened when sensing braking forces that exceed another threshold.

For example, both may be opened when sensing braking forces of about 0.5g or more while only the additional bypass path may be opened when sensing braking forces that do not exceed 0.2g.

Fig. 8A is a block diagram of the inputs and outputs of force control loop 171 speed control loop 172 which are part of controller 119. The force control loop and the speed control loop outputs are the RPM (denoted N_d) of diesel motor 160 and control-angle (Φ) of variable angle swash plate pump 161. The input (feedback) to force control loop 171 can be a force sensor signal and hydraulic system pressure (P). Speed control loop 172 input (feedback) may be the wheels odometer signal.

Fig. 8B illustrates an example of a Multi Input/Multi Output (MIMO) controller. The controller controls the speed and force applied by the towbarless tug. It receives multiple inputs variables such as:

- W_{des} – towbarless tug desired speed V_{des} by diesel motor speed (RPM);
- D_p – hydrostatic pump displacement (torque/flow $T_p = D_p \times P$, $Q_p = D_{pwe}$); and
- D_m – hydrostatic motor displacement (torque/flow $T_m = D_m \times P$, $Q_m = D_{mwm}$);

as well as outputs multiple control variables such as:

- V_{eh} – Vehicle Speed (which is controlled by hydraulic motor speed W_m);
- $F_{traction}$ – Vehicle Traction Force (which is controlled by hydraulic motor pressure P); and
- $W_{e\ Motor}$ – diesel motor speed.

Fig. 9 illustrates various forces applied on the plane and on the towbarless tug.

Fig. 10 illustrates various control loops that are implemented by a controller of the towbarless airplane tug.

Fig. 11 is a flow chart of method **2000** for towing an airplane.

Method **2000** starts by stage **2010** of towing an airplane by a towbarless airplane tug while sensing, by at least one force sensor, a force applied to a landing gear of the airplane in at least one generally horizontal direction and while maintaining a bypass path closed; wherein the
5 bypass path is coupled to a variable angle swash plate pump and hydraulic motor of a tug wheel driving module that is connected to a tug wheel.

Stage **2010** can be implemented by any of the towbarless airplane tug activities mentioned above.

Stage **2010** is followed by stage **2015** of sensing a pilot-controlled braking of the
10 airplane. Stage **2010** is triggered by one of the force sensors.

Stage **2015** is followed by stage **2020** of determining to open a bypass path.

Stage **2020** is followed by stage **2030** of opening, by a tug controller, at least partially in response to an output of the at least one force sensor indicating airplane pilot-controlled braking of the airplane, a bypass path so as to reduce a force applied to the landing gear of the airplane as
15 the result of the airplane pilot-controlled braking, wherein during a braking period that follows the opening of the bypass path at least most of the hydraulic fluid circulates between the hydraulic motor and the bypass path so as to reduce a rotational speed of the tug wheel.

Stage **2030** can include either one of the following or a combination thereof:

- opening a bypass path that is sized to reduce a flow of hydraulic fluid through the bypass
20 path in relation to a flow of hydraulic fluid when the bypass path is closed;
- opening the bypass path, using a valve, within a time period that is much smaller than the brake period; and
- opening the bypass, using a valve, within a time period that is much smaller than a
25 resonance period of the hydraulic motor.

Stage **2030** is followed by closing the bypass path. The bypass path can be closed when the force applied on the landing gear is below a threshold or when a predefined braking period ended or a combination thereof. The braking period can stop when the plane completely stops or travels at a speed that is below a predefined speed threshold.

Method **2000** can include stage **2040** of applying one or more control loops. Stage **2040**
30 can be executed in parallel to either one of stages **2010**, **2015**, **2020**, **2030** and **2035**. Stage **2040** can include applying a speed control loop, a force control loop, a feedback and/or a feed forward loop, and the like.

Stage **2040** can include determining, by the tug controller a control angle of the variable angle swash plate pump. Conveniently, stage **2020** of determining opening the bypass path
35 includes applying a control loop that can be triggered by an outcome of such a control loop.

Stage **2040** can include at least one of the following or a combination thereof:

- controlling the speed of the towbarless airplane tug and applying a force on the landing gear of the airplane by determining a control angle of the variable angle swash plate pump;
- 5 • introducing fast changes in the control angle of the variable angle swash plate pump to prevent a force applied on the landing gear of the airplane to exceed a force threshold;
- inducing slow changes in the control angle of the variable angle swash plate pump in response to a desired speed of the towbarless airplane tug; and
- 10 • applying a feed-forward process to determine the control angle of the variable angle swash plate pump.

Stage **2040** includes sub-stages of sensing a speed change of the airplane (**2042**), applying a feed-forward process to the variable angle swash plate pump (**2044**), that results changing the control angle of the variable angle swash plate pump (**2046**) that causes the airplane to slow down.

15 Fig. 12 illustrates the airplane as including an electronic flight bag (EFB) **991** that communicated (in a wireless manner) with an EFB **992** of the towbarless airplane tug. Both EFBs may be equipped with displays. These EFBs can allow a pilot to remotely control the towbarless airplane tug.

EFB **992** can communicate in a wireless manner with a remote command center such as
20 an airport tower. The wireless communication can allow a provision of information to the airport tower and send commands to the towbarless airplane tug. Various communication protocols such as Wi-Fi, Wi-Max, Bluetooth, and the like can be used.

Fig. 13 illustrates the towbarless airplane tug as including a first camera **881** that is directed to the front of the towbarless airplane tug and can assist in detecting obstacles, and a
25 second camera **882** that views support assembly **125** and can assist in monitoring the manner in which the wheel is supported by the towbarless airplane tug.

The movement of the towbarless airplane tug may be responsive to the location and movements of one or more other towbarless airplane tugs. If multiple towbarless airplane tugs share the same path (or if their paths overlap) the towing of one towbarless airplane tug should
30 be responsive to the towing process of the other towbarless airplane tug.

Assuming that two towbarless airplane tugs are expected to tow their airplanes to the same takeoff runway - that the towing process should end at substantially the same location (which is usually the beginning of the takeoff runway), and assuming that there is a predefined timing difference between adjacent takeoffs. If, for example a first plane is expected to arrive (by
35 towing) to the beginning of the takeoff runway at a first point in time then the second airplane

should not arrive (to the beginning of the takeoff runway) until after the predefined timing difference lapsed. Typically, instead of defining a single timing difference a range of desired timing differences is defined. The timing differences are usually dependent upon the throughput of the airfield and the current air traffic load. Typical timing differences can range between one and three minutes, although this is not necessarily so.

In many cases these timing differences can be obtained by reducing the towing speed in a manner than the actual towing speed is lower than the maximum allowable towing speed. The maximum allowable towing speed is usually defined per area and is responsive to various variable such as the slope of the road, weather conditions (for example, snow, rain, strong winds), curvature of the road, and other factors which would affect the maximum allowable towing speed.

A reduction of speed can reduce air pollution and can also reduce braking attempts of the pilot.

The required speed can be calculated by the towbarless airplane tug, by a central control entity and the like. For example, one towbarless airplane tug can calculate the desired speed of one or more other towbarless airplane tugs.

Information relating to the location and additionally or alternatively the speed of towbarless airplane tugs can be transmitted from one towbarless airplane tug to another, to a central control entity, and the like. One towbarless airplane tug can relay information related to one or more other towbarless airplane tugs to each other and, additionally or alternatively, to a central control entity.

Figure 14 illustrates three towbarless airplane tugs **1601**, **1602**, and **1603**. It is assumed that all three towbarless airplane tugs are expected to tow their airplanes to the same takeoff runway **1610**, and that the towing should end at substantially the same location, i.e., runway area **1612**. Towbarless airplane tugs **1601**, **1602**, and **1603** can exchange information relating to their speed and location and, additionally or alternatively, this information can be provided by a central entity such as a control system of the airport tower, such as the control system illustrated in Fig. 4E.

The three towbarless airplane tugs **1601**, **1602**, and **1603** may use radars or other detectors to detect the speed and/or location of each other.

It is assumed that towbarless airplane tug **1601** precedes towbarless airplane tug **1602** and that towbarless airplane tug **1603** follows towbarless airplane tug **1602**. It is also assumed that an allowed timing difference range is defined, for example ranging between Δt_1 and Δt_2 .

Towbarless airplane tug **1602** is expected to arrive to location **1612** at a first point in time t_1 . This expected time of arrival can be calculated or measured (if towbarless airplane tug **1602**

already arrived to runway area **1612**) by either one of towbarless airplane tugs **1601**, **1602**, and **1603** or by another entity and can be sent to towbarless airplane tugs **1602** and **1603**.

The towing scheme of towbarless airplane tug **1602** can be designed so that it will arrive to runway area **1612** at a second point of time t_2 , wherein t_2 ranges between $(t_1 + \Delta t_1)$ and $(t_1 + \Delta t_2)$. The towing scheme includes the desired speed along the path that leads to location **1612**. In any case the desired speed should not exceed the allowable speed as dictated by road and air conditions. The towing scheme can be calculated by a central control entity or towbarless airplane tug **1602** but it can also be calculated by another towbarless airplane tug.

The towing scheme of towbarless airplane tug **1603** can be designed so that it will arrive to runway area **1612** at a third point of time t_3 . t_3 ranges between $(t_2 + \Delta t_1)$ and $(t_2 + \Delta t_2)$. The towing scheme includes the desired speed along the path that leads to location **1612**. In any case the desired speed should not exceed the allowable speed as dictated by road and air conditions. The towing scheme may be calculated by a central control entity, by towbarless airplane tug **1603**, or by another towbarless airplane tug.

A cruise control scheme may be applied by the towbarless airplane tug.

The cruise control scheme allows a pilot to dictate the actual speed of the towbarless airplane tug by maintaining the speed of the airplane within a predefined speed range during a predefined period, for example in cases where the actual speed of the towbarless airplane tug is lower than a desired speed of the towbarless airplane tug.

The cruise control scheme allows a pilot to dictate the actual speed of the towbarless airplane tug by performing a pilot controlled braking or deceleration – in case that the actual speed of a towbarless airplane tug is higher than the desired speed of the towbarless airplane tug.

The pilot can exit the cruise control, and thus allow the towbarless airplane tug to attempt to match its actual speed to a desired speed, by pushing the brakes and disconnecting the cruise control mechanism.

Fig. 15 illustrates method **1700** for towing an airplane.

Method **1700** starts by any one of stages **1707**, **1708**, and **1709**.

Stage **1707** includes calculating the desired speed of the towbarless airplane tug. Stage **1707** can include at least one of the following:

- calculating the desired speed of the towbarless airplane tug based upon its location;
- calculating the desired speed of the towbarless airplane tug based upon its location and a location of at least one other towbarless airplane tug;
- calculating the desired speed of the towbarless airplane tug based upon its location and a location and a speed of at least one other towbarless airplane tug that shares at least one path with the towbarless airplane tug;

- calculating the desired speed of the towbarless airplane tug based upon its location and a desired time of arrival of the towbarless airplane tug to an end of towing location; and
- calculating the desired speed of the towbarless airplane tug based upon its location, an estimated time of arrival of another towbarless airplane tug to an end of towing point, and a desired time of arrival of the towbarless airplane tug to the end of towing location.

Stage 1708 includes transmitting speed and location information to at least one other towbarless airplane tug. Stage 1708 can include transmitting speed and location information to a remote command center and receiving from the remote command center speed and location information of at least one other towbarless airplane tug.

Stage 1709 includes detecting a speed and a location of at least one other towbarless airplane tug by utilizing a sensor such as a radar or laser sensor or alike.

Stages 1707, 1708, and 1709 are followed by stage 1710 of comparing between an actual speed of a towbarless airplane tug and a desired speed of the towbarless airplane tug. The actual speed can be measured and the desired speed can be received by the towbarless airplane tug or can be calculated by the towbarless airplane tug.

Stage 1710 is followed by stage 1720 of maintaining the actual speed of the towbarless airplane tug if the actual speed of a towbarless airplane tug is lower than the desired speed of the towbarless airplane tug, and if the actual speed of the towbarless airplane tug was maintained within a predefined speed range during a predefined period that preceded the comparing. The predefined speed range can be a relatively narrow range.

Stage 1710 can also be followed by stage 1730 of maintaining the actual speed of the towbarless airplane tug if the actual speed of a towbarless airplane tug is higher than the desired speed of the towbarless airplane tug and if detecting at least one of an airplane pilot-controlled braking and deceleration of the airplane.

Stages 1720 and 1730 can be followed by stage 1740 of changing the actual speed of the towbarless airplane tug to match the desired speed of the towbarless airplane tug is detecting an airplane pilot-controlled braking.

Method 1700 can also include stage 1790 of applying a positive traction force by the towbarless airplane tug during the towing of the plane. By applying only can be extended or not affected by the additional forces applied by the tug.

Fig. 16 is a timing diagram that illustrates a relationship between desired speed and actual speed.

By way of explanation, Fig. 18 includes speed values, force value, and RPM values. These are non-limiting examples of speeds, forces, and RPMs.

The timing diagram illustrates an example of changes (over time) of a desired speed of a towbarless tug (also referred to “desired speed”), an actual speed of a towbarless tug (also referred to “actual speed”), braking applied by a pilot, force applied on the landing gear of the airplane (that is supported by the towbarless airplane tug) and revolution rate of a diesel motor of the towbarless airplane tug.

Table 1 illustrates these values during points in time $t_0 - t_{18}$.

Table 1

Time	Desired speed	Actual speed	Braking applied by pilot ?	Force applied on landing gear by tug – percent of airplane takeoff weight	RPM of diesel motor
t_0	0	0	Yes	3%	1500
t_1	10	0	No	3%	1500
t_2	10	5	No	3-5%	2200
t_3	10	10	No	5-2%	2200
t_4	20	10	No	2%	2200
t_5	20	20	No	5%	2200
t_6	10	20	Yes	2%	2200
t_7	10	11	No	2%	2200
t_8	20	11	Yes	2%	2200
t_9	20	0	Yes	3%	2200
t_{10}	20	0	No	3%	1500
t_{11}	20	5	No	3-5%	2200
t_{12}	20	10	Yes	5%	2200
t_{13}	10 (20)	10	No	2%	2200
t_{14}	10 (20)	10	Yes	2%	2200
t_{15}	20	8	No	3-5%	2200
t_{16}	20	20	No	5%	2200
t_{17}	20	20	No	2%	2200
t_{18}	20	0	Yes	3%	1500

The towing process starts at t_1 . Between t_0 and t_1 the pilot presses the brakes and the towbarless airplane tug is motionless.

At t_1 the towbarless airplane tug starts moving and its actual speed increases until it reaches (at t_3) a desired speed of 10 knots. At t_4 the desired speed increases to 20 knots and between t_4 and t_5 the speed of the towbarless airplane tug increases until it reaches (at t_5) the desired speed of 20 knots. Between t_5 and t_6 the actual speed and the desired speed are equal to 20 knots and the tug maintains its speed. Between t_6 and t_7 the pilot presses the brakes (because of a possible turning maneuver with a lower desired speed of 10 knots) and the actual speed of the towbarless airplane tug decreases to 11 knots until t_8 . Between t_8 and t_{10} the pilot hits the brakes and although the desired speed is 20 knots the actual speed decreases to zero (at t_9) and is maintained at this level until t_{10} . Between t_{10} and t_{12} the speed of the tug increases to 10 knots. Between t_{12} and t_{13} the pilot maintains the speed of the airplane to about 10 knots and this causes

the desired speed to be changed to 10 knots. In other words, the pilot sets the cruise speed to be 10 knots. This speed is maintained until the pilot presses the brakes during a short period (between t_{14} and t_{15}) and disconnects the cruise control. Accordingly, the desired speed is reset to 20 knots and between t_{15} and t_{16} the speed increases until it reaches 20 knots. At t_{17} the pilot starts a braking session that causes the towbarless airplane tug to stop.

The timing diagram also illustrates that these accelerations and decelerations may result in changes in the force applied on the landing gear by the towbarless airplane tug. Peaks are detected at t_3 , t_5 , between t_8 and t_9 , at t_{12} , and at t_{16} .

Figure 17 illustrates method **1900** for controlling a towbarless airplane tug.

Method **1900** starts by stage **1910** of obtaining, by the towbarless airplane tug, speed and location information of at least one other towbarless airplane tug that are expected to share at least a portion of a towing path with the towbarless airplane tug.

Stage **1910** is followed by stage **1920** of calculating the desired speed of the towbarless airplane tug based upon a speed and a location of the towbarless airplane tug and the speed and location information.

Stage **1920** can be followed by either one of stages **1930** and **1940**.

Stage **1930** includes providing the desired speed to the towbarless airplane tug. Stage **1930** is followed by stage **1940** of determining the actual speed of the towbarless airplane tug in response to the desired speed.

Stage **1940** is followed by stage **1950** of towing an airplane by the towbarless airplane tug in response to the desired speed.

Method **1900** can include applying a cruise control scheme, and additionally or alternatively, determining a desired speed based upon at least one other towbarless airplane tug speed and/or location.

Stage **1920** can include at least one of the following:

- calculating the desired speed of the towbarless airplane tug based upon a location of the towbarless airplane tug and a desired time of arrival of the towbarless airplane tug to an end of towing location; and
- calculating the desired speed of the towbarless airplane tug based upon a location of the towbarless airplane tug, an estimated time of arrival of at least one other towbarless airplane tug to an end of towing point and desired time of arrival of the towbarless airplane tug to the end of towing location.

Method **1900** can also include one or more of the following stages:

- stage **1990** of transmitting speed and location information to at least one other towbarless airplane tug;

- stage **1992** of transmitting speed and location information to a remote command center;
- stage **1993** of receiving from the remote command center speed and location information of at least one other towbarless airplane tug; and
- stage **1994** of detecting a speed and a location of at least one other towbarless airplane tug by utilizing a sensor such as a radar, laser sensor, or the like.

The controller **119** of towbarless airplane tug **100** can participate in the execution of either one of methods **1700** and **1900**.

For example, controller **119** can be configured to perform at least one of the following operations or a combination thereof:

- comparing between an actual speed of a towbarless airplane tug and a desired speed thereof;
- controlling the at least one tug wheel driver to maintain the actual speed of the towbarless airplane tug if the actual speed of a towbarless airplane tug is lower than the desired speed of the towbarless airplane tug, and if the actual speed of the towbarless airplane tug was maintained within a predefined speed range (for example, a narrow predefined range) during a predefined period that preceded the comparing;
- controlling the at least one tug wheel driver to maintain the actual speed of the towbarless airplane tug if the actual speed of a towbarless airplane tug is higher than the desired speed of the towbarless airplane tug, and if at least one of an airplane pilot-controlled braking and deceleration of the airplane is detected;
- controlling the at least one tug wheel driver to change the actual speed of the towbarless airplane tug to match the desired speed of the towbarless airplane tug if an airplane pilot-controlled braking is detected;
- calculating the desired speed of the towbarless airplane tug;
- calculating the desired speed of the towbarless airplane tug based upon a location of the towbarless airplane tug;
- calculating the desired speed of the towbarless airplane tug based upon its location and a location of at least one other towbarless airplane tug;
- calculating the desired speed of the towbarless airplane tug based upon its location and a location and a speed of at least one other towbarless airplane tug that shares at least one path with the towbarless airplane tug;
- calculating the desired speed of the towbarless airplane tug based upon its location and a desired time of arrival of the towbarless airplane tug to an end of towing location; and

- calculating the desired speed of the towbarless airplane tug based upon its location, an estimated time of arrival of another towbarless airplane tug to an end of towing point, and desired time of arrival of the towbarless airplane tug to the end of towing location.

In accordance with another example, controller 119 can be configured to perform at least one of the following operations or a combination thereof:

- receive speed and location information of at least one other towbarless airplane tug that are expected share at least a portion of a towing path with the towbarless airplane tug;
- calculate the desired speed of the towbarless airplane tug based upon its speed and location and the speed and location information;
- calculate the desired speed of the towbarless airplane tug based upon its location and a desired time of arrival of the towbarless airplane tug to an end of towing location; and
- calculate the desired speed of the towbarless airplane tug based upon its location, an estimated time of arrival of at least one other towbarless airplane tug to an end of towing point, and desired time of arrival of the towbarless airplane tug to the end of towing location.

The towbarless airplane tug may include a receiver and a transmitter. Referring to the example set fourth in Fig. 4E, they may be included in or otherwise integrated within controller 119. The transmitter can be arranged to transmit speed and location information to at least one other towbarless airplane tug. The transmitter can transmit speed and location information to a remote command center (such as the control system in the airport tower) and the receiver can receive from the remote command center speed and location information of at least one other towbarless airplane tug.

The towbarless airplane tug may further include a radar, laser sensor, or the like, that is configured to detect a speed and a location of at least one other towbarless airplane tug. The radar, laser sensor, or the like may have a range of few hundred meters and may operate at very high frequencies (40 GHz and above).

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the invention includes both combinations and sub-combinations of various features described hereinabove as well as modifications thereof which would occur to persons skilled in the art upon reading the foregoing description and which are not in the prior art. In addition, those skilled in the art to which this invention pertains will readily appreciate that numerous changes, variations and modifications can be made without departing from the scope of the invention *mutatis mutandis*.

CLAIMS

1. A towbarless airplane tug configured for receiving a landing gear of an airplane and towing it thereby, said tug comprising:

- a chassis configured for receiving thereon at least a portion of said landing gear;
- 5 • a propulsion arrangement configured to move the tug in a direction along a trajectory and comprising a variable angle swash plate hydraulic pump coupled to a variable angle swash plate hydraulic motor and to a controllable bypass path valve, configured such that a hydraulic fluid circulates between the pump and the motor so as to activate said propulsion arrangement to increase at least one of the speed and the traction force
10 of the tug when the bypass path is in a closed state, and at least most of the hydraulic fluid circulates across the motor via the bypass path valve so as to reduce at least one of a rotational speed and traction force of the tug when the bypass path is in an opened state;
- at least one force sensor configured to measure, directly or indirectly, a force exerted
15 by said chassis on said landing gear in at least said direction due to a speed differential between said tug and said airplane; and
- a controller in communication with said force sensor and being configured to alter one or more parameters of movement of the tug such that the force exerted by said chassis on said landing gear is maintained below a predetermined value by regulating at least
20 the power available to the propulsion arrangement, the pump and motor swash-plates, and the state of the bypass path valve.

2. The towbarless airplane tug according to claim 1, further comprising a hydraulic motor cross valve to allow a free flow of hydraulic fluid across the motor, for free tug movement, when the bypass path is closed.

3. The towbarless airplane tug according to any one of claims 1 and 2, wherein the bypass path is associated with a brake period following opening of the bypass path wherein hydraulic fluid is diverted from said swash plate pump, said controller being further configured to control the state of the bypass path, said valve being characterized by a response period that is much smaller than said brake period.

4. The towbarless airplane tug according to any one of the preceding claims, said propulsion driving module further comprising a valve which controls the state of the bypass path, said valve being characterized by a response period that is much smaller than a resonance period of the swash plates of said hydraulic pump and motor.

5. The towbarless airplane tug according to any one of the preceding claims, wherein said
35 controller is configured to regulate displacement of the hydraulic motor.

6. The towbarless airplane tug according to any one of the preceding claims, wherein said controller is configured to regulate a control angle of said swash plate pump.

7. The towbarless airplane tug according to claim 6, wherein said controller is configured to induce fast changes in the control angle of said swash plate pump.

8. The towbarless airplane tug according to any one of claims 6 and 7, wherein said controller is configured to induce slow changes in the control angle of said swash plate pump.

9. The towbarless airplane tug according to any one of claims 6 through 8, wherein said controller is configured to utilize a feed-forward process to regulate the control angle of said swash plate pump.

10. The towbarless airplane tug according to any one of the preceding claims, further comprising energy absorbers arranged to absorb energy between said landing gear and said chassis.

11. The towbarless airplane tug according to any one of the preceding claims, wherein the altering of said one or more parameters of movement causes the tug to reduce at least one of its speed and traction force.

12. The towbarless airplane tug according to any one of the preceding claims, wherein said chassis comprises a support assembly configured for the receiving of said portion of the landing gear and being mounted on said chassis such that it is moveable thereon at least in said direction.

13. The towbarless airplane tug according to claim 12, wherein said force sensor is configured to measure the force exerted by said support assembly on said chassis in at least said direction.

14. The towbarless airplane tug according to any one of the preceding claims, wherein said parameters of movement are selected from a group comprising speed, direction, acceleration, and deceleration.

15. The towbarless airplane tug according to any one of the preceding claims, wherein said controller is configured to calculate a resultant force exerted by said chassis on said landing gear at least based on one or more external factors.

16. The towbarless airplane tug according to claim 15, wherein said external factors are selected from a group comprising:

- data relating to slopes at various locations along an airplane travel surface to be traversed by said tug;
- data relating to wind forces affecting said airplane and tug;
- data relating to rolling friction forces of said airplane and or tug at various locations along said airplane travel surface; and
- data relating to obstacles.

17. The towbarless airplane tug according to claim 16, wherein said data relating to slopes is provided by an inclination sensing functionality.

18. The towbarless airplane tug according to any one of claims 16 and 17, wherein said data relating to slopes is predetermined and stored as slope data in a database, said controller being further configured to determine the position of the tug on said airplane travel surface and to relate said slope data to said position.

19. The towbarless airplane tug according to claim 16, wherein said data relating to rolling friction forces is predetermined and stored as friction data in a database, said controller being further configured to determine the position of the tug on said airplane travel surface and to relate said friction data to said position.

20. The towbarless airplane tug according to claim 16, wherein said tug is configured to detect obstacles along the airplane path.

21. The towbarless airplane tug according to any one of the preceding claims, wherein said controller is configured to communicate wirelessly with a remote command center.

22. The towbarless airplane tug according to Claim 21, wherein said controller is configured to communicate wirelessly with said remote command center via an electronic flight bag.

23. The towbarless airplane tug according to any one of the preceding claims, further comprising an electronic flight bag configured to communicate wirelessly with a similar device within the airplane.

24. A method for towing an airplane, the method comprising providing a towbarless airplane tug comprising:

- a chassis configured for receiving thereon at least a portion of a landing gear of said airplane; and
- a propulsion arrangement configured to move the tug in a direction along a trajectory and comprising a variable angle swash plate hydraulic pump coupled to a variable angle swash plate hydraulic motor and to a controllable bypass path valve, configured such that a hydraulic fluid circulates between the pump and the motor so as to activate said propulsion arrangement to increase at least one of the speed and the traction force of the tug when the bypass path is in a closed state, and at least most of the hydraulic fluid circulates across the motor via the bypass path valve so as to reduce at least one of a rotational speed and traction force of the tug when the bypass path is in a opened state;

the method further comprising causing said tug to tow said airplane while altering one or more parameters of movement of the tug such that a force exerted by said chassis on said landing gear

is maintained below a predetermined value by regulating at least the power available to the propulsion arrangement, the pump and motor swash-plates, and the state of the bypass path valve.

25. The method according to claim 24, wherein said tug is in accordance with any one of claims 1 through 24.

26. A towbarless airplane tug configured for receiving a landing gear of an airplane and towing it thereby, said tug comprising:

- a chassis configured for receiving thereon at least a portion of said landing gear;
- a propulsion arrangement configured to move the tug in a direction along a trajectory;
- and
- a controller configured to compare between an actual speed of a towbarless airplane tug and a predetermined desired speed thereof, and to direct said propulsion arrangement to maintain the actual speed of the towbarless airplane tug if:
 - the actual speed is lower than the desired speed; and
 - the actual speed was maintained within a predefined speed range during a predefined period that preceded the comparing.

27. The towbarless airplane tug according to claim 26 wherein the controller is further configured to detect airplane pilot-controlled braking and deceleration of the airplane, and is further configured to direct said propulsion arrangement to maintain the actual speed if:

- the actual speed is higher than the desired speed; and
- at least one of an airplane pilot-controlled braking and deceleration of said airplane is detected.

28. The towbarless airplane tug according to claim 27, wherein the controller is further configured to direct said propulsion arrangement to change the actual speed of the towbarless airplane tug to match the desired speed if an airplane pilot-controlled braking is detected.

29. The towbarless airplane tug according to any one of claims 26 through 28, being further configured to apply a positive traction force at all times during a towing of the airplane.

30. The towbarless airplane tug according to any one of claims 26 through 29, being further configured to protect in real time the landing gear from exceeding its maximum allowed fatigue load.

31. The towbarless airplane tug according to any one of claims 26 through 29, wherein the controller is further configured to calculate the desired speed.

32. The towbarless airplane tug according to any one of claims 26 through 30, wherein the controller is further configured to calculate a desired traction force corresponding to the desired speed.

33. The towbarless airplane tug according to any one of claims 26 through 32, wherein the controller is further configured to calculate the desired speed at least based upon a location of the tug.

34. The towbarless airplane tug according to any one of claims 26 through 33, wherein the controller is further configured to calculate the desired speed at least based upon a location of the tug and a location of at least one other tug.

35. The towbarless airplane tug according to any one of claims 26 through 34, wherein the controller is further configured to calculate the desired speed at least based upon a location of the tug and a location and a speed of at least one other tug that shares at least one path therewith.

36. The towbarless airplane tug according to any one of claims 26 through 35, wherein the controller is further configured to calculate the desired speed at least based upon a location of the tug and a desired time of arrival thereof at an end of towing location.

37. The towbarless airplane tug according to any one of claims 26 through 36, wherein the controller is further configured to calculate the desired speed at least based upon a location of the tug, an estimated time of arrival of another tug at an end of towing point, and a desired time of arrival of the tug at the end of towing location.

38. The towbarless airplane tug according to any one of claims 26 through 37, further comprising a transmitter configured to transmit information relating to speed and location of the tug.

39. The towbarless airplane tug according to claim 38, further comprising a receiver configured to receive information relating to speed and location of at least one other tug from a remote command center.

40. The towbarless airplane tug according to any one of claims 26 through 39, further comprising a detector configured to detect a speed and a location of at least one other tug by utilizing a sensor; said controller being configured to calculate the desired speed at least based upon the speed and location of said other tug.

41. The towbarless airplane tug according to claim 40, said controller being further configured to calculate the desired speed based upon a desired time of arrival at an end of towing location and an estimated time of arrival of said other tug at an end of towing point.

42. A method for controlling a towbarless airplane tug, the method comprising:

- obtaining information relating to speed and location of at least one other tug that is expected to share at least a portion of a towing path with the tug; and
- calculating the desired speed of the tug at least based upon the speed and location thereof and said information.

43. The method according to claim 42, further comprising calculating the desired speed based upon desired time of arrival of the tug at an end of towing location.

44. The method according to any one of claims 42 and 43, further comprising calculating the desired speed of the towbarless airplane tug based upon an estimated time of arrival of said one other tug at an end of towing point.

45. The method according to any one of claims 42 through 44, further comprising transmitting information relating to speed and location of the tug to said other tug.

46. The method according to any one of claims 42 through 45, further comprising transmitting information relating to speed and location of the tug to a remote command center and receiving therefrom information relating to speed and location information of said other tug.

47. The method according to any one of claims 42 through 46, wherein said tug obtains said information relating to speed and location of at least one other tug utilizing a sensor.

48. A towbarless airplane tug configured for receiving a landing gear of an airplane and towing it thereby, said tug comprising:

- a chassis configured for receiving thereon at least a portion of said landing gear;
- a propulsion arrangement configured to move the tug in a direction along a trajectory;
- a controller configured to operate according to the method of any one of claims 42 through 47.