

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A47L 9/16		A1	(11) International Publication Number: WO 96/21389
			(43) International Publication Date: 18 July 1996 (18.07.96)
(21) International Application Number: PCT/GB96/00022			(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 8 January 1996 (08.01.96)			
(30) Priority Data: 9500424.8 10 January 1995 (10.01.95) GB			
(71) Applicant (for all designated States except US): NOTETRY LIMITED [GB/GB]; Sycamore House, Bathford, Bath BA1 7RS (GB).			
(72) Inventor; and (75) Inventor/Applicant (for US only): DYSON, James [GB/GB]; Sycamore House, Bathford, Bath BA1 7RS (GB).			
(74) Agent: SMITH, Gillian, Ruth; Marks & Clerk, 57-60 Lincoln's Inn Fields, London WC2A 3LS (GB).			

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: **DUST SEPARATION APPARATUS**

(57) Abstract

The invention provides dust separating apparatus (10) comprising a cyclone (14) having an outer wall (14a) and an air inlet (12), a shroud (16) and an airflow path, the airflow path being arranged so as to direct an airflow flowing, in use, in the dust separating apparatus into the cyclone (14) via the air inlet (12) and out of the cyclone through the shroud (16). The air inlet (12) of the cyclone (14) is formed by a conduit (12a) projecting into the cyclone (14) between the outer wall (14a) and the shroud (16). This allows a swivel coupling to be attached to the air inlet (12) providing greater flexibility and maneuverability of the dust separating apparatus (10).

