

MECHANICAL LOCKING OF FLOOR PANELSArea of Invention

The invention generally relates to the field of floor panels with mechanical locking systems comprising a separate flexible tongue allowing easy installation. The invention provides new improved locking systems and installation methods for building panels, especially floor panels.

Background of the Invention

In particular, yet not restrictive manner, the invention concerns a mechanical locking system for rectangular floor panels with long and short edges. It should be emphasized that long and short edges are only used to simplify the description. The panels could also be square, they could have more than 4 edges and the adjacent edges could have angles other than 90 degrees. However, the invention is as well applicable to building panels in general. More particularly the invention relates to the type of mechanically locking systems which allow that all four edges of a panel could be locked to other panels by a single angling action comprising a flexible and/or displaceable and/or rotating tongue in order to facilitate the installation of building panels.

A floor panel of this type is presented in WO2006/043893, which discloses a floor panel with a locking system comprising a locking element cooperating with a locking groove, for horizontal locking, and a flexible tongue cooperating with a tongue groove, for locking in a vertical direction. The flexible tongue bends in the

horizontal plane during connection of the floor panels and makes it possible to install the panels by vertical folding or solely by vertical movement. By "vertical folding" is meant a connection of three panels where a first and second panel are in a connected state and where a single angling action of a new panel, referred to as the "folding panel", connects two perpendicular edges of the new panel, at the same time, to the first and second panel. Such a connection takes place for example when a long edge of the first panel in a first row is already connected to a long edge of a second panel in a second row. The new folding panel is then connected by angling to the long edge of the first panel in the first row. This specific type of angling action, which also connects the short edge of the new folding panel and second panel, is referred to as "vertical folding". The short edges are generally connected horizontally with a strip comprising a locking element on a "strip panel" and a locking groove on the lower part of the folding panel cooperating with the locking element of the strip panel. It is also possible to connect two panels by lowering a whole panel solely by a vertical movement against another panel. This specific type of locking is referred to as "vertical locking"

Similar floor panels are further described in WO2003/016654, which discloses locking system comprising a tongue with a flexible tab. The tongue is extending and bending essentially in a vertical direction and the tip of the tab cooperates with a tongue groove for vertical locking.

Vertical locking and vertical folding of this type creates a separation pressure at the short edges when the

flexible tongue or flexible parts of the tongue are displaced horizontally in a double action during the angling of the long edges. Parts of the tongue are displaced inwardly during the initial part of the locking
5 and they are thereafter displaced towards the initial position during the final part of the locking action. The inventor has analysed several types of floor panels and discovered that there is a considerable risk that the short edges could be pushed away from each other during
10 installation and that a gap could occur between the edge portions of the short edges. Such a gap could prevent further installation and the floor panels will not be possible to connect. It could also cause serious damage to the locking system at the short edges. Pushing the
15 floorboards sideways towards the short edges during installation could prevent the gap. Such an installation method is however complicated and difficult to use since three actions have to be combined and used simultaneously in connection with angling down of the long edges as
20 described below.

- a) The edges of a new floor panel has to be brought in contact with a first floor panel laying on the floor and the long edge of the new panel has to be pressed forward in angled position towards the first panel
- 25 b) The new panel has to be displaced sideways, in the pressed and angled up position, and pressed sideways against a short edge of a second panel laying on the floor in order to counteract the counter pressure of the tongue

c) The new panel must finally be angled down to the floor and the forward and sideways pressure must be maintained during the angling action.

The inventor has discovered that separation and
5 installation problems often occur when the panels have a small thickness and small compact locking systems on the long edges or when the panel core is made of a material with smooth surfaces such as high density fibreboard (HDF). Such problems could also occur when the panels are
10 short or in connection with the installation of the first or last panel in each row since such installation is generally made with panels which are cut to a smaller length in order to adapt the floor to the wall position. Separation problems are of course extremely difficult to
15 handle in any type of panels using locking systems with a strong flexible tongue that creates a substantial horizontal separation pressure during the vertical folding. Such strong tongues are very important in many applications where a high quality vertical connection is
20 required and panels with such flexible tongues are very difficult to install with the known installation methods.

The invention aims to solve separation problems in floorings, which are intended to be installed with vertical folding or vertical locking or just angling of
25 long edges.

Vertical folding according to known technology locks the panels vertically when they are angled down. The panels are possible to unlock. This could be done with special tools, which are inserted into the locking system. It is
30 also possible to angle up a whole row and to disconnect

panels from each other. It would be an advantage if individual panels could be locked and unlocked in an easier way, preferably with a simple reverse angling action. Damaged panels or incorrectly installed panels
5 could be adjusted, exchanged or reinstalled.

Another objective of the invention is therefore to provide solutions to this problem with a new locking system that after the vertical folding is not connected vertically and that could be released with a simple
10 angling in the reverse direction.

Vertical folding according to known technology requires that some parts of the locking system are bended, compressed or displaced when the panels are angled down. This creates a resistance, which is a disadvantage during
15 installation. A third objective of the invention is to provide solutions that avoids such resistance as much as possible and where preferably all types of resistance caused by the vertical locking parts during the vertical folding are reduced considerably or completely eliminated.

20 Different types of floorboards require different locking solutions. A locking system adapted to lock thin laminate floorings of 5-8 mm with a core of HDF is not always possible to use to lock for example thick wood floorings with a thickness of 14 - 25 mm and with a core of various
25 types of wood species and qualities. A fourth objective is to provide solutions suitable for a wide range of different floor types and different sizes of the same floor type.

Definition of Some Terms

In the following text, the visible surface of the installed floor panel is called "front face", while the opposite side of the floor panel, facing the sub floor, is called "rear face". The edge between the front and rear face is called "joint edge". If not defined otherwise upper and lower means towards the front face and towards the rear face. Inner and outer means towards or away from the centre of the panel. By "horizontal plane" is meant a plane, which extends parallel to the outer part of the surface layer. Immediately juxtaposed upper parts of two adjacent joint edges of two joined floor panels together define a "vertical plane" perpendicular to the horizontal plane. By "horizontally" is meant parallel with the horizontal plane and by "Vertically" parallel to the vertical plane.

By "joint" or "locking system" are meant co acting connecting means, which connect the floor panels vertically and/or horizontally. By "mechanical locking system" is meant that joining can take place without glue. Mechanical locking systems can in many cases also be combined with gluing. By "integrated with" means formed in one piece with the panel or factory connected to the panel. By "separate" parts, components element and similar is meant that they are produced separately and not in one piece with the core or the main body of the panel. Separate parts are generally factory connected and integrated with the panel but they could be supplied as lose parts, which are intended to be used during installation of panels.

By a "flexible tongue" is meant a separate tongue which has at least some flexible parts and which has a length direction along the joint edges and which is forming a part of the vertical locking system. The whole tongue
5 could for example be bendable or it could have flexible and resilient parts that can be bent and/or compressed and that could at least partly spring back to or towards its initial position. The flexibility causes the tongue to be displaced at least partly horizontally during locking..
10 Flexible tongue is used in this document broadly since most of the shown embodiments have at least some flexible parts. The invention does not exclude a flexible tongue, which essentially or partly is made of a rigid material.

By a "displaceable tongue" is meant any type of a tongue
15 which connects adjacent edges vertically and which is made of a separate material and connected to a floor panel and which is wholly or partly displaceable between an unlocked position and a locked position. A displaceable tongue could be flexible or rigid

20 By "tongue" is meant any part in an edge section that prevents a vertical displacement.

By "angling" is meant a connection that occurs by a turning motion, during which an angular change occurs between two parts that are being connected, or
25 disconnected. When angling relates to connection of two floor panels, the angular motion takes place with the upper parts of joint edges at least partly being in contact with each other, during at least part of the motion.

By an "angling locking system" is meant a mechanical locking system which could be connected vertically and horizontally with angling comprising a tongue and a groove that locks two adjacent edges in a vertical direction and
5 a locking strip with a locking element in one edge of a panel called "strip panel" that cooperates with a locking groove on another edge of a panel called "groove panel" and locks the edges in a horizontal direction. The locking element and the locking groove have generally rounded
10 guiding surfaces that guide the locking element into the locking groove and locking surfaces that locks and prevents horizontal separation between the edges.

Vertical folding is not a pure combination of for example an angling locking system on a long edges and a vertical
15 locking system on short edges since the vertical and the angling actions are combined and the short edges are folded together in the same way as scissors. The locking takes place gradually from one edge section adjacent to one long edge, which is angled, to the other edge section
20 adjacent to the other opposite long edge. Such locking of two adjacent edges is defined as a "folding lock"

"Vertical folding" is a locking of three panels where combinations of angling on long edges and folding on short edges is used. By "vertical folding along the vertical
25 plane" is meant a vertical folding with the upper edges of two short edges essentially in contact during the essentially the whole folding action until the edges are locked together.

Summary of the Invention

The present invention aims at a set of building panels, especially floor panels or a floating flooring with a mechanical locking system comprising a separate displaceable tongue on the short edge which is configured
5 to improve installation and disconnection of floor panel installed with vertical folding or angling and which will counteract or prevent separation of the short edges during installation.

The invention is based on a first basic understanding
10 that such separation problems are related to the separate displaceable tongue in a folding lock, which has to be pressed inwardly into the displacement groove in order to snap back horizontally towards the tongue groove during the vertical folding. The objective of the invention is to
15 provide a locking system that could be locked with vertical motion or angling of an adjacent edge and where the separation force of the displaceable tongue during vertical motion or angling is reduced considerably or preferably eliminated due to the fact that the inwardly
20 directed displacement of the displaceable tongue into the displacement groove during installation is reduced considerably or completely eliminated.

The invention provides for new embodiments of locking systems at short edges according to different aspects
25 offering respective advantages. Useful areas for the invention are wall panels, ceilings, exterior applications and floor panels of any shape and material e.g. laminate; especially panels with surface materials contain thermosetting resins, wood, HDF, veneer or stone.

The invention comprises according to a first basic principle a set of floor panels comprising a locking system with a displaceable tongue integrated with an edge of a floor panel for connecting the edge vertically to an adjacent edge of a similar panel. The displaceable tongue is configured to be displaced essentially horizontally and essentially in one direction only from the initial position to a final outer locked position into a tongue groove.

- 10 The invention comprises according to a first embodiment a set of essentially identical floor panels provided with first and second connectors, the connectors are integrated with the floor panels and configured to connect adjacent edges. The first connector comprises a locking strip with an upwardly directed locking element at an edge of one floor panel and a downwardly open locking groove at an adjacent edge of another floor panel for connecting the adjacent edges in a horizontal direction perpendicular to the adjacent edges, the second connector comprises a displaceable tongue at an edge of one floor panel, and a horizontally open tongue groove in an adjacent edge of another floor panel for connecting the adjacent edges in vertical direction, the connectors are configured to be locked with angling or a vertical motion. A locking part of the displaceable tongue is arranged in an inner initial position in a displacement groove at an edge of a panel. The locking part is configured to be displaced essentially horizontally and essentially in one direction only from the initial position to a final outer locked position into the tongue groove.

One essential difference against known technology is that at least a part of a tongue is displaced essentially in one direction only from the initial unlocked position, where it has been factory connected to an edge, and to the
5 locked position where it locks the edges vertically. The locking is a "single snap action" or a "single displacement action" Known flexible and displaceable tongues are first displaced inwardly into the displacement groove and then outwardly into the tongue groove. These
10 two displacements are generally of the same magnitude. In several cases the first displacement is even larger than the second displacement, for example when the locking is made with pre tension against a part of the tongue groove. Such a locking is a "double action snap". The major
15 advantage of a single snap action or a single displacement action is that locking could be accomplished without any separation forces that will push for example the short edges apart during locking and installation.

The expression "essentially in one direction only" means
20 that some double action embodiments are covered by the invention and are not excluded preferably in such cases where a first displacement into the displacement groove is essentially smaller than the second displacement into the tongue groove. The first displacement could for example be
25 used to release the displaceable tongue from its inner unlocked position or just to accomplish a part of a displacement to an unlocked or partly locked position.

According to a first aspect of the first principle the invention provides a set of floor panels comprising a
30 locking system with a separate flexible tongue integrated with an edge of a floor panel for connecting the edge

vertically to an adjacent edge of a similar panel. A part of the tongue is configured to be displaced essentially horizontally and essentially in one direction only from an initial position to a final outer locked position. The
5 tongue is configured to be twisted along the joint during locking.

According to an embodiment of the first principle, the invention provides for a flexible tongue having a knee joint with a pressing extension extending essentially
10 horizontally from the knee joint and a locking extension extending essentially vertically from the knee joint upwards. The locking extension has a locking part at an upper part above the knee joint. The locking part locks in the tongue groove when for example an adjacent short edge
15 of the first and second panels is pressed vertically against the pressing extension until the short edges are positioned in an essentially the same plane.

The vertical pressing against the pressing extension is preferably caused by vertical folding.

20 According to a second aspect of the first principle A set of floor panels are provided comprising a locking system with a separate flexible tongue integrated with an edge of a floor panel for connecting the edge vertically to an adjacent edge of a similar panel. The flexible tongue
25 comprises parts under pre tension.

According to an embodiment of the second aspect floor panels are provided with for example short edges having a locking system with a separate flexible tongue that locks with a single action. A vertical movement of one short
30 edge causes a part of a displaceable tongue to snap

essentially in one direction from an inner initial
unlocked position, where the displaceable tongue is
connected to a displacement groove with pre tension, to an
outer vertically locked position. The release of the pre
5 tension is preferably caused by vertical folding.

According to a third aspect of the first principle, A set
of floorpanels are provided comprising a locking system
with a separate tongue integrated with an edge of a
floorpanel for connecting the edge vertically to an
10 adjacent edge of a similar panel. At least a part of the
tongue is displaceable and the locking is accomplished by
a sideways pressure applied at an edge section of the
tongue and essentially along the edge.

According to one embodiment of this third aspect the
15 invention comprises a displaceable tongue, which is
displaced in a displacement groove. The invention is
characterized in that the displacement of the displaceable
tongue from an initial unlocked position, where it is
factory connected, and into a tongue groove is caused by
20 for example a long edge of a third panel which is angled
and connected to the first and second panels when they are
located in essentially the same plane and with their short
edges in contact.

This third aspect allows that the panels are unlocked
25 vertically until a third panel in a consecutive row is
connected. Vertical folding and disconnection with angling
down and up again could be made in a simple way since
there is no tongue that creates any resistance and that
locks vertically. The vertical locking is initiated first
30 when a new row of panels are installed. This is a major

advantage against all known fold down systems that have a vertical locking. Locking systems according to this principle could be made with a displaceable tongue, on for example the short edge of a panel, that returns to the
5 initial unlocked position when a long edge of a panel in an adjacent row is released with for example angling up. This allows that the whole floor could be disconnected with a simple angling action of individual panels. It is not necessary, as with the known technology, to disconnect
10 the whole row with angling in order to disconnect a floor. Alternatively the locking system can be configured so that the bendable stays in its outer position, due to friction between the tongue and the panels or by permanent deformation of the tongue, even if the third panel is
15 removed.

All these three basic embodiments where the displacement is caused by:

- a) pressing on a pressing extension,
- b) releasing a pre tension,
- 20 c) and displacing a tongue on the short edge with the long edge,

are based on the major principle that the displacement is essentially in one direction only and that such a displacement could be made with only very limited or non
25 existent separation forces.

The above-mentioned aspects have been described with panels having long and short edges. The panels could have more than four edges and they could be square.

According to a second principle, the invention provides a method to install and disconnect floor panels with an angling locking system on for example long edges and a displaceable tongue on the short edges. The method
5 comprises the step of:

1. Connecting the long edges of a second and a new panel in a second row to a long edge of a first panel in a first row such that the short edges of the second and new panel in the second row are in contact and in essentially the
10 same plane.

2. Connecting a third panel in a third row with angling to the long edges of the second and new panels whereby a displaceable tongue on the short edge of the second or new panel is displaced into a tongue groove such that the
15 short edges are locked vertically and horizontally.

According to this second principle, the invention provides a method to disconnect floor panels with an angling locking system on for example long edges and a displaceable tongue on the short edges, which connect
20 floor panels vertically. The method comprises the step of:

1. Disconnecting the long edges of a third panel in a third row from a long edge of a second and new panel in a second row and disconnecting a displaceable tongue and the vertical locking between a new panel and a second panel in
25 a second row with angling up of the third panel away from the sub floor.

2. Disconnecting the new panel from the long edges of a first panel in a first row and from the short edges of the second panel with angling up.

According to a third principle, the invention provides panels and locking systems with a horizontal flexible or displaceable locking element which allows the panels to be connected with a horizontal displacement towards each other in an essentially common plane according to the same basic principles as used for the vertical folding as described in this document. The locking element is displaced vertically and locks in a horizontal direction into a locking groove located in an upper or lower part of an upper or lower lip. The locking in the vertical direction is preferably accomplished with a tongue and a groove. This third principle is only schematically described in this document since all embodiments and principles which are used for the vertical locking could be used for the horizontal locking. It is obvious that parts cooperating horizontally should be adjusted to vertically etc.

A second aim of the invention is to provide new and improved embodiments of separate flexible tongues that could be used in all types of locking systems where a displacement of at least a part of a tongue is required in order to accomplish a vertical or horizontal locking of panels. The aim is to improve the locking function and the locking strength compared to known technology.

The invention provides a flexible tongue having a length direction. At least one of the edges extending in the length direction is rigid. The flexible tongue has in the length direction one or several flexible cavities which could be compressed and spring back towards the initial position

The invention is useful in all types of floorings and especially in floorings where it is difficult to prevent separation by for example friction between long edges or where known tongues create high separation forces. The invention is therefore especially suitable for short panels for example 40 - 120 cm where the friction along the long edges is low, for wide panels with a width of more than 20 cm since known flexible tongues are long and will create an extensive tongue pressure, and for panels with for example a core of HDF, compact laminate or plastic materials and similar where the friction is low due to very smooth and low friction surfaces in the locking system. The invention is also useful in thin panels, for example with a thickness of 6-9 mm, and especially is such panels with compact locking systems on long edges, for example with locking strips shorter than 6 mm, since such floor panels and such locking system will have small contact surface with low friction.

Several advantages could be reached with a flooring system configured according to one or several of the principles described above. A first advantage consists in that installation could be made in a simple way and no sideway pressure has to be applied during installation in order to prevent floorboards to separate at the short edges. A second advantage is that the risk of edge separation, which could cause cracks in the locking system during folding, is reduced considerably. A third advantage is that locking systems could be formed with more rigid and stronger tongues that could lock the panels vertically with higher strength. A fourth advantage is that locking

and unlocking could be made easier and with a more reliable locking function.

A tongue could comprise of plastic material and could be produced with for example injection moulding. With this
5 production method a wide variety of complex three-dimensional shapes could be produced at low cost and the flexible tongues may easily be connected to each other to form tongue blanks. A tongue could also be made of an extruded or machined plastic or metal section, which could
10 be further shaped with for example punching to form a flexible tongue. The drawback with extrusion, besides the additional productions steps, is that it is difficult but not impossible to reinforce the tongue, e.g. by fibres. Extruded plastic section could however be a preferred
15 alternative when the tongue has a cross section, which is essentially of a rectangular shape. Wood based material such as for example HDF or compact laminate or sheet shaped plastic material could also be used to form a flexible or displaceable tongue.

20 Any type of polymer materials could be used such as PA (nylon), POM, PC, PP, PET or PE or similar having the properties described above in the different embodiments. These plastic materials could, when for example injection moulding is used, be reinforced with for instance glass
25 fibre, Kevlar fibre, carbon fibre or talk or chalk. A preferred material is glass fibre, preferably extra long, reinforced PP or POM.

The short edges could be disconnected with a needle shaped tool, which could be inserted from the corner
30 section into the tongue groove and press the flexible

tongue back into the displacement groove. One panel could
 than be angled up while the other panel is still on the
 sub floor. Of course the panels could also be disconnected
 in the traditional way by angling up or displacement along
 5 the joint

All references to "a/an/the [element, device, component,
 means, step, etc]" are to be interpreted openly as
 referring to at least one instance of said element,
 device, component, means, step, etc., unless explicitly
 10 stated otherwise.

Almost all embodiments are described with separate
 tongues on the strip panel mainly in order to simplify the
 description. The separate tongue could be located in the
 edge of the folding panel.

15 Brief Description of the Drawings

- | | |
|-----------|--|
| Figs 1a-d | illustrate a prior art locking system |
| Figs 2a-b | show a prior art flexible tongue during
the locking action. |
| Figs 3a-b | show a floor panels with a prior art
mechanical locking system on a short
edge. |
| Figs 4 | show how short edges of two floor panels
could be locked with vertical folding
according to prior art. |
| Figs 5a-d | show embodiments of short edge locking
systems which create a separation force
during locking. |

	Fig 6 a-d	shows an embodiment according to the first aspect of the invention.
5	Fig 7a-c	shows in a 3D embodiments of the flexible tongue according to the first aspect of the invention
	Fig 8a-d	show an embodiment of the second aspect of the invention.
10	Fig 9a-b	show a displaceable tongue according to an embodiment of the second aspect of the invention
	Fig 9c-g	show embodiments according to the third aspect of the invention.
	Fig 10a-d	show embodiments according to the third aspect of the invention.
15	Fig 11a-d	show embodiments according to the first and second aspect of the invention
20	Fig 11e-g	show examples of how the basic principles of the invention could be used to connect panels with horizontal snapping
	Fig 12a-d	show an edge section of an embodiment of the invention
25	Fig 13a-f	show installation of panels having a flexible tongue according to one preferred embodiment
	Fig 14a-h	show embodiments of a flexible tongue

	Fig 15a-f	show embodiments of a flexible tongue and a tool to create a sideways pressure.
	Fig 16a-e	show examples of how a tongue is connected and produced.
5	Fig 17a-j	show embodiments of a displaceable tongue.
	Fig 18a-i	show embodiments of flexible and displaceable tongues.
	Fig 19a-e	show embodiments of a flexible tongue.
10	Fig 20a-c	show embodiments of flexible tongues.
	Fig 21a-d	show embodiments of flexible and displaceable tongues.
	Fig 22a,b	show installation of a last row.
15	Fig 23a-c	show embodiments of a displaceable tongue.
	Fig 24a-d	show installation of panels according to the bending principle with a flexible tongue.
20	Fig 25a-b	show a flexible tongue with a rigid part.
	Fig 26a-c	show a flexible tongue which prevents with means that prevent displacement along to edge.

Description of Embodiments of the Invention

Figures 1 - 4 and the related description below describe published embodiments and are used to explain the major principles of the invention. The showed embodiments are only examples.

A prior art floor panel 1, 1' provided with a mechanical locking system and a flexible tongue 30 is described with reference to Figs 1a-1d.

10 Figure 1a illustrates schematically a cross-section of a joint between a short edge joint edge 4a of a panel 1 and an opposite short edge joint edge 4b of a second panel 1'.

The front faces of the panels are essentially positioned in a common horizontal plane HP, and the upper parts 21, 41 of the joint edges 4a, 4b abut against each other in a vertical plane VP. The mechanical locking system provides locking of the panels relative to each other in the vertical direction D1 as well as the horizontal direction D2.

20 To provide joining of the two joint edges in the D1 and D2 directions, the edges of the floor panel have in a manner known per se a locking strip 6 with a locking element 8 in one joint edge, hereafter referred to as the "strip panel" which cooperates with a locking groove 14 in the other joint edge, hereafter referred to as the "fold panel", and provides the horizontal locking.

The prior art mechanical locking system comprises a separate flexible tongue 30 fixed into a displacement groove 40 formed in one of the joint edges. The flexible

tongue 30 has a groove portion P1, which is located in the displacement groove 40 and a projecting portion P2 projecting outside the displacement groove 40. The projecting portion P2 of the flexible tongue 30 in one of the joint edges cooperates with a tongue groove 20 formed in the other joint edge.

Figure 3a shows a cross section A-A of a panel according to figure 3b seen from above. The flexible tongue 30 has on one of the edge sections a friction connection 36 which could be shaped for instance as a local small vertical protrusion. This friction connection keeps the flexible tongue in the displacement groove 40 during installation, or during production, packaging and transport, if the flexible tongue is integrated with the floor panel at the factory.

Figure 2a and 2b shows the position of the flexible tongue 30 after the first displacement towards the bottom of the displacement groove 40. The displacement is caused essentially by bending of the flexible tongue 30 in its length direction by the folding panel and such bending creates separation forces that could cause the long edges to slide and the short edges to separate during folding.

Figure 4 shows one embodiment of a vertical folding. A first panel 1'' in a first row R1 is connected to a second panel 1' in a second row R2. A new panel 1' is moved with its long edge 5a towards the long edge 5b of first panel 1'' at a normal installation angle of about 25-30 degrees, pressed to the adjacent edge and connected with its long edge 5a to the long edge 5b of the first panel with angling. This angling action also connects the short edge

4b of the new pane 1' with the short edge 4a of the second panel 1. The fold panel 1' is locked to the strip panel 1 with a combined vertical and turning motion along the vertical plane VP and with a contact between the top edges
 5 of the second panel 1 and the new panel 1'.

Figures 5a - 5c shows known examples of flexible tongues 30, which could be used to lock short edges according to known technology. Figure 5a shows a separate tongue 30 on the strip panel with a flexible snap tab extending
 10 downwards. Figure 5c shows a separate tongue with a flexible snap tab inside a displacement groove 40. The snap tab could extend upwards or downwards and could be on the strip panel or on the folding panel. Figure 5 c shows a flexible tongue 30 comprising protrusions 60, as shown
 15 in figure 5d and these protrusions could be located in the displacement groove 40 or extend from the vertical plane into the tongue groove 20. All these embodiments will create a separation pressure P when the flexible parts of the tongue are pressed inwardly towards the bottom of te
 20 displacement groove and this could cause the short edges to separate such that the locking system will be damaged or such that the panels will not be possible to install.

Figure 6a-d shows embodiments of panels with a locking system according to the first aspect of the invention. The
 25 strip panel 1 has a locking strip 6 with a locking element 8 and a flexible tongue 30, which is connected to a displacement groove 40. The flexible tongue 30 has a knee joint 15 with a lower pressing extension 17 extending essentially horizontally outwards from the vertical plane
 30 VP, comprising a press locking element 18. The knee joint has also a locking extension 16 extending essentially

vertically with a locking part 19 in the upper part of the locking extension 16. The folding panel 1' has a locking groove 14 which cooperates with the locking element 8 and locks the panels horizontally and a press locking groove 10 which cooperates with the press locking element 18 and prevents horizontal displacement between the folding panel 1' and the displaceable locking element 31. The folding panel 1' has also a tong groove which cooperates with the locking part 19 and locks the panels 1, 1' vertically.

The pressing extension 17 will be bended downwards with the press locking element 18 locked to the press locking groove 11 when the folding panel 1' is moved vertically downwards towards the strip panel 1 essentially along the vertical plane VP as shown in figures 6b and c. The locking part 19 will finally snap into the tongue groove 20 when the upper parts of the joint edges 21, 41 are essentially in the same horizontal plane and the panels 1, 1' will be locked vertically D1 and horizontally D2 without any horizontal pressure that could displace the edges away from each other during the vertical folding. The bending of the pressing extension 17 and the flexibility of the flexible tongue 30 allowing the pressing extension and the locking part to separate at least slightly from each other during locking is an essential feature that allows a high quality locking with the upper edges locked in a common plane. The locking system according to the invention is a vertical snap system. The tongue will during the vertical folding twist in the length direction. The edge which is close to the long side which is connected with angling (4b1 in figure 4) will during the vertical folding obtain a position as shown in figure 6c while the other edge (4b2 in figure 4)

will be in a position as shown in figure 6a. The bending of the pressing extension 17 will vary along the length of the tongue 31. Even a small bending of some 0,1 mm could improve the locking function and quality considerable and
5 allows that gaps or vertical play is reduced considerably or preferably excluded.

Figures 7a-c show flexible tongues. Figure 7a show a flexible tongue 30, which could for example be made by extrusion. Figure 7 b show an embodiment, which could be
10 produced by a combination of extrusion and mechanical forming such as punching or cutting. Parts of the lower extension 22 could be removed in order to increase flexibility and twisting of the lower extension. This means that the length LP of the pressing extension will
15 vary along the flexible tongue 30. Figure 7c shows another embodiment, which is made by injection moulding. The locking extension and the pressing extension have apertures 24, 23 or alternatively thinner sections which facilitates flexibility since twisting in the length
20 direction of the displaceable tongue could be used to make parts more bendable with maintained locking strength. This means that the thickness of the locking part TL, and/or the locking extension TE and/or the pressing extension TP could vary along the flexible tongue 30.

25 Several alternatives are possible within the main principle of the invention. The press locking element 18 could also have a downwardly extending protrusion 18' such that it could lock into a locking groove 14' located on the upper part of the strip 6, similar to the embodiment
30 shown in figure 11a and 11f. A horizontal locking could be accomplished without the use of a large locking element 8

and this could give lower costs due to less material waste and possibilities to use the invention in very thin floorings for example thinner than 7 mm. The pressing extension 17 could have various lengths and it could cover
5 a part or even the whole locking element 8 as shown by the dotted lines in figure 6d.

Figure 8a-d show an embodiment according to the second aspect of the invention. The flexible tongue 30 has an inner unlocked position and an outer locked position. The
10 flexible tongue 30 is in its unlocked position fixed into the displacement groove with pre tension caused for example by an flexible tongue part 51 that presses the flexible tongue 30 upwards. A horizontal tongue lock 52 on the flexible tongue 30 cooperates with a horizontal groove
15 lock 53 in the displacement groove 40 and prevents the flexible tongue 30 to snap out towards its final locked position. The groove lock could be formed with various angles. A scraping tool could for example be used to form surfaces with high locking angles. The flexible tongue
20 snaps out towards the locked position where the locking part 19 locks in the displacement groove when an upper part 21 of the short edge on the folding panel 1' moves a part of the flexible tongue downwards and releases the horizontal tongue and groove locks 52,53 as shown in
25 figures 8b,c. Several alternatives with different shapes of flexible parts, locking means and releasing means could be used to create a pretension of the flexible tongue, to lock the tongue to the displacement groove and to release the flexible tongue so that it snaps towards its locked
30 position. The flexible parts could be made of the same material as the flexible tongue or of separate flexible

materials connected to the tongue or the displacement groove. Horizontal separation forces are generally not present in this type of single snap actions where the tongue is displaced essentially in one direction. Even in
 5 the case when the pre tension would be released when the fold lock is not completely locked, separation problems will be reduced since the locking element 8 of the strip panel is partly in the locking groove 14 of the fold panel and prevents separation. This is shown in figure 8b.

10 Figures 9a show an embodiment of the flexible tongue seen from above and figure 9b show the same embodiment seen from the panel edge parallel with the horizontal plane. The protrusion 51 is a flexible part that extends both horizontally and vertically and could therefore press the
 15 flexible tongue in these both directions in order to lock the flexible tongue with pre tension and to displace it to the final locked position.

Figure 9c and 9e shows an embodiment of the third aspect of the first principle seen in the same way as described
 20 above. A displaceable tongue is provided which has one or more essentially horizontal protrusions 60 with friction connections 36 which hold the displaceable tongue 31 fixed to the displacement groove 40. The displaceable tongue 31 will be displaced with its locking part 19 in the
 25 displacement groove with a turning motion essentially around the friction connections on the protrusions when a sideway pressure P is applied at an pressing edge 32 on the displaceable tongue as shown in figure 9e. This turning motion will also displace the displaceable tongue
 30 into the tongue groove 20. Several other alternatives could be used to obtain a displacement with a sideway

pressure. The displaceable tongue could be combined with one or several separate wedge shaped elements which could be used to displace and push a displaceable tongue into the tongue groove when the tongue or the separate element is displaced sideways. Other alternatives are displaceable tongues with parts that hold the tongue in the displacement groove during transport and which are intended to be separated from the tongue when a sideways pressure is applied. The known bow shaped tongue, as shown in figure 3b, could of course also be used. A side pressure will bend the tongue and the protruding part P2 will be displaced perpendicular to the length direction of the tongue. All known principles, where a sideways pressure is used to accomplish a perpendicular displacement, could be used to displace a locking part into a tongue groove. All embodiments shown in this document are based on the following three principles

- The link principle where a turning around a centre points is used to accomplish the displacement
- The wedge principle where two wedges slide against each other
- The bending principle where parts are bended to a bow shaped form.

These three principles could be combined and a displaceable tongue could have parts where the link, wedge and bending principles are used to convert a sideways pressure to a perpendicular displacement in order to bring parts of a tongue into a groove and to lock floorboards vertically or horizontally.

This third aspect of the invention offers the advantages that all parts of the displaceable tongue could be made rigid. Flexible tongues or flexible parts are however preferred in several applications.

5 Figure 9f show an embodiment where the pressing edge 32 is exposed at the long edge 5b of a second panel 1 which is connected to a first panel 1''. A new panel 1' is connected with angling to the long edge of the first panel 1'' and laid flat on the sub floor such that the short
10 edges 4a, 4b of the second and new panels are in the same plane. A third panel 1a as shown in figure 9g could now be connected with angling to the long edges 5b of the second 1 and new panels 1' and the pressing edge 32 could be pressed inwardly along the short edge of the second panel
15 1 by for example the tongue 10 of the third panel 1a. The displaceable tongue 31 will now be displaced along the short edges but also into the tongue groove 20 of the new panel 1' and the second 1 and the new panel 1' will be locked horizontally and the risk for edge separation
20 during locking is eliminated. This installation method and locking system is further explained in figures 10a-10d. Figure 10a shows how a tongue 10 presses the edge section 32 in a direction along the short edge during angling of the long edges. Figure 10b shows the locked position with
25 the displaceable tongue in its final locked position. The tongue could during locking create a substantial pressure against the pressing edge and the short edges could be locked firmly against each other in the vertical direction. Figure 10 c shows the position of the second 1
30 and the new panels 1' before their short edges are locked vertically and figure 10d show the locked position when

the tongue of the third panel 1a has displaced the
displaceable tongue 31 to its final locked position.

It is obvious that the tongue could be displaced with a
pressure against the pressing edge, which is applied by
5 the installer during installation, with for example a tool
and not by the angling of the third panel. It is also
obvious that displaceable tongues could be connected to an
edge of the panel during installation.

The invention comprises a method to install floor panels
10 with an angling locking system on long edges and a
displaceable tongue on the short edges. The method
comprises the step of

Connection the long edges of a second 1, and a new panel
1' to a long edge of a first panel 1'' in a first row R1
15 such that the short edges of the second and new panel in
the second row R2 are in contact and in essentially the
same plane.

Connecting a third panel in a third row R3 with angling
to the long edges of the second and new panels whereby a
20 displaceable tongue on the short edge of the second and new
panels is displaced such that the short edges are locked
vertically and horizontally.

The invention comprises a method to disconnect floor
panels with an angling locking system on long edges and a
25 flexible tongue on the short edges as shown in figures 10d
and 10c. The flexible tongue 30 could be flexible in such
a way that it returns to the initial unlocked position
when the sideway pressure P is released as shown for
example by the figure 14f-14h. The panels are installed

and locked as shown in figure 10d. The method, which comprises the step below, is described with reference to figure 10c.

The method comprises the steps:

- 5 1. Disconnecting the long edges 5a of a third panel 1a in a third row from a long edge 5b of a second 1 and new panel 1' in a second row and disconnecting a flexible tongue 30 and the vertical locking between a new panel 1' and a second panel 1 in a second row with angling up of
10 the third panel 1a away from the sub floor.

2. Disconnecting the new panel 1' from the long edges 5b of a first panel 1'' in a first row and from the short edges 4a of the second panel 1 with angling up of the new panel 1'.

- 15 All the three link, wedge and bend principles could be reversible.

Figures 11a - 11d are examples, which show that all embodiments of the displaceable and flexible tongues could be adjusted such that they could be alternatively
20 connected to the opposite short edge on the folding panel. It is obvious from the figures that the displaceable tongue 31 as shown in figure 9f could be connected into a displacement groove on the new panel 1' which is folded against the second strip panel 1. Figure 11a shows that
25 the pressing extension 17 could have a downwardly extending press locking element 18' which locks into a locking groove 14' located on the upper part of the strip 6. The dotted line shows that the strip could be made shorter.

Figures 11e-11g is an example that shows that the basic principles of the displaceable tongue and its function and geometry could be used to connect floor panels vertically with an essentially horizontal single snap action. The embodiment show a flexible locking element 61 which is fixed in a groove with pre tension and released during the horizontal displacement of one panel edge against an other panel edge. All shown embodiments according the described principles of locking and disconnecting panels could be used to connect and disconnect panels horizontally according the same principles as shown for the vertical folding. It is obvious that all shown flexible or displaceable tongues could be used as flexible or displaceable locking elements 61 which could be displaced vertically instead of horizontally into a locking groove 14. A new panel could be connected according to the principle that it is displaced horizontally locked to a first panel in a first row and preferably along the connected long edges until the top edges of the new and the second panels are in contact and the tongue 10 is in the groove 9 as shown by the figures 11e - f. The displaceable locking element 61 could for example be displaced vertically by a third panel 1a which is angled to the long edges of the new panel 1' and the second panel 1. The third panel could press against a pressing edge of the displaceable locking element 61 and cause a vertical displacement of a part of the locking element 61. The locking element 61 could for example spring back to its unlocked position when the pressure is released. This allows that the panels could be released by a reverse horizontal displacement away from the short edges. It is obvious that vertical displacements based on the link,

wedge and bending principles could be used to lock horizontally. This third principle of the invention could also be combined with the first principle. The edges could have a displaceable tongue and a displaceable locking
5 element. The locking element 61 could be on the lower part 10b or on the upper part 10a of the tongue 10 and the locking groove 14 could be at an inner part of the strip 6 or in the upper lip. Such an undercut in a locking groove in the upper lip 9a could be formed by for example
10 scraping.

The invention comprises therefore according to a third principle a set of essentially identical floor panels each comprising one pair of opposite edges provided with first and second connectors integrated with the floor panels and
15 configured to connect adjacent edges vertically and horizontally. At least one of the first or second connector comprises a separate locking element integrated with the panel and connected to a displacement groove in an unlocked position. The separate locking element is
20 configured to be displaced horizontally or vertically in one direction only from an inner unlocked position and to an outer locked position in order to lock two adjacent edges vertically and/or horizontally.

Such an embodiment will facilitate easy installation
25 since no compression forces have to be overcome in order to press the locking element into a displacement groove in order to accomplish a vertical or horizontal snap action.

All embodiments of the invention could be used on long and/or short edges or on the strip panel and/or the groove
30 panel. The invention does not exclude tongues on both

adjacent edges or several tongues on the same edge side by side or over and under each other. The shown locking systems according to the first and second aspect of the invention could be formed such that they could for example
5 be connected by angling and/or snapping. The locking system according to the third aspect of the invention could be locked by horizontal snapping of the long edges whereby for example the tongue on the long edge could press against the pressing edge of the displaceable tongue
10 during the horizontal snapping of the long edges. All embodiments could have a geometry allowing disconnection with angling up. The panels could have edges which are not perpendicular, and they could have more than 4 edges for example 5, 6, 8 edges and even up to 12 edges.

15 Figure 12a - 12 show an edge section of a displaceable tongue 31. Figure 12a shows the displaceable tongue before it is connected into the displacement groove 40. The horizontal protrusion 60 has in this embodiment a friction connection 36 and an angle, to the length direction of the
20 displaceable tongue, of about 50-60 degrees. Fig. 12b shows the initial connection of the displaceable tongue 31 during the connection of the tongue to the displacement groove 40. The horizontal protrusion 60 is bent to a lower angle of for example 35 - 40 degrees. Figure 12c shows a
25 displacement of the displaceable tongue along the joint edge. This displacement will position the displaceable tongue in a correct position in the length direction along the short edge and to a pre determined position in relation to the long edge of the panel. This displacement
30 will bring the pressing edge 32 in the correct position and eliminate production tolerances. A high quality

locking requires that the displaceable tongue and the pressing edge 32 is positioned with high precision preferably with a tolerance not exceeding 1 mm. Figure 12 shows how the displaceable tongue 31 is displaced in the locking direction LD perpendicularly to the sideways pressure P which is applied parallel to the length direction of the displaceable tongue 31. The horizontal protrusion 60 has in this position an angle of about 70 - 75 degrees. It bends essentially along a circle C. This is an advantage since the pressing force P in the locking direction could be considerably higher than the locking force in the pressing direction PD. This will create a strong vertical locking and force the short edges to obtain a position in the same plane even in the case that the short edges of the panels are slightly curved in different directions. Figure 12d shows that the pressing edge 32 could be flexible and bendable. This is an advantage and will eliminate production tolerances related to the position and geometry of the displaceable tongue and the locking system. The displaceable tongue could lock with pre tension into the tongue groove 40.

Figures 13a-e show the function of a displaceable tongue 31 which is made of a very simple component, preferably a extruded or moulded plastic section with a simple and essentially rectangular cross section. Figures 13a show a first panel 1'' and a second panel before they are connected. Figure 13b shows a cross section of the short edge 4a of the second panel 1. Figure 13 shows the panels in a connected stage. The displaceable tongue is in the displacement groove 40. Figure 13d shows that a new panel 1' (not shown in figure 13c) could be moved vertically up

and down and that there is no vertical connection that prevents angling up or down of the long edges of a new 1' and a first 1'' panel. In order to simplify the description, figure 13e is shown without the new panel.

5 The connection of the third panel 1a to the second panel 1 will press one of the edge sections Es1 towards an edge of the first panel 1'', preferably against the inner part of the long edge tongue groove 9, and another of the edge sections Es2, in this case the pressing edge 32, against
10 an edge of the third panel 1a, preferably against the long edge tongue 10. The displaceable tongue 31 will bend in a horizontal plane and in a length direction. A part could be displaced into a tongue groove 20 as shown in figure 13f. The displaceable tongue 31 will revert to the initial
15 position as shown in figure 13 c, if the third panel 1a is disconnected and the pressure on the edge sections Es1 and Es2 is released. This allows the new panel 1' to be discontented by an angling up action. The locking with vertical folding and the disconnection with angling up are
20 preferably carried out along the vertical plane VP with the top edges of the new and the second panels in contact. The bending or displacement should preferably be more pronounced at the edge section Es1 that is opposite to the section Es2 where the side pressure is applied. This gives
25 a stronger lock since friction forces in the length direction of the joint could be reduced and the perpendicular force into the tongue groove could be higher. This means that the bending could start at the edge section Es2 and it could gradually increase towards
30 the press section Es2. The tongue could obtain a locked position such that the major part of the middle section is parallel with the tongue groove. A major advantage

compared to the known technology is that a considerably stronger pressure is obtained during the final stage of the locking than during the initial stage. This could be used to lock the edges with strong pre tension. The
5 opposite is present in the known locking systems where the tongue pressure is at its peak when the tongue is in the inner position. It is an advantage if the lower part of the displacement groove 40 is formed in a plane, which is over the top of the locking element, as shown in figure
10 13f

Figures 14 a-b show that the bending of the displaceable tongue 31 could be facilitated if the displaceable tongue is slightly bended horizontally along the length direction in unlocked position.

15 Figure 14c shows a displaceable tongue 31, which in this case also is a flexible tongue, since it is bendable in the length direction. It has a simple and essentially rectangular cross section and at least one friction
20 connection that holds the tongue in the displacement groove during transport and installation. The tongue has a length L and a width direction W. Figure 14d shows a displaceable tongue 31, which is slightly bended horizontally in a horizontal plane parallel to the main plane of the panels. This facilitates further bending and
25 displacement. Figure 14e shows that a friction connection could be replaced by a displaceable tongue that is slightly bended vertically perpendicular to the horizontal plane. It is obvious that the tongues could be connected into a displacement groove without any special friction
30 connections or bended forms. A tight fit could be sufficient. Glue is not excluded. All these embodiments

could be combined. The tongue could for example be produced such that is slightly bended vertically and horizontally. All these tongues could preferably be formed in a plastic material by injection moulding or by
5 extrusion or simply by punching of a sheet shaped plastic material.

Figures 14f-h show another principle to form a displaceable tongue. The tongue has along its length L a middle section S1 that has a smaller width than a part
10 closer to the edge sections Es1, Es2. This facilitates bending. Figures 14g and 14h show the bending when a sideways pressure P is applied and released.

Figure 15a-c show an embodiment of a displaceable and flexible tongue 31 with flexible edge sections Es1, Es2
15 which allow that a major part of the tongue is displaced, and that there is a vertical locking element 19 over essentially the major part of the length of the short edge.

Figure 15d-e show that flexible edge sections according to figure 15a-c and bending according to figure 14b could
20 be combined.

Figure 15f show that the displaceable tongue could be displaced with a tool that creates the sideways pressure.

Figure 16a-16d shows connection of a separate tongue or
25 any similar loose element. A displaceable tongue 31 is connected into a groove 40 at the edge with a pusher that preferably connects one edge of the tongue. Figure 16b shows that a pressure wheel PW could be used to connect the displaceable tongue 31 further into a groove 40.

Figure 16d show that a position device PD could be used to position the tongue in relation to one long edge. This could be made in line in a continuous flow.

Figure 16e show how a displaceable or flexible tongue 31 could be formed from a tongue blank TB, for example from an extruded section which is punched in order to form and separate the tongues from the extruded tongue blank TB. Friction connections could be formed for example by punching or with heat.

Figures 17a-17j show embodiments of flexible and displaceable tongues 31 according to the invention. Figures 17a-b show a flexible tongue 30 with a middle section comprising two parts separated from each other in the width W direction. Figures 17c-e show tongues where the width W varies along the length L of the flexible tongue 30.

Figures 14a-14h, 15a-15e and 17a-17e are all examples of embodiments based on the bending principle.

Figure 17f-g show the wedge principle with a displaceable double tongue with two parts 31a, 31b that comprises cooperating wedges 70 that are displaced and separated from each other in the width direction W when a sideways pressure P is applied.

Figure 17h - 17j show an edge section of a double tongue where the two parts 31a and 31b are connected. Figure 17h shows how such a double tongue could be produced and folded together when connected as shown in figure 17i. The connection 62 that connect the two parts could be bended,

expanded, compressed or separated from one of the parts when a sideways pressure P is applied.

Figures 18a-c show an embodiment of the displaceable tongue 31 according to the link principle, which has
5 several horizontal protrusions 60 that during the connection of the tongue to the groove 40 (figure 18b) and displacement (figure 18c) are rotated around a centre point. The protrusions could be bended and they could be permanently rotated or alternatively flexible such that
10 they could return at least partly to the initial unlocked position when the side pressure is released.

Figure 18d shows a blank TB of an extruded section with an essentially rectangular cross section comprising one or more friction connections 36 as shown in figure 18e.

15 The embodiments as showed in figures 18f-18i, and which are based on the link principle, shows how rather complex forms with one or several horizontal protrusions comprising a friction connection could be obtained by punching and/or forming a blank of an extruded section.

20 Figure 18h and 18i show that the principles of obtaining a horizontal displacement into a tongue groove with a sideways pressure and with a tongue comprising horizontal protrusions or with a tongue that bends, could be combined. The shown tongue 31 is displaced partly with the
25 horizontal protrusions 60 according to the link principle and partly with a bow shaped part which is displaced according to the bending principle.

The known technology as described in connection with figures 1-5 could be combined with the embodiments of the

invention. Part of a flexible tongue could be pressed into a displacement groove during the vertical folding as shown in for example figure 5 and it could thereafter snap back into the tongue groove. A sideways pressure could
 5 thereafter be applied and a final and stronger locking could be obtained according to the principles of the invention. Such combinations could also be made with the flexible locking element, which locks horizontally as shown and described in connection to figures 11e-11g

10 Figure 19a show an embodiment of the pre tension principle where two parts of a flexible tongue 30 are connected under pre tension to each other with a hook 63. Figure 19b shows the tongue 31 when the pre tension has been released by the hook 63.

15 Figure 19c-19e show that this hook could be released by an vertical pressure caused by an edge of the folding panel 1' and the result is that a part of the tongue 30 springs into the tongue groove.

Figures 20a-b show an embodiment of the pretension
 20 principle where the inner part of the tongue 30 is flexible and pushes an outer rigid part into the tongue groove when the hook 63 has released the pre tension. The flexibility is obtained by a flexible cavity 72

Figure 20c shows an injection moulded flexible tongue 30
 25 where the displacement is based on the pre tension principle and where several hooks 63 gradually release the pre tension during the vertical folding. Parts of the tongue 31 will gradually be displaced into the tongue groove. It is obvious that such a flexible tongue could be
 30 used to lock floorboards without the hooks 63 and with the

double action principle where the parts of the tongue are gradually displaced into a displacement groove and back again into the tongue groove according to the known principles associated with vertical folding and described in figures 1-4. The inner groove section with its substantially rigid part 73 could be permanently connected into the displacement groove with strong friction or pre tension or it could alternatively be glued into a groove. The tongue could have several flexible cavity sections 72. They could be connected on one or both sides with rigid parts 73 - one in the inner part of the displacement groove and one in the outer part - that locks into a tongue groove.

It is also obvious that flexible tongues could be made according to for example the embodiments 17b, 19b and 20b such that they could be compressed and such that they could be used to lock floorboards according to the principles described in figure 1-4 where a part of the flexible tongue is bent in length direction during the vertical folding. A tongue 30 could as shown in figure 20b have an inner flexible part 72 and a rigid outer part 73 that locks into a tongue groove when the flexible part 72 is compressed during the vertical folding to a position as shown in figure 20a. The tongue 30 could of course have several such flexible section 72 along its length that are bent and compressed in the length direction of the tongue. Such a principle is shown in figure 25 a,b.

Figure 21a and show an embodiment according to the wedge principle where a wedge part 70 is separated from the displaceable tongue during the displacement into the

groove 40. Figure 21b show a tongue 31 where several parts are separated during displacement.

Figure 21c show an injection moulded tongue 31 with several horizontal protrusions 60 according to the link principle where the thickness and the width of the tongue varies along the length.

Figure 21d show a tongue 30 with several bow shaped parts that could be displaced according to the bending principle.

Figure 22a and 22b show how the last row close to a wall 71 could be locked if the tongue 30 for example is made according to the bending principle. The outer part of the tongue 30 is displaced sideways by a simple tool. This method could also be used for the first row. Alternatively a needle shaped tool could be inserted into the displacement groove in order to displace the tongue. A friction connection or similar at one edge could be used to lock the first row in the same way as for all other panels. Most of the embodiments according to the wedge and link principles are displaceable in the first row in the same way as for other rows.

Figure 23a-23c show an embodiment according to the wedge principle that consist of two parts 31a and 31b, which are folded together and connected to one component with one or several wedge hooks 77. Displacement, production tolerances and pressure forces could be controlled in a very precise way with curved and/or flexible wedges 70a, 70b and locking parts 78a, 78b that lock along the joint and which cooperate with each other in order to facilitate a controlled displacement into a tongue groove. Complex,

advanced and cost effective features could be accomplished with preferably injection mouldings. In a preferred embodiment, the two parts are produced in the same mould.

The shown embodiments are only examples. An "unlimited" number of alternatives could be made with combinations of the shown embodiments and generally known principles.

Figures 24a - 24d show locking of a floorboard which in this case is a wood flooring and the displacement is according to the bending principle. The tongue 30 is in this embodiment fixed to the floorboard such that it protrudes slightly outside the long edge tongue 9. When the flexible tongue 30 comes into contact with the inner part of the tongue groove 10 it is displaced along the joint as shown in figure 24b. The third panel 1a is connected with angling and its tongue 10 presses against the pressing edge 32 of the flexible tongue 30. Figure 24d shows how the tongue 31 is compressed with one of its edge sections Es1 in contact with the inner part of the long edge groove 9 of the first panel 1'' and the other edge section Es2 in contact with the tip of the tongue 10 of the third panel 1a. The bending principle allows that the floor could be installed in both directions - with the long edge tongue part on the strip or with the long edge strip under the tongue. It could be mentioned that a compression of about 0,5 mm could results in a tongue bending of about 2 mm. Even with production tolerances of some 0,1 mm for the flexible tongue 30 and for the machining of the floorboard 1, the tongue 10 and the groove 9, it is possible to obtain a high quality lock mainly due to fibre compression and the fact that the bow

shaped form is converted to a straight line when pressure and displacement along the joint increases.

Figure 25a shows a new embodiment of a flexible tongue that could be used to lock floorboards with vertical
 5 folding according to the known principle where the tongue is displaced inwardly by an edge during the vertical folding. The displacement is caused by flexible cavities 72 which are possible to compress and bend. Figure 25a shows the outer locked position of a flexible tongue 30
 10 and figure 25b the inner compressed and unlocked position. The tongue has in this embodiment a rigid outer part 73 that locks into a tongue groove when the flexible part 72 snaps towards the initial position. The flexible tongue 30 could of course have several such flexible cavity section
 15 72 along its length that are bent and compressed in the length direction of the tongue.

Figure 26a show an embodiment, which could be used to position and fix the displaceable tongue in order to prevent displacement of the tongue along the joint when
 20 the side pressure is applied. This embodiment allows that even panels in the first row could be locked with bending of the tongue. The displaceable tongue has a side hook 79 which locks for example against the inner part of the long edge groove 9. The side hook is via an extension 80
 25 connected to an edge section Es1 of the tongue opposite to the pressing edge 32. This side hook 79 is also used to position the tongue 30 and the pressing edge 32 in a correct position against the long edge. Figure 26b shows the bending when the side pressure P is applied. Side
 30 hooks and positioning elements could be applied on both long edges as an alternative to the previous mentioned

friction connection. A side hook could for example be applied in the locking groove of a long edge.

Figure 26c shows an embodiment with friction connections 36, which prevents displacement along the edge. Parts of
5 the tongue could also be glued to the edge. The pressing edge has a fixing protrusion 81, which extends along a groove of the long edge. This protrusion could be used in for example wood floors with a lamella core in order to over bridge spaces between the lamellas and to make sure
10 that a tongue part always presses against the pressing edge 32.

The displacement of a tongue according to the wedge principle could also be made with a displacement groove that has one or several parts formed like wedges. This
15 means that the depth and/or thickness of the displacement groove will vary along the length of the edge.

CLAIMS

1. A set of floor panels (1, 1') provided with a locking
5 system comprising a separate displaceable tongue (31)
integrated with an edge (4a, 4b) of a floor panel for
connecting the edge vertically to an adjacent edge of a
similar panel c h a r a c t e r i s e d in that at least a
part of the displaceable tongue (31) is displaced and that
10 the locking is accomplished by a sideways pressure (P)
applied at an edge section of the displaceable tongue (31)
and essentially along the edge (4a, 4b).
2. The set floor panels as claimed in claim 1,
c h a r a c t e r i s e d in that the panels are provided
15 with first and second connectors (9,10, 6,8,14, 20,31), the
connectors are integrated with the floor panels and
configured to connect adjacent edges, the first connector
comprises a locking strip (6) with an upwardly directed
locking element (8) at an edge of a floor panel and a
20 downwardly open locking groove (14) at an adjacent edge of
another floor panel for connecting the adjacent edges in a
horizontal direction D2 perpendicular to the adjacent
edges, the second connector comprises the displaceable
tongue (10,31) at an edge of a floor panel, and a
25 horizontally open tongue groove (9,20) in an adjacent edge
of another floor panel for connecting the adjacent edges in
vertical direction D1, the connectors are configured to be
locked with angling or a vertical motion and that a locking
part (19) of the displaceable tongue (31) is arranged in an
30 inner initial position in a displacement groove (40) at an
edge of a panel and that the locking part is configured to

be displaced essentially horizontally and essentially in one direction only from the initial unlocked position to a final outer locked position in the tongue groove (20) of another adjacent panel by the sideways pressure P directed
5 in the length direction of the displaceable tongue.

3. The set of floor panels as claimed in claim 2,
c h a r a c t e r i s e d in that the displaceable tongue
(31) of a panel in a first row is configured such that the
displacement of the locking part (19) is caused by an edge
10 of a panel in a second row.

4. The set of floor panels as claimed in claim 1 or 2,
c h a r a c t e r i s e d in that the displaceable tongue
is flexible and that a part of the tongue 31 is bent in the
length direction L of the tongue 31.

15 5. The set of floor panels as claimed in claim 3 or 4,
c h a r a c t e r i s e d in that the width W of the
tongue 31 varies in the length direction L.

6. The set of floor panels as claimed in claim 1
c h a r a c t e r i s e d in that the displacement is
20 caused by a bending principle.

7. The set of floor panels as claimed in claim 1
c h a r a c t e r i s e d in that the displacement is
caused by a link principle.

8. The set of floor panels as claimed in claim 1
25 c h a r a c t e r i s e d in that the displacement is
caused by a wedge principle.

9. A set of floor panels comprising a locking system with a separate displaceable locking element (61) integrated with an edge (4a, 4b) of a floor panel for connecting the edge horizontally to an adjacent edge (4a, 4b) of a
- 5 similar panel c h a r a c t e r i s e d in that at least a part of the displaceable locking element (61) is displaced and that the locking is accomplished by a sideways pressure (P) applied at an edge section of the displaceable locking element (61) and essentially along the edge.