

UK9-91-032

1

LAMINAR FLOW FAN AND ELECTRICAL APPARATUS INCORPORATING FAN

This invention relates to the field of laminar flow fans comprising a plurality of rotatable parallel disk elements and also to apparatus incorporating such fans.

- 5 Laminar flow fans are commonly used for impelling a fluid medium (a liquid or gas). In particular, they are suited to low flow, high back pressure forced air cooling of electrical apparatus when low acoustic fan noise is required. Typically, these fans comprise an assembly of parallel annular or frustro-conical elements, mounted in spaced apart
10 relationship and face-to-face about a common rotation axis. In operation, the assembly is rotated about this axis by a suitable motor; the fluid is drawn in at the centre of the assembly, impelled towards the outer edges of the elements by viscous interaction with the surface of the elements and is finally expelled at the periphery of the assembly.
15 Examples of laminar flow fans may be found in GB 2 126 653 and US 2 632 598.

- A large variety of cooling systems have been proposed for providing efficient cooling of a number of electrical or electronic devices housed together in an enclosure. In many of today's computer system units, a
20 number of different elements including mass storage devices, circuit cards and associated power supplies are provided which must be cooled sufficiently in order to ensure safe operating temperatures. The cooling system employed in such system units commonly comprises one or more axial flow fans placed at the rear of the unit which operate to draw cooling
25 air through apertures in the front bezel of the unit, over the electrical devices and to expel exhaust air through apertures at the rear of the unit. One common type of system unit is the floor standing 'tower' in which a tower is supported in an upright position by a support foot.

- While these cooling systems are undoubtedly adequate for the
30 purpose, they have a number of drawbacks. Firstly, the fans take up valuable space within the unit which results in an increase in the overall size of the unit and secondly the noise produced by axial fans can be significant in an office environment.

- The present invention seeks to improve on prior cooling systems and
35 accordingly provides a laminar flow fan comprising a stack of parallel

REPLACED SHEETS		SG
☒	Description : paged ...1... to paged ...2...	
☒	Claim(s) : paged ...6... to paged ...7...	
☐	Drawing(s) : paged to paged	
☒	Abstract : paged ...f... to paged ...-...	
DATE OF RECEIPT		

This Sheet Has Been Replaced



spaced apart disk elements mounted for rotation by a motor; characterised in that the diameters of the disk elements vary within the stack so as to maximise utilisation of the available internal space of housing in which the fan is mounted.

5 Thus when the predetermined housing has a shape such that full use of the internal space cannot be achieved using a standard axial flow fan or laminar fan with equal diameter disk elements, the laminar flow fan of the present invention including varying diameter disk elements achieves maximum utilisation of the available space. For a given housing, a fan
10 shaped according to the present invention can be shown to be more efficient than an axial flow fan in the same housing. In addition, tailoring of the disk element diameters according to the present invention results in an increase in the total surface area of the fan over a non-tailored laminar flow fan thereby providing an increase in
15 efficiency.

In a second aspect of the invention, there is provided an apparatus for housing and cooling one or more electrical devices comprising: a chassis secured to a cooling assembly enclosure in which chassis the one or more electrical devices are mountable; and a laminar flow fan of the
20 type defined above which is mounted within the enclosure.

In this way, efficient cooling of the electrical devices is achievable without the cooling system taking up valuable space within the chassis. In addition, profiling the shape of the disk element stack of the laminar flow fan allows for the most efficient use of the available
25 space within the base thus optimising the fan efficiency for a particular shape of base cavity.

The form factor of a laminar flow fan is ideal for this design since the air is drawn through the central 'eye' of the disk elements and expelled radially through louvres in the base. In addition, laminar flow
30 fans are quieter in general than other more commonly used types of fan.

A preferred embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

This Sheet Has Been Replaced



Figure 1 is a schematic cross sectional view of a laminar flow fan according to the present invention;

Figure 2 is a top view of one disk element used in the laminar flow fan according to the present invention;

- 5 Figure 3 is a schematic cross sectional view of an electrical apparatus housing incorporating the fan of Figure 1;

Figure 4 is a schematic perspective view of a removable foot pedestal cooling assembly including a pair of laminar flow fans.

Figure 1 shows a laminar flow fan 10 comprising a plurality of disk
10 elements 12, 14, 16, 18, 20, 22, 24, each having a central aperture, (13
in Figure 2) which are held in a spaced apart relationship about a common
rotation axis 26. In this description, the fan elements are shown as
annular discs; however other element shapes e.g frustro-conical may be
employed. The disks are commonly made of a plastics material, of the
15 order of 1mm in thickness and typically spaced by 0.5 to 3 mm in a fan
used to impel air. However, the dimensions of all the fan components and
element spacings depend on the performance required from the particular
fan.

The plurality of disks is secured by means of three support posts
20 (two of which are identified by reference numeral 50) to a non-apertured
bottom plate 44 which is attached to and driven by rotor element 40
forming part of motor 42. Figure 2 shows a single disk element including
a central aperture incorporating three notches 60 which engage with posts
50 to hold the disk element fixed in position. Further details of the
25 laminar flow fan including the method of assembly may be found in
European Patent 474 929. It will however be appreciated that the exact
construction of the laminar flow fan is not critical to the present
invention.

A typical operational speed for this type of fan, when used to
30 impel air, might be between several hundred and perhaps three thousand
revolutions per minute.

The fan is mounted within a hollow housing 70 by fixing the motor
42 to the inner surface of housing base plate 72. It can be seen in

Figure 1 that the housing is frustro-conical in cross section with the diameter of the disks making up the stack decreasing in a direction away from the bottom plate 44 such that the overall shape of the fan conforms closely to the cross section of the housing. Tailoring the disk
5 diameters in this manner allows for a more efficient use of the internal volume of the housing than would be the case for a laminar flow fan made up of disks having a constant diameter equal to the diameter of the topmost disk in the fan of Figure 1. Maximising use of the internal
10 volume of the housing using the present invention gives a greater volume flow for a given speed than for the fan with constant diameter disks. Hence, it is possible to reduce the speed of the fan with a consequent reduction in noise while maintaining the required cooling efficiency. It will be appreciated that the disk diameters may readily be tailored to conform to housings with shapes different to that shown in Figure 1.

15 Figure 2 shows a tower unit 80 comprising a main chassis 82 attached to a base 70 in the form of a hollow foot pedestal shaped like the housing of Figure 1. Mounted within the hollow foot pedestal is a laminar flow fan as depicted in Figure 1. The tower chassis contains one or more electrical units 84 e.g. disk drives, power supplies etc and
20 includes cooling apertures 76 in its top surface to permit intake of cooling air. An outlet aperture 88 in the lower surface 86 of the main chassis is aligned with a corresponding aperture (78 in Figure 1) in the top of the foot pedestal to allow passage of cooling air from chassis to base. Included in the external wall 75 of the foot pedestal are a
25 plurality of exhaust apertures 74, which are aligned with the edges of each of the disks.

In operation, air is drawn by the fan through the inlet apertures at the top of the chassis. This cooling air passes over the electrical units within the chassis and carries away heat produced by the units. As
30 is well known in the cooling art, baffles (not shown) may be located at appropriate positions in the chassis in order to direct the flow of cooling air at specific portions of the units to be cooled e.g. circuit boards. The heated air is then drawn through the outlet aperture of the chassis and into the central intake aperture of the fan. The air is
35 turned through ninety degrees as it passes over the surfaces of the disks from which it is expelled via the outlet apertures in the foot pedestal into the external environment.

Figure 4 shows a perspective schematic view of the foot pedestal assembly which is removably attachable to the main chassis of the tower unit. It can be seen that the top outer surface of the assembly includes a pair of apertures 100, 102 which communicate with the central intake apertures of a pair of laminar flow fans arranged side by side in the pedestal assembly. The lower surface of the chassis to which the pedestal of Figure 4 is attachable will include a pair of outlet apertures corresponding to the pedestal inlet apertures.

Also included at each corner of the pedestal upper surface is a locating peg 90 which is positioned to mate with a corresponding aperture (not shown) on the chassis lower surface. A connector 110 is also provided on the pedestal upper surface via which power is supplied to the fan motors from a power supply in the chassis.



UK9-91-032

6

CLAIMS

1. A laminar flow fan comprising a stack of parallel spaced apart disk elements (12,14,16,18,20,22) mounted for rotation by a motor (40); characterised in that the diameters of the disk elements vary within the
5 stack so as to maximise utilisation of the available internal space of a housing in which the fan is mounted.
2. A laminar flow fan as claimed in claim 1, wherein the diameters of the disk elements vary monotonically along the stack.
3. Apparatus for housing and cooling one or more electrical devices
10 comprising:

a chassis (82) secured to a cooling assembly enclosure (70) in which chassis the one or more electrical devices are mountable; and

a laminar flow fan as claimed in claim 1 or claim 2 for cooling the devices, the fan being mounted within the enclosure.
- 15 4. Apparatus as claimed in claim 3, wherein the cooling assembly enclosure forms a base portion of the apparatus, the chassis being supported on the base portion.
5. Apparatus as claimed in claim 4, wherein the cross sectional area of the available internal space in the base portion increases in a
20 direction away from the contact between the base and the chassis with the diameter of the disk elements making up the stack increasing in the same direction.
6. Apparatus as claimed in any of claims 3 to 5, wherein the stack of rotatable disk elements is mounted for rotation on a motor and includes a
25 central intake aperture (78) for receiving cooling air from the chassis, the enclosure including exhaust apertures through which cooling air is expelled radially from the disk elements.
7. Apparatus as claimed in any of claims 4 to 6 wherein the base portion and laminar flow fan together form a removable cooling assembly
30 including power connector means (110) for attaching to a corresponding connector on the chassis to provide power to the cooling means.



* C L M S *

8. Apparatus as claimed in any of claims 4 to 7, including a pair of laminar flow fans mounted side by side in the base.

This Sheet Has Been Replaced



* C L M S *

This Sheet Has Been Replaced



UK9-91-032

8

ABSTRACT

LAMINAR FLOW FAN AND APPARATUS INCORPORATING SUCH A FAN

A laminar flow fan is described which is adapted to fit into a the internal cavity of a fan housing (70). The fan comprises a stack of .
5 parallel disk elements (12,14,16,18,20,22) mounted for rotation on a motor (40) with the diameters of the disk elements varying within the stack to more fully utilise the available internal space of the housing. Apparatus which uses such a fan as part of its forced air cooling system to cool one or more electrical devices is also described.

This Sheet Has Been Replaced






FIG. 1




FIG. 2




FIG. 3




FIG. 4


ABSTRACT

LAMINAR FLOW FAN AND APPARATUS INCORPORATING SUCH A FAN

A laminar flow fan is described which is adapted to fit into a the internal cavity of a fan housing (70). The fan comprises a stack of parallel disk elements (12,14,16,18,20,22) mounted for rotation on a motor (40) with the diameters of the disk elements varying within the stack to more fully utilise the available internal space of the housing. Apparatus which uses such a fan as part of its forced air cooling system to cool one or more electrical devices is also described.

Fig. 1

THIS SHEET HAS BEEN
REPLACED



3-4048382

2004 10 10

LAMINAR FLOW FAN AND ELECTRICAL APPARATUS INCORPORATING FAN

This invention relates to the field of laminar flow fans comprising a plurality of rotatable parallel disk elements and also to apparatus incorporating such fans.

Laminar flow fans are commonly used for impelling a fluid medium (a liquid or gas). In particular, they are suited to low flow, high back pressure forced air cooling of electrical apparatus when low acoustic fan noise is required. Typically, these fans comprise an assembly of parallel annular or frustro-conical elements, mounted in spaced apart relationship and face-to-face about a common rotation axis. In operation, the assembly is rotated about this axis by a suitable motor; the fluid is drawn in at the centre of the assembly, impelled towards the outer edges of the elements by viscous interaction with the surface of the elements and is finally expelled at the periphery of the assembly. Examples of laminar flow fans may be found in GB 2 126 653 and US 2 632 598.

A large variety of cooling systems have been proposed for providing efficient cooling of a number of electrical or electronic devices housed together in an enclosure. In many of today's computer system units, a number of different elements including mass storage devices, circuit cards and associated power supplies are provided which must be cooled sufficiently in order to ensure safe operating temperatures. The cooling system employed in such system units commonly comprises one or more axial flow fans placed at the rear of the unit which operate to draw cooling air through apertures in the front bezel of the unit, over the electrical devices and to expel exhaust air through apertures at the rear of the unit. One common type of system unit is the floor standing 'tower' in which a tower is supported in an upright position by a support foot.

While these cooling systems are undoubtedly adequate for the purpose, they have a number of drawbacks. Firstly, the fans take up valuable space within the unit which results in an increase in the overall size of the unit and secondly the noise produced by axial fans can be significant in an office environment.

This is the replacement sheet

Date: - 9 OCT 1997

REPLACEMENT SHEETS		SG
☒	Description : paged 121 to paged 122	
☒	Claim(s) : paged 1 to paged 1	
☐	Drawing(s) : paged to paged	
☒	Abstract : paged 1 to paged 1	
DATE OF RECEIPT		9/10/97

SUMMARY OF THE INVENTION

It is an object of the present invention to ameliorate one or more disadvantages of the prior art.

According to one aspect of the present invention there is provided an apparatus for housing and cooling one or more electrical devices comprising: a chassis secured to a cooling assembly enclosure in which chassis the one or more electrical devices are mountable; and a laminar flow fan mounted within said cooling assembly enclosure for cooling the devices, said laminar flow fan comprising: (a) a motor; and (b) a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of the disk elements vary within the stack so as to maximize utilization of the available internal space of the cooling assembly enclosure, wherein the cooling assembly enclosure forms a base portion of the apparatus on which the chassis is supported, the cross sectional area of the available internal space in the base portion increasing away from the contact with the chassis with the diameter of the disk elements making up the stack increasing away from the chassis contact.

According to another aspect of the present invention there is provided an apparatus for housing and cooling one or more electrical devices comprising: a chassis secured to a cooling assembly enclosure in which chassis the one or more electrical devices are mountable; and a laminar flow fan mounted within said cooling assembly enclosure for cooling the devices, said laminar flow fan comprising: (a) a motor; and (b) a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of the disk elements vary within the stack so as to maximize utilization of the available internal space of the cooling assembly enclosure, wherein the stack of rotatable disk elements mounted for rotation on said motor includes a central intake aperture for receiving cooling air from the chassis, wherein the cooling assembly enclosure forms a base portion of the apparatus on which the chassis is supported, the base portion including exhaust apertures through which cooling air is expelled radially from the disk elements.

This is the replacement sheet

Date: - 9 OCT 1997

According to still another aspect of the present invention there is provided an apparatus for housing and cooling one or more electrical devices comprising: a chassis secured to a cooling assembly enclosure in which chassis the one or more electrical devices are mountable; and a laminar flow fan mounted within said cooling assembly enclosure for cooling the devices, said laminar flow fan comprising: (a) a motor; and (b) a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of the disk elements vary within the stack so as to maximize utilization of the available internal space of the cooling assembly enclosure, wherein the cooling assembly enclosure forms a base portion of the apparatus on which the chassis is supported, wherein the base and laminar flow fan are a removable cooling assembly including power connector means for attaching to a corresponding connector on the chassis to provide power to the fan.

According to still another aspect of the present invention there is provided a laminar flow fan, adapted to fit into a predetermined housing, comprising: a motor; and a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of each of the disk elements vary within the stack to conform to the shape of the housing so as to maximize utilization of the available internal space of the housing.

DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

A preferred embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

This is the replacement sheet

Date: - 9 OCT 1997

CLAIMS

What is claimed is:

1. An apparatus for housing and cooling one or more electrical devices comprising:

a chassis secured to a cooling assembly enclosure in which chassis the one or more electrical devices are mountable; and

a laminar flow fan mounted within said cooling assembly enclosure for cooling the devices, said laminar flow fan comprising:

(a) a motor; and

(b) a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of the disk elements vary within the stack so as to maximize utilization of the available internal space of the cooling assembly enclosure, wherein the cooling assembly enclosure forms a base portion of the apparatus on which the chassis is supported, the cross sectional area of the available internal space in the base portion increasing away from the contact with the chassis with the diameter of the disk elements making up the stack increasing away from the chassis contact.

2. An apparatus for housing and cooling one or more electrical devices comprising:

a chassis secured to a cooling assembly enclosure in which chassis the one or more electrical devices are mountable; and

a laminar flow fan mounted within said cooling assembly enclosure for cooling the devices, said laminar flow fan comprising:

(a) a motor; and

(b) a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of the disk elements vary within the stack so as to maximize utilization of the available internal space of the cooling assembly enclosure, wherein the stack of rotatable disk elements mounted for rotation on said motor includes a central intake aperture for receiving cooling air from the chassis, wherein the cooling assembly enclosure forms a base portion of the apparatus on which the chassis is supported, the base portion including exhaust apertures through which cooling air is expelled radially from the disk elements.

3. An apparatus for housing and cooling one or more electrical devices comprising:

a chassis secured to a cooling assembly enclosure in which chassis the one or more electrical devices are mountable; and

This is the replacement sheet



Date: 9 OCT 1997

a laminar flow fan mounted within said cooling assembly enclosure for cooling the devices, said laminar flow fan comprising:

(a) a motor; and

(b) a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of the disk elements vary within the stack so as to maximize utilization of the available internal space of the cooling assembly enclosure, wherein the cooling assembly enclosure forms a base portion of the apparatus on which the chassis is supported, wherein the base and laminar flow fan are a removable cooling assembly including power connector means for attaching to a corresponding connector on the chassis to provide power to the fan.

4. A laminar flow fan, adapted to fit into a predetermined housing, comprising:

a motor; and

a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of each of the disk elements vary within the stack to conform to the shape of the housing so as to maximize utilization of the available internal space of the housing.

5. A laminar flow fan as claimed in claim 4 wherein the diameters of the disk elements vary from a disk element positioned at one end of the stack to a disk element positioned at the other end of the stack.

6. An apparatus for housing and cooling one or more electrical devices comprising:

a chassis secured to a cooling assembly enclosure in which chassis the one or more electrical devices are mountable; and

a laminar flow fan mounted within said cooling assembly enclosure for cooling the devices, said laminar flow fan comprising:

(a) a motor; and

(b) a stack of parallel spaced apart disk elements mounted for rotation about a common axis by said motor, wherein the diameters of the disk elements vary within the stack to conform to the shape of said cooling assembly enclosure so as to maximize utilization of the available internal space of the cooling assembly enclosure.

7. The apparatus for housing and cooling electrical devices of claim 6, wherein the diameters of the disk elements vary from a disk element positioned at one end of the stack to a disk element positioned at the other end of the stack.



This is the replacement sheet

Date: - 9 OCT 1997

8. The apparatus for housing and cooling electrical devices of claim 6, wherein the cooling assembly enclosure forms a base portion of the apparatus on which the chassis is supported.

9. The apparatus for housing and cooling electrical devices of claim 8, wherein at least two laminar flow fans are mounted side by side in the base.



This is the replacement sheet

Date: - 9 OCT 1997

THIS SHEET HAS BEEN
REPLACED

ABSTRACT

LAMINAR FLOW FAN AND APPARATUS INCORPORATING SUCH A FAN

A laminar flow fan is described which is adapted to fit into a the internal cavity of a fan housing (70). The fan comprises a stack of parallel disk elements (12,14,16,18,20,22) mounted for rotation on a motor (40) with the diameters of the disk elements varying within the stack to more fully utilise the available internal space of the housing. Apparatus which uses such a fan as part of its forced air cooling system to cool one or more electrical devices is also described.

This Sheet Has Been Replaced



This is the replacement sheet

Date: - 9 OCT 1997

ABSTRACT

LAMINAR FLOW FAN AND APPARATUS INCORPORATING SUCH A FAN

A laminar flow fan is described which is adapted to fit into a the internal cavity of a fan housing (70). The fan comprises a stack of parallel disk elements (12,14,16,18,20,22) mounted for rotation on a motor (40) with the diameters of the disk elements varying within the stack to more fully utilise the available internal space of the housing. Apparatus which uses such a fan as part of its forced air cooling system to cool one or more electrical devices is also described.

REPLACEMENT SHEET

04 DEC 1997