



MODEM AND METHOD FOR TRANSMITTING DATA IN A MEDIUM NOTABLY SUCH AS AIR AND WATER

The invention relates notably to a modem and a method making it possible to transmit data in a medium such as the marine medium or else air.

It thus relates to an acoustic modem for underwater transmissions and its associated method.

5 It is also aimed at data transmissions in air, via ultrasound waves, for example.

The problem posed is notably the transmission of data of any type between two corresponding parties immersed in a given medium such as water and at a throughput of several hundred bits per second while using as small as possible
10 a bandwidth and a calculation power reduced to the minimum, in particular for autonomous equipment operating with batteries.

The electromagnetic waves conventionally used (from a few hundred kHz to a few GHz) propagating extremely poorly in water, the modem (modulator-demodulator) therefore uses acoustic waves to transport the messages transmitted.

15 It should be recalled that the underwater medium has an extremely complex behavior in respect of acoustic waves. Because of its inhomogeneities (salinity, temperature, currents, etc.) the path followed by the waves is a straight line only for very short distance and this path varies over time.

The waves which reach the receiver may follow several paths with very
20 different delays. These paths can be either "direct" (several different routes converging towards the receiver), or "indirect" (reflections on the surface of the water, possibly perturbed by waves, as well as on the bottom which can have all sorts of types of reliefs).

In practice, this results in the arrival at the receiver of numerous replicas
25 of the signal emitted, each having at a given instant its own amplitude, phase, delay and frequency shift.

To this should possibly be added a frequency shift due to the relative radial speed of the corresponding parties (Doppler effects) as well as a pseudoperiodic frequency shift due to the swell in the case where one at least of the
30 opposite parties is on the surface.



In certain cases, there is a need for almost perfect reliability of transmission. If it is a text, it is possible to tolerate several isolated errors, because they will be corrected automatically by the reader. When a binary file is involved (for example a JPEG image), the required is approximately error rate to 0, otherwise the
 5 image will be very degraded.

Moreover, the system is "wideband".

In practical applications, the bandwidth of the signal emitted is not negligible compared with the central emission frequency. The Doppler shift being proportional to frequency, the low frequencies have a smaller frequency shift than
 10 the high frequencies.

What is more, since the relative speed of the emitter and of the receiver is not always negligible with respect to the speed of sound in water (about 1500 m/s), a time dilation or contraction effect is observed, according to the sign of the relative speed.

15 For example, a message emitted for a duration of 10s will be received in 10.13 seconds if the separation speed is +10 m/s (36 km/h or about 20 knots) thereby posing synchronization tracking problems.

Systems of "spread spectrum" type, in which the useful flow rate is very low compared with the bandwidth used, are known from the prior art.

20 These systems consist in over-modulating (spreading) the useful binary train (at a few tens of bits per second) by another much faster binary train known to both corresponding parties in such a way that its bandwidth is at least several tens (if not hundreds) of times the band theoretically necessary.

By well known procedures for "correlation" and estimation of the
 25 frequency shift (Doppler compartment) the receiver attempts to despread the signal received by the known binary train so as to isolate one (or a few) of the replicas of the message having the best quality so as to decode the content thereof.

One of the drawbacks of systems of this type is their low spectral efficiency (wide band, low throughput) and the complexity of the systems for initial
 30 detection (acquisition) under non-trivial propagation conditions.

The invention relates to a method for transmitting data, characterized in that it comprises at least the following steps: emitting packets of at least two types: pure data (long packets), acknowledgments of receipt (acknowledgment) (short packets), each packet is formed of three components:

- a - an acquisition preamble, for presence detection and the joint determination of the initial values of the time shift and of the frequency shift,
- b - the data proper,
- c - a set of unmodulated fixed carriers making it possible to permanently estimate the frequency shift.

5 The acquisition preamble is, for example, formed of a set of pulses of finite duration spaced apart by at least a minimum duration T_g ; to transmit the data, in step b), the signal emitted consists of N regularly spaced carriers modulated independently and in a synchronous manner; the fixed carriers can have an
10 amplitude greater than those conveying the data.

 The pulses of the acquisition preamble are, for example, non-linear frequency ramps, rising or falling "hyperbolic chirps" whose characteristics are fixed by their duration and the extreme frequencies used (minimum and maximum).

 The pulses of the acquisition preamble can be amplitude modulated as a
15 function of the instantaneous frequency so as to obtain an almost "flat" frequency spectrum.

 Two types of pulses are used for example to distinguish between data messages and acknowledgment messages.

 It is possible to use a modulation of differential type, with 2 or 4 phase
20 states.

 Reference symbols of known phases are, for example, inserted at known positions.

 The phase reference symbols may have a higher power than the unknown symbols on condition that their phases are properly chosen.

25 It is possible to use a position code corresponding to a polynomial $P(d)$ such that the product $P(d) \cdot P(1/d)$ has coefficients of nonzero degree equal to 0 or 1.

 Binary codes, for example, are used.

 The method exhibiting the above characteristics is, for example, used for acoustic transmissions of data in a medium suitable for conveying said waves,
30 namely the underwater medium, air, rock, etc.

 The invention exhibits notably the following advantages:

- The proposed solution is of low complexity,
- It is based on one of the large categories of modems which have proven themselves in conventional radio transmissions, namely a parallel modem.

Other characteristics and advantages will be more apparent on reading the description which follows of an example given by way of wholly nonlimiting illustration together with the appended figures which represent:

- Figure 1 a diagram of the detection of signals in the case of a parallel modem,
- Figure 2, the structure of a data packet generated following the method according to the invention,
- Figure 3, an illustration of several collections of frequencies and of their distortion,
- Figure 4, in a time-frequency chart, the signal emitted, and
- Figures 5 to 13, several examples of synchronization patterns and the graphical representation of their autocorrelation .

In order to better understand the subject of the invention, the description which follows relates to an acoustic modem for the underwater transmission of data.

- The explanations can however apply in respect of devices for transmitting data in air using ultrasound waves. The operating principle of this modem is comparable with that of a parallel modem known to the person skilled in the art. The duration for which the phases/amplitudes are constant is called a symbol and has a duration T_s . A symbol is composed of two parts:

- A "useful" part of duration T_u , which conveys the information to be transmitted (defined by the choice of the phase and/or of the amplitude),
- A "guard time" of duration T_g whose role is to allow all the replicas of the signal to combine so as to give a stable and demodulatable signal of duration T_u .

- The duration of the symbol is simply the sum of T_u and T_g .

Figure 1 shows diagrammatically an exemplary use of such a modem for a channel with 4 distinct paths.

- This figure reveals that, so long as the difference in the arrival times of the various replicas remains less than T_g , there always exists a signal portion of minimum duration T_u that can be processed by the receiver.

Moreover, the "tailoff" of the n th symbol has a maximum duration of T_g and will therefore be superimposed on the start of the perturbed part of the $n+1$ th symbol without disturbing the latter.

The frequency offset between carriers is a multiple of the inverse of T_u , i.e. $dF = k/T_u$. This is the condition whereby, when the receiver is properly synchronized, the signals detected on the N carriers are completely independent of one another.

5 The modem and the method according to the invention rely notably on the following idea: transmission is effected through packets of fixed or variable duration that is optimized according to the system assumptions which define in particular the range of the emitters/receivers therefore the maximum duration of propagation.

10 The invention relates notably to a system for acoustically transmitting underwater data comprising at least one module suitable for emitting packets (bursts) of at least two types: pure data (long packets), acknowledgments of receipt (acknowledgments, short packets).

Each packet of long packet type or of short packet type is formed of three
15 components:

- a - an acquisition preamble, 1, for presence detection and the joint determination of the initial values of the time shift and of the frequency shift; this initial part intended for receiver lock-on makes it possible to define the instant of arrival of the message and its global frequency shift; this acquisition preamble is formed of a series of pulses of shapes and instants of emission that are known to the receiver,
- 20 b - the data proper, 2; part during which the receiver must at one and the same time continuously adjust its evaluation of the Doppler shift and its evaluation of the instant of arrival of the message and attempt to demodulate the data received,
- 25 c - a set of unmodulated fixed carriers, 3, making it possible to permanently estimate the frequency shift.

A series of pulses is emitted at very precise instants so as to guarantee optimal acquisition.

30 In the case where very reliable transmission is required, two types of message are envisaged:

- Pure data messages, conveying the useful information,

- Acknowledgment of receipt messages, intended to indicate to the emitter whether reception was performed correctly so that it can retransmit the parts of the message which have been poorly received.

5 a - The acquisition preamble 1 is formed of a set of pulses 4 of finite duration spaced apart by at least a minimum duration T_g .

These pulses are for example rising or falling non-linear frequency ramps ("hyperbolic chirps") whose characteristics are fixed by their duration and the extreme frequencies used.

10 These pulses are amplitude modulated as a function of the instantaneous frequency so as to obtain an almost "flat" frequency spectrum.

The choice of the nature and position of each pulse is, by construction, known to the receiver and must be optimized to obtain the best performance. Optimization is for example carried out by simulation, by testing all the possibilities
15 and retaining the best one or best ones.

b - The data are transmitted according to the well-known method of the parallel modem which assumes that the signal emitted consists of N regularly spaced carriers modulated independently and in a synchronous manner (symbols).

20 The data comprise reference symbols 5 and data symbols 6. The duration of the symbol is as previously T_s .

The modulation is of differential type, with 2 or 4 phase states according to the robustness required.

At regular intervals are disposed symbols whose phases are fixed and
25 known so as to initiate (or reinitiate) the differential demodulation. These phases are optimized so as to obtain a quasi-constant amplitude of the signal emitted, thereby making it possible to temporarily increase the amplitude of the individual carriers so as to obtain "solid" references.

The phases giving the best result follow a quadratic law as a function of
30 frequency.

c - The fixed carriers are of greater amplitude than those conveying the data. This is highly recommended so as to limit the influence of the neighboring carriers on the quality of estimation of the frequency shift.

Their phases are optimized to minimize the "peak factor" of the whole set (ratio of the maximum instantaneous power to the mean power).

Various types of modulation and synchronization patterns that can be used will now be detailed.

5

Modulation type

Innumerable modulation systems of variable complexities and flow rate exist which can be used in the method and the system according to the invention. The expression "modulation system" is understood to mean a method which, on the basis of a binary train, unambiguously defines the amplitude and the phase to be applied to a given carrier at a given instant.

In this exemplary implementation, the signal received (i.e. its demodulatable part) possibly being the superposition of a large number of replicas all having independent phases and amplitudes, neither the value of the amplitude nor that of the phase are significant, since it is in practice impossible to estimate the gain (complex: gain and phase shift) of the channel at each symbol and at each frequency.

On the other hand, if the rate of variation of the gain and of the delay of each path varies little from one symbol to another, it is possible to utilize the phase difference between two successive symbols.

A differential phase modulation will therefore be used:

- either with 2 states if the channel is highly perturbed (phase variation of 0 or 180°),
- or with 4 states (phase variation of 0, +90°, -90° or 180°) if it is less so.

For N data carriers, there will thus be N or 2 N new bits at each symbol.

If the guard time T_g is equal to the useful duration ($T_g = T_u$) this corresponds (for 2 states) to a raw rate of N bits in a symbol duration T_s in a bandwidth of around N/T_u , i.e. 0.5 bits/s per Hz: a signal with 3 KHz of band will be able to convey at most 1.500 b/s (.3000 b/s for 4 states).

Of course, the net rate will be smaller than that announced above because of the packet-based emission, and of the essential addition of error detector/corrector codes to the useful data and of ancillary signals (packet number, etc.) that are highly protected.

Note that it is necessary to have a reference initial symbol for which all the phases are fixed so as to initiate the demodulation process which will consist in measuring the phase difference between two successive symbols (on a given carrier) so as to deduce therefrom the information emitted.

- 5 If required, this reference symbol may be repeated at regular intervals so as to "retune" the receiver.

Synchronization pulses

10 Within the framework of the example with regard to underwater transmission (wide band), the initial synchronization is based on the emission of pulses modulated in frequency and in amplitude in such a way that:

- (1) the frequency spectrum is as regular ("flat") as possible,
 (2) the detection is always of the same quality that is to say always gives a maximum amplitude as detector output, whatever the Doppler shift with the
 15 associated temporal contraction/dilation effect.

Condition (1) leads naturally to the use of a signal which is a frequency "ramp", that is to say the signal traverses the entire band of the frequencies used (from F0 to F1). This type of signal is commonly dubbed a "chirp" and often used in the field of radar.

- 20 Condition (2) requires the employment of a non-linear frequency variation called a "hyperbolic chirp" where the value of the frequency is a hyperbolic function of time and not a linear function as in simple chirps.

This function $f(t)$ is the following:

$$25 \quad f(t) = \frac{F_0 F_1 T}{F_0 t - F_1 t + F_1 T}$$

where T is the duration of the pulse emitted less than or equal to T_u

As the signal does not sweep all the frequencies between F0 and F1 at a constant rate, its spectral power density is not constant and therefore requires a complementary amplitude modulation to obtain a flat spectrum.

- 30 The instantaneous amplitude of the signal will therefore be higher just where the frequency variation is fastest.

It is easily shown that the amplitude must be proportional to the square root of the derivative of the frequency with respect to time, i.e., here, very simply proportional to the instantaneous frequency.

$$5 \quad \sqrt{\frac{\partial f(t)}{\partial t}} = \frac{\sqrt{F_0 F_1 | - F_0 + F_1 | T}}{|F_0 t - F_1 t + F_1 T|} \alpha f(t)$$

Presence detection is done by correlating the signal received with its replica limited to the frequency span which is systematically received whatever the Doppler shift.

Figure 4 shows the time-frequency chart of the signal emitted, with $F_0 =$
 10 1500 Hz, $F_1 = 5000$ Hz and $T = 40$ ms. It also shows the charts of the signal received at 50 m. for a relative speed of +50 m/s and -50 m/s. The Doppler shift coefficient δ is dependent on this relative speed and equals 0 if it is zero. Its exact value is:

$$\delta = \frac{v_r(R) - v_r(E)}{C - v_r(R)}$$

C : speed of sound in water

$v_r(E)$: radial speed of the emitter

$v_r(R)$: radial speed of the receiver

Reference frame: the water, assumed motionless

15

The thick curve in triplicate is the signal which remains unchanged whatever the frequency shift, and which is therefore used as reference in the acquisition correlators charged with individually processing each pulse.

20 It should be noted that if the values of F_0 and F_1 (falling chirp) are exchanged, it suffices to exchange the start and end of the pulses to get the result.

Other beneficial point: the intercorrelation between the rising chirps ($F_1 > F_0$) and the falling chirps ($F_0 > F_1$) is particularly weak, thereby making it possible to very easily discern the two types of pulses.

25

Synchronization pattern

First of all, the pulses must be spaced apart by at least one duration T_g to avoid the overlapping of the responses of the correlators of the receiver at two successive pulses.

5

Position code

One of the possible variants is a "position code" having an aperiodic autocorrelation equal to 0 or 1 everywhere except at the instant of synchronization where this autocorrelation equals N if there are N pulses.

10

Such a code can for example be represented by a polynomial of the type:

$$P(d) = 1 + d^4 + d^9 + d^{15} + d^{22} + d^{32} + d^{34}$$

where the operator d^n corresponds to a pulse at position n . This code can also be represented in graphical form (Figure 5).

As regards its autocorrelation, the simplest representation is graphical (Figure 6). It clearly shows the main correlation spike on which a good detection will be made, knowing that all the side lobes are negligible.

This autocorrelation is the graphical representation of the product $P(d)P(1/d)$ which models the correlation process to be performed.

A good position code corresponds for example to a polynomial $P(d)$ such that the product $P(d)P(1/d)$ has coefficients of nonzero degree equal to 0 or 1.

The distinction between the two types of messages (message containing the data or else acknowledgment message) will be able to be made by using either rising chirps only, or falling chirps only.

To improve performance, it is possible to accept slightly higher side lobes:

25

$$P(d) = 1 + d + d^3 + d^6 + d^{12} + d^{13} + \dots + d^{35}$$

as with (13 nonzero coefficients, therefore correlation spike equal to 13)

representable by Figure 7 and whose autocorrelation is as follows (max. 3 side lobes) Figure 8.

30 Binary codes

Unique sequence

Another possibility is to make use of a binary sequence having excellent

autocorrelation properties.

In this case, the pulses are emitted at regular intervals.

The 0 bits of the sequence result in chirps of a given type, and the 1 bits in chirps of the other type.

- 5 It is possible to take as example a Barker sequence of 13 bits, constituted thus:

$\{0, 1, 0, 1, 0, 0, 1, 1, 0, 0, 0, 0, 0\}$

Or, in another form:

$\{-1, +1, -1, +1, -1, -1, +1, +1, -1, -1, -1, -1, -1\}$

Its autocorrelation then has the form of the signal of Figure 9.

- 10 If this same sequence is emitted while inverting all the bits (by exchanging rising and falling chirps), the output of the correlator is inverted, as in Figure 10.

It is then possible to emit either the original sequence, or the inverted sequence to distinguish the two types of messages as a function of the polarity of

- 15 the global correlation spike.

Pair of sequences

There exists another possibility which consists in utilizing two distinct sequences having excellent autocorrelation and intercorrelation properties.

- 20 For example, the following sequences (again 13 bits)

Sequence A = $\{-1, +1, -1, +1, +1, -1, +1, +1, +1, -1, -1, -1, -1\}$

Sequence B = $\{-1, -1, +1, -1, -1, +1, -1, -1, -1, +1, +1, +1, -1\}$

Their autocorrelation and intercorrelation are as follows.

- Figure 11 corresponds to the autocorrelation of A, Figure 12
25 corresponds to the autocorrelation of B and Figure 13 to the intercorrelation of A and B.

The emission of one or the other sequence will make it possible to distinguish between the two types of messages that are possible.

- 30 **Estimation of the frequency shift**

Having regard to the variability of the channel, the estimation of the instantaneous frequency shift, performed within the framework of the present invention, relies on a "diversity" effect which consists in using a collection of P unmodulated carriers, distributed almost regularly throughout the band of the signal,

instead of some of the existing carriers (to preserve orthogonality). P must be small compared with N (of the order of 10% or less) so as not to overly decrease the useful throughput of the link.

This guarantees that if a few carriers are of low level, there will
5 practically always be others of sufficient level to compensate.

Moreover, since the estimation of the common frequency shift has to be strongly filtered, the shift estimation carriers will finish slightly after the message itself to compensate for the delay due to the filtering.

It is not essential to make them begin before the start of the message,
10 which is the synchronization preamble previously described. Specifically, it has been rendered insensitive to the Doppler by virtue of the hyperbolic chirps and only the END thereof has to be detected, the moment at which a good estimation of the frequency is then available.

CLAIMS

- 1 - A method for transmitting data, characterized in that it comprises at least the following steps: emitting packets of at least two types, pure data, and
5 acknowledgment of receipt messages, each packet is formed of three components:
- a - an acquisition preamble, (1) for presence detection and the joint determination of the initial values of the time shift and of the frequency shift,
 - b - the data proper (2),
 - c - a set of unmodulated fixed carriers (3) suitable for permanently estimating
10 the frequency shift.
- 2 - The method as claimed in claim 1, characterized in that:
- a - the acquisition preamble is formed of a set of pulses of finite duration spaced apart by at least a minimum duration T_g ,
 - 15 b - to transmit the data, a signal consisting of N regularly spaced carriers modulated independently and in a synchronous manner is emitted ,
 - c - fixed carriers of greater amplitude than those conveying the data are used.
- 3 - The method as claimed in claim 2, characterized in that non-linear frequency
20 ramps, rising or falling "hyperbolic chirps" whose characteristics are fixed by their duration and the extreme frequencies used (minimum and maximum), are used for the pulses of the acquisition preamble.
- 4 - The method as claimed in claim 2, characterized in that the pulses of the
25 acquisition preamble are amplitude modulated as a function of the instantaneous frequency to obtain an almost "flat" frequency spectrum.
- 5 - The method as claimed in claim 1, characterized in that two types of pulses are used to distinguish between data messages and acknowledgment messages.
30
- 6 - The method as claimed in claim 1, characterized in that a modulation of differential type, with 2 or 4 phase states, is used.

7 – The method as claimed in claims 1 and 6, characterized in that reference symbols of known phases are inserted at known positions.

5 8 – The method as claimed in claim 7, characterized in that reference symbols of phases having a higher power than the unknown symbols are used.

9 - The method as claimed in one of claims 1 or 2, characterized in that a position code corresponding to a polynomial $P(d)$ such that the product $P(d) \cdot P(1/d)$ has coefficients of nonzero degree equal to 0 or 1 is used.

10

10 – The method as claimed in one of claims 1 to 2, characterized in that binary codes are used.

11 – The use of the method as claimed in one of claims 1 to 10 with acoustic
15 transmissions of data in a medium suitable for conveying said waves, namely the underwater medium, air, rock, etc.