

THIS SHEET HAS BEEN
REPLACED

OK! pat.

OERLIKON CONTRAVES AG, Birchstrasse 155, CH-8050 Zürich / Switzerland

5

This Sheet Has Been Replaced



Case 97-C172/SG

10

Singapore

15

20

PROJECTILE AND METHOD FOR PRODUCING IT

FIELD OF THE INVENTION

25

The invention relates to a projectile with a jacket and a projectile body, which is arranged in the jacket and maintained in place by a centering device and whose diameter from front to back is the same or increasing, and to a method for producing it.

BACKGROUND OF THE INVENTION

30

Such long known projectiles, for example steel jacket projectiles, have a jacket of steel and a projectile core or respectively a projectile body made of hardened lead or, with so-called tipped projectiles, a projectile core or respectively a projectile body of steel. Other projectiles, such as the hard core projectiles used for antitank operations, for example, consist of a very hard and heavy armor-piercing projectile or respectively armored core and a coat of soft steel. Projectiles are also known, whose jacket consists at least partially of a suitable plastic material.

35




With some of these projectiles, wherein as a rule the projectile body fills the entire jacket, variations in shape or size of the core or respectively of the projectile body of the identical caliber or respectively jacket are hardly possible. Other projectiles, by means of which it would be possible to equip identical jackets with different projectile bodies and in this way to obtain different projectiles, are comparatively expensive to produce.

For example, French patent publication **FR 1 242 187** describes a projectile with a projectile body, a jacket consisting of a projectile tip and a projectile casing fastened on the exterior of the projectile tip, and a sealing body closing off the jacket at the rear and extending around the rear area of the projectile body. The diameter of the projectile body is approximately zeppelin-shaped, which means that initially it increases from the front to the back and decreases again later. It is therefore not possible to first produce the jacket and to subsequently equip it with the projectile core, which would be desirable for producing the same jackets in large series in order to subsequently produce different projectiles from them by equipping them with different projectile bodies. In particular, it is not possible to produce the projectile tip by injection molding.

A projectile is known from French patent publication **FR 812 377**, in connection with which it would be possible to equip the same jackets with different projectile cores, depending on the intended use. This projectile has a projectile body, centered at the front by a ring, and a jacket surrounding it, which is closed at the back by a metallic sealing body which extends around the projectile body in its rear area. The sealing body is intended above all to constitute additional mass, i.e. should be correspondingly heavy, and therefore must be made of metal. The jacket comprises the projectile tip and the projectile casing formed integrally with the projectile tip, and is also made of metal. The disadvantage of this projectile essentially lies in that its manufacture is comparatively elaborate, particularly since the jacket and the sealing body are both made of metal, so that it is not possible to produce one of the two elements or both elements by injection molding.

A further projectile with a jacket and a projectile body is known from US Patent **US 3,795,196**. The jacket consists of the projectile tip at the front, while the rear area of the jacket is formed by the sealing body which is simultaneously used for closing the jacket off at the rear. This sealing body is made of metal. This projectile does not have a projectile casing. Two centering rings are provided for centering the projectile core. The shaping would theoretically allow the equipping of the same type of jacket with different projectile bodies. But it would then be necessary to introduce the projectile bodies from the front into



the jacket. But because of the structure having centering rings, injection molding of the projectile tip and thus a cost-effective manufacture would not be possible.

Finally, a projectile is known from French patent publication **FR 2 238 137**, whose

5 projectile core is conical in its front half and cylindrical in its rear half. This projectile core is enclosed in a jacket. In principle, the shaping would permit the equipping of jackets of the

same type with different projectile bodies from the rear and in this way the production of different projectiles. The jacket of this projectile is formed by a projectile tip made of an

injectable material, more accurately of plastic, which is injection-molded on the metallic

10 projectile casing. The rear opening of the jacket is closed by a closure or sealing body,

which projects into the jacket and partially encloses the projectile core. In the front portion of

the projectile, the outer surface of the jacket is constituted by the projectile tip, and in the

rear portion of the projectile by the metallic sealing body.

15 In this respect the projectile is embodied the same as that of US Patent **US 3,795,196** but

has, in contrast to the projectile of the said US Patent **US 3,795,196**, a projectile casing.

The projectile casing, which rests against the projectile body in its central area, does not lie against the outer surface of the jacket, but is only used to form an indirect screw connection

between the projectile tip and the sealing body. A collar formed on the portion of the sealing

20 body projecting into the jacket is mainly used as the centering device. The main

disadvantage of this projectile lies in that its manufacture is elaborate for the following reason: the sealing body constitutes the rear portion of the outer surface of the jacket.

Therefore a guide ring will have to be fastened on the sealing body, so that it becomes

obvious to make the sealing body of metal. This has as a result that the centering

25 arrangement which must have precise dimensions, must also be made of metal, all of which is connected with a comparatively large outlay.

In summary it must be said that none of the known projectiles meet the requirements mentioned above regarding the use of different projectile bodies, on the one hand, and

30 simple manufacture, on the other.

OBJECT AND SUMMARY OF THE INVENTION

35 It is therefore the object of the invention to propose, based on the prior art in

accordance with French patent publication **FR 2 238 137**, a projectile of the type mentioned




at the outset, as well as a process for producing it, wherein the jacket can be equipped with projectile bodies of different types in accordance with the respective purpose, and which can be produced in a simple and therefore cost-effective manner.

5 This object is attained by means of the features of the characterizing portions of claims 1 or respectively 10.

10 With the novel projectile, the projectile body is embodied in such a way that its diameter from the front to the back is constant or increasing, but not decreasing, so that the projectile core can be introduced from the rear into the prefabricated jacket. The jacket consists of of a generally metallic projectile casing and a projectile tip of an injectable cured material, preferably of plastic, which is injection-molded to the projectile casing. A recess for the projectile core and a centering arrangement for guiding and fixing the projectile body in place are provided in the interior of the projectile tip. Thus the centering arrangement of the novel
15 projectile is provided on an injection-molded component, i.e. the projectile tip, so that the high cost of producing the centering arrangement on a metallic component are avoided. The outer surface of the jacket, which in the front part of the projectile is constituted by the projectile tip, is constituted by the metallic projectile casing in the rear part of the projectile, which in this way can be used as a solid fastening basis for fastening the guide ring. The
20 rear opening of the jacket, the rim of which is constituted by the projectile casing, is closed by means of a sealing body, which extends into the interior of the jacket and in the process extends partially around the projectile core.

25 Since the guide ring need not be fastened on the sealing body, preferably not only the projectile tip, but also the sealing body is made of plastic and is generally injection-molded after equipping the jacket, so that manufacturing and assembling are performed in one work step. A particularly advantageous projectile is obtained with an injection-molded sealing body, since by means of it the projectile body is completely fixed in place in the axial direction without it being necessary, for example, to perform a highly precise mechanical
30 production, or respectively also in cases in which the projectile core has been produced within comparatively large permissible variations.

35 In the course of producing the projectile, the projectile tip is injection-molded onto the projectile casing in a first step, and the projectile body is pushed into the centering device from behind until reaching a detent in a second step. The sealing body is applied in a third step. The latter is preferably produced by means of the introduction of an injectable material



into the interior of the projectile casing or respectively the jacket, after which the projectile body is completely surrounded in the front at the detent, laterally on its circumferential surface and in the rear at its end surface, by the injected material of the projectile tip and the sealing body.

5

The advantages attained by means of the invention are to be seen in that it is possible to use single- or multi-element projectile bodies of various types and sizes in the same jacket, wherein furthermore the proposed fabricating process is simple and time-saving, since in contrast to the projectile of French patent publication **FR 2 238 137** not only the projectile tip per se, but also the centering device is made of an injectable material, so that advantageous manufacturing costs can be achieved. If the sealing body is also made of an injectable material, which is easily possible and is even recommended, the manufacturing costs are further reduced.

10

15

The invention will be explained in more detail in what follows by means of two exemplary embodiments in connection with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

20

Fig. 1 represents a longitudinal section along the line I - I in **Fig. 2** through the projectile in accordance with the invention in a first embodiment,

Fig. 2 represents two semi-cross sections a, b through the projectile along the lines II - II and II' - II' in **Fig. 1**,

25

Fig. 3 represents a longitudinal section through the projectile along the line III - III in **Fig. 4** following a first method step,

30

Fig. 4 represents two semi-cross sections a, b through the projectile along the lines IV - IV and IV' - IV' in **Fig. 3**,

Fig. 5 represents a longitudinal section through the projectile in a second embodiment along the line V - V in **Fig. 6**,

35

Fig. 6 represents two semi-cross sections a, b through the projectile along the lines VI - VI and VI' - VI' in **Fig. 5**,



Fig. 7 represents a longitudinal section through the projectile in a variant of the second embodiment along the line V - V in **Fig. 6**,

Fig. 8 represents a longitudinal section through the projectile in a further variant of
5 second embodiment along the line V - V in **Fig. 6**.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 **Figs. 1 to 4** represent a projectile with a jacket **1**, which is formed by a projectile casing **2** and a projectile tip **3** fixedly connected therewith. In a first step of a fabricating process, the projectile tip **3**, which consists of an injected material, preferably of a highly heat-resistant, fiber-reinforced thermoplastic material, is injection-molded to the projectile casing **2**, wherein it penetrates projectile casing grooves **4** arranged in the interior of the projectile
15 casing **2** and is anchored in this way. The projectile tip **3** has a cylindrical recess **5**, which is coaxial in respect to the longitudinal projectile axis, for receiving and centering a projectile body **6**. Four channels **7**, offset by 90°, are provided in the recess **5**, whose bottom surface **8** is concentrically arched in the form of a partial circle in respect to the recess **5**. Four strips **9** are arranged on the rim of the recess **5** on the back of the projectile tip **3** and are offset by
20 90° in respect to the channels **7**, and are at a distance from each other which corresponds to the width of the channels **7**. In cross section, the strips **9** are arcuate and have a thickness corresponding to the depth of the channels **7**. The recess **5** is continued in the direction toward the projectile tip in a cylindrical recess extension **10**, which also extends coaxially in respect to the longitudinal axis of the projectile and has a lesser diameter than the recess **5** and, together with the recess **5**, constitutes a shoulder, which is intended to form an axial
25 detent **11** for the projectile core.

In accordance with the first exemplary embodiment, the projectile body **6**, which at times is also identified as the projectile core or penetrator, has a cylindrical shape with projectile
30 body edges **12**, **13**, rounded at the ends. The projectile body **6** has practically the same diameter as the recess **5** and on its exterior is provided with circumferential projectile body grooves **14**. In a second step of the fabricating process, the projectile body **6** is pushed through the projectile casing **2**, represented in Fig. 3, which is still open at the back, along the strips **9** into the recess **5** until it is in contact with the detent **11** at the shoulder provided
35 for this, and is maintained centered in this position.



A sealing body **15**, consisting of the same injectable material as the projectile tip **3**, i.e. preferably of thermoplastic material, is formed in a third fabricating step by injecting the injectable material into the projectile casing **2**, still open at the back. In the process, the injectable material also penetrates into the channels **7** and between the strips **9** of the projectile tip **3**, as well as into the projectile body grooves **14** of the projectile body **6**.

Thereafter, the projectile body **6** is completely enclosed in the injectable or respectively injected material at the front at the shoulder constituting the detent **11**, laterally, and in the back, and is firmly anchored in the jacket **1**. The injectable material furthermore also penetrates into further projectile casing grooves **16**, provided on the inside of the projectile casing **2**, and into rear projectile casing grooves **17**, by means of which the sealing body **15** is firmly anchored in the projectile casing **2**, as can be seen from *Figs. 1* and *2*.

In a manner known per se, a circumferential casing channel **18** for fastening a cartridge casing, not represented, and a circumferential ring channel **19** are provided in the rear area of the projectile casing **2**, wherein a guide ring **20** is disposed in the circumferential ring channel for guiding the projectile in a weapons tube.

In accordance with *Fig. 5*, the projectile body of the second embodiment consists of several partial projectile bodies **21** to **25**. As shown by way of an example, the partial projectile bodies **21** to **25** can consist of cylinder-shaped pellets which are lined up in the longitudinal projectile direction, the same as previously described by means of *Fig. 1*, and in the second fabricating step are inserted into the centering device formed by the recess **5** and the strips **9**, and which are enclosed in the injectable material and firmly anchored in the course of the formation of the sealing body **15** in the third step of the fabricating process.

However, it is also possible to use partial projectile elements of a different shape and number. The type or respectively the material of the partial projectile elements can also be different in general or within a projectile. For example, it is possible to use a frangible heavy metal for the partial projectile bodies **21** and **24**, a ductile heavy metal for the partial projectile bodies **22** and **25** and an incendiary composition for the partial projectile body **23**.

In accordance with *Fig. 5*, a guide ring **31** is embedded in a circumferential channel **32** of a projectile casing **30**. In the third step of the fabricating process, the guide ring **31** is formed integrally with the sealing body **33** by injecting the highly heat-resistant fiber-reinforced thermoplastic material into the projectile casing **30** open at the back. Several radial recess **34** are provided in the circumferential channel **32** for the exit of the injectable material into the latter from the projectile casing **30**. The fabricating costs of the projectile



can be lowered and the wear occurring in the weapons tube during firing can be reduced by means of a guide ring 31 manufactured and fastened in this way.

Two semi-cross sections a, b through the projectile along the lines VI - VI and VI' - VI' in
5 Fig. 5 are represented in Fig. 6.

Fig. 7 represents a variant of the form of the partial projectile bodies 21 to 25
represented in Fig. 5. For even more exact centering, the individual partial projectile bodies
21 to 25 have in this case, on the one hand, peg-shaped extensions 27 on the front faces,
10 and the end faces have corresponding depressions 26, into which the peg-shaped
extensions project. These extensions 27 and also the corresponding depressions 26 can be
simply manufactured and permit a simple assembly with perfect mutual centering. This
centering is all the more important, the better the projectiles need to be balanced.

15 Fig. 8 shows a further variant of the shape of the partial projectile bodies 21 to 25
represented in Fig. 5. Here, peg-like extensions 27A are provided on the end faces of the
pellet-shaped partial projectile bodies 21 to 25, which engage depressions 26A provided in
the front faces of the succeeding partial projectile bodies.



WHAT IS CLAIMED IS:

This Sheet Has Been Replaced



5 1. A projectile with a jacket (1) and a projectile body (6), which is arranged in the jacket (1) and maintained in place by a centering device and whose diameter from front to back is the same or increases, wherein the jacket (1) consists of a projectile casing (2) and a projectile tip (3) injection-molded on the projectile casing, and is closed off in the rear by a sealing body (15), which extends into the interior of the jacket (1) and in the process partially
10 extends around the projectile body (6),

characterized in that

the exterior surface of the projectile casing (2) forms the rear section of the exterior surface of the jacket (1), and the centering device (5, 9) in which the projectile body (6) is guided and maintained is arranged in the interior of the projectile tip (3).

15

2. The projectile in accordance with claim 1,

characterized in that

the projectile body (6) has a cylindrical shape and is provided with circumferential
20 projectile body grooves (14).

3. The projectile in accordance with claim 1,

characterized in that

25 the projectile body is formed of a plurality of partial projectile bodies (21 to 25).

4. The projectile in accordance with claim 3,

characterized in that

30 the partial projectile bodies (21 to 25) are cylindrical pellets, which are lined up with each other.

5. The projectile in accordance with one of claims 3 and 4,

characterized in that

35 the partial projectile bodies (21 to 25) consist of different materials.



6. The projectile in accordance with at least one of claims 3 and 5,

characterized in that

at least one of the partial projectile bodies (21 to 25) consists at least in part of ductile
5 and frangible heavy metal, and at least one of the partial projectile bodies (21 to 25) is an
incendiary composition.

This Sheet Has Been Replaced



7. The projectile in accordance with at least one of claims 3 to 6,

characterized in that

10 the partial projectile bodies (21 to 25) have means (26, 27; 26A, 27A) for mutual
centering.

15 8. The projectile in accordance with claim 1,

characterized in that

the centering device (5, 9) has a recess (5), which is coaxial in respect to the
longitudinal projectile axis and has four channels (7), offset by 90°, whose bottom surfaces
(8) are concentrically arched in the form of a partial circle in respect to the recess (5), and
20 that four strips (9) are arranged on the rim of the recess (5) on the back of the projectile tip
(3), which are offset by 90° in respect to the channels (7), and are at a distance from each
other which is equal to the width of the channels (7), wherein the strips (9) are arcuate in
cross section and have a thickness corresponding to the depth of the channels (7).

25 9. The projectile in accordance with claim 1,

characterized in that

the projectile tip (3) and/or the sealing body (15) are injection-molded of a preferably
highly heat-resistant fiber- reinforced thermoplastic material.

30 10. A method from producing the projectile in accordance with at least one of claims 1
to 9,

characterized in that

35 - in a first step the projectile tip (3) is injection- molded on the projectile casing (2),
wherein it is securely anchored in projectile casing grooves (4) arranged in the interior of the



projectile casing (2),

- in a second step, the projectile body (6, 21 to 25) is pushed into the centering device (5, 9) of the projectile tip (3) through the still open projectile casing (2), and

5 - in a third step the projectile casing (2), which is still open at its rear, is closed by the sealing body (15).

11. The method in accordance with claim 10,

characterized in that

10 the sealing body (15) intended for closing off the projectile casing (2), still open at the rear, is formed by the injection of injectable material, preferably plastic, into the projectile casing (2), wherein the plastic material penetrates into the channels (7) and between the strips (9) of the projectile tip (3), after which the projectile body (6, 21 to 25) is completely surrounded at the front at a detent (11), laterally on its circumferential surface, and at the
15 rear by the plastic material of the projectile tip (3) and the sealing body (15).

This Sheet Has Been Replaced

