



(51) International Patent Classification:

E03B 7/07 (2006.01) *E03B* 1/00 (2006.01)
F16L 55/00 (2006.01) *G01M* 3/28 (2006.01)
G05D 7/00 (2006.01)

(21) International Application Number:

PCT/AU2009/000402

(22) International Filing Date:

1 April 2009 (01.04.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2008901562 1 April 2008 (01.04.2008) AU
2008904936 23 September 2008 (23.09.2008) AU

(71) Applicant (for all designated States except US): **PREMIER-FOSTERS (AUSTRALIA) PTY LIMITED**
[AU/AU]; 17/2 Richard Close, North Rocks, NSW 2151 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **FOSTER, Geoffrey, Frederick** [AU/AU]; 14 Venetta Road, Glenorie, NSW 2157 (AU).

(74) Agent: **SPRUSON & FERGUSON**; Gpo Box 3898, Sydney, NSW 2001 (AU).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: FLOW CONTROL DEVICE AND FLOW CONTROL METHOD



(57) Abstract: A water flow control device (27) that may, for example, deliver water to a domestic dwelling (10). The device (27) includes a plurality of valves, which may include three valves (12, 13, 14). The valves (12, 13) are connected to an outlet conduit (16) by means of a flow restriction device (15). The valves (12, 13, 14) are electronically operated and are controlled by a programmable logic controller (PLC) (17).