

(D)

2160259

- 1 -

FLUID-TIGHT SLIDE FASTENER

The present invention relates to a slide fastener, and more particularly to a fluid-tight slide fastener stringer.

There are known various fluid-tight slide fasteners. One such fluid-tight slide fastener includes a stringer tape which supports edgewise a row of continuous coupling elements on one side and a sealing member on the other side. For example a fluid-tight slide fastener of this type is disclosed by U.S. Patent No. 3501816 as shown in Figure 9 of the accompanying drawings. This slide fastener produces a seal when a pair of rows of coupling elements 102 are coupled underneath the coplanar stringer tapes 101 urging opposed sealing lips 104 to bear against each other above the tapes 101. Each of the sealing lips 104 formed into a wedge-shaped projection is raised from a general plane of the coplanar tapes 101 with the result that the sealing lips 104 necessarily bear upon each other with a sealing force directed at a level

remote from a level at which the coupling elements 102 are intermeshed together. In this mutually compressed relation, only the tapes 101 support the opposing sealing lips 104. The supporting tapes 101, however, fail to support the same strongly enough to keep the sealing force unidirectional and parallel to the general plane of the tapes to obtain most effective seal against leakage.

Another type of fluid-tight slide fastener is disclosed by Japanese Utility Model Publication (Jikkosho) 55-31939. This prior fastener as shown in Figure 10 includes a pair of stringer tapes 201, each having a row of discrete coupling elements 203 each bracketing a longitudinally folded edge 202 of the tape 201 and a sealing member 204 underlying the latter for thereby allowing the sealing members 204 to be sandwiched tightly in between the elements rows and the folded tape edges. However, each one of the discrete coupling elements 203 has a bracketing structure 203a which adds to the cost of manufacture of the slide fastener products and also impairs the appearance of an article to which the fastener is attached.

According to the present invention, there is provided a fluid-tight slide fastener comprising a pair of fastener halves each including:

- (a) a support tape;
- (b) a row of continuous coupling elements extending along an innermost longitudinal edge of said tape on one side of the latter;
- (c) a connecting means securing said row of coupling elements to said tape;
- (d) an elastomeric seal member extending on the other side of said tape in a substantially coextensive relation, and having a longitudinal contact edge portion

transversely projecting beyond a median plane of symmetry defined by said slide fastener halves in engagement, said plane being perpendicular to a general plane of said seal member, said longitudinal contact edge portion being adapted to bear against the opposed corresponding longitudinal contact edge portion of the mating fastener half;

(e) said support tape including a longitudinal reinforced and/or bulked-up edge portion substantially at or adjacent said longitudinal edge of said tape for supporting said contact edge portion of the seal member; and

(f) said connecting means having a portion extending along and adjacent to said longitudinal reinforced and/or bulked-up edge portion and remotely from said longitudinal contact edge portion of said seal member so that said connecting means holds said longitudinal reinforced and/or bulked-up edge portion in place to prevent the same from being displaced remotely from said row of coupling elements when the pair of fastener halves are coupled together for closing the slide fastener.

It is believed possible by means of the present invention to provide a slide fastener producing an effective fluid-tight seal even when the same has a relatively simple structure including known continuous coupling elements stitched thereto by a conventional stitching means.

The invention will be described by way of example with reference to the accompanying drawing, wherein:-

Figure 1 is a schematic transverse cross-sectional view of halves of a fluid-tight slide fastener embodying the invention, showing the halves
5 separated from each other;

Figure 2 is a schematic transverse cross-sectional view similar to Figure 1, showing the halves coupled;

Figure 3 is a schematic transverse cross-sectional view of another embodiment of the
10 invention, showing the halves separated;

Figure 4 is a schematic transverse cross-sectional view similar to Figure 3, showing the halves coupled;

15 Figure 5 is a point diagram illustrating a warp-knitted fabric structure of the support tape of Figures 1 and 2.

Figures 6 through 8 are schematic transverse cross-sectional views of the fluid-tight slide fastener
20 of Figures 1 and 2, illustrating manufacturing processes of the same; and

Figures 9 and 10 are schematic transverse cross-sectional view of prior fluid-tight slide fasteners.

25 The present invention is particularly useful when embodied in fluid-tight slide fasteners such as embodiments shown in the

accompanying drawings.

In Figure 1, a pair of slide fastener halves or stringers 10, 10 are substantially mirror images of each other and lying in a general plane. To clarify the description of the invention, only one of the stringers is described hereinafter.

The fastener stringer 10 includes a stringer tape or support tape 11 supporting on one side thereof a row of continuous coupling elements 12 extending along its innermost longitudinal edge and an elastomeric sealing member 15 lying substantially coextensively with tape 11 on the other side thereof.

The support tape 11 is made of a warp-knitted fabric having alternating ridges (or wales) 18 and grooves 19 extending longitudinally in a parallel relation to one another on one side of the tape 11. The warp-knitted fabric is diagrammatically illustrated in Figure 5. An innermost one of the ridges 18' is substantially at or adjacent to the innermost edge of the tape 11.

The row of continuous coupling elements 12 formed into a continuous helical coil includes a core 13 extending therethrough, and is stitched securely to the support tape 11 by means of threads 14 running via the core 13 in and out of the tape 11. The threads 14 have a portion 14' disposed adjacent to the innermost ridge 18', namely in a groove 19 defined between the

ridge 18' and another ridge 18 adjacent to the latter, so that the threads 14 hold the ridge 18' in place with respect to the row of the coupling elements 12, and enable the ridge 18' to support obliquely the coupling
5 elements row 12.

The sealing member 15 is made of an elastically deformable material such as silicon rubber, butyl, neoprene, polyurethane rubber or other elastomeric material. •

10 The sealing member 15 is secured substantially coextensively to the tape 11 and extends over the ridge 18' for providing a longitudinal contact edge portion 16 projecting transversely beyond a vertical median plane of symmetry P of the interengaged stringers 10.
15 The contact edge portion 16 is thus reinforced by the ridge 18' supporting on its innermost side the same. The contact edge portions 16 of the stringers 10 are adapted to abut on each other to produce a tight seal therebetween when the stringers are coupled together as
20 shown in Figure 2. Each one of the contact edge portions 16 is transversely reinforced and bulked-up (that is, made more bulky or thicker) by the ridge 18' of the tape.

Figure 5 diagrammatically shows a warp-knitted fabric of which the support tapes 11 are made. The warp-knitted fabric
25 consists of a pair of base portions or webs 30 and a connector portion 11a extending longitudinally therebetween. Each one of the base

portions 30 includes a plurality of threads 31 knitted as tricot stitches, a plurality of threads 32 knitted as chain stitches, and a plurality of inlaid weft threads 33 running transversely of the threads 32,33 across the tape. The threads 31, 32 run longitudinally to form in combination a plurality of wales 18 each including a succession of stitch loops of the threads 31, 32. Each one of the weft threads 33 runs over respective five wales 18 in alternatively reversed directions and looping in either one of the most remote pair in five wales 18. The innermost adjacent pair of wales 18' respectively includes threads 32' each having a higher degree of strength than the other threads 31, 32, 33 so as to solidify the wales 18' defining the ridges of the tapes 11. The connector portion 11a includes a connector thread 34 extending longitudinally in a zigzag fashion via the innermost wales 18' of the base portions 30 for interconnecting the same to each other. The connector portion 11a is free from wales, and thus thinner than the base portions 30. The base portions 30 in Figure 5 correspond to a pair of the support tapes 11 in Figure 1, respectively. With this warp-knitted fabric structure of a high stitch-density, the wales 18' per se are strong enough to suppress an anti-pressing force of resiliency in the sealing material at the contact edge portions 16.

When the stringers 10 are coupled together as

- 8 -

shown in Figure 2 by interengaging both rows of coupling elements 12, the opposed longitudinal edges or ridges 18' of the tapes 11 are forced to move toward each other, whereupon the ridges 18' and the contact edge portions 16 supported thereon are hindered from moving away from the coupling elements rows 12, in other words upwardly as viewed in Figure 2. As a result, the edge ridges 18' of the tapes supportably push the respective contact edge portions 16 in an abutment relation parallel to the general plane of the tapes 11 and hence of the stringers 10 for thereby bearing against each other to produce a fluid-tight seal in the median plane P. At this time longitudinal edge portions 16 bulge sideways to form raised portions 17 ensuring a tight seal between the (Figure 2) sealing members 15 in the median plane P.

Figure 3 shows another embodiment similar to the stringers of Figures 1 and 2, and one difference therefrom is a structure of the support tapes 21. The tape 21 is made of a woven fabric woven of a plurality of warp threads and a plurality of weft threads (not shown), and has a longitudinal ridge 28 having a function similar to the ridge 18' of the stringer 10 of Figure 1. The ridge 28 is defined by one of the warp threads 28 extending longitudinally through the weft threads of the tape 21. The warp threads 28 have a

thickness greater than that of the other warp threads. Alternatively, the ridge may be formed into a cord extending similarly through the weft threads. The row of coupling elements 12 is secured similarly to the
5 tape 21 by means of the threads 14, a portion of which is located adjacent to the ridge 28 so that the threads 14 hold the ridge 28 in place and prevent the same from being displaced remotely from the coupling elements row 12 when the stringers 20 are coupled together. Thus the
10 tapes 20 also provide the ridges 28 supporting the opposed contact edge portions 28 through the threads 14 stably enough to force the latter to bear upon each other as shown in Figure 4. Therefore the stringers 20 also produce a stable fluid-tight seal when coupled
15 together.

Figures 6 through 8 illustrate a manufacturing process of a fluid-tight slide fastener embodying the invention.

In Figure 6, a pair of coplanar support tapes 11
20 having the opposed longitudinal ridges respectively on one sides thereof are laterally continuous to each other via a connector portion 11a. The pair of continuous coupling elements 12 are stitched to the other sides of the tapes respectively by means of the
25 stitching threads 14 along the respective innermost edges of the tapes 11. The threads 14 are partially disposed adjacent to the respective ridges 18'.

- 10 -

Then as shown in Figure 7, the sealing material 15 is attached to all the surface of the other side of the coplanar continuous tapes 11. The tapes 11 with the sealing member attached thereto are cut into a pair of fastener halves or stringers 10 by a cutter means C as shown in Figure 8 with the result that each one of the separate stringers 10 provides the longitudinal contact edge portion 16 projecting beyond the vertical median plane P as shown in Figure 8. At this time, fragments of the connector threads 34 remained in the tapes 11 may be unremoved as the embodiment shown in Figure 1.

In each one of the embodiments described above, the support tapes have opposed longitudinal ridges which are reinforced and/or bulked-up and are disposed adjacent to the corresponding contact edge portions of the sealing material. With this arrangement, the slide fastener provides the ridges of the tapes deliberately supporting the contact edge portion strongly enough to suppress an resilient force normally urging to recover the original form of the contact edge portion and thus pushing back the latter in the opposite direction, with the result that the same are kept to bear against each other for producing a fluid-tight seal therebetween.

Advantageously, these embodiments may incorporate conventional continuous coupling elements to be stitched to the tape, for thereby eliminating a

- 11 -

neccessity of relatively complicated structure such as
the coupling elements 203 having bracket portions 203a
of the prior fastener of Figure 10. Therefore the
slide fasteners each have a simple
5 structure which allows for an economical production of
effective fluid-tight slide fastener.

10

15

20

25



23

CLAIMS:

1. A fluid-tight slide fastener comprising a pair of fastener halves each including:

(a) a support tape;

(b) a row of continuous coupling elements extending along an innermost longitudinal edge of said tape on one side of the latter;

(c) a connecting means securing said row of coupling elements to said tape;

(d) an elastomeric seal member extending on the other side of said tape in a substantially coextensive relation, and having a longitudinal contact edge portion transversely projecting beyond a median plane of symmetry defined by said slide fastener halves in engagement, said plane being perpendicular to a general plane of said seal member, said longitudinal contact edge portion being adapted to bear against the opposed corresponding longitudinal contact edge portion of the mating fastener half;

(e) said support tape including a longitudinal reinforced and/or bulked-up edge portion substantially at or adjacent said longitudinal edge of said tape for supporting said contact edge portion of the seal member; and

241



(f) said connecting means having a portion extending along and adjacent to said longitudinal reinforced and/or bulked-up edge portion and remotely from said longitudinal contact edge portion of said seal member so that said connecting means holds said longitudinal reinforced and/or bulked-up edge portion in place to prevent the same from being displaced remotely from said row of coupling elements when the pair of fastener halves are coupled together for closing the slide fastener.

2. A fluid-tight slide fastener according to claim 1, wherein said connecting means is made of threads.



- 14 -

3. A fluid-tight slide fastener according to claim 1, wherein said tape is made of a knitted fabric including a plurality of wales on at least said other side thereof, one of said wales providing at least a substantial part of said longitudinal reinforced and/or bulked-up edge portion of the tape.

4. A fluid-tight slide fastener according to claim 1, wherein said tape is made of a woven fabric including a warp thread thicker than the other threads of said woven fabric, said longitudinal thread providing said longitudinal ridge portion.

5. A fluid-tight slide fastener substantially as described with reference to and as illustrated in Figures 1 and 2 of the accompanying drawings.

6. A fluid-tight slide fastener substantially as described with reference to and as illustrated in Figures 1, 2 and 5 of the accompanying drawings.

7. A fluid-tight slide fastener substantially as described with reference to and as illustrated in Figures 3 and 4 of the accompanying drawings.
