

Description

Background of the Invention

The present invention pertains to global mobile communications and more particularly to a satellite cellular telephone and data communication system.

Present geostationary satellite communication systems allow point-to-point communication. That is, the satellite functions as a relay station or a "bent pipe". The satellite simply receives information from one point on earth and transmits it to another fixed point on earth.

One such point-to-point satellite communication system is shown in U.S. Patent 4,720,873. This system shows point-to-point communications through a satellite for network programming and advertising purposes.

Some basic multiplexing functions may be supplied within the satellites of a satellite communication system. One such system is shown in U.S. Patent 4,480,328. This patent teaches a satellite communication system in which the satellite is a relay station for TDMA multiplexed data.

The above-mentioned systems and other systems teach the use of a single satellite for communications from one point to another. These satellite systems show no selectivity or switching of data among a plurality of users.

Accordingly, it is an object of the present invention to provide a global low-earth orbiting multiple satellite cellular communication system which interfaces directly among a number of cellular telephone and data transmission equipped users and also interfaces these users to the public switched telephone network (PSTN).

From PROCEEDINGS OF THE IEEE, vol. 72, no. 11, November 1984, pages 1627-1636; K; BRAYER *et al.*:

"Packet Switching for Mobile Earth Stations via Low-Orbit Satellite Network" there is known a satellite communication system. Also, from PROCEEDINGS OF THE IEEE, vol. 75, no. 1, January 1987, pages 74-81;

R. BINDER *et al.*: "Crosslink Architectures for a Multiple Satellite System" there is known a satellite communication system. These two known systems are concerned with cross linking arrangements. Neither of these known systems is a cellular system, and neither of these known systems employs hand-off between cells.

Summary of the Invention

In accomplishing the object of the present invention, a novel satellite cellular telephone and data communication system is shown.

A satellite cellular telephone communication sys-

tem establishes communication among a plurality of users. This communication system includes satellite switches positioned in low-earth orbit. Wireless communication links couple the users to the satellite switches. The satellite switches establish a communication link between selected ones of the users.

Each satellite switch includes a hand-off arrangement for handing-off the communication link between satellite switches. Each satellite switch provides a number of cells for establishing and maintaining the communication link. Each satellite switch includes another hand-off arrangement for handing-off the communication link from one cell to another cell within the satellite switch.

Brief Description of the Drawings

FIG. 1 is a layout diagram depicting the satellite switching system configuration of the present invention.

FIG. 2 is a block diagram depicting the interconnection of the satellite switching units with its association mobile users and interconnection to the public switched telephone network.

FIG. 3 is a projection of the areas served by a plane of cellular satellite switches about the earth.

FIG. 4 is a block diagram of a data base arrangement for a satellite cellular communication system.

Description of the Preferred Embodiment

Referring to FIG. 1, a satellite configuration for the satellite cellular telephone communication system is shown. In this configuration, a number of satellites are shown in low-earth orbit. A number of satellites are placed in each orbiting plane. There are several orbiting planes (3 through 8) as shown which are highly inclined in nature and provide switching coverage for the entire earth.

This satellite cellular structure is somewhat analogous to the present day cellular mobile telephone system. In that system, cellular sites are fixed and users are mobile. As a user travels from one cell site to another, his telephone call is handed off from one cellular switching unit to another.

In the present invention, users are relatively fixed at any given time while the satellites, which are the cells, are in continuous movement. With a hand-held or mobile mounted cellular telephone, connection to one of the satellite switches shown in FIG. 1 is made directly from the hand-held mobile mounted or remotely fixed telephone to one of the nearest satellite switches. Each satellite is moving about the earth. As the satellite which originally acted as the switching unit for a particular user leaves a cell of that switch, the user's call is "handed off" to the appropriate adjacent cell. Adjacent cells may be cells within one satellite or cells of other satellites located either in a par-

particular orbiting plane or an adjacent orbiting plane. Users may "roam", but this roaming distance is relatively small compared to the traveling distance of the satellite switches.

Similar to the cellular mobile telephone system, the satellite cellular communication system provides spectral efficiency. This means that the same frequency may be simultaneously used by different satellite switches. Spectral efficiency is provided by the spatial diversity between the satellite switches and users.

The users may be located anywhere on a land mass, on the water or in the air at an altitude less than that of the low-earth orbiting satellites. For example, a person on one land mass could call a person on another land mass, a person on a boat or a person in an aircraft.

Low power hand-held mobile mounted or fixed radio telephones may be used in this system. The power requirement is less than 10 watts with present technology.

In this system, each satellite shown is a switching unit. Current satellite communication systems act primarily as a relay station or "bent pipe". That is, they provide fixed point-to-point communications. In the present invention, a switching function is provided within each of the orbiting satellites.

As previously mentioned, each of the orbiting planes of satellites is highly inclined in the preferred embodiment of the invention. Orbiting satellite planes with lower inclination are also workable. However, the lower inclination requires more satellite switching units and/or higher orbiting altitudes to achieve whole earth coverage than does the highly inclined orbiting satellite configuration.

In a preferred embodiment, highly inclined orbit configuration, it was found that satisfactory earth coverage could be accomplished with forty-eight (48) low earth orbiting satellites. These satellites could be arranged in six (6) highly inclined orbiting planes, eight (8) satellites per plane. Other configurations could be used. Other lower inclined orbiting arrangements would require substantially more satellites in order to achieve the same coverage of the earth as highly inclined configuration.

Each satellite contains a satellite switching unit, suitable antennas 11 (helical antennas for up/down links and lenses for cross links, for example) and an unfolding array of solar cells 12 along with storage batteries (not shown) connected to the solar cells to provide power for the switching unit. The satellite buses or vehicles themselves are low-earth orbiting satellites such as those commercially available. The satellites are put into orbit by a launching vehicle. When in orbit, the solar cell array is opened and the switching unit thereby activated. The satellites are then individually brought on line via standard telemetry, tracking and control (TT&C) channels to form the net-

work.

As shown in FIG. 1, a user A with a hand-held telephone goes off-hook. This request for a channel is received by a particular satellite 1, as shown in FIG. 1. A frequency channel is assigned to the user and the caller's desired number is then routed through the system. Each satellite is a distributed local processor and determines how switching of the call is to occur. Satellite 1 switches the call to the appropriate cell contained either within its own cell complement or to the appropriate satellite cell complement. The path is determined by each satellite switching unit until the call is received by satellite 2. Satellite 2 then routes this call to the particular hand-held user B shown in FIG. 1.

Although two hand-held users are shown, the users may be on the water, in a moving vehicle, airborne or part of a PSTN where the link is through a gateway. Each satellite is a local processor. The system determines to which appropriate satellite or cell the call is to be switched. Each satellite determines an optimal path from itself to the next appropriate satellite. These determinations may be made based upon the office code portion of the telephone number of the called user.

Each satellite typically may project four (4) or more cells or lobes onto the earth and contain four (4) or more corresponding cells for switching. These cells of coverage are achieved via antennas (helical typically) with fixed beam widths appropriate to the number of cells. Overlapping cells will be differentiated using present cellular techniques. These areas or lobes are shown in FIG. 3 for one particular plane of satellites about the earth. This figure depicts a high inclined orbiting satellite cellular switches. Each satellite determines the optimal path from it to the next satellite through which to route a particular call or data transmission. These satellite switches operate on data packets and therefore may transmit digital voice or data. Downlink and uplink data/digital voice is received on an FDM basis demodulated and then packetized for satellite-to-satellite communication.

FIG. 2 depicts the interconnection of a portion of one plane of satellites. In addition, the connection of the satellite to the satellite's corresponding mobile users and to the public switched telephone network is shown. Three satellites are shown. Satellite 40, Satellite 50 and Satellite 60. Satellite 40 is connected to Satellite 50 by link i. Satellite 50 is connected to Satellite 60 by link i+1. Satellite 60 is connected to the next sequential satellite of the plane (not shown) via link i+2. Satellite 40 is connected to the next preceding satellite (not shown) via link i-1. Each plane of satellites forms a ring of connected satellites around the earth.

As previously mentioned, the drawing of FIG. 2 shows one plane of the satellites. In addition, each satellite is connected to one or more satellites in other

orbiting planes. That is, each satellite is connected to a previous and next satellite in its orbiting plane and to one or more satellites in other orbiting planes.

The intersatellite links link i-1, link i, etc. may be implemented via data transmission on a microwave beam or via a laser beam. Existing technologies currently provide for such data transmission.

Connection between the satellites and its mobile users is achieved by beams j-1, and j+1, for example. These beams correspond to the lobes shown in FIG. 3 and to the switching cells mentioned above. These beams are achieved via the satellite up/down link antennas which provide communication to users via the users omnidirectional antenna. The limit on the number of users that a particular satellite may handle at one time depends on bandwidth allocated plus power available on the satellite. Typically this number may be 50,000 users per satellite.

Satellite 40 is shown connected to a trunk site or gateway 10 via beam j-1. Any satellite, such as Satellite 40, is capable of transmitting and receiving data from a gateway, such as gateway 10. This gateway link can be accomplished using the packetized data similar to the satellite-to-satellite links.

Gateway 10 includes units which interconnect to the public switched telephone network (PSTN) 20. All public switched telephone network users 30 are connected to the public switched telephone network 20. As a result of the satellite 40 being connected through gateway 10 to PSTN 20, a mobile user of the satellite cellular system which is connected directly via a beam to a satellite may transmit voice or data via the satellite structure (satellite-to-satellite via corresponding links), through gateway 10, through the public switched telephone network 20 to selected users of the PSTN 30 or vice versa.

Each satellite provides several data transmission beams. These data transmission beams project the lobes of coverage shown in FIG. 3 which depicts four beams. Each satellite projects four such lobes. As shown in FIG. 2, a satellite may use one or more of its beams to provide interface to a gateway. At least one beam is required for establishing a link between each gateway and the satellite. Typically a satellite links to only one gateway. One gateway provides sufficient trunking to interconnect a number of mobile users to the public switched telephone network 20.

Each satellite performs internal switching among its four beams or cells. This is analogous to intraoffice switching for conventional telecommunication systems.

The up/down linking arrangement between the satellites and its mobile users or gateways via the beams may transmit and receive data in the range of approximately 2.1 to 3.9 GHz, for example. The present technology and band availability makes this a preferred data transmission range. However, the scope of the present invention is not limited to data transmis-

sion exclusively within this range.

As previously mentioned, the data (digital voice or data) is transmitted in packet form. As a result, high-speed data transmission as well as voice data transmission may be accomplished via the satellite system. Data transmission rates, given the present available bandwidths, are at least 1200 baud. However, with extended bandwidth, substantially higher data rates can be achieved by this system.

FIG. 4 depicts one satellite switching unit 100 directly connected to mobile users 120 via beam 102. Satellite 100 is connected to data base computer 110 via beam 104. Satellite 100 is also connected to data base computer 130 via beam 106. This connection may be direct via a beam 106 as shown in FIG. 4 or indirect through other satellites to data base computer 130.

A mobile user might "roam" or travel in a home area. The home area may be a city, such as New York, Los Angeles, etc. The data base computer 110 contains all the information relative to each of its mobile users. As long as a particular mobile user is operating within his home area, all the available information concerning that user is available at the local home area data base computer.

If, for example, a home area user in Los Angeles travels to New York City and attempts to use his satellite cellular telephone for communication, the data base computer in the user's new area, New York City, is not aware of the existence of that user. If data base computer 110 is the mobile user's home area, Los Angeles, data base computer 110 has all the information for this particular mobile user. As a result, the mobile user would not be allowed to place calls because he was not recognized by his home area's data base computer.

In order to overcome this problem, each mobile user is periodically interrogated by the system as to its location so when he goes off-hook, his call for service can be recognized and routed. However, since the data base of a particular user is stored in his home area data base computer via the satellite system, the satellite system first interrogates the home area to determine that he is no longer there and to obtain the user's switching information. When that determination is made, the new home area's data base computer can be updated to include this "roaming" user. As a result, this user is then allowed to originate and receive calls in his new area. Because the satellite system interrogates the user's home data base computer to determine his location, the user can be found throughout the entire satellite system. Thus, the system provides the capability for finding "roaming" users and establishing communications with them.

To facilitate tracking of each mobile user, each mobile telephone provides a control signal which is periodically monitored so that when a subscriber originates a call, the nearest satellite can track him and

through the satellite network interrogate his home data base computer to determine his pertinent customer information. The mobile telephone may automatically indicate to the satellite network a new location for updating the data base computer. This control signal allows the incoming calls of "roaming" users to be validated via satellite-to-satellite linking to the home area's data base computer.

Each satellite in the satellite cellular communication system is self-navigating. That is, it uses the Global Positioning Satellite system (GPS) or time and ephemeris data from which to compute its location information. In addition, from the fixed location of the Global Positioning Satellite system or other vehicle, each satellite can determine its position and alter its course accordingly to stay within its proper orbit while providing switching services.

Each satellite may switch a call intrasatellite (within the particular switching unit or cell) or may connect the call via a microwave or laser links (link i, i+1, etc.) to another satellite within its plane or out of plane (adjacent). Each satellite may distinguish a particular telephone number and determine whether that number is within its own calling area or the area of another satellite. If it is within the area of another satellite, the call is cross-linked to the next appropriate satellite or cell which makes the same determination until the satellite serving that telephone number is reached. That satellite down-links to the particular mobile user sought to be called. Due to this structure, the satellite network provides a distributed nodal switching capability. Each satellite is a local switch for a particular area, but the area is constantly changing. Therefore, calls are handed-off as satellites move out of the range of a particular telephone user.

Various multiplexing techniques (i.e. FDMA, TDM CDMA, etc.) may be used to enhance the transmission capability between various satellites on the links as shown in FIG. 2.

Since the switching units of this system are orbiting the earth and relatively secure from tampering, this system provides the capability to support secure voice and data transmission via data encryption and decryption techniques commonly known in the art. Since the switching units enjoy the security of being hundreds of miles above the earth, the system also lends itself to military communication applications.

Claims

1. A satellite cellular communication system for communicating among a plurality of users comprising:
a plurality of satellite switching means (1, 2) positioned in low-earth orbit; and
link means (j, j+1) for coupling said users to one of said plurality of satellite switching means es-

establishing a communication link between selected ones of said users via said satellite switching means;

each of said plurality of satellite switching means including first means (40, 50, 60) for handing-off the communication link between said satellite switching means;

each of said plurality of satellite switching means including a plurality of cell means (40, 50, 60) for providing the communication link; and

each of said plurality of satellite switching means including second means for handing-off (40, 50, 60) the communication link from a first to a second cell means within the same satellite switching means.

2. A satellite cellular communication system as claimed in claim 1, said satellite switching means including: a plurality of satellite switching unit means (40-60) positioned surrounding the earth in low-earth orbit; and second link means (j) for permitting multi-directional communication between one satellite switching unit means and any adjacent satellite switching unit means.
3. A satellite cellular communication system as claimed in claim 2, said second link means including microwave communication means.
4. A satellite cellular communication system as claimed in claim 2, said second link means including laser communication means.
5. A satellite cellular communication system as claimed in claim 2, said satellite switching unit means including:
antenna means (11) coupled to said plurality of users for establishing communication between said users and satellite switching unit means;
solar cell means (12) for providing power for said satellite switching unit means; and
storage battery means connected to said solar cell means for storing said power.
6. A satellite cellular communication system as claimed in claim 1, said satellite switching means including a plurality of cell means coupled to one another, one said cell means operating to hand-off said established communication link between users to another one of said cell means.
7. A satellite cellular communication system as claimed in claim 1, wherein each of said users is connected to said link means by cellular telephone means (A, B).
8. A satellite cellular communication system as claimed in claim 1, said link means further cou-



through the satellite network interrogate his home data base computer to determine his pertinent customer information. The mobile telephone may automatically indicate to the satellite network a new location for updating the data base computer. This control signal allows the incoming calls of "roaming" users to be validated via satellite-to-satellite linking to the home area's data base computer.

Each satellite in the satellite cellular communication system is self-navigating. That is, it uses the Global Positioning Satellite system (GPS) or time and ephemeris data from which to compute its location information. In addition, from the fixed location of the Global Positioning Satellite system or other vehicle, each satellite can determine its position and alter its course accordingly to stay within its proper orbit while providing switching services.

Each satellite may switch a call intrasatellite (within the particular switching unit or cell) or may connect the call via a microwave or laser links (link i , $i+1$, etc.) to another satellite within its plane or out of plane (adjacent). Each satellite may distinguish a particular telephone number and determine whether that number is within its own calling area or the area of another satellite. If it is within the area of another satellite, the call is cross-linked to the next appropriate satellite or cell which makes the same determination until the satellite serving that telephone number is reached. That satellite down-links to the particular mobile user sought to be called. Due to this structure, the satellite network provides a distributed nodal switching capability. Each satellite is a local switch for a particular area, but the area is constantly changing. Therefore, calls are handed-off as satellites move out of the range of a particular telephone user.

Various multiplexing techniques (i.e. FDMA, TDM CDMA, etc.) may be used to enhance the transmission capability between various satellites on the links as shown in FIG. 2.

Since the switching units of this system are orbiting the earth and relatively secure from tampering, this system provides the capability to support secure voice and data transmission via data encryption and decryption techniques commonly known in the art. Since the switching units enjoy the security of being hundreds of miles above the earth, the system also lends itself to military communication applications.

Claims

1. A satellite cellular communication system for communicating among a plurality of users comprising:
a plurality of satellite switching means (1, 2) positioned in low-earth orbit; and
link means (j , $j+1$) for coupling said users to one of said plurality of satellite switching means es-

tablishing a communication link between selected ones of said users via said satellite switching means;

each of said plurality of satellite switching means including first means (40, 50, 60) for handing-off the communication link between said satellite switching means;

each of said plurality of satellite switching means including a plurality of cell means (40, 50, 60) for providing the communication link; and

each of said plurality of satellite switching means including second means for handing-off (40, 50, 60) the communication link from a first to a second cell means within the same satellite switching means.

2. A satellite cellular communication system as claimed in claim 1, said satellite switching means including: a plurality of satellite switching unit means (40-60) positioned surrounding the earth in low-earth orbit; and second link means (j) for permitting multi-directional communication between one satellite switching unit means and any adjacent satellite switching unit means.

3. A satellite cellular communication system as claimed in claim 2, said second link means including microwave communication means.

4. A satellite cellular communication system as claimed in claim 2, said second link means including laser communication means.

5. A satellite cellular communication system as claimed in claim 2, said satellite switching unit means including:

antenna means (11) coupled to said plurality of users for establishing communication between said users and satellite switching unit means; solar cell means (12) for providing power for said satellite switching unit means; and storage battery means connected to said solar cell means for storing said power.

6. A satellite cellular communication system as claimed in claim 1, said satellite switching means including a plurality of cell means coupled to one another, one said cell means operating to hand-off said established communication link between users to another one of said cell means.

7. A satellite cellular communication system as claimed in claim 1, wherein each of said users is connected to said link means by cellular telephone means (A, B).

8. A satellite cellular communication system as claimed in claim 1, said link means further cou-



pling said satellite switching means (40, 50, 60) to a public switched telephone network means (20), said public switched telephone network means operating to selectively connect users (30) of said public switched telephone network means with first (70) or second (80) users directly coupled to said satellite switching system via said link means.

9. A satellite cellular communication system as claimed in claim 8, wherein there is further included means for connecting (10) said link means to said public switched telephone network means, said means for connecting providing gateway facility services between said satellite switching means and said public switched telephone network means.

10. A satellite cellular communication system as claimed in claim 1, further comprising: data base means (110-130) coupled to said satellite switching means via said link means, said data base means for storing and transmitting switching information pertinent to each of said plurality of users.

11. A satellite cellular communication system as claimed in claim 10, further comprising: cellular telephone means (70-80) having a control signal for connecting each of said users to said satellite switching means via said link means; said satellite switching means (40, 50, 60) operating in response to said control signal of each of said user's cellular telephone means to update said data base means with a present location of each user.

12. A satellite cellular communication system as claimed in claim 1, wherein each said satellite switching means includes distributed local processor means (40-60) for determining switching of a call between users.

13. A satellite cellular communications system as claimed in claim 1, wherein each said satellite switching means includes distributed nodal switching means (40-60).

Patentansprüche

1. Zellulares Satelliten-Nachrichtenverbindungssystem zur Nachrichtenverbindung für eine Vielzahl von Benutzern, welches System umfaßt: eine Vielzahl von in einer erdnahen Umlaufbahn positionierten Satelliten-Schaltermitteln (1, 2); und Verbindungsmittel (j, j+1), um die Benutzer mit ei-

nem der Vielzahl von Satelliten-Schaltermitteln zu verbinden, um dadurch eine Nachrichtenverbindung zwischen ausgewählten Benutzern über das Satelliten-Schaltermittel einzurichten; wobei jedes der Satelliten-Schaltermittel erste Mittel (40,50,60) zum Weitergeben der Nachrichtenverbindung unter den Satelliten-Schaltermitteln enthält;

jedes der Vielzahl von Satelliten-Schaltermitteln eine Vielzahl von Zellenmitteln (40,50,60) zum Schaffen der Nachrichtenverbindung enthält; und

jedes der Vielzahl von Satelliten-Schaltermitteln zweite Mittel zum Weitergeben (40,50,60) der Nachrichtenverbindung von einem ersten zu einem zweiten Zellenmittel innerhalb des gleichen Satelliten-Schaltermittels enthält.

2. Zellulares Satelliten-Nachrichtenverbindungssystem nach Anspruch 1, bei dem das Satelliten-Schaltermittel enthält: eine Vielzahl von Satelliten-Schaltereinheit-Mitteln (40-60), die in einer die Erde erdnah umgebenden Umlaufbahn positioniert sind; und

zweites Verbindungsmittel (j), um eine Mehrrichtungs-Nachrichtenverbindung zwischen einem Satelliten-Schaltereinheit-Mittel und jedem benachbarten Satelliten-Schaltereinheit-Mittel zuzulassen.

3. Zellulares Satelliten-Nachrichtenverbindungssystem nach Anspruch 2, bei dem das zweite Verbindungsmittel Mikrowellen-Nachrichtenverbindungsmittel enthält.

4. Zellulares Satelliten-Nachrichtenverbindungssystem nach Anspruch 2, bei dem das zweite Verbindungsmittel Laser-Nachrichtenverbindungsmittel enthält.

5. Zellulares Satelliten-Nachrichtenverbindungssystem nach Anspruch 2, bei dem das Satelliten-Schaltereinheit-Mittel enthält:

Antennenmittel (11), das mit der Vielzahl von Benutzern zum Einrichten von Nachrichtenverbindung zwischen den Benutzern und dem Satelliten-Schaltereinheit-Mittel gekoppelt ist; Solarzellenmittel (12) zur Stromversorgung für das Satelliten-Schaltereinheit-Mittel; und mit dem Solarzellenmittel verbundenes Speicherbatteriemittel zur Stromspeicherung.

6. Zellulares Satelliten-Nachrichtenverbindungssystem nach Anspruch 1, bei dem das Satelliten-Schaltermittel eine Vielzahl miteinander gekoppelter Zellenmittel enthält, wobei eines der Zellenmittel die Weitergabe der Eingerichteten Nachrichtenverbindung zu einem anderen der



Zellenmittel bewirkt.

7. Zellulares Satelliten-Nachrichtenverbundungssystem nach Anspruch 1, bei dem jeder Benutzer mit dem Verbindungsmittel durch zellulare Fernsprechnittel verbunden ist. 5
8. Zellulares Satelliten-Nachrichtenverbundungssystem nach Anspruch 1, bei dem das Verbindungsmittel weiter das Satelliten-Schaltermittel (40, 50, 60) mit einem öffentlich zugänglichen Fernsprechnetz-Mittel (20) koppelt, welches öffentlich zugängliche Fernsprechnetz-Mittel wahlweises Verbinden von Benutzern (30) des öffentlich zugänglichen Fernsprechnetz-Mittels mit ersten (70) oder zweiten (80) Benutzern bewirkt, die über das Verbindungsmittel direkt mit dem Satelliten-Schaltermittel gekoppelt sind. 10 15
9. Zellulares Satelliten-Nachrichtenverbundungssystem nach Anspruch 8, bei dem weiter Mittel zum Anschließen (10) des Verbindungsmittels an dem öffentlich zugänglichen Fernsprechnetz-Mittel enthalten ist, wobei das Mittel zum Anschließen Durchleit-Dienstleistungen zwischen dem Satelliten-Schaltermittel und dem öffentlich zugänglichen Fernsprechnetz-Mittel schafft. 20 25
10. Zellulares Satelliten-Nachrichtenverbundungssystem nach Anspruch 1, welches weiter umfaßt: mit dem Satelliten-Schaltermittel über das Verbindungsmittel gekoppeltes Datenbasismittel, welches Datenbasismittel zum Speichern und Übertragen von jeden der Vielzahl von Benutzern betreffender Verteilungsinformation bestimmt ist. 30 35
11. Zellulares Satelliten-Nachrichtenverbundungssystem nach Anspruch 10, welches weiter umfaßt: zellulares Fernsprechnittel (70-80) mit einem Steuersignal zum Verbinden jedes Benutzers mit dem Satelliten-Schaltermittel über das Verbindungsmittel; wobei das Satelliten-Schaltermittel (40, 50, 60) in Reaktion auf das Steuersignal jedes zellularen benutzerseitigen Fernsprechnittels Aktualisierung des Datenbasismittels mit einem gegenwärtigen Aufenthaltsort jedes Benutzers bewirkt. 40 45
12. Zellulares Satelliten-Nachrichtenverbundungssystem nach Anspruch 1, bei dem jedes jeweilige Satelliten-Schaltermittel verteiltes örtliches Prozessormittel (40-60) zum Bestimmen des Schaltens eines Anrufes zwischen Benutzern enthält. 50 55
13. Zellulares Satelliten-Nachrichtenverbundungssystem nach Anspruch 1, bei dem jedes jeweilige Satelliten-Verteilermittel verteiltes Knoten-

Schaltermittel (40-60) enthält.

Revendications

1. Système de communication cellulaire par satellite pour une communication parmi une pluralité d'utilisateurs comprenant :
 - une pluralité de moyens de commutation de satellite (1, 2) placés sur une orbite basse; et
 - des moyens de liaison (j, j+1) pour le couplage desdits utilisateurs à un de ladite pluralité de moyens de commutation de satellite établissant une liaison de communication entre des utilisateurs choisis desdits utilisateurs via lesdits moyens de commutation de satellite;

chacun de ladite pluralité de moyens de commutation de satellite comprenant des premiers moyens (40, 50, 60) pour transférer la liaison de communication entre lesdits moyens de commutation de satellite;

chacun de la pluralité de moyens de commutation de satellite comprenant une pluralité de moyens de cellule (40, 50, 60) pour assurer la liaison de communication; et

chacun de ladite pluralité de moyens de commutation de satellite comprenant un second moyen de transfert (40, 50, 60) de la liaison de communication d'un premier à un second moyen de cellule dans le même moyen de commutation de satellite.
2. Système de communication cellulaire par satellite selon la revendication 1, dans lequel lesdits moyens de commutation de satellite comprennent une pluralité de moyens d'unité de commutation de satellite (40 à 60) placés autour de la terre en orbite basse et un second moyen de liaison (j) pour permettre une communication multidirectionnelle entre un moyen d'unité de commutation de satellite et un quelconque moyen adjacent d'unité de commutation de satellite.
3. Système de communication cellulaire par satellite selon la revendication 2, dans lequel ledit second moyen de liaison comprend un moyen de communication par micro-ondes.
4. Système de communication cellulaire par satellite selon la revendication 2, dans lequel ledit second moyen de liaison comprend un moyen de communication par laser.
5. Système de communication cellulaire par satellite



- te selon la revendication 2, dans lequel lesdits moyens d'unité de commutation de satellite comprennent un moyen d'antenne (11) couplé à ladite pluralité d'utilisateurs pour établir la communication entre lesdits utilisateurs et les moyens d'unité de commutation de satellite; un moyen de cellule solaire (12) pour fournir la puissance auxdits moyens d'unité de commutation de satellite et un moyen de batterie de stockage raccordé audit moyen de cellule solaire pour le stockage de ladite puissance.
6. Système de communication cellulaire par satellite selon la revendication 1, dans lequel lesdits moyens de commutation de satellite comprennent une pluralité de moyens de cellule respectivement couplés, un dit moyen de cellule servant à transférer ladite liaison de communication établie entre les utilisateurs vers un autre desdits moyens de cellule.
7. Système de communication cellulaire par satellite selon la revendication 1, dans lequel chacun desdits utilisateurs est raccordé auxdits moyens de liaison par des moyens de téléphone cellulaire (A, B).
8. Système de communication cellulaire par satellite selon la revendication 1, dans lequel lesdits moyens de liaison couplent, de plus, lesdits moyens de commutation de satellite (40, 50, 60) à un moyen de réseau téléphonique public commuté (20), ledit moyen de réseau téléphonique commuté servant à connecter, de façon sélective, les utilisateurs (30) dudit moyen de réseau téléphonique public commuté avec des premier (70) ou second (80) utilisateurs directement couplés audit système de commutation de satellite via lesdits moyens de liaison.
9. Système de communication cellulaire par satellite selon la revendication 8, comprenant, de plus, un moyen pour la connexion (10) desdits moyens de liaison audit moyen de réseau téléphonique public commuté, ledit moyen de connexion fournissant des services de connecteur de réseau entre lesdits moyens de commutation de satellite et ledit moyen de réseau téléphonique public commuté.
10. Système de communication cellulaire par satellite selon la revendication 1, comprenant, de plus, un moyen de base de données (110-130) couplé auxdits moyens de commutation de satellite via lesdits moyens de liaison, ledit moyen de base de données stockant et émettant une information de commutation concernant chacun de ladite pluralité d'utilisateurs.
11. Système de communication cellulaire par satellite selon la revendication 10, comprenant, de plus, des moyens de téléphone cellulaire (70-80) possédant un signal de commande pour la connexion de chacun desdits utilisateurs auxdits moyens de commutation de satellite via lesdits moyens de liaison, lesdits moyens de commutation de satellite (40, 50, 60) fonctionnant en réponse audit signal de commande de chacun desdits moyens de téléphone cellulaire d'utilisateur pour mettre à jour ledit moyen de base de données à l'aide de la position présente de chaque utilisateur.
12. Système de communication cellulaire par satellite selon la revendication 1, dans lequel chacun desdits moyens de commutation de satellite comprend un moyen de processeur local réparti (40-60) pour déterminer une commutation d'un appel entre utilisateurs.
13. Système de communication cellulaire par satellite selon la revendication 1, dans lequel chacun desdits moyens de commutation de satellite comprend des moyens de commutation nodale répartie (40-60).