



- (51) International Patent Classification:
G01R 11/56 (2006.01)
- (21) International Application Number:
PCT/US2011/062799
- (22) International Filing Date:
1 December 2011 (01.12.2011)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13/275,759 18 October 2011 (18.10.2011) US
2,755,459 20 October 2011 (20.10.2011) CA
- (71) Applicant (for all designated States except US): **ITRON, INC.** [US/US]; 2111 N. Molter Road, Liberty Lake, Washington 99019 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **JOHNSON, Matthew** [US/US]; 3531 West Excell Lane, Spokane, Washington 99208 (US).
- (74) Agent: **MOOSE, Richard, M.**; Dority & Manning, P.A., P O Box 1449, Greenville, South Carolina 29602-1449 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: TRAFFIC MANAGEMENT AND REMOTE CONFIGURATION IN A GATEWAY-BASED NETWORK




FIG. 1

(57) Abstract: Disclosed are apparatus and methodology for remotely configuring gateway devices in a gateway-based Advanced Metering Infrastructure (AMI) network. Remotely configurable gateway devices are provided for Internet Protocol (IP) communications between consumption measuring devices and a utility central facility. Communications between the gateway device and central facility may be by way of wired or wireless communications and may include configuration information multicast from the central facility to selected gateway devices.

WO 2013/058791 A3



Published:

(88) Date of publication of the international search report:

— *with international search report (Art. 21(3))*

10 April 2014