



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification : Not classified	A2	(11) International Publication Number: WO 00/41496 (43) International Publication Date: 20 July 2000 (20.07.00)
(21) International Application Number: PCT/IL99/00691 (22) International Filing Date: 19 December 1999 (19.12.99) (30) Priority Data: 60/115,628 12 January 1999 (12.01.99) US 09/293,343 16 April 1999 (16.04.99) US 09/365,584 2 August 1999 (02.08.99) US (71) Applicant (for all designated States except US): POWERD-SINE LTD. [IL/IL]; Zvi Bergman Street 5, P.O. Box 4670, 49277 Petach Tikva (IL). (72) Inventors; and (75) Inventors/Applicants (for US only): LEHR, Amir [IL/IL]; Shlomo Hamelech Street 52, 64386 Tel Aviv (IL). ATIAS, Ilan [IL/IL]; Kadima Street 29A, 34383 Haifa (IL). KORCHARZ, Dror [IL/IL]; Hertzal Street 24, 59304 Bat Yam (IL). PINCU, David [IL/IL]; Shenker Street 18, 58261 Holon (IL). (74) Agents: COLB, Sanford, T. et al.; Sanford T. Colb & Co., P.O. Box 2273, 76122 Rehovot (IL).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: IMPROVED STRUCTURE CABLING SYSTEM (57) Abstract This invention discloses a local area network including a hub, a plurality of nodes, communication cabling connecting the plurality of nodes to the hub for providing data communication, and a power supply distributor operative to provide at least some operating power to at least some of the plurality of nodes via the communication cabling.		