

GAS TURBINE ENGINE WITH FAN VARIABLE AREA NOZZLE TO REDUCE FAN INSTABILITY

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The application claims priority to United States Application No. 13/340,787, filed December 30, 2011, which is a continuation in part of United States Application No. 13/314,365, filed December 8, 2011.

BACKGROUND

[0002] The present invention relates to a gas turbine engine, and more particularly to a turbofan engine having a fan variable area nozzle (VAFN) which moves axially to change a bypass flow path area thereof.

[0003] Conventional gas turbine engines generally include a fan section and a core engine with the fan section having a larger diameter than that of the core engine. The fan section and the core engine are disposed about a longitudinal axis and are enclosed within an engine nacelle assembly.

[0004] Combustion gases are discharged from the core engine through a core exhaust nozzle while an annular fan flow, disposed radially outward of the primary airflow path, is discharged through an annular fan exhaust nozzle defined between a fan nacelle and a core nacelle. A majority of thrust is produced by the pressurized fan air discharged through the fan exhaust nozzle, the remaining thrust being provided from the combustion gases discharged through the core exhaust nozzle.

[0005] The fan nozzles of conventional gas turbine engines have a fixed geometry. The fixed geometry fan nozzles are a compromise suitable for take-off and landing conditions as well as for cruise conditions. Some gas turbine engines have implemented fan variable area nozzles. The fan variable area nozzle provide a smaller fan exit nozzle diameter during cruise conditions and a larger fan exit nozzle diameter during take-off and landing conditions. Existing fan variable area nozzles typically utilize relatively complex mechanisms that increase overall engine weight to the extent that the increased fuel efficiency therefrom may be negated.

SUMMARY

[0006] A nacelle assembly for a high-bypass gas turbine engine according to an exemplary aspect of the present disclosure includes a core nacelle defined about an engine centerline axis, a fan nacelle mounted at least partially around the core nacelle to define a fan bypass flow path for a fan bypass airflow, a fan variable area nozzle axially movable relative the fan nacelle to vary a fan nozzle exit area and adjust a fan pressure ratio of the fan bypass airflow during engine operation, and a controller operable to control the fan variable area nozzle to vary a fan nozzle exit area and adjust the pressure ratio of the fan bypass airflow to reduce a fan instability.

[0007] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the fan instability may be a fan flutter.

[0008] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the controller may be operable to reduce the fan nozzle exit area at a cruise flight condition.

[0009] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the fan variable area nozzle may define a trailing edge of the fan nacelle.

[0010] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the nacelle assembly may further include a gear system driven by a core engine within the core nacelle to drive a fan within the fan nacelle.

[0011] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the fan may define a corrected fan tip speed less than about 1150 ft / second.

[0012] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the fan pressure ratio may be less than about 1.45.

[0013] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the core engine may include a low

pressure turbine which defines a pressure ratio that is greater than about five (5). Additionally or alternatively, the core engine may include a low pressure turbine which defines a pressure ratio that is greater than five (5).

[0014] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the nacelle assembly may further include a gear system driven by a core engine within the core nacelle to drive a fan within the fan nacelle, the gear system defines a gear reduction ratio of greater than or equal to about 2.3.

[0015] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the nacelle assembly may further include a gear system driven by a core engine within the core nacelle to drive a fan within the fan nacelle, the gear system defines a gear reduction ratio of greater than or equal to about 2.5.

[0016] In a further non-limiting embodiment of any of the foregoing nacelle assembly for a high-bypass gas turbine engine embodiments, the fan bypass airflow may define a bypass ratio greater than about six (6). Additionally or alternatively, the fan bypass airflow may define a bypass ratio greater than about ten (10). Additionally or alternatively, the fan bypass airflow may define a bypass ratio greater than ten (10).

[0017] A method of reducing fan instability in a gas turbine engine according to another exemplary aspect of the present disclosure includes adjusting a pressure ratio of the fan bypass airflow.

[0018] In a further non-limiting embodiment of any of the foregoing method of reducing fan instability in a gas turbine engine embodiments, adjusting the fan pressure ratio may include adjusting the fan pressure ratio to less than about 1.45.

[0019] In a further non-limiting embodiment of any of the foregoing method of reducing fan instability in a gas turbine engine embodiments, the method may further include driving a fan with a low pressure spool through a geared architecture.

[0020] In a further non-limiting embodiment of any of the foregoing method of reducing fan instability in a gas turbine engine embodiments, the method may further include driving a fan with a low pressure spool through a geared architecture, the fan having a corrected fan tip speed less than about 1150 ft / second.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The various features and advantages of this invention will become apparent to those skilled in the art from the following detailed description of the currently preferred embodiment. The drawings that accompany the detailed description can be briefly described as follows:

[0022] Figure 1A is a general schematic partial fragmentary view of an exemplary gas turbine engine embodiment for use with the present invention;

[0023] Figure 1B is a rear view of the engine;

[0024] Figure 1C is a side view of the engine integrated with a pylon;

[0025] Figure 1D is a perspective view of the engine integrated with a pylon;

[0026] Figure 2A is a sectional side view of the VAFN in a closed position;

[0027] Figure 2B is a sectional side view of the VAFN in an open position; and

[0028] Figure 3 is a graph of a bypass duct normalized cross-sectional area distribution.

[0029] Figure 4 is a graph of a Effective Area Increase vs. Nozzle Translation;

[0030] Figure 5 is a graph of a duct area distribution;

[0031] Figure 6A is schematic geometric view of the auxiliary port location;

[0032] Figure 6B is schematic geometric view of the auxiliary port entrance angle; and

[0033] Figure 6C is schematic geometric view of a VAFN outer surface curvature.

DETAILED DESCRIPTION

[0034] Figure 1A illustrates a general partial fragmentary schematic view of a gas turbofan engine 10 suspended from an engine pylon P within an engine nacelle assembly N as is typical of an aircraft designed for subsonic operation.

[0035] The turbofan engine 10 includes a core engine within a core nacelle 12 that houses a low spool 14 and high spool 24. The low spool 14 includes a low pressure compressor 16 and low pressure turbine 18. The low spool 14 drives a fan section 20 through a gear train 22. The high spool 24 includes a high pressure compressor 26 and high pressure turbine 28. A

combustor 30 is arranged between the high pressure compressor 26 and high pressure turbine 28. The low and high spools 14, 24 rotate about an engine axis of rotation A.

[0036] The engine 10 is preferably a high-bypass geared aircraft engine. In one disclosed, non-limiting embodiment, the engine 10 bypass ratio is greater than about six (6), with an example embodiment being greater than ten (10), the gear train 22 is an epicyclic gear train such as a planetary gear system or other gear system with a gear reduction ratio of greater than about 2.3 and the low pressure turbine 18 has a pressure ratio that is greater than about 5. In one disclosed embodiment, the engine 10 bypass ratio is greater than about ten (10:1), the turbofan diameter is significantly larger than that of the low pressure compressor 16, and the low pressure turbine 18 has a pressure ratio that is greater than about 5:1. Low pressure turbine 18 pressure ratio is pressure measured prior to inlet of low pressure turbine 18 as related to the pressure at the outlet of the low pressure turbine 18 prior to exhaust nozzle. The gear train 22 may be an epicycle gear train such as a planetary gear system or other gear system with a gear reduction ratio of greater than about 2.5:1. It should be understood, however, that the above parameters are only exemplary of one embodiment of a geared architecture engine and that the present invention is applicable to other gas turbine engines including direct drive turbofans.

[0037] Airflow enters a fan nacelle 34, which at least partially surrounds the core nacelle 12. The fan section 20 communicates airflow into the core nacelle 12 to power the low pressure compressor 16 and the high pressure compressor 26. Core airflow compressed by the low pressure compressor 16 and the high pressure compressor 26 is mixed with the fuel in the combustor 30 and expanded over the high pressure turbine 28 and low pressure turbine 18. The turbines 28, 18 are coupled for rotation with, respective, spools 24, 14 to rotationally drive the compressors 26, 16 and through the gear train 22, the fan section 20 in response to the expansion. A core engine exhaust E exits the core nacelle 12 through a core nozzle 43 defined between the core nacelle 12 and a tail cone 32.

[0038] The core nacelle 12 is supported within the fan nacelle 34 by structure 36 often generically referred to as Fan Exit Guide Vanes (FEGVs). A bypass flow path 40 is defined between the core nacelle 12 and the fan nacelle 34. The engine 10 generates a high bypass flow arrangement with a bypass ratio in which approximately 80 percent of the airflow entering the fan nacelle 34 becomes bypass flow B. The bypass flow B communicates through the generally annular fan bypass flow path 40 and is discharged from the engine 10 through a fan

variable area nozzle (VAFN) 42 which defines a fan nozzle exit area 44 between the fan nacelle 34 and the core nacelle 12 at a fan nacelle end segment 34S of the fan nacelle 34 downstream of the fan section 20.

[0039] Thrust is a function of density, velocity, and area. One or more of these parameters can be manipulated to vary the amount and direction of thrust provided by the bypass flow B. The Variable Area Fan Nozzle (“VAFN”) 42 operates to effectively vary the area of the fan nozzle exit area 44 to selectively adjust the pressure ratio of the bypass flow B in response to a controller C. Low pressure ratio turbofans are desirable for their high propulsive efficiency. However, low pressure ratio fans may be inherently susceptible to fan stability/flutter problems at low power and low flight speeds. The VAFN 42 allows the engine to change to a more favorable fan operating line at low power, avoiding the instability region, and still provide the relatively smaller nozzle area necessary to obtain a high-efficiency fan operating line at cruise.

[0040] A significant amount of thrust is provided by the bypass flow B due to the high bypass ratio. The fan section 20 of the engine 10 is designed for a particular flight condition -- typically cruise at about 0.8 Mach and about 35,000 feet. The flight condition of 0.8 Mach and 35,000 ft, with the engine at its best fuel consumption - also known as “bucket cruise Thrust Specific Fuel Consumption (“TSFC”)” - is the industry standard parameter of lbm of fuel being burned divided by lbf of thrust the engine produces at that minimum point. “Low fan pressure ratio” is the pressure ratio across the fan blade alone, without the Fan Exit Guide Vane (“FEGV”) system 36. The low fan pressure ratio as disclosed herein according to one non-limiting embodiment is less than about 1.45. “Low corrected fan tip speed” is the actual fan tip speed in ft/sec divided by an industry standard temperature correction of $[(T_{\text{ambient deg R}}) / 518.7]^{0.5}$. The “Low corrected fan tip speed” as disclosed herein according to one non-limiting embodiment is less than about 1150 ft / second.

[0041] As the fan blades within the fan section 20 are efficiently designed at a particular fixed stagger angle for an efficient cruise condition, the VAFN 42 is operated to effectively vary the fan nozzle exit area 44 to adjust fan bypass air flow such that the angle of attack or incidence on the fan blades is maintained close to the design incidence for efficient engine operation at other flight conditions, such as landing and takeoff to thus provide optimized engine operation over a range of flight conditions with respect to performance and other operational parameters such as noise levels.

[0042] The VAFN 42 is separated into at least two sectors 42A-42B (Figure 1B) defined between the pylon P and a lower Bi-Fi splitter L which typically interconnects a larger diameter fan duct reverser cowl and a smaller diameter core cowl (Figure 1C and 1D). Each of the at least two sectors 42A-42B are independently adjustable to asymmetrically vary the fan nozzle exit area 44 to generate vectored thrust. It should be understood that although two segments are illustrated, any number of segments may alternatively or additionally be provided.

[0043] In operation, the VAFN 42 communicates with a controller C or the like to adjust the fan nozzle exit area 44 in a symmetrical and asymmetrical manner. Other control systems including an engine controller or aircraft flight control system may also be usable with the present invention. By adjusting the entire periphery of the VAFN 42 symmetrically in which all sectors are moved uniformly, thrust efficiency and fuel economy are maximized during each flight condition. By separately adjusting the circumferential sectors 42A-42B of the VAFN 42 to provide an asymmetrical fan nozzle exit area 44, engine bypass flow is selectively vectored to provide, for example only, trim balance or thrust controlled maneuvering enhanced ground operations or short field performance.

[0044] The VAFN 42 generally includes an auxiliary port assembly 50 having a first fan nacelle section 52 and a second fan nacelle section 54 movably mounted relative the first fan nacelle section 52. The second fan nacelle section 54 axially slides along the engine axis A relative the fixed first fan nacelle section 52 to change the effective area of the fan nozzle exit area 44. The second fan nacelle section 54 slides aftward upon a track fairing 56A, 56B (illustrated schematically in Figure 1C and 1D) in response to an actuator 58 (illustrated schematically). The track fairing 56A, 56B extend from the first fan nacelle section 52 adjacent the respective pylon P and the lower Bi-Fi splitter L (Figure 1D).

[0045] The VAFN 42 changes the physical area and geometry of the bypass flow path 40 during particular flight conditions. The bypass flow B is effectively altered by sliding of the second fan nacelle section 54 relative the first fan nacelle section 52 between a closed position (Figures 2A) and an open position (Figures 2B). The auxiliary port assembly 50 is closed by positioning the second fan nacelle section 54 in-line with the first fan nacelle section 52 to define the fan nozzle exit area 44 as exit area F0 (Figure 2A).

[0046] The VAFN 42 is opened by moving the second fan nacelle section 54 aftward along the track fairing 56A, 56B away from the first fan nacelle section 52 to open an auxiliary

port 60 which extends between the open second fan nacelle section 54 relative the first fan nacelle section 52 to essentially provide an increased fan nozzle exit area 44 exit area F1. That is, the exit area F1 with the port 60 is greater than exit area F0 (Figure 2B).

[0047] In one disclosed embodiment, the auxiliary port 60 is incorporated into the exhaust system of a high bypass ratio commercial turbofan engine within the bypass duct aft of the Fan Exit Guide Vanes (FEGVs; Figures 2A, 2B). The auxiliary port 60 is located in the aft section of the bypass duct outer wall.

[0048] Referring to Figure 3, the bypass duct area distribution, the effective area increase vs. translation (Figure 4), area distribution (Figure 5), and auxiliary port 60 location (Figure 6A) and wall curvatures (Figure 6B-6C) are tailored to provide a proper flow-field that allows the auxiliary port 60 to obtain the required additional effective exit area. The auxiliary port 60 will essentially double the effective area gain due to translation. The auxiliary port 60 provides a relatively low weight method of providing increased exit area to control the fan operating line without causing high system losses or unacceptable aircraft installation issues. By tailoring the bypass duct area distribution and outer wall curvature, the desired maximum effective area increase is achieved before the stroke of the auxiliary port 60 reaches its effective area increase limit.

[0049] The auxiliary port exit plane 44B (defined as the plane between the stationary section's trailing edge and the moving sections leading edge) initially has an opening in which the exit plane normal vector is near-axial, but as the stroke increases, the normal vector becomes more inclined and approaches a near-radial vector. Once the exit plane normal has become near-radial, the maximum auxiliary port effectiveness has been reached. Once this point is reached, the rate of the effective area vs. translation changes from steep slope of the "well designed port" the shallow rate of the "main nozzle only", since additional area will be provided through the main nozzle 44A due to the inward slope of the core nacelle 12. A well designed auxiliary port nozzle will achieve approximately +25% effective area before the port effectiveness limit is reached. That is, there is a limited range of stroke in which the auxiliary port doubles the rate of additional effectiveness. Outside of this range, the rate of additional effectiveness may be equivalent to a translating nozzle that has no auxiliary port. Or put another way, the auxiliary port reduces the stroke necessary for a pure translating nozzle to achieve a desired effective area.

[0050] Referring to Figure 5, the cross-sectional area at the auxiliary port 60 is greater than the maximum required effective area of the VAFN 42 and the bypass duct area distribution is tailored to ensure the duct cross-sectional area forward of the auxiliary port 60 is greater than the port opening cross-sectional area. This avoids a situation where an upstream internal cross-section becomes the controlling flow area (i.e. is smaller than the exit area), which can lead to operational limits and structural issues.

[0051] Referring to Figure 6A, the auxiliary port 60 in the disclosed embodiment, is located no more forward than $0.1 \text{ DEL_X} / \text{L_DUCT}$ defined from a point D at the largest radius R_{max} of the annular fan bypass flow path 40 defined by the second fan nacelle section 54. R_{max} is defined through point D and perpendicular to the engine axis A. Point D in the disclosed non limiting embodiment is located on an inner wall surface 54I of the second fan nacelle section 54 when the second fan nacelle section 54 is in a closed position. DEL_X is the axial distance to the forward most point of the auxiliary port 60 from R_{max} . L_DUCT is the overall axial length of the annular fan bypass flow path 40. The angle between the mean port line and the fan duct outer wall is relatively low to provide well-behaved, low loss exit flow. In the disclosed embodiment, the auxiliary port 60 entrance angle (Theta_in) relative to the fan bypass duct OD wall, is less than 20 degrees (Figure 6B) while the outer VAFN surface has an $\text{R_ARC} / \text{CHORD} > 0.7$ where R_ARC is a radial distance from the engine axis A to a radial outer wall surface 54O of the second fan nacelle section 54 and CHORD is the chord length of the second fan nacelle section 54. (Figure 6C). The curvature of the outer wall surface 54O near the auxiliary port 60 promotes flow through the auxiliary port 60. In one disclosed embodiment, the stroke of the second fan nacelle section 54 necessary to obtain an additional 20% effective exit area is approximately 8.4 inches.

[0052] In operation, the VAFN 42 communicates with the controller C to move the second fan nacelle section 54 relative the first fan nacelle section 52 of the auxiliary port assembly 50 to effectively vary the area defined by the fan nozzle exit area 44. Various control systems including an engine controller or an aircraft flight control system may also be usable with the present invention. By adjusting the axial position of the entire periphery of the second fan nacelle section 54 in which all sectors are moved simultaneously, engine thrust and fuel economy are maximized during each flight regime by varying the fan nozzle exit area. By separately adjusting the sectors of the second fan nacelle section 54 to provide an asymmetrical

fan nozzle exit area 44, engine bypass flow is selectively vectored to provide, for example only, trim balance, thrust controlled maneuvering, enhanced ground operations and short field performance.

[0053] The foregoing description is exemplary rather than defined by the limitations within. Many modifications and variations of the present invention are possible in light of the above teachings. The preferred embodiments of this invention have been disclosed, however, one of ordinary skill in the art would recognize that certain modifications would come within the scope of this invention. It is, therefore, to be understood that within the scope of the appended claims, the invention may be practiced otherwise than as specifically described. For that reason the following claims should be studied to determine the true scope and content of this invention.

CLAIMS

1. A nacelle assembly for a high-bypass gas turbine engine comprising:
a core nacelle defined about an engine centerline axis;
a fan nacelle mounted at least partially around said core nacelle to define a fan bypass flow path for a fan bypass airflow;
a gear system driven by a core engine within the core nacelle to drive a fan within the fan nacelle, wherein said fan defines a corrected fan tip speed less than about 1150 ft / second;
a fan variable area nozzle movable relative said fan nacelle to vary a fan nozzle exit area;
and
a controller operable to control said fan variable area nozzle to vary the fan nozzle exit area and adjust a fan pressure ratio of the fan bypass airflow to reduce a fan instability during engine operation, wherein said controller operates to adjust said fan nozzle exit area to maintain a fan pressure ratio less than about 1.45.
2. The assembly as recited in claim 1, wherein said fan instability is a fan flutter.
3. The assembly as recited in claim 1, wherein said controller is operable to reduce said fan nozzle exit area at a cruise flight condition.
4. The assembly as recited in claim 1, wherein said fan variable area nozzle defines a trailing edge of said fan nacelle.
5. The assembly as recited in claim 1, wherein said core engine includes a low pressure turbine which defines a low pressure turbine pressure ratio that is greater than about five (5).
6. The assembly as recited in claim 1, wherein said core engine includes a low pressure turbine which defines a low pressure turbine pressure ratio that is greater than five (5).

7. The assembly as recited in claim 1, wherein said gear system is driven by a core engine within the core nacelle to drive the fan within the fan nacelle, said gear system defines a gear reduction ratio of greater than or equal to about 2.3.

8. The assembly as recited in claim 1, wherein said gear system is driven by a core engine within the core nacelle to drive the fan within the fan nacelle, said gear system defines a gear reduction ratio of greater than or equal to about 2.5.

9. The assembly as recited in claim 1, wherein said fan bypass airflow defines a bypass ratio greater than about six (6).

10. The assembly as recited in claim 1, wherein said fan bypass airflow defines a bypass ratio greater than about ten (10).

11. The assembly as recited in claim 1, wherein said fan bypass airflow defines a bypass ratio greater than ten (10).

12. A method of reducing fan instability in a gas turbine engine comprising:
driving a fan with a low pressure spool through a geared architecture, the fan having a corrected fan tip speed less than about 1150 ft / second; and
adjusting a pressure ratio of a fan bypass airflow to less than about 1.45.

13. The assembly as recited in claim 1, wherein the fan variable area nozzle includes a first section and a second section movable axially relative to the first section and an auxiliary port between the first section and the second section for changing the effective area of the fan nozzle, wherein the auxiliary port includes an entrance angle relative to an outer wall of the fan nacelle that is less than 20 degrees.

14. The assembly as recited in claim 13, wherein the controller is in communication with the fan variable area nozzle to control movement of the second section relative to the first section to reduce an exit area of the fan variable area nozzle at a cruise flight condition.