

CLAIMS

What is claimed is:

1. A static mixing device subassembly, said subassembly comprising:
 - a first grid formed of a first set of spaced-apart and parallel-extending deflector blades;
 - a second set of spaced-apart and parallel-extending deflector blades that are interleaved with and cross the second set of deflector blades at a preselected angle, adjacent ones of the interleaved deflector blades in the first and second sets each having opposite ends and side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along a transverse strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposite ends of the deflector blades, the deflector blades in the second grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes;
 - a third grid formed of a third set of spaced-apart and parallel-extending deflector blades;
 - and
 - a fourth set of spaced apart and parallel-extending deflector blades that are interleaved with and cross the third set of deflector blades at a preselected angle, adjacent ones of the interleaved deflector blades in the third and fourth sets each having opposite ends and side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along a transverse strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposite ends of the deflector blades, the deflector blades in the fourth grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes,

wherein one of the ends in at least some of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend that aligns the first and second grids of deflector blades with the third and fourth grids of deflector blades.

2. The static mixing device subassembly of claim 1, wherein the offset planes of the segments of the deflector blades in the second set are parallel to each other and the offset planes of the segments of the deflector blades in the fourth set are parallel to each other.

3. The static mixing device subassembly of claim 2, wherein one of the ends in each of the deflector blades in the second set is spaced apart from and aligned with one of the ends in each of the deflector blades in the fourth set.

4. The static mixing device subassembly of claim 2, wherein the first, second, third and fourth grids have a least one side shaped to conform to a curved longitudinal plane.

5. The static mixing device subassembly of claim 2, wherein each of the deflector blades in the first, second, third and fourth sets is planar.

6. The static mixing device subassembly of claim 2, wherein the cut portions of the side edges joining the adjacent ones of the deflector blades in the first, second, third and fourth sets are each linear.

7. The static mixing device subassembly of claim 2, wherein the first and second grids cross at an included angle within the range of 45 to 135 degrees and the third and fourth grids cross at an included angled within the range of 45 to 135 degrees.

8. The static mixing device subassembly of claim 2, including apertures in at least some of the deflector blades in the first, second, third and fourth sets.

9. The static mixing device subassembly of claim 2, wherein said one of the ends of each of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend.

10. A static mixing device subassembly, said subassembly comprising:

a first grid formed of a first set of spaced-apart, parallel-extending, planar deflector blades;

a second set of spaced-apart, parallel-extending, planar deflector blades that are interleaved with and cross the second set of deflector blades at an included angle within the range of 45 to 135 degrees, adjacent ones of the interleaved deflector blades in the first and second sets each having opposite ends and linear side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along a transverse strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposite ends of the deflector blades, the deflector blades in the second grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes;

a third grid formed of a third set of spaced-apart, parallel-extending, planar deflector blades; and

a fourth set of spaced apart, parallel-extending, planar deflector blades that are interleaved with and cross the third set of deflector blades at an included angle within the range of 45 to 135 degrees, adjacent ones of the interleaved deflector blades in the third and fourth sets each having opposite ends and linear side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along a transverse strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposite ends of the deflector blades, the deflector blades in the fourth grid each having a bent portion that places

segments of the deflector blade on opposite sides of the uncut portion in offset planes that are parallel to each other,

wherein one of the ends in at least some of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend that aligns the first and second grids of deflector blades with the third and fourth grids of deflector blades,

wherein one of the ends in each of the deflector blades in the second set is spaced apart from and aligned with one of the ends in each of the deflector blades in the fourth set,

wherein the first, second, third and fourth grids have a least one side shaped to conform to a curved longitudinal plane.

11. The static mixing device subassembly of claim 10, including apertures in at least some of the deflector blades in the first, second, third and fourth sets.

12. The static mixing device subassembly of claim 10, wherein said one of the ends of each of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend.

13. A static mixing device comprising static mixing device subassemblies of claim 3 in which the interconnected uncut ends of the deflector blades in the first and third sets in one of the static mixing subassemblies are joined to said spaced apart and aligned ends of the deflector blades in the second and fourth sets in an adjacent one of the static mixing subassemblies.

14. The static mixing device of claim 13, wherein the first, second, third and fourth grids have a least one side shaped to conform to a curved longitudinal plane.

15. The static mixing device of claim 13, wherein each of the deflector blades in the first, second, third and fourth sets is planar.

16. The static mixing device of claim 13, wherein the cut portions of the side edges joining the adjacent ones of the deflector blades in the first, second, third and fourth sets are each linear.
17. The static mixing device of claim 13, wherein the first and second grids cross at an included angle within the range of 45 to 135 degrees.
18. The static mixing device of claim 13, including apertures in at least some of the deflector blades in the first, second, third and fourth sets.
19. A method of making a static mixing device, comprising the steps of:
 - cutting and bending a sheet of material to form a plurality of static mixing device subassemblies of claim 3; and
 - joining adjacent ones of static mixing subassemblies together by joining the uncut ends of the deflector blades in the first and third sets in one of the adjacent static mixing subassemblies to the spaced apart and aligned ends of the deflector blades in the second and fourth sets in the other one of the adjacent static mixing subassemblies.
20. The method of claim 19, wherein the uncut ends of the deflector blades in the first and third sets in one of the adjacent static mixing subassemblies are joined by welding to the spaced apart and aligned ends of the deflector blades in the second and fourth sets in the another one of the adjacent static mixing subassemblies.