



"ANNULAR CUTTER CONNECTING APPARATUS AND ANNULAR CUTTER"

5 The present invention relates to an annular cutter
connecting apparatus for connecting an annular cutter
to a drilling machine used for drilling relatively deep
holes in a workpiece made of a hard material, and an
annular cutter connected by such a connecting apparatus
to the drilling machine, and more particularly to an
annular cutter connecting apparatus for connecting an
10 annular cutter to a drilling machine with ease,
receiving only an annular cutter suited for the
drilling machine and preventing any annular cutter not
suited therefor from being connected to the drilling
machine, and such an annular cutter.

15 The conventional drilling machine for drilling a
workpiece made of a hard material generally forms holes
by driving an annular cutter having downward directed
blade edges at a constant rotational speed and feed.
Upon drilling a workpiece made of a hard material on
20 this drilling machine, it is necessary to change the
annular cutter which is now used when it is not suited
for the workpiece to be drilled.

There have been developed various annular cutter
connecting apparatuses which facilitate replacement of
25 annular cutters, and annular cutters which can be
replaced easily. There are variety of annular cutter
connecting apparatuses, the simplest type of which
connects an annular cutter to an arbour by means of a
blot, and a relative complicated type of which uses
30 locking members such as balls for holding the arbour.

An annular cutter connecting apparatus which has a
relative complicated structure as disclosed in Japanese
Laid-open Patent Application 62-74515 will be described
with reference to Figs. 1 and 2.

35 A conventional annular cutter 1 connected to an
arbour 2 of a drilling machine (not shown) and



transmits the rotation and the feed required for drilling operation from the drilling machine to an annular cutter 8. A cylindrical rotation transmitting member 3 is irrotationally connected to the arbour 2 by means of a key 4. A plurality of holding holes 6 for holding fixing balls 5 are formed in the lateral wall of the lower portion of the rotation transmitting member 3 so as to be directed toward the axis of the rotation transmitting member 3.

On an intermediate portion of the inner peripheral surface of the rotation transmitting member 3 are formed a plurality of engaging portions 7 (Fig. 2) which extend toward the central axis of the member 3 and transmit rotation from the rotation transmitting member 3 to the annular cutter 8. A pushing sleeve 9 for pushing the fixing balls 5 toward the central axis of the rotation transmitting member 3 surrounds the rotation transmitting member 3 so as to be slidable axially thereof. Between the pushing sleeve 9 and the rotation transmitting member 3 is provided a compression coil spring 10 for urging the pushing sleeve 9 downward. The pushing sleeve 9 is held by a holding ring 11 fixed to the outer peripheral surface of the rotation transmitting member 3 so that the pushing sleeve 9 is prevented from slipping off the rotation transmitting member 3.

The annular cutter 8 has a downwardly open cylindrical body having a plurality of blades (not shown) formed on the lower end thereof. On the upper end of the cylindrical body is formed a cylindrical shank portion 12 inserted in the lower portion of a cylindrical central hole (hereinafter referred to as the "fixing hole") formed by the inner peripheral surface of the rotation transmitting member 3. Axially projecting portions 13 engageable with the engaging portions 7 are formed on the upper end of the shank

portion 12. An annular groove 14 for receiving the fixing balls 5 is formed in an intermediate portion of the outer peripheral wall of the shank portion 12.

5 A centre pin 15 for determining the drilled position axially slidably passes through the central hole of the annular cutter 8. An annular engaging groove 16 for receiving engaging balls 17 is formed in the upper end portion of the centre pin 15. The annular cutter 8 is connected to the arbour 2 in the
10 fixing hole by pushing the engaging balls 17 into the engaging groove 16. The centre pin 15 is urged downward by a compression coil spring 18 through the balls 17, and a sealing member 19 is abutted against the upper shoulder of another annular groove 20 so as
15 to prevent cutting oil from flowing downward from the cylindrical central hole in the arbour 2, when the centre pin 15 is not in use. During the drilling operation, however, the lower end tip of the centre pin 15 is pressed against a to-be-drilled workpiece (not
20 shown) made of a hard material, and the centre pin 15 is pushed in the fixing in the rotation transmitting member 3 against the urging force of the compression coil spring 18. Accordingly, the sealing member 19 is released from the shoulder of the annular groove 20 of
25 the annular cutter 8, and the cutting oil is supplied from the cylindrical hole of the arbour 2 to the blade edges of the annular cutter 8, whereby the drilling operation is performed smoothly.

The annular cutter 8 is fixed to the rotation
30 transmitting member 3 in the following way. First, the pushing sleeve 9 is moved upward against the urging force of the compression coil spring 10. Next, the shank portion 12 of the annular cutter 8 is inserted into the fixing hole of the rotation transmitting
35 member 3 until the projecting portions 13 engage the engaging portions 7. In this state, the pushing

portion 21 of the pushing sleeve 9 is displaced from the fixing balls 5, and the fixing balls 5 face the cylindrical ball-escaping hole 22 of the sleeve 9 so that the balls 5 are movable radially outward. Thus, the shank portion 12 of the annular cutter 8 is inserted freely in the cylindrical hole of the rotation transmitting member 3.

When the annular cutter 8 is fully inserted in the rotation transmitting member 3, the pushing sleeve 9 is released. Then, the pushing sleeve 9 is moved downward by the urging force of the compression coil spring 10 and pushes the fixing balls 5 into the annular groove 14 of the shank portion 12. In this way, the annular cutter 8 is fixed to the rotation transmitting member 3.

Upon drilling a workpiece made of a hard material, the annular cutter now on the drilling machine must be replaced by an annular cutter having a diameter suited for holes to be formed, if the annular cutter now on the drilling machine has not such a suitable diameter.

However, the conventional annular cutter connecting apparatus can connect any annular cutter to the arbour so long as the inner diameter of fixing hole of the rotation transmitting member corresponds to the outer diameter of the shank portion of the annular cutter and the annular groove coincides with fixing balls. Thus, an annular cutter not suited for the driving capability of a drilling machine and for the material of a workpiece is sometimes connected to the arbour 2 mistakenly. If the drilling operation continues without noticing this mistake, unexpected high cutting resistance is produced during the drilling operation. As a result, the driving mechanism of the drilling machine tends to be damaged and/or the blade edges of the annular cutter 8 are apt to be broken.

In case where only blade edges are broken, this

problem can be solved by replacing the annular cutter 8 with a suitable one. When, however, the driving mechanism of the drilling machine is broken, the drilling operation must be interrupted for a long time in order to repair the driving mechanism, deranging the production plan. When the annular cutter 8 is not suited for the material of a workpiece, burrs tend to be produced to lower the dimensional accuracy of the formed holes, even if the holes can be formed. As cut chips are wound around the annular cutter 8, the pushing sleeve 9 is sometimes pushed up against the urging force of the compression coil spring 10, and the annular cutter 8 is apt to be adversely loosened or removed from the arbour 2.

When the annular cutter 8 is fixed to the arbour 2 as shown in Fig. 2, the pushing sleeve 9 is lowered so that the annular cutter fixing balls 5 coincide with the escaping hole 22 formed in the lower end portion of the pushing sleeve 9 and are set in a waiting state in the escaping hole 22. In the conventional annular cutter connecting apparatus 1 of a general type, part of each ball 5 projects from the inner peripheral surface of the rotation transmitting member 3 into a central bore defined by the inner peripheral surface of the rotation transmitting member 3 (Fig. 1). Flat faces 23 each having a depth corresponding to the extended amount of each ball 5 into the central bore are formed on the parts of the outer peripheral surface of the shank portion 12 of the annular cutter 8, which parts extend from the annular groove 14 to the upper end of the shank portion 12. When the shank portion 12 is fixed to the arbour 2, the flat faces 23 align with the corresponding balls 5, and then the shank portion is pushed into the central bore.

Any annular cutter can be connected to the arbour 2 so long as the annular cutter is provided with a

shank portion 12 having an outer diameter corresponding to the inner diameter of central hole of the arbour 2 and flat faces 23 for receiving the balls 5 extending from the holding holes 6 into the central hole. Thus, the subject matter in that only a suitable annular cutter can be fixed to a specific arbour cannot be achieved by the conventional annular cutter 1.

Japanese Examined Utility Model Application No. 64-3603 discloses one of the conventional annular cutter connecting apparatus which uses a bolt by which an annular cutter is connected to an arbour. This conventional apparatus will be described with reference to Fig. 3. The shank portion 24 of an annular cutter is inserted in the central bore 26 of an arbour 25. Then, a fixing bolt 27 provided in the arbour 25 is turned to engage a flat face 28 formed on the lateral wall of the shank portion 24, and the annular cutter is connected to the arbour 25. The centre O_1 of the shank portion 28 should coincide with the centre O_2 of the receiving hole 26 of the arbour 25. Actually, however, slight manufacturing errors of the shank portion 24 and the receiving hole 26 and/or fitting tolerances between them produce a centre displacement δ ranging from 1/100 to 1/50mm. This displacement provides eccentricity of the annular cutter, giving an adverse effect to the annular cutter.

The first object of the present invention is to provide an annular cutter connecting apparatus which connects to a drilling machine only an annular cutter suited for the drilling machine and prevents a pushing sleeve of the apparatus from being loosened or removed even when cut chips are wound around the pushing sleeve during the drilling operation.

The second object of the present invention is to provide an annular cutter to be connected to a drilling machine by means of such an annular cutter connecting

apparatus.

5 In order to achieve the first objective of the present invention, an annular cutter comprises a shank extending along an axis of the annular cutter that can be adapted to be inserted into and removed from a bore of an arbour. The shank can be fastened, and the arbour has a first end connected to a cutter drive and the other end where the bore opens to receive the shank.

10 According to the features of claim 1, the arbour comprises a cylindrical wall defining the bore, a hole radially extending through the wall with a lock member radially movable and received in the hole, an operative sleeve provided around the wall, a spring for urging the sleeve towards said second position, and a support member adapted to engage with the locking member radially inwardly when urged by the first control surface of the operative sleeve, and when the shank is not inserted into the bore, to hold the locking member such that the locking member radially projects into the bore. This is to ensure that the drilling machine only accepts an annular cutter suited for itself and the arbour is attached with ease.

25 According to claim 1, the annular cutter comprises a locking member, a recessed locking member and has means adapted to be engaged with the support member.

30 According to claim 1, the operating sleeve has two control surfaces, with the sleeve having first and second control surfaces to be radially aligned with the hole in its first and second positions, respectively with the second control surface being radially inside in relation to the first control surface.

35 According to claim 1, the locking member extends axially on the shank to a predetermined length from a free end of the shank and is adapted to pass the locking member when engaged by the first control surface and thereby radially projecting into the bore when the shank is inserted into the bore.

40 According to claim 1, once the shank is inserted into the bore, the support member is disengaged from the locking member and released.

45 According to claim 1, once the shank is inserted into the bore at a predetermined length, the recessed locking member is radially aligned with the locking member so that the receiving portions allow the corresponding locking member to move radially inward. This allows the

50

sleeve to move to the second position by means of the spring, whereby the second control surface engages with and secures the locking members in the depressed locking member receiving portions.

5

In order to achieve the second object of the present invention, an annular cutter comprises a substantially hollow cylindrical blade portion having one end, a shank portion coaxially formed on the end of the blade portion having a lateral side, locking member passing means formed on the lateral side of the shank portion and depressed locking member receiving portions formed in or on the locking member passing means and arranged circumferentially thereof.

10

Fig. 1 is a longitudinal cross-sectional view of a conventional annular cutter connecting apparatus;

15

Fig. 2 is a side view of the main part of the annular cutter connecting apparatus of Fig. 1;

20

Fig. 3 is a transversal cross-sectional view of the fixing portion of another conventional annular connecting apparatus using a fixing bolt with an annular cutter fixed thereto;

25

Fig. 4 is a longitudinal cross-sectional view of the main part of an annular cutter connecting apparatus according to one embodiment of the present invention in which an annular cutter to be connected the arbour of the apparatus is separated from the apparatus;

30

Fig. 5 is a longitudinal cross-sectional view of the main part of the annular cutter connecting apparatus of Fig. 4 with the annular cutter connected to the arbour;

35

Fig. 6 is a longitudinal cross-sectional view of the pushing sleeve of the annular cutter connecting apparatus of Fig. 4;

40

Fig. 7 is a cross-sectional view along line 7-7 in Fig. 6;

6;

Fig. 8 is a cross-sectional view along line 8-8 in Fig. 4;

45

Fig. 9 is a cross-sectional view along line 9-9 in Fig. 4;

4;

50

8a

Fig. 10 is a cross-sectional view along line 10-10 in Fig. 5;

5 Fig. 11 is a front view of a first embodiment of an annular cutter according to the present invention;

Fig. 12 is a side view of the annular cutter of Fig. 11;

Fig. 13 is a transversal cross-sectional view of second and third embodiments of annular cutters according to the present receiving portions;

5 Fig. 14 is a front view of the third embodiment of the annular cutter according to the present invention;

Fig. 15 is a side view of the third embodiment of the annular cutter;

Fig. 16 is a front view of a fourth embodiment of an annular cutter according the present invention; and

10 Fig. 17 is a side view of the annular cutter of Fig. 16.

An annular cutter connecting apparatus and an annular cutter according to the present invention will be described by way of preferred embodiments with reference to the accompanying drawings.

15 First, the annular cutter connecting apparatus according to the present invention will be described.

As shown in Figs. 4 and 5, a rotational speed and a feed required for drilling operation is transmitted from a drilling machine (not shown) to an arbour 101 connected thereto. The arbour 101 is formed with a cylindrical central bore 102 to which cutting oil is supplied from the drilling machine through an oil passage (not shown).

25 A seal member 103 is set in position by a retaining ring 104 in the lower portion of the central bore 102. A valve body 105 for opening and closing oil paths comprises a head portion 106, a flange portion 107 formed at the side of the seal member 103 and formed with oil grooves 108 and a rod portion 109
30 coaxially extending downward from the flange portion 107 and idly fitted in the central hole 103a of the seal member 103.

In the non-operative condition, the flange portion 107 is pressed against the seal member 103 by the
35 urging force of a compression coil spring 110 provided

in the central bore 102, thereby preventing the cutting oil from leaking downward from the central hole 102. The valve body 105, the seal member 103 and the compression coil spring 110 constitute a valve for opening and closing the oil paths.

During the drilling operation, the centre pin 138 of each of annular cutters 130A, 130B, 130C and 130D which will be described later in detail is pressed against a workpiece and is lifted up. The head portion 139 formed on the upper end of the centre pin 138 abuts against the lower end of the rod portion 109 of the valve body 105 and raises it. The flange portion 107 is separated from seal member 103 against the urging force of the compression coil spring 110. As a result, the cutting oil flows down through the oil passages 108, spaces formed between the flange portion 107 and the seal member 103 and between the inner peripheral surface of the central hole of the seal member 103 and the outer peripheral surface of the rod portion 109 and reaches the edges of the blade portion 131.

Holding holes 112 for receiving locking members for fixing the annular cutter 130A (balls 113 in this embodiment and hereinafter referred to as the "fixing balls 113") are circumferentially arranged in the lower end portion 111 of the arbour 101. Each holding hole 112 may have the same inner diameter throughout the whole depth, but it is preferred that the inner wall of the holding hole 112 be tapered so that the inside inner diameter at the inner end of the hole 112 is smaller than the outside inner diameter at the outer end thereof. This prevents the balls 113 from falling in the central bore 102 of the arbour 101.

A substantially hollow cylindrical supporting member 114 is axially slidably fitted in the lower end portion of the central bore 102 and is urged downward by the urging force of a compression coil spring 114

provided between the supporting member 114 itself and the retaining ring 104. In the outer peripheral wall of the lower end portion of the supporting member 114 is formed an annular neck 116 having a smaller outer diameter than the remaining part of the outer peripheral wall, for receiving the fixing balls 113 which partially project from the holding holes 112 toward the central bore 102. The depth of the annular neck 116 is shown by E in Fig. 8.

The outer peripheral surface 117 of the lower end portion 111 of the arbour 101 is reduced in diameter and an annular cutter fixing sleeve 118 is fitted thereon. As shown in Figs. 6 and 7, the sleeve 118 comprises a cylindrical first control face 119 defined by the inner peripheral surface of the sleeve 118 and having an inner diameter equal to the outer diameter of the lower portion 111 of the arbour 101, and second control faces 120 forming shallow U-shaped depressions arranged circumferentially in the first control face 119. A ring-shaped return spring chamber 121 formed in the end of the sleeve 118 which end becomes the lower end of the sleeve 118 when it is attached to the arbour 101. In this embodiment, three second control faces 120 are arranged circumferentially equidistantly arranged in the first control face 119. The number of the second control faces is not limited to three. However, three are the most suitable because the shank portion of the annular cutter is supported most stably by the three second control faces 120. The second control faces 120 may be circumferentially arranged at irregular intervals, but it is preferable that they be arranged regularly so that they receive equal loads.

The first control face 119 pushes the fixing balls 113 and causes parts of the fixing balls 113 to project from the holding holes 112 deep into the central bore 102. The sleeve 118 can be rotated in the direction of

an arrow A as shown in Fig. 8. In a non-operative condition, the sleeve 118 assumes the rotated state in the direction of the arrow A by means of the a return spring 124 as shown in Fig. 8. In this state, the
5 fixing balls 113 are in contact with the corresponding second control faces 120 and are received by the neck portion 116 of the supporting member 114. Thus, they are at the waiting position as shown in Fig. 4.

Referring to Figs. 4 and 5, the return spring
10 chamber 121 is covered with a ring cover 151 held on the lower end of the outer peripheral wall of the arbour 101 by a holding ring 152.

As shown in Figs. 4 to 6 and 9, a substantially C-shaped return spring 124 is housed in the return
15 spring chamber 121. One end 125 of the return spring 124 is fixed to the arbour 101 and the other end 126 thereof is fixed to the sleeve 118, and the sleeve 8 is always urged in the direction of the arrow A in Fig. 8 so as to push the fixing balls 113 into the central
20 bore 102.

Next, embodiments of annular cutters according to the present invention will be described.

Fig. 11 and 12 show a first embodiment of an annular cutter 130A according to the present invention
25 which comprises a substantially hollow cylindrical blade portion 131 having the open lower end and a cylindrical shank portion 132A formed coaxially on its upper end. On the lateral side of the shank portion 132A are formed flat faces 133 arranged circumferentially at equal intervals. A depressed ball receiving
30 portion 134A forming a hemispherical depression for receiving the respective fixing ball 113 is formed in each flat face 133. The depressed ball receiving portion 134A is an example of a locking member
35 receiving portion for connecting an annular cutter to an arbour.

Fig. 13 is a transversal cross-sectional view showing a second annular cutter 130B in a state in which it is connected to the arbour 101. A cylindrical shank portion 132B is coaxially formed on the upper end of a blade portion 131 having the same structure of the blade portion 131 of the first embodiment of the annular cutter 130A, and flat faces 133 are formed on the lateral side of the shank portion 132B in the same manner as the flat faces 133 on the shank portion 132A of the first embodiment of the annular cutter 130A. A ball receiving portion 134B having a conical shape in a horizontal cross section is formed in each flat face 133. The ball receiving portion 134B is also an example of the locking member receiving portion.

Figs. 14 and 15 show a third embodiment of an annular cutter 130C of the present invention. Its shank portion 132C has the same structure as the shank portion 132A of the first embodiment of the annular cutter 130A (the shank portion 132A having the hemispherically depressed ball receiving portions 134A) or the shank portion 132B of the second embodiment of the annular cutter 130B (the shank portion 132B having the conically depressed ball receiving portions 134B). Another flat face 153 is formed on the portion of the outer peripheral surface of the shank portion 132C between adjacent two flat faces 133. The flat face 153 is shown by broken lines in Figs. 4 and 5. The other structure is the same as that of the first and second embodiments of the annular cutters 130A and 130B. The annular cutter 130C can be connected to an arbour by means of a conventional annular cutter connecting apparatus by using the flat face 153 as a passing portion.

Fig. 13 also shows a transversal cross section of the third embodiment of the annular cutter 130C having conically depressed ball receiving portions in a state

in which the annular cutter 130C is connected to the
arbour 101. The annular cutter, the shank portion and
the conically depressed ball receiving portions of the
third embodiment are shown by (130C), (132C) and
5 (134C), respectively, in Fig. 13.

Figs. 16 and 17 show a fourth embodiment of an
annular 130D which has a blade portion 131 having the
same structure as that of the first embodiment of the
annular cutter 130A. A cylindrical guide portion 135
10 is coaxially formed on the upper end of the shank
portion 132D provided on the upper end of the blade
portion 131. The guide portion 135 has an outer
diameter reduced from the outer diameter of the shank
portion 132D so that it does not hit against the fixing
15 balls 113 when the shank portion 132D is inserted in
the central bore 102 of the arbour 101.

Hemispherically depressed ball receiving portions 134D
are formed circumferentially in a step portion 136
defined between the upper end of the shank portion 132D
20 and the lower end of the guide portion 135. The
depressed ball receiving portion 134D is also an
example of the locking member receiving portion.

In the embodiments described above, the flat faces
133 and guide portion 135 constitute locking member
25 passing means, and the locking member passing means and
the locking member receiving portions constitute
engaging portions.

The number, the positions and sizes of the flat
faces 133 of the annular cutter 130A and 130B, and the
30 guide portions 135 and the ball receiving portions
134A, 134B, 134C and 134D of the annular cutters 130C
and 130D correspond to the number, the positions and
the size of the fixing balls 18 when the shanks of the
annular cutter are fully inserted in the central bore
35 102 of the arbour 101 (Fig. 5). Because of this
arrangement, only the specific annular cutters 132A,

132B, 132C and 132D can be connected to the arbour 101 but other annular cutters cannot be connected thereto. Each of the shank portions of the first to fourth embodiments of the annular cutters has three ball receiving portions arranged circumferentially equidistantly. However, the shank portion may have a polygonal cross section.

As shown in Figs. 5 and 6, the centre pin 137 for setting a to-be-drilled position extends through the centre hole of the annular cutter 130A so as to be movable axially. On the upper end of the centre pin 138 is formed a head 139 having a larger outer diameter than the outer diameter of the centre pin 138 so as to prevent the centre pin 138 from slipping off the central hole 137 of the annular cutter 130A. As described above, the point formed on the lower end of the centre pin 138 abuts against a workpiece which is being drilled, and the centre pin 138 is lifted. The valve body 105 for opening and closing the oil passage is lifted by the head 139 of the centre pin 138 to allow the cutting oil in the arbour 101 to flow down to the edges of the blades formed on the blade portion 131 of the annular cutter 130A. Each of the second to fourth embodiments of the annular cutters 130B, 130C and 130D is provided with a centre pin having the same structure as that of the first embodiment of the centre pin 138.

Operation

First, the processes of how to fix the annular cutters to the arbors will be described.

The shank portion 132A of the annular cutter 130A is inserted from below in the central bore 102 of the arbour 101 which is in a state shown in Figs. 4 and 8. As the shank portion 132A is inserted, the supporting member 114 is lifted by the shank portion 132A and disengaged from the fixing balls 113. The fixing balls

113 roll on the flat faces 133 and engage the ball receiving portions 134A provided in the shank portion 132A at the final stage of the insertion. At the same time, the sleeve 118 is rotated in the direction of the arrow A in Fig. 8 by the urging force of the return spring 124. As a result, the fixing balls 113 contact the first control face 119 and are firmly pushed in the ball receiving portions 134A. Thus, the annular cutter 130A is connected to the arbour 101 in one-touch operation, as shown in Fig. 5.

Upon the connection of the first embodiment of the annular cutter 130A to the arbour 101, the upper end of the shank portion 132A reaches the region of the fixing balls 113, as the shank portion 132A is inserted in the central bore 102 of the arbour 101. When the flat faces 133 of the shank portion 132A are axially aligned with the fixing balls 113, the fixing balls 113 engage the ball receiving portions 134A by merely pushing the annular cutter 130A in the central hole. When, on the other hand, the flat faces are not axially aligned with the fixing balls 113, the upper end of the shank portion 132A hits against the fixing balls 113, and no further insertion of the shank portion 132A is permitted. However, after the flat faces 133 have been aligned with the fixing balls 113 by rotating the annular cutter 130A around its own axis, the annular cutter 130A can be inserted further, enabling the fixing balls 113 to be engaged with the ball receiving portions 134A easily so that the connection of the annular cutter 130A to the arbour 101 is completed.

The second and third embodiments of the annular cutters 130B and 130C can be connected to the arbour 101 in the same way as the first embodiment of the annular cutter 130A. As described above, the third embodiment of the annular cutter 130C can be connected to the arbour by means of a conventional annular cutter

connecting apparatus.

5 In an aligned state, the fourth embodiment of the annular cutter 130D is fully inserted in the central hole 102 of the arbour 101, and the balls 113 are fitted in the ball receiving portions 134D, whereby the annular cutter 130D is connected to the arbour 101. In a misaligned state, however, the step portion 136 of the shank portion 134D hits against the fixing balls 113, as the shank portion 134D is inserted in the
10 central bore 102 of the arbour 101. In this case, the cutter 130D is rotated around its own axis to axially align the receiving portions 134D with the fixing balls 113. Thereafter, the shank portion 132D is further inserted in the central bore 102 of the arbour 101 so
15 that the fixing balls 113 engage the ball receiving portions 134D. In this way, the annular cutter 130D is connected to the arbour 101.

The three point support attained by the balls 113 of the first to fourth embodiment 130A, 130B, 130C and
20 130D ensures accurate transmission of the rotation and the rotational force from the arbour 101 to the annular cutters 130A, 130B, 130C and 130D and prevention of centre displacement between the annular cutter and the arbour 101, leading to accurate drilling operation.
25 The reception of the balls 13 in the ball receiving portions of the shank portion of the annular cutter according to the present invention allows the annular cutter to be moved slightly upward and downward repeatedly due to the cutting resistance or the like
30 during the drilling operation so that cut chips are broken into small pieces, the drilling efficiency is improved and the life of the annular cutter is prolonged.

35 As apparent from the above description, only an annular cutter having locking member passing means whose size and arrangement are suited for an annular

cutter connecting apparatus which is now to be used can be connected to an arbour, but an unsuitable annular cutter is prevented from being connected thereto. Even when long chips are produced and wound around the sleeve 118 thereby lifting the sleeve 118, the sleeve 118 is not rotated in the direction in which the annular cutter is released from the annular cutter connecting apparatus. Thus, the annular cutter is not loosened or removed by such chips from the arbour 101.

10 The annular cutter is removed from the arbour 101 in the following way.

15 The sleeve 118 of the annular cutter 130A is manually rotated in the direction opposite to the direction of the arrow A in Fig. 8, and the second control faces 120 are caused to face the fixing balls 113. Then, the annular cutter 130A is pushed downward by the urging force of the compression coil spring 115 and automatically slips off the arbour 101. Thus, the removal of the annular cutter 130A from the arbour 101 can also be performed in one-touch operation, although it is necessary to hold the annular cutter 130A during its removal in order to avoid dropping of the annular cutter 130A. As the annular cutter 130A is pushed out of the arbour 101, the supporting member 114 is lowered by the urging force of the compression coil spring 115, and finally the fixing balls 113 are held by the annular neck 116. In this way, the annular cutter connecting apparatus is returned to the original state as shown in Fig. 4. The removing operation is applicable to the other embodiments of the annular cutters 130B, 130C and 130D.

CLAIMS

1. An annular cutter comprising:

5 a shank extending along an axis of the annular
cutter that can be adapted to be inserted into and removed
from a bore of an arbour;

said shank being able to be fastened;

said arbour having a first end to be connected to a
cutter drive and a second end where said bore opens to
10 receive said shank;

said arbour having:

a cylindrical wall defining said bore;

a hole radially extending through said wall;

15 a lock member radially movable and received
in said hole;

an operating sleeve having two control
surfaces, said sleeve having first and second
control surfaces to be radially aligned with
said hole in its first and second positions,
20 respectively with said second control surface
being radially inside in relation to said
first control surface;

a spring for urging said sleeve towards said
second position;

25 a support member adapted to engage with
said locking member radially inwardly when
urged by said first control surface of said
operative sleeve, and when said shank is not
inserted into said bore, to hold said locking
30 member such that the locking member radially
projects into said bore;

said annular cutter having:

a locking member passing means that extends axially on
said shank to a predetermined length from a free

end of the shank and is adapted to pass
said locking member when engaged by said
first control surface and thereby radially
projecting into said bore when said shank is
5 inserted into said bore;

means adapted to be engaged with said support
member thereby disengaging said support
member from said locking member when said
shank is inserted into said bore;

10 recessed locking member receiving portions
formed in or on said locking member passing
means such that when said shank is inserted
into said bore at a predetermined length, the
recessed locking member receiving portion is radially
15 aligned with said locking member so that the recessed
locking member receiving portions allows the
corresponding locking member to move radially inward,
whereby allowing the said sleeve to move to the
second position by means of said spring, and
20 said second control surface engages with and
secures the locking members in said depressed
locking member receiving portions.

25 2. An annular cutter according to claim 1, wherein
said locking member passing means comprises flat faces
formed on and arranged circumferentially of said side of
said shank portion, and said depressed locking member
receiving portions are formed in said flat faces.

30 3. An annular cutter according to claim 2, wherein
said depressed locking member receiving portions are
hemispherical.

20a

4. An annular cutter according to claim 2, wherein
said depressed locking member receiving portions are
conical.
- 5
5. An annular cutter according to any one of claims 2
to 4, wherein another flat portion for passing a locking
member of a conventional annular cutter connecting
apparatus is formed on said outer peripheral surface of
10 said shank portion between two adjacent ones of said flat
portions.
6. An annular cutter according to claim 1, wherein
said locking member passing means comprises a cylindrical
15 guide portion having a smaller outer diameter than said
shank portion and formed on said other end of said shank
portion, an annular step portion, in which said depressed
locking member receiving portions are defined between said
shank portion and said guide portion.
- 20
7. An annular cutter according to claim 5, wherein
said depressed locking member receiving portions are
hemispherical.
- 25 8. An annular cutter, substantially as hereinbefore
described with reference to Figures 4, 5 and 11 to 17.