

HEMETIC MOTOR COOLING FOR HIGH TEMPERATURE ORGANIC RANKINE CYCLE SYSTEM

5

BACKGROUND

The present disclosure relates generally to Organic Rankine Cycle (ORC) systems and, more particularly, to a secondary cooling system therefor.

The Organic Rankine Cycle (ORC) is a vapor power cycle with an organic fluid refrigerant instead of water/steam as the working fluid. The working fluid is heated in an “evaporator/boiler” by a source of waste or low quality heat. The fluid starts as a liquid and ends up as a vapor. The high-pressure refrigerant vapor expands in the turbine to produce power. The low-pressure vapor exhausted from the turbine is condensed then sent back to the pump to restart the cycle.

The simple Rankine cycle used for power generation follows the process order: 1) Adiabatic pressure rise through a pump; 2) Isobaric heat addition in a preheater, evaporator and superheater; 3) Adiabatic expansion in a turbine; and 4) Isobaric heat rejection in a condenser, although other cycle modifications are possible such as the addition of a vapor-to-liquid recuperator.

ORC generators may be hermetic or non-hermetic. Non-hermetic generators do not share the working fluid environment and are typically cooled by air or water. Hermetic generators share and are cooled by refrigerant from the main cycle.

Figure 1 schematically illustrates a conventional Organic Rankine Cycle system with standard hermetic generator cooling. A small secondary flow of liquid refrigerant is extracted from the pump exit and communicated to the generator casing. In this case the fluid is first fed through a stator cooling jacket and partially boils while picking up heat from stator losses. The remaining two-phase refrigerant is then sprayed into the rotor volume picking up heat from rotor and windage losses. The vaporized refrigerant is then vented downstream of the turbine exhaust.

30

SUMMARY

An Organic Rankine Cycle (ORC) system according to an exemplary aspect of the present disclosure includes a turbine driven by a working fluid and a generator

driven by the turbine. The generator includes a rotor volume at sub-atmospheric pressure, the working fluid sprayed into said rotor volume.

5 An Organic Rankine Cycle (ORC) system according to an exemplary aspect of the present disclosure includes a secondary cooling flow circuit in communication with a rotor volume at sub-atmospheric pressure, said secondary cooling flow circuit sprays a working fluid into said rotor volume.

A method of operating an Organic Rankine Cycle (ORC) system according to an exemplary aspect of the present disclosure includes spraying a working fluid into a rotor volume at sub-atmospheric pressure.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Various features will become apparent to those skilled in the art from the following detailed description of the disclosed non-limiting embodiment. The drawings that accompany the detailed description can be briefly described as follows:

15 Figure 1 is a schematic diagram of a RELATED ART organic Rankine cycle in which the low-side saturation temperature is cool enough to provide generator cooling; and

Figure 2 is a schematic diagram of an organic Rankine cycle with a low side saturation temperature is too warm for direct generator cooling and a secondary cooling flow circuit according to one disclosed non-limiting embodiment;

20 Figure 3 is an expanded view of a turbine generator of the organic rankine cycle with a secondary cooling flow circuit.

Figure 4 is an expanded cross-sectional view of a shaft seal with dual labyrinth seals.

25

DETAILED DESCRIPTION

Figure 2 schematically illustrates an Organic Rankine Cycle (ORC) system 20. The ORC system 20 generally includes a power producing turbine 22 which is driven by a working fluid such as Siloxane MM, Novec649, or other high boiling point refrigerant. The turbine 22 drives a generator 24 that produces power. A refrigerant pump 26 increases the pressure of the working fluid from a condenser 28. An evaporator 30 such as a boiler receives a significant heat input from a heat source circuit (thermal oil in this example) 36, vaporizes the working fluid with the vapor

then passed through to the turbine 22. Upon leaving the turbine 22, the relatively lower pressure vapor passes to the condenser 28 where it is condensed by way of heat exchange relationship with a cooling fluid system 38. The condensed working fluid is then circulated to the evaporator 30 by the pump 26 to complete the cycle. It should be appreciated, however, that additional cycles and other fluids may alternatively be utilized.

With reference to Figure 3, the generator 24 generally includes a housing 40, a stator 42, a rotor 44, and a rotor seal 46. The rotor seal 46 separates the generator 24 from the turbine 22 which generally includes a radial inflow turbine 48, a volute 50 and nozzle, shroud and diffuser. That is, the rotor seal 46 separates a turbine volume T from a rotor volume G. The radial inflow turbine 48 rotates within the turbine volume T about an axis A in response to a working fluid communicated through the volute 50 to drive the generator 22 through the rotor 44. The radial inflow turbine 48 rotates the rotor 44 about the axis of rotation A within the stator 42. The example shown in Figure 3 is an oil-free high-speed direct-drive system with magnetic bearings and no gears, but other embodiments will have the same seal and cooling requirements.

A secondary cooling flow circuit 51 communicates a relatively small amount of the cooling fluid to the generator 22 to provide thermal management thereof. The secondary cooling flow circuit 51 generally includes a cold heat exchanger 52 to condense the working fluid and effectively pulls the working fluid out of the housing 40 through a main drain line 54. The secondary loop condenser 52 also receives cooling fluid. The main drain line 54 removes vapor and liquid working fluid from the housing 40 and generates a sub-atmospheric pressure within the rotor volume G.

Below the cold heat exchanger is a receiver tank 53 to accumulate liquid. A pump 56 pumps the condensed/cooled working fluid from the receiver tank 53 to a valve system that consists of a restriction valve 57, and a check valve 59. The valve 57 is varied to set the pressure at the pump exit. If the valve 57 is wide open then the pump exit pressure will be only slightly above the rotor cavity pressure and well below the primary system pressure. The check valve 59 will remain closed and no refrigerant will flow through line 26I.

As valve 57 closes, the pump exit pressure rises until it exceeds the primary system pressure at 26 and refrigerant flows out of the secondary cooling loop 51 to the primary loop. This flow is necessary because flow leaks into the secondary

cooling loop 51 through the seal 46 and must be removed or else loop 51 may eventually fill up with liquid working fluid. Valve 57 is thus used to control the amount of working fluid in circuit 51.

From Valve 57, the liquid working fluid flows into the stator cooling jacket to
5 absorb heat from the stator 42 generated by joule heating, and the liquid working fluid is partially boiled.

The working fluid is then sprayed into the rotor volume G through a nozzle
58. It should be appreciated that one or more nozzles may be circumferentially
arranged about the rotor 44. Since the working fluid received heat from the stator 42,
10 the working fluid is now two-phase. A small pressure drop may be used at the nozzle
to disperse the working fluid. As the working fluid is in a saturated environment
within the housing 40, the working fluid will be at a temperature determined by its
pressure. The working fluid passes between the rotor 44 and the stator 42 and further
receives heat generated by windage and rotor internal losses when sprayed toward the
15 rotor 44. The working fluid thereafter collects in the housing 40 and reenters the main
drain line 54.

With reference to Figure 4, dual labyrinth seals, 46A and 46B, are used on
each side of a circumferential groove 62. In one disclosed non-limiting embodiment, a
seal bleed line 58 communicates with the rotor seal 46 to prevent relatively hot vapor
20 from the radial in flow turbine 46 from blowing through the seal 46 into contact with
the bearing system 60 which supports rotor 44. In the disclosed, non-limiting
embodiment, the seal 46 may include a circumferential groove 62 or other passage
which delineates the separation between the rotor volume G from the turbine volume
T. The groove 62 is in communication with the seal bleed line 58 to thereby provide
25 a bypass from the rotor seal 46 to the main drain line 54.

It should be understood that relative positional terms such as "forward," "aft,"
"upper," "lower," "above," "below," and the like are with reference to the normal
operational attitude of the vehicle and should not be considered otherwise limiting.

It should be understood that like reference numerals identify corresponding or
30 similar elements throughout the several drawings. It should also be understood that
although a particular component arrangement is disclosed in the illustrated
embodiment, other arrangements will benefit herefrom.

Although particular step sequences are shown, described, and claimed, it
should be understood that steps may be performed in any order, separated or

combined unless otherwise indicated and will still benefit from the present disclosure.

5 The foregoing description is exemplary rather than defined by the limitations within. Various non-limiting embodiments are disclosed herein, however, one of ordinary skill in the art would recognize that various modifications and variations in light of the above teachings will fall within the scope of the appended claims. It is therefore to be understood that within the scope of the appended claims, the disclosure may be practiced other than as specifically described. For that reason the appended claims should be studied to determine true scope and content.

CLAIMS

What is claimed is:

1. An Organic Rankine Cycle (ORC) system comprising:
5 a turbine driven by a working fluid; and
a generator driven by said turbine, said generator includes a rotor volume at sub-atmospheric pressure, said working fluid sprayed into said rotor volume.
2. The system as recited in claim 1, wherein the working fluid is Siloxane MM.
10
3. The system as recited in claim 1, wherein the working fluid is Novec649.
4. The system as recited in claim 1, wherein said working fluid is communicated over a stator of said generator.
15
5. The system as recited in claim 1, further comprising a rotor seal which separates said rotor volume from a turbine volume.
6. The system as recited in claim 5, further comprising a bleed line in
20 communication with said rotor seal.
7. The system as recited in claim 6, further comprising a main drain line in communication with said rotor volume.
- 25 8. The system as recited in claim 7, wherein said bleed line is in communication with said main drain line.
9. The system as recited in claim 8, further comprising a heat exchanger in communication with said main drain line.
30
10. The system as recited in claim 9, further comprising a pump downstream of said heat exchanger.

11. An Organic Rankine Cycle (ORC) system comprising:
a secondary cooling flow circuit in communication with a rotor volume at sub-atmospheric pressure, said secondary cooling flow circuit sprays a working fluid into said rotor volume.
- 5
12. The system as recited in claim 11, wherein said working fluid is communicated over a stator within the rotor volume.
13. The system as recited in claim 11, further comprising a rotor seal which
10 separates said rotor volume from a turbine volume.
14. The system as recited in claim 13, further comprising a bleed line in communication with said rotor seal.
- 15 15. The system as recited in claim 14, further comprising a main drain line in communication with said rotor volume and said bleed line.
16. The system as recited in claim 15, further comprising a heat exchanger in communication with said main drain line and a pump downstream of said heat
20 exchanger, a operable to increase a pump exit pressure until the pump exit pressure exceeds a primary system pressure such that said working fluid flows out of said secondary cooling loop to a primary cooling loop.
17. A method of operating an Organic Rankine Cycle (ORC) system comprising:
25 spraying a working fluid into a rotor volume at sub-atmospheric pressure.
18. The method as recited in claim 17, further comprising:
communicating the working fluid over a stator prior to the spraying.
- 30 19. The method as recited in claim 17, further comprising:
separating the rotor volume from a turbine volume with a rotor seal; and
bleeding the working fluid from the rotor seal.

20. The method as recited in claim 17, further comprising:

closing a valve to increase a pump exit pressure until the pump exit pressure exceeds a primary system pressure and the working fluid flows out of a secondary cooling loop to a primary cooling loop.