

Description

The invention relates to a fuel-oxidant mixture for use with an apparatus for flame plating using detonation means and the coated layer produced therefrom. More particularly, the invention relates to a fuel-oxidant mixture containing at least two combustible gases, such as, for example, acetylene and propylene.

Flame plating by means of detonation using a detonating gun (D-Gun) have been used in industry to produce coatings of various compositions for over a quarter of a century. Basically, the detonation gun comprises a fluid-cooled barrel having a small inner diameter of about 2.5 cm (about one inch). Generally a mixture of oxygen and acetylene is fed into the gun along with a comminuted coating material. The oxygen-acetylene fuel gas mixture is ignited to produce a detonation wave which travels down the barrel of the gun where it heats the coating material and propels the coating material out of the gun onto an article to be coated. US- A-2 714 563 discloses a method and apparatus which utilizes detonation waves for flame coating. The use of other gas mixtures such as hydrogen-air, propane-oxygen, and hydrogen oxygen is also therein disclosed. However these fuel gases are not mixed with acetylene.

In general, when the fuel gas mixture in a detonation gun is ignited, detonation waves are produced that accelerate the comminuted coating material to about 731.5m/sec (about 2400 ft/sec) while heating it to a temperature about its melting point. After the coating material exits the barrel of the detonation gun a pulse of nitrogen purges the barrel. This cycle is generally repeated about four to eight times a second. Control of the detonation coating is obtained principally by varying the detonation mixture of oxygen to acetylene.

In some application, such as, for example, producing tungsten carbide-cobalt-based coatings, it was found that improved coatings could be obtained by diluting the oxygen-acetylene fuel mixture with an inert gas such as, for example, nitrogen or argon. The gaseous diluent has been found to reduce or tend to reduce the flame temperature since it does not participate in the detonation reaction. US- A- 2 972 550 discloses the process of diluting the oxygen-acetylene fuel mixture to enable the detonation-plating process to be used with an increased number of coating compositions and also for new and more widely useful applications based on the coating obtainable.

Generally, acetylene has been used as the combustible fuel gas because it produces both temperatures and pressures greater than those obtainable from any other saturated or unsaturated hydrocarbon gas. However, for some coating applications, the temperature of combustion of an oxygen-acetylene mixture of about 1:1 atomic ratio of oxygen to carbon yields combustion products much hotter than desired. As stated above, the general procedure for compensating for the high temperature of combustion of the oxygen-acetylene fuel gas is to dilute the fuel gas mixture with an inert gas such as, for example, nitrogen or argon. Although this dilution resulted in lowering the combustible temperature, it also results in a concomitant decrease in the peak pressure of the combustion reaction. This decrease in peak pressure results in a decrease in the velocity of the coating material propelled from the barrel onto a substrate. It has been found that with an increase of a diluting inert gas to the oxygen-acetylene fuel mixture, the peak pressure of the combustion reaction decreases faster than does the combustion temperature.

It has now been found possible to provide a gaseous fuel-oxidant mixture for use in a detonation gun that can provide for lower fuel combustion temperatures than that obtainable from conventional oxygen-acetylene fuel gases while providing for relatively high peak pressures in the combustion reaction.

It has also been found possible to provide a gaseous fuel-oxidant mixture for use in a detonation gun that can provide for the same fuel combustion temperatures as that obtainable from conventional oxygen-acetylene fuel gases diluted with an inert gas while not sacrificing peak pressure in the combustion reaction.

It has further been found possible to provide coatings for substrates using the gaseous fuel-oxidant mixture employed in the process of the present invention.

According to the present invention there is provided a process of flame plating with a detonation gun which comprises using a gaseous fuel-oxidant mixture comprising (a) an oxidant and (b) a fuel mixture comprising a mixture of acetylene and a second combustible gas selected from propylene, methane, ethylene, methyl acetylene, propane, pentane, a butadiene, a butylene, a butane, ethylene oxide, ethane, cyclopropane, propadiene, cyclobutane and mixtures thereof.

In one embodiment of the present invention a process of flame plating with a detonation gun comprises the step of introducing desired fuel and oxidant gases into the detonation gun to form a detonatable mixture, introducing a comminuted coating material into the detonatable mixture within the gun, and detonating the fuel-oxidant mixture to impinge the coating material onto an article to be coated. The detonation gun could comprise a mixing chamber and a barrel portion so that the detonatable fuel-oxidant mixture could be introduced into the mixing and ignition chamber while a comminuted coating material is introduced into the barrel. The ignition of the fuel-oxidant mixture would then produce detonation waves

which travel down the barrel of the gun where it heats the comminuted coating material and propels the coating material onto a substrate.

The oxidant for use in the present invention could be selected from oxygen, nitrous oxide and mixtures thereof and the like.

5 The combustible fuel mixture for use in this invention is acetylene (C_2H_2) and a second combustible gas selected from propylene (C_3H_6), methane (CH_4), ethylene (C_2H_4), methyl acetylene (C_3H_4), propane (C_3H_8), ethane (C_2H_6), butadienes (C_4H_6), butylenes (C_4H_8), butanes (C_4H_{10}), cyclopropane (C_3H_6), propadiene (C_3H_4), cyclobutane (C_4H_8), pentane, ethylene oxide (C_2H_4O) and mixtures thereof.

As stated above, acetylene is considered to be the best combustible fuel for detonation gun operations since it produces both temperatures and pressures greater than those obtainable from any other saturated or unsaturated hydrocarbon. To reduce the temperature of the reaction products of the combustible gas, nitrogen or argon was generally added to dilute the oxidant-fuel mixture. This had the disadvantage of lowering the pressure of the detonation wave thus limiting the achievable particle velocity. Unexpectedly, it was discovered that when a second combustible gas, such as, for example, propylene, is mixed with acetylene, the reaction of the combustible gases with an appropriate oxidant yields a peak pressure at any temperature that is higher than the pressure of an equivalent temperature nitrogen diluted acetylene-oxygen mixture. If, at a given temperature, an acetylene-oxygen-nitrogen mixture is replaced by an acetylene-second combustible gas-oxygen mixture, the gaseous mixture containing the second combustible gas will always yield higher peak pressure than the acetylene-oxygen-nitrogen mixture.

20 The theoretical values of RP% and RT% are defined as follows:

$$RP\% = 100 (P_D/P_0)$$



$$RT\% = 100 \Delta T_D/\Delta T_0$$

25 P_0 and ΔT_0 are respectively the pressure and temperature rise following the detonation of a 1:1 mixture of oxygen and acetylene from the following equation:



30 P_D and ΔT_D are, respectively, the pressure rise and temperature rise following the detonation of either an oxygen-acetylene mixture diluted with nitrogen or an acetylene-second hydrocarbon gas-oxygen mixture where the ratio of carbon to oxygen is 1:1.

Different temperatures are achieved by using different values for either X or Y in the following equation:



40 The values of RP% versus RT% for the detonation of either an oxygen-acetylene mixture diluted with nitrogen or an acetylene-second hydrocarbon-oxygen mixture are shown in Figure 1. As evident from Figure 1, as one adds N_2 , as in Equation 2a, to lower the value of ΔT_D and hence RT%, the peak pressure P_D and hence RP%, is also decreased. For example, if sufficient nitrogen is added to reduce ΔT_D to 60% of ΔT_0 , the peak pressure P_D drops to 50% of P_0 . If, however, an acetylene-second hydrocarbon-oxygen mixture is used for any value of ΔT_D or RT%, the value of P_D and hence RP% will be larger than if a nitrogen diluted acetylene-oxygen mixture is used. For example, as shown in Figure 1, if an acetylene propylene-oxygen mixture is used to obtain a value of RT% equal to 60%, the ratio of RP% is 80%, a value 1.6 times greater than if an acetylene-oxygen-nitrogen mixture is employed to achieve a value of RT% equal to the same value. It is believed that higher pressures increase particle velocity, which results in improved coating properties.

50 For most applications the gaseous fuel-oxidant mixture of this invention could have an atomic ratio of oxygen to carbon of from about 0.9 to about 2.0, preferably from about 0.96 to about 1.6 and most preferably from about 0.98 to 1.4. An atomic ratio of oxygen to carbon below 0.9 would generally be unsuitable because of the formation of free carbon and soot while a ratio above 2.0 would generally be unsuitable for carbide and metallic coatings because the flame becomes excessively oxidizing.

55 In a preferred embodiment of the invention the gaseous fuel-oxidant mixture would comprise from 35 to 80 percent by volume oxygen, from 2 to 50 percent by volume acetylene and 2 to 60 percent by volume of a second combustible gaseous fuel. In a more preferable embodiment of the invention the gaseous fuel-oxidant mixture would comprise from 45 to 70 percent by volume oxygen, from 7 to 45 percent by volume

acetylene and 10 to 45 percent by volume of a second combustible fuel. In another more preferable embodiment of the invention the gaseous fuel-oxidant mixture would comprise from 50 to 65 percent by volume oxygen, from 12 to 26 percent by volume acetylene and 18 to 30 percent by volume of a second combustible gaseous fuel such as, for example, propylene. In some applications, it may be desirable to add an inert diluent gas to the gaseous fuel-oxidant mixture. Suitable inert diluting gases would be argon, neon, krypton, xenon, helium and nitrogen.

Generally, all prior art coating materials that could be employed with the fuel-oxidant mixture of the prior art in detonation gun applications can be used with the novel gaseous fuel-oxidant mixture of this invention. In addition, the prior art coating compositions, when applied at lower temperatures and higher pressures than that of the prior art, produce coatings on substrates that have conventional compositions but novel and unobvious physical characteristics such as hardness. Examples of suitable coating compositions for use with the gaseous fuel-oxidant mixture of this invention would include tungsten carbide-cobalt, tungsten carbide-nickel, tungsten carbide-cobalt chromium, tungsten carbide-nickel chromium, chromium-nickel, aluminum oxide, chromium carbide-nickel chromium, chromium carbide-cobalt chromium, tungsten-titanium carbide-nickel, cobalt alloys, oxide dispersion in cobalt alloys, alumina-titania, copper based alloys, chromium based alloys, chromium oxide, chromium oxide plus aluminum oxide, titanium oxide, titanium plus aluminum oxide, iron based-alloys, oxide dispersed in iron based-alloys, nickel, nickel based alloys, and the like. These unique coating materials are ideally suited for coating substrates made of materials such as titanium, steel aluminum nickel, cobalt, alloys thereof and the like.

The powders for use in the D-Gun for applying a coating according to the present invention are preferably powders made by the cast and crushed process. In this process the constituents of the powder are melted and cast into a shell shaped ingot. Subsequently, this ingot is crushed to obtain a powder which is then screened to obtain the desired particle size distribution.

However, other forms of powder, such as sintered powders made by a sintering process, and mixes of powders can also be used. In the sintering process, the constituents of the powder are sintered together into a sintered cake and then this cake is crushed to obtain a powder which is then screened to obtain the desired particle size distribution.

Some examples are provided below to illustrate the present invention. In these examples, coatings were made using the following powder compositions shown in Table 1.

TABLE 1

Sample Powder	Coating Material Powders						
	Composition -wt %					Powder Size	
	Co	C	Fe	Other	W	% through Mesh*	Max. % of Min. size
A Cast & Crushed	9.0 to 10.0	4.3 to 4.8	1.5 max	.21 max	Bal.	95% through 325*	10% less than 5 microns
B Sintered	11 to 13	5.15 min	0.5 max	0.5 max	Bal.	98% through 325*	15% less than 15 microns
C Mix of Cast & Crushed & Sintered	10.5 to 12.5	4.5 to 4.8	1.25 max	1.0 max	Bal.	98% through 325*	15% less than 5 microns
D Cast & Crushed	10 to 12	3.9% to 4.3	2.0 max	0.2 max	Bal.	98% through 325*	10% less than 5 microns

*U.S. Standard Mesh size, "325" being equivalent to a mesh opening of 0.044 mm. Microns = micrometers.

EXAMPLE 1

The gaseous fuel-oxidant mixtures of the compositions shown in Table 2 were each introduced to a detonation gun to form a detonatable mixture having an oxygen to carbon atomic ratio as shown in Table 2. Sample coating powder A was also fed into the detonation gun. The flow rate of each gaseous fuel-oxidant mixture was 0.38 m³/min (13.5 cubic feet per minute-cfm) except for the samples 28, 29 and 30 which were 0.31 m³/min (11.0 cfm), and the feed rate of each coating powder was 53.3 grams per minute (gpm) except

for sample 29 which was 46.7 gpm and sample 30 which was 40.0 gpm. The gaseous fuel-mixture in volume percent and the atomic ratio of oxygen to carbon for each coating example are shown in Table 2. The coating sample powder was fed into the detonation gun at the same time as the gaseous fuel-oxidant mixture. The detonation gun was fired at a rate of about 8 times per second and the coating powder in the detonation gun was impinged onto a steel substrate to form a dense, adherent coating of shaped microscopic leaves interlocking and overlapping with each other.

The percent by weight of the cobalt and carbon in the coated layer were determined along with the hardness for the coating. The hardness of most of the coating examples in Table 2 were measured as the Rockwell superficial hardness and converted into Vickers hardness. The Rockwell superficial hardness method employed is per ASTM standard method E-18. The hardness is measured on a smooth and flat surface of the coating itself deposited on a hardened steel substrate. The Rockwell hardness numbers were converted into Vickers hardness numbers by the following formula: $HV.3 = -1774 + 37.433 HR45N$ where HV.3 is the Vickers hardness obtained with 0.3 kgf load and HR45N is the Rockwell superficial hardness obtained on the N scale with a diamond penetrator and a 45 kgf load. The hardness of the coatings of line 28, 29 and 30 was measured directly as Vickers hardness. The Vickers hardness method employed is measured essentially per ASTM standard method E-384, with the exception that only one diagonal of the square indentation was measured rather than measuring and averaging the lengths of both diagonals. A load of 0.3 kgf was used (HV.3). These data are shown in Table 2. The values shows that the hardness was superior for coatings obtained using propylene in place of nitrogen in the gaseous fuel-mixture.

Erosion is a form of wear by which material is removed from a surface by the action of impinging particles. The particles are generally solid and carried in either a gaseous or a fluid stream, although he particles may also be fluid carried in a gaseous stream.

There are a number of factors which influence the wear by erosion. Particle size and mass, and their velocity are obviously important because they determine the kinetic energy of the impinging particles. The type of particles, their hardness, angularity and shape, and their concentration may also affect the rate of erosion. Furthermore, the angle of particle impingement will also affect the rate of erosion. For test purposes, alumina and silica powders are widely used.

The test procedure similar to the method described in ASTM G 76-83 are used to measure the erosion wear rate of the coatings presented in the examples. Essentially, about 1.2 gm per minute of alumina abrasive is carried in a gas stream to a nozzle which is mounted on a pivot so that it can be set for various particle impingement angles while a constant standoff is maintained. It is standard practice to test the coatings at both 90° and 30° impingement angles.

During the test, the impinging particles create a crater on the test sample. The measured scar depth of the crater is divided by the amount of abrasive which impinged on the sample. The results, in micrometers (microns) of wear per gram of abrasive, is taken as the erosion wear rate (μ/gm). These data are also shown in Table 2.

The hardness and erosion wear data show that using an acetylene-hydrocarbon gas-oxygen mixture in place of a nitrogen diluted acetylene-oxygen mixture can produce a coating having a higher hardness at the same cobalt content (compare sample coating 9 with sample coatings 22 and 23) or higher cobalt content at the same hardness (compare sample coating 1 with sample coating 22).

TABLE 2

D-GUN PARAMETERS AND PROPERTIES OF COATINGS
MADE FROM POWDER A

Sample Coating	<u>Gaseous Fuel-Mixture</u> (Vol %)			<u>O₂ to C</u> <u>Atomic Ratio</u>	<u>Hardness</u> ⁽¹⁾ <u>Vickers</u> (Kg/mm ²)	<u>Chemistry</u>		<u>Erosion</u> (μ/gm)	
	<u>C₃H₆</u>	<u>C₂H₂</u>	<u>O₂</u>			<u>% Co</u>	<u>% C</u>	<u>90°</u>	<u>30°</u>
1	37.0	3.7	59.3	1.0	1130	19.1	3.5	116	22
2	29.8	12.8	57.4	1.0	1185	17.0	3.1	103	20
3	29.8	10.0	60.2	1.1	1185	15.6	2.3	85	20
4	29.8	7.5	62.7	1.2	1160	14.3	1.8	94	21
5	29.8	5.3	64.9	1.3	1145	13.3	1.6	92	22
6	29.8	3.2	67.0	1.4	1135	12.8	1.3	90	22
7	25.6	18.0	56.4	1.0	1225	16.7	3.5	94	19
8	25.6	16.6	57.8	1.05	1210	14.1	2.8	90	20
9	25.6	15.3	59.1	1.1	1225	13.6	2.1	82	19
10	25.6	12.9	61.5	1.2	1190	12.8	1.6	78	21
11	25.6	10.6	63.8	1.3	1185	11.4	1.4	75	20
12	25.6	8.6	65.8	1.4	1160	11.0	1.2	79	23
13	25.6	6.7	67.7	1.5	1145	10.6	1.0	81	24
14	25.6	5.7	68.7	1.6	1120	10.7	1.0	84	25
15	25.6	3.4	71.0	1.7	1110	10.3	0.9	94	26
16	18.6	26.7	54.7	1.0	1220	14.2	3.6	104	23
17	18.6	24.1	57.3	1.1	1240	11.3	2.2	87	24
18	18.6	21.8	59.6	1.2	1180	10.1	1.6	81	21

TABLE 2 (Continued)

**D-GUN PARAMETERS AND PROPERTIES OF COATINGS
MADE FROM POWDER A**

		Gaseous Fuel-Mixture (Vol %)			O ₂ to C Atomic Ratio	Hardness ⁽¹⁾ Vickers (Kg/mm ²)	Chemistry		Erosion (μ/gm)	
	Sample Coating	C ₃ H ₆	C ₂ H ₂	O ₂			% Co	% C	90°	30°
5	19	18.6	17.6	63.8	1.4	1195	8.0	0.9	74	20
10	20	18.6	14.1	67.3	1.6	1110	7.8	0.6	95	26
15	21	18.6	11.1	70.3	1.8	1095	7.9	0.6	122	28
20		N ₂	C ₂ H ₂	O ₂			% Co	% C	90°	30°
25	22	45	27.8	27.2	0.98	1140	13.6	3.6	94	20
30	23	45	27.5	27.5	1.0	1030	13.6	3.5	90	18
35	24	45	25.0	30.0	1.2	1009	11.4	2.1	77	16
	25	45	22.9	32.1	1.4	991	11.2	1.6	81	22
	26	45	21.2	33.8	1.6	883	10.9	1.2	94	23
	27	45	19.6	35.4	1.8	930	10.6	1.1	110	25
	28	40	30.3	29.7	0.98	1080*	13.2	3.5	106	20
	29	30	35.3	34.7	0.98	1150*	10.7	3.6	109	18
	30	10	42.8	42.2	0.98	1300*		3.7	119	20

Note (1) measured as Rockwell superficial hardness and converted to Vickers hardness unless otherwise indicated by an asterisk (*).

EXAMPLE 2

The gaseous fuel-oxidant mixture of the compositions shown in Table 3 were each introduced into a detonation gun at a flow rate of 0.38 m³/min (13.5 cubic feet per minute) to form a detonatable mixture having an atomic ratio of oxygen to carbon as also shown in Table 3. The coating powder was Sample A and the fuel-oxidant mixture and powder feed rate are as also shown in Table 3. As in Example 1, the Vickers hardness and erosion rate (μ/gm) data were determined and these data are shown in Table 3. As evidenced from the data, various hydrocarbon gases can be used in conjunction with acetylene to provide a gaseous fuel-oxidant mixture in accordance with this invention of coat substrates. The Vickers hardness data show that using an acetylene-hydrocarbon gas-oxygen mixture in place of an acetylene-oxygen-nitrogen mixture can produce either a coating having a higher hardness at the same cobalt content (compare sample coatings 5 and 10 with sample coating 23 in Table 2) or a coating having a higher cobalt

content for the same hardness (compare sample coatings 6, 8 and 11 with sample coating 22 in Table 2).

TABLE 3

O-GUN PARAMETERS AND PROPERTIES OF COATINGS
MADE FROM POWDER A

Sample Coating	Gaseous Fuel-Mixture (Vol %)			O ₂ to C Atomic Ratio	Powder Feed Rate (gpm)	Hardness Vickers (Kg/mm ²)	Chemistry		Erosion (μ/gm)	
	CH ₄	C ₂ H ₂	O ₂				% Co	% C	90°	30°
	<u>CH₄</u>	<u>C₂H₂</u>	<u>O₂</u>				<u>% Co</u>	<u>% C</u>	<u>90°</u>	<u>30°</u>
1	12.9	40.3	46.8	1.0	53	1272	9.3	3.6	93	20
2	21.2	34.1	44.7	1.0	53	1231	12.6	3.4	96	21
3	27.8	29.2	43.0	1.0	53	1180	15.1	3.2	102	21
4	17.1	32.9	50.0	1.0	53	1270	9.6	3.7	96	20
5	29.2	20.8	50.0	1.0	53	1186	13.6	3.7	97	21
6	39.2	10.8	50.0	1.0	53	1160	16.5	3.8	103	20
7	39.2	10.8	50.0	1.0	40	1192	17.3	3.6	103	20
8	17.1	19.6	45.0	1.0	53	1120	16.2	3.5	97	21

* Sample Coating 8 also contained 18.3 volume percent nitrogen.

TABLE 3 (Continued)

D-GUN PARAMETERS AND PROPERTIES OF COATINGS
MADE FROM POWDER A

10 Sample Coating	<u>Gaseous Fuel-Mixture</u> (Vol %)			<u>O₂ to C</u> <u>Atomic Ratio</u>	<u>Powder</u> <u>Feed Rate</u> (gpm)	<u>Hardness</u> <u>Vickers</u> (Kg/mm ²)	<u>Chemistry</u>		<u>Erosion</u> (μ/gm)	
	<u>C₂H₄</u> <u>3.8</u>	<u>C₂H₂</u> <u>2.2</u>	<u>O₂</u> <u>2</u>				<u>% Co</u>	<u>% C</u>	<u>90°</u>	<u>30°</u>
9	7.0	41.2	51.8	1	53	1240	9.5	3.8	112	21
15 10	12.3	34.6	53.1	1	53	1196	13.3	3.8	99	21
11	16.8	29.0	54.2	1	53	1140	16.6	3.7	106	20
12	16.8	29.0	54.2	1	40	1161	16.9	3.6	102	19
20										
	<u>C₂H₄</u> <u>4.10</u>	<u>C₂H₂</u> <u>2.2</u>	<u>O₂</u> <u>2</u>				<u>% Co</u>	<u>% C</u>	<u>90°</u>	<u>30°</u>
25 13	5.7	41.5	52.9	1	53	1263	9.5	3.8	106	19

EXAMPLE 3

The gaseous fuel-oxidant mixture of the compositions shown in Table 4 were each introduced into a detonation gun to form a detonatable mixture having an atomic ratio of oxygen to carbon as also shown in Table 4. The coating powder was sample B and the fuel-oxidant mixture is as also shown in Table 4. The gas flow rate was 0.38 m³/min (13.5 cubic feet per minute-cfm) with the feed rate being as shown in Table 4. As in Example 1, the hardness and erosion rate (μ/gm) were determined and these data are shown in Table 4. While sintered powders do not show a great change in cobalt content with gun temperature, higher hardness coatings with equivalent cobalt contents can be obtained with acetylene-hydrocarbon gas-oxygen mixtures than with acetylene-oxygen-nitrogen mixtures (compare sample coating 4 with sample coating 1).

TABLE 4

D-GUN PARAMETERS AND PROPERTIES OF COATINGS
MADE FROM POWDER B

5

Sample Coating	Gaseous Fuel-Mixture (Vol %)			O ₂ to C Atomic Ratio	Powder Feed Rate (gpm)	Hardness Vickers (Kg/mm ²)	Chemistry		Erosion (μ/gm)	
	N ₂	C ₂ H ₂	O ₂				% Co	% C	90°	30°
1	45	27.8	27.2	0.98	17	940	12.9	5.2		
2	45	27.8	27.2	0.98	25	920	13.1	5.1	76	9.5
	C ₃ H ₆	C ₂ H ₂	O ₂				% Co	% C	90°	30°
3	18.6	27.3	54.1	0.98	17	1070	13.3	5.1	82	12
4	18.6	27.3	54.1	0.98	25	1160	12.9	5.2	72	11
5	25.6	18.6	55.8	0.98	25	1045	13.5	5.2	68	9
6	29.8	12.8	57.4	1.0	25	890	12.7	4.5	71	8
7	37	3.7	59.3	1.0	25	935	13.6	5.2	86	9

EXAMPLE 4

The gaseous fuel-oxidant mixture of the compositions shown in Table 5 were each introduced into a detonation gun to form a detonatable mixture having an atomic ratio of oxygen to carbon as also shown in Table 5. The coating powder was sample C and the fuel-oxidant mixture is as also shown in Table 5. The gas flow rate was 0.38 m³/min (13.5 cubic feet per minute-cfm) with the feed rate being as shown in Table 5. As in Example 1, the Vickers hardness and erosion rate (μ/gm) were determined and these data are shown in Table 5. The Vickers hardness data show that using an acetylene-hydrocarbon gas-oxygen mixture in place of an acetylene-oxygen-nitrogen mixture can produce a coating having a higher hardness at the same cobalt content (compare sample coating 2 with sample coating 1).

TABLE 5

D-GUN PARAMETERS AND PROPERTIES OF COATINGS
MADE FROM POWDER C

Sample Coating	<u>Gaseous Fuel-Mixture</u> (Vol %)			<u>O₂ to C</u> <u>Atomic Ratio</u>	<u>Powder</u> <u>Feed Rate</u> (gpm)	<u>Hardness</u> <u>Vickers</u> (Kg/mm ²)	<u>Chemistry</u>		<u>Erosion</u> (μ/gm)	
	<u>N₂</u>	<u>C₂H₂</u>	<u>O₂</u>				<u>% Co</u>	<u>% C</u>	<u>90°</u>	<u>30°</u>
1	45	27.5	27.5	1.0	36.7	980	13.4	4.1	79	15
								</		

EXAMPLE 5

The gaseous fuel-oxidant mixture of the compositions shown in Table 6 were each introduced into a detonation gun to form a detonatable mixture having an atomic ratio of oxygen to carbon as also shown in Table 6. The coating powder was sample D and the fuel-oxidant mixture is as also shown in Table 6. The gas flow rate was 0.38 m³/min (13.5 cubic feet per minute-cfm) except for sample coatings 17, 18 and 19 which were 11.0 cfm, and the feed rate was 46.7 grams per minute (gpm). As in Example 1, the Vickers hardness and erosion rate (μ/gm) were determined and these data are shown in Table 6. The Vickers hardness data show that using an acetylene-hydrocarbon gas-oxygen mixture in place of an acetylene-oxygen-nitrogen mixture can produce either a coating having a higher hardness at the same cobalt content (compare sample coating 5 with sample coating 17) or a coating having a higher cobalt content for the same hardness (compare sample coating 5 with sample coating 18).

TABLE 6

**D-GUN PARAMETERS AND PROPERTIES OF COATINGS
MADE FROM POWDER D**

10	Sample Coating	Gaseous fuel-Mixture (Vol %)				O ₂ to C Atomic Ratio	Hardness ⁽¹⁾		Chemistry		Erosion (μ/gm)	
		C ₃ H ₆	C ₂ H ₂	O ₂	N ₂		Vickers (Kg/mm ²)		% Co	% C	90°	30°
	1	37.0	3.7	59.3	-	1.0			17.6	3.2		
	2	29.8	12.8	57.4	-	1.0	1235		15.2	2.4	109	24
15	3	29.8	7.5	62.7	-	1.2	1200		13.2	0.9	86	25
	4	29.8	3.2	67.0	-	1.4	1180		11.6	0.6	77	24
	5	25.6	18.0	56.4	-	1.0	1250		15.5	3.2	100	25
20	6	25.6	16.6	57.8	-	1.05	1230		14.3	2.1	88	24
	7	25.6	15.3	59.1	-	1.1	1185		13.7	1.6	81	24
	8	25.6	12.9	61.5	-	1.2	1110		12.6	1.0	75	24
25	9	25.6	10.6	63.8	-	1.3	1215		14.4	1.3	81	24
	10	25.6	8.6	65.8	-	1.4	1020		10.5	0.7	71	23
	11	25.6	6.7	67.7	-	1.5	1095		9.9	0.5	75	25
30	12	25.6	5.7	68.7	-	1.6	1180		9.8	0.5	84	25
	13	25.6	3.4	71.0	-	1.7	1115		9.5	0.5	93	25
	14	18.6	24.1	57.3	-	1.1	1260		10.0	1.3	69	22
	15	18.6	21.8	59.6	-	1.2	1215		9.3	0.9	65	22
35	16	18.6	17.6	63.8	-	1.4	920		7.0	0.5	101	25
	17	-	30.3	29.7	40	0.98	1100*		15.6	3.4	120	30
	18	-	35.3	34.7	30	0.98	1250*		12.2	3.5	120	26
40	19	-	42.8	42.2	10	0.98	1375*		6.9	3.6	120	23

Note (1) Measured as Rockwell superficial hardness and converted to Vickers hardness unless otherwise indicated with an asterisk (*).

Claims

1. A process of flame plating with a detonation gun which comprises using a gaseous fuel-oxidant mixture comprising (a) an oxidant and (b) a fuel mixture comprising a mixture of acetylene and a second combustible gas selected from propylene, methane, ethylene, methyl acetylene, propane, pentane, a butadiene, a butylene, a butane, ethylene oxide, ethane, cyclopropane, propadiene, cyclobutane and mixtures thereof.
2. A process according to claim 1, wherein the oxidant is selected from oxygen, nitrous oxide and mixtures thereof.



TABLE 6

**D-GUN PARAMETERS AND PROPERTIES OF COATINGS
MADE FROM POWDER D**

5

		Gaseous Fuel-Mixture (Vol %)				O_2 to C	Hardness ⁽¹⁾		Chemistry		Erosion (μ /gm)	
Sample Coating		C_3H_6	C_2H_2	O_2	N_2	Atomic Ratio	Vickers (Kg/mm ²)		% Ca	% C	90°	30°
10	1	37.0	3.7	59.3	-	1.0			17.6	3.2		
	2	29.8	12.8	57.4	-	1.0	1235		15.2	2.4	109	24
15	3	29.8	7.5	62.7	-	1.2	1200		13.2	0.9	86	25
	4	29.8	3.2	67.0	-	1.4	1180		11.6	0.6	77	24
	5	25.6	18.0	56.4	-	1.0	1250		15.5	3.2	100	25
20	6	25.6	16.6	57.8	-	1.05	1230		14.3	2.1	88	24
	7	25.6	15.3	59.1	-	1.1	1185		13.7	1.6	81	24
	8	25.6	12.9	61.5	-	1.2	1110		12.6	1.0	75	24
25	9	25.6	10.6	63.8	-	1.3	1215		14.4	1.3	81	24
	10	25.6	8.6	65.8	-	1.4	1020		10.5	0.7	71	23
	11	25.6	6.7	67.7	-	1.5	1095		9.9	0.5	75	25
	12	25.6	5.7	68.7	-	1.6	1180		9.8	0.5	84	25
30	13	25.6	3.4	71.0	-	1.7	1115		9.5	0.5	93	25
	14	18.6	24.1	57.3	-	1.1	1260		10.0	1.3	69	22
	15	18.6	21.8	59.6	-	1.2	1215		9.3	0.9	65	22
35	16	18.6	17.6	63.8	-	1.4	920		7.0	0.5	101	25
	17	-	30.3	29.7	40	0.98	1100*		15.6	3.4	120	30
	18	-	35.3	34.7	30	0.98	1250*		12.2	3.5	120	26
40	19	-	42.8	42.2	10	0.98	1375*		6.9	3.6	120	23

Note (1) Measured as Rockwell superficial hardness and converted to Vickers hardness unless otherwise indicated with an asterisk (*).

Claims

1. A process of flame plating with a detonation gun which comprises using a gaseous fuel-oxidant mixture comprising (a) an oxidant and (b) a fuel mixture comprising a mixture of acetylene and a second combustible gas selected from propylene, methane, ethylene, methyl acetylene, propane, pentane, a butadiene, a butylene, a butane, ethylene oxide, ethane, cyclopropane, propadiene, cyclobutane and mixtures thereof.
2. A process according to claim 1, wherein the oxidant is selected from oxygen, nitrous oxide and mixtures thereof.



3. A process according to claim 1 or 2, wherein the mixture contains from 35 to 80 percent by volume of the oxidant, from 2 to 50 percent by volume of acetylene, and from 2 to 60 percent by volume of the second combustible gas.
- 5 4. A process according to claim 3, wherein the mixture contains from 45 to 70 percent by volume oxidant, from 7 to 45 percent by volume acetylene and from 10 to 45 percent by volume of the second combustible gas.
- 10 5. A process according to claim 4, wherein the mixture contains from 50 to 65 percent by volume oxidant, from 12 to 26 percent by volume acetylene and from 18 to 30 percent by volume of the second combustible gas.
- 15 6. A process according to any of claims 1 to 5, wherein the mixture has an atomic ratio of oxygen to carbon of from 0.9 to about 2.0.
7. A process according to claim 6, wherein the second combustible gas is selected from propylene, propane and butylene and the atomic ratio of oxygen to carbon is from 0.95 to 1.6.
- 20 8. A process according to any of claims 1 to 6, wherein the second combustible gas consists substantially of propylene.
9. A process according to any of claims 1 to 8, wherein the mixture contains an inert diluting gas.
- 25 10. A process according to claim 9, wherein the inert diluting gas is selected from argon, neon, krypton, xenon, helium and nitrogen.
11. A process according to claim 10, wherein the inert diluting gas is nitrogen.
- 30 12. A process according to any of claims 1 to 11, wherein the gaseous fuel-oxidant mixture is introduced into the gun to form a detonatable mixture, a powdered coating material is introduced into the detonatable mixture within the gun, and the fuel-oxidant mixture is detonated to impinge the coating material onto an article to be coated.
- 35 13. A process according to claim 12, wherein the detonation gun has a mixing and ignition chamber and a barrel portion, wherein the gaseous fuel-oxidant mixture is introduced into the gun through the mixing and ignition chamber, a comminuted coating material is introduced into the barrel portion, and the gaseous fuel-oxidant mixture is detonated within the gun to impinge the coating material onto an article to be coated.

40 Patentansprüche

1. Verfahren zum Flammplattieren mit einer Detonationskanone unter Verwendung eines gasförmigen Brennstoff/Oxidationsmittel-Gemisches, das (a) ein Oxidationsmittel und (b) ein Brennstoffgemisch aufweist, das seinerseits ein Gemisch aus Acetylen und einem zweiten brennbaren Gas aufweist, das aus Propylen, Methan, Ethylen, Methylacetylen, Propan, Pentan, einem Butadien, einem Butylen, einem Butan, Ethylenoxid, Ethan, Cyclopropan, Propadien, Cyclobutan und Gemischen derselben ausgewählt ist.
- 45 2. Verfahren nach Anspruch 1, wobei das Oxidationsmittel aus Sauerstoff, die Stickstoffoxid und Gemischen derselben ausgewählt ist.
3. Verfahren nach Anspruch 1 oder 2, wobei das Gemisch 35 bis 80 Volumenprozent Oxidationsmittel, 2 bis 50 Volumenprozent Acetylen und 2 bis 60 Volumenprozent des zweiten brennbaren Gases enthält.
- 55 4. Verfahren nach Anspruch 3, wobei das Gemisch 45 bis 70 Volumenprozent Oxidationsmittel, 7 bis 45 Volumenprozent Acetylen und 10 bis 45 Volumenprozent des zweiten brennbaren Gases enthält.



5. Verfahren nach Anspruch 4, wobei das Gemisch 50 bis 65 Volumenprozent Oxidationsmittel, 12 bis 26 Volumenprozent Acetylen und 18 bis 30 Volumenprozent des zweiten brennbaren Gases enthält.
6. Verfahren nach einem der Ansprüche 1 bis 5, wobei das Gemisch ein Atomverhältnis von Sauerstoff zu Kohlenstoff von 0,9 bis etwa 2,0 hat.
7. Verfahren nach Anspruch 6, wobei das zweite brennbare Gas aus Propylen, Propan und Butylen ausgewählt ist und das Atomverhältnis von Sauerstoff zu Kohlenstoff 0,95 bis 1,6 beträgt.
8. Verfahren nach einem der Ansprüche 1 bis 6, wobei das zweite brennbare Gas im wesentlichen aus Propylen besteht.
9. Verfahren nach einem der Ansprüche 1 bis 8, wobei das Gemisch ein inertes Verdünnungsgas enthält.
10. Verfahren nach Anspruch 9, wobei das inerte Verdünnungsgas aus Argon, Neon, Krypton, Xenon, Helium und Stickstoff ausgewählt ist.
11. Verfahren nach Anspruch 10, wobei das inerte Verdünnungsgas Stickstoff ist.
12. Verfahren nach einem der Ansprüche 1 bis 11, wobei das gasförmige Brennstoff/Oxidationsmittel-Gemisch in die Kanone zur Bildung eines detonierbaren Gemisches eingeleitet wird, ein pulverförmiger Auftragwerkstoff in das detonierbare Gemisch innerhalb der Kanone eingebracht wird, und das Brennstoff/Oxidationsmittel-Gemisch zur Detonation gebracht wird, um den Auftragwerkstoff auf einen zu beschichtenden Gegenstand auftreffen zu lassen.
13. Verfahren nach Anspruch 12, wobei die Detonationskanone eine Misch- und Zündkammer und einen Laufteil aufweist, wobei das gasförmige Brennstoff/Oxidationsmittel-Gemisch in die Kanone über die Misch- und Zündkammer eingeleitet wird, ein zerkleinerter Auftragwerkstoff in den Laufteil eingeleitet wird, und das gasförmige Brennstoff/Oxidationsmittel-Gemisch innerhalb der Kanone zur Detonation gebracht wird, um den Auftragwerkstoff auf einen zu beschichtenden Gegenstand auftreffen zu lassen.

Revendications

1. Procédé de placage à la flamme à l'aide d'un canon à détonation, qui consiste à utiliser un mélange gazeux combustible-comburant comprenant (a) un comburant et (b) un mélange combustible comprenant un mélange d'acétylène et d'un second gaz combustible choisi parmi du propylène, du méthane, de l'éthylène, du méthylacétylène, du propane, du pentane, un butadiène, un butylène, un butane, de l'oxyde d'éthylène, de l'éthane, du cyclopropane, du propadiène, du cyclobutane et des mélanges de ceux-ci.
2. Procédé selon la revendication 1, dans lequel le comburant est choisi entre l'oxygène, l'oxyde azoteux et des mélanges de ceux-ci.
3. Procédé selon la revendication 1 ou 2, dans lequel le mélange contient 35 à 80 % en volume du comburant, 2 à 50 % en volume d'acétylène et 2 à 60 % en volume du second gaz combustible.
4. Procédé selon la revendication 3, dans lequel le mélange contient 45 à 70 % en volume de comburant, 7 à 45 % en volume d'acétylène et 10 à 45 % en volume du second gaz combustible.
5. Procédé selon la revendication 4, dans lequel le mélange contient 50 à 65 % en volume de comburant, 12 à 26 % en volume d'acétylène et 18 à 30 % en volume du second gaz combustible.
6. Procédé selon l'une quelconque des revendications 1 à 5, dans lequel le mélange a un rapport atomique de l'oxygène au carbone de 0,9 à environ 2,0.
7. Procédé selon la revendication 6, dans lequel le second gaz combustible est choisi entre du propylène, du propane et du butylène et le rapport atomique de l'oxygène au carbone est de 0,95 à 1,6.



8. Procédé selon l'une quelconque des revendications 1 à 6, dans lequel le second gaz combustible est constitué sensiblement de propylène.
- 5 9. Procédé selon l'une quelconque des revendications 1 à 8, dans lequel le mélange contient un gaz inerte de dilution.
- 10 10. Procédé selon la revendication 9, dans lequel le gaz inerte de dilution est choisi entre l'argon, le néon, le krypton, le xénon, l'hélium et l'azote.
- 10 11. Procédé selon la revendication 10, dans lequel le gaz inerte de dilution est de l'azote.
- 15 12. Procédé selon l'une quelconque des revendications 1 à 11, dans lequel on introduit le mélange gazeux combustible-comburant dans le canon pour former un mélange détonant, on introduit une matière de revêtement en poudre dans le mélange détonant à l'intérieur du canon, et on fait détoner le mélange combustible-comburant pour projeter la matière de revêtement sur un article à revêtir.
- 20 13. Procédé selon la revendication 12, dans lequel le canon à détonation comporte une chambre de mélange et de mise à feu et une partie de corps, dans lequel on introduit le mélange gazeux combustible-comburant dans le canon par l'intermédiaire de la chambre de mélange et de mise à feu, on introduit une matière pulvérisée de revêtement dans la partie de corps, et on fait détoner le mélange gazeux combustible-comburant à l'intérieur du canon pour projeter la matière de revêtement sur un article à revêtir.