

DETERMINATION OF HEAT SOAK CONDITIONS

FIELD OF INVENTION

5 This invention relates to fuel injection systems for internal combustion engines and methods of operation of such systems.

BACKGROUND OF THE INVENTION

10 Liquid fuels which can be injected using fuel injection are petrol, LNG and LPG. This present invention will be discussed mainly in relation to LPG but can be also applicable to petrol and low boiling point or high vapour pressure fuels. The invention is applicable to internal combustion engines operating with a single fuel or to such engines operating with dual fuels.

15 Fuel injection systems for internal combustion engines can be adapted to supply liquid fuels to the inlet manifold for each cylinder of an internal combustion engine. This system is known as multi-point liquid fuel injection. By suitable control of the operation of the injectors accurate amounts of liquid fuel can be supplied to each cylinder depending upon engine conditions and demand characteristics.

There is a problem, however, in that for liquid fuel injection to be accurate the fuel in the injectors adjacent the injection point must be liquid at all times.

20 The environment around each cylinder, however, can at times during engine operation be very hot and such a temperature in this region is not conducive to injection of a liquid fuel which has a low boiling point.

25 LPG (propane and butane) is in equilibrium pressure state with both gas and liquid being present inside a fuel tank of a vehicle because of its properties, that is its boiling point is usually lower than the ambient temperature (when the temperature is above zero). Considering these properties of LPG, the liquid will vaporise when the surrounding temperature is higher than the liquid temperature.

In a practical situation, such as liquid LPG flowing to a fuel rail and injectors of

a fuel injection system, in under - bonnet typical temperatures, it will remain in a liquid state where there is a sufficient recirculation rate only. While the vehicle is running care is taken to ensure that there is sufficient circulation flow rate, minimum number of restrictions and some pressure elevation above that of the equilibrium pressure to maintain the liquid state. When the vehicle has been running and is stopped and the engine is not running, however, the LPG liquid in the fuel rails and injectors immediately starts to vaporise due to the high under - bonnet temperatures relative to the liquid temperature. This process will tend to raise the pressure in the fuel rail but the general design of fuel rails is to prevent build up of an overpressure by a relief valve. A mixture of liquid and vapour therefore flows into the LPG tank via a return line. It will be seen therefore that from the instant that recirculation stops the liquid in the fuel rail is replaced by dry gas and the temperature in the fuel rail injectors and valves start to rise steadily because of the heat transfer from the various components and the under - bonnet conditions. The rise in temperature and heating is a function of time and the surrounding temperature. The surrounding temperature is also a function of previous engine loads, engine speeds and running time.

These conditions may be referred to as heat soak conditions.

Starting the fuel pump after a heat soak condition will draw liquid LPG from the bottom of the fuel tank and the liquid is transferred into the fuel rail, injectors and valves. As the liquid fills the fuel rail it starts to vaporise until the surface temperature drops to that of the liquid temperature with a gradient distribution due to flow. The time taken for the fuel rail assembly to equalise in temperature to that of the liquid is dependant on the temperature of the LPG in the tank, fuel rail and injector design, surface to volume ratio of the metal parts and the absolute temperature of the fuel rail assembly.

It is an object of this invention, therefore, for efficient operation of a fuel injected engine operating with low boiling point fuels, to be able to determine by an easy method when such heat soak conditions occur so that suitable action may be taken to overcome the heat soak conditions before starting the engine or upon starting the engine.

It is a further object of this invention to provide an apparatus suitable for determination of such heat soak conditions.

SUMMARY OF THE INVENTION

In one form therefore although this may not necessarily be the only or broadest form the invention is said to reside in a method of determination of heat soak conditions in an internal combustion engine using fuel injection where the or one of the fuels used in the engine is susceptible to vaporisation in fuel rails due to high engine temperatures, the method including the steps of measuring a first temperature in a tank for the fuel, measuring a second temperature at the fuel rail and ascertaining the difference between the first and second temperature, wherein a significant difference indicates heat soak conditions.

In an alternative form the invention is said to reside in an apparatus to enable the determination of heat soak conditions in an internal combustion engine operated by fuel injection, comprising means to determine a first temperature in a fuel rail for the fuel injector, means to determine a second temperature in a fuel tank for the fuel and means to subtract the first temperature from the second temperature, wherein heat soak conditions are present if the first temperature minus the second temperature is greater than a selected value.

The fuel as discussed above may be petrol, LNG or LPG in a single fuel vehicle or may be petrol and LPG or LNG with a dual fuel vehicle.

A significant difference in the temperature between the fuel tank and the fuel rail may be in the range of 2°C to 5°C or greater, depending upon the actual construction of the fuel rail and fuel tank, the positions of the sensors in or on the fuel rail and fuel tank, the type of sensor used, the heat capacity of the rail and the type of fuel being used.

The type of sensor may be a liquid probe temperature sensor or a surface contact temperature detector.

It will be seen that by this invention there is provided a cost effective method and apparatus for detecting the under bonnet heat soak conditions by placing a temperature sensor on the fuel rail and a temperature sensor in or on the fuel tank.

The location of the temperature sensor on the rail and tank is relative, that is,

the calibration will vary depending upon the location of the sensor. The sensor can either be a liquid probe or a surface contact external detector insulated from the surroundings. A relatively fast response sensor is preferred to ensure prompt indication of temperature. Such a sensor should have a response of about one second.

Preferably the temperature sensor on the fuel rail is positioned adjacent to the last injector on the fuel rail where the fuel line returns to the fuel tank. Once fuel is circulating again it will take longest to get to that point and cool that point down sufficiently for the liquid LPG to remain useable as a fuel at the operating pressure.

A method by which the heat soak determination may be done is as follows. On turning on the ignition key an electronic control unit for the fuel injection reads the two temperature inputs from the fuel rail and the fuel tank and calculates a temperature difference (ΔT). The temperature difference is then entered into a look - up table and an engine state is determined. If the temperature difference is greater than a predetermined value, typically 2° to 5° C then it is determined that there are heat soak conditions present. Depending on the value of the temperature difference a time of running on some alternative fuel supply system will be obtained from the look - up table.

During the period that heat soak conditions are present the engine can only run by other means. Such other means may be by use of an alternative fuel such as petrol or by injection of fuel into an air intake line at a position remote from the engine where the temperature is not so high.

Alternatively, starting of the engine may be prevented and only pumping of fuel may occur until such time as the heat soak condition has been alleviated.

During the period that the engine is running by such other means the fuel pump for instance the LPG pump may be pumping liquid in the fuel rail assembly and maintaining recirculation until the fuel rail is cooled and ΔT becomes equal to or less than the predetermined value. The actual time taken to cool the fuel rail assembly depends upon various factors such as the actual temperature and the heat capacity of the fuel rail and typically it may vary from 2 to 15 seconds or longer.

In an alternative system there may be used fast acting temperature sensors on both the fuel tank and the fuel rail and rather than calculating a time to operate on the alternative fuel supply system there may be continuous checking of the temperature difference until the difference is less than a selected value, for instance typically 2° to 5° C at which time the alternative fuel supply system is switched off and the normal fuel supply system is used.

One advantage of a continuous detection system is that unwanted emissions may be avoided by going back to the more efficient fuel as soon as possible rather than after a fixed time which may not be optimum for all conditions and temperatures.

This generally describes the invention but to assist with understanding of the invention reference will now be made to a preferred embodiment of the invention as shown in the accompanying drawings.

In the drawings

FIG 1 shows a schematic view of an engine and single fuel supply system embodying the present invention, and

FIG 2 shows a schematic view of an engine and dual fuel supply system embodying the present invention

In Fig 1 an engine 1 shown schematically has four cylinders 2. Each cylinder is fed inlet air through inlet pipe 3 from inlet manifold 4. An injector 6 injects the necessary fuel as determined by an injector controller 7 into the inlet pipe 3. Fuel is supplied via a fuel rail 8 from a fuel line 9 extending to a fuel tank 10. A fuel return rail 12 and line 11 allows excess fuel to be returned to the fuel tank 10.

When there is an attempt to start the engine incorporating the present invention the controller 7 measures the temperature at the fuel tank 10 by means of a temperature probe 15 and on the fuel rail 8 by means of temperature probe 16. The temperature in the tank is subtracted from the temperature in the rail and if the temperature difference is greater than perhaps 2 to 5°C then the system assumes that there is at least some heat soak conditions present in the fuel rail and injectors and the controller 7

activates a further injector 20 to inject fuel into the inlet manifold 4 at a point remote from the engine.

In FIG 2 a substantively similar construction of engine is provided with the same items having the same reference numerals.

- 5 This system however is a dual fuel system where a first fuel tank 30 has a low boiling point fuel and a second fuel tank 35 has a higher boiling point fuel. Fuel from the tank 30 is supplied to the inlet rail 8 by inlet fuel line 31 and excess fuel is returned to the tank 30 by means of outlet fuel rail 12 and return fuel line 32. Fuel from the tank 35 is supplied to the inlet rail 8 by inlet fuel line
10 33 and excess fuel is returned to the tank 35 by means of outlet fuel rail 12 and return fuel line 34.

- If upon engine starting the temperature difference between the temperature calculated in the fuel tank 30 by means of probe 36 and the temperature calculated in the fuel rail by means of probe 37 then the engine is operated on
15 the higher boiling point fuel from the tank 35 and fuel is pumped to the auxiliary injector 40 by means of fuel line 41 which branches off fuel inlet line 33 from the tank 35. The auxiliary injector is mounted on the inlet manifold 4 at a position remote from the engine.

- We have seen that by this invention the presence of heat soak conditions can
20 be determined when it is intended to start an engine by comparison of temperatures in two critical points.

It will be realised of course that if the temperature difference is less than a selected value then the engine could be operated using the main injectors 6 with either the low boiling point fuel or the high boiling point fuel.

- 25 This present invention therefore provides a convenient method and apparatus by which heat soak conditions in an internal combustion engine may be detected.



1. A method of determining the presence of heat soak conditions in an internal combustion engine using fuel injection where the or one of the fuels used in the engine is susceptible to vaporisation in a fuel rail due to high engine temperatures, the method including the steps of measuring a first temperature in a tank for the fuel, measuring a second temperature at the fuel rail, ascertaining the difference between the first and second temperature, wherein a significant difference indicates heat soak conditions.
2. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the measurement is done once and a look - up is used to determine a time for which heat soak conditions are deemed to be present.
3. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the measurement is done continuously and heat soak conditions are deemed to be present while the temperature difference is greater than a selected value.
4. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the temperature sensors are liquid probe temperature sensors.
5. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the temperature sensors are surface contact temperature sensors.
6. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the engine is a single low boiling point fuel engine and further including the step of switching to an auxiliary injector upon starting when heat soak conditions are detected.
7. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the engine is a dual fuel engine and further including the step of switching from a low boiling point fuel to a high boiling point fuel upon starting when heat soak conditions are detected.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



8. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 7 wherein the step of switching from a low boiling point fuel to a high boiling point fuel upon starting when heat soak conditions are detected also includes the step switching to an auxiliary injector.
9. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine operated by fuel injection, comprising a first temperature sensor to determine a first temperature of a fuel rail for the fuel injector, a second temperature sensor to determine a second temperature in a fuel tank for the fuel and calculation means to subtract the first temperature from the second temperature, wherein heat soak conditions are deemed to be present if the first temperature minus the second temperature is greater than a selected value.
10. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 9 wherein the calculation means includes a look - up table.
11. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 9 wherein the calculation means includes means to continuously compare the temperatures and to determine if heat soak conditions are present.
12. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 9 wherein the temperature sensors are liquid probe temperature sensors.
13. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 9 wherein the temperature sensors are surface contact temperature sensors.
14. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 9 further including an auxiliary injector for the fuel for use when heat soak conditions are detected.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



15. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 9 wherein the engine is a single fuel engine.

5 16. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 9 wherein the engine is a dual fuel engine.

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



1/1




FIG 1




FIG 2



1. A method of determining the presence of heat soak conditions in a dual fuel internal combustion engine using fuel injection where the low boiling point fuel used in the engine is susceptible to vaporisation in a fuel rail due to high engine temperatures, the method including the steps of measuring a first temperature in a tank for the low boiling point fuel, measuring a second temperature at the fuel rail, ascertaining the difference between the first and second temperature, wherein a significant difference indicates heat soak conditions, and switching from the low boiling point fuel to a higher boiling point fuel upon starting the engine when such heat soak conditions are detected.
2. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the measurement is done once and a look - up is used to determine a time for which heat soak conditions are deemed to be present.
3. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the measurement is done continuously and heat soak conditions are deemed to be present while the temperature difference is greater than a selected value.
4. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the temperature sensors are liquid probe temperature sensors.
5. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the temperature sensors are surface contact temperature sensors.
6. A method of determining the presence of heat soak conditions in an internal combustion engine as in Claim 1 wherein the step of switching from the low boiling point fuel to the higher boiling point fuel upon starting when heat soak conditions are detected also includes the step switching to an auxiliary injector.

27/3




7. An apparatus to enable the determination of the presence of heat soak conditions in a dual fuel internal combustion engine operated by fuel injection of either a low boiling point fuel or a high boiling point fuel,
- 5 comprising a first temperature sensor to determine a first temperature of a fuel rail for the fuel injector, a second temperature sensor to determine a second temperature in a fuel tank for the low boiling point fuel and calculation means to subtract the first temperature from the second temperature, wherein heat soak conditions are deemed to be present if the first temperature minus the
- 10 second temperature is greater than a selected value and means to switch from the low boiling point fuel to the high boiling point fuel when the heat soak conditions are deemed to be present on starting the engine.
8. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 7 wherein the
- 15 calculation means includes a look - up table.
9. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 7 wherein the calculation means includes means to continuously compare the temperatures and to determine if heat soak conditions are deemed to be present.
- 20 10. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 7 wherein the temperature sensors are liquid probe temperature sensors.
11. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 7 wherein the
- 25 temperature sensors are surface contact temperature sensors.
12. An apparatus to enable the determination of the presence of heat soak conditions in an internal combustion engine as in Claim 9 further including an auxiliary injector for the high boiling point fuel for use when heat
- 30 soak conditions are detected upon starting.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F02D 19/02, 19/06, F02M 21/02	A1	(11) International Publication Number: ✓ WO 95/35442 (43) International Publication Date: 28 December 1995 (28.12.95)
(21) International Application Number: ✓ PCT/AU95/00368 (22) International Filing Date: ✓ 21 June 1995 (21.06.95) (30) Priority Data: PM 6323 ✓ 21 June 1994 (21.06.94) ✓ AU ✓ (71) Applicant (for all designated States except US): BIOCOP PTY. LTD. [AU/AU]; 2-8 Gray Street, Kilkenny, S.A. 5009 (AU). <i>see PCT/16/306</i> (72) Inventor; and (75) Inventor/Applicant (for US only): SMITH, Rodney, Sinclair [AU/AU]; "High Field", Glen Bold Road, Echunga, S.A. 5153 (AU). ✓ (74) Agent: COLLISON & CO.; 117 King William Street, Adelaide, S.A. 5000 (AU).		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG). Published With international search report. 9612099-3 1PSS copy.

(54) Title: DETERMINATION OF HEAT SOAK CONDITIONS **✓**

(57) Abstract

A method and an arrangement for determining the presence of heat soak conditions in an internal combustion engine (1) of a type using fuel injection. Particularly useful when the or one of the fuels used in the engine (1) is susceptible to vaporisation in a fuel rail (8) due to high engine temperatures. The method includes the steps of measuring a first temperature in a tank (10) for the fuel, measuring a second temperature at the fuel rail (8), ascertaining the difference between the first and second temperature, wherein a significant difference indicates heat soak conditions. If heat soak conditions are detected then an auxiliary injector (20) may be operated or in dual fuel engines a higher boiling point fuel may be used.