

APPARATUS FOR PRODUCING ACIDIC AQUEOUS SOLUTION AND
METHOD FOR PRODUCING ACIDIC AQUEOUS SOLUTION

[Technical Field]

[0001]

5 The present invention relates to an apparatus for producing an acidic aqueous solution and a method for producing an acidic aqueous solution.

 Priority is claimed on Japanese Patent Application No. 2019-162099, filed September 5, 2019, the content of which is incorporated herein by reference.

[Background Art]

10 [0002]

 In a wastewater treatment process, it is essential to add an acidic aqueous solution in order to treat wastewater. For example, in order for the wastewater treatment process to function normally, an acidic aqueous solution is added to adjust the pH. In addition, depending on the apparatus, it is necessary to periodically chemically and physically wash the apparatus, and it is necessary to use an acidic aqueous solution at
15 that time. For example, in a chelation treatment, an ion exchange resin and the like, it is necessary to periodically perform washing with an acidic aqueous solution to restore performance.

[0003]

20 On the other hand, since the acidic aqueous solution used in the wastewater treatment process needs to be transported from the outside and stored, it causes a large economic burden.

[0004]

 On the other hand, for example, Patent Literature 1 discloses an organic
25 wastewater treatment apparatus including a first softening treatment apparatus that

performs a softening treatment on organic wastewater containing salts and organic substances to reduce a calcium concentration, a suspended solid (SS) removal treatment apparatus that performed one or more treatments selected from the group consisting of a biological treatment, a coagulation precipitation treatment, an activated carbon

5 adsorption treatment, a sand filtration treatment, a microfiltration membrane treatment or a combination of two or more thereof, a salt removal apparatus including any apparatus among an electrodialysis treatment apparatus that performs separation into electrodialysis concentrated water and electrodialysis treated water by an electrodialysis treatment, a reverse osmosis membrane treatment apparatus that performs separation into reverse
10 osmosis concentrated water and reverse osmosis membrane treated water by a reverse osmosis membrane treatment, an NF membrane treatment apparatus that performs separation into NF membrane concentrated water and NF membrane treated water by a nanofiltration (NF) membrane treatment or two or more of these apparatuses, a second softening treatment apparatus that performs a softening treatment on the electrodialysis
15 concentrated water, reverse osmosis concentrated water or NF membrane concentrated water to reduce a calcium concentration, and an electrolysis treatment apparatus that electrolyzes second softening treated water obtained in the second softening treatment apparatus to produce a sodium hypochlorite solution.

[0005]

20 In addition, Patent Literature 2 discloses a method for treating wastewater containing a neutral salt of monovalent ions, including supplying wastewater to be treated to a diluting solution chamber of a pre-electrodialysis tank, supplying a concentrate containing a salt produced by neutralizing ions that have passed through an ion-exchange membrane in the pre-electrodialysis tank to an electrolytic dialysis tank
25 composed of three chambers: a positive electrode chamber, a central chamber, and a

negative electrode chamber, as units, which have a cation-exchange membrane and an anion-exchange membrane as diaphragms, and performing decomposition into an acid and a base that constitute a salt and performing collection, and a treatment apparatus to which the treatment method is applied.

5 [Citation List]

[Patent Literature]

[0006]

[Patent Literature 1]

Japanese Unexamined Patent Application, First Publication No. 2014-14738

10 [Patent Literature 2]

Japanese Unexamined Patent Application, First Publication No. H08-001168

[Summary of Invention]

[Technical Problem]

[0007]

15 Incidentally, in a wastewater treatment, if the acidic aqueous solution used in the wastewater treatment process can be produced and used on-site, and it is not necessary to transport the acidic aqueous solution from the outside and store it, it is thought that it would be possible to significantly reduce the economic burden.

[0008]

20 Some aspects of the present invention have been made in view of the above circumstances, and embodiments of the present invention provide an apparatus for producing an acidic aqueous solution and a method for producing an acidic aqueous solution through which it is possible to produce and use an acidic aqueous solution used in a wastewater treatment process on-site, and it is possible to significantly reduce the
25 economic burden.

[Solution to Problem]

[0009]

To solve the above-described problem, some aspects of the present invention use the following structure.

5 (1) That is, a first aspect of the present invention is an apparatus for producing an acidic aqueous solution, including: an electrodialyzer that has a monovalent ion perm-selective ion-exchange membrane and separates wastewater containing chloride ions and alkali metal ions into electrodialysis concentrated water and electrodialysis diluted water by an electrodialysis treatment; an electrolyzer that electrolyzes the electrodialysis
10 concentrated water to produce an acidic aqueous solution; and a first circulator that circulates at least some of the acidic aqueous solution to the wastewater supplied to the electrodialyzer.

[0010]

 (2) In the apparatus for producing an acidic aqueous solution according to the first
15 aspect of the present invention, the apparatus may further include a second circulator that circulates at least some of the acidic aqueous solution to the electrolyzer.

[0010a]

 Disclosed herein is an apparatus for producing an acidic aqueous solution, the apparatus comprising: an electrodialyzer that has a monovalent ion perm-selective ion-
20 exchange membrane and separates wastewater containing chloride ions and alkali metal ions into electrodialysis concentrated water and electrodialysis diluted water by an electrodialysis treatment; an electrolyzer that electrolyzes the electrodialysis concentrated water to produce an acidic aqueous solution; a first circulator that circulates at least some of the acidic aqueous solution to the wastewater supplied to the electrodialyzer; and a
25 second circulator that circulates at least some of the acidic aqueous solution to the

electrolyzer, wherein a cation-exchange membrane of the monovalent ion perm-selective ion-exchange membrane is a m-phenolsulfonic acid-phenolic resin, or a resin obtained by subjecting a styrene-divinylbenzene copolymer to a sulfonation reaction, a cationic polymer electrolyte containing a polyethyleneimine is formed on a surface of the cation-exchange membrane, and an anion-exchange membrane of the monovalent ion perm-selective ion-exchange membrane is an m-phenylenediamine-phenolic condensed resin, or a resin obtained by subjecting a styrene-divinylbenzene copolymer to an amination reaction.

[0011]

10 (3) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, in the electrolyzer, an anode may be a hydrogen gas diffusion electrode.

[0012]

15 (4) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the apparatus may further include a sodium hypochlorite producing device that electrolyzes a part of the electrodialysis concentrated water to produce a sodium hypochlorite aqueous solution.

[0013]

20 (5) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the apparatus may further include a hydrogen peroxide producing device that electrolyzes a part of the electrodialysis concentrated water to produce hydrogen peroxide.

[0014]

25 (6) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the electrodialyzer may perform the electrodialysis

treatment on the wastewater in which the concentration of the chloride ions is 0.01 mg/L or more.

[0015]

(7) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the electrodialyzer may perform the electrodialysis treatment on the wastewater in which the concentration of the alkali metal ions is 0.01 mg/L or more.

[0016]

(8) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the anode may include a conductive metal substrate and a catalyst layer.

[0017]

(9) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the thickness of the conductive metal substrate may be 0.05 to 5 mm.

[0018]

(10) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the thickness of the catalyst layer may be 0.1 to 100 μm .

[0019]

(11) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the porosity of the anode may be 10 to 95%.

[0020]

(12) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, the anode further may include an underlayer made of

a valve metal base alloy containing tantalum and titanium components between the conductive metal substrate and the catalyst layer.

[0021]

(13) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, a discharge pipe for the sodium hypochlorite aqueous solution produced by the sodium hypochlorite producing device may be connected to a discharge pipe for the wastewater.

[0022]

(14) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, in the electrolyzer, a cathode may be an oxygen gas diffusion electrode.

[0023]

(15) In the apparatus for producing an acidic aqueous solution according to the first aspect of the present invention, a discharge pipe for the hydrogen peroxide produced by the hydrogen peroxide producing device may be connected to a discharge pipe for the wastewater.

[0024]

(16) A second aspect of the present invention is a method for producing an acidic aqueous solution, including: an electrodialysis process in which wastewater containing chloride ions and alkali metal ions is separated into electrodialysis concentrated water and electrodialysis diluted water by an electrodialysis treatment; an electrolysis process in which the electrodialysis concentrated water is electrolyzed to produce an acidic aqueous solution; and a first circulating process in which at least some of the acidic aqueous solution is circulated to the wastewater supplied in the electrodialysis process.

[0025]

(17) In the method for producing an acidic aqueous solution according to the second aspect of the present invention, the method may further include a second circulating process in which at least some of the acidic aqueous solution is used in the electrolysis process.

5 [0025a]

A method for producing an acidic aqueous solution from wastewater containing chloride ions and alkali metal ions, the method, comprising: an electrodialysis process in which the wastewater is separated, by using an electrodialyzer including a monovalent ion perm-selective ion-exchange membrane, into electrodialysis concentrated water and
10 electrodialysis diluted water by an electrodialysis treatment; an electrolysis process in which the electrodialysis concentrated water is electrolyzed to produce an acidic aqueous solution; a first circulating process in which at least some of the acidic aqueous solution is circulated to the wastewater supplied in the electrodialysis process; and a second circulating process in which at least some of the acidic aqueous solution is used in the
15 electrolysis process, wherein a cation-exchange membrane of the monovalent ion perm-selective ion-exchange membrane is a m-phenolsulfonic acid-phenolic resin, or a resin obtained by subjecting a styrene-divinylbenzene copolymer to a sulfonation reaction, a cationic polymer electrolyte containing a polyethyleneimine is formed on a surface of the cation-exchange membrane, and an anion-exchange membrane of the monovalent ion
20 perm-selective ion-exchange membrane is an m-phenylenediamine-phenolic condensed resin, or a resin obtained by subjecting a styrene-divinylbenzene copolymer to an amination reaction.

[0026]

(18) In the method for producing an acidic aqueous solution according to the
25 second aspect of the present invention, the electrolysis process may be performed by a

hydrogen oxidation reaction.

[0027]

(19) In the method for producing an acidic aqueous solution according to the second aspect of the present invention, a sodium hypochlorite producing process in which
5 a part of the electrodialysis concentrated water may be electrolyzed to produce a sodium hypochlorite aqueous solution.

[0028]

(20) In the method for producing an acidic aqueous solution according to the second aspect of the present invention, the method may further include hydrogen peroxide
10 producing in which a part of the electrodialysis concentrated water is electrolyzed to produce hydrogen peroxide.

[Advantageous Effects of Invention]

[0029]

According to an apparatus for producing an acidic aqueous solution and a
15 method for producing an acidic aqueous solution according to one aspect of the present invention, it is possible to produce and use an acidic aqueous solution used in a wastewater treatment process on-site, and it is possible to significantly reduce the economic burden.

[Brief Description of Drawings]

20 [0030]

Fig. 1 is a schematic view of an apparatus for producing an acidic aqueous solution 100 according to a first embodiment.

Fig. 2 is a schematic view showing an electrodialyzer 111, which is an example of an electrodialyzer.

Fig. 3 is a schematic view showing a two-chamber electrolyzer 121, which is an example of an electrolyzer.

Fig. 4 is a schematic view showing a three-chamber electrolyzer 125, which is an example of an electrolyzer.

5 Fig. 5 is a schematic view of an apparatus for producing an acidic aqueous solution 101 according to a second embodiment.

Fig. 6 is a schematic view showing a sodium hypochlorite producing device 131, which is an example of a sodium hypochlorite producing device.

10 Fig. 7 is a schematic view of an apparatus for producing an acidic aqueous solution 102 according to a third embodiment.

Fig. 8 is a schematic view showing a hydrogen peroxide producing device 141, which is an example of a hydrogen peroxide producing device.

Fig. 9 is a schematic view of an apparatus for producing an acidic aqueous solution 103 according to a fourth embodiment.

15 Fig. 10 is a schematic view of a method for producing an acidic aqueous solution according to the first embodiment.

Fig. 11 is a schematic view of a method for producing an acidic aqueous solution according to the second embodiment.

20 Fig. 12 is a schematic view of a method for producing an acidic aqueous solution according to the third embodiment.

Fig. 13 is a schematic view of a method for producing an acidic aqueous solution according to the fourth embodiment.

[Detailed Description]

[0031]

25 [Overview]

In recent years, with the increase in population and improvement of living conditions, the amount of clean water used has increased, and water resources have become insufficient. In addition, deterioration of the water quality of rivers and wastewater has progressed, and countermeasures therefor are urgently needed worldwide.

5 For example, projects to use recycled water are being considered for the purpose of sustainable use of water resources.

[0032]

Wastewater treatments are generally divided into a primary treatment, a secondary treatment, and a tertiary treatment.

10 In the primary treatment, large waste particles (SS: suspended solids) are removed. SS is specifically the solids in sewage mixed with human waste.

In the secondary treatment, organic substances in the sewage that could not be removed in the primary treatment are removed according to the action of microorganisms. Specifically, in the secondary treatment, a simple aeration treatment,
15 an activated sludge treatment, a methane fermentation treatment or the like is performed.

In the tertiary treatment (also referred to as an advanced treatment or a post-treatment), nitrogen, phosphorus, difficult-to-decompose substances and the like are removed by a chemical, physical, or a biological method.

Examples of chemical treatments include separation of contaminants using a
20 coagulant or the like, and decomposition of contaminants using an oxidant such as ozone.

The physical treatment includes adsorption by activated carbon and separation by a membrane treatment.

For membranes used for separation by a membrane treatment, a reverse osmosis membrane (that is, a reverse osmosis (RO) membrane), an ultrafiltration membrane (that

is, an ultrafiltration (UF) membrane), a microfiltration membrane (that is, a microfiltration (MF) membrane) and the like are used.

[0033]

In the wastewater treatment process, in order to treat wastewater, it is essential
5 to add an acidic aqueous solution. For example, in order for the wastewater treatment process to function normally, an acidic aqueous solution is added to adjust the pH. In addition, depending on the apparatus, it is necessary to periodically chemically and physically wash the apparatus, and it is necessary to use an acidic aqueous solution at that time. For example, in a chelation treatment, use of an ion exchange resin and the
10 like, it is necessary to periodically perform washing with an acidic aqueous solution to restore performance.

[0034]

On the other hand, since the acidic aqueous solution used in the wastewater treatment process needs to be transported from the outside and stored, it causes a large
15 economic burden.

[0035]

In the conventional organic wastewater treatment apparatus described in Patent Literature 1 described above, it is possible to produce sodium hypochlorite, but it is not possible to produce an acidic aqueous solution used in the wastewater treatment process
20 on-site.

In addition, in the wastewater treatment apparatus described in Patent Literature 2, a problem of an acidic aqueous solution that needs to be transported from the outside can be addressed, but a problem of the produced acidic aqueous solution that needs to be stored cannot be addressed. Therefore, in the conventional treatment method, the acidic

aqueous solution used in the wastewater treatment process could not be produced and used on-site.

[0036]

An apparatus for producing an acidic aqueous solution according to a first
5 embodiment is an apparatus for producing an acidic aqueous solution that produces an acidic aqueous solution from wastewater containing chloride ions and alkali metal ions (hereinafter simply referred to as wastewater), including an electrodialyzer that has a monovalent ion perm-selective ion-exchange membrane and separates the wastewater into electrodialysis concentrated water and electrodialysis diluted water by an
10 electrodialysis treatment, an electrolyzer that electrolyzes the electrodialysis concentrated water to produce an acidic aqueous solution, and a first circulator that circulates at least some of the acidic aqueous solution to the wastewater supplied to the electrodialyzer. Thereby, it is possible to achieve a complete type (zero chemical charge (ZCC)) in which the acidic aqueous solution used in the wastewater treatment process is locally produced
15 and locally consumed on-site, and it is possible to significantly reduce the economic burden.

[0037]

(Apparatus for producing acidic aqueous solution)

A first aspect of the present invention is an apparatus for producing an acidic
20 aqueous solution that produces an acidic aqueous solution from wastewater containing chloride ions and alkali metal ions, including an electrodialyzer that has a monovalent ion perm-selective ion-exchange membrane and separates the wastewater into electrodialysis concentrated water and electrodialysis diluted water by an electrodialysis treatment, an electrolyzer that electrolyzes the electrodialysis concentrated water to

produce an acidic aqueous solution, and a first circulator that circulates at least some of the acidic aqueous solution to the wastewater supplied to the electrodialyzer.

[0038]

<Apparatus for producing acidic aqueous solution according to first embodiment>

5 An apparatus for producing an acidic aqueous solution according to a first embodiment includes an electrodialyzer, an electrolyzer, and a first circulator.

The apparatus for producing an acidic aqueous solution according to the first embodiment will be described in detail with reference to Fig. 1.

[0039]

10 · Wastewater

In the apparatus for producing an acidic aqueous solution according to the first embodiment, wastewater (referred to as raw water) includes, for example, organic wastewater which contains at least chloride ions and alkali metal ions, and cannot be reused or discharged into rivers. Specific examples thereof include organic wastewater
15 having a high salt concentration from such as seawater, excreta, and leachates from garbage landfill. These generally contain impurities (hereinafter referred to as various ion components) such as calcium ions, magnesium ions, sodium ions, silica (for example, ionic silica, and colloidal silica), chloride ions, and carbonate ions.

[0040]

20 In order to further improve the effects of the first embodiment, the lower limit value of the chloride ion concentration of wastewater is preferably 0.01 mg/L or more. On the other hand, the upper limit value of the chloride ion concentration of wastewater is not particularly limited, and is, for example, 500 mg/L or less.

In addition, the lower limit value of the alkali metal ion concentration of
25 wastewater is preferably 0.01 mg/L or more. On the other hand, the upper limit value of

the alkali metal ion concentration of wastewater is not particularly limited, and is, for example, 500 mg/L or less.

[0041]

Here, in this specification, the cation concentration is a value measured by
5 inductively coupled plasma (ICP) emission spectroscopy. Specifically, it is a value measured using an emission spectrophotometer (ICP-AES; SPS5520, commercially available from Seiko Instruments Inc.) using an argon gas ICP as a light source.

On the other hand, the anion concentration is a value measured using an ion chromatography analyzer (ICA-2000; commercially available from DKK-TOA
10 Corporation).

[0042]

An apparatus for producing an acidic aqueous solution 100 according to the first embodiment shown in Fig. 1 has the following configuration.

A wastewater inflow pipe 10 through which wastewater is supplied is connected
15 to an electro dialysis dilution chamber of an electro dialyzer 110. In addition, a dialysis water electro dialysis concentration chamber supply pipe 9 through which dialysis water is supplied is connected to an electro dialysis concentration chamber of the electro dialyzer 110. An electro dialysis concentrated water supply pipe 11 and an electro dialysis diluted water discharge pipe 12 are connected to the outlet side of the electro dialyzer 110. The
20 electro dialyzer 110 is connected to an electrolyzer 120 via the electro dialysis concentrated water supply pipe 11. A first circulator 13, an acid water discharge pipe 14, and a second circulator 15 are connected to the outlet side of the electrolyzer 120.

[0043]

The electro dialyzer 110 is an apparatus that has a monovalent ion perm-selective
25 ion-exchange membrane and separates wastewater containing chloride ions and alkali

metal ions into electro dialysis concentrated water and electro dialysis diluted water by an electro dialysis treatment.

Specific examples of the electro dialyzer 110 include an electro dialyzer 111 having a monovalent ion perm-selective ion-exchange membrane shown in Fig. 2.

5 The electro dialyzer 111 having a monovalent ion perm-selective ion-exchange membrane includes an anode 112 and a cathode 113. In addition, it is divided into an electro dialysis dilution chamber 116 and an electro dialysis concentration chamber 117 by alternately providing a monovalent anion perm-selective ion-exchange membrane 114 and a monovalent cation perm-selective ion-exchange membrane 115 between the anode
10 112 and the cathode 113.

[0044]

The wastewater inflow pipe 10 through which wastewater is supplied is connected to the electro dialysis dilution chamber of the electro dialyzer 110. On the other hand, the dialysis water electro dialysis concentration chamber supply pipe 9
15 through which dialysis water is supplied is connected to the electro dialysis concentration chamber of the electro dialyzer 110. Here, the dialysis water is water containing a small amount of multivalent ions (for example, tap water).

When the dialysis water containing a small amount of multivalent ions is supplied to the electro dialysis concentration chamber of the electro dialyzer, it is possible
20 to improve the efficiency of production of an acidic aqueous solution of an electrolyzer to be described below.

[0045]

Here, the apparatus for producing an acidic aqueous solution 100 according to the first embodiment includes the dialysis water electro dialysis concentration chamber
25 supply pipe 9. However, depending on the water quality of wastewater, the dialysis

water electro dialysis concentration chamber supply pipe 9 may not be provided, and only the wastewater inflow pipe 10 may be connected to the electro dialyzer 110.

That is, wastewater may be supplied to both the electro dialysis concentration chamber and the electro dialysis dilution chamber of the electro dialyzer 110.

5 [0046]

Specific examples of the anode 112 include an electrode in which a catalyst layer is formed by firing a catalyst on a conductive metal substrate that is stable to oxidation.

Examples of conductive metals include titanium.

10 Examples of catalysts include precious metals such as platinum, iridium, ruthenium, and rhodium; valve metals such as titanium and tantalum; and oxides of valve metals.

[0047]

In the anode 112, the thickness of the conductive metal substrate is preferably
15 0.05 to 5 mm.

In addition, the thickness of the catalyst layer is preferably 0.1 to 100 μm .

[0048]

The porosity of the anode 112 is preferably 10 to 95%.

In order to improve adhesion of the catalyst, a roughening treatment is
20 preferably performed on the conductive metal. Examples of roughening treatments include a blasting treatment by spraying powder, etching using a soluble acid, and plasma spraying.

[0049]

When the anode 112 is produced, before a catalyst layer is formed, it is
25 preferable to form an AIP underlayer made of a valve metal base alloy containing

tantalum and a titanium component on the conductive metal substrate by an arc ion plating (AIP) method. When the AIP underlayer is provided on the conductive metal substrate, it is possible to further prevent interfacial corrosion of the metal substrate. In addition, an underlayer composed of a TiTaO_x oxide layer may be formed in place of the AIP underlayer.

[0050]

More specifically, as the anode 112, a Ti mesh electrode formed with a catalyst composed of Pt and Ir oxide or the like can be used.

[0051]

Like the anode 112, as the cathode 113, an electrode in which a catalyst layer is formed by firing a catalyst on a conductive metal substrate that is stable to oxidation may be exemplified.

Examples of conductive metals include titanium, nickel, iron, stainless steel, and carbon.

Examples of catalysts include precious metals such as platinum, iridium, ruthenium, and rhodium; valve metals such as titanium and tantalum; and oxides of valve metals.

In addition, as the cathode 113, a platinum-plated conductive metal may be used.

[0052]

Specific examples of the monovalent anion perm-selective ion-exchange membrane 114 include those in which a membrane having a dense structure is formed on the surface of the anion-exchange membrane. The membrane limits movement of multivalent ions by a sieving effect, and thus the transport rate of multivalent ions is reduced.

Specific examples of anion-exchange membranes include an m-phenylenediamine-phenolic condensed resin and a resin obtained by subjecting a styrene-divinylbenzene copolymer to an amination reaction.

[0053]

5 As a commercially available example of the monovalent anion perm-selective ion-exchange membrane 114, ACS (commercially available from ASTOM Corporation) or the like can be used.

[0054]

Specific examples of the monovalent cation perm-selective ion-exchange
10 membrane 115 include those in which a membrane having a dense structure is formed on the surface of the cation-exchange membrane. The membrane limits movement of multivalent ions by a sieving effect, and thus the transport rate of multivalent ions is reduced.

Specific examples of cation-exchange membranes include a m-phenolsulfonic
15 acid-phenolic resin, and a resin obtained by subjecting a styrene-divinylbenzene copolymer to a sulfonation reaction.

In addition, as the monovalent cation perm-selective ion-exchange membrane 115, those in which a cationic polymer electrolyte containing a polyethyleneimine is formed on the surface of the cation exchange membrane may be used. In this case, as
20 the valence of cations is higher, movement of the surface due to a repulsive effect is more constrained, and the monovalent cation selectivity is exhibited.

[0055]

As a commercially available example of the monovalent cation perm-selective ion-exchange membrane 115, CIMS (commercially available from ASTOM Corporation)
25 or the like can be used.

[0056]

When the apparatus for producing an acidic aqueous solution 100 includes the electro dialyzer 110 having a monovalent ion perm-selective ion-exchange membrane, it is possible to increase the concentration of monovalent anions (for example, chloride ions) in wastewater. Therefore, in the electrolyzer 120 to be described below, it is possible to produce the acidic aqueous solution more efficiently. In addition, multivalent ions that are likely to adhere to the electrolyzer 120 can be removed in advance.

[0057]

10 The electro dialysis diluted water produced by the electro dialyzer 110 is discharged through the electro dialysis diluted water discharge pipe 12.

On the other hand, the electro dialysis concentrated water produced by the electro dialyzer 110 is supplied to the electrolyzer 120 through the electro dialysis concentrated water supply pipe 11.

15 [0058]

The electrolyzer 120 is an apparatus that electrolyzes the electro dialysis concentrated water to produce an acidic aqueous solution and an alkaline aqueous solution.

Specific examples of the electrolyzer 120 include a two-chamber electrolyzer 121 shown in Fig. 3 and a three-chamber electrolyzer 125 shown in Fig. 4.

[0059]

The two-chamber electrolyzer 121 shown in Fig. 3 includes an anode 122 and a cathode 123, and is divided into an anode chamber and a cathode chamber by a diaphragm 124.

25 [0060]

As the anode 122, the same ones described above as the anode 112 of the electrolyzer 110 may be exemplified. Among these, a hydrogen gas diffusion electrode is preferably used.

When the hydrogen gas diffusion electrode is used, it is possible to further
5 minimize generation of chlorine.

[0061]

The hydrogen gas diffusion electrode is a gas electrode composed of catalyst particles that easily oxidize hydrogen and carbon particles that serve carriers for the catalyst particles.

10 Specific examples of catalyst particles include platinum and ruthenium.

[0062]

Specific examples of hydrogen gas diffusion electrodes include an electrode including a support and a power feeder.

Examples of supports of hydrogen gas diffusion electrodes include those in
15 which a hydrophobic resin is fixed on a conductive carbon material (for example, a sheet, cloth, and paper) having catalyst particles.

Examples of power feeders include a porous plate such as a metal mesh made of a material that is durable to acidity. The support and the power feeder are bonded by crimping.

20 [0063]

As the cathode 123, the same ones described above as the cathode 113 of the electrolyzer 110 may be exemplified.

[0064]

Specific examples of the diaphragm 124 include an ion-exchange membrane, a
25 porous resin film and a porous ceramic film. Among these, it is preferable to provide a

neutral membrane such as a porous resin film and a porous ceramic film. Examples of commercially available products of porous resin films include Y9201 (commercially available from Yuasa Membrane Systems Co., Ltd.).

[0065]

5 The three-chamber electrolyzer 125 shown in Fig. 4 includes an anode 126 and a cathode 127, and is divided into an anode chamber 1, an intermediate chamber 2, and a cathode chamber 3 by an anion-exchange membrane 128 on the side of the anode 126 and a cation-exchange membrane 129 on the side of the cathode 127.

 In the three-chamber electrolyzer 125, electrolysis is performed only in the
10 intermediate chamber 2, and ions produced in the intermediate chamber 2 move to the anode chamber 1 and the cathode chamber 3 on both sides.


[0066]

 According to electrolysis from electrodialysis concentrated water, an acidic aqueous solution is produced in the anode chamber 1, and a basic aqueous solution is
15 produced in the cathode chamber 3. Unlike the two-chamber electrolyzer 121, the three-chamber electrolyzer 125 has an advantage that salt water is not mixed with the acidic aqueous solution and the basic aqueous solution.

 Here, as the anode 126 and the cathode 127 in the three-chamber electrolyzer 125, the same ones described as the anode 122 and the cathode 123 in the two-chamber
20 electrolyzer 121 may be exemplified.

[0067]


 For example, when wastewater containing sodium ions and chloride ions is electrolyzed using the electrolyzer 120, a reaction represented by the following Formula (1) proceeds, and a sodium hydroxide aqueous solution (that is, an alkaline aqueous
25 solution) and a hydrochloric acid (that is, an acidic aqueous solution) are obtained.



[0068]

In addition, when the electrolyzer 120 in which the anode is a hydrogen gas diffusion electrode is used, a hydrogen oxidation reaction represented by the following

5 Formula (2) occurs in the anode. In addition, the total reaction is as shown in the following Formula (3).



[0069]

10 As the raw hydrogen gas, a high-purity electrolytic hydrogen gas generated in the cathode is used. It is possible to minimize generation of chlorine by keeping a potential lower than a chlorine generation potential.

[0070]

15 The acidic aqueous solution (for example, hydrochloric acid) produced in the electrolyzer 120 is circulated to wastewater supplied to the electrodialyzer 110 via the first circulator 13 and the wastewater inflow pipe 10.

The acidic aqueous solution produced in the electrolyzer 120 can be circulated to wastewater to adjust the pH of the wastewater.

20 For example, the wastewater supplied to the electrodialyzer 110 described above may be treated in advance by a crystallizer that removes calcium carbonate or an alkaline precipitation device that precipitates and removes heavy metals as hydroxides. In this case, since the wastewater is alkaline (a pH of about 11 or more), it is preferable to circulate the acidic aqueous solution produced in the electrolyzer 120 in wastewater to adjust the pH of the wastewater. Specifically, it is preferable to adjust the pH of the

wastewater to 10 or less, and it is more preferable to adjust the pH of the wastewater to 3 to 9.

Thereby, it is possible to further prevent deterioration of the monovalent anion perm-selective ion-exchange membrane 114 and the monovalent cation perm-selective ion-exchange membrane 115.

[0071]

Here, in this specification, the pH of various aqueous solutions is a value obtained by measuring the pH of various aqueous solutions at 25°C with a pH meter (D74, commercially available from HORIBA, Ltd.).

[0072]

In addition, the acidic aqueous solution (for example, hydrochloric acid) produced in the electrolyzer 120 is used to wash the inside of the electrolyzer 120 when the electrolyzer 120 is stopped via the second circulator 15. Here, the electrolyzer 120 may include a storage tank in which the acidic aqueous solution is stored.

[0073]

Here, in the schematic view of the apparatus for producing an acidic aqueous solution according to the first embodiment shown in Fig. 1, the apparatus for producing an acidic aqueous solution 100 includes the second circulator 15. However, the apparatus for producing an acidic aqueous solution 100 may not include the second circulator 15.

[0074]

In addition, the electrolyzer 120 may be connected to another apparatus in order to use the alkaline aqueous solution produced in the electrolyzer 120. Examples of other apparatuses include a crystallizer that removes calcium carbonate using an alkaline

aqueous solution and an alkaline precipitation device that precipitates and removes heavy metals as hydroxides.

[0075]

The apparatus for producing an acidic aqueous solution 100 according to the first embodiment described above includes the above electrodialyzer 110, the electrolyzer 120, and the first circulator 13. In the apparatus for producing an acidic aqueous solution 100 according to the first embodiment, an acidic aqueous solution required for adjusting the pH of the wastewater and preventing deterioration of the monovalent ion perm-selective ion-exchange membrane of the electrodialyzer can be produced on-site in the electrolyzer 120, and used in the electrodialyzer 110 via the first circulator 13. Therefore, it is not necessary to transport and store the acidic aqueous solution from the outside and it is possible to significantly reduce the economic burden.

[0076]

<Apparatus for producing acidic aqueous solution according to second embodiment>

An apparatus for producing an acidic aqueous solution according to a second embodiment further includes a sodium hypochlorite producing device in addition to the apparatus for producing an acidic aqueous solution according to the first embodiment. That is, the apparatus for producing an acidic aqueous solution according to the second embodiment includes an electrodialyzer, an electrolyzer, a first circulator, and a sodium hypochlorite producing device.

The apparatus for producing an acidic aqueous solution according to the second embodiment will be described in detail with reference to Fig. 5.

[0077]

An apparatus for producing an acidic aqueous solution 101 according to the second embodiment shown in Fig. 5 has the following configuration.

The wastewater inflow pipe 10 through which wastewater is supplied is connected to the electro dialysis dilution chamber of the electro dialyzer 110. In addition, the dialysis water electro dialysis concentration chamber supply pipe 9 through which dialysis water is supplied is connected to the electro dialysis concentration chamber of the electro dialyzer 110. The first electro dialysis concentrated water supply pipe 11, the electro dialysis diluted water discharge pipe 12, and a second electro dialysis concentrated water supply pipe 16 are connected to the outlet side of the electro dialyzer 110. The electro dialyzer 110 is connected to the electrolyzer 120 via the electro dialysis concentrated water supply pipe 11. The first circulator 13, the acid water discharge pipe 14, and the second circulator 15 are connected to the outlet side of the electrolyzer 120. In addition, the electro dialyzer 110 is connected to a sodium hypochlorite producing device 130 via the second electro dialysis concentrated water supply pipe 16. A sodium hypochlorite aqueous solution discharge pipe 17 is connected to the outlet side of the sodium hypochlorite producing device 130.

[0078]


The sodium hypochlorite producing device 130 is an apparatus that electrolyzes a part of the electro dialysis concentrated water to produce sodium hypochlorite.

Specific examples of the sodium hypochlorite producing device 130 include a one-chamber electrolyzer 131 shown in Fig. 6. The one-chamber electrolyzer 131 includes an anode 132 and a cathode 133.

Here, as the anode 132 and the cathode 133 in the sodium hypochlorite producing device 131, the same ones described as the anode 122 and the cathode 123 in the two-chamber electrolyzer 121 may be exemplified.

[0079]

In the sodium hypochlorite producing device 130, a reaction represented by the following Formula (4) occurs, and sodium hypochlorite can be produced from chloride ions contained in wastewater.



[0080]

The sodium hypochlorite can be used as, for example, a disinfectant for treated water on which a wastewater treatment is performed. Therefore, if the sodium hypochlorite aqueous solution discharge pipe 17 is connected to a pipe through which
10 wastewater on which a wastewater treatment is performed is discharged, the sodium hypochlorite can be used on-site.

[0081]

Here, the apparatus for producing an acidic aqueous solution 101 according to the second embodiment includes the dialysis water electro dialysis concentration chamber
15 supply pipe 9. However, depending on the water quality of wastewater, the dialysis water electro dialysis concentration chamber supply pipe 9 may not be provided, and only the wastewater inflow pipe 10 may be connected to the electro dialyzer 110.

That is, wastewater may be supplied to both the electro dialysis concentration chamber and the electro dialysis dilution chamber of the electro dialyzer 110.

20 [0082]

In addition, the apparatus for producing an acidic aqueous solution 101 according to the second embodiment includes the second circulator 15 that circulates the acidic aqueous solution (for example, hydrochloric acid) produced in the electrolyzer 120 in order to wash the inside of the electrolyzer 120. However, the apparatus for

producing an acidic aqueous solution 101 according to the second embodiment may not include the second circulator 15.

[0083]

In the apparatus for producing an acidic aqueous solution 101 according to the second embodiment described above, in addition to the effects of the apparatus for producing an acidic aqueous solution 100 according to the first embodiment described above, a sodium hypochlorite aqueous solution used as a disinfectant for treated water can be produced on-site in the sodium hypochlorite producing device 130. In addition, when the produced sodium hypochlorite aqueous solution is added to the treated water, the sodium hypochlorite aqueous solution can be used as a disinfectant.

[0084]

<Apparatus for producing acidic aqueous solution according to third embodiment>

An apparatus for producing an acidic aqueous solution according to a third embodiment further includes a hydrogen peroxide producing device in addition to the apparatus for producing an acidic aqueous solution according to the first embodiment. That is, the apparatus for producing an acidic aqueous solution according to the second embodiment includes an electrodialyzer, an electrolyzer, a first circulator, and a hydrogen peroxide producing device.

The apparatus for producing an acidic aqueous solution according to the third embodiment will be described in detail with reference to Fig. 7.

[0085]

An apparatus for producing an acidic aqueous solution 102 according to the third embodiment shown in Fig. 7 has the following configuration.

The wastewater inflow pipe 10 through which wastewater is supplied is connected to the electrodialysis dilution chamber of the electrodialyzer 110. In

addition, the dialysis water electro dialysis concentration chamber supply pipe 9 through which dialysis water is supplied is connected to the electro dialysis concentration chamber of the electro dialyzer 110. The first electro dialysis concentrated water supply pipe 11, the electro dialysis diluted water discharge pipe 12, and a third electro dialysis concentrated water supply pipe 18 are connected to the outlet side of the electro dialyzer 110. The electro dialyzer 110 is connected to the electrolyzer 120 via the electro dialysis concentrated water supply pipe 11. The first circulator 13, the acid water discharge pipe 14, and the second circulator 15 are connected to the outlet side of the electrolyzer 120. In addition, the electro dialyzer 110 is connected to a hydrogen peroxide producing device 140 via the third electro dialysis concentrated water supply pipe 18. A hydrogen peroxide discharge pipe 19 is connected to the outlet side of the hydrogen peroxide producing device 140.

[0086]

The hydrogen peroxide producing device 140 is an apparatus that electrolyzes a part of the electro dialysis concentrated water to produce hydrogen peroxide.

[0087]

As the hydrogen peroxide producing device 140, for example, a two-chamber electrolyzer 141 having a gas diffusion electrode shown in in Fig. 8 may be exemplified.

The two-chamber electrolyzer 141 having a gas diffusion electrode includes an anode 142 and a cathode 143, and is divided into an anode chamber 145 and a cathode chamber 146 by a diaphragm 144.

[0088]

As the anode 142, specifically, the same ones described above as the anode 112 of the electro dialyzer 110 may be exemplified.

[0089]

As the cathode 143, specifically, it is preferable to use a porous oxygen gas diffusion electrode having excellent mass transfer of oxygen gas, which is a raw material.

As a porous oxygen gas diffusion electrode, more specifically, an oxygen gas diffusion electrode in which a graphite powder having a particle size of about several
 5 tens of μm is used as a catalyst, and a sheet mixed with a fluororesin solution is fixed to a conductive support having excellent air permeability such as a carbon cloth or carbon paper with a hot press is preferable.


[0090]

The inter-electrode distance between the anode 142 and the cathode 143 in the
 10 hydrogen peroxide producing device 140 is preferably 0.2 to 5 mm.

As the diaphragm 144, the same ones described above as the diaphragm 124 in the two-chamber electrolyzer 121 may be exemplified.

[0091]

When electrolysis is performed while supplying an oxygen-containing gas from
 15 behind the gas diffusion electrode in which a cathode catalyst is formed described above, hydrogen peroxide (ion) is produced by a reaction represented by the following Formula (5).



[0092]

20 When the hydrogen peroxide is used in combination in, for example, in the ultraviolet (UV) treatment process in the final stage of drinking water production, an advanced oxidation process (AOP) proceeds, and contributes to improvement of water quality. In addition, if wastewater is treated with ozone, when an oxidation treatment with ozone becomes excessive, for example, hydrogen peroxide can also be used for

decomposition of bromic acid, which is generally produced by oxidation of bromide ions contained in the wastewater.

In addition, when a disinfection treatment with a sodium hypochlorite aqueous solution is performed, hydrogen peroxide can also be used when excess sodium

5 hypochlorite is removed.

When the hydrogen peroxide discharge pipe 19 is connected to the apparatus that performs the above treatment or a discharge pipe for the treated water that is treated by the apparatus, the hydrogen peroxide produced by the hydrogen peroxide producing device 140 described above can be used.

10 [0093]

Here, the apparatus for producing an acidic aqueous solution 102 according to the third embodiment includes the dialysis water electro dialysis concentration chamber supply pipe 9. However, depending on the water quality of wastewater, the dialysis water electro dialysis concentration chamber supply pipe 9 may not be provided, and only

15 the wastewater inflow pipe 10 may be connected to the electro dialyzer 110.

That is, wastewater may be supplied to both the electro dialysis concentration chamber and the electro dialysis dilution chamber of the electro dialyzer 110.

[0094]

In addition, the apparatus for producing an acidic aqueous solution 102 according to the third embodiment includes the second circulator 15 that circulates the acidic aqueous solution (for example, hydrochloric acid) produced in the electrolyzer 120 in order to wash the inside of the electrolyzer 120. However, the apparatus for producing an acidic aqueous solution 102 according to the third embodiment may not include the second circulator 15.

25 [0095]

In the apparatus for producing an acidic aqueous solution 102 according to the third embodiment described above, in addition to the effects of the apparatus for producing an acidic aqueous solution 100 according to the first embodiment described above, hydrogen peroxide that is generally used in the wastewater treatment process can be produced on-site in the hydrogen peroxide producing device 140. In addition, when the produced hydrogen peroxide is added to treated water, the hydrogen peroxide can be used.

[0096]

<Apparatus for producing acidic aqueous solution according to fourth embodiment>

An apparatus for producing an acidic aqueous solution according to a fourth embodiment further includes a sodium hypochlorite producing device and a hydrogen peroxide producing device in addition to the apparatus for producing an acidic aqueous solution according to the first embodiment. That is, the apparatus for producing an acidic aqueous solution according to the fourth embodiment includes an electro dialyzer, an electrolyzer, a first circulator, a sodium hypochlorite producing device, and a hydrogen peroxide producing device.

The apparatus for producing an acidic aqueous solution according to the fourth embodiment will be described in detail with reference to Fig. 9.

[0097]

An apparatus for producing an acidic aqueous solution 103 according to the fourth embodiment shown in Fig. 9 has the following configuration.

The wastewater inflow pipe 10 through which wastewater is supplied is connected to the electro dialysis dilution chamber of the electro dialyzer 110. In addition, the dialysis water electro dialysis concentration chamber supply pipe 9 through which dialysis water is supplied is connected to the electro dialysis concentration chamber

of the electro dialyzer 110. The first electro dialysis concentrated water supply pipe 11, the electro dialysis diluted water discharge pipe 12, the second electro dialysis concentrated water supply pipe 16 and the third electro dialysis concentrated water supply pipe 18 are connected to the outlet side of the electro dialyzer 110. The electro dialyzer 110 is connected to the electrolyzer 120 via the electro dialysis concentrated water supply pipe 11. The first circulator 13, the acid water discharge pipe 14, and the second circulator 15 are connected to the outlet side of the electrolyzer 120. In addition, the electro dialyzer 110 is connected to the sodium hypochlorite producing device 130 via the second electro dialysis concentrated water supply pipe 16. The sodium hypochlorite aqueous solution discharge pipe 17 is connected to the outlet side of the sodium hypochlorite producing device 130. In addition, the electro dialyzer 110 is connected to the hydrogen peroxide producing device 140 via the third electro dialysis concentrated water supply pipe 18. The hydrogen peroxide discharge pipe 19 is connected to the outlet side of the hydrogen peroxide producing device 140.

[0098]

Here, the apparatus for producing an acidic aqueous solution 103 according to the fourth embodiment includes the dialysis water electro dialysis concentration chamber supply pipe 9. However, depending on the water quality of wastewater, the dialysis water electro dialysis concentration chamber supply pipe 9 may not be provided, and only the wastewater inflow pipe 10 may be connected to the electro dialyzer 110.

That is, wastewater may be supplied to both the electro dialysis concentration chamber and the electro dialysis dilution chamber of the electro dialyzer 110.

[0099]

In addition, the apparatus for producing an acidic aqueous solution 103 according to the fourth embodiment includes the second circulator 15 that circulates the

acidic aqueous solution (for example, hydrochloric acid) produced in the electrolyzer 120 in order to wash the inside of the electrolyzer 120. However, the apparatus for producing an acidic aqueous solution 103 according to the fourth embodiment may not include the second circulator 15.

5 [0100]

In the apparatus for producing an acidic aqueous solution 103 according to the fourth embodiment described above, in addition to the effects of the apparatus for producing an acidic aqueous solution 100 according to the first embodiment described above, a sodium hypochlorite aqueous solution used as a disinfectant for treated water and hydrogen peroxide that is generally used in the wastewater treatment process can be produced on-site. In addition, the produced sodium hypochlorite aqueous solution and hydrogen peroxide can be used on-site.

[0101]

(Method for producing acidic aqueous solution)

15 A second aspect of the present invention is a method for producing an acidic aqueous solution in which an acidic aqueous solution is produced from wastewater containing chloride ions and alkali metal ions, including an electrodialysis process in which the wastewater is separated into electrodialysis concentrated water and electrodialysis diluted water by an electrodialysis treatment, an electrolysis process in which the electrodialysis concentrated water is electrolyzed to produce an acidic aqueous solution, and a first circulating process in which at least some of the acidic aqueous solution is circulated to the wastewater supplied to the electrodialysis process.

[0102]

<Method for producing acidic aqueous solution according to first embodiment>

A method for producing an acidic aqueous solution according to a first embodiment includes an electrodialysis process 210, an electrolysis process 220, and a first circulating process.

The schematic view of the method for producing an acidic aqueous solution according to the first embodiment is as shown in Fig. 10.

[0103]

[Electrodialysis process]

The electrodialysis process 210 is a process of separating wastewater containing chloride ions and alkali metal ions into electrodialysis concentrated water and electrodialysis diluted water by an electrodialysis treatment.

Specifically, a large number of electrodialysis membranes as in the above electrodialyzer (Fig. 2) are arranged, wastewater is supplied to an electrodialyzer including an electrodialysis concentration chamber and an electrodialysis dilution chamber alternately formed, a current is caused to flow, and thus electrodialysis concentrated water containing various ion components at a high concentration can be obtained in the concentration chamber, and electrodialysis diluted water containing various ion components at a low concentration can be obtained in the dilution chamber.

[0104]

In electrodialysis conditions, the temperature is preferably 25 to 60°C, and the current density is preferably 1 to 10 A/dm².

[0105]

When the method for producing an acidic aqueous solution according to the first embodiment includes the electrodialysis process 210, since the concentration of chloride ions in wastewater can increase, in the electrolysis process to be described below, the acidic aqueous solution can be produced more efficiently. In addition, multivalent ions

that are likely to adhere to the electrolyzer used in the electrolysis process can be removed in advance.

[0106]

[Electrolysis process]

5 The electrolysis process 220 is a process in which a part of wastewater is electrolyzed to obtain an acidic aqueous solution and an alkaline aqueous solution.


Specifically, in this method, by applying a voltage to a pair of electrodes having electron conductivity (that is, a positive electrode; an anode, and a negative electrode; a cathode) and an electrolyte having ion conductivity, an oxidation reaction occurs in the
10 anode, and a reduction reaction occurs in the cathode, and an acidic aqueous solution and an alkaline aqueous solution are obtained.

[0107]

The electrolysis process 220 can be performed using, for example, the above two-chamber electrolyzer (refer to Fig. 3) and three-chamber electrolyzer (refer to Fig.
15 4).

[0108]

In the electrolysis process 220, for example, when wastewater containing sodium ions and chloride ions is electrolyzed, a reaction represented by the following Formula (6) proceeds, and a sodium hydroxide aqueous solution (that is, an alkaline
20 aqueous solution) and a hydrochloric acid (that is, an acidic aqueous solution) are obtained.



[0109]



For example, in the two-chamber electrolyzer (Fig. 3) to be described below, a
25 mixture of hydrochloric acid and salt water is obtained as the acidic aqueous solution,

and a mixture of sodium hydroxide and salt water is obtained as the alkaline aqueous solution.

On the other hand, in the three-chamber electrolyzer (Fig. 4) to be described below, the sodium hydroxide aqueous solution is obtained in the cathode chamber, and
5 hydrochloric acid is obtained in the anode chamber.

The hydrochloric acid obtained in the reaction is mixed with wastewater supplied to the electrodialysis process 210 described above, and used to adjust the pH.
[0110]

In addition, when the electrolyzer in which the anode is a hydrogen gas diffusion
10 electrode is used, a hydrogen oxidation reaction represented by the following Formula (7) occurs in the anode. In addition, the total reaction is as shown in the following Formula (8).



15 [0111]

As the raw hydrogen gas, a high-purity electrolytic hydrogen gas generated in the cathode is used. It is possible to minimize generation of chlorine by keeping a potential lower than a chlorine generation potential.

[0112]

20 In the electrolysis process 220, according to the above hydrogen oxidation reaction, an acidic aqueous solution and an alkaline aqueous solution can be produced, and thus it is possible to further minimize generation of chlorine.

[0113]

[First circulating process]

The first circulating process is a process in which at least some of the acidic aqueous solution produced in the electrolysis process 220 is circulated to the wastewater supplied in the electrodialysis process.

The pH of the wastewater supplied in the electrodialysis process is adjusted with the acidic aqueous solution obtained in the electrolysis process 220.

For example, the wastewater supplied to the electrodialysis process 210 describe above may be treated in advance by a crystallizer that removes calcium carbonate or an alkaline precipitation device that precipitates and removes heavy metals as hydroxides. In this case, since the wastewater is alkaline (a pH of about 11 or more), it is preferable to circulate the acidic aqueous solution produced in the electrolysis process to the wastewater to adjust the pH of the wastewater. Specifically, it is preferable to adjust the pH of the wastewater to 10 or less, and it is more preferable to adjust the pH of the wastewater to 3 to 9.

Thereby, it is possible to further prevent deterioration of the monovalent anion perm-selective ion-exchange membrane and the monovalent cation perm-selective ion-exchange membrane of the electrodialyzer used in the electrodialysis process.

[0114]

[Washing process]

The method for producing an acidic aqueous solution according to the first embodiment may include a washing process. The washing process is a process in which the apparatus (that is, the electrolyzer) used in the electrolysis process 220 described above is washed using at least some of the acidic aqueous solution. Due to continuous operations of the electrolyzer for a long time, hardness components are precipitated on the diaphragm and the cathode in the apparatus of the electrolyzer, which causes deterioration of performance of the electrolyzer. Therefore, it is preferable to

intermittently stop the electrolyzer and wash with the acidic aqueous solution obtained in the electrolysis process 220. The frequency of washing depends on the water quality and operation conditions, and washing is preferably performed every several hours to several tens of hours and several tens of minutes to several hours.

5 [0115]

The method for producing an acidic aqueous solution according to the first embodiment described above includes the above electro dialysis process, the electrolysis process 220, and a first circulating process. An acidic aqueous solution required for adjusting the pH of the wastewater and preventing deterioration of the monovalent ion perm-selective ion-exchange membrane used in the electro dialysis process can be produced on-site in the electrolysis process 220, and used in the electro dialysis process according to the first circulating process. Therefore, it is not necessary to transport and store the acidic aqueous solution from the outside and it is possible to significantly reduce the economic burden.

15 [0116]

<Method for producing acidic aqueous solution according to second embodiment>

A method for producing an acidic aqueous solution according to a second embodiment includes an electro dialysis process 210, an electrolysis process 220, a first circulating process, and a sodium hypochlorite producing process 230.



20 The schematic view of the method for producing an acidic aqueous solution according to the second embodiment is as shown in Fig. 11.

[0117]

[Sodium hypochlorite producing process]

The sodium hypochlorite producing process 230 is a process of electrolyzing a part of electro dialysis concentrated water to produce a sodium hypochlorite aqueous solution.

When an anode catalyst is appropriately selected, the reaction as shown in the following Formula (4) occurs, and sodium hypochlorite can be produced from chloride ions contained in wastewater.



[0118]

The sodium hypochlorite can be used as a disinfectant for treated water.

Therefore, in the method for producing an acidic aqueous solution according to the second embodiment, in addition to the effects of the method for producing an acidic aqueous solution according to the first embodiment described above, when a sodium hypochlorite aqueous solution used as a disinfectant for treated water is produced on-site in the sodium hypochlorite producing process, and added to the treated water, the sodium hypochlorite aqueous solution can be used as a disinfectant.

The hypochlorous acid component is stably present as hypochlorous acid ions in the alkaline region and hypochlorous acid in the acidic region, and either can be produced by changing the pH of the solution to be electrolyzed. It is known that sterilizing power is higher in the latter case. Sodium hypochlorite in one aspect of the present invention is a general term for these.

[0119]

<Method for producing acidic aqueous solution according to third embodiment>

A method for producing an acidic aqueous solution according to a third embodiment includes an electrodialysis process 210, an electrolysis process 220, a first circulating process, and a hydrogen peroxide producing process 240.

The schematic view of the method for producing an acidic aqueous solution according to the third embodiment is as shown in Fig. 12.

[0120]

[Hydrogen peroxide producing process]

The hydrogen peroxide producing process 240 is a process of electrolyzing a part of electrodialysis concentrated water to produce hydrogen peroxide.

10 [0121]

The hydrogen peroxide producing process can be performed using, for example, the above hydrogen peroxide producing device.

When the hydrogen peroxide is used in combination in, for example, in the UV treatment process in the final stage of drinking water production, an advanced oxidation process (AOP) proceeds, and contributes to improvement of water quality. In addition, if wastewater is treated with ozone, when an oxidation treatment with ozone becomes excessive, for example, hydrogen peroxide can also be used for decomposition of bromic acid produced by oxidation of bromide ions contained in the wastewater.

In addition, when a disinfection treatment with a sodium hypochlorite aqueous solution is performed, hydrogen peroxide can also be used when excess sodium hypochlorite is removed.

[0122]

In the method for producing an acidic aqueous solution according to the third embodiment described above, in addition to the effects of the method for producing an acidic aqueous solution according to the first embodiment described above, hydrogen

peroxide that is generally used in the wastewater treatment process can be produced on-site in the hydrogen peroxide producing device. In addition, when the produced hydrogen peroxide is added to treated water, the hydrogen peroxide can be used.

[0123]

5 <Method for producing acidic aqueous solution according to fourth embodiment>

A method for producing an acidic aqueous solution according to a fourth embodiment includes an electrodialysis process 210, an electrolysis process 220, a first circulating process, a sodium hypochlorite producing process 230, and a hydrogen peroxide producing process 240.

10 The schematic view of the method for producing an acidic aqueous solution according to the fourth embodiment is as shown in Fig. 13.

[0124]

In the method for producing an acidic aqueous solution according to the fourth embodiment, in addition to the effects of the method for producing an acidic aqueous solution according to the first embodiment described above, a sodium hypochlorite aqueous solution used as a disinfectant for treated water and hydrogen peroxide that is generally used in the wastewater treatment process can be produced on-site. In addition, the produced sodium hypochlorite aqueous solution and hydrogen peroxide can be used on-site.

20 [Examples]

[0125]

While the present invention will be described below in more detail with reference to examples, the present invention is not limited to these examples.

[0126]

25 ·Water to be treated

As water to be treated, acidic aqueous solutions of examples were produced using test water (referred to as simulated wastewater) containing various ion components (sodium ions, calcium ions, magnesium ions, chloride ions, bicarbonate ions, and silica) shown in Table 1.

5 [0127]

<Example 1>

An acidic aqueous solution was produced using the apparatus for producing an acidic aqueous solution including an electrodialyzer and an electrolyzer shown in Fig. 1.

[0128]

10 [Electrodialysis process]

In a small electrodialysis cell (S3 commercially available from ASTOM Corporation, 10 concentration chamber sections, an electrode area of 55 cm²) into which a monovalent ion perm-selective ion-exchange membrane was incorporated, the dilution chamber of the electrodialysis cell was filled with 8 L test water (of which the pH was
15 adjusted to 6.6 using hydrochloric acid obtained in the electrolysis process to be described below), the concentration chamber of the electrodialysis cell was filled with 0.5 L tap water, the flow rate of each chamber was fixed at 5 mL/min, and a voltage of 10 V was applied to perform an electrodialysis process.

As a result, the electrodialysis concentrated water and the electrodialysis diluted
20 water shown in Table 1 were obtained. Here, the current value was about 0.25 A.

[0129]

[Electrolysis process]

As the electrolyzer, a two-chamber electrolysis cell (the electrolysis area was 10 cm²) including a Ti mesh formed with a catalyst composed of Pt and Ir oxide as a
25 positive electrode (that is, the anode), a Ni mesh as a negative electrode (that is, the

cathode), and Y9201 (diaphragm: commercially available from Yuasa Membrane Systems Co., Ltd.) as a diaphragm and having a diaphragm with an inter-electrode distance of 2 mm was used.

The electro dialysis concentrated water was supplied to the anode chamber of the two-chamber electrolysis cell at a flow rate of 5 mL/min, and the electro dialysis concentrated water was supplied to the cathode chamber of the two-chamber electrolysis cell at a flow rate of 2.5 mL/min. Electrolysis was performed at a current density of 5 A/dm². The cell voltage was 6 V.

As a result, in the anode chamber of the two-chamber electrolysis cell, a 0.7 g/L hydrochloric acid shown as an acidic aqueous solution in Table 1 was obtained (pH 1.7). In addition, in the cathode chamber of the two-chamber electrolysis cell, a 4 g/L sodium hydroxide aqueous solution and a 2.5 g/L sodium carbonate aqueous solution shown as an alkaline aqueous solution in Table 1 were obtained (pH 12.8).

[0130]

[Method for measuring pH of raw water and various treated waters]

The pH of the raw water and various treated waters shown in Table 1 was a value of the pH measured at 25°C with a pH meter (D74, commercially available from HORIBA, Ltd.).

[0131]

[Method for measuring content of various ion components]

In the analysis method of the concentration of various ion components of raw water and various treated waters shown in Table 1 (that is, electro dialysis concentrated water, electro dialysis diluted water, an acidic aqueous solution, and an alkaline aqueous solution), the concentration of cations was a value measured using an emission

spectrophotometer (ICP-AES; SPS5520, commercially available from Seiko Instruments Inc.) using an argon gas ICP as a light source.

On the other hand, the concentration of anions was measured using an ion chromatography analyzer (ICA-2000; commercially available from DKK-TOA

5 Corporation).

[0132]

[Method for measuring amount of hydrochloric acid, sodium hydroxide aqueous solution, and sodium carbonate aqueous solution produced]

Hydrochloric acid was quantified with a sodium hydroxide aqueous solution
10 with a known concentration. The sodium hydroxide aqueous solution and the sodium carbonate aqueous solution were quantified by two-step titration with hydrochloric acid with a known concentration.

[0133]

[Table 1]

	Concentration	Na ⁺	Ca ²⁺	Mg ²⁺	Cl ⁻	HCO ₃ ⁻	SiO ₂	pH
Test water	[mg/L]	500	200	70	370	400	100	8
Electrodialysis concentrated water	[mg/L]	3,600	220	1	3,300	2,300	100	6.6
Electrodialysis diluted water	[mg/L]	280	190	70	160	290	100	6.6.
Acidic aqueous solution	[mg/L]	2,500	100	1	1,050	0	90	1.7
Alkaline aqueous solution	[mg/L]	5,900	350	2	3,300	2,300	100	12.8

15 [0134]

<Example 2>

An acidic aqueous solution was produced in the same method as in Example 1 except that, as the positive electrode (that is, the anode) of the electrolyzer (also referred

to as a two-chamber electrolysis cell), a hydrogen gas diffusion electrode in which a catalyst layer in which a Pt/C powder catalyst and a fluororesin solution were mixed was fixed on carbon paper at an amount of 1 mg/cm^2 with a hot press was used, and 1.2 times more hydrogen gas than a theoretical mixing amount for performing the electrolysis reaction was supplied to the gas chamber formed on the back side of the anode. The obtained amount of the hydrochloric acid and sodium hydroxide produced was about the same as in Example 1, but no free chlorine was produced.

[0135]

<Example 3>

10 An acidic aqueous solution was produced using the apparatus for producing an acidic aqueous solution including an electrodialyzer, an electrolyzer, and a hydrogen peroxide producing device shown in Fig. 7.

 The electrodialyzer and the electrodialysis process, and the electrolyzer and the electrolysis process were the same as in Example 1, a 0.7 g/L hydrochloric acid was
15 obtained in the anode chamber of the two-chamber electrolysis cell (pH 1.7). In addition, in the cathode chamber of the two-chamber electrolysis cell, 4 g/L sodium hydroxide, and 2.5 g/L sodium carbonate were obtained (pH 12.8).

[0136]

[Hydrogen peroxide producing process]

20 As the hydrogen peroxide producing device, a two-chamber electrolysis cell (the electrolysis area was 10 cm^2) including a Ti mesh formed with a catalyst composed of Pt and Ir oxide as a positive electrode (that is, the anode), an oxygen gas diffusion electrode in which a catalyst layer in which a graphite powder catalyst and a fluororesin solution were mixed was fixed on carbon paper at an amount of 10 mg/cm^2 with a hot press as a
25 negative electrode (that is, the cathode), and Y9201 (diaphragm: commercially available

from Yuasa Membrane Systems Co., Ltd.) as a diaphragm, and having a diaphragm with an inter-electrode distance of 2 mm was used.

The electrodialysis concentrated water was supplied to the anode chamber of the two-chamber electrolysis cell at a flow rate of 5 mL/min, and the electrodialysis

5 concentrated water was supplied to the cathode chamber of the two-chamber electrolysis cell at a flow rate of 2.5 mL/min. Electrolysis was performed at a current density of 5 A/dm². The cell voltage was 5.5 V.

As a result, 1.1 g/L hydrogen peroxide (as H₂O₂) was obtained.

[0137]

10 [Method for measuring amount of hydrogen peroxide produced]

When titanium sulfate was added to the hydrogen peroxide aqueous solution, a complex compound of hydrogen peroxide and titanium was formed, and the UV absorption spectrum of the complex compound was measured as the absorbance using UV-2550 (commercially available from Shimadzu Corporation), and thus the amount of

15 hydrogen peroxide produced was obtained.

[0138]

Here, the methods for measuring the pH and the amount of the acidic aqueous solution and the alkaline aqueous solution produced were the same as the measurement methods of Example 1 described above.

20 [0139]

<Comparative Example 1>

An acidic aqueous solution was produced in the same method as in Example 1 except that a small electrodialysis cell (S3 commercially available from ASTOM Corporation, 10 concentration chamber sections, an electrode area of 55 cm²) into which

25 a known ion-exchange membrane having no monovalent ion perm-selectivity was

incorporated in place of the monovalent ion perm-selective ion-exchange membrane was used.

As a result, the cell voltage sharply increased, and electrolysis could not be continued.

5 [0140]

In Examples 1 and 2, it was confirmed that the acidic aqueous solution for adjusting the pH of the wastewater supplied to the electrodialyzer could be produced on-site from the wastewater in the electrolyzer.

In addition, in Example 3, it was confirmed that, in addition to the acidic
10 aqueous solution, hydrogen peroxide could be produced on-site from the wastewater.
[0141]

On the other hand, it was confirmed that, when the electrodialyzer including an ion-exchange membrane having no monovalent ion perm-selectivity of Comparative Example 1 was used, a large amount of calcium and magnesium components were
15 precipitated on the cathode and the ion-exchange membrane having no monovalent ion perm-selectivity, and the acidic aqueous solution could not be continuously obtained.
[0142]

Thereby, it was confirmed that, according to the apparatus for producing an acidic aqueous solution and the method for producing an acidic aqueous solution using
20 these apparatuses according to the first to fourth embodiments, the acidic aqueous solution used in the wastewater treatment process could be produced and used on-site, and economic burden could be significantly reduced.

[Reference Signs List]

[0143]

25 100, 101, 102, 103 Apparatus for producing acidic aqueous solution

- 110, 111 Electrodialyzer
- 120 Electrolyzer
- 13 First circulator
- 121 Two-chamber electrolyzer
- 5 125 Three-chamber electrolyzer
- 130, 131 Sodium hypochlorite producing device
- 140, 141 Hydrogen peroxide producing device
- 210 Electrodialysis process
- 220 Electrolysis process
- 10 230 Sodium hypochlorite producing process
- 240 Hydrogen peroxide producing process

[0144]

- It will be appreciated that many further modifications and permutations of various aspects of the described embodiments are possible. Accordingly, the described aspects
- 15 are intended to embrace all such alterations, modifications, and variations that fall within the spirit and scope of the appended claims.

[0145]

- The reference in this specification to any prior publication (or information derived from it), or to any matter which is known, is not, and should not be taken as an
- 20 acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge in the field of endeavour to which this specification relates.

[CLAIMS]

[Claim 1]

An apparatus for producing an acidic aqueous solution, the apparatus comprising:

5 an electrodialyzer that has a monovalent ion perm-selective ion-exchange membrane and separates wastewater containing chloride ions and alkali metal ions into electrodialysis concentrated water and electrodialysis diluted water by an electrodialysis treatment;

 an electrolyzer that electrolyzes the electrodialysis concentrated water to
10 produce an acidic aqueous solution;

 a first circulator that circulates at least some of the acidic aqueous solution to the wastewater supplied to the electrodialyzer; and

 a second circulator that circulates at least some of the acidic aqueous solution to the electrolyzer,

15 wherein a cation-exchange membrane of the monovalent ion perm-selective ion-exchange membrane is a m-phenolsulfonic acid-phenolic resin, or a resin obtained by subjecting a styrene-divinylbenzene copolymer to a sulfonation reaction,

 a cationic polymer electrolyte containing a polyethyleneimine is formed on a surface of the cation-exchange membrane, and

20 an anion-exchange membrane of the monovalent ion perm-selective ion-exchange membrane is an m-phenylenediamine-phenolic condensed resin, or a resin obtained by subjecting a styrene-divinylbenzene copolymer to an amination reaction.

[Claim 2]

The apparatus for producing an acidic aqueous solution according to claim 1,

25 wherein, in the electrolyzer, the anode is a hydrogen gas diffusion electrode.

[Claim 3]

The apparatus for producing an acidic aqueous solution according to claim 1 or 2, further comprising

a sodium hypochlorite producing device that electrolyzes a part of the
5 electro dialysis concentrated water to produce a sodium hypochlorite aqueous solution.

[Claim 4]

The apparatus for producing an acidic aqueous solution according to any one of claims 1 to 3, further comprising

a hydrogen peroxide producing device that electrolyzes a part of the
10 electro dialysis concentrated water to produce hydrogen peroxide.

[Claim 5]

The apparatus for producing an acidic aqueous solution according to any one of claims 1 to 4,

wherein the electro dialyzer performs the electro dialysis treatment on the
15 wastewater in which the concentration of the chloride ions is 0.01 mg/L or more.

[Claim 6]

The apparatus for producing an acidic aqueous solution according to any one of claims 1 to 5,

wherein the electro dialyzer performs the electro dialysis treatment on the
20 wastewater in which the concentration of the alkali metal ions is 0.01 mg/L or more.

[Claim 7]

The apparatus for producing an acidic aqueous solution according to claim 2,
wherein the anode includes a conductive metal substrate and a catalyst layer.

[Claim 8]

25 The apparatus for producing an acidic aqueous solution according to claim 7,

wherein the thickness of the conductive metal substrate is 0.05 to 5 mm.

[Claim 9]

The apparatus for producing an acidic aqueous solution according to claim 7 or

8,

5 wherein the thickness of the catalyst layer is 0.1 to 100 μm .

[Claim 10]

The apparatus for producing an acidic aqueous solution according to any one of claims 7 to 9,

wherein the porosity of the anode is 10 to 95%.

10 [Claim 11]

The apparatus for producing an acidic aqueous solution according to any one of claims 7 to 10,

wherein the anode further includes an underlayer made of a valve metal base alloy containing tantalum and titanium components between the conductive metal
15 substrate and the catalyst layer.

[Claim 12]

The apparatus for producing an acidic aqueous solution according to claim 3,

wherein a discharge pipe for the sodium hypochlorite aqueous solution produced by the sodium hypochlorite producing device is connected to a discharge pipe for the
20 wastewater.

[Claim 13]

The apparatus for producing an acidic aqueous solution according to claim 1,

wherein, in the electrolyzer, a cathode is an oxygen gas diffusion electrode.

[Claim 14]

25 The apparatus for producing an acidic aqueous solution according to claim 4,

wherein a discharge pipe for the hydrogen peroxide produced by the hydrogen peroxide producing device is connected to a discharge pipe for the wastewater.

[Claim 15]

A method for producing an acidic aqueous solution from wastewater containing
5 chloride ions and alkali metal ions, the method, comprising:

an electrodialysis process in which the wastewater is separated, by using an electrodialyzer including a monovalent ion perm-selective ion-exchange membrane, into electrodialysis concentrated water and electrodialysis diluted water by an electrodialysis treatment;

10 an electrolysis process in which the electrodialysis concentrated water is electrolyzed to produce an acidic aqueous solution;

a first circulating process in which at least some of the acidic aqueous solution is circulated to the wastewater supplied in the electrodialysis process; and

a second circulating process in which at least some of the acidic aqueous
15 solution is used in the electrolysis process,

wherein a cation-exchange membrane of the monovalent ion perm-selective ion-exchange membrane is a m-phenolsulfonic acid-phenolic resin, or a resin obtained by subjecting a styrene-divinylbenzene copolymer to a sulfonation reaction,

a cationic polymer electrolyte containing a polyethyleneimine is formed on a
20 surface of the cation-exchange membrane, and

an anion-exchange membrane of the monovalent ion perm-selective ion-exchange membrane is an m-phenylenediamine-phenolic condensed resin, or a resin obtained by subjecting a styrene-divinylbenzene copolymer to an amination reaction.

25 [Claim 16]

The method for producing an acidic aqueous solution according to claim 15 or 16,

wherein the electrolysis process is performed by a hydrogen oxidation reaction.

[Claim 17]

5 The method for producing an acidic aqueous solution according to claim 15 or 16, further comprising

a sodium hypochlorite producing process in which a part of the electrodialysis concentrated water is electrolyzed to produce a sodium hypochlorite aqueous solution.

[Claim 18]

10 The method for producing an acidic aqueous solution according to any one of claims 15 to 17, further comprising

hydrogen peroxide producing process in which a part of the electrodialysis concentrated water is electrolyzed to produce hydrogen peroxide.