




- (51) International Patent Classification:
E21B 19/16 (2006.01)
- (21) International Application Number:
PCT/US2012/058001
- (22) International Filing Date:
28 September 2012 (28.09.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/540,763 29 September 2011 (29.09.2011) US
- (71) Applicant (for all designated States except US): **NATIONAL OILWELL VARCO NORWAY AS** [NO/NO]; Serviceboks 401, N-4604 Kristiansand S (NO).
- (71) Applicant (for MW only): **FALESKI, Thaddeus, J.** [US/US]; Conley Rose, P.C., 1001 McKinney, Suite 1800, Houston, TX 77002 (US).
- (72) Inventors; and
- (71) Applicants (for US only): **ROSANO, Hugo, Leonardo** [MX/NO]; Hoietun 51, N-4619 Mosby (NO). **DRZEWIECKI, Lopek** [CA/CA]; 13915-115A Avenue, Edmonton, alberta T5M 3C2 (CA).
- (74) Agent: **FALESKI, Thaddeus J.**; Conley Rose, P.C., 1001 McKinney, Suite 1800, Houston, TX 77002 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

[Continued on next page]

(54) Title: SIMULTANEOUS CLAMP AND TORQUE DRIVE



(57) Abstract: A clamping system (210) for making and breaking threaded connections between a first tubular and a second tubular comprises a clamp assembly- The clamp assembly includes a first cam gear (220), a first plurality of clamp members (240) disposed within the first cam gear, and a torque gear (250). Each clamp member is pivotally coupled to the torque gear. Each clamp member is configured to pivot between a withdraw position radially spaced apart from the first tubular and a gripping position engaging the first tubular. In addition, the clamping system comprises a clamp actuator. The clamp actuator includes a mounting shaft (264), a first clamp drive gear (280x) rotatably coupled to the mounting shaft, and a torque drive gear (280y) rotatably coupled to the mounting shaft. The first clamp drive gear is configured to rotate the first cam gear and the torque drive gear is configured to rotate the torque gear.



(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (*Art. 21(3)*)
- with amended claims (*Art. 19(1)*)

(88) Date of publication of the international search report:

19 December 2013

Date of publication of the amended claims: 20 February 2014