

TITLE OF THE INVENTION:
ADVANCED METHODS AND DESIGNS FOR BALANCING
A STRANDED TERMINATION ASSEMBLY

Patent Application of
Richard V. Campbell

CROSS-REFERENCES TO RELATED APPLICATIONS

This non-provisional patent application claims the benefit of an earlier-filed provisional application. The first provisional application was assigned serial number 61/984,830. It listed the same inventor.

**STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR
DEVELOPMENT**

Not Applicable.

MICROFICHE APPENDIX

Not Applicable

DESCRIPTION

Title of the Invention: Advanced Methods and Designs for Balancing a Stranded Termination Assembly

1. Technical Field.

5 This invention relates to the field of tensile strength members such as multi-stranded synthetic cables. More specifically, the invention comprises devices and methods for balancing the load carried by a synthetic cable among its constituent strands.

2. Background Art.

10 A cable must generally be provided with one or more end connections in order to be useful. The end connections allow the cable to carry and transmit a useful load. An end connection may be a simple device – such as a large hook – employed to connect the cable to an anchoring point. Larger synthetic cables typically include multiple constituent strands. It is preferable to attach an individual connective device to each strand. Such a connective device is referred to in this disclosure as a “strand termination.” Multiple strand terminations are
15 connected together somehow to create a unified cable end connection. The unified cable end connection is referred to in this disclosure as an “overall cable termination.”

For small cables simple end-fittings work fairly well. For larger cables, however, more complicated end-fittings are needed in order to produce acceptable break strength. This is particularly true for large, multi-stranded cables made of synthetic filaments (having diameters
20 of 20 mm or more). FIG. 1 shows a cable 10 made from advanced high-strength synthetic filaments. Some terminology used in the construction of cables will benefit the reader’s understanding, though it is important to know that the terminology varies within the industry. For purposes of this patent application, the smallest individual component of the cable is known as a “filament.” A filament is often created by an extrusion process (though others are used).
25 Many filaments are grouped together to create a strand 12. The filaments are braided and/or twisted together using a variety of known techniques in order to create a cohesive strand. There may also be sub-groups of filaments within each strand. As the overall cable size gets larger, more and more layers of filament organization will typically be added. The strands 12 are

typically braided and/or twisted together to form cable 10. In other examples the strands may be
30 purely parallel and encased in individual surrounding jackets. In still other examples the strands
may be arranged in a “cable lay” pattern that is well known in the fabrication of wire ropes.

Many different materials are used for the filaments in a synthetic cable. These include
DYNEEMA, SPECTRA, TECHNORA, TWARON, KEVLAR, VECTRAN, PBO, carbon fiber,
nano-tubes, and glass fiber (among many others). In general the individual filaments have a
35 thickness that is less than that of human hair. The filaments are very strong in tension, but they
are not very rigid. They also tend to have low surface friction. These facts make such synthetic
filaments difficult to handle during the process of adding a termination and difficult to organize.
The present invention is particularly applicable to terminations made of such high-strength
synthetic filaments, for reasons which will be explained in the descriptive text to follow. While
40 the invention could in theory be applied to older cable technologies – such as wire rope – it likely
would offer little advantage and the additional time and expense of implementing the invention
would not be worthwhile. Thus, the invention is not really applicable to wire rope and other
similar cables made of very stiff elements.

The cable shown in FIG. 1 is a well-known exemplary construction made by braiding or
45 otherwise interrelating twelve strands together. Polyester ropes using this construction are
known to have an external diameter up to about 6 inches (see specification MIL-R-24750). Even
larger polyester ropes are made by constricting parallel sub-ropes in a braided-strand jacket.

When a cable has non-parallel strands the interrelationship between the strands becomes
quite complex. The overall cable has a central axis. Each individual strand is on average
50 running parallel to the cable’s central axis. However, at any given point along the cable’s length,
no individual strand is parallel to the cable’s central axis. When such a cable is loaded, the
individual strands move and shift. The cable “clinches” together and strand-to-strand friction
becomes a significant component of the cable’s performance. When a large amount of tension is
applied to such a cable in its initial post-manufacturing state, it is known for the cable’s diameter
55 to shrink by up to 30%. The individual strands must slip over one another and settle into a stable
configuration.

It is important for the overall strength of most cables - the 12-strand configuration of FIG. 1 being a good example - that the overall load be shared equally among the constituent strands. For a 12-strand construction, the ideal result is that each strand carries exactly 1/12 of the total load. Other cables may have a desired non-equal tension distribution, such as a cable having some relatively large strands and other relatively small strands. However, in all cases, it is preferable to have a "target" distribution of tension among the constituent strands and to provide a system that meets this target distribution.

High-strength synthetic filaments have very little surface friction and strands made of these filaments also have very little surface friction. Thus, it is possible for one individual strand to "slip" with respect to neighboring strands. A strand that slips tends to "unload" itself and shift the load it was carrying to its neighbors. This is obviously an undesirable result.

In order to add an overall cable termination to an end of a multi-stranded synthetic cable, each individual strand must be cut to length and have a strand termination added (It is not essential that all strands in the cable undergo this process but in most embodiments all strands will be involved). The cutting and terminating processes are inherently imperfect. The result will generally be that some terminated strands will wind up being longer than desired while others will wind up being shorter than desired. If a tensile load is placed on the cable with no accommodation for these manufacturing tolerances, the relatively "short" strands will be loaded first and they will carry more load than the relatively long strands.

One approach to reducing this problem is to make the application of a tensile load to each strand individually adjustable. In order to achieve this goal a tension-applying apparatus may be applied to each strand termination individually. Looking again at FIG. 1, the reader will note how the strands on the free end of cable 10 have been unbraided so that they are individually accessible.

FIG. 2 shows a section view through a strand termination 30 that has been added to the free end of an individual strand 12. The prior art approaches to adding a termination are explained in detail in commonly-owned U.S. Patent Nos. 7,237,336, 7,669,294, 8,048,357, 8,236, 219, and 8, 371,015, which are hereby incorporated by reference. These prior patents

85 generally concern potted terminations, but as discussed previously the invention applies to all types of termination.

FIG. 2 shows a sectional view through the components used to create the termination. The reader will note that anchor 18 includes an expanding cavity 20 that expands as one proceeds from the portion of the anchor facing the length of cable (the “proximal” end, which is the bottom end in the orientation of the view) toward the portion of the anchor facing in the opposite direction (the “distal” end, which is the top end in the orientation of the view). The expanding cavity in this example is a linear taper between two straight portions – all joined by fillets. Differing wall profiles may be used to create a wide variety of expanding cavities.

The end portion of strand 12 is potted into the expanding cavity in order to lock anchor 18 to strand 12. The filaments of the strand are splayed apart and infused with liquid potting compound (either before or after being placed within expanding cavity 22). The liquid potting compound may be added by a variety of methods, including: (1) “painting” or otherwise wetting the filaments with potting compound and then sliding the anchor into position over the painted filaments, (2) positioning the splayed filaments in the cavity and then pouring in potting compound, (3) pre-wetting the filaments in a separate mold designed to wet the filaments, and (4) injecting pressurized potting compound into the cavity. However the potting compound is introduced, the splayed filaments remain within cavity 20 while the potting compound hardens. Once it has hardened the result is a mechanical interlock between the filament-reinforced “plug” (contained in potted region 22) of solid material and the cavity. Tension applied to the cable will thereby be transmitted to the strand.

The potting compound used is typically a high-strength resin. However, the term “potting compound” as used in this description means any substance which transitions from a liquid to a solid over time.

Potting is only one approach known in the art. Other common examples include “spike-and-cone” or “spike-and-barrel” designs, compression or friction fittings, composite-connections, capstan wrapping, etc. The most common approach is wrapping a length of filaments around an eye on the end of the strand and splicing a length of the strand back into

itself – typically referred to as a “spliced eye.” The present invention is applicable to any method of creating a termination on the end of a synthetic filament tensile member. Although
115 potted examples are shown in these descriptions the invention is not limited to that approach, and the reader should understand the term “strand termination” to broadly encompass all methods of attaching a device to the end of a strand.

FIG. 2 shows additional components that are added to facilitate the gathering of multiple strands into a single, load-transferring element. In the example shown, loading stud 24 has been
120 connected to anchor 18 via threaded engagement 28. Loading stud 24 includes male thread 26 over a significant length (The threads are shown schematically but are not actually depicted for purposes of visual clarity). This threaded stud allows the completed assembly to be attached to other things to ultimately create an overall cable termination.

The use of a threaded stud is a “high-end” example. In other instances the anchor will
125 simply be a cylinder with a load-bearing flange facing downward in the orientation of FIG. 2. The connection between the cylinder and another object could then be placing the load-bearing flange against another surface.

FIG. 3 shows the cable after an identical (in this example) strand termination 30 has been added to the end of each strand 12. The reader will observe how a length of each strand is
130 preferably unbraided from the cable structure so that a free length exists proximate the termination. This allows each strand to be manipulated so that it may be attached to another device. A separate device or devices is used to aggregate all the individual strands and strand terminations to a unified load-transferring assembly. This unified assembly will be referred to as an “overall cable termination” in order to distinguish it from the individual “strand terminations”
135 applied to each strand. The design of the strand terminations, the overall cable termination, and the unifying devices employed to create the overall cable termination, can take on many and various forms. The present invention is applicable to all of these forms.

As stated previously, it is ideal for each strand within a cable assembly to carry an equal percentage of the total load (other than for cables designed to distribute the load unequally).
140 However, when a cable made of synthetic filaments is first terminated and loaded, the

manufacturing tolerances will generally cause some strands to shift or “slip” relative to others – thereby altering the proportional load sharing that was intended. The present invention loads the cable in a controlled and carefully designed manner resulting in a reduction in misalignments and a more evenly distributed load among the cable’s constituent strands.

145 Throughout this disclosure cables will be used as an example of a tensile strength member. However the invention should not be viewed as being limited to cables. The term “tensile strength member” or “tensile member” encompasses cables and sub-components of cables such as strands. The invention also encompasses non-cable structures intended to carry loads in tension.

150 Likewise, the term “anchor” should be viewed broadly to encompass virtually anything that can be attached to a strand or cable. The anchor would ordinarily include some features facilitating attachment – such as a hook or threads.

SUMMARY OF INVENTION

155 The present invention comprises devices and methods for loading a cable in order to create a desired distribution of the load among the cable’s constituent strands. Strand terminations are applied to many – and possibly all of – the cable’s strands. The ultimate goal is to connect the strand terminations to a collector in order to create an overall cable termination. The relationship between each strand termination and the collector is allowed to “float” using the
160 inventive process while the cable is tensioned and an appropriate spatial relationship between each strand tensioner and the collector is determined. Once the appropriate relationship is found, it is configured to be repeatable (such as by locking the strand termination in place or by recording its position for later application to the same or similar collector).

 In a preferred embodiment, a strand tensioner is provided for each individual strand
165 termination. Tension is applied to the cable through the strand tensioners. Tension may be individually adjusted for each strand (up or down) in order to achieve a predetermined apportionment of the overall load.

BRIEF DESCRIPTION OF DRAWINGS

170 FIG. 1 is an elevation view, showing the braided structure of an exemplary 12-strand cable.

 FIG. 2 is a sectional view, showing a termination created on the end of a single cable strand.

175 FIG. 3 is a perspective view, showing 12 terminations attached to 12 strands in an exemplary cable.

 FIG. 4 is a perspective view, Showing a collector used to assemble the 12 terminations of FIG. 3.

 FIG. 5 is a sectional perspective view, showing an exemplary attachment between a termination and a collector.

180 FIG. 6 is a perspective view, showing all 12 terminations attached to the collector.

 FIG. 7 is a perspective view, showing a particular type of strand tensioner.

 FIG. 8 is a side elevation view, showing an assembly used to apply loads to all the strands in a cable assembly in a controlled fashion.

 FIG. 9 is a plot of strand displacement and applied tension over time.

185 FIG. 10 is a plot of strand displacement and applied tension over time.

 FIG. 11 is a plot of strand displacement and applied tension over time.

 FIG. 12 is a plot of strand displacement over time for multiple strands.

 FIG. 13 is a side elevation view, showing an assembly used to apply loads to all the strands in a cable assembly in a controlled fashion.

190 FIG. 14 is a detailed perspective view, showing a rotation-limiting feature.

 FIG. 15 is a detailed perspective view, showing an alternate embodiment for a strand tensioner.

 FIG. 16 is a detailed perspective view, showing an alternate embodiment for a strand tensioner.

195 FIG. 17 is a sectional elevation view, showing the use of a load cell to monitor individual strand loading.

REFERENCE NUMERALS IN THE DRAWINGS

200	10	cable
	12	strand
	18	anchor
	20	cavity
	22	potted region
205	24	loading stud
	26	male thread
	28	threaded engagement
	30	termination
	34	collector
210	36	loading flange
	38	receiver
	40	nut
	42	washer
	44	hemi bearing
215	46	opening
	48	coupler
	50	strand tensioner
	52	cylinder
	54	mount
220	56	rod
	58	fixture
	60	pressure controller/sensor
	62	process controller
	64	fixture

225	66	space frame
	68	collector brace
	70	primary load fixture
	72	hydraulic cylinder
	74	attachment
230	76	boss
	78	hole
	80	lock wire
	82	cross hole
	84	castellated nut
235	86	notch
	88	strand tensioner
	90	telescoping clevis
	92	flat
	94	load cell
240	96	wiring

DESCRIPTION OF EMBODIMENTS

FIG. 4 shows an exemplary device used to gather all the strands into a unified whole and thereby create an overall cable termination. Collector 34 includes twelve receivers 38, each of which is configured to connect to a single strand termination (In other embodiments a receiver may be configured to connect to multiple strand terminations). Collector 34 typically includes some type of load-transferring feature designed to transfer a load from the collector to some external element. Loading flange 36 is a simple example of a load-transferring feature. The collector in this example is very simplistic and is unlikely to represent a design that would actually be used. However, it does serve well to clearly illustrate the inventive features.

FIG. 5 shows an exemplary connection between a termination on a strand and the collector. Loading stud 24 is passed through opening 46 and through receiver 38 in collector 34. Receiver 38 includes a hemispherical concave portion sized to accept hemi bearing 44. Hemi bearing 44 and receiver 38 form a ball-and-socket connection that allows the termination to rotate with respect to collector 34. This is a sophisticated type of connection that won't be included in many embodiments. Many embodiments will simply use a washer bearing against a flat surface on collector 34. Still other embodiments won't use a threaded stud and will instead simply mate two surfaces together to make the connection.

Nut 40 can be selectively tightened on loading stud 24 (the threads are not shown in the view) in order to urge washer 42 against hemi bearing 44 and hemi bearing 44 against receiver 38. To apply the inventive method, collector 34 is ordinarily placed in a loading fixture that holds it in position. The far end of the cable to which the strand belongs is likewise held in place (such as by winding it around a capstan or some other means, such as applying an overall cable termination to the far end). A substantial tensile load is then applied to the cable as a whole. Those skilled in the art will then appreciate that by tightening or loosening nut 40 a user can fine tune the tension on the particular strand to which loading stud 24 is attached (as well as its position with respect to collector 34). The ball-and-socket connection in this embodiment allows the strand termination to align itself with the strand during this process.

FIG. 6 shows an assembly of collector 34 and all twelve strands. The reader will observe that twelve loading studs 24 are in position and a nut 40 is connected to each stud (The loading studs 24 shown in FIG. 6 are longer than depicted in FIG. 5 in order to give an additional range of adjustment. Also – the threads on the exterior surface of the loading studs are again omitted for purposes of visual clarity). This view illustrates the advantage of including a ball-and-socket connection in some of the embodiments. As each strand emerges from the cable's braided construction it assumes a particular angle with respect to the collector. Some diverge more than others, and the ball-and-socket connection accommodates this divergence. Of course, one could carefully determine a fixed angle to use for each strand. However, this is difficult as cable construction varies even within the same braiding scheme.

280 The ball-and-socket connection should properly be viewed as one example among many possible connection types. The reader is referred to commonly-owned U.S. Patent No. 8,371,015 for additional examples regarding the application of an attachment to a sub-component of a larger cable.

285 The term “collector” in this context should be viewed broadly as anything that is used to collect a tensile load from two or more strand terminations. It may be a unified piece as shown but may also be an assembly of multiple pieces. Further, a “stand-in” collector may be used to pre-load the cable and adjust each of the strand terminations (as described subsequently) and the strand terminations may ultimately be connected to an entirely different collector.

290 It is not common for a user to take an assembly for a large cable such as shown in FIG. 6 and place it into service without pre-loading the assembly and testing it. It is important to pre-load the assembly to settle the strands and other components into a stable configuration before the cable is placed into service. In this context it is desirable to know a particular cable’s maximum working load in the service environment it is destined to enter. The pre-load process might apply a tension to the cable that is equal to 100% or even as much as 150% of the expected maximum working load.

300 While most large cables are pre-loaded as a whole, the present invention seeks to pre-load the cable at the strand level and manipulate the strand termination to collector connections in order to create a desired apportionment of the overall load among the constituent strands. Without careful preloading a large cable assembly will very likely have an uneven distribution of load to each individual strand. The inventive process significantly reduces this phenomenon.

One could use the configuration of FIG. 6 to progressively tighten all twelve nuts and thereby place an initial load on the cable. Such a process would be unlikely to produce an optimal result, however. The present invention obtains advantages by individually applying tension to the strands in a large, multi-stranded cable.

305 FIG. 13 shows an exemplary apparatus that can be used to apply the desired pre-load to a cable. Fixture 58 holds collector 34 in place via collector brace 68. This fixture includes a central passage through which cable 10 freely passes. The far end of cable 10 (not shown) must

be held statically, such as by winding it around a capstan or providing a second collector on the far end.

310 Collector 34 is held within fixture 58 during the tensioning process. Significantly, however, it is not generally used to apply any tension to the cable strands during the pre-loading process. During the process, each individual strand termination is allowed to float with respect to collector 34. Tension to the cable is actually applied directly through the strand terminations themselves (as will be described subsequently). As tension is applied, the inventive components
315 operate to apportion the overall load among the individual strands in a predetermined arrangement (usually this will be an equal load applied to each strand but there are exceptions). Once the desired pre-load is applied and the strand terminations are adjusted to achieve the desired load apportionment, then the relationship between each strand termination and the collector is established (such as by locking the strand termination to the collector in the desired
320 position or by recording the desired position so that it can later be reestablished).

 In the embodiment of FIG. 13, collector 34, fixture 58, space frames 66, fixture 64, and all the connected components move in unison. This entire assembly may slide within a larger frame or otherwise be stabilized.

 In this exemplary apparatus one or more hydraulic cylinders 72 connect primary load
325 fixture 70 to attachment 74 on the moving assembly. The right side of the one or more hydraulic cylinders 72 (in the orientation of the view) is fixed to a substantial and stationary anchor point. When the one or more hydraulic cylinders 72 are activated, the moving assembly (along with collector 34) is urged to the right in the view. This action applies tension to cable 10 (since the far end of the cable is held).

330 The frame structures shown are preferably very stout so that a large tensile load may be applied. For some cables it may be desirable to provide a tensile load of 1 million pounds or more.

 Simply applying a defined pre-load using a common “pull” for the entire cable will rarely produce a desired apportionment of the overall load among the cable’s constituent strands. One
335 reason for this fact is that it is virtually impossible for all the strands of the cable to have exactly

the designed length. Returning to FIG. 3, the reader will recall that each individual strand must be cut to length and have a strand termination added to its free end. The manufacturing tolerances of both the cutting operation and the termination operator can only go so far. Some of the strands will wind up being shorter than designed and others will wind up being longer than designed. Of course, when the cable is initially placed under tension, the shorter strands will carry most of the load and the longer strands may in fact carry very little. For this reason, it is desirable to be able to adjust the position of each of the strand terminations with respect to the collector.

Looking now at FIG. 6, the reader will recall that the preferred connections between each strand termination and the collector include an adjustment feature. The adjustment feature in the embodiment of FIG. 6 is the nut 40 placed on each loading stud 24. These nuts can be tightened manually to provide the desired adjustment. There are many other ways to adjust the spatial relationship between a strand termination and the collector. However the adjustment is made, it is desirable to automate the process of apportioning the load among the various strands.

Returning now to FIG. 13, the reader will observe that each loading stud on each individual strand is attached to a strand tensioner 50. All the strand tensioners are attached to fixture 64. Thus, when the moving assembly is moved to the right under the force imparted by the one or more hydraulic cylinders 72, it is the strand tensioners (50) (in this particular embodiment) that actually apply the tension to the cable. The loading stud on each strand passes through the collector but should not transfer any significant forces to the collector. Instead, the loading stud is attached to its respective strand tensioner 50.

FIG. 7 shows an exemplary strand tensioner 50. This particular strand tensioner includes a hydraulic cylinder 52 with an extending/retracting rod 56. Coupler 48 is provided on the free end of the rod. The coupler in this example includes a female threaded hole configured to engage an individual loading stud 24. The coupler is threaded over the loading stud and a rotation-limiting device is then preferably applied. Exemplary rotation-limiting devices include a jam nut, a cross-pin, and aviation safety wire. The term “coupler” should be read broadly to

include any device able to transmit tension from a strand tensioner to a strand termination, and may include hooks, brackets, and many other types of devices.

365 The rotation limiting device prevents rotation between coupler 48 and loading stud 24 once the coupler is firmly attached to the loading stud. It is also preferable to limit rotation between rod 56 and cylinder 52. A keyway may be used to rotationally lock the rod and cylinder together. Mount 54 is provided to attach strand tensioner 50 to an external frame. One or more pivots may be provided on mount 54 so that the angle of strand tensioner 50 may be made
370 adjustable. Appropriate hydraulic connections are provided so that hydraulic pressure may be used to extend and retract rod 56 – if desired.

 In a preferred embodiment, strand tensioners 50 could be viewed as “passive” devices. In this embodiment, the hydraulic lines leading from each strand tensioner 50 are fed into a common, pressurized reservoir. The reservoir can be contained within pressure controller/sensor
375 60 (see FIG. 13). Returning to FIG. 7, the hydraulic cylinders within each strand tensioner 50 are double-acting cylinders for this example. The piston within each of these double-acting cylinders is preferably placed near the mid-point of its range of travel (midway between the two illustrated fluid ports).

 One could “plumb” the cylinders in different ways. Those skilled in the art will know
380 that double-acting hydraulic cylinders typically have two hydraulic ports – one on each extreme of the piston’s range of travel. The port that is used for the “retract” stroke (causing the rod to retract into the cylinder) is generally located near the rod end of the hydraulic cylinder. All the hydraulic lines leading from the retract ports in this example are connected to a common, pressurized hydraulic reservoir.

385 Returning to FIG. 13, when the one or more hydraulic cylinders 72 are pressurized to begin moving the fixture 64 and the strand tensioners 50 to the right (in the orientation of FIG. 13), the tension on the cable tends to pull the rods out of the hydraulic cylinders in the strand tensioners 50. This motion pressurizes the retract port on each of the cylinders within strand tensioners 50. In this embodiment, of course, all the retract ports are connected to a common,

390 pressurized hydraulic reservoir. As a result, the same pressure winds up being applied to each retract port.

The result is that the tension being applied to each individual strand must be equalized and the motion of the rods within the strand tensioners 50 ensures that this is the case without the need for any sophisticated active control. A simple operational example will make this point
395 clear. One of the strands in the assembly will draw taut first and this fact will cause the rod in the strand tensioner attached to that particular strand to start moving out of its cylinder. This will displace hydraulic fluid within that strand tensioner and cause that hydraulic fluid to be expelled out the retract port on the particular strand tensioner. The common reservoir is pressurized, so expelling fluid from one cylinder causes the same volume of fluid to be discharged into the other
400 cylinders. As a result, the rods in the other strand tensioners 50 actually retract a small distance until their attached strands draw taut.

Similar “equalization” displacements take place among all twelve strand tensioners 50. Some rods will extend outward through a small displacement stroke, other rods will retract through a small displacement stroke, and likely still others will not move much at all. This is
405 why it is a good idea to start the process with the pistons in the hydraulic cylinders within the strand tensioners near the middle of their range of travel, rather than at an extreme. The result is that by moving fixture 64 through a small displacement all strand tensioners 50 wind up with an equal amount of internal pressure in the hydraulic cylinders and all the connected strands wind up with the same amount of tension.

410 Returning now to FIG. 7, displacement sensor 64 may be provided to monitor the motion of the rod during the tensioning process. The tension actually being applied can be monitored by monitoring the hydraulic pressure applied to the cylinder.

Returning now to FIG. 13, some exemplary operations of the components will be described. This example is applying tension to a 12-strand cable. Thus, fixture 64 must provide
415 mounting attachment points for twelve strand tensioners 50. As may be seen, each strand tensioner is preferably mounted so that it will be parallel to the strand termination it will be connected to. Fixture 64 preferably includes features allowing the mounting position of each

strand tensioner to be adjusted as desired, though some embodiments may include fixed positions. The result in this example is a radial pattern of diverging strand tensioners. Several
420 space frames 66 are positioned to keep fixtures 58 and 64 in position so that the substantial tensile forces applied to the strands do not distort the assembly.

In some embodiments the strand tensioners may be remotely located, with the connection to the strand terminations being made with cables passing over pulleys. Other embodiments might use levers or other remote-mounting mechanisms. Thus, the construction shown is
425 properly viewed as exemplary.

Pressure controller/sensor 60 provides hydraulic pressure to each of the twelve strand tensioners. In many instances the same pressure will be fed to all tensioners, since this will ultimately produce a uniform tension among the strands. If a common pressure is desired, the prior example of simply plumbing all the retract ports on all the cylinders within strand
430 tensioners 50 to a common, pressurized reservoir may be used. However, in other instances it will be desirable to vary the pressure applied to each tensioner. Thus, pressure controller 60 may be configured to independently apply pressure to each cylinder and to monitor and maintain a selected pressure for each cylinder. This may be desirable for cable lay constructions, where a higher tension may be applied to the inner strands than the outer strands.

435 Process controller 62 preferably receives information regarding the translation of each cable strand (via an input such as displacement sensor 64) and the tension applied to each strand. Strand tension may be derived from the pressure applied to each strand tensioner or via some other source – such as a load cell or strain gage placed on the strand termination or on the strand tensioner.

440 In a representative pre-load operation, pressure would be applied to one or more hydraulic cylinders 72 to pull the slack out of the cable and apply increasing tension. Hydraulic pressure will then be created within the strand tensioners 50 as the load is transferred from fixture 64 to cable 10. In a simple version, a slow “ramp up” of even hydraulic pressure could be applied by the one or more hydraulic cylinders 72. If the overall concept is to apply a balanced
445 load among all the strands, then applying uniform pressure to all the cylinders will cause some

loading studs 24 to be pulled further through collector 34 than others (since the longer strands will still have more slack needing to be pulled out, in this example).

Once a uniform tension in all strands has been achieved and the desired total tension has been achieved, the relative position between each strand termination and the collector should be
450 locked in place so that the strands don't shift significantly when the pre-load is removed. Any suitable locking mechanism can be used. For the example of FIG. 6, one would simply apply a uniform amount of torque to each of the nuts 40 while the strand tensioners 50 maintain tension on the strands.

More generally, the invention seeks to preserve the proper spatial relationship between
455 each strand termination and the collector, so that the proper relationship can be recreated when the cable is put into use. One way to preserve this relationship is mechanically locking the strand terminations in the position determined to be correct during the preloading process. There are certainly other ways, however. One could, for example, accurately measure and record the spatial relationship between each strand termination and the collector without mechanically
460 locking the strand terminations in position. Later, the correct spatial relationship would be recreated by adjusting each strand termination until it repeated the previously taken measurements. This could be done with the same collector used in the pre-load process. It could also be done with another substitute collector. For example, the collector used in the pre-load process might be a modular assembly intended only for the taking of accurate measurements and
465 not for field use. It might be equipped with expensive position sensors that one would not wish to install in the field.

As stated previously, cables using synthetic filaments tend to have relatively little surface friction. Thus, if one does not load a stranded termination carefully it is possible for one strand to slip relative to the others in a direction that is roughly parallel to the cable's central axis (a
470 "longitudinal slip"). Once such a slip occurs it is difficult to detect and in many instances impossible or impractical to correct. As an example, a particular cable might be 100 meters in length. A longitudinal slip can occur anywhere along the cable's length where there is an imbalance in tension. Such a slip is not generally an issue within the cable itself. However, a

slip near one of the cable's terminated ends can be a significant problem. The slip produces a localized disturbance in the cable's structure. This will nearly always cause a weakness at the point of the slip and an overall reduction in the cable's breaking strength. Even if one balances the strand tensions at the ends of the cable after such a slip, the internal disturbance in the cable's structure will compromise its performance. Perhaps more significantly, the compromise in performance may not be detectable without actually testing the cable to the breaking point.

So long as the strands are initially loaded in a controlled manner, holding the tension on the individual strands reasonably even, the region where the strands transition from the free cable structure to the collector should stay reasonably balanced. The goal is primarily the prevention of a slip. The approach is to carefully control and regulate the tension applied to each individual strand so that no significant imbalance occurs. In the absence of an imbalance a slip is unlikely.

In an open-loop embodiment of the inventive process, one can apply a stepped increase in tension. For example, one may apply a tensile load of 1% of the anticipated ultimate break strength, check for the tension of the strands, then move up to a 5% load, recheck, then move up to a 10% load, and so on. Automated strand adjustment can allow for continuous tension to be maintained on the cable.

Consistency and repeatability are very important in the cable industry – particularly where the cables carry large loads. The present invention seeks to pre-load the cable and adjust each strand termination to the appropriate spatial relationship with the collector without producing a longitudinal slip. In a closed-loop embodiment, strand tension and/or position can be monitored and fed to a process controller that automatically adjusts the tension applied to each strand. The loading process is preferably modified in real time in the event that unwanted slippage is detected.

The reader should understand that some minimal slippage is inherent in the preloading process. It can likely never be eliminated altogether. But, it is possible by using the present invention to eliminate large-scale damaging slips. One approach is to simultaneously apply tension through all twelve of the loading studs shown in FIG. 6 and to apply that tension in a controlled fashion.

It is generally important to control the rotation of the strand during loading. Since the strand itself almost always has some type of twisted construction (such as braided or wound) rotation is highly related to tension. Thus, it is preferable to apply tension to a strand without
 505 allowing it to rotate. Further, once the tensioning process is complete, it is preferable to limit rotation between the strand and the collector. Otherwise the strand may “unwind” itself.

In an exemplary implementation of the closed-loop embodiment, a strand tensioner 50 (as described previously) is provided for each strand in a cable. FIG. 13 illustrates one possible fixturing arrangement. The reader will recall that collector 34 is simply held in place during the
 510 tensioning process. The strands pass through the collector but should not transfer any significant forces to the collector as the strand tensioners go to work. Process controller 62 preferably receives information regarding the translation of each cable strand (via an input such as displacement sensor 64) and the tension applied to each strand. Strand tension may be derived from the pressure applied to each hydraulic cylinder or via some other source – such as a load
 515 cell or strain gage placed on the strand termination or on the strand tensioner.

In the closed-loop embodiments, process controller 62 ideally includes a processor running a control program. This allows a prescribed “ramp up” of strand tension. However, the process need not be a fixed one but is more preferably an adaptive process that changes according to the sensor values. FIGs. 9 – 12 illustrate several examples of operation for the
 520 device of FIG. 8. The reader should bear in mind, however, that the operational configurations are virtually limitless and so the examples provided should not be viewed as limiting.

FIG. 9 shows an example where tension is steadily raised on all strands at the same time (though only a single strand is plotted). The upper plot shows the linear displacement of the termination affixed to “Strand 1.” The lower plot shows the tension applied to the same “Strand
 525 1.”

The first part of the curve is non-linear and represents the initial removal of slack. Once the slack is removed, displacement is roughly a linear function of applied tension. This continues up through Point A. At point A, Strand 1 experiences a significant longitudinal slip. The rate of displacement suddenly increases in a non-linear fashion. At the same instant the

530 tension applied actually falls (Point A' on the lower plot). The decrease in tension results from the fact that the strand-to-strand friction has transitioned from a static mode to a dynamic mode.

The substantial slip continues until Point B, when Strand 1 stops slipping with respect to its neighbors and resumes elastic elongation. At this point the tension in Strand 1 also returns to a linear relationship (Point B' in the lower plot). FIG. 9 represents an "open loop" scenario where
535 tension is ramped up at a fixed rate and no slip detection is included.

However, it may be possible to detect and prevent significant longitudinal slips using the information available in FIG. 9. The slope of the displacement curve (dy/dx) should remain fairly constant in the absence of a significant slip. By monitoring the rate of change of this slope (d^2y/dx^2) the control system can detect a sudden slope increase – which strongly suggests the
540 onset of a slip.

FIG. 10 illustrates this scenario. At Point A in the upper plot process controller 62 detects the onset of a potentially damaging slip. The controller immediately reduces the applied tension on Strand 1 (see lower plot) so that a smooth displacement is maintained. Tension continues to be ramped up on the other strands within the cable. The increase in tension on the
545 other strands will tend to "re-clench" the previously slipping Strand 1 (recall the complex braided structure shown in FIG. 1).

Once the controller determines that the slip is under control (such as by monitoring the rate of change of the displacement plot slope, among other methods) tension on Strand 1 is ramped back up (shown as Points B and B'). A normal increase is then continued unless
550 another slip is detected.

In some instances a slip may occur so quickly that the tensioning apparatus cannot respond rapidly enough. In those cases the best approach will be to regulate the tension applied to each strand in such a fashion as to prevent the slip to begin with. If the displacement sensors then detect a slip, this information may still be useful because it informs the operator that the
555 cable contains a significant defect and it may no longer be possible to use it in its intended application.

Of course, there are many tension-increasing profiles that are non-linear. In some cable constructions it is advantageous to pulse the application of tension. FIG. 11 shows a plot depicting this type of “ramp up.” Again, the plot shows only one strand in a 12-strand cable, but the plots for the other eleven strands would be similar (in the absence of a slip). Slack is removed and tension is ramped up until Point A. Tension is then stepped down to a low level and a low-tension interval (from Point A to Point B) is maintained so that the cable structure can stabilize.

At Point B tension is again applied and increased. Another “rest” interval commences at Point C and continues to Point D. This process continues until a desired amount of pre-load has been applied to the cable.

FIG. 12 shows a combined plot of displacement versus time for all twelve strands in a 12-strand braided cable. The process controller typically measures and compares the values for all the cable strands as the tensioning process proceeds. Another effective slip detection method is to “scan” for one strand passing too far outside the average for all the strands. In the plot of FIG. 12 one strand (Strand 3) has experienced a substantial longitudinal slip and its displacement has suddenly progressed rapidly beyond that of the other strands. When this condition is detected the controller can reduce the tension on Strand 3 and allow the cable to stabilize as the tension on the other strands is increased.

FIG. 8 shows a simplified alternate tensioning fixture. In this embodiment fixture 58 and fixture 64 are stationary. Tension is applied to the far end of the cable using another fixture, or some other means such as by rotating a capstan around which the cable is wound. As described for the embodiment of FIG. 13, the tension on the individual strands is regulated and adjusted using the individual strand tensioners 50. It may be regulated via connecting them to a common, pressurized reservoir, or via an active control approach.

Of course, other automated tensioners could be substituted for the hydraulic cylinder shown in FIG. 7. FIGs. 15 and 16 show one embodiment for such as device. Strand tensioner 88 slips over nut 40. An electrically-activated gear drive within strand tensioner 88 engages and turns nut 40 while the stand tensioner 88 remains in the position shown.

585 It is preferable to secure loading stud 24 so that it does not turn with the nut. A pair of
opposing flats 92 are provided on loading stud 24. Telescoping clevis 90 is part of strand
tensioner 88. This component includes a clevis notch sized to engage the two flats on the
loading stud. FIG. 16 shows telescoping clevis 90 in an activated state. It engages the two flats
92 and prevents the rotation of loading stud 24. In this configuration, the gear drive within
590 strand tensioner 88 rotates nut 44 and thereby increases or decreases the tension on the strand to
which loading stud 24 is attached. The control of strand tensioner 88 may be manual. On the
other hand, strand tension 88 may be substituted for strand tensioner 50 in the embodiment of
FIG. 13. In that case, strand tensioner 88 could be controlled by process controller 62.

FIG. 17 illustrates a substitute sensing method that could be used for virtually any
595 embodiment. In this version, the conventional washer between nut 40 and collector 34 has been
replaced by load cell 94. This load cell is provided with wiring 96 to connect it to a remote
sensor monitor or possibly the process controller itself. Using this load cell the tension on each
strand may be monitored. The wired connection could be replaced by a wireless one having an
internal battery with enough energy to last through the preloading process. It could even be
600 made rechargeable in order to be useful for load monitoring in the field.

Those skilled in the art will appreciate that many other devices and methods could be
used in place of the embodiments described. For example:

1. The displacement sensor on the hydraulic cylinders could be replaced by an
optical system that uses light to measure the displacement of each loading stud;
- 605 2. The pressure sensors in the hydraulic system could be replaced with direct load
sensors – such as load cells or strain gages;
3. The threaded connection between the strand tensioner and the loading stud could
be replaced with a different type of connection; and
4. Pulsed hydraulic force could be applied to the tensioning process rather than a
610 smooth “ramp up.”

Once a controlled and monitored pre-load has been applied to the cable, it is desirable to
stabilize the position of the strand terminations with respect to the collector. Obviously the cable

is not useful while locked into the fixture of FIG. 8. One way to transition to the completed product is to hold the final tension within the fixture of FIG. 13 and advance nuts 40 to a tightened position with a specified amount of torque. Once a suitable balance is achieved, the geometric relationship between the strand terminations and the collector is preferably secured so that the “relaxation” of the cable won’t allow disorganization to resume. There are many, many ways to secure this geometric relationship. FIG. 14 depicts another way this could be done. Castellated nut 84 is used in the place of a conventional nut. The castellated nut is tightened against collector 34 to secure loading stud 24 in place. Two proximate bosses 76 with associated holes 78 are provided on collector 34. Once the castellated nut is in position, lock wire 80 is passed around one boss, through a suitable cross hole 82 in loading stud 24 (and through two of the notches 86 on the castellated nut) and around the other boss. Using such a device the rotation of the loading stud is limited and the rotation of the castellated nut is limited.

The strand tensioners are then released and the cable can be removed from the fixture and prepared for use. The nuts may be secured in position using other device such as a cottar key, tack welding, or any other suitable method. If desired, the protruding length of loading stud 24 can be removed at that time.

The tightening of the nuts may be done by automated machinery, since it is generally undesirable for a human operator to come near the collector assembly while the strand tensioners are maintaining tension. The amount of force applied is such that a component failure could produce a dangerous condition.

Returning to FIG. 7, those skilled in the art will realize that other components could be used in the place of the threaded engagement between nut 40 and loading stud 24. Once the final tension is applied, a shim of suitable thickness could be placed between a portion of the loading stud and the collector. It is also desirable in some circumstances to clamp the collector from the underside (in the perspective of FIG. 5). A separate shim or fastener can be used for this purpose. Clamping from both sides minimizes the motion of the termination with respect to the collector after the pre-load has been applied. In still other examples some portion of the strand termination may be tack welded to the collector.

The invention thus described is applicable to any large synthetic cable. It is perhaps most useful for construction where the constituent strands interact in a significant way. This includes cables having a braided construction, or cable lay construction. It also includes cables made using simple helical twists, as well as other constructions. Such cables are said to have an interwoven structure. However, the load-balancing aspects of the invention are potentially useful for all synthetic cables, including those with a purely parallel construction built with parallel strands encased in a wound external jacket.

The invention is also applicable to virtually any defined tensioning plan. The example of FIGs. 10 and 11 are only two among the virtually endless possibilities. Many of the inventive embodiments monitor the amount of tension being applied in the cable through indirect means. An example of this is using the pressure applied to the hydraulic cylinder in the example of FIG. 8. One may easily calculate the applied tension by knowing the pressure. On the other hand, one may simply use pressure as a good proxy for applied tension and base the controlling algorithms directly on pressure. Process controller 62 preferably includes a processor running software that can accommodate these and other variations.

Once the desired strand loading plan has been achieved in the fixture, the appropriate spatial relationship between each of the strand terminations and the collector has been established. The term “spatial relationship” will be understood to mean the relative position of a strand termination with respect to the collector. In some instances this may be a single linear dimension. Looking at the example of FIG. 6, if one omits a ball-and-socket connection and simply passes the loading studs 24 through holes in the collector 34, then adjusting the nuts 40 will adjust one linear dimension. In other examples, however, there may be more than one degree of freedom involved.

Many other variations are possible, including:

1. The “strand tensioner” could assume many forms other than those examples given;
2. The connections between the strand tensioners and the strand terminations could assume many other forms;

3. The collector could be an assembly of multiple pieces that are not joined until the
670 cable is put into use; and

4. The tension monitoring for each strand could be via a wireless transmission from
a load cell mounted in each receiver.

Although the preceding description contains significant detail, it should not be construed
as limiting the scope of the invention but rather as providing illustrations of the preferred
675 embodiments of the invention. Those skilled in the art will be able to devise many other
embodiments that carry out the present invention. Thus, the language used in the claims shall
define the invention rather than the specific embodiments provided.

680

685

690

695

CLAIMS

Having described my invention, I claim:

- 700 Claim 1. A method for preparing a synthetic cable for use, said synthetic cable having multiple strands with a strand termination affixed to an end of each of said multiple strands, comprising:
- a) providing a collector having a plurality of receivers, each of said receivers being configured to accept a said strand termination;
 - b) providing a loading fixture, including a plurality of hydraulic cylinders;
 - 705 c) connecting said collector to said loading fixture;
 - d) using said loading fixture to apply a predefined tensioning plan to said strand terminations by connecting each of said hydraulic cylinders to a strand termination, said tensioning plan being configured to apply an overall tension to said cable and a specific strand tension to each
 - 710 individual strand;
 - e) while said predefined tensioning plan is being applied, determining a spatial relationship between each of said strand terminations and said collector; and
 - f) preserving said spatial relationships determined for each of said strand
 - 715 terminations.
- Claim 2. A method for preparing a synthetic cable for use as recited in claim 1, wherein said step of preserving said spatial relationships comprises mechanically locking said strand terminations in said determined spatial relationships.
- 720 Claim 3. A method for preparing a synthetic cable for use as recited in claim 1, wherein said step of preserving said spatial relationships comprises measuring and recording said spatial relationships.

- 725 Claim 4. A method for preparing a synthetic cable for use as recited in claim 1, further comprising providing a second collector and using said preserved spatial relationships to connect said strand terminations to said second collector.
- 730 Claim 5. A method for preparing a synthetic cable for use as recited in claim 1, wherein said strands are freely floating with respect to said collector during said application of said tensioning plan.
- 735 Claim 6. A method for preparing a synthetic cable for use as recited in claim 5, wherein each of said hydraulic cylinders is independently controlled.
- 740 Claim 7. A method for preparing a synthetic cable for use as recited in claim 1, wherein all of said hydraulic cylinders are connected to a single, pressurized reservoir.
- 745 Claim 8. A method for preparing a synthetic cable for use as recited in claim 1, wherein each of said strand terminations includes a threaded loading stud with a nut threaded onto said loading stud, said nut being configured to bear against said collector.
- 750 Claim 9. A method for preparing a synthetic cable for use as recited in claim 1, wherein each of said hydraulic cylinders is connected to one of said terminations by a threaded coupler.
- 750 Claim 10. A method for preparing a synthetic cable for use as recited in claim 1, wherein each of said hydraulic cylinders is a double-acting cylinder.

Claim 11. A method for preparing a synthetic cable for use, said synthetic cable having multiple strands with a strand termination affixed to an end of each of said multiple strands, comprising:

- a) providing a collector having a plurality of receivers, each of said receivers being configured to accept a said strand termination;
- b) providing a loading fixture that is separate from said collector, said loading fixture including a plurality of strand tensioners;
- c) connecting said collector to said loading fixture;
- d) using said loading fixture to apply a predefined tensioning plan to said strand terminations by connecting each of said strand tensioners to a strand termination, said tensioning plan being configured to apply an overall tension to said cable and a specific strand tension to each individual strand;
- e) while said predefined tensioning plan is being applied, mechanically connecting each of said strand terminations to said collector in order to preserve a spatial relationship then existing between each of said strand terminations and said collector.

Claim 12. A method for preparing a synthetic cable for use as recited in claim 11, wherein said strand tensioning plan comprises evenly dividing said overall tension among all of said strands.

Claim 13. A method for preparing a synthetic cable for use as recited in claim 11, wherein each of said strand tensioners is connected to one of said strand terminations by a threaded coupler.

Claim 14. A method for preparing a synthetic cable for use as recited in claim 11, wherein each of said strand tensioners comprises a hydraulic cylinder.

- 780 Claim 15. A method for preparing a synthetic cable for use as recited in claim 14, wherein
all of said hydraulic cylinders are connected to a single, pressurized reservoir.
- Claim 16. A method for preparing a synthetic cable for use as recited in claim 11, wherein
each of said strand terminations includes a threaded loading stud with a nut
785 threaded onto said loading stud, said nut being configured to bear against said
collector.
- Claim 17. A method for preparing a synthetic cable for use as recited in claim 13, wherein
each of said strand tensioners comprises an electric drive configured to engage
790 and rotate one of said nuts.
- Claim 18. A method for preparing a synthetic cable for use as recited in claim 14, wherein
each of said hydraulic cylinders is a double-acting cylinder.
- 795

ABSTRACT

Devices and methods for loading a cable in order to create a desired distribution of the load among the cable's constituent strands. Strand terminations are applied to many – and possibly all of – the cable's strands. The ultimate goal is to connect the strand terminations to a collector in order to create an overall cable termination. The relationship between each strand termination and the collector is allowed to “float” using the inventive process while the cable is tensioned and an appropriate spatial relationship between each strand tensioner and the collector is determined. Once the appropriate relationship is found, it is configured to be repeatable (such as by locking the strand termination in place or by recording its position for later application to the same or similar collector).