

Description

This invention relates to a process of manufacturing slide fasteners from an elongate stringer chain (100) which comprises feeding said stringer chain (100) sequentially along a path of processing through a plurality of processing units including a gapping unit (11), a bottom end stop applying unit (12), a slider applying unit, a top end stop applying unit and a stringer chain cutting unit.

There are known various control systems for effecting a controlled operation of respective processing units in a slide fastener production line during a substantially continuous cycle of operation. GB-A- 221 953 which forms the basis of claim 1 discloses a process for controlling the entire apparatus for making slide fastener products of different lengths, styles, sizes and/or colors. The arrangement of such prior art apparatus is shown in figure 4 of the accompanying drawings in which a buffer W or storage device is provided between succeeding machines including a gapping machine P, a bottom stop fitting machine Q, a slider mounting machine R, a top stop fitting machine S and a cutting machine T, the maximum and minimum level of workpiece supply Y in the buffer W being a determining factor to continue or discontinue the operation of the respective upstream and downstream machines. The feeding of the workpiece or stringer chain W through the various machines is relied upon the repetitive maximum and minimum levels of the workpiece W in each buffer W. This process therefore has a drawback in that the time required to complete each production cycle is prolonged, that the workpiece W is prone to become tainted or entangled while being stored in the buffers W, and that the workpiece W gets taut when its supply in each buffer W is depleted, resulting sometimes in defective slide fastener products.

The present invention seeks to provide a process of the type mentioned above which will eliminate the foregoing drawbacks of the prior art and which will enable an automatic mass production of slide fasteners with utmost efficiency and accuracy.

According to the invention, a process satisfying these requirements is characterized by holding said stringer chain (100) in substantially tensionless condition by allowing it to sag by its own gravity at least over a predetermined slide fastener product length between each adjacent pair of said units (11; 12; 13); and effecting the operation of each of said units in synchronism with a selected one of said units which has the slowest cycle of operation.

The above and other objects and features of the invention will appear clear from the following detailed description taken with reference to the accompanying drawings which illustrate some preferred embodiments which the invention may as-

sume in practice.

Figure 1 is a diagrammatic equipment layout illustrating the process of the invention;

Figures 2a through 2e inclusive are plan views illustrating a slide fastener being processed in respective successive stages of production;

Figures 3a through 3c inclusive are block diagrams utilized to explain three different modes of control of the respective processing units for the manufacture of slide fasteners according to the invention; and

Figure 4 is a small scale side elevational view of a prior art manufacturing system.

The term stringer chain 100 as used herein designates an elongate strip (Figure 2a) comprising a pair of oppositely disposed tapes 101 and a row of coupling elements 102 secured to and along an inner longitudinal edge of each of the tapes 101.

Figure 1 shows a general layout of an apparatus employed to carry the process of the invention into practice. The apparatus 10 essentially comprises a gapping unit 11 for removing a predetermined number of coupling elements 102 to provide a gap or an element-devoid space portion 103 (Figure 2b); a bottom end stop applying unit 12 for applying a bottom end stop 104 at the trailing end of each gap 103 (Figure 2c); and a combination unit 13 including a slider applying unit for mounting a slider 105 (Figure 2d) astride the coupling elements 102 on the pair of opposed tapes 101, a top end stop applying unit for applying a top end stop 106 (Figure 2d) at the end of a terminal element 102 on each tape 101, and a cutting unit for cutting the tapes 101 transversely across the center line 107 (Figure 2d) of each gap 103.

The stringer chain 100 is metered, cut to a predetermined length and stored in a stockyard 14 in advance of entry into the processing apparatus 10. The stringer chain 100 passes through a first detector 15 operatively associated with a metering roll 16 and stops upon movement for a distance corresponding to one slide fastener product length, during which time the stringer chain 100 is gapped by the gapping unit 11. This is followed by operation of a first feed roller 17 to advance the stringer chain 100.

According to an important feature of the invention, the first feed roller 17 is controlled so as to begin its rotation in synchronism with an operating cycle of a slowest processing unit in the apparatus 10 which is the combination slider and top end stop applying and cutting unit 13 as exemplified in the illustrated embodiment. A completion of one operating cycle of the slowest unit 13 (beginning with advancing movement of the stringer chain 100 and ending with attachment of a slider and top end stops onto the chain 100 and cutting the chain 100) dictates the first feed roller 17 to advance or feed

the downstream portion of the stringer chain 100 through a first guide roll 18 onto the bottom end stop applying unit 12 and the upstream portion of the chain 100 onto the gapping unit 11. In a manner similar to the first feed roller 17, a second feed roller 19 operates in synchronism with the operating cycle of the slowest unit 13 and draws the stringer chain 100 forwardly onto the bottom end stop applying unit 12. A second detector 20 monitors the movement of the stringer chain 100 for a distance corresponding to one slide fastener product length and dictates the second feed roller 19 to stop so as to allow the unit 12 to apply a bottom end stop 104 to the upstream terminal elements 102 of the stringer chain 100 as depicted in Figure 2c.

According to another feature of the invention, the stringer chain 100 is always held in tensionless condition by allowing it to sag by its own gravity at least over one slide fastener product length between the first feed roller 17 adjacent to the gapping unit 11 and the first guide roll 18 immediately upstream of the bottom end stop applying unit 12 and also between the second feed roller 19 immediately downstream of the bottom end stop applying unit 12 and a second guide roll 21 immediately upstream of the combination unit 13, as illustrated in Figure 1. The distance over which the stringer chain 100 is held substantially tensionless may be greater than one slide fastener product length where the product is relatively short.

The stringer chain 100 now assembled with a bottom end stop 104 is further advanced by means of feed grippers 22, 22 onto the combination unit 13, wherein the chain 100 is assembled with a slider 105 and top end stops 106 supplied from a parts holder 23. The stringer chain 100 thus assembled with slider 105 and top end stops 106 as depicted in Figure 2d is gripped and pulled toward an outlet end of the apparatus 10 by a take-out gripper 24 for a distance corresponding to one slide fastener length as detected by a third detector 25, whereupon the stringer chain 100 is cut by a cutter 26 transversely across the cutting line 107 centrally of the gap 103 to produce a finished slide fastener 108 (Figure 2e) which is further carried onward by the gripper 24 over to a conveyor 27, thence to a product tray 28 in which finished slide fasteners are stacked and bundled in a manner well known in the art.

The gaps 103 are utilized for actuating the second detector 20 and the third detectors 25 as for example by a mechanical means such as a pin installed at the gap 103, or by an optical means emitting a light beam through the gap 103 in a manner well known in the art, whereby the detectors 20 and 25 respectively read and signal one predetermined slide fastener product length after

another over the stringer chain 100.

The processing units 11, 12 and 13 are controlled for their respective cycles of operation by respective control devices (A), (B) and (C) as schematically illustrated in Figures 3a - 3c. Figure 3a shows a mode of control in which the control device (C) associated with the slowest processing unit (III) is arranged to supervise the other two control devices (B) and (C) linked to the processing units (I) and (II), respectively. The cycle of processing operation begins with the transmission of an information signal from each of the control devices (A) and (B) to the master control device (C) that the stringer chain 100 is ready to make advancing or feeding movement. With all of the three units (I), (II) and (III) set up, the master control device (C) transmits an information signal to the control devices (A) and (B), respectively, to initiate feeding of the stringer chain 100, whereupon the units (I) and (II) are put into operation simultaneously and the stringer chain 100 is fed and monitored by the detectors 20 and 25, followed by assembling the chain 100 with the respective slide fastener component parts (bottom end stop 104, slider 105 and top end stops 106) at the respective units (I) and (II). An information signal representing the completion of the work of the respective units (I), (II) and (III) is transmitted from the respective control devices (A), (B) and (C) to the master control (C), whereupon the next cycle of operation begins with the transmission of a "feed-start" signal from the master control (C) to the respective control devices (A) and (B). The processing units (I) and (II) are thus operated in synchronized relation to the slowest working unit (III).

Figure 3b shows another mode of control in which the processing unit (II) is the slowest and hence its associated control device (B) serves as a master to supervise the other two control devices (A) and (C).

Figure 3c illustrates a further mode of control in which a central control device (D) is installed to supervise all of the three control devices (A), (B) and (C) so that the respective processing units (I), (II) and (III) are maintained in synchronized cycle of operation.

Various changes and modifications may be made in the foregoing embodiments of the invention without departing from the spirit and scope of the appended claims. For example, the combination processing unit 13 may be built into separate units for applying sliders 105 and top end stops 106 respectively and cutting the stringer chain 100, thus providing a total of five stages of operation. It is also possible to connect the master control device (C), as shown in Figure 3a, to a computer control system (E) storing a specific production program designed to manufacture a variety of slide

fastener products differing in style, length, color, etc., including for example a separable type of bottom end stop. Alternatively, such computer control system (E) may be connected to the central control device (D) for similar purposes.

Claims

1. A process of manufacturing slide fasteners from an elongate stringer chain (100) which comprises feeding said stringer chain (100) sequentially along a path of processing through a plurality of processing units including a gapping unit (11), a bottom end stop applying unit (12), a slider applying unit, a top end stop applying unit and a stringer chain cutting unit (13) characterized by holding said stringer chain (100) in substantially tensionless condition by allowing it to sag by its own gravity at least over a predetermined slide fastener product length between each adjacent pair of said units (11; 12; 13); and effecting the operation of each of said units in synchronism with a selected one of said units which has the slowest cycle of operation.
2. The process as defined in claim 1 which further comprises controlling the operation of each of said units (11, 12, 13) with a computer program designed to manufacture slide fasteners differing in style, length and/or color.

Patentansprüche

1. Verfahren zur Herstellung von Reißverschlüssen aus einer langgestreckten Reißverschlussschleife (100), bei dem die Reißverschlussschleife (100) längs einer Bearbeitungsbahn nacheinander durch mehrere Bearbeitungseinheiten hindurchbewegt wird, umfassend eine Lückenbildungseinheit (11), eine untere Begrenzungsteil-Anbringeinheit (12), eine Schieber-Anbringeinheit, eine obere Begrenzungsteil-Anbringeinheit und eine Reißverschlussschleifen-Schneideinheit (13), dadurch gekennzeichnet, daß die Reißverschlussschleife (100) in im wesentlichen spannungslosem Zustand gehalten wird, indem sie zumindest über eine bestimmte Länge eines Reißverschluszeugnisses zwischen jedem benachbarten Paar der besagten Einheiten (11; 12; 13) unter ihrem Eigengewicht durchhängen kann, und daß die Betätigung jeder der besagten Einheiten in zeitlicher Abhängigkeit von einer dieser Einheiten, die den langsamsten Arbeitszyklus hat, erfolgt.
2. Verfahren nach Anspruch 1, ferner umfassend die Steuerung der Betätigung jeder der besag-

ten Einheiten (11, 12, 13) mit einem Computerprogramm, das so ausgebildet ist, um hinsichtlich der Machart, Länge und/oder Farbe unterschiedliche Reißverschlüsse herzustellen.

Revendications

1. Procédé de fabrication de fermetures à glissière à partir d'une longue chaîne de bande d'accrochage (100), qui comprend l'amenée de ladite chaîne de bande d'accrochage (100) de façon séquentielle le long d'un trajet de traitement passant par une pluralité d'unités de traitement qui comprennent une unité (11) de création d'intervalles, une unité (12) de pose de butées d'extrémité inférieure, une unité de pose de curseur, une unité de pose de butées d'extrémité supérieure et une unité (13) de coupe de chaîne de bande d'accrochage, caractérisé par le fait de maintenir ladite chaîne de bande d'accrochage (100) à l'état sensiblement sans tension, en la laissant fléchir sous l'effet de son propre poids sur une longueur prédéterminée au moins de la fermeture à glissière, entre chaque paire d'unités adjacentes (11, 12, 13) et le fait de procéder à la mise en fonctionnement de chacune desdites unités en synchronisme avec l'une sélectionnée desdites unités qui a le cycle de fonctionnement le plus lent.
2. Procédé selon la revendication 1, qui comprend en outre le fait de commander le fonctionnement de chaque unité (11, 12, 13) à l'aide d'un programme d'ordinateur conçu pour la fabrication de fermetures à glissière qui diffèrent en style, longueur et/ou couleur.



fastener products differing in style, length, color, etc., including for example a separable type of bottom end stop. Alternatively, such computer control system (E) may be connected to the central control device (D) for similar purposes.

Claims

1. A process of manufacturing slide fasteners from an elongate stringer chain (100) which comprises feeding said stringer chain (100) sequentially along a path of processing through a plurality of processing units including a gapping unit (11), a bottom end stop applying unit (12), a slider applying unit, a top end stop applying unit and a stringer chain cutting unit (13) characterized by holding said stringer chain (100) in substantially tensionless condition by allowing it to sag by its own gravity at least over a predetermined slide fastener product length between each adjacent pair of said units (11; 12; 13); and effecting the operation of each of said units in synchronism with a selected one of said units which has the slowest cycle of operation.
2. The process as defined in claim 1 which further comprises controlling the operation of each of said units (11, 12, 13) with a computer program designed to manufacture slide fasteners differing in style, length and/or color.

Patentansprüche

1. Verfahren zur Herstellung von Reißverschlüssen aus einer langgestreckten Reißverschlußkette (100), bei dem die Reißverschlußkette (100) längs einer Bearbeitungsbahn nacheinander durch mehrere Bearbeitungseinheiten hindurchbewegt wird, umfassend eine Lückenbildungseinheit (11), eine untere Begrenzungsteil-Anbringeinheit (12), eine Schieber-Anbringeinheit, eine obere Begrenzungsteil-Anbringeinheit und eine Reißverschlußketten-Schneideinheit (13), dadurch gekennzeichnet, daß die Reißverschlußkette (100) in im wesentlichen spannungslosem Zustand gehalten wird, indem sie zumindest über eine bestimmte Länge eines Reißverschlußerzeugnisses zwischen jedem benachbarten Paar der besagten Einheiten (11; 12; 13) unter ihrem Eigengewicht durchhängen kann, und daß die Betätigung jeder der besagten Einheiten in zeitlicher Abhängigkeit von einer dieser Einheiten, die den langsamsten Arbeitszyklus hat, erfolgt.
2. Verfahren nach Anspruch 1, ferner umfassend die Steuerung der Betätigung jeder der besag-

ten Einheiten (11, 12, 13) mit einem Computerprogramm, das so ausgebildet ist, um hinsichtlich der Machart, Länge und/oder Farbe unterschiedliche Reißverschlüsse herzustellen.

Revendications

1. Procédé de fabrication de fermetures à glissière à partir d'une longue chaîne de bande d'accrochage (100), qui comprend l'amenée de ladite chaîne de bande d'accrochage (100) de façon séquentielle le long d'un trajet de traitement passant par une pluralité d'unités de traitement qui comprennent une unité (11) de création d'intervalles, une unité (12) de pose de butées d'extrémité inférieure, une unité de pose de curseur, une unité de pose de butées d'extrémité supérieure et une unité (13) de coupe de chaîne de bande d'accrochage, caractérisé par le fait de maintenir ladite chaîne de bande d'accrochage (100) à l'état sensiblement sans tension, en la laissant fléchir sous l'effet de son propre poids sur une longueur prédéterminée au moins de la fermeture à glissière, entre chaque paire d'unités adjacentes (11, 12, 13) et le fait de procéder à la mise en fonctionnement de chacune desdites unités en synchronisme avec l'une sélectionnée desdites unités qui a le cycle de fonctionnement le plus lent.
2. Procédé selon la revendication 1, qui comprend en outre le fait de commander le fonctionnement de chaque unité (11, 12, 13) à l'aide d'un programme d'ordinateur conçu pour la fabrication de fermetures à glissière qui diffèrent en style, longueur et/ou couleur.