

**INTEGRATED FUEL INJECTOR IGNITERS
SUITABLE FOR LARGE ENGINE
APPLICATIONS AND ASSOCIATED
METHODS OF USE AND MANUFACTURE**

**CROSS-REFERENCE TO RELATED
APPLICATION(S)**

The present application claims priority to and the benefit of each of the following: U.S. Provisional Application No. 61/304,403, filed Feb. 13, 2010 and titled FULL SPECTRUM ENERGY AND RESOURCE INDEPENDENCE, and U.S. Provisional Application No. 61/312,100, filed Mar. 9, 2010 and titled SYSTEM AND METHOD FOR PROVIDING HIGH VOLTAGE RF SHIELDING, FOR EXAMPLE, FOR USE WITH A FUEL INJECTOR. The present application is a continuation-in-part of each of the following: U.S. patent application Ser. No. 12/841,170, filed Jul. 21, 2010 and titled INTEGRATED FUEL INJECTORS AND IGNITERS AND ASSOCIATED METHODS OF USE AND MANUFACTURE; U.S. patent application Ser. No. 12/804,510, filed Jul. 21, 2010 and titled FUEL INJECTOR ACTUATOR ASSEMBLIES AND ASSOCIATED METHODS OF USE AND MANUFACTURE; U.S. patent application Ser. No. 12/841,146, filed Jul. 21, 2010 and titled INTEGRATED FUEL INJECTOR IGNITERS WITH CONDUCTIVE CABLE ASSEMBLIES; U.S. patent application Ser. No. 12/841,149, filed Jul. 21, 2010 and titled SHAPING A FUEL CHARGE IN A COMBUSTION CHAMBER WITH MULTIPLE DRIVERS AND/OR IONIZATION CONTROL; U.S. patent application Ser. No. 12/841,135, filed Jul. 21, 2010 and titled CERAMIC INSULATOR AND METHODS OF USE AND MANUFACTURE THEREOF; U.S. patent application Ser. No. 12/804,509, filed Jul. 21, 2010 and titled METHOD AND SYSTEM OF THERMOCHEMICAL REGENERATION TO PROVIDE OXYGENATED FUEL, FOR EXAMPLE, WITH FUEL-COOLED FUEL INJECTORS; and U.S. patent application Ser. No. 12/804,508, filed Jul. 21, 2010 and titled METHODS AND SYSTEMS FOR REDUCING THE FORMATION OF OXIDES OF NITROGEN DURING COMBUSTION IN ENGINES. Furthermore, each of the preceding applications: claims priority to and the benefit of U.S. Provisional Application No. 61/237,425, filed Aug. 27, 2009 and titled OXYGENATED FUEL PRODUCTION; claims priority to and the benefit of U.S. Provisional Application No. 61/237,466, filed Aug. 27, 2009 and titled MULTIFUEL MULTIBURST; claims priority to and the benefit of U.S. Provisional Application No. 61/237,479, filed Aug. 27, 2009 and titled FULL SPECTRUM ENERGY; is a continuation-in-part of U.S. patent application Ser. No. 12/581,825, filed Oct. 19, 2009 and titled MULTIFUEL STORAGE, METERING AND IGNITION SYSTEM; is a continuation-in-part of PCT Application No. PCT/US09/67044, filed Dec. 7, 2009 and titled INTEGRATED FUEL INJECTORS AND IGNITERS AND ASSOCIATED METHODS OF USE AND MANUFACTURE; is a continuation-in-part of U.S. patent application Ser. No. 12/653,085, filed Dec. 7, 2009 and titled INTEGRATED FUEL INJECTORS AND IGNITERS AND ASSOCIATED METHODS OF USE AND MANUFACTURE; claims priority to and the benefit of U.S. Provisional Application No. 61/304,403, filed Feb. 13, 2010 and titled FULL SPECTRUM ENERGY AND RESOURCE INDEPENDENCE; and claims priority to and the benefit of U.S. Provisional Application No. 61/312,100, filed Mar. 9, 2010 and titled SYSTEM AND METHOD FOR PROVIDING HIGH VOLTAGE RF SHIELDING, FOR EXAMPLE, FOR USE WITH A FUEL INJECTOR. Moreover, U.S. patent

application Ser. No. 12/581,825 is a divisional of U.S. patent application Ser. No. 12/006,774 (now U.S. Pat. No. 7,628,137), filed Jan. 7, 2008 and titled MULTIFUEL STORAGE, METERING AND IGNITION SYSTEM. PCT Application No. PCT/US09/67044 claims priority to and the benefit of U.S. Provisional Application No. 61/237,466, filed Aug. 27, 2009 and titled MULTIFUEL MULTIBURST. U.S. patent application Ser. No. 12/653,085 is a continuation-in-part of U.S. patent application Ser. No. 12/006,774 (now U.S. Pat. No. 7,628,137), filed Jan. 7, 2008 and titled MULTIFUEL STORAGE, METERING AND IGNITION SYSTEM; and claims priority to and the benefit of U.S. Provisional Application No. 61/237,466, filed Aug. 27, 2009 and titled MULTIFUEL MULTIBURST. Each of the applications referenced above is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The following disclosure relates generally to integrated fuel injectors and igniters suitable for large engine applications and other sized engine applications for injecting and igniting various fuels in a combustion chamber.

BACKGROUND

Fuel injection systems are typically used to inject a fuel spray into an inlet manifold or a combustion chamber of an engine. Fuel injection systems have become the primary fuel delivery system used in automotive engines, having almost completely replaced carburetors since the late 1980s. Conventional fuel injection systems are typically connected to a pressurized fuel supply, and fuel injectors used in these fuel injection systems generally inject or otherwise release the pressurized fuel into the combustion chamber at a specific time relative to the power stroke of the engine. In many engines, and particularly in large engines, the size of the bore or port through which the fuel injector enters the combustion chamber is small. This small port accordingly limits the size of the components that can be used to actuate or otherwise inject fuel from the injector. Moreover, such engines also generally have crowded intake and exhaust valve train mechanisms, further restricting the space available for components of these fuel injectors.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic cross-sectional side view of an integrated injector/igniter ("injector") configured in accordance with an embodiment of the disclosure.

FIG. 2A is a partially exploded cross-sectional side view of an injector configured in accordance with another embodiment of the disclosure.

FIG. 2B is a cross-sectional side view of a flow valve configured in accordance with an embodiment of the disclosure.

FIGS. 3A-5A are a series of cross-sectional side views of injectors configured in accordance with further embodiments of the disclosure.

FIG. 5B is a cross-sectional side view of a first flow path taken substantially along the lines 5B-5B of FIG. 5A, and FIG. 5C is a cross-sectional side view of a second flow path taken substantially along the lines 5C-5C of FIG. 5A. FIG. 5D is a cross-sectional side view of an alternative embodiment of the first flow path taken substantially along lines 5B-5B of FIG. 5A, and FIG. 5E is a cross-sectional side view of an alternative embodiment of the second flow path taken substantially along the lines 5C-5C of FIG. 5A.

FIGS. 5F and 5G are side views of flow valves configured in accordance with embodiments of the disclosure.

FIG. 6 is a cross-sectional side view of an injector configured in accordance with an additional embodiment of the disclosure.

DETAILED DESCRIPTION

The present application incorporates by reference in its entirety the subject matter of the U.S. Patent Applications, filed concurrently herewith on Oct. 27, 2010 and titled: ADAPTIVE CONTROL SYSTEM FOR FUEL INJECTORS AND IGNITERS Ser No. 12/913,749; and FUEL INJECTOR SUITABLE FOR INJECTING A PLURALITY OF DIFFERENT FUELS INTO A COMBUSTION CHAMBER 61/407,437.

A. OVERVIEW

The present disclosure describes integrated fuel injection and ignition devices for use with internal combustion engines, as well as associated systems, assemblies, components, and methods regarding the same. For example, several of the embodiments described below are directed generally to adaptable fuel injectors/igniters that can optimize the injection and combustion of various fuels based on combustion chamber conditions. In certain embodiments, these fuel injectors/igniters are also particularly suited for large engine applications, such as retrofit assemblies as well as new assemblies, having limited space constraints for such injectors/igniters. Certain details are set forth in the following description and in FIGS. 1-6 to provide a thorough understanding of various embodiments of the disclosure. However, other details describing well-known structures and systems often associated with internal combustion engines, injectors, igniters, and/or other aspects of combustion systems are not set forth below to avoid unnecessarily obscuring the description of various embodiments of the disclosure. Thus, it will be appreciated that several of the details set forth below are provided to describe the following embodiments in a manner sufficient to enable a person skilled in the relevant art to make and use the disclosed embodiments. Several of the details and advantages described below, however, may not be necessary to practice certain embodiments of the disclosure.

Many of the details, dimensions, angles, shapes, and other features shown in the Figures are merely illustrative of particular embodiments of the disclosure. Accordingly, other embodiments can have other details, dimensions, angles, and features without departing from the spirit or scope of the present disclosure. In addition, those of ordinary skill in the art will appreciate that further embodiments of the disclosure can be practiced without several of the details described below.

Reference throughout this specification to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present disclosure. Thus, the occurrences of the phrases "in one embodiment" or "in an embodiment" in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics described with reference to a particular embodiment may be combined in any suitable manner in one or more other embodiments. Moreover, the headings provided herein are for convenience only and do not interpret the scope or meaning of the claimed disclosure.

FIG. 1 is a schematic cross-sectional side view of an integrated injector/igniter **100** ("injector **100**") configured in accordance with an embodiment of the disclosure. The injector **100** shown in FIG. 1 is intended to schematically illustrate several of the features of the injectors and assemblies described below. Accordingly, these features described with reference to FIG. 1 are not intended to limit any of the features of the injectors and assemblies described below. As shown in FIG. 1, the injector **100** includes a body **102** having a middle portion **104** extending between a first end portion or base portion **106** and a second end portion or nozzle portion **108**. The base portion **106** is accordingly spaced apart from the nozzle portion **108**.

The nozzle portion **108** is configured to at least partially extend through an engine head **110** to inject and ignite fuel at or near an interface **111** of a combustion chamber **112**. In certain embodiments, the nozzle portion **108** can include components that are configured to fit within a relatively small injector port frequently used in large engine applications, such as in marine propulsion engines, for example. In the illustrated embodiment, for example an injection port **107**, such as an injection port of a modern diesel engine, can have a diameter D of approximately 8.4 millimeters (0.33 inch) or less. In other embodiments, however, the diameter D can be greater than approximately 8.4 millimeters. As described in detail below, the injector **100** is particularly suited to provide adaptive and rapid actuation under high fuel delivery pressure, while eliminating unwanted fuel dribble into the combustion chamber **112**, even in such relatively small injection ports **107**. Moreover, as also described in detail below, the injector **100** is also configured to account for a relatively large distance or length L between the combustion chamber interface **111** and several actuating components carried by the body **102** that are spaced apart from the engine head **110**. In modern diesel engines or other large engines, for example, crowded intake and exhaust valve train mechanisms at the engine head **110** may require separation lengths L of 12-36 inches, or more.

In the embodiment shown in FIG. 1, the injector **100** includes a core assembly **113** extending from the base portion **106** to the nozzle portion **108**. The injector **100** also includes a body insulator **142** coaxially disposed over at least a portion of the core assembly **113**. The core assembly **113** includes an ignition rod or conductor **114**, an ignition insulator **116**, and a valve **118**. The ignition conductor **114** is operably coupled to a voltage source at the base portion **106** and extends from the base portion **106** through the nozzle portion **108**. The ignition conductor **114** includes an end portion **115** proximate to the interface **111** of the combustion chamber **112** that includes one or more ignition features that are configured to generate an ignition event with the head **110**. The ignition insulator **116** is coaxially disposed over at least a portion of the ignition conductor **114** and extends from the base portion **106** at least partially into the nozzle portion **108**. The valve **118** is coaxially disposed over at least a portion of the insulator **116**. In the illustrated embodiment, the valve **118** has a first length, the ignition insulator **116** has a second length greater than the first length, and the ignition conductor **114** has a third length greater than the second length. The valve **118** is configured to move between an open position (as shown in FIG. 1) and a closed position. More specifically, the valve **118** includes a sealing end portion **119** that rests against a corresponding valve seat **121** when the valve **118** is in the closed position. The valve seat **121** can be carried by the body insulator **142**. As the valve **118** moves to the open position, the end portion **119** is spaced away from the valve seat **121** to allow fuel to flow or otherwise pass by the valve seat **121**.

The injector **100** also includes a valve operator assembly **125** carried by the base portion **106**. The valve operator assembly **125** includes at least an actuator or driver **120** and a processor or controller **122**. More specifically, the driver **120** is positioned at the base portion **106** and is operably coupled to the valve **118**. The driver **120** is also operably coupled to the controller **122**. The driver **120** can be actuated from any suitable force generating mechanism (e.g., electrical, electro-mechanical, magnetic, etc.) to engage and move the valve **118**. The controller **122** can also be operably coupled to one or more sensors carried by the injector **100** or positioned elsewhere in an engine where the injector **100** is installed. These sensors can detect combustion chamber data or other engine-related data that can be correlated to combustion chamber data. In one embodiment, for example, the controller **122** can be operably coupled to sensors that are optical fibers carried by the ignition conductor **114**. Accordingly, the controller **122** can direct or otherwise control the driver **120** to actuate the valve **118** in response to one or more combustion chamber properties.

In operation, fuel is introduced in the base portion **106** into a fuel flow path or channel **124**. The fuel channel **124** extends between the body **102** and the valve **118** from the base portion **106** through the middle portion **104** to the nozzle portion **108**. Precise metered amounts of fuel can be selectively and adaptively introduced into the combustion chamber **112** by the injector **100**. For example, the driver **120** actuates the valve **118** to slide or otherwise move the valve **118** longitudinally along the insulator **116** to space the sealing end portion **119** of the valve **118** away from the valve seat **121**. As the valve **118** moves between the open and closed positions in directions generally parallel with a longitudinal axis of the injector **100**, the ignition conductor **114** and the insulator **116** remain stationary within the body **102**. The insulator **116** therefore acts as a central journal bearing for the valve **118** and can accordingly have a low friction outer surface that contacts the valve **118**. Moreover, and as discussed in detail below, the ignition conductor **114** can create an ignition event to ignite the fuel before or as the fuel enters the combustion chamber **112**. As also discussed in detail below, the sealing end portion **119** of the valve **118** can be positioned at various locations within the injector **100** including, for example, within the injection port **107** and/or adjacent to the interface **111** of the combustion chamber **112**.

FIG. 2A is a cross-sectional side view of an integrated injector/igniter **200** ("injector **200**") configured in accordance with another embodiment of the disclosure. The embodiment illustrated in FIG. 2A includes several features that are generally similar in structure and function to the corresponding features of the injector **100** described above with reference to FIG. 1. For example, the injector **200** illustrated in FIG. 2 includes a body **202** having a middle portion **204** extending between a first end portion or base portion **206** and a second end portion or nozzle portion **208**. The nozzle portion **208** is configured to be at least partially inserted into an injection port **207** in an engine head **210**. As described in detail below, the injector **200** is configured to overcome the difficult problem with many modern diesel engines or other large engines that limit the size of the injector port **207** to about 8.4 mm (0.33 inch) or less in diameter, and that also limit the available space with crowded intake and exhaust valve train mechanisms often requiring a separation length L of approximately 12-36 inches more between an interface **211** at a combustion chamber **212** and the valve operating components of the injector **200**.

According to features of the illustrated embodiment, the injector **200** also includes a core assembly **213** extending

through the body 202 from the base portion 206 at least partially into the nozzle portion 208. The core assembly 213 facilitates the fuel injection and ignition. More specifically, the core assembly 213 includes a core or ignition insulator 216 coaxially disposed over an ignition rod or conductor 214. The core assembly 213 also includes a moveable tube valve 218 coaxially disposed over the core insulator 216. In the illustrated embodiment, the ignition conductor 214 is a stationary ignition member that can be an electrically conductive rod or Litz wire bundle. The ignition conductor 214 is coupled to an ignition or terminal 227 in the base portion 206 to receive voltage energy. More specifically, the ignition terminal 227 is coupled to a voltage supply conductor 209, which is in turn coupled to a suitable voltage source. In one embodiment, for example, the ignition terminal 227 can supply at least approximately 80 KV (DC or AC) to the ignition conductor 214. In other embodiments, however, the ignition terminal 227 can supply a greater or lesser voltage to the ignition conductor 214.

The ignition conductor 214 also includes one or more ignition features 234 positioned at the nozzle portion 208. In the illustrated embodiment, the ignition features 234 can be acicular threads or other types of projections extending circumferentially away from the ignition member 214. The ignition features 234 remain stationary and act as a first electrode. The inner diameter of the injection port 207 acts as a corresponding second electrode for creating an ignition event, such as a plasma ignition event. In certain embodiments, for example, and as shown in FIG. 2A, the nozzle portion 208 can include a thin conductive electrode liner or plating 235 on at least a portion of the inner surface or diameter of the injection port 207. The electrode liner 235 can be used to protect the inner surface of the injection port 207 from plasma erosion. In embodiments without the electrode liner 235, however, high frequency AC can be used to eliminate plasma erosion on the inner surface of the injection port 207.

In the illustrated embodiment, the ignition conductor 214 also includes one or more sensors, such as one or more optical fibers 217, disposed within the ignition conductor 214. The optical fibers 217 can extend longitudinally through the ignition conductor 214 and are configured to transmit data from the combustion chamber 212 to one or more components in the injector 100 or in the engine utilizing the injector 100.

According to certain features of the illustrated embodiment, the core insulator 216 remains stationary on the ignition conductor 214 and can be constructed from a ceramic insulator as disclosed in the co-pending applications incorporated by reference in their entireties above. In one embodiment, for example, the core insulator 216 can be made from a long-lead spiral form constructed from a PTFE or PEEK monofilament. In other embodiments, however, the core insulator 216 can be made from other materials suitable for containing the voltage delivered to and/or generated within the injector 200. For example, the core insulator 216 can be constructed from insulative materials suitable for containing 80 KV (DC or AC) at temperatures up to about 1000° F. In other embodiments, however, the insulator 216 can be configured to contain more or less voltage, as well as operate in hotter or colder temperatures. As also described in detail below, the core insulator 216 can also serve as a low friction central journal bearing surface for the valve 218 as the valve 218 moves between open and closed positions along the core insulator 216.

As shown in the illustrated embodiment, the valve 218 is an outwardly opening valve (e.g., opening in a direction toward the combustion chamber 212) that is movable along the insulator 216 to selectively introduce fuel from the nozzle portion 208 into the combustion chamber 212. More specifically, the

valve 218 is configured to slide along the insulator 216 between open and closed positions and in directions that are generally parallel to a longitudinal axis of the injector 200. The valve 218 includes a first end portion 223 opposite a second or sealing end portion 219. The sealing end portion 219 forms a fluid tight seal against a corresponding valve seat 221 when the valve 218 is in a closed position. Further details of the valve 218 are described below with reference to FIG. 2B.

FIG. 2B is a partially exploded side cross-sectional view of the valve 218 shown in FIG. 2A. Referring to FIG. 2B, the valve 218 includes a hollow core or body 244 having an inner surface 246 opposite an outer surface 248. The body 244 can be made from reinforced structural composites as disclosed in U.S. patent application Ser. No. 12/857,461, filed Aug. 16, 2010, and entitled "INTERNALLY REINFORCED STRUCTURAL COMPOSITES AND ASSOCIATED METHODS OF MANUFACTURING," which is incorporated herein by reference in its entirety. For example the body 244 can be made from relatively low density spaced graphite or graphene structures that provides the benefits of reducing inertia, achieving high strength and stiffness, and providing high fatigue endurance strength. More specifically, the body 244 can be constructed from a light weight but strong graphite structural core that is reinforced by one or more carbon-carbon layers. The carbon-carbon layer(s) may be prepared from a suitable precursor application of carbon donor (e.g., petroleum pitch or a thermoplastic such as a polyolefin or PAN). The one or more carbon-carbon layers can further provide radio frequency shielding and protection. Additional protection may be established by plating the outer surface 248 with a suitable alloy, such as a nickel alloy that may be brazed to the body 244 by a suitable braze alloy composition. The inner surface 246 is configured to slide or otherwise move along the core insulator 216 (FIG. 2A). Accordingly, at least a portion of the inner surface 246 can include a suitable low friction coating, such as a polyimide, PEEK, Parylene H, or a PTFE copolymer, to facilitate the movement of the valve 218 along the core insulator 216 (FIG. 2A). In addition, the outer surface 248 can also include high strength materials, such as graphite filament reinforced polyimide or graphite tape with thermoset adhesives.

According to further features of the illustrated embodiment, the valve 218 includes the enlarged sealing end portion 219 that is configured to seal against or otherwise rest on the valve seat 221 (FIG. 2A) when the valve 218 is in the closed position. The sealing end portion 219 has a generally funnel shape or a generally annularly flared shape having a diameter that is greater than the diameter of the body 244. More specifically, the sealing end portion 219 is an end portion of the body 244 that has a gradually increasing diameter. In certain embodiments, the sealing end portion 219 can include an elastomeric coating or elastomeric portion to facilitate sealing with the corresponding valve seat 221 (FIG. 2A). In the illustrated embodiment, for example, the exterior surface 248 of the sealing end portion 219 can include an elastomeric ring or coating, such as a fluorosilicone coating, a perfluoroelastomer, or other fluoroelastomers, to at least partially conform to the shape of the corresponding valve seat. In other embodiments, such as for inwardly opening valves as described in detail below, the inner surface 246 can include the elastomeric ring or coating to facilitate sealing with a corresponding valve seat. Moreover, in still further embodiments the valve seat that contacts the sealing end portion 219 can include an elastomeric coating or elastomeric portion to facilitate sealing.

In the illustrated embodiment, the valve 218 also includes one or more stop members or stop collars 230 (identified

individually as a first stop collar **230a** and a second stop collar **230b**) that can be attached to the outer surface **248** of the first end portion **223**. Although the stop collars **230** are shown as separate components from the valve **218** in FIG. 2B, in other embodiments the stop collars **230** can be integrally formed on the outer surface **248** of the valve **218**. As described in detail below, the stop collars **230** are configured to contact or otherwise engage an actuator or driver in the injector **200** to move the valve **218** between the open and closed positions.

Referring again to FIG. 2A, and as discussed in detail below, when the valve **218** is actuated to an open position, the sealing end portion **219** of the valve **218** becomes spaced apart from the valve seat **221** to selectively introduce fuel into the injection port **207**. As shown in the illustrated embodiment, the valve seat **221** is positioned adjacent to the end of the core insulator **216**. The valve seat **221** is also positioned adjacent to the ignition features **235** of the ignition conductor **214**. In other embodiments, however, the ignition features **235** can be positioned at other locations relative to the valve seat **221** including, for example, at a location spaced apart from the valve seat **221** and proximate to the interface **211** of the combustion chamber **212**.

The first end portion **223** of the valve **218** is operably coupled to a valve operator assembly **225**. The valve operator assembly **225** is configured to selectively move the valve **218** between the open and closed positions. More specifically, the valve operator assembly **225** includes a driver **220** operably coupled to the valve **218**, a force generator **226** (shown schematically) configured to induce movement of the driver **220**, and a processor or controller **222** operably coupled to the force generator **226**. The force generator **226** can be any suitable type of force generator for inducing movement of the driver **220** including, for example, electric, electromagnetic, magnetic, and other suitable force generators as disclosed in any of the patents and patent applications incorporated by reference above. Moreover, the controller **222** can also be coupled to one or more sensors positioned throughout the injector **200**.

The driver **220** is coaxially disposed over the first end portion **223** of the valve **218** and includes a stop cavity **228** having a first contact surface **229** that engages the one or more stop collars **230** on the first end portion **223** of the valve **218**. A biasing member or spring **232** engages a second contact surface **231** of the driver **220** opposite the first contact surface **229**. The spring **232** is positioned within a spring cavity **233** in the base portion **206**. Accordingly, the spring **232** urges the driver **220** in a direction away from the nozzle portion **208** (e.g., toward the base portion **206**). As the spring **232** urges the driver **220** toward the base portion **206**, the first contact surface **229** engages the stop collar **230** on the valve **218** to tension the valve **218** or otherwise urge the valve **218** toward the base portion **206** to retain the sealing end portion **219** of the valve **218** against the valve seat **221** in a normally closed position. In certain embodiments, the valve operator assembly **225** can also include one or more additional biasing members **236**, such as electromagnets or permanent magnets, which can selectively bias the driver **220** toward the base portion **206** to tension the valve **218** in the normally closed position between injection events.

The base portion **206** also includes a fuel fitting or inlet **238** configured to introduce fuel into the injector **200**. The fuel can travel from the fuel inlet **238** through the force generator **226** as indicated by base portion fuel paths **239**. The fuel exits the force generator **226** through multiple exit channels **240** fluidly coupled to a fuel flow path or channel **224** extending longitudinally adjacent to the core assembly **213**. More specifically, the fuel flow path **224** extends between the valve **218**

and an inner surface of an insulative body 242 of the middle portion 204 and the nozzle portion 208. The electrically insulated body 242 can be made from a ceramic or polymer insulator suitable for containing the high voltage developed in the injector 200, as disclosed in the patent applications incorporated by reference in their entireties above. When the sealing end portion 219 of the valve 218 contacts the valve seat 221, the sealing end portion 219 seals or otherwise closes the fuel flow path 224. However, as the driver 220 opens the valve 218, fuel flows toward the combustion chamber 212 past the valve seat 221 and sealing end portion 219. As fuel flows toward the combustion chamber 212, the ignition conductor 214 conveys DC and/or AC voltage from 209 to ionization initiation features 234 to ionize and rapidly propagate and thrust the fuel toward the combustion chamber. In certain embodiments, for example, when the force generator 226 actuates the driver 220 to in turn move the valve 218, fuel flows by the ignition features 234 of the ignition conductor 214. As the fuel flows, the ignition features 234, the ignition features 234 generate an ignition event to partially or substantially ionize the fuel by application of ionizing voltage to the voltage terminal 227 via the voltage supply conductor 209. More specifically, ignition voltage applied to the ignition features 234 develops plasma discharge blasts of ionized fuel that is rapidly accelerated and injected into the combustion chamber 212. Generating such high voltage at the ignition features 234 initiates ionization, which is then rapidly propagated as a much larger population of ions in plasma develops and travels outward to thrust fuel past the interface 211 into the combustion chamber 212 into surplus air to provide insulation of more or less adiabatic stratified chamber combustion. As such, the injector 200, as well as other injectors described herein, is capable of ionizing air within the injector prior to introducing fuel into the ionized air, ionizing fuel combined with air, as well as layers of ionized air without fuel and ionized fuel and air combinations, as disclosed in the patent applications incorporated by reference in their entireties above.

FIG. 3A is a cross-sectional side view of an integrated injector/igniter 300a ("injector 300a") configured in accordance with another embodiment of the disclosure. The injector 300a illustrated in FIG. 3A includes several features that are generally similar in structure and function to the corresponding features of the injectors described above with reference to FIGS. 1-2B. For example, as shown in FIG. 3A, the injector 300a includes a body 302 having a middle portion 304 extending between a first end portion or base portion 306 and a second end portion or nozzle portion 308. The nozzle portion 308 at least partially extends into an injection port 307 in a cylinder head 310. In certain embodiments, the nozzle portion 308 is configured to fit within an injection port 307 having a diameter D of approximately 8.4 millimeters (0.33 inch) or less, such as modern diesel injection ports, for example. In other embodiments, however, the nozzle portion 308 can fit within a diameter D that is larger. The injector 300a also includes a valve operator assembly 325 carried by the base portion 306. The valve operator assembly 325 is operably coupled to a core assembly 313 for injecting and igniting fuel into a combustion chamber 312.

The core assembly 313 includes a stationary core insulator 316 coaxially disposed over a stationary ignition member or conductor 314. The ignition conductor 314 can include one or more sensors or fiber optic cables 317 extending longitudinally therethrough to transmit data from the combustion chamber 312 to the valve operator assembly 325 or another controller. The core assembly 313 also includes a tube valve 318 coaxially disposed over the core insulator 316. The valve

318 includes a first end portion **323** at the base portion **306** that engages the valve operator assembly **325**. The valve **318** also includes a second or sealing end portion **319** that engages or otherwise contacts a valve seat **321** carried by a body insulator **342**. The valve operator assembly **325** actuates or moves the valve **318** along the core insulator **316** between an open position (as shown in FIG. 3A) and a closed position. In the open position, the sealing end portion **319** of the valve **318** is spaced apart from the valve seat **321** to allow fuel to flow from a fuel flow path or channel **324** past the valve seat **321** into the nozzle portion **308**. The fuel flow channel **324** extends through the body **302** in an annular space between the valve **318** and the body insulator **342**.

In the embodiment shown in FIG. 3A, the sealing end portion **319** of the valve **318** is smaller than the injection port **307**. More specifically, the sealing end portion **319** has a maximum outer diameter that is less than the diameter **D** of the injection port **307**. As also shown in the illustrated embodiment, the sealing end portion **319** is spaced apart from a combustion chamber interface **311** by a relatively large distance or length **L**. More specifically, in the illustrated embodiment, the length **L** is approximately equal to a thickness of the engine head **310**, which can be 12 or more inches in some cases. In other embodiments, however, and as described in detail below with reference to FIG. 3B, for example, the sealing end portion **319** of the valve **318** can be positioned at other locations relative to the interface **311**. Accordingly, the injector **300a** illustrated in FIG. 3A is configured to account for a relatively large length **L** between the combustion chamber interface **311** and the sealing end portion **319** of the valve **318**. In modern diesel engines or other large engines, for example, crowded intake and exhaust valve train mechanisms may require separation lengths **L** of 12-36 inches, or more.

According to additional features of the illustrated embodiment, the injector **300a** also includes one or more ignition features **334** extending along a portion of the ignition conductor **314**. The ignition features **334** are configured to generate an ionization, propulsive thrust and/or ignition event with the head **310**. More specifically, as shown in FIG. 3A the ignition features **334** can be made of a conductive material that is spirally wound around the ignition conductor **314** in a coiled or corkscrew configuration including brush-like whisker or rod-like conductors. The ignition features **334** accordingly extend away from the ignition conductor **314** toward the inner surface of the injection port **307**. When ignition energy is applied to the ignition features **334** via the ignition conductor **314**, the ignition features **334** generate an ignition event (e.g., a plasma spark) to ignite or ionize fuel, air, and/or air and fuel mixtures. In embodiments where the ignition event is a plasma event, ignition by the plasma blast ionizes the fuel and accelerates the ionized fuel into the combustion chamber **312**.

FIG. 3B is a cross-sectional side view of an integrated injector/igniter **300b** ("injector **300b**") configured in accordance with yet another embodiment of the disclosure. The illustrated injector **300b** includes several of the same features of the injector **300a** illustrated in FIG. 3A. For example, the injector **300b** illustrated in FIG. 3B includes the core assembly **313** operably coupled to the valve operator assembly **325**. The core assembly **313** includes the ignition conductor **314**, the core insulator **316**, and the valve **318**, and extends from the base portion **306** at least partially into the nozzle portion **308**. In the illustrated embodiment, however, the sealing end portion **319** of the valve **318** is positioned adjacent to or slightly recessed from the interface **311** of the combustion chamber **312**. More specifically, the valve seat **321** and the

sealing end portion 319 of the valve 318 are positioned in the injection port 307 at a location that is adjacent or proximate to the combustion chamber interface 311. Accordingly, the ignition conductor 314 includes one or more ignition features downstream from the sealing end portion 319 of the valve 318 and proximate to the combustion chamber interface 311 to generate the ignition event at the combustion chamber interface 311.

FIG. 4 is a cross-sectional side view of an integrated injector/igniter 400 (“injector 400”) configured in accordance with another embodiment of the disclosure. The injector 400 illustrated in FIG. 4 includes several features that are generally similar in structure and function to the corresponding features of the injectors described above with reference to FIGS. 1-3B. For example, as shown in FIG. 4, the injector 400 includes a body 402 having a middle portion 404 extending between a first end portion or base portion 406 and a second end portion or nozzle portion 408. The nozzle portion 408 is configured to extend into a threaded 14 millimeter spark plug port in a cylinder head or it may have a nozzle such as shown in FIG. 1, 3A, 3B, or 6 to fit within a port having a diameter of approximately 8.4 millimeters (0.33 inch) or less, as found in many modern diesel injection ports for example. In other embodiments, however, the nozzle portion 408 can be configured for different sized injection ports. The nozzle portion 408 may further include another thread selection exterior surface 409 for suitable secure engagement with respect to the combustion chamber.

The injector 400 also includes a valve operator assembly 425 carried by the base portion 406. The valve operator assembly 425 is operably coupled to a core assembly 413 for injecting and igniting fuel in a combustion chamber. The core assembly 413 includes a stationary core insulator 416 coaxially disposed over a stationary ignition member or conductor 414. The ignition conductor 414 can include one or more sensors or fiber optic cables 417 extending longitudinally therethrough to transmit data from the combustion chamber to the valve operator assembly 425, which can include a controller or processor 422 or a wireless or cable connected communication node to a suitable computer, controller or processor. In the illustrated embodiment, the ignition conductor 414 includes an enlarged or expanded end portion 433 configured to be proximate to the interface with the combustion chamber. The expanded end portion 433 provides an increased area for the fiber optic cables 417 at the interface with the combustion chamber. The expanded end portion 433 also carries one or more ignition features 434 that are configured to generate an ignition event with an inner surface 437 of the nozzle portion 408. More specifically, in the illustrated embodiment the ignition features 434 can include a plurality of threads or acicular protrusions extending circumferentially around the expanded end portion 433 of the ignition conductor 414. The expanded end portion 433 also includes a valve seat 421, as described in further detail below.

The core assembly 413 extends through an insulative body 442 of the body 402. The insulative body 442 can be made from a ceramic or polymer insulator suitable for containing the high voltage developed in the injector 400. The core assembly 413 also includes a tube valve 418 coaxially disposed over the core insulator 416. In the embodiment illustrated in FIG. 4, however, the valve 418 is an inwardly opening valve (e.g., opening in a direction away from the combustion chamber) and is movable relative to the core insulator 414 to selectively introduce fuel from the nozzle portion 408 into the combustion chamber. More specifically, the valve 418 is configured to slide or otherwise move relative to the core insulator 416 in directions that are generally par-

allel to a longitudinal axis of the injector 400. The valve 418 can be similar in structure to the valve described above and can include, for example, a light weight but strong graphite structural core reinforced by a carbon-carbon layer. The valve 418 includes a first end portion 423 in the base portion 406 that engages the valve operator assembly 425. The valve 418 also includes a second or sealing end portion 419 that engages or otherwise contacts a valve seat 421 in the nozzle portion 408 carried by an ignition conductor 414. The sealing end portion 419 and/or the valve seat 421 can include one or more elastomeric portions as described in detail above. The valve operator assembly 425 actuates the valve 418 relative to the core insulator 416 between an open position (as shown in FIG. 4) and a closed position. In the open position, the sealing end portion 419 of the valve 418 is spaced apart from the valve seat 421 to allow fuel to flow from a fuel flow path or channel 424 past the valve seat 421 and out of the nozzle portion 408. The fuel flow channel 424 extends through the middle portion 404 between the valve 418 and the core insulator 416.

The valve operator assembly 425 includes a force generator 426 (e.g., an electric, electromagnetic, magnetic, etc. force generator) that induces movement of a driver 420. The force generator 426 can also be operably coupled to a processor or controller 422, which can in turn also be coupled to the one or more fiber optic cables 417 extending through the ignition conductor 414. As such, the controller 422 can selectively energize or otherwise activate the force generator 426, for example, in response to one or more combustion chamber conditions or engine parameters. The driver 420 engages one or more stops 430 integrally formed with or otherwise attached to the first end portion 423 of the valve 418 to move the valve 418 between the open and closed positions. The valve operator assembly 425 can also include a first biasing member 432 that contacts the valve 418 and at least partially urges the valve 418 to the closed position in a direction toward the nozzle portion 408. The valve operator assembly 425 can further include a second biasing member 435 that at least partially urges the driver 420 toward the nozzle portion 408. In certain embodiments, the first biasing member 432 can be a spring, such as a coil spring, and the second biasing member 435 can be a magnet or a permanent magnet. In other embodiments, however, the first biasing member 432 and the second biasing member 435 can include other components suitable for providing a biasing force against the valve 418 and the driver 420.

According to additional features of the embodiment illustrated in FIG. 4, the nozzle portion 408 can include additional features for detecting or otherwise collecting and transmitting data from the combustion chamber to one or more controllers via the injector 400. For example, the nozzle portion 408 can include one or more openings 491 in the sealing end portion 419 of the valve 418, to allow relevant data from the combustion chamber to be at least partially transmitted through the injector 400. The nozzle portion 408 can further include a pressure seal 493 carried by the valve seat 421, as well as one or more temperature sensors 495 carried by the fiber optic cables 417. These detecting features can be configured for detecting, sensing, or otherwise transmitting relevant combustion chamber data, such as temperature data, optical data, pressure data, thermal data, acoustic data, and/or any other data from the combustion chamber.

In operation, fuel enters the base portion 406 via a fuel fitting or inlet 438. The fuel inlet 438 introduces the fuel into the force generator 426, and the fuel exits the force generator 426 through multiple exit channels 440 fluidly coupled to the fuel flow path 424 extending longitudinally adjacent to the core assembly 413. As the valve operator assembly 425

moves the valve **418** from the closed position to the open position (e.g., in a direction away from the combustion chamber), the nozzle portion **408** injects and ignites the fuel. More specifically, when the force generator **426** induces the movement of the driver **420**, the driver **420** moves a first distance D_1 prior to contacting the stop **430** carried by the valve **418**. As such, the driver **420** can gain momentum or kinetic energy before engaging the valve **418**. After the driver **420** contacts the stop **430**, the driver **420** continues to move to a second distance D_2 while engaging the valve **418** to exert a tensile force on the valve **418** and move the valve **418** to the open position. As such, when the valve is in the open position (as illustrated in FIG. 4), the sealing end portion **419** of the valve **418** is spaced apart from the valve seat **421** by an open distance generally equal to the second distance D_2 minus the first distance D_1 . As the fuel flows past the open sealing end portion **419** of the valve **418**, the one or more ignition features **434** can generate a fuel ionization, air ionization and/or an ionization of mixed fuel and air event to combust the fuel as a stratified charge in the combustion chamber. The drivers or actuators of any of the injectors described herein can accordingly move a predetermined distance to at least partially gain momentum before engaging the corresponding valve.

FIG. 5A is a cross-sectional side view of an integrated injector/igniter **500** ("injector **500**") configured in accordance with another embodiment of the disclosure. The injector **500** illustrated in FIG. 5 includes several features that are generally similar in structure and function to the corresponding features of the injectors described above with reference to FIGS. 1-4. For example, as shown in FIG. 5, the injector **500** includes a body **502** having a middle portion **504** extending between a first end portion or base portion **506** and a second end portion or nozzle portion **508**. The nozzle portion **508** is configured to extend into a threaded injection port in a cylinder head as shown, or it may be configured as shown in FIG. 1, 3A or 3B or 6 to fit within a port having a diameter of approximately 8.4 millimeters (0.33 inch) or less, as found in many modern diesel injection ports for example. In other embodiments, however, the nozzle portion **508** can be configured for different sized injection ports. The nozzle portion **508** may further include any number of alternate thread selections on the exterior surface **509** for suitable engagement with the combustion chamber.

The injector **500** also includes a valve operator assembly **525** at the base portion **506**. The valve operator assembly **525** is configured to actuate multiple valves positioned throughout the body **502** of the injector **500**. More specifically, the valve operator assembly **525** includes a force generator **526** (e.g., a piezoelectric, electromagnetic, magnetic, etc. force generator) that induces movement of a driver **520**. The force generator **526** can also be operably coupled to a processor or controller to selectively pulse or activate the force generator **526**, for example, in response to one or more combustion chamber conditions or engine parameters. The driver **520** engages a first check valve or base valve **554** at the base portion **506**. More specifically, the base valve **554** may include one or more stops **530** that engage the driver **520** such that the driver **520** moves the base valve **554** between open and closed positions (the base valve **554** is shown in the closed position in FIG. 5A). The one or more stops **530** can be attached to or otherwise integrally formed with a first end portion **555** of the base valve **554**. The base valve **554** also includes a base valve head or sealing portion **556** opposite the first end portion **555** of conduit component **542** as shown. Thus base valve head **556** engages a corresponding valve seat **558** at a transition from the base portion **506** to the middle portion **504** of the injector **500**.

According to additional features of the illustrated embodiment, the injector 500 also includes an insulative body 542 extending through at least the middle portion 504 and the nozzle portion 502. The insulative body 542 can be made from a ceramic or polymer insulator suitable for containing the high voltage developed in the injector 500. The injector 500 further includes a fuel flow path extending through the insulative body 542. More specifically, in the injector 500 includes a first fuel flow section 562 extending away from the check valve 554 into the middle portion 504. The first fuel flow section 562 is fluidly coupled to a second fuel flow section 564 and extends from the middle portion 504 into the nozzle portion 508.

In certain embodiments, the first fuel flow section 562 and the second fuel flow section 564 can be made from materials that accommodate fuel expansion and contraction to at least partially prevent fuel dribble from the nozzle portion 508 at the combustion chamber interface. More specifically, each of the first fuel flow path 562 and the second fuel flow path 564 can include one or more channels extending through a closed cell spring, such as a closed cell foam spring, having a suitable cross-section to allow the fuel to flow therethrough. In certain embodiments, the first and second flow paths 562, 564 can be made from materials with suitable thermal and chemical resistance, as well as fatigue resistance. More specifically, these materials can include silicone, fluorosilicone, and various fluoropolymers including, for example, PFA, PTFE, PVDF, and other copolymers. These components can be extruded or injection molded with numerous open or closed cells or closed volumes that are filled with a gas or working fluid. For example, such a gas can include argon, carbon dioxide, nitrogen, etc, and such a working fluid can include ammonia, propane, butane, fluorinated methane, ethane, or butane. Moreover, this gas or working fluid provides an inventory of liquid and vapor that can serve as an evaporant upon heat addition, and a phase condenser upon heat loss, to thereby serve as a combined spring and thermal flywheel or barrier against adverse expansion and fuel dribble at the combustion chamber interface.

FIGS. 5B and 5D illustrate various embodiments of suitable cross-sectional shapes of the first fuel flow path 562, and FIGS. 5C and 5E illustrate various embodiments of suitable cross-sectional shapes of the second fuel flow path 564. More specifically, FIG. 5B is a cross-sectional view of the first flow path 562 taken substantially along lines 5B-5B of FIG. 5A. In the embodiment illustrated in FIG. 5B, the first fuel flow path 562 includes a first flow path guide 565 including multiple first flow passages or channels 567. The first guide 565 can be made from a closed cell spring material, and the channels 567 extend longitudinally through the first guide 565. FIG. 5C is a cross-sectional view of the second flow path 564 taken substantially along lines 5C-5C of FIG. 5A. In the embodiment illustrated in FIG. 5C, the second flow path 564 includes a second flow path guide 569 including multiple separate regions or sections 563 with corresponding second flow passages or channels 571. Although six regions 563 are shown in the illustrated embodiment, in other embodiments the second guide 569 can include a greater or lesser number of second channels 571. The second flow channels extend longitudinally through the second guide 569. FIG. 5D is a cross-sectional view of an alternative embodiment of the first flow path 562 taken substantially along lines 5B-5B of FIG. 5A. In the embodiment illustrated in FIG. 5D, the first fuel flow path 562 includes a first flow path guide 565 including a cross-shaped first flow passage or channel 567. The first guide 565 can be made from a closed cell spring material, and the channel 567 extends longitudinally through the first guide

565. FIG. 5E is a cross-sectional view of the second flow path **564** taken substantially along lines 5C-5C of FIG. 5A. In the embodiment illustrated in FIG. 5E, the second flow path **564** includes a second flow path guide **569** including multiple a second star shaped flow passages or channel **571**. The second flow channel **571** extends longitudinally through the second guide **569**.

Referring again to FIG. 5A, at the nozzle portion **508** the injector **500** further includes a radially expanding sleeve or flow valve **566** operably coupled to a core or ignition assembly **575**. The ignition assembly **575** includes a stationary ignition conductor **576** coaxially disposed over at least a portion of the second flow section **564**. In certain embodiments, the ignition conductor **576** can be a conductive casing or cover, such as a metallic casing or metallic plated ceramic, disposed over the second flow section **564**. The ignition conductor **576** is coupled to a voltage supply conductor **509** via a voltage terminal **574**. The voltage supply conductor **509** is in turn coupled to a suitable voltage source. In one embodiment, the ignition terminal **574** can supply at least approximately 80 KV (DC or AC) to the ignition conductor **576**. In other embodiments, however, the ignition terminal **574** can supply a greater or lesser voltage to the ignition conductor **576**. The ignition assembly **575** also includes an ignition adapter **578** coupled to the ignition conductor **576**. The ignition adapter **578** provides one or more fuel passage ways **578H** and is also coupled to a nozzle ignition conductor or rod **580**. The ignition rod **580** is threadably received into the ignition adapter **578** and extends from the ignition adapter **578** to a distal end portion of the nozzle portion **508** to be positioned at the interface with the combustion chamber. In the illustrated embodiment, the ignition rod **580** includes an ignition member or electrode **584** positioned at the nozzle portion **508**. The ignition electrode **584** can be a separate component that is attached to the ignition rod **580**. In other embodiments, however, the ignition electrode **584** can be integrally formed with the ignition rod **580**. Moreover, the ignition features **586** can include smooth portions and/or acicular threads or other types of projections extending circumferentially away from the ignition electrode **584**. The ignition electrode **584** and corresponding ignition features **586** remain stationary and act as a first electrode. The inner diameter of the nozzle portion **508** acts as a corresponding second electrode for creating an ignition event, such as a plasma ignition event, with the ignition features **586**.

The ignition assembly **575** also includes an ignition insulator **582** coaxially disposed over at least a portion of the ignition electrode **584**. The ignition insulator **582** can be made from a suitable insulative or dielectric material and accordingly insulates ignition rod **580** from the ignition electrode **509**. The ignition insulator **582** includes an enlarged end portion **583** having a greater cross-sectional dimension (e.g., diameter) adjacent to the ignition electrode **584**. The enlarged end portion **583** is configured to contact the flow valve **566** as shown during the normally closed position. According to additional features of the illustrated embodiment, the nozzle portion **508** may also include one or more biasing members **581** configured to bias or otherwise attract portions of the flow valve **566**.

In the illustrated embodiment the flow valve **566** is a radially opening or expanding flow valve. More specifically, the flow valve **566** is a deformable or elastomeric sleeve valve **566** that is coaxially disposed over at least a portion of the second fuel flow section **564**, the ignition conductor **576**, the ignition adapter **578**, the ignition rod **580**, and the ignition insulator **582** as shown. The flow valve **566** includes a first or stationary end portion **568** that is anchored, adhered, or oth-

erwise coupled to the ignition conductor 576 at a location downstream from the ignition insulator 582. For example, the first end portion 568 can be adhered to the ignition conductor 576 with a suitable adhesive, thermopolymer, thermosetting compound, or other suitable adhesive. The flow valve 566 further includes a second deformable or movable end portion 570 opposite the stationary end portion 568. The movable end portion 570 contacts the enlarged end portion 583 of the ignition insulator 582 and is configured to at least partially radially expand, enlarge, or otherwise deform to allow fuel to exit the nozzle portion 508 of the injector 500. Further details of the embodiments of the flow valve 566 are discussed below with reference to FIGS. 5F and 5G.

FIG. 5F is a side view of one embodiment of a first flow valve 566a configured in accordance with an embodiment of the disclosure and that can be used in the nozzle portion 508 of the injector 500 of FIG. 5A. In the embodiment shown in FIG. 5F, the first flow valve 566a has a generally cylindrical or tubular sleeve shape that includes the first or stationary end portion 568 opposite the second deformable or movable end portion 570. The first flow valve 566a can include an attachment collar or stop 569 extending around at least a portion of the stationary end portion 568. The attachment stop 569 is configured to help retain the stationary end portion 568 at the desired location on the ignition conductor 576 by at least partially engaging the insulative body 542 (FIG. 5A). According to additional features of the illustrated embodiment, the deformable or movable end portion 570 can include multiple spaced apart deformable finger portions or reeds 571. The reeds 571 are positioned in the nozzle portion 508 to at least partially overlap and contact the enlarged end portion 583 of the ignition insulator 582. Moreover, the reeds 571 are configured to deform or otherwise expand radially outwardly as illustrated by reeds 571 shown in broken lines. As such, the pressurized fuel and/or one or more actuators can deflect or deform one or more of the reeds 571 to allow the fuel to exit through normally covered and closed ports to provide fuel injection from the nozzle portion 508 of the injector 500. In one embodiment, the first flow valve 566a can be made from a metallic material, such as spring steel. In other embodiments, however, the first flow valve can be made from a suitable elastomer.

FIG. 5G is a side view of a second flow valve 566b configured in accordance with an embodiment of the disclosure and that can also be used in the nozzle portion 508 of the injector 500 (FIG. 5A). The second flow valve 566b is generally similar in structure and function to the first flow valve 566a shown in FIG. 5B. The second flow valve 566b, however, does not include separate deformable portions or reeds. Rather, the second flow valve 566b includes a second deformable or movable end portion 570 that has a generally cylindrical or tubular sleeve shape. The deformable end portion includes multiple spaced apart deformable sections 573 that are deposited on the second flow valve 566b. More specifically, in one embodiment the second flow valve 566b can be made from a suitable elastomer or other deformable material, and the deformable sections 573 can include discrete sections or segments of a deposited ferromagnetic material, such as a metallic coating. For example, the deformable sections 573 can include a metallic coating comprised of materials such as glass iron, an iron cobalt alloy (e.g., approximately 48% cobalt and 52% iron), iron chrome silicon, or other suitable iron alloys. As such, the deformable sections 573 can selectively deform the second end portion 570 of the second flow valve 566 in response to a magnetic force applied to the second flow valve 566.

Referring again to FIG. 5A, according to additional features of the illustrated embodiment, the injector **500** also includes a fuel exit passage **572** in the nozzle portion **508** positioned between the flow valve **566** and the ignition insulator **582**. The fuel exit passage **572** is fluidly coupled to the second fuel flow section **564** via the ignition adapter **578**. During operation, fuel is introduced into the fuel exit passage **572** and selectively dispersed from the nozzle portion **508** by actuation of the flow valve **566**. More specifically, during operation fuel enters the fuel injector **500** into the base portion **506** via a first fuel fitting or inlet **538a**. The first fuel inlet **538a** introduces the fuel into the force generator **526**, and the fuel exits the force generator **526** through multiple exit channels **540**. The exit channels **540** are fluidly coupled to a fuel flow path or channel **524**. In other embodiments, however, the base portion **506** can include an optional second fuel inlet **538b** (shown in broken lines) to introduce the fuel directly into the fuel flow path **524**, rather than through the force generator **526**. The driver **520** includes multiple fuel flow channels or passages extending therethrough to allow the fuel to flow to an intermediate fuel flow volume **560**. When the base valve head **556** rests against the valve seat **558**, the base valve head seals the intermediate fuel flow volume **560**.

As the valve operator assembly **525** moves the check valve or base valve **554** to the open position by lifting the base valve head **556** off of the valve seat **558**, the pressurized fuel is introduced into the first fuel flow section **564**. In certain embodiments, for example, the force generator **526** can actuate the driver **520** to move a first distance prior to contacting the stop **530** on the base valve **554**. After gaining momentum and contacting the stop **530**, the driver **520** can move a second distance along with the base valve **554** to open the base valve head **556**. The pressurized fuel then flows from the first fuel flow section **564** through the second fuel flow section **566** and through the ignition adapter **578** into the fuel exit passage **572**. In one embodiment, the pressure of the fuel in the fuel exit passage **572** is sufficient to at least partially radially expand or otherwise deform the movable end portion **570** of the flow valve **566** to allow the fuel to flow past the enlarged end portion **583** of the ignition insulator **580**. The position of the flow valve **566** in the nozzle portion **508** accordingly prevents dribble or undesired trickle of fuel from the nozzle portion **508**. In other embodiments, one or more actuators, drivers, selective biasing members, or other suitable force generators can at least partially radially expand or otherwise deform the movable end portion **570** of the flow valve **566**. As the flow valve **566** selectively dispenses the fuel from the fuel exit passage **572**, the fuel flows past the one or more ignition features **586** that can generate an ignition event to ignite and inject the fuel into the combustion chamber.

FIG. 6 is a cross-sectional side view of an integrated injector/igniter **600** ("injector **600**") configured in accordance with yet another embodiment of the disclosure. As explained in detail below, the injector **600** is particularly suited for large engine applications including, for example, gas turbines and various high-speed rotary combustion engines to operate with multiple fuel selections and/or multiburst applications. The injector **600** is also particularly suited for applications including relatively small injection ports as described above. The injector **600** illustrated in FIG. 6 includes several features that are generally similar in structure and function to the corresponding features of the injectors described above with reference to FIGS. 1-5G. For example, as shown in FIG. 6, the injector **600** includes a body **602** having a middle portion **604** extending between a first or base portion **606** and a second or nozzle portion **608**. The nozzle portion **608** is configured to extend into an injection port in a cylinder head, such as a port

having a diameter of approximately 8.4 millimeters (0.33 inch) or less, as found modern diesel injection ports for example. In other embodiments, however, the nozzle portion 608 can be configured for different sized injection ports.

The injector 600 further includes one or more base assemblies 629 (identified individually as a first base assembly 629a and a second base assembly 629b) configured to receive fuel into the base portion 606 of the injector 600 and selectively meter the fuel to the nozzle portion 608. More specifically, each base assembly 629 includes a valve operator assembly 625 configured to actuate a corresponding poppet or base valve 654. More specifically, the valve operator assembly 625 includes a force generator 626 (e.g., an electric, electromagnetic, magnetic, etc. force generator) that induces movement of a driver 620. The force generator 626 can also be operably coupled to a corresponding controller or processor 622 (identified individually a first controller 622a and a second controller 622b) to selectively pulse or actuate the force generator 626, for example, in response to one or more combustion chamber conditions or other engine parameters. The driver 620 engages a first check valve or base valve 654 at the base portion 606. More specifically, the base valve 654 includes one or more stops 630 that engage a biasing member 617 (e.g., a coil spring) positioned in a biasing member cavity 619 to bias the base valve towards a closed position as shown in FIG. 6 (e.g., in a direction toward the nozzle portion 608). The base valve stop 630 also engages the driver 620 such that the driver 620 moves the base valve 654 between the open and closed positions. The base valve 654 also includes a base valve head or sealing portion 656 that engages a corresponding valve seat 658 in the normally closed position as shown.

According to additional features of the illustrated embodiment, the injector 600 also includes a fuel inlet fitting 638 (identified individually as a first fuel inlet fitting 638a and a second fuel inlet fitting 638b) operably coupled to the corresponding base assembly 629 to introduce the fuel into the base assembly 629. In each base assembly 629, the fuel flows through the force generators 626 and the driver 620 to move past the base valve head 656 when the base valve is in the open position. The injector 600 further includes fuel connecting conduits 657 (identified individually as a first fuel connecting conduit 657a and a second fuel connecting conduit 657b) to transport the fuel from the base portion 606 to a fuel flow path or channel 624 extending through the middle portion 606 and the nozzle portion 608 of the body 602. The fuel flow channel 624 extends longitudinally adjacent to a core assembly 613, which extends through the body 602 from the base portion 606 at least partially into the nozzle portion 608. The core assembly 613 includes a core insulator 616 coaxially disposed over an ignition member or conductor 614. The core assembly 613 also includes a cylindrical or tubular enclosure member 688 that at least partially defines the fuel flow channel 624 with the ignition insulator 616. The core assembly 613 extends through an insulative body 642 of the body 402. The ignition conductor 614 is operably coupled to an ignition terminal 627 to supply an ignition voltage to the ignition electrode 684 having one or more ignition features 686. The ignition electrode 684 is a first electrode that can generate ignition events with a second electrode 685, which can be a conductive portion of the distal end of the nozzle portion 608. The ignition insulator 616 includes an enlarged end portion 683 having a greater cross-sectional dimension (e.g., a greater cross-sectional diameter) adjacent to the ignition electrode 684.

The enlarged end portion 683 of the ignition insulator 616 is configured to contact a flow control valve 666 carried by the nozzle portion 608. The flow valve 666 is a radially expanding



valve that includes a first or stationary end portion **668** that is anchored, adhered, or otherwise coupled to the enclosure member **688** at a location downstream from the enlarged end portion **683** of the ignition insulator **616**. For example, the first end portion **668** can be adhered to an outer surface of the enclosure member **688** with a suitable adhesive, thermopolymer, thermosetting compound, or other suitable adhesive. The flow valve **666** further includes a second deformable or movable end portion **670** opposite the stationary end portion **668**. The movable end portion **670** contacts the enlarged end portion **683** of the ignition insulator **682** and is configured to at least partially radially expand, enlarge, or otherwise deform to allow fuel to exit the nozzle portion **608** of the injector **600**. More specifically, the enclosure member **688** includes multiple fuel exit ports **669** adjacent to the movable end portion **670** of the flow valve **666**.

During operation, fuel is introduced into the base assembly **629** via the fuel inlet fitting **638**. The fuel flows through the force generator **626** and the driver **622** to arrive at the base valve head **656**. When the valve operator assembly **625** moves the valve **654** to the open position to space the base valve head **656** apart from the valve seat **658**, the fuel flows past the base valve head **656** and into the fuel connecting conduits **657**. From fuel connecting conduits **657**, the pressurized fuel flows into the fuel flow channel **624**. In one embodiment, the pressure of the fuel in the fuel flow channel **624** is sufficient to at least partially radially expand or otherwise deform the movable end portion **670** of the flow valve **666** to allow the fuel to flow past the enlarged end portion **683** of the ignition insulator **680**. In other embodiments, however, one or more actuators, drivers, selective biasing members, or other suitable force generators can at least partially radially expand or otherwise deform the movable end portion **670** of the flow valve **666**. As the flow valve **666** selectively dispenses the fuel from the fuel exit ports **669**, the fuel flows past the one or more ignition features **686** that can generate an ignition event to ignite and inject the fuel into the combustion chamber.

In certain embodiments, each base assembly **629**, as well as other fuel flow controllers, can be configured to perform: 1) control of fuel flow by opening any of the valve assemblies, and 2) production of ionizing voltage upon completion of the valve opening function. To achieve both of these functions, in certain embodiments, for example, each force generator **626** can be a solenoid winding including a first or primary winding and a secondary winding. The secondary winding can include more turns than the first winding. Each winding can also include one or more layers of insulation (e.g., varnish or other suitable insulators), however the secondary winding may include more insulating layers than the first winding. The force generator **626** can also be electrically coupled to the conductor **614**. By winding a force generator **626** or solenoid as a transformer with a primary winding and a secondary winding of many more turns, the primary can carry high current upon application of voltage to produce pull or otherwise induce movement of the driver **620** in of the plunger. Upon opening the relay to the primary winding, the driver **620** is released and a very high voltage will be produced by the secondary winding. The high voltage of the secondary winding can be applied to the plasma generation ignition event by providing the initial ionization after which relatively lower voltage discharge of a capacitor that has been charged with any suitable source (including energy harvested from the combustion chamber by photovoltaic, thermoelectric, and piezoelectric generators) continues to supply ionizing current and thrust of fuel into the combustion chamber.

Embodiments of the integrated injector igniters and, in particular, the flow valves disclosed in detail herein provide several advantages over conventional injectors and igniters. One advantage, for example, is that these flow valves have a radially compact shape and configuration that is particularly suited to be positioned in the nozzle portion of an injector used in modern diesel engines or other large engines with very limited size restrictions at the injection port. As noted above, for example, an injection port of a modern diesel engine often has an injection port diameter of about 8.4 mm (0.33 inch). As disclosed herein, these flow valves and associated actuating, insulating, and igniting components can operate within the limited available space. Moreover, positioning these valves at or proximate to the combustion chamber interface can at least partially prevent unwanted fuel dribble. In instances that heat gain tends to cause expansion of fuel to produce pressure between injection events, the embodiments similar to those shown in FIGS. 5B, 5C, 5D, and/or 5E may be used to prevent fuel dribble into the combustion chamber at undesirable times. Moreover, the embodiments of the flow valves disclosed herein are particularly suitable to resonate thereby achieving a very high rate of operation capability. Moreover, the embodiments disclosed herein are able to provide a rigid connection of a valve operator, such as a driver or plunger, with corresponding valve in both inwardly and outwardly opening configurations. In addition, these embodiments provide high temperature operating capabilities for applications in adiabatic engines and other applications that require relatively high admissions of heat from the combustion chamber. Furthermore, these embodiments can provide stationary delivery of ignition voltage to thereby allow delivery of very high voltage and consequent electrode gap currents to rapidly convert liquid fuels as they are injected into high speed blasts of ionized vapors and plasmas. These embodiments can also achieve much greater horsepower rates, such as 10,000 HP per injector for selected gas turbine and large piston engine applications that can accommodate extremely rapid completion of combustion to eliminate the need/use of precombustion chambers and combustion cans. Moreover, these embodiments can also provide for the center ignition or electrode assembly to integrate components and provide composited functions including instrumentation by fibers 617 such as optical filaments, electrical current and voltage conduction to thereby serve as the stationary valve seat for normally closed valve. What's more, these embodiments can have a significantly high dielectric strength capable of 50 KV to 150 KV of ionization voltage at current pulses of 1000 or more instantaneous amps through the ignition electrodes as shown.

In addition, several of the embodiments described in detail above of the fuel injectors may be used in engines that are configured to combust a hydrogen-characterized fuel (e.g., ammonia) or other fuels with low energy density (e.g., carbon monoxide and hydrogen), which may be 3000 times less energy dense than diesel. For example, engines of oceanic tankers that transport liquid methane, propane, ammonia, methanol, and/or other commodities can have operating cost savings when they are equipped with several embodiments of the injectors disclosed herein. In one embodiment, for example, the carried commodity may be reformed using waste heat from the engines as follow:



This is accomplished by converting the propulsion engines (including heat engines such as compression-ignition diesel type engines, various rotary combustion engines, and gas turbines) to operate on fuels that may be reformed from such commodities by endothermic reactions in which the heat rejected by such heat engines is utilized to drive such reactions. In other embodiments, the injector may also be used in power plants, chemical plants, and/or other suitable locations with heat producing engines.

In these types of embodiments, thermo-chemical regeneration using heat rejected by an engine provides attractive fuel savings because the hydrogen characterized fuels that are produced yield 15 to 30% more energy upon combustion than their feedstock. In addition, the embodiments of the injectors disclosed herein can allow hydrogen characterized fuels to combust up to 12 times faster than diesel or bunker fuels, thus greatly improving engine efficiency and eliminating particulates in the exhaust of the engine.

From the foregoing, it will be appreciated that specific embodiments of the disclosure have been described herein for purposes of illustration, but that various modifications may be made without deviating from the spirit and scope of the invention. For example, the dielectric strength of the insulators disclosed herein may be altered or varied to include alternative materials and processing means. The actuators and drivers may be varied depending on fuel and/or the use of the corresponding injectors. Moreover, components of the injector may be varied including for example, the electrodes, the optics, the actuators, the valves, and the nozzles or the bodies may be made from alternative materials or may include alternative configurations than those shown and described and still be within the spirit of the disclosure.

Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise," "comprising," and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in a sense of "including, but not limited to." Words using the singular or plural number also include the plural or singular number, respectively. When the claims use the word "or" in reference to a list of two or more items, that word covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list. In addition, the various embodiments described above can be combined to provide further embodiments. All of the U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in the Application Data Sheet are incorporated herein by reference, in their entirety. Aspects of the disclosure can be modified, if necessary, to employ fuel injectors and ignition devices with various configurations, and concepts of the various patents, applications, and publications to provide yet further embodiments of the disclosure.

These and other changes can be made to the disclosure in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the disclosure to the specific embodiments disclosed in the specification and the claims, but should be construed to include all systems and methods that operate in accordance with the claims. Accordingly, the invention is not limited by the disclosure, but instead its scope is to be determined broadly by the following claims.

I claim:

1. An injector for introducing and igniting fuel at an interface with a combustion chamber, the injector comprising:
 - an injector body including—
 - a base portion configured to receive fuel into the injector body;
 - a nozzle portion opposite the base portion, wherein the nozzle portion is configured to be positioned proximate to the combustion chamber for injecting fuel in the combustion chamber;
 - a body insulator extending through at least a portion of the body; and
 - a valve seat carried by the body insulator, wherein the valve seat is positioned at or proximate to the nozzle portion;
 - a fuel flow path extending through the body; and
 - a core assembly extending through the body coaxially with at least a portion of the fuel flow path, the core assembly including—
 - an ignition rod extending from the base portion to the nozzle portion;
 - an ignition insulator coaxially disposed over the ignition rod, the ignition insulator extending from the base portion at least partially into the nozzle portion; and
 - a valve coaxially disposed over the ignition insulator, wherein the valve includes a sealing head adjacent to the valve seat, and wherein the valve moves along the ignition insulator between an open position in which the sealing head is spaced apart from the valve seat to allow fuel to exit the fuel flow path, and a closed position in which the sealing head at least partially contacts the valve seat to close the fuel flow path.
2. The injector of claim 1 wherein the nozzle portion has a diameter of approximately 0.33 inch or less.
3. The injector of claim 1 wherein the nozzle portion has a length of approximately 12 inches or more.
4. The injector of claim 1, further comprising a valve operator assembly carried by the base portion, the valve operator assembly comprising:
 - a driver surrounding at least a portion of the valve and movable between a first position and a second position, wherein when the driver is in the first position the valve is retained in the closed position, and when the driver moves to the second position the driver engages and moves the valve to the open position;
 - a force generator configured to actuate the driver to move between the first and second positions; and
 - a controller configured to selectively activate the force generator.

5. The injector of claim 4, further comprising a fuel inlet fluidly coupled to the force generator to introduce fuel into the base portion via the force generator.

6. The injector of claim 1 wherein the valve includes a first end portion opposite the sealing head, and wherein the injector further comprises a driver movably positioned in the base portion between a first position and a second position, wherein when the driver is in the first position the valve is retained in the open position, and when the driver moves to the second position the driver engages the first end portion of the valve and moves the valve to the open position.

7. The injector of claim 6 wherein the first end portion of the valve includes a stop, and wherein the driver contacts the stop when the driver engages the first end portion of the valve.

8. The injector of claim 6 wherein the driver moves a predetermined distance before engaging the first end portion of the valve as the driver moves toward the second position.

9. The injector of claim 1, further comprising one or more optical fibers extending through the ignition rod, wherein the one or more optical fibers are configured to transmit combustion chamber data from the combustion chamber to a controller operably coupled to the injector.

10. The injector of claim 1, wherein the ignition rod includes one or more ignition features positioned in the nozzle portion between the sealing head of the valve and the combustion chamber, and wherein the one or more ignition features are configured to generate an ignition event to ignite fuel exiting the nozzle portion.

11. The injector of claim 10 wherein the one or more ignition features are spirally wound around at least a portion of the ignition rod.

12. The injector of claim 1 wherein the sealing head of the valve is spaced apart from the interface with the combustion chamber by a distance of at least approximately 12 inches or more.

13. The injector of claim 1 wherein the sealing head of the valve is configured to be positioned in the nozzle portion adjacent to the interface with the combustion chamber.

14. The injector of claim 1, further comprising a controller for:

selectively controlling the movement of the valve with reference to the ignition insulator; and
selectively controlling an ignition event generated by the ignition rod.

15. The injector of claim 1 wherein the valve has a first length, the ignition insulator has a second length greater than the first length, and the ignition rod has a third length greater than the second length.

16. The injector of claim 1 wherein the valve is an outwardly opening valve moving in a direction toward the combustion chamber when the valve moves from the closed position to the open position.

17. The injector of claim 1 wherein the valve is an inwardly opening valve moving in a direction away from the combustion chamber when the valve moves from the closed position to the open position.

18. The injector of claim 1, wherein the fuel flow path extends through the body between the valve and the body insulator.

19. An injector for introducing fuel into a combustion chamber, the injector comprising:

a body having a first end portion opposite a second end portion, wherein the second end portion is configured to be positioned adjacent to an interface of the combustion chamber and the first end portion is configured to be spaced apart from the combustion chamber;

an ignition conductor extending through the body from the first end portion to the second end portion, wherein the ignition conductor is configured to transmit ignition energy from the first end portion to the second end portion and generate an ignition event proximate to the interface of the combustion chamber;

an insulator extending longitudinally along the ignition conductor and surrounding at least a portion of the ignition conductor;

a valve extending longitudinally along the insulator from the first end portion to the second end portion, wherein the valve includes a sealing end portion, and wherein the valve is movable along the insulator between an open position and a closed position; and

a valve seat at or proximate to the second end portion of the body, wherein when the valve is in the open position the sealing end portion is spaced apart from the valve seat and when the valve is in the closed position the sealing end portion contacts at least a portion of the valve seat.

20. The injector of claim 19 wherein the insulator is a first insulator and wherein the injector further comprises:

a second insulator extending longitudinally along the body and spaced radially apart from the valve; and

an annular fuel flow passage extending from the first end portion to the second end portion between the second insulator and the valve.

21. The injector of claim 19, further comprising a fuel flow passage coaxially disposed around and surrounding the valve.

22. The injector of claim 19 wherein the sealing end portion of the valve comprises an enlarged end portion of the valve having a first diameter that is greater than a second diameter of the valve.

23. The injector of claim 19, further comprising one or more optical sensors extending from the first end portion to the second end portion, wherein the one or more optical fibers are configured to detect or transmit combustion chamber data from the combustion chamber.

24. The injector of claim 23 wherein the one or more optical sensors extend longitudinally through the ignition conductor.

25. The injector of claim 19 wherein the valve further comprises a base portion opposite the sealing end portion, the injector further comprising:

- an actuator positioned in the first end portion, wherein the actuator is movable between a first position and a second position, wherein when the actuator moves from the first position toward the second position the actuator contacts the base portion of the valve and moves the valve from the closed position toward the open position; and

- a force generator positioned in the first end portion adjacent to the actuator, wherein the force generator is configured to activate the actuator to move the actuator between the first and second positions.

26. The injector of claim 19 wherein the valve extends at least partially through the second end portion of the body, and the sealing end portion of the valve is positioned adjacent to the interface of the combustion chamber.

27. The injector of claim 19, further comprising one or more ignition features carried by the ignition conductor, wherein the one or more ignition features are positioned between the sealing end portion of the valve and the interface of the combustion chamber, and wherein the one or more ignition features are configured to generate an ignition event to ignite fuel that passes beyond the sealing end portion of the valve.

28. The injector of claim 19 wherein the second end portion of the body has a diameter of approximately 0.33 inch or less.

29. An injector for introducing fuel into a combustion chamber, the injector comprising:

- a nozzle portion configured to be positioned adjacent to an interface with the combustion chamber;

- a base portion opposite the nozzle portion and configured to be spaced apart from the nozzle portion;

- an ignition conductor at least partially extending through the nozzle portion;

- an ignition insulator coaxially disposed over at least a portion of the ignition conductor; and

- a valve positioned in the nozzle portion and coaxially disposed over at least a portion of the ignition insulator and radially spaced apart from at least a portion of the ignition insulator, wherein the valve includes—

- a first end portion that remains generally stationary with reference to the ignition insulator; and

- a second sealing end portion positioned between the first end portion and the combustion chamber, wherein the second sealing end portion is at least partially deformable in a direction radially away from the ignition insulator to move from a closed position to an open position to inject fuel from the nozzle portion into the combustion chamber.

30. The injector of claim **29** wherein the valve is a first valve, and wherein the injector further comprises a second valve positioned in the base portion, wherein the second valve moves in a direction generally parallel to a longitudinal axis of the injector from a closed position and an open position to allow the fuel to flow from the base portion to the nozzle portion.

31. The injector of claim **30** wherein the second valve is independently movable from the first valve.

32. The injector of claim **29** further comprising a driver movably positioned in the base portion coaxially surrounding at least a portion of the second valve, wherein the driver is movable between a first position and a second position, wherein as the driver moves from the first position toward the second position the driver engages the second valve and moves the second valve from the closed position toward the open position.

33. The injector of claim **29** wherein the ignition conductor is a first ignition conductor, and wherein the injector further comprises a second ignition conductor electrically coupled to the first ignition conductor, wherein the second ignition conductor extends from the nozzle portion toward the base portion and at least partially encases a fuel flow passage extending longitudinally through the injector.

34. The injector of claim **29**, further comprising an ignition terminal at the base portion, wherein the ignition terminal is configured to be operably coupled to an ignition energy source, and wherein the ignition conductor extends from the ignition terminal in the base portion to the nozzle portion.

35. The injector of claim **34** wherein the ignition insulator is coaxially disposed over the ignition conductor and extends from the base portion at least partially into the nozzle portion.

36. The injector of claim **29** wherein the ignition insulator includes an enlarged end portion positioned adjacent to the interface with the combustion chamber, and wherein the second sealing end portion of the valve is positioned adjacent to the enlarged end portion of the ignition insulator.