

METHOD AND DEVICE FOR THE DRILLING OF HOLES IN GROUND OR
ROCKY MATERIAL

The present invention relates to a method for drilling, in
5 particular percussion drilling or rotary percussion
drilling, holes in soil or rock material, wherein a
borehole is formed by a percussive and/or rotational
movement carried out by a drill bit mounted on a drill rod
assembly and an envelope tube and/or a jacket tube is
10 introduced into the borehole, as well as to a device for
drilling, in particular percussion drilling or rotary
percussion drilling, holes in soil or rock material,
wherein a borehole is formed by a percussive and/or
rotational movement carried out by a drill bit mounted on a
15 drill rod assembly and an envelope tube and/or a jacket
tube is capable of being introduced into the borehole.

In the context of methods and devices for drilling and, in
particular, percussion drilling or rotary percussion
20 drilling holes in soil or rock material, various
embodiments are known. Thus, it is, for instance, known to
couple a drill bit directly with a drill rod assembly for
the introduction of impact energy where, for instance, an
envelope and/or jacket tubes is introduced into the
25 interior of the borehole under tensile stress by the drill
bit, appropriate coupling between the envelope tube and/or
the jacket tube and the drill bit being realized on the end
facing away from the working surface. That embodiment
involves the drawback that also the energy required for the
30 introduction of the envelope and/or jacket tubes causing,
for instance, friction resistances by partially abutting on
the borehole wall must be introduced via the drill bit.

In addition, embodiments are known, in which an accordingly
sturdily designed envelope tube is provided, which
cooperates with the drill bit particularly on the outer
5 periphery of the same, such embodiments renouncing the use
of a substantially central drill rod assembly for the
introduction of impact energy. That embodiment, in
particular, involves the disadvantage that a very sturdy
and, hence, heavy jacket tube, which is usually provided
10 for short-distance bores such as, for instance, well bores,
has to be employed for the introduction of the required
excavation energy.

Departing from a method and device of the initially defined
15 kind, the present invention aims to enable the reliable
introduction of excavation or impact energy into the drill
bit as well as into the envelope and/or jacket tubes.

To solve these objects, a method of the initially defined
20 kind is essentially characterized in that the impact energy
introduced by the drill rod assembly is transmitted
partially, particularly centrally, by the drill rod
assembly onto the drill bit and partially via an impact
shoe cooperating with the drill rod assembly onto the
25 envelope and/or jacket tubes . Because of the fact that the
energy or impact energy is transmitted onto the drill bit
separately and, in particular, centrally by the drill rod
assembly and partially onto the envelope and/or jacket
tubes via an impact shoe cooperating with the drill rod
30 assembly, decoupling during the introduction of the drill
bit from the envelope and/or the jacket tubes to be
additionally introduced during the drilling procedure is
feasible. It is, thus, enabled to limit the excavation or

impact energy to be transmitted onto the drill bit to just the extent required for drilling, whereby according to the invention the forces required for the introduction of the envelope and/or jacket tubes can, moreover, be taken into
5 account separately from friction resistances optionally present between the outer peripheries of the envelope and/or jacket tubes and the borehole produced. By such decoupling of the drill bit from the envelope and/or jacket tubes for the introduction of the envelope and/or jacket
10 tubes, it is not necessary, as opposed to known configurations, to introduce the energy required for the introduction of the envelope and/or jacket tubes from the drill rod assembly onto the drill bit and subsequently onto the jacket tube, so that merely the energy required for
15 mining or boring need be transmitted to the drill bit.

To ensure a favorable introduction of the energy required for the entrainment or introduction of the envelope and/or jacket tubes into the interior of the borehole by the
20 impact shoe having a comparatively large outer diameter, it is proposed according to a preferred embodiment that the impact energy is transmitted from the drill rod assembly onto the impact shoe via an interposed impact ring. Such an impact ring allows for the transmission of energy from the
25 centrally arranged drill rod assembly usually having a comparatively small diameter onto the impact shoe having a large diameter, the impact shoe being designed to substantially match the diameter of the envelope and/or jacket tubes coupled therewith. By providing a separate
30 impact ring, it is further possible to take into account the different stresses acting on the individual parts.

For a particularly uniform introduction of energy, or transmission of the same onto the drill bit and the impact ring and impact shoe, respectively, using elements that are simple and cost-effective to produce, it is proposed
5 according to a preferred embodiment that the transmission of the impact energy from the drill rod assembly onto the impact shoe and/or the interposed impact ring and onto the drill bit is each effected via abutment or stop surfaces each enclosing an acute angle with the longitudinal axis of
10 the drill rod assembly or having a spherical calotte shape. Such abutment surfaces each enclosing an acute angle with the longitudinal axis of the drill rod assembly or having a calotte shape, in particular, between the drill rod assembly and the drill bit end facing away from the working
15 surface, are simple to produce with the respective tolerances necessary for a proper force transmission.

For the simple and safe haulage of excavated material, it is proposed according to a further preferred embodiment
20 that excavated material is introduced into an annular space defined between the outer periphery of the drill rod assembly and the inner peripheries of the envelope tube and the adjoining jacket tube via at least one passage opening provided in the working surface of the drill bit, and
25 removed from the borehole. The excavated material can, thus, be directly introduced into the annular space between the drill rod assembly and the envelope tube and jacket tube following upon the drill bit through the at least one passage opening provided in the drill bit so as to ensure
30 the reliable and safe removal of excavated material from the region of the working surface of the drill bit.

In order to enable the proper passage of excavated material, which is discharged through the at least one passage opening provided in the working surface of the drill bit, through the impact ring arranged at a distance
5 from the drill bit and provided to transmit the impact energy from the substantially centrally arranged drill rod assembly onto the impact shoe, it is contemplated according to a particularly preferred embodiment that the impact ring is formed with a passage opening for material haulage,
10 which corresponds with the at least one passage opening of the working surface of the drill bit, and coupled with the drill rod assembly for rotational movement with the drill bit.

15 The completion of a bore, as a rule, is followed by the removal of at least the drill rod assembly from the borehole, whereupon the borehole with the envelope and/or jacket tubes remaining in the borehole is, for instance, filled with a curing mass. For a particularly simple and
20 fast removal of at least the drill rod assembly, after completing the borehole or bore it is proposed according to a further preferred embodiment of the invention that the drill bit and optionally the impact ring are coupled with the drill rod assembly by a plug-in connection, wherein in
25 particular complementary polygonal surfaces of the plug-in connection are provided. Such complementary polygonal surfaces of a plug-in connection allow for the safe coupling with, and reliable force introduction on, the drill bit, while such a plug-in connection readily enables
30 the removal of the drill rod assembly from the drill bit by simple retraction. By providing an impact ring that is separate from the impact shoe, it is, moreover, feasible for the impact ring to remain within the borehole upon

removal of the drill rod assembly such that an impediment during the removal of the drill rod assembly through the impact ring having an enlarged diameter relative to the drill rod assembly, by material optionally remaining in the annular space between the outer periphery of the drill rod assembly and the inner diameters of the envelope and/or jacket tubes need be feared.

To achieve the initially defined objects, a device of the initially defined kind is, moreover, essentially characterized in that the drill bit is capable of being acted upon by the drill rod assembly in its central region and the drill rod assembly acts on an impact shoe cooperating with the envelope and/or jacket tubes. As already pointed out above, a uniform introduction of the impact or excavation energy to be transmitted onto the drill bit is feasible with such an embodiment, whereby the drilling progress or drilling procedure will be accelerated or supported. Furthermore, no special measures have to be taken with regard to partial drill bit zones to be preferably reinforced for the introduction of the impact energy and distribution of the same over the entire working surface. By decoupling the drill bit from the envelope and/or jacket tubes, it is, moreover, feasible to design the drill bit in an accordingly simplified manner, since the forces required for the introduction of the envelope and/or jacket tubes need not be transmitted onto the envelope and/or jacket tubes by the drill bit, but the envelope and/or jacket tubes are introduced into the interior of the borehole via the impact shoe cooperating with the drill rod assembly or acted upon by the same.

To provide simple coupling between the drill rod assembly and the impact shoe and the proper introduction of energy onto the impact shoe for the entrainment of the envelope and/or jacket tubes into the interior of the drill rod assembly, it is provided according to a preferred embodiment that the drill rod assembly is coupled via an interposed impact ring with the impact shoe for the transmission of impact energy onto the envelope and/or jacket tubes.

10

In this context, it is proposed according to a further preferred embodiment that the impact ring is designed to be separate from the impact shoe and the drill rod assembly. This enables individual elements of the device according to the invention to be produced separately from one another and, hence, in a easier manner while, furthermore, ensuring that, upon removal of the drill rod assembly after completion of the bore, as will be further elucidated below, the impact shoe may remain within the borehole besides the drill bit and the envelope and/or jacket tubes so as to enable the simple extraction or removal of the drill rod assembly without having to fear an impediment, during the removal of the drill rod assembly, by excavated material possibly remaining within the borehole on account of the impact ring having a larger external dimension for coupling with the impact shoe.

For the reliable introduction into the interior of the bore hole, of the envelope and/or jacket tubes following upon the drill bit, it is provided according to a further preferred embodiment that the impact shoe is welded with the envelope and/or jacket tubes. By coupling or welding the envelope and/or jacket tubes with the impact shoe, it

30

is ensured that the impact energy to be introduced onto the envelope and/or jacket tubes for the introduction into the borehole, particularly under tensile stress, as in contrast to known configurations will not be initially introduced into the drill bit, whereupon the envelope and/or jacket tubes will be drawn into the borehole via the drill bit, but that decoupling of the advance movement of the drill bit and the entrainment movement of the envelope and/or jacket tubes of the drill bit will take place.

10

For a particularly reliable haulage of excavated material from the region of the drill bit, it is proposed according to a further preferred embodiment that the drill bit on its working surface comprises at least one passage opening for the introduction of material into an annular space defined between the outer periphery of the drill rod assembly and the inner peripheries of the envelope tube and the adjoining jacket tube. At least one such passage opening enables the reliable introduction of excavated material directly from the region of the working surface of the drill bit into the annular space defined between the outer periphery of the drill rod assembly and the inner peripheries of the envelope tube and the adjoining jacket tube.

25

In order to enable the proper transport of excavated material even through the region of the impact ring constituting a coupling between the centrally arranged drill rod assembly and the impact shoe located on the outer periphery, it is provided according to a further preferred embodiment that the impact ring comprises at least one passage opening in alignment with the passage opening(s) of the working surface of the drill bit.

30

To enable as uniform a haulage of excavated material as possible over the total working surface of the drill bit and subsequently through the impact ring, it is provided
5 according to a further preferred embodiment that a plurality of passage openings each at substantially equal angular distances from one another, in particular three passage openings at mutual angular distances of 120° , are provided on the outer peripheral regions of the drill bit
10 and impact ring.

To provide reliable and simple coupling between the drill rod assembly and the drill bit, it is further proposed according to the invention that the drill bit and the
15 impact ring are coupled with the drill rod assembly via plug-in connections, wherein the plug-in connections between the drill bit and the impact ring with the drill rod assembly comprise in particular polygonal stop or abutment surfaces. Such a plug-in connection with polygonal
20 stop or abutment surfaces enables the reliable transmission of force, particularly also under consideration of the rotational movement to be imparted to the drill bit, whereupon, after completion of the borehole, the separation or detachment of the drill rod assembly from the drill bit
25 and optionally impact ring is effected by the simple retraction of the drill rod assembly.

In order to provide a reliable transmission or introduction of the energy to be introduced from the drill rod assembly
30 onto the drill bit as well as the envelope and/or jacket tubes via the interposed impact ring and impact shoe, it is provided according to a further preferred embodiment that the impact shoe, and optionally the impact ring, as well as

the drill rod assembly and the drill bit comprise stop surfaces each enclosing an acute angle with the longitudinal axis of the drill rod assembly or having a spherical calotte shape and provided for the transmission
5 of impact energy from the drill rod assembly onto the drill bit and the impact shoe and impact ring, respectively. Such stop surfaces enclosing acute angles with the longitudinal axis of the drill rod assembly or having spherical calotte shapes can be constructed for the partially high forces to
10 be introduced in an accordingly cost-effective and reliable manner.

In order to enable targeted drilling during the production of a borehole, it is provided according to a further
15 preferred embodiment that a guide tube overlapping the impact shoe is arranged to follow the drill bit on the end facing away from the excavation surface, which guide tube, together with the drill bit, is capable of being rotated relative to the impact shoe as well as the envelope and/or
20 jacket tubes connected therewith. This guide tube has an accordingly short length in order not to excessively increase the frictional forces acting between the outer periphery of the guide tube and the produced borehole, while the envelope and/or jacket tubes are merely subjected
25 to tensile stresses as explained above and, hence, introduced solely in the longitudinal direction of the borehole without rotational movement.

To ensure coupling between the guide tube and the impact
30 shoe, it is provided according to a further preferred embodiment that the guide tube and the impact shoe are secured in the axial direction, for instance, by a spring washer.

In the following, the invention will be explained in more detail by way of an exemplary embodiment schematically illustrated in the drawing. Therein:

5 Fig. 1 depicts a longitudinal section through a device according to the invention for carrying out the method of the invention;

Fig. 2 is a front elevation view of the drill bit of the embodiment according to Fig. 1 in the sense of arrow II,

10 Fig. 1 being a section along line I-I of Fig. 2; and

Fig. 3 is a side view of the device according to the invention.

In the Figures, a drill bit is generally denoted by 1, which, in a manner known per se, comprises a plurality of hard-metal or hard-material inserts 2 for excavating material not illustrated in detail in order to form a borehole not illustrated in detail, either.

20 As is apparent from Fig. 1, the drill bit 1 is coupled with a drill rod assembly 4 on its side facing away from the working surface 3, Fig. 1 showing but the foremost section of the drill rod assembly 4, wherein the drill rod assembly 4, in a manner known per se, is accordingly extensible, for
25 instance, via a screw connection indicated at 5. The drill rod assembly 4 substantially centrally in the region of a plug-in connection 6 cooperates directly with the drill bit 1, wherein Fig. 1, moreover, schematically indicates a flush channel 7 provided within the drill rod assembly 4
30 and running into respective flush openings 8 provided in the region of the working surface 3 of the drill bit 1.

In addition to the central coupling of the drill rod assembly 4 with the drill bit 1 in the region of the plug-in connection 6, it is, moreover, provided that the drill rod assembly 4 at a distance from the plug-in connection 6
5 cooperates with an impact ring 9 which, in turn, cooperates with an impact shoe 10. The impact shoe 10 transmits energy onto an envelope tube 15 via the interposed impact ring 9.

For the simple and proper transmission of impact energy
10 from the drill rod assembly 4 onto the impact ring 9 and, subsequently, onto the impact shoe 10, stop surfaces or abutment surfaces 12 and 13 are provided, said stop surfaces or abutment surfaces 12 and 13 each enclosing an acute angle with the longitudinal axis 14 of the drill rod
15 assembly 4. The abutment surfaces 11 between the drill bit 1 and the central drill rod assembly 4 are calotte-shaped to transmit the required forces.

In addition, it is apparent from Fig. 1 that the impact
20 shoe 10 is connected with the envelope tube 15 via a weld 16 such that an action upon the impact shoe 10 in the direction of the drilling or mining movement 17 will, at the same time, entrain the envelope tube 15 as well as the jacket tube 18 coupled with the envelope tube 15 and
25 following upon the same. Coupling between the envelope tube 15 and the adjoining jacket tube 18 is realized by coupling via a ring 19.

From Fig. 1 it is further apparent that the drill bit end
30 facing away from the working surface 3 is followed by a guide tube 20, which is firmly connected with the drill bit 1 while overlapping the impact ring 10 at least partially.

An axial securing means between the impact ring 10 and the guide tube 20 is indicated in Fig. 1 as a spring washer 21.

As is particularly apparent from Fig. 3, the guide tube 20
5 rotates together with the drill bit 1 in the sense of arrow
22 during an excavation procedure, while the envelope tube
15 and the adjoining jacket tube 18 are taken along into
the interior of the borehole via the impact shoe 10 solely
in the sense of the drilling movement 17 without any
10 rotational movement.

To provide particularly reliable and exact coupling between
the drill rod assembly 4 and the drill bit 1, polygonal
connection or abutment surfaces are provided in the region
15 of the plug-in connection 6.

Moreover, it is provided that the impact ring 9 is designed
to be separate from both the impact shoe 10 and the drill
rod assembly 4 such that, upon completion of a borehole,
20 the drill rod assembly 4 can be readily removed from the
borehole and, hence, the interior of the envelope tube 15
and the adjoining jacket tube 18 in a direction opposite to
the drilling direction 17, whereby no impediment by
material present in the interior of the envelope and/or
25 jacket tubes 15 and/or 18, respectively, need be feared,
because the impact ring 9 too will remain in the borehole,
i.e., in the interior of the envelope tube 15.

For the proper haulage of excavated material not
30 illustrated in detail, it is provided that the drill bit 1
on its working surface 3 comprises at least one and, in the
embodiment illustrated, three passage openings 23, which
are each arranged in a substantially equally spaced-apart

angular relationship of 120° . It is, in particular, apparent from the schematic view of Fig. 2 that also the impact ring 9 comprises accordingly aligned passage openings 24 so as to provide a large passage cross section that enables the discharging of material directly through the working surface of the drill bit 1 and, subsequently, into the annular space 25 defined between the outer periphery of the drill rod assembly 4 and the inner peripheries of the envelope tube 15 and/or adjoining jacket tube 18.

Considering the fact that the impact ring 9, as pointed out above, is designed separately from both the impact shoe 10 and the drill rod assembly 4, it is, thus, feasible to safely remove or retract the drill rod assembly 4 upon completion of the bore even with coarse material being possibly present in the annular space 25, since, besides the substantially smooth outer periphery of the drill rod assembly 4, which is apparent from the right-hand portion of Fig. 1, partial region 26 having a reduced cross section and surrounded by the impact ring 9 does not constitute an impediment for the removal of the drill rod assembly 4 upon completion of the bore.

Claims:

1. A method for drilling, in particular percussion drilling or rotary percussion drilling, holes in soil or rock material, wherein a borehole is formed by a percussive and/or rotational movement carried out by a drill bit (1) mounted on a drill rod assembly (4) and an envelope tube and/or a jacket tube (15, 18) is introduced into the borehole, characterized in that the impact energy introduced by the drill rod assembly (4) is transmitted partially, particularly centrally, by the drill rod assembly (4) onto the drill bit (1) and partially via an impact shoe (10) cooperating with the drill rod assembly (4) onto the envelope and/or jacket tubes (15, 18).
2. Method according to claim 1, characterized in that the impact energy is transmitted from the drill rod assembly (4) onto the impact shoe (10) via an interposed impact ring (9) ..
3. A method according to claim 1 or 2, characterized in that the transmission of the impact energy from the drill rod assembly (4) onto the impact shoe (10) and/or the interposed impact ring (9) and onto the drill bit (1) is each effected via abutment or stop surfaces (12, 13) each enclosing an acute angle with the longitudinal axis (14) of the drill rod assembly (4) or having a spherical calotte shape.
4. A method according to any one of the claims 1 to 3, characterized in that excavated material is introduced into an annular space (25) defined between the outer periphery of the drill rod assembly (4) and the inner peripheries of

the envelope tube (15) and the adjoining jacket tube (18) via at least one passage opening (23) provided in the working surface of the drill bit (1), and removed from the borehole.

5

5. A method according to claim 4, characterized in that the impact ring (9) is formed with a passage opening (24) for material haulage, which corresponds with the at least one passage opening (23) of the working surface of the drill
10 bit (1), and coupled with the drill rod assembly (4) for rotational movement with the drill bit (1).

6. A method according to any one of claims 1 to 5, characterized in that the drill bit (1) and optionally the
15 impact ring (9) are coupled with the drill rod assembly (4) by a plug-in connection, wherein in particular complementary polygonal surfaces of the plug-in connection are provided.

20 7. A device for drilling, in particular percussion drilling or rotary percussion drilling, holes in soil or rock material, wherein a borehole is formed by a percussive and/or rotational movement carried out by a drill bit (1) mounted on a drill rod assembly (4) and an envelope tube
25 and/or a jacket tube (15, 18) is capable of being introduced into the borehole, characterized in that the drill bit (1) is capable of being acted upon by the drill rod assembly (4) in its central region and the drill rod assembly (4) acts on an impact shoe (10) cooperating with
30 the envelope and/or jacket tubes (15, 18).

8. Device according to claim 7, characterized in that the drill rod assembly (4) is coupled via an interposed impact

ring (9) with the impact shoe (10) for the transmission of impact energy onto the envelope and/or jacket tubes (15, 18).

5 9. A device according to claim 7 or 8, characterized in that the impact ring (9) is designed to be separate from the impact shoe (10) and the drill rod assembly (4).

10 10. A device according to claim 7, 8 or 9, characterized in that the impact shoe (10) is welded with the envelope tube (15) and/or the jacket tube (18).

15 11. A device according to any one of claims 7 to 10, characterized in that the drill bit (1) on its working surface (3) comprises at least one passage opening (23) for the introduction of material into an annular space (25) defined between the outer periphery of the drill rod assembly (4) and the inner peripheries of the envelope tube (15) and the adjoining jacket tube (18).

20 12. A device according to claim 11, characterized in that the impact ring (9) comprises at least one passage opening (24) in alignment with the passage opening(s) (23) of the working surface of the drill bit (1).

25 13. A device according to claim 11 or 12, characterized in that a plurality of passage openings (23, 24) each at substantially equal angular distances from one another, in particular three passage openings at mutual angular
30 distances of 120°, are provided on the outer peripheral regions of the drill bit (1) and impact ring (9).

14. A device according to any one of claims 7 to 13,
characterized in that the drill bit (1) and the impact ring
(9) are coupled to the drill rod assembly (4) via plug-in
connections (6), wherein the plug-in connections (6)
5 comprise in particular polygonal stop or abutment surfaces.

15. A device according to any one of claims 7 to 14,
characterized in that the impact shoe (10) and optionally
the impact ring (9) as well as the drill rod assembly (4)
10 and the drill bit (1) comprise stop surfaces each enclosing
an acute angle with the longitudinal axis (14) of the drill
rod assembly (4) or having a spherical calotte shape and
provided for the transmission of impact energy from the
drill rod assembly (4) onto the drill bit (1) and the
15 impact shoe (10) and impact ring (9), respectively.

16. A device according to any one of claims 7 to 15,
characterized in that a guide tube (20) overlapping the
impact shoe (10) is arranged to follow the drill bit (1) on
20 the end facing away from the working surface (3), which
guide tube, together with the drill bit (1), is capable of
being rotated relative to the impact shoe (10) as well as
the envelope and/or jacket tubes (15, 18) connected there-
with.

25

17. A device according to claim 16, characterized in that
the guide tube (20) and the impact shoe (10) are secured in
the axial direction, for instance, by a spring washer (21).