

9800076-3

PATENT
97-047 SG

SPECIFICATION

18053
copy

BOARD STRADDLE MOUNTED ELECTRICAL CONNECTOR ✓

Field of the Invention

5 This invention generally relates to the art of electrical connectors and, particularly, to a system for straddle mounting an electrical connector to an edge of a printed circuit board.

Background of the Invention

10 In the electronics industry, electrical connectors often are mounted to printed circuit boards for electrical connection to circuit traces on the boards. Typically, the electrical connectors are positioned on the printed circuit boards, and electrical terminals are soldered to circuits on the boards. The connectors usually
15 include some form of locking or retention means to hold the connectors to the boards. The locking or retention means can vary from mounting posts molded integrally with the connector housings to separate mounting clips which engage the connector housings to hold the connectors to the board.
20 The integral mounting posts or the separate clips usually are inserted into holes in the printed circuit board.

Providing locking or retention means as described above becomes more difficult when electrical connectors are mounted at the edge of a printed circuit board, such as in
25 a cutout in the edge of the board. The locking or retention means becomes still more difficult to design when the electrical connectors are straddle mounted to the edge of the board. In other words, the connector may include terminals which are solder connected to both opposite sides
30 or surfaces of the board.

Electrical connectors which are straddle mounted to the edge of a printed circuit board, as described above, often are more prone to become damaged during handling than



REPLACED SHEETS		SG
☒	Description : paged1..... to paged8.....	
☒	Claim(s) : paged9..... to paged14.....	
☐	Drawing(s) : paged to paged to paged	
☒	Abstract : paged15..... to paged to paged	
DATE OF RECEIPT		

connectors which are mounted on a surface of the board inwardly of the peripheral edges thereof. Without a secure locking or retention means, the housings of straddle mounted electrical connectors literally can be torn away from the retention clips and the connector terminals secured to opposite sides of the board.

The present invention is directed to solving these problems by providing a new and improved locking or retention means or system to hold straddle mounted connectors to the edge of a printed circuit board.

Summary of the Invention

An object, therefore, of the invention is to provide a new and improved system for straddle mounting an electrical connector to a printed circuit board.

In the exemplary embodiment of the invention, the printed circuit board has an edge and opposite surfaces, with circuit traces on the opposite surfaces near the edge. The electrical connector includes an elongated housing having opposite ends, with the housing being adapted for straddle mounting to the printed circuit board along the edge thereof. Terminals are mounted on the housing and include tail portions for connection to the circuit traces on the opposite surfaces of the printed circuit board.

The invention contemplates a pair of generally U-shaped mounting clips each having a pair of legs joined by a bight portion. One mounting clip is located at each opposite end of the elongated housing. The bight portion of each mounting clip embraces a portion of the housing. The legs of each mounting clip are juxtaposed against the opposite surfaces of the printed circuit board for connection to appropriate mounting pads thereon.

As disclosed herein, the mounting clips are located in wing portions of the housing projecting longitudinally outwardly of the housing beyond a central mating portion of the housing. The housing has a mating



side remote from the board and mounting side adjacent the edge of the board. A pair of passages extend through each wing of the housing between the mating side and the mounting side. The legs of a respective one of the mounting clips extend through the passages, and the bight portion of the mounting clip engages a portion of the housing at the mating side thereof. Therefore, the housing cannot be torn away from the mounting clips.

Other features of the invention include a pair of latches on the housing located longitudinally outwardly of the mounting clips. The latches are adapted for latching the connector to an appropriate complementary mating connector. The printed circuit board includes a cutout in the edge thereof for locating the housing of the connector.

Other objects, features and advantages of the invention will be apparent from the following detailed description taken in connection with the accompanying drawings.



Brief Description of the Drawings

The features of this invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements in the figures and in which:

FIGURE 1 is a perspective view of one embodiment of an electrical connector incorporating the concepts of the invention;

FIGURE 2 is a vertical section taken generally along line 2-2 of Figure 1;

FIGURE 3 is a side elevational view of the connector of Figure 1;

FIGURE 4 is a fragmented plan view of an edge area of a printed circuit board whereat the connector is straddle mounted;

FIGURE 5 is a rear perspective view showing the connector of Figure 1 straddle mounted to the board of Figure 4;

FIGURE 6 is a perspective view of a second embodiment of an electrical connector incorporating the concepts of the invention;

FIGURE 7 is a perspective view of the right-hand end of the connector of Figure 6, with the mounting clip removed from the connector; and

FIGURE 8 is a view similar to that of Figure 7, with the mounting clip inserted through the connector.



Detailed Description of the Preferred Embodiments

Referring to the drawings in greater detail, and first to Figures 1-3, an electrical connector, generally designated 10, includes an elongated housing, generally designated 12, having opposite ends 12a. The housing has a mating side 14 and a mounting side 16, with a mating portion 18 projecting at the mating side. The housing includes a pair of wing portions 20 projecting longitudinally outwardly beyond mating portion 18. A pair of latch arms 22 project in a mating direction from wing portions 20 alongside but spaced longitudinally outwardly of the opposite ends of mating portion 14. Housing 12, including mating portion 18, wing portions 20 and latch arms 22, is a unitary structure molded of dielectric material such as plastic or the like.

As best seen in Figures 1 and 2, housing 12 of connector 10 includes a plurality of terminal-receiving passages 24 extending between mating side 14 and mounting side 16 of the housing through mating portion 18. The passages are arranged in two rows as best seen in Figure 1 for mounting two rows of conductive terminals, generally designated 26, as best seen in Figure 2. Each terminal includes a bifurcated or female end 26a for receiving a pin or male terminal of an appropriate complementary mating connector, with the pin terminals being inserted into passages 24 in the direction of arrows "A" (Fig. 2). The terminals have tail portions 26b projecting outwardly of passages 24 beyond mounting side 16 of the housing. The tail portions are arranged in two rows so that they are capable of connection to circuit traces on the opposite surfaces of a printed circuit board, as the connector is straddle mounted to an edge of the board.

Figure 4 shows a printed circuit board, generally designated 28, which has an edge 30 and opposite surfaces 32 with circuit traces which include contact pads 34 on both opposite surfaces of the board. The contact pads are



arranged in a row on each opposite surface of the board for engaging the two rows of tail portions 26b (Fig. 2) of the terminals when the connector is straddle mounted to the edge of the board. Actually, the connector is mounted in a cutout 36 in edge 30 of the board, and the cutout has a polarizing notch 38 at one end thereof for receiving a polarizing boss 40 (Figs. 1 and 3) projecting from mounting side 16 of the connector housing. Lastly, as seen in Figure 4, a mounting pad 42 is located at each opposite end of each row of contact pads 34 on each opposite surface 32 of printed circuit board 12. Like contact pads 34 which are soldered to terminal tails 26b, mounting pads 42 are of solderable material.

The invention contemplates the provision of a pair of generally U-shaped mounting clips, generally designated 44, with each clip having a pair of legs 46 joined by a bight portion 48. One mounting clip 44 is located at each opposite end of elongated housing 12 in each wing portion 20 of the housing.

Figure 5 shows electrical connector 10 straddle mounted within cutout 36 in edge 30 of printed circuit board 28. It can be seen that terminal tail portions 26b are in engagement with contact pads 34 on surface 32 of the printed circuit board. Although only one surface is visible in Figure 5, the terminal tail portions from the connector are in engagement with the contact pads on the opposite or undersurface of the board as viewed in Figure 5. It also can be seen how legs 46 of mounting clips 44 are in engagement with mounting pads 42 on the board. In final assembly, terminal tail portions 26b are soldered to contact pads 34 on the board, and legs 46 of mounting clips 44 are soldered to mounting pads 42 on the board.

Figure 6 shows a modified version of the electrical connector and is generally designated 50. Connector 50 is substantially identical to connector 10 except that latch arms 22 of connector 10 are not used on


connector 50. Therefore, like reference numerals have been applied to Figures 6-8 to designate like components of the connector as described above in relation to Figures 1-3 and 5. On the other hand, with the latch arms omitted from connector 50, the location and mounting of mounting clips 44 on the connector housing can be better seen in the embodiment of Figures 6-8.

More particularly, referring to Figures 7 and 8 in conjunction with Figure 6, a pair of passages 52 (Fig. 7) extend through housing 12 between mating side 14 and mounting side 16, entirely through each wing portion 20 at each opposite end 12a of the housing. The details of one of the mounting clips 44 is shown clearly in Figure 7, with the mounting clip removed from the housing. In addition to legs 46 and bight portion 48 of the mounting clip, the mounting clip also is provided with teeth 54 in the side edges thereof near bight portion 48. These teeth dig into the plastic material of the housing within passages 52 to hold the mounting clip in the housing. Each mounting clip 44 is assembled to the housing in the direction of arrow "B" (Fig. 7) until the mounting clip is fully assembled as shown in Figure 8. During assembly, legs 46 are inserted into and through passages 52 in the respective wing portion 20 of the housing. Teeth 54 of the mounting clip are forced into an interference fit with the plastic material within passages 52. When fully assembled, whereas bight portion 48 of the mounting clip is rigidly fixed to the housing, legs 46 are resilient in the direction of double-headed arrow "C" (Fig. 8) so that the legs grip opposite surfaces of printed circuit board 28 at mounting pads 42. When assembled, bight portion 48 of the mounting clip embraces a substantial portion 56 (Fig. 7) of the housing so that the housing cannot be pulled away from the mounting clips when the clips are fully secured, as by soldering, to mounting pads 42 on the printed circuit board.



5 It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and the invention is not to be limited to the details given herein.



CLAIMS

1. A system for straddle mounting an electrical connector (10,50) to a printed circuit board (28), comprising:


5 said printed circuit board (28) having an edge (30) and opposite surfaces (32), with circuit traces (34) on said opposite surfaces of the board near the edge;

 said electrical connector (10,50) including an elongated housing (12) having opposite ends (12a) and being adapted for straddle mounting to the printed circuit board (28) along the edge (30) thereof, with terminals (26) on the housing and including tail portions (26a) for connection to the circuit traces (34) on the opposite surfaces (32) of the printed circuit board (28); and

15 a pair of generally U-shaped mounting clips (44) each having a pair of legs (46) joined by a bight portion (48), one mounting clip being located at each opposite end (12a) of the elongated housing (12), the bight portion (48) of each mounting clip (44) embracing a portion (56) of the housing, and the legs (46) of each mounting clip being juxtaposed against said opposite surfaces (32) of the printed circuit board (28) for connection to appropriate mounting pads (42) thereon.

25 2. The system of claim 1 wherein said mounting clips (44) are located in wing portions (20) of the housing (12) projecting longitudinally outwardly of the housing beyond a central mating portion (18) of the housing.





3. The system of claim 2, including a pair of latches (22) on the housing (12) located longitudinally outwardly of the mounting clips (44), the latches being adapted for latching the connector (10) to an appropriate complementary mating connector.

5

4. The system of claim 1 wherein said housing (12) has a mating side (14) remote from the board (28) and a mounting side (16) adjacent the edge of the board, and including a pair of passages (52) extending through the housing in a direction between the mating side and the mounting side for each mounting clip (44), with the legs (46) of the respective mounting clip extending through the passages (52) and the bight portion (48) of the mounting clip engaging a portion (56) of the housing between the passages.

10

15

5. The system of claim 1 wherein said printed circuit board (28) includes a cutout (36) in the edge (30) thereof for locating the housing (12) of the connector.





6. A system for straddle mounting an electrical connector (10,50) to a printed circuit board (28), comprising:

5 said printed circuit board (28) having an edge (30) and opposite surfaces (32), with circuit traces (34) on said opposite surfaces of the board near the edge;

10 said electrical connector (10,50) including an elongated housing (12), the housing being adapted for straddle mounting to the printed circuit board at the edge thereof and having a mating side (14) remote from the board and a mounting side (16) adjacent the edge of the board, a central mating portion (18) and wing portions (20) at opposite ends (12a) of the housing projecting longitudinally outwardly of the mating portion, and a pair of passages (52) extending through each wing portion (20) of the housing in a direction between the mating side and the mounting side of the housing;

15 a plurality of terminals (26) mounted in the housing (12) and including tail portions (26a) projecting from the housing for connection to the circuit traces (34) on the opposite surfaces (32) of the printed circuit board (28); and

20 a pair of generally U-shaped mounting clips (44) each having a pair of legs (46) joined by a bight portion (48), one mounting clip being located at each opposite end (12a) of the elongated housing (12), the bight portion (48) of each mounting clip (44) embracing a portion (52) of the housing, and the legs (46) of each mounting clip extending through the pair of passages (52) in the respective wing portion (20) and being juxtaposed against said opposite surfaces (32) of the printed circuit board (28) for connection to appropriate mounting pads (42) thereon.



5 7. The system of claim 6, including a pair of
latches (22) on the housing (12) located longitudinally
outwardly of the mounting clips (44), the latches being
adapted for latching the connector (10) to an appropriate
complementary mating connector.

8. The system of claim 6 wherein said printed
circuit board (28) includes a cutout (36) in the edge (30)
thereof for locating the housing (12) of the connector.

This Sheet Has Been Replaced



9. A system for straddle mounting an electrical connector (10,50) to a printed circuit board (28), comprising:

5 said printed circuit board (28) having an edge (30) and opposite surfaces (32), with circuit traces (34) on said opposite surfaces of the board near the edge;

10 said electrical connector (10,50) including a housing (12) adapted for straddle mounting to the printed circuit board (28) at the edge thereof, with terminals (26) on the housing including tail portions (26a) for connection to the circuit traces (34) on the opposite surfaces (32) of the printed circuit board (28); and

15 a generally U-shaped mounting clip (44) having a pair of legs (46) joined by a bight portion (48), the legs being juxtaposed against said opposite surfaces (32) of the printed circuit board (28) for connection to appropriate mounting pads (42) thereon, and the bight portion (48) embracing a portion (56) of the housing (12).

20 10. The system of claim 9, including a latch (22) on the housing located outwardly of the mounting clip (44), the latch being adapted for latching the connector (10) to an appropriate complementary mating connector.

This Sheet Has Been Replaced



5 11. The system of claim 9 wherein said housing (12) has a mating side (14) remote from the board (28) and a mounting side (16) adjacent the edge of the board, and including a pair of passages (52) extending through the housing in a direction between the mating side and the mounting side, the legs (46) of the mounting clip (44) extending through the passages (52) and the bight portion (48) of the mounting clip engaging a portion (56) of the housing between the passages.

10 12. The system of claim 9 wherein said printed circuit board (28) includes a cutout (36) in the edge (30) thereof for locating the housing (12) of the connector.

This Sheet Has Been Replaced

