

## CORRECTED VERSION

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
30 July 2009 (30.07.2009)

(10) International Publication Number  
**WO 2009/092846 A8**

(51) International Patent Classification:  
*H03H 9/02* (2006.01) *B81B 3/00* (2006.01)  
*H03H 9/24* (2006.01)

(21) International Application Number:  
PCT/FI2009/000020

(22) International Filing Date:  
23 January 2009 (23.01.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
61/023,414 24 January 2008 (24.01.2008) US

(71) Applicant (for all designated States except US): VTI  
TECHNOLOGIES, OY [FI/FI]; PL 27, FI-01621 Van-  
taa (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KAAJAKARI, Ville;  
500 S. Bonner St, Ruston, LA 71270 (US).

(74) Agent: BORENIUS & CO OY AB; Tallberginkatu 2A,  
FI-00180 Helsinki (FI).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ,  
EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,  
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,  
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,  
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO,  
NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG,  
SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,  
TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,  
MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR),  
OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML,  
MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(48) Date of publication of this corrected version:  
17 September 2009

(15) Information about Correction:  
see Notice of 17 September 2009

(54) Title: A MICROMECHANICAL RESONATOR




Fig. 4

(57) Abstract: The invention relates to design of micromechanical resonators and, more precisely, to the design of microelectromechanical systems (MEMS) resonators. The invention provides an improved design structure for a microelectromechanical systems (MEMS) resonator in which the width of the spring elements (3), (23-24), (27-30) is greater than the width of the electrode fingers (5-9), (25-26), (31-34), said widths specifically dimensioned so that the sensitivity of the resonant frequency change with respect to dimensional manufacturing variations Formula approaches zero. The improved structure is frequency robust to manufacturing variations and enables reliable frequency referencing with good performance, particularly in small size solutions.