

09/05/03
200 3027489

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



162162

(43) International Publication Date
16 May 2002 (16.05.2002)

PCT

(10) International Publication Number
WO 02/39182 A1

(51) International Patent Classification⁷: **G03B 27/42**,
27/52, G01N 21/86, G01B 11/14

[US/US]; 6632 Mt. Wellington Drive, San Jose, CA 95120
(US). **WADE, Bryan** [US/US]; 1572 Mizzen Ln., Half
Moon Bay, CA 94019 (US).

(21) International Application Number: PCT/US01/47539

(74) Agents: **MOLL, Robert**; PatentPlanet, 1173 St. Charles
Court, Los Altos, CA 94024 et al. (US).

(22) International Filing Date:
8 November 2001 (08.11.2001)

(81) Designated States (*national*): JP, KR, SG, US.

(25) Filing Language: English

(84) Designated States (*regional*): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

(26) Publication Language: English

(30) Priority Data:
09/709,975 10 November 2000 (10.11.2000) US

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments


(71) Applicant (*for all designated States except US*): **ASML**
[US/US]; 541 E. Trimble Road, San Jose, CA 95131 (US).

(71) Applicants and

(72) Inventors: **BABIKIAN, Dikran** [US/US]; 870 El Cap-
itan Drive, Millbrae, CA 94030 (US). **STARK, Larry**

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: SYSTEMS AND METHODS FOR EXPOSING SUBSTRATE PERIPHERY



(57) Abstract: The present invention describes systems (10) and methods for exposure and removal of material on the periphery of a substrate. The system includes an emitting radiation or exposure source, preferably a guide such as an optical assembly (36) and an emitter (41), an edge detector (43), a transport, which comprise rotating and radial mechanisms, and a substrate support. The optical assembly (36) directs radiation from the exposure source to the wafer or emitter. The transport supports the emitter and the edge detector (43) about the substrate, and a tracking exposure head preferably supports the emitter and edge detector (43). As the emitter (41) moves along the periphery of the substrate, the edge detector (43) sends signals to control systems, which process signals, and command the transport to adjust the position of the emitter (41) when necessary to expose the periphery of the substrate. In another embodiment, the system provides an exposure source chamber, a process chamber, and optionally a control chamber to isolate particle and thermal problems. In another embodiment, the wafer is in a rotating drum, which supports a radial mechanism, supporting a tracking exposure head (40) holding the emitter and edge detector. The drum

and tracking exposure head (40) have guidance components and stopping mechanisms.

WO 02/39182 A1



ACTION