

A Flame Barrier, Apparatus and Method for Entertaining Guests

Background of the Invention

Field of the Invention

- 5 **[0001]** The subject matter described herein relates generally to barriers for thermal energy and products of combustion and to apparatus and methods employing such a barrier for entertaining guests.

Related Art

- 10 **[0002]** To provide high entertainment value for today's sophisticated customer, themed entertainment venues, such as theme parks and amusement parks, include a variety of entertainment that is expected to thrill a guest. In one example, the entertainment involves action associated with a ride itself such as the effect of gravitational forces on the body that arises during high speed twists, turns, ups and
15 downs of a roller coaster. In another example, the entertainment involves the surprise and apprehension created during a perceived event. For example, the Mummy attraction at Universal Studios Florida provides, among other special effects, several fire effects that are passed by guests during a ride through the attraction. The guests are located 20 to 30 feet from the flaming prop that is lit to provide the
20 effect of radiating heat and a flash of light. At this distance, the sense of surprise and apprehension created by the effect is limited. Currently, when guests are directed close to an effect, within arms length, a simulated flame such as a flapping fabric, lighting effects, faux fire, fog and projection are typically used instead of a real flame.

Furthermore, the path at which a flame burst follows is never directed toward a guest at close distances, thus limiting the guest's real sense of danger.

[0003] Accordingly, it is desired to increase the effect of surprise and apprehension associated with a flaming prop in order to provide the high entertainment value demanded by a sophisticated customer or guest.

Brief Description of the Invention

[0004] According to a first aspect, there is provided an apparatus for entertaining multiple guests, comprising: a device that selectively generates a flame; and a barrier interposed between each guest and the flame and wherein the barrier is configured to remain transparent throughout multiple repetitions of use of the device for generating a flame; wherein the barrier comprises a sheet comprising at least one of glass and plastic; wherein the barrier further comprises a coating located on a surface of the sheet, the coating comprising a liquid resin.

[0005] According to a second aspect, there is provided an apparatus for entertaining multiple guests, comprising: a device that selectively generates a flame; and a barrier interposed between each guest and the flame and wherein the barrier is configured to remain transparent throughout multiple repetitions of use of the device for generating a flame; wherein the barrier comprises a sheet comprising at least one of glass and plastic; wherein the sheet further comprises an electrode mounted to a surface of the sheet located proximal to the device that selectively generates at least one flame and the electrode conducting an electrical charge to the surface.

[0006] According to a third aspect, there is provided a method of entertaining at least one guest, comprising: directing at least one guest to a location; orienting the at least one guest in a particular direction; generating a flame that extends toward the location and wherein

generating a flame further comprises generating a flame in a direction that generally opposes the particular direction that the at least one guest is oriented; and interposing a barrier between the at least one guest and the flame to prevent injury to the at least one guest while entertaining the at least one guest; wherein the steps of directing and orienting the at least one guest and generating a flame are selectively repeatable and further comprising configuring the barrier to remain transparent at least during the step of generating at least one flame and throughout each repetition thereof; wherein configuring the barrier to remain transparent comprises using means for preventing the build up of soot on the barrier.

[0006a] According to a fourth aspect, there is provided a method of entertaining at least one guest, comprising: directing at least one guest to a location; orienting the at least one guest in a particular direction; generating a flame that extends toward the location and wherein generating a flame further comprises generating a flame in a direction that generally opposes the particular direction that the at least one guest is oriented; and interposing a barrier between the at least one guest and the flame to prevent injury to the at least one guest while entertaining the at least one guest; wherein directing and orienting the at least one guest and generating a flame are selectively repeatable and further comprising configuring the barrier to remain transparent at least during the step of generating at least one flame and throughout each repetition thereof; wherein configuring the barrier to remain transparent comprises applying an electrical charge to the barrier.

Brief Description of the Drawings

[0007] The following detailed description is made with reference to the accompanying drawings, in which:

[0008] Figure 1 is a diagram showing, from a side view, a barrier and a device for generating a flame located on one side of a barrier in accordance with one embodiment of the present invention and a guest to be entertained located on another side of the barrier;

[0009] Figure 2 is another diagram showing a perspective view of the embodiment of Figure 1;

[0010] Figure 3 is a diagram showing a barrier located between scenic elements and a device for generating a flame located on one side of a barrier and a path for a ride vehicle located on another side of the barrier in accordance with another embodiment of the present invention;

[0011] Figure 4 is a sectional view of the barrier of Figure 1, taken along line 1-1;

[0012] Figure 5 is a partial sectional view of the barrier of Figure 1, showing a substrate and a coating;

[0013] Figure 6 is a diagram showing another embodiment of fluid blast system in accordance with the present invention; and

[0014] Figure 7 is a diagram showing an embodiment of a liquid flow system in accordance with the present invention.

Detailed Description of the Preferred Embodiment

[0015] An embodiment of the present invention concerns a barrier and a device for generating a flame and another involves a method of entertaining guests using the barrier and the device for generating a flame that provides a sophisticated guest with an increased effect of surprise and apprehension. In particular embodiments, the
5 barrier may comprise a material that is configured to withstand repeated blasts of the flame and to remain transparent during each blast.

[0016] Throughout the present disclosure, it is intended that the term "flame" be given the broadest reasonable interpretation including a simulated flame or a genuine flame, the latter of which falling under a definition, e.g., found in *The Dictionary of*
10 *Scientific and Technical Terms*, Fifth Edition, McGraw-Hill, Inc., 1994, Page 766 of a hot luminous reaction front (or wave) in a gaseous medium into which reactants flow and out of which products flow.

[0017] Referring now to Figure 1, an apparatus for entertaining a guest 8 in accordance with one embodiment of the present invention is illustrated generally at
15 10. In this embodiment, the apparatus 10 comprises a device for generating a flame 12 and a barrier 14.

[0018] In the illustrated embodiment, the device for generating a flame 12 comprises a body 16 and a nozzle 18. The internal workings within the body 16 are known and thus are not described herein, except to say that each combine to function to
20 generate, through combustion or other means, a flame 20 that may be directed by the nozzle 18. Although not shown as such, it is contemplated in the present invention that the nozzle 18 may be adjustable to direct the flame in any particular direction. Also, the nozzle may be adjustable to vary the volume of the flame and/or

provide a differing geometry of the flame such as a rectangular cross-sectional configuration or flat flame shape.

[0019] It has been found that in one aspect of the invention, a volume of the flame 20 that is greater than about 0.26 m³ is sufficiently large to increase an effect of surprise and apprehension in a guest 8. In the illustrated embodiment, a rough approximation of a volume (V) of the flame 20 may be determined using an appropriate volumetric formula for a frusto-conical section using a height dimension h, and radii, r₁ and r₂ as provided below:

$$i. V = \pi(r_2^2 + r_1 r_2 + r_1^2)h/3.$$

[0020] It will be appreciated that the volume is roughly approximated simply because it is a flame that may be flowing and therefore inherently has a somewhat amorphous volume. For example, a flame may be in the configuration of a traveling vortex ring.

Accordingly, it will be appreciated, that important features of the flame are a perceived size, including for example, the angle from a guest's point of view and/or perspective cues from the environment, and a perceived proximity.

[0021] Referring now to Figure 2, one embodiment of the barrier 14 comprises a frame 22 and a layer or sheet of material 24. It will be appreciated that in other embodiments of the present invention, the barrier 14 may comprise a fluid such as water, for example, a waterfall (not shown) or air, for example, a flow of high velocity air (also not shown) and combinations thereof.

[0022] The frame 22 may comprise a suitably strong and a flame resistant material

such as steel and may function to support and strengthen the barrier 14 while allowing for an appropriate amount of expansion of the material 24.

[0023] The material 24 may comprise any suitable material that is transparent and is capable of withstanding the thermal pulse of the flame blast 20 and quasi steady

5 state temperature of the barrier 14 which may result from repeated blasts of the flame 20. Where the flame 20 is generated by combustion, suitable materials include glass-ceramics, borosilicate glass and plastics with a high melting temperature.

Suitable glass-ceramics include those sold under the trademark "FIRELIGHT" by the TGP company (www.fireglass.com), "PYRAN" by the Schott company

10 (www.us.schott.com) and "SUPERLITE", by the Safti company (www.safti.com).

Suitable borosilicate glass includes that sold under the trademark "BOROFLOAT" by the Schott company. Suitable high temperature plastics may include high temperature polycarbonate such as that sold by the General Electric Company (www.GE.com) under the trademarks "GEPAX", "LEXAN" and "VEROLITE" and that

15 sold by the Bayer company (www.bayer.com) under the trademark "MAKROLON."

The high temperature plastics may each also include a blend having a fire retardant additive such as a silicone compound. It will be understood that in certain

applications it will be appreciated that the material of the barrier 14 may not need to be a high temperature material. It will be appreciated that this depends upon the

20 magnitude of the blast of a flame, frequency, and known or ascertained heat transfer properties.

[0024] As illustrated in Figure 5, the material 24 may comprise a coating 25 that functions to provide a thermal barrier to increase the fire resistant properties of the

flame barrier. Example coatings are those sold under the trademarks "Fire Kote 100" by the Universal Fire Shield company and "Hy-Tech Flame Resist" by the Hy-Tech Company. These coatings may comprise an aqueous based resin liquid coating.

Furthermore, this coating may also be configured, through the addition of a

5 suspended conductive material such as copper (CU), aluminum (AL), silver (AG) or gold (Au), to carry an electrostatic charge as described below.

[0025] In order to prevent the build up of particulate matter, such as soot, on the material 24, various particular embodiments may be employed in accordance with the present invention. For example, a pair of electrodes 26 may be mounted to the frame 10 22 in order to provide an electrostatic charge to the coating on the material 24. For preventing the build up of soot, or in other words repelling soot from building up on the material 24, it will be appreciated that this charge may be generally the same as the natural charge of soot or the flame may include a component material having a particular charge or the soot may be given a charge during the combustion or

15 transport process. Other particular embodiments include cleaning of the barrier 14 between blasts or a number of times throughout a day such as by use of a mechanical squeegee 28 that wipes the soot away wherein either the squeegee moves or the barrier moves, an air blast or water spray (either from a head 30) that is optionally along with a squeegee and through mechanical vibration of the barrier.

20 **[0026]** One embodiment of a fluid blast system for removing soot or preventing the buildup of soot on a barrier is shown in Figure 6. As shown, a blower 32 is located to provide a fluid output, such as pressurized air, represented by arrows 34, that flows in a direction that is parallel to a longitudinal axis of the barrier 14. Such an

arrangement may advantageously vary a flow pattern, represented by arrows 36, of a flame thereby reduce the build up and/or facilitate removal of soot.

[0027] Referring now to Figure 7, one embodiment of a liquid flow apparatus in accordance with the present invention for removing soot or preventing the buildup of soot on a barrier is shown generally at 38. The liquid flow apparatus 38 may
5 comprise a container 40 that supports a volume of a liquid such as water and includes an output spout 42. The output spout 42 may be located on a flame directed side of the barrier 14 and configured to provide a generally laminar flow of liquid in the direction of arrow 44 via gravity. A collector 46 may collect the liquid and
10 a pump 48 is provided for circulating the liquid through a filter 50 back to the container 40.

[0028] Referring again to Figure 1 and in one particular embodiment, the barrier 14 may be transparent in the human visual range (wavelengths of 0.4-0.7 μ) while blocking other radiation wavelengths including IR radiation (about 1 – 12 μ). This is
15 accomplished, e.g., by coating the barrier 14 with a material comprising a low emissivity and that is spectrally selective or by the bulk properties of the selected material. It will be appreciated that the foregoing allows a much larger flame effect much closer to the guests as the IR radiation from the free carbon is largely reflected by the visually transparent surface.

20 **[0029]** In another particular embodiment, the barrier 14 may be partially transparent in the IR, e.g., through use of a known coating that provides an incomplete IR blocking to convey a partial sense of intense heat to a guest. Such a coating is sold under the trademark "SUNCOAT" by Milgard Windows, Inc of Tacoma, WA.

[0030] It will be appreciated that radiation from the heated barrier 14 itself may be incident on the guests, in order to counter act this, the barrier may be cooled between blasts to increase the likelihood of surprising a guest.

[0031] Referring also again to Figure 1, in one particular embodiment and in order to best surprise the guest 8 and create a suitable amount of apprehension, it has been found that the distance d between the guest and the barrier 14 may be limited to approximately 3 feet. In operation and upon the guest 8 arriving at location L, the flame generating device 12 is energized and the flame 20 is created to surprise and entertain the guest.

[0032] Another embodiment of the present invention is shown generally at 100 in Figure 3. In Figure 3, like components to those described above are not repeated hereafter and are labeled similarly to that in Figure 2 excepting that each begins with one hundred. In this embodiment, rather than a single guest 8 (Figure 2) being entertained by a flame 120, a ride system 132 is illustrated wherein multiple guests 108 are carried in a vehicle 132 that follows a track 134. Also, in this embodiment, scenery 136 and 138 are both provided to increase the likelihood of surprising the guests 108.

[0033] A further embodiment of the present invention is shown in Figure 4, therein a method of entertaining at least one guest is shown generally at 200. In this embodiment and, as shown at 202, the method comprises directing at least one guest to a location; as shown at 204, orienting the at least one guest in a particular direction; as shown at 206, generating a flame that extends toward the location and in a direction that opposes the particular direction that the at least one guest is

oriented; and, as shown at 208, interposing a barrier between the at least one guest and the flame to prevent injury to the at least one guest while entertaining the at least one guest. It will be appreciated that the steps of directing and orienting the at least one guest and generating a flame may be selectively repeatable and the method may
5 further comprise configuring the barrier to remain transparent at least during the step of generating at least one flame and throughout each repetition thereof.

[0034] While the present invention has been described in connection with what are presently considered to be the most practical and preferred embodiments, it is to be understood that the present invention is not limited to these herein disclosed

10 embodiments. Rather, the present invention is intended to cover all of the various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

CLAIMS

1. An apparatus for entertaining multiple guests, comprising:
a device that selectively generates a flame; and
a barrier interposed between each guest and the flame and wherein the barrier is configured to remain transparent throughout multiple repetitions of use of the device for generating a flame;
wherein the barrier comprises a sheet comprising at least one of glass and plastic;
wherein the barrier further comprises a coating located on a surface of the sheet, the coating comprising a liquid resin.
2. The apparatus of claim 1, wherein the device that selectively generates a flame generates a flame that is configured to extend at least up to the barrier.
3. The apparatus of claim 2, wherein the flame has a volume of at least approximately 0.26 cubic meters.
4. The apparatus of claim 1, wherein the barrier is stationary.
5. The apparatus of claim 1, further comprising a vehicle for transporting multiple guests to a location adjacent the barrier.
6. The apparatus of claim 1, wherein the device that selectively generates a flame is configured to generate the flame via combustion.
7. The apparatus of claim 1, wherein the barrier is further configured to be transparent to wavelengths in the visual spectrum.
8. The apparatus of claim 1, wherein the barrier is further configured to be partially or completely transparent to wavelengths in the IR spectrum.
9. An apparatus for entertaining multiple guests, comprising:
a device that selectively generates a flame; and
a barrier interposed between each guest and the flame and wherein the barrier is configured to remain transparent throughout multiple repetitions of use of the device for generating a flame;
wherein the barrier comprises a sheet comprising at least one of glass and plastic;

wherein the sheet further comprises an electrode mounted to a surface of the sheet located proximal to the device that selectively generates at least one flame and the electrode conducting an electrical charge to the surface.

10. The apparatus of claim 9, wherein the device that selectively generates a flame generates a flame that is configured to extend at least up to the barrier.

11. The apparatus of claim 10, wherein the flame has a volume of at least approximately 0.26 cubic meters.

12. The apparatus of claim 9, wherein the barrier is stationary.

13. The apparatus of claim 9, further comprising a vehicle for transporting multiple guests to a location adjacent the barrier.

14. The apparatus of claim 9, wherein the device that selectively generates a flame is configured to generate the flame via combustion.

15. The apparatus of claim 9, wherein the barrier is further configured to be transparent to wavelengths in the visual spectrum.

16. The apparatus of claim 9, wherein the barrier is further configured to be partially or completely transparent to wavelengths in the IR spectrum.

17. A method of entertaining at least one guest, comprising:
directing at least one guest to a location;
orienting the at least one guest in a particular direction;
generating a flame that extends toward the location and wherein generating a flame further comprises generating a flame in a direction that generally opposes the particular direction that the at least one guest is oriented; and

interposing a barrier between the at least one guest and the flame to prevent injury to the at least one guest while entertaining the at least one guest;

wherein the steps of directing and orienting the at least one guest and generating a flame are selectively repeatable and further comprising configuring the barrier to remain transparent at least during the step of generating at least one flame and throughout each repetition thereof;

wherein configuring the barrier to remain transparent comprises using means for preventing the build up of soot on the barrier.

18. The method of claim 17, wherein the barrier comprises at least one of glass and plastic.
19. The method of claim 18, further comprising coating a surface of the barrier to retain transparency throughout each repetition of the step of generating a flame.
20. The method of claim 17, wherein the step of generating a flame comprises generating a flame that is in a line of sight of a guest.
21. The method of claim 17, wherein the means for preventing the build up of soot on the barrier comprises at least one of a squeegee, a fluid curtain and a flow of liquid.
22. The method of claim 17, wherein the step of generating at least one flame that extends toward the location comprises generating a flame that extends at least up to the barrier.
23. The method of claim 22, wherein the flame has a volume of at least 0.26 cubic meters.
24. The method of claim 17, wherein the barrier is disposed within 3 feet of the location to which the at least one guest is directed.
25. The method of claim 17, wherein the barrier is stationary.
26. The method of claim 17, wherein the at least one guest comprises multiple guests.
27. The method of claim 17, wherein the steps of directing and orienting the at least one guest comprises transporting multiple guests.
28. The method of claim 17, wherein the step of generating a flame is carried out through combustion.
29. A method of entertaining at least one guest, comprising:
 - directing at least one guest to a location;
 - orienting the at least one guest in a particular direction;
 - generating a flame that extends toward the location and wherein generating a flame further comprises generating a flame in a direction that generally opposes the particular direction that the at least one guest is oriented; and

interposing a barrier between the at least one guest and the flame to prevent injury to the at least one guest while entertaining the at least one guest;

wherein directing and orienting the at least one guest and generating a flame are selectively repeatable and further comprising configuring the barrier to remain transparent at least during the step of generating at least one flame and throughout each repetition thereof;

wherein configuring the barrier to remain transparent comprises applying an electrical charge to the barrier.

30. The method of claim 29, wherein the barrier comprises at least one of glass and plastic.

31. The method of claim 30, further comprising coating a surface of the barrier to retain transparency throughout each repetition of the step of generating a flame.

32. The method of claim 29, wherein the step of generating a flame comprises generating a flame that is in a line of sight of a guest.

33. The method of claim 29, wherein the step of generating at least one flame that extends toward the location comprises generating a flame that extends at least up to the barrier.

34. The method of claim 33, wherein the flame has a volume of at least 0.26 cubic meters.

35. The method of claim 29, wherein the barrier is disposed within 3 feet of the location to which the at least one guest is directed.

36. The method of claim 29, wherein the barrier is stationary.

37. The method of claim 29, wherein the at least one guest comprises multiple guests.

38. The method of claim 29, wherein the steps of directing and orienting the at least one guest comprises transporting multiple guests.

39. The method of claim 29, wherein the step of generating a flame is carried out through combustion.