

SPECIFICATION

CONNECTED HOLLOW STRUCTURE AND PACKAGING MEMBER

TECHNICAL FIELD

05 This invention relates to a connected hollow structure having a large number of parallel hollow portions of a predetermined sectional shape, and a packaging member.

BACKGROUND ART

10 Corrugated fiberboards are, for instance, typical of a conventional member fabricated from paper sheets and having hollow portions parallel to one another.

 The corrugated fiberboards are classified into A to E-flute corrugated fiberboards according to the size
15 of flutes, and also classified into a single faced corrugated fiberboard, a double faced corrugated fiberboard, a double wall corrugated fiberboard and a triple wall corrugated fiberboard according to a difference in structure.

20 These corrugated fiberboards are used for forming packaging boxes, cushioning materials and other packaging members. Recently, a proposal has been made that a layered corrugated fiberboard be used for forming cushioning materials for packaging, frame structures for

packaging, and core materials of heat-insulating panels or the like.

The corrugated fiberboard and the layered corrugated fiberboard member as described above have the
05 following problems.

Namely, one of the problems is that the corrugated fiberboard must be fabricated by the use of base boards, and as a result, it is not possible to freely select a material (i.e., base board) for the
10 corrugated fiberboard.

Another problem is that since the corrugated fiberboard is one of so-called standardized products, there is restrictions on selection of a void content (which means a ratio of the sectional area of hollow
15 portions to the whole sectional area in a section crossing at right angles to the hollow portions in this specification) for the corrugated fiberboard.

A further problem is that it is not possible to freely select a sectional shape for the hollow portions.

20 In connection with the above problems, a still further problem is that cushioning materials, packaging frame structures and other packaging members which are formed by the use of layered corrugated fiberboards are limited in selection of their hardness or the strength
25 of elasticity from the viewpoint of design.

Coincidentally, this problem means that their use is restricted within narrow limits.

A yet further problem is that several pieces of base boards and linerboard, and besides, a large number of steps are required for fabricating a corrugated fiberboard, and as a result, an increase in fabrication
05 cost is inevitable.

DISCLOSURE OF THE INVENTION

It is an object of the present invention to provide a connected hollow structure, in which its material is selected more widely according to the
10 purpose, and a packaging member comprised of such a connected hollow structure.

Another object of the present invention is to provide a connected hollow structure, in which its void content is freely designed according to the purpose, and
15 a packaging member comprised of such a connected hollow structure.

A further object of the present invention is to provide a connected hollow structure, in which the sectional shape of hollow portions is freely selected
20 according to the purpose, and a packaging member comprised of such a connected hollow structure.

A still further object of the present invention is to provide a connected hollow structure, in which its hardness and the strength of elastic force and
25 withstanding strength are selected more widely according to the purpose, in cooperation with the selection of the

material and the freedom of design of the void content and the sectional shape of hollow portions, and a packaging member comprised of such a connected hollow structure.

05 A yet further object of the present invention is to provide a connected hollow structure, which is fabricated through fewer steps by the use of a piece of sheet, to which various kinds of materials are applied, and a packaging member comprised of such a connected
10 hollow structure.

 A yet further object of the present invention is to provide a connected hollow structure which is used for various purposes.

 In order to attain the above objects, a connected
15 hollow structure according to the present invention is formed as follows.

 Namely, according to a connected hollow structure in a first mode of the present invention, a large number of hollow structures of an arbitrarily sectional shape
20 are connected in parallel to each other, and the connected hollow structure is comprised of a piece of sheet, and takes the shape resembling a unicursal figure in section.

 The sheet may be freely selected from a group
25 consisting of ordinary sheets, water-resistant sheets, coated printing sheets having the coated surface, laminated sheets, styrene paper (formed by solidifying a

non-woven fabric into a sheet-like shape by means of heating or using a resin, for instance), hard or semi-hard plastic sheets, thick paper, corrugated fiberboards, thin plywood and so on.

05 The hollow structures adjacent to each other are bonded together with an adhesive or connected or joined together directly or indirectly through other means.

 The connected hollow structure in the first mode shows cushioning properties depending on the quality of
10 a sheet selected as the material of the connected hollow structure or the sectional shape and apparent specific gravity (i.e., void content) of the hollow structures, since the hollow structures are deformed when an external force is applied to the connected hollow
15 structure in a direction crossing each hollow structure. The connected hollow structure in the first mode is suitable for use as a cushioning material, a packaging frame structure or like packaging member by making use of the elasticity or depending on the sectional shape of
20 the hollow structures, and besides, may be used for various purposes by making use of the hollow structures.

 Thus, it is possible to fabricate a connected hollow structure, which has the apparent specific gravity (void content) according to the purpose and
25 shows the withstanding strength or elasticity according to the purpose, by freely selecting the shape and sectional area of the hollow structures and the quality

of the sheet, as described above.

Further, since the connected hollow structure takes the shape resembling a unicursal figure in section and is comprised of a piece of sheet, it is possible to
05 fabricate the connected hollow structure through fewer steps at low cost.

Furthermore, the connected hollow structure is designed more freely, and therefore, may be used for various purposes.

10 According to a connected hollow structure in a second mode of the present invention, in the connected hollow structure in the first mode, the hollow structures include first and second hollow structures each having a corner portion of a convex angular
15 section. Each first hollow structure having the corner portion directed toward one surface of the connected hollow structure and a partial circumference facing the other surface of the connected hollow structure and each second hollow structure having the corner portion
20 directed toward the other surface of the connected hollow structure and a partial circumference facing one surface of the connected hollow structure are formed in an alternate arrangement, and the first and second hollow structures adjacent to each other have at least a
25 part of side walls, which include each corner portion, in common.

The connected hollow structure in the second

mode is easily patterned according to the purpose by selecting the sectional shape and size of the hollow structures, since the first and second hollow structures are formed in an alternate arrangement such that the
05 corner portion of each first hollow structure is directed to be substantially reverse to that of each second hollow structure.

Further, the first and second hollow structures are formed in a dense arrangement, since the first and
10 second hollow structures adjacent to each other have at least a part of the side walls, which include the corner portion of each hollow structure, in common. Therefore, the connected hollow structure in the second mode is suitable for use as not only a packaging member, but
15 also a core material of a heat-insulating panel or like panel and a carrier for carrying adsorbents by applying a layered connected hollow structure formed such that the hollow structures are in parallel with each other.

Furthermore, the hollow structures are easily
20 connected together through a mechanical means by joining or connecting the first hollow structures together in a portion of the corner portion of each second hollow structure positioned between the adjacent first hollow structures or joining or connecting the second hollow
25 structures together in a portion of the corner portion of each first hollow structure positioned between the adjacent second hollow structures.

According to a connected hollow structure in a third mode of the present invention, in the connected hollow structure in the second mode, the first and second hollow structures have a polygonal section, and
05 the connected hollow structure is formed by folding the sheet along folds formed on the sheet.

Therefore, the connected hollow structure in the third mode is patterned more easily, and also formed by machining more easily.

10 Further, it is possible to fabricate a connected hollow structure which takes various shapes according to the purpose by properly selecting the sectional shape of the hollow structures.

According to a connected hollow structure in a
15 fourth mode of the present invention, in the connected hollow structure in the third mode, the first and second hollow structures in portions other than at least both ends of the connected hollow structure have a polygonal section including sides of the same number.

20 Further, according to the connected hollow structure in the fourth mode, it is possible to design a connected hollow structure which takes various shapes according to the purpose, such as a connected hollow structure, in which hollow structures have a similar or
25 non-similar sectional shape. Otherwise, a connected hollow structure which is uniform in apparent thickness on the whole, and has a cylindrical shape, a gutter-like

shape, a channel-like shape or the like may be designed by properly selecting the sectional size of the hollow structures. Further, since the sides included in the sectional shape of the first and second hollow
05 structures are of the same number, the connected hollow structure in the fourth mode is formed by machining more easily.

Connected hollow structures in fifth to eighth modes of the present invention are typical of the
10 connected hollow structure in the fourth mode.

Namely, according to the connected hollow structure in the fifth mode, in the connected hollow structure in the fourth mode, the first and second hollow structures have a triangular section.

15 According to the fifth mode, since the hollow structures have a polygonal section including the fewest sides, it is the easiest to form the folds on the sheet and to fold the sheet by machining, and it is possible to fabricate a connected hollow structure most
20 efficiently.

According to the connected hollow structure in the sixth mode of the present invention, the first and second hollow structures have an isosceles triangular or right-angled triangular section.

25 According to the sixth mode, it is possible to fabricate a panel-shaped connected hollow structure, which is uniform in apparent thickness of each portion,

by designing the first and second hollow structures, for instance, so as to have the isosceles triangular section, to be of the same sectional size, and to be arranged such that the base surfaces of the first and
05 second hollow structures respectively face both surfaces of the connected hollow structure. Since a plane pressure acts on the connected hollow structure, mainly on two equal side walls of each hollow structure, the connected hollow structure shows withstanding strength
10 against the plane pressure more uniformly in each portion of the connected hollow structure. Further, when the connected hollow structure is exposed to a relatively high plane pressure, the hollow structures are transformed such that two same-sized and angled side
15 walls of the hollow structures are bent. Thus, the connected hollow structure shows elasticity against the plane pressure substantially uniformly in each portion of the connected hollow structure.

Further, according to the sixth mode, it is
20 possible to fabricate a connected hollow structure, which is uniform in apparent thickness of each portion and has a cylindrical shape on the whole or a semi-cylindrically channel-like shape, by designing the first and second hollow structures so as to have the isosceles
25 triangular section, to be of the same height in section and to form the base surface of each first hollow structure narrower than that of each second hollow

structure (i.e., to intersect two equilateral surfaces at a small angle).

Furthermore, according to the sixth mode, it is possible to fabricate a panel-shaped connected hollow
05 structure, which is uniform in apparent thickness of each portion, by designing the first and second hollow structures so as to have the right-angled triangular section, to be of the same sectional size, and to be arranged such that one of the side surfaces including a
10 right angle faces each surface of the connected hollow structure. In this case, a plane pressure acts on the connected hollow structure, mainly on vertical side walls and inclined side walls of the hollow structures. However, the connected hollow structure shows high
15 withstanding strength against the plane pressure, since the vertical side walls of the hollow structures are arranged at predetermined intervals.

According to the connected hollow structure in the seventh mode, the first and second hollow structures
20 have a quadrangular or pentagonal section.

According to the seventh mode, it is possible to fabricate a connected hollow structure which takes various shapes according to the purpose, such as a connected hollow structure which has a panel-like shape
25 to be uniform in thickness of each portion, or a cylindrical shape, a channel-like shape, a gutter-like shape or the like, by designing the first and second

hollow structures to have a special section.

According to the connected hollow structure in the eighth mode, the first and second hollow structures have a hexagonal or more polygonal section.

05 Each hollow structure of the connected hollow structure in the eighth mode has a large number of side surfaces. Thus, when the side surfaces of the hollow structures are of the same size, the connected hollow structure shows high withstanding strength against an
10 external force applied to the hollow structures in the length direction. Further, this connected hollow structure shows more flexible elasticity against a plane pressure, since, when the connected hollow structure is exposed to a plane pressure, the hollow structures are
15 transformed and absorb such a plane pressure. Furthermore, this connected hollow structure is suitable for use as a frame structure for packaging rod-shaped articles such as linear fluorescent lamps by inserting such articles into the hollow structures, for instance.

20 According to a connected hollow structure in a ninth mode of the present invention, in the connected hollow structure in the third mode, the first and second hollow structures in portions other than at least both ends of the connected hollow structure have a polygonal
25 section including sides of the same number, and the polygonal section of the first hollow structures is different from that of the second hollow structures in

number of sides.

Connected hollow structures in tenth and eleventh modes of the present invention are typical of the connected hollow structure in the ninth mode.

05 Namely, according to the connected hollow structure in the tenth mode, either the first or second hollow structures have a triangular section, and the others have a quadrangular or pentagonal section.

10 According to the connected hollow structure in the eleventh mode, either the first or second hollow structures have a quadrangular section, and the others have a pentagonal section.

15 According to the tenth and eleventh modes, it is possible to fabricate a connected hollow structure which takes various shapes according to the purpose, such as a connected hollow structure which has a panel-like shape to be uniform in thickness of each portion, or a cylindrical shape, a channel-like shape, a gutter-like shape or the like, by designing the first and second
20 hollow structures so as to have a special section, and by properly selecting the sectional size of these hollow structures.

25 According to a connected hollow structure in a twelfth mode of the present invention, in the connected hollow structure in the third mode, either the first or second hollow structures in portions other than at least both ends of the connected hollow structure have a

polygonal section including sides of the same number,
and the others include hollow structures respectively
having polygonal sections different in number of sides.

Connected hollow structures in thirteenth and
05 fourteenth modes of the present invention are typical of
the connected hollow structure in the twelfth mode.

Namely, according to the connected hollow
structure in the thirteenth mode, either the first or
second hollow structures have a triangular section,
10 and the others include hollow structures having a
quadrangular section and those having a pentagonal
section.

According to the connected hollow structure in
the fourteenth mode, either the first or second hollow
15 structures have a triangular section, and the others
include hollow structures having a triangular section
and those having a pentagonal section.

According to the thirteenth and fourteenth modes,
it is possible to fabricate a connected hollow structure
20 which takes various shapes according to the purpose,
such as a connected hollow structure which has a panel-
like shape to be uniform in thickness of each portion,
or a cylindrical shape, a channel-like shape, a gutter-
like shape or the like, by designing the others of the
25 first and second hollow structures to have a special
section, and by properly selecting the sectional size of
the hollow structures.

According to a connected hollow structure in a fifteenth mode of the present invention, the first and second hollow structures in portions other than at least both ends of the connected hollow structure include
05 hollow structures respectively having polygonal sections different in number of sides.

Connected hollow structures in sixteenth and seventeenth modes of the present invention are typical of the connected hollow structure in the fifteenth mode.

10 Namely, according to the connected hollow structure in the sixteenth mode, the first and second hollow structures include hollow structures having a triangular section and those having a quadrangular or pentagonal section.

15 According to the connected hollow structure in the seventeenth mode, the first and second hollow structures include hollow structures having a quadrangular section and those having a pentagonal section.

20 According to the sixteenth and seventeenth modes, it is possible to fabricate a connected hollow structure which takes various shapes according to the purpose, such as a connected hollow structure which has a panel-like shape to be uniform in thickness of each portion,
25 or a cylindrical shape, a channel-like shape, a gutter-like shape or the like, by designing the hollow structures other than those having the triangular

section to have a special section, and by properly selecting the sectional size of the hollow structures.

According to a connected hollow structure in an eighteenth mode of the present invention, in the
05 connected hollow structure in any of the fifth, seventh, tenth, thirteenth, fourteenth, sixteenth and seventeenth modes, one side surface of the first and second hollow structures in portions other than at least both ends of the connected hollow structure forms the partial
10 circumferences (i.e., partial circumferences facing both surfaces of the connected hollow structure) of the first and second hollow structures described above.

The connected hollow structure in the eighteenth mode has an advantage in being fabricated without
15 forming irregularities on the surface.

According to a connected hollow structure in a nineteenth mode of the present invention, in the connected hollow structure in the eighteenth mode, the partial circumferences of the first hollow structures
20 and those of the second hollow structures are respectively connected together, and the connected hollow structure has a panel-like shape to be substantially uniform in apparent thickness.

The connected hollow structure in the nineteenth mode has both surfaces of the substantially smooth
25 panel-like shape, and therefore, is suitable for use as a packaging member for packaging articles, and besides,

a core material of a heat-insulating panel or like hollow panel.

According to a connected hollow structure in a twentieth mode of the present invention, in the
05 connected hollow structure in the eighteenth mode, the partial circumferences of the first hollow structures and those of the second hollow structures are respectively connected together, and the connected hollow structure has a cylindrical or gutter-like shape
10 on the whole.

The connected hollow structure in the twentieth mode is suitable for use as a frame structure for packaging bottles or like articles having a rod-shaped drum portion.

15 According to a connected hollow structure in a twenty-first mode of the present invention, in the connected hollow structure in the eighteenth mode, the partial circumferences of the first hollow structures and those of the second hollow structures are
20 respectively connected together, and the connected hollow structure has a rising portion formed at least on one surface so as to gradually rise from one portion to the other.

The connected hollow structure in the twenty-
25 first mode is suitable for use as a member for packaging an article by forming the rising portion on one surface so as to be fit for the external shape of the article,

for instance.

According to a connected hollow structure in a twenty-second mode of the present invention, in the connected hollow structure in the twenty-first mode, a
05 pitch of the first and second hollow structures formed in the rising portion is made smaller in proportion to the scale of rising.

According to the connected hollow structure in the twenty-second mode, since the pitch of the hollow
10 structures formed in the rising portion is small, the withstanding strength against the plane pressure applied to the rising portion is easily made uniform with that against the plane pressure applied to a portion other than the rising portion.

15 According to a connected hollow structure in a twenty-third mode of the present invention, in the connected hollow structure in any of the nineteenth, twenty-first and twenty-second modes, the hollow
structure positioned at both ends of the connected
20 hollow structure has a chamfered inclined side surface extending in the length direction of the hollow structure.

In this case, the hollow structure positioned at both ends of the connected hollow structure in the
25 twenty-third mode has the chamfered inclined side surface, and therefore, even when other substance is brought into contact with the chamfered surface of the

connected hollow structure, the other substance or the chamfered surface of the connected hollow structure is hardly damaged.

According to a connected hollow structure in a
05 twenty-fourth mode of the present invention, in the connected hollow structure in the eighteenth mode, the connected hollow structure has a projection formed at least on one surface so as to extend in the length direction of the hollow structures, and the partial
10 circumferences of the first or second hollow structures in the projection are connected together.

The connected hollow structure in the twenty-fourth mode is very convenient for use as a packaging member for packaging an article by forming the
15 projection so as to be fit for a concave portion formed on the surface of the article.

According to a connected hollow structure in a twenty-fifth mode of the present invention, in the connected hollow structure in the twenty-fourth mode,
20 the connected hollow structure has a plurality of projections, and a portion between the projections is formed into a channel-like portion.

The connected hollow structure in the twenty-fifth mode is suitable for use as a packaging member for
25 packaging an article by inserting such an article wholly or partially into the channel-like portion.

According to a connected hollow structure in a

twenty-sixth mode of the present invention, in the connected hollow structure in the twenty-fourth or twenty-fifth mode, a pitch of the first and second hollow structures formed in the projection is made
05 smaller than that of the first and second hollow structure formed in a portion other than the projection.

According to the connected hollow structure in the twenty-sixth mode, since the pitch of the hollow structures formed in the projection is small, the
10 withstanding strength against the plane pressure applied to the projection is easily made uniform with that against the plane pressure applied to a portion other than the projection.

According to a connected hollow structure in a
15 twenty-seventh mode of the present invention, in the connected hollow structure in any of the twenty-fourth to twenty-sixth modes, the hollow structure positioned at both ends of the projection has a chamfered inclined side surface extending in the length direction of the
20 hollow structure at both ends of the projection.

In this case, the hollow structure positioned at both ends of the projection of the connected hollow structure in the twenty-seventh mode has the chamfered inclined side surface, and therefore, even when other
25 substance is brought into contact with the chamfered surface of the connected hollow structure, the other substance or the chamfered surface of the connected

hollow structure is hardly damaged. In addition, the chamfered surface functions as a guide for articles to be packaged.

According to a connected hollow structure in a
05 twenty-eighth mode of the present invention, in the connected hollow structure in any of the nineteenth to twenty-seventh modes, all or part of at least either the first or second hollow structures have the partial circumferences of a circular arc section.

10 The hollow structures facing the surface of the connected hollow structure in the twenty-eighth mode have the partial circumferences of the circular arc section, and therefore, when this connected hollow structure is exposed to a plane pressure, the circular
15 arc portion of the hollow structures shows elasticity (cushioning properties) and partially absorbs such a plane pressure.

According to a connected hollow structure in a
twenty-ninth mode of the present invention, in the
20 connected hollow structure in the third mode, all or part of at least either the first or second hollow structures have the partial circumferences respectively composed of a plurality of side surfaces substantially uniformly projecting from one surface of the connected
25 hollow structure, and the hollow structures have a quadrangular or more polygonal section.

A plurality of side surfaces of each hollow

structure form the partial circumference facing the surface of the connected hollow structure in the twenty-ninth mode, and therefore, when the connected hollow structure is exposed to a plane pressure, the partial
05 circumferences respectively composed of the plurality of side surfaces are transformed and partially absorb such a pressure.

According to a connected hollow structure in a thirtieth mode of the present invention, in the
10 connected hollow structure in the twenty-ninth mode, the partial circumferences of the first hollow structures and those of the second hollow structures are respectively connected together, and the connected hollow structure has a panel-like shape to be
15 substantially uniform in apparent thickness.

The connected hollow structure in the thirtieth mode has the panel-like shape to be substantially uniform in apparent thickness, and therefore, is suitable for use as a member for packaging articles, and
20 besides, a core material of a heat-insulating panel or like hollow panel.

According to a connected hollow structure in a thirty-first mode of the present invention, in the connected hollow structure in the twenty-ninth mode, the
25 partial circumferences of the first hollow structures and those of the second hollow structures are respectively connected together, and the connected

hollow structure has a cylindrical or gutter-like shape on the whole.

The connected hollow structure in the thirty-first mode is suitable for use as a frame structure for
05 packaging bottles or like articles having a rod-shaped drum portion.

According to a connected hollow structure in a thirty-second mode of the present invention, in the connected hollow structure in the twenty-ninth mode,
10 the partial circumferences of the first hollow structures and those of the second hollow structures are respectively connected together, and the connected hollow structure has a rising portion formed at least on one surface to gradually rise from one portion to the
15 other.

The connected hollow structure in the thirty-second mode is suitable for use as a member for packaging an article by forming the rising portion on one surface so as to be fit for the external shape of
20 the article, for instance.

According to a connected hollow structure in a thirty-third mode of the present invention, in the connected hollow structure in the thirty-second mode, a pitch of the first and second hollow structures formed
25 in the rising portion is made smaller in proportion to the scale of rising.

According to the connected hollow structure in

the thirty-third mode, since the pitch of the hollow structures formed in the rising portion is small, the withstanding strength against the plane pressure applied to the rising portion is made easily uniform with that
05 against the plane pressure applied to a portion other than the rising portion.

According to a connected hollow structure in a thirty-fourth mode of the present invention, in the connected hollow structure in any of the nineteenth to
10 thirty-third modes, each side wall common to the first and second hollow structures adjacent to each other has an appropriate number of bending node stripes extending in the length direction of each hollow structure.

When a pressure of not less than a predetermined
15 value is applied perpendicularly to the hollow structures of the connected hollow structure in the thirty-fourth mode, the side walls common to the first and second hollow structures adjacent to each other are bent along the nodes to a certain extent and function as
20 cushions to absorb such a pressure.

According to a connected hollow structure in a thirty-fifth mode of the present invention, in the connected hollow structure in the thirty-fourth mode, each bending node takes the shape of a small groove and
25 is formed on one surface of each side wall common to the first and second hollow structures adjacent to each other, and the grooves are bent inwardly in a convex

shape when the side walls are bent.

According to a connected hollow structure in a
thirty-sixth mode of the present invention, in the
connected hollow structure in any of the nineteenth to
05 thirty-third modes, at least part of the first and
second hollow structures have an appropriate number of
holes formed in portions other than the partial
circumferences. Thus, the weight of the connected
hollow structure is reduced in proportion to the number
10 of holes, and the side walls of the hollow structures
having the holes are easily transformed against a plane
pressure, and as a result, show more flexible
elasticity.

According to a connected hollow structure in a
15 thirty-seventh mode of the present invention, in the
connected hollow structure in the third mode, the first
and second hollow structures are formed such as to
gradually reduce the sectional size from one end toward
the other.

20 The connected hollow structure in the thirty-
seventh mode has a circular or sectorial plane such that
the side of each hollow structure having the smaller
sectional size forms an inner periphery, and both
surfaces of the connected hollow structure are inclined
25 downwards toward the inner periphery. Thus, the
connected hollow structure in the thirty-seventh mode is
suitable for use as a packaging member for protecting

the end of a rod-shaped member by bringing the connected hollow structure into contact with the end of the rod-shaped member.

According to a connected hollow structure in a
05 thirty-eighth mode of the present invention, in the connected hollow structure in the third mode, all or part of at least either the first or second hollow structures have a plurality of small hollow portions. Since the hollow structures have the plurality of small
10 hollow portions, the withstanding strength against a plane pressure is increased. Thus, the connected hollow structure in the thirty-eighth mode is suitable for use as a carrier for carrying adsorbents by utilizing the small hollow portions of the hollow structures.

15 According to a connected hollow structure in a thirty-ninth mode of the present invention, in the connected hollow structure in the third mode, the first and second hollow structures have a pentagonal or more polygonal section, and either the first or second hollow
— 20 structures have a portion of a concave section formed in the side wall common to the first and second hollow structures adjacent to each other.

When a plane load is applied to the connected hollow structure in the thirty-ninth mode, the side
25 walls are further bent along the concave portions so as to enlarge the concave portions, and satisfactorily function as cushions to absorb such a plane load.

A connected hollow structure in a fortieth mode of the present invention, in the connected hollow structure in the first mode, comprises parallel connecting sheet portions bonded together, and a large
05 number of cylindrical hollow structures formed by bonding circumferential portions together in the length direction in joint portions between the connecting sheet portions adjacent to each other.

The connected hollow structure in the fortieth
10 mode is suitable for use as a packaging member for protecting linear fluorescent lamps or like rod-shaped or cylindrical articles to be packaged by inserting such articles into the cylindrical hollow structures, or other packaging members such as a cushioning material by
15 making use of flexible cushioning properties of the hollow structures.

According to a connected hollow structure in a forty-first mode of the present invention, in the connected hollow structure in the fortieth mode, the
20 hollow structures have a circular or elliptical section.

The connected hollow structure in the forty-first mode has the hollow structures of the cylindrical or elliptical shape, and therefore, is more suitable for use as a packaging member for protecting rod-shaped or
25 cylindrical articles to be packaged by inserting such articles into the hollow structures, or other packaging members such as a cushioning material by making use of

the cushioning properties of the hollow structures.

According to a connected hollow structure in a
forty-second mode of the present invention, in the
connected hollow structure in the fortieth or forty-
05 first mode, the connected hollow structure has a
cylindrical shape with the hollow structures positioned
along the inner periphery.

The connected hollow structure in the forty-
second mode is suitable for use as a cushioning material
10 for articles to be packaged, or other packaging members
for protecting bottles or like articles having a drum
portion by inserting such articles into the connected
hollow structure.

According to a connected hollow structure in a
15 forty-third mode of the present invention, in the
connected hollow structure in the first mode, a large
number of first and second hollow structures having a
drop-shaped or pseudo drop-shaped section are formed in
an alternate arrangement and in an alternately inverse
20 position by forming portions having the sectional shape
of a letter S and portions having the sectional shape of
an inverted letter S in an alternate arrangement such
that the side of each portion having the shape of the
letter S is connected to the side of the adjacent
25 portion having the shape of the inverted letter S.

The connected hollow structure in the forty-third
mode is suitable for use as a packaging member for

protecting rod-shaped or cylindrical articles to be packaged by inserting such articles into the hollow structures, or other packaging members such as a cushioning material by making use of the cushioning
05 properties of the hollow structures.

According to a connected hollow structure in a forty-fourth mode of the present invention, either the first or second hollow structures are smaller in sectional size than the others, and the connected hollow
10 structure has a cylindrical shape on the whole with the hollow structures of the smaller sectional size positioned along the inner periphery.

The connected hollow structure in the forty-fourth mode is suitable for use as a cushioning material
15 for articles to be packaged, or other packaging members for protecting bottles or like articles having a drum portion by inserting such articles into the connected hollow structure.

According to a connected hollow structure in a
20 forty-fifth mode of the present invention, in the connected hollow structure in the first mode, a large number of hollow structures are formed in a dense arrangement in parallel to each other such that first hollow portions having an angular section and second
25 hollow portions having an inverted angular section are combined together in a symmetrical shape, and the hollow structures adjacent to each other are connected together

substantially in the shape of a letter S or an inverted letter S.

Since the hollow structures composed of the hollow portions show flexible elasticity, the connected
05 hollow structure in the forty-fifth mode is suitable for use as a packaging member such as a cushioning material for articles to be packaged, and besides, other packaging members for protecting linear fluorescent lamps or like rod-shaped or cylindrical articles to be
10 packaged by inserting such articles into the hollow portions. Further, when the connected hollow structure in the forty-fifth mode has more hollow structures which are rounded in a cylindrical shape on the whole, the hollow portions positioned along the cylindrical inner
15 surface are compressively transformed to easily form a connected hollow structure of a cylindrical shape. Thus, the connected hollow structure in the forty-fifth mode is suitable for use as a packaging member for protecting bottles or like articles to be packaged.

20 — According to a connected hollow structure in a forty-sixth mode of the present invention, in the connected hollow structure in the forty-fifth mode, either the first or second hollow portions have a semicircular, trapezoidal or triangular section, and the
25 others have a semicircular, trapezoidal or triangular section in inverse relation to the afore-mentioned hollow portions.

The connected hollow structure in the forty-sixth mode has an advantage in being easily fabricated, since the hollow portions have the shape as described above.

05 A packaging member in a forty-seventh mode of the present invention is wholly or partly formed of the connected hollow structure in any of the first to forty-sixth modes.

A packaging member in a forty-eighth mode of the present invention is composed of a connected bottom
10 structure, a connected side structure placed uprightly on the side of the connected bottom structure, and a connected rear structure placed uprightly on the rear of the connected bottom structure and at a right angle with the connected side structure. The connected
15 bottom structure, the connected side structure and the connected rear structure are respectively formed of the connected hollow structure as defined in claim 19 or 30.

The packaging member in the forty-eighth mode is
— suitable for use as a corner protection frame for
20 protecting an article having a corner including three sides at right angles to one another by bringing the corner portion of such an article into contact with the inside of the packaging member.

According to a packaging member in a forty-ninth
25 mode of the present invention, in the packaging member in the forty-eighth mode, the connected side structure is placed on the connected bottom structure such that

first and second hollow structures of the connected side structure are substantially at right angles with first and second hollow structures of the connected bottom structure; the connected rear structure is placed on the
05 connected bottom structure such that first and second hollow structures of the connected rear structure extend along the first and second hollow structures of the connected bottom structure, while being oriented at an angle of 90° with the first and second hollow structures
10 of the connected bottom structure; the connected side structure and the connected rear structure are connected to the connected bottom structure through individual connecting sheet portions; and the connected bottom structure, the connected side structure and the
15 connected rear structure respectively have the first and second hollow structures of the same sectional shape and are comprised of a piece of sheet.

Since the packaging member in the forty-ninth mode is formed as described above, the connected bottom
20 structure, the connected side structure and the connected rear structure are substantially uniform in withstanding strength and elasticity. Further, this packaging member is comprised of a piece of sheet, and as a result, is formed economically.

25 According to a packaging member in a fiftieth mode of the present invention, in the packaging member in the forty-eighth or forty-ninth mode, the partial

circumferences, which face the inside of the packaging member, of at least part of hollow structures have a circular arc section. Thus, when a plane pressure is applied to the connected hollow structure, the partial
05 circumferences of the circular arc section show elasticity (cushioning properties) and partially absorb such a pressure.

A packaging member in a fifty-first mode of the present invention is comprised of the layered connected
10 hollow structure in the nineteenth mode formed in block shape such that hollow portions of each layer are in parallel to each other. The packaging member in the fifty-first mode is suitable for use as a packaging support block or cushioning block, and besides, a
15 packaging frame structure for encasing bottles or like articles by inserting such articles into the hollow structures.

According to a packaging member in a fifty-second mode of the present invention, in the packaging
20 member in the fifty-first mode, a hole is formed perpendicularly to the hollow structures of the connected hollow structure.

The packaging member in the fifty-second mode is suitable for use as a packaging frame structure also
25 serving as a cushioning material for packaging an article having a portion fit for the shape of the hole by inserting such a portion of the article into the

hole.

According to a packaging member in a fifty-third mode of the present invention, in the packaging member in the fifty-first or fifty-second mode, the first and
05 second hollow structures of the connected hollow structures of the layers are formed in parallel to each other in a symmetrical arrangement in section, and the connected hollow structures of the layers adjacent to each other are connected together as one body and
10 comprised of a piece of sheet.

According to the packaging member in the fifty-third mode, the connected hollow structure of each layer shows substantially uniform elasticity and withstanding strength against a plane pressure. Further, the
15 packaging member in the fifty-third mode is wholly comprised of a piece of sheet, and as a result, is formed economically.

A packaging member in a fifty-fourth mode of the present invention is composed of a connected bottom
20 structure, a pair of connected side structures placed uprightly on both sides of the connected bottom structure, a connected front structure placed uprightly on the front of the connected bottom structure and at right angles with the connected side structures, and a
25 connected rear structure placed uprightly on the rear of the connected bottom structure and at right angles with the connected side structures, and the connected bottom

structure, the connected side structures, the connected front structure and the connected rear structure are formed of the connected hollow structure as defined in claim 19 or 30.

05 The packaging member in the fifty-fourth mode takes the shape of a relatively high-edged tray on the whole, and therefore, is suitable for use as a protecting frame for packaging an article having a portion fit for the internal shape of the packaging
10 member by inserting such a portion of the article into the packaging member, or a pallet for carrying articles and so on.

 According to a packaging member in a fifty-fifth mode of the present invention, in the packaging member
15 in the fifty-fourth mode, the connected front structure and the connected rear structure are placed on the connected bottom structure such that the first and second hollow structures of the connected front
structure and the connected rear structure extend along
20 the first and second hollow structures of the connected bottom structure, while being oriented at an angle of 90° with the first and second hollow structures of the connected bottom structure; both the connected side
structures are placed on the connected bottom structure
25 such that the first and second hollow structures of the connected side structures are substantially at right angles with the first and second hollow structures of

the connected bottom structure; the connected front structure and the connected rear structure are connected to the connected bottom structure through connecting sheet portions; the connected front structure and one
05 connected side structure, and the connected rear structure and the other connected side structure are respectively connected together through individual connecting sheet portions; and the connected bottom structure, both the connected side structures, the
10 connected front structure and the connected rear structure have the first and second hollow structures of the same sectional shape and are comprised of a piece of sheet.

According to the packaging member in the fifty-
15 fifth mode, the connected bottom structure, both the connected side structures, the connected front structure and the connected rear structure show substantially uniform withstanding strength and elasticity. Further,
the packaging member in the fifty-fifth mode is wholly
20 comprised of a piece of sheet, and as a result, is formed economically.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a fragmentary perspective view of a connected hollow structure in a first embodiment
25 according to the present invention;

Fig. 2 is a fragmentary end view of the connected

hollow structure of Fig. 1, which is transformed under the action of a vertical load;

Fig. 3 is a fragmentary developed plan view of the connected hollow structure of Fig. 1;

05 Fig. 4 is a fragmentary perspective view of a connected hollow structure in a second embodiment according to the present invention;

Fig. 5 is a fragmentary developed plan view of the connected hollow structure of Fig. 4;

10 Fig. 6 is a fragmentary enlarged sectional view of the connected hollow structure of Fig. 4;

Fig. 7 is a fragmentary perspective view of a connected hollow structure in a third embodiment according to the present invention;

15 Fig. 8 is a perspective view of a connected hollow structure in a fourth embodiment according to the present invention;

Fig. 9 is an end view of the connected hollow structure of Fig. 8, which is transformed under the
20 action of a vertical load;

Fig. 10 is a perspective view of a connected hollow structure in a fifth embodiment according to the present invention;

Fig. 11 is a fragmentary developed plan view of
25 the connected hollow structure of Fig. 10;

Fig. 12 is a developed perspective view of the connected hollow structure of Fig. 10 immediately before

completion;

Fig. 13 is a perspective view of a connected hollow structure in a sixth embodiment according to the present invention;

05 Fig. 14 is a perspective view of a connected hollow structure in a seventh embodiment according to the present invention;

Fig. 15 is a fragmentary developed plan view of the connected hollow structure of Fig. 13;

10 Fig. 16 is a developed side view of the connected hollow structure of Fig. 13 immediately before completion;

Fig. 17 is a fragmentary developed plan view of the connected hollow structure of Fig. 14;

15 Fig. 18 is a perspective view of a connected hollow structure in an eighth embodiment according to the present invention;

Fig. 19 is a fragmentary developed plan view of the connected hollow structure of Fig. 18;

20 Fig. 20 is a perspective view of a connected hollow structure in a ninth embodiment according to the present invention;

Fig. 21(A) is an end view of a connected hollow structure in a tenth embodiment according to the present
25 invention;

Fig. 21(B) is an end view of a connected hollow structure in an eleventh embodiment according to the

present invention;

Fig. 22 is a developed plan view of the connected hollow structure of Fig. 20;

Fig. 23 is a developed side view of a connected
05 hollow structure in a twelfth embodiment according to the present invention before complete development;

Fig. 24 is a side view of the connected hollow structure of Fig. 23 after completion;

Fig. 25 is a fragmentary side view of a connected
10 hollow structure in a thirteenth embodiment according to the present invention;

Fig. 26 is a fragmentary side view of a connected hollow structure in a fourteenth embodiment according to the present invention;

15 Fig. 27 is a perspective view of a connected hollow structure in a fifteenth embodiment according to the present invention;

Fig. 28 is a perspective view of a connected hollow structure in a sixteenth embodiment according to
20 the present invention;

Fig. 29 is a perspective view of a connected hollow structure in a seventeenth embodiment according to the present invention;

Fig. 30 is a fragmentary end view of a connected
25 hollow structure in an eighteenth embodiment according to the present invention;

Fig. 31 is a fragmentary end view of a connected

hollow structure in a nineteenth embodiment according to the present invention;

Fig. 32 is a fragmentary end view of a connected hollow structure in a twentieth embodiment according to
05 the present invention;

Fig. 33 is a fragmentary end view of a connected hollow structure in a twenty-first embodiment according to the present invention;

Fig. 34 is a fragmentary end view of a connected
10 hollow structure in a twenty-second embodiment according to the present invention;

Fig. 35 is a fragmentary end view of a connected hollow structure in a twenty-third embodiment according to the present invention;

15 Fig. 36 is a fragmentary perspective view of a connected hollow structure in a twenty-fourth embodiment according to the present invention;

Fig. 37 is a fragmentary end view of a connected hollow structure in a twenty-fifth embodiment according
20 to the present invention;

Fig. 38 is a fragmentary end view of a connected hollow structure in a twenty-sixth embodiment according to the present invention;

Fig. 39 is a fragmentary end view of a connected
25 hollow structure in a twenty-seventh embodiment according to the present invention;

Fig. 40 is a fragmentary end view of a connected

hollow structure in a twenty-eighth embodiment according to the present invention;

Fig. 41 is a fragmentary perspective view of a connected hollow structure in a twenty-ninth embodiment
05 according to the present invention;

Fig. 42(C) is a fragmentary end view of a connected hollow structure in a thirtieth embodiment according to the present invention;

Fig. 42(D) is a fragmentary end view of a
10 connected hollow structure in a thirty-first embodiment according to the present invention;

Fig. 43 is an end view of a connected hollow structure in a thirty-second embodiment according to the present invention;

15 Fig. 44 is an end view of a connected hollow structure in a thirty-third embodiment according to the present invention;

Fig. 45 is a fragmentary perspective view of a connected hollow structure in a thirty-fourth embodiment
20 according to the present invention;

Fig. 46 is a fragmentary end view of a connected hollow structure in a thirty-fifth embodiment according to the present invention;

Fig. 47 is a fragmentary end view of a connected
25 hollow structure in a thirty-sixth embodiment according to the present invention;

Fig. 48 is a fragmentary perspective view of a

connected hollow structure in a thirty-seventh embodiment according to the present invention;

Fig. 49 is a fragmentary perspective view of a connected hollow structure in a thirty-eighth embodiment
05 according to the present invention;

Fig. 50 is a fragmentary perspective view of a connected hollow structure in a thirty-ninth embodiment according to the present invention;

Fig. 51 is a fragmentary perspective view of a
10 connected hollow structure in a fortieth embodiment according to the present invention;

Fig. 52 is a fragmentary perspective view of a connected hollow structure in a forty-first embodiment according to the present invention;

15 Fig. 53 is a perspective view of a connected hollow structure in a forty-second embodiment according to the present invention;

Fig. 54 is an end view of the connected hollow structure of Fig. 53, which is transformed under the
20 action of a vertical load;

Fig. 55 is a fragmentary end view of a connected hollow structure in a forty-third embodiment according to the present invention;

Fig. 56 is a fragmentary perspective view of a
25 connected hollow structure in a forty-fourth embodiment according to the present invention;

Fig. 57 is a fragmentary end view of a connected

hollow structure in a forty-fifth embodiment according to the present invention;

Fig. 58 is a fragmentary end view of a connected hollow structure in a forty-sixth embodiment according to the present invention;

Fig. 59 is a fragmentary end view of a connected hollow structure in a forty-seventh embodiment according to the present invention;

Fig. 60 is a fragmentary end view of a connected hollow structure in a forty-eighth embodiment according to the present invention;

Fig. 61 is a fragmentary end view of a connected hollow structure in a forty-ninth embodiment according to the present invention;

Fig. 62 is a fragmentary perspective view of a connected hollow structure in a fiftieth embodiment according to the present invention;

Fig. 63 is a fragmentary end view of a connected hollow structure in a fifty-first embodiment according to the present invention;

Fig. 64 is a perspective view of a connected hollow structure in a fifty-second embodiment according to the present invention;

Fig. 65 is a fragmentary end view of a connected hollow structure in a fifty-third embodiment according to the present invention;

Fig. 66 is a fragmentary side view of a connected

hollow structure in a fifty-fourth embodiment according to the present invention;

Fig. 67 is a fragmentary side view of a connected hollow structure in a fifty-fifth embodiment according to the present invention;

Fig. 68 is a fragmentary perspective view of a connected hollow structure in a fifty-sixth embodiment according to the present invention;

Fig. 69 is a fragmentary side view of a connected hollow structure in a fifty-seventh embodiment according to the present invention;

Fig. 70 is a fragmentary perspective view of a connected hollow structure in a fifty-eighth embodiment according to the present invention;

Fig. 71 is a side view of a connected hollow structure in a fifty-ninth embodiment according to the present invention;

Fig. 72 is a fragmentary perspective view of a connected hollow structure in a sixtieth embodiment according to the present invention;

Fig. 73 is a fragmentary perspective view of a connected hollow structure in a sixty-first embodiment according to the present invention; and

Fig. 74 is a fragmentary perspective view of a connected hollow structure in a sixty-second embodiment according to the present invention.

BEST MODE FOR EMBODYING THE INVENTION

Hereinafter will be described a connected hollow structure according to the present invention in detail with reference to the accompanying drawings.

05 (First embodiment)

Fig. 1 shows a connected hollow structure corresponding to claims 5, 6 and 19.

A connected hollow structure 1 in a first embodiment is fabricated from a sheet a (See Fig. 2) consisting of a piece of board. The connected hollow structure 1 comprises hollow structures 10 including first hollow structures 11, which are of the substantially same size and have an isosceles triangular section (close to a regular triangular section in this embodiment), and second hollow structures 12 which are substantially equal in size and sectional shape to the first hollow structures. However, the second hollow structure 12 at both ends of the connected hollow structure 1 has a right-angled triangular section, and is equal in height to other second hollow structures 12.

The first and second hollow structures 11, 12 are formed such that a corner portion (i.e., an angular portion included in two equilaterals) 13 of each first hollow structure 11 and that of each second hollow structure 12 are directed to be reverse to each other, and a partial circumference 14 forming one side surface

(i.e., a base surface) of each first hollow structure 11 and that forming one side surface of each second hollow structure 12 face the opposite surfaces of the connected hollow structure 1.

05 The first hollow structures 11, 11 adjacent to each other are bonded together in a portion of the corner portion 13 of each second hollow structure 12 positioned between the first hollow structures 11, 11 adjacent to each other. The second hollow structures
10 12, 12 adjacent to each other are bonded together in a portion of the corner portion 13 of each first hollow structure 11 positioned between the second hollow structures 12, 12 adjacent to each other.

 The first and second hollow structures 11, 12
15 adjacent to each other have side walls 15, which form the borders between the first and second hollow structures adjacent to each other, in common. Therefore, each side wall 15 in the border between the first and second hollow structures adjacent to each
20 other has the same thickness as the sheet a which is used as a material of the connected hollow structure.

 According to the connected hollow structure 1 formed as described above, the partial circumferences 14 of the first hollow structures 11 adjacent to each other
25 and those of the second hollow structures 12 adjacent to each other are respectively connected together. Thus, the connected hollow structure 1 has a panel-like shape

to be substantially uniform in apparent thickness T, and takes the shape resembling a unicursal figure in section.

The connected hollow structure 1 in the first
05 embodiment is fabricated as follows. Firstly, as shown in Fig. 3, while the sheet a used as a material of the connected hollow structure is being delivered, convex folds a2, a2, along which the sheet a is folded in a convex shape (i.e., the shape of an inverted letter V in
10 section), and concave folds a1, a1, along which the sheet a is folded in a concave shape (i.e., the shape of a letter V), are formed on the sheet a so as to extend in the cross direction of the sheet in an alternate arrangement every two rows and in parallel to each other
15 by using, for instance, a press or rotary press cutter. When a corrugated fiberboard is applied to the sheet a, the folds a1, a2 are formed so as to intersect flutes (not shown) of the corrugated fiberboard at a predetermined angle.

20 The distance between the concave folds a1, a1, that between the convex folds a2, a2 and that between the concave and convex folds a1, a2 adjacent to each other are determined according to the sectional size of the hollow structures 11, 12.

25 Subsequently, the top surface of the sheet a at portions of the convex folds a2 and the undersurface of the sheet a at portions of the concave folds a1 are

respectively coated with glue (i.e., an adhesive).

Thereafter, the sheet a is folded in sequence along the folds a1, a2 from the leading end of the sheet a in the delivery direction to form the upper and lower partial
05 circumferences 14, 14, and the sides of the upper and lower partial circumferences 14, 14 adjacent to each other are bonded together so as to be flush with each other.

When the sheet a is folded in sequence as
10 described above, the convex folds a2, a2 form upward corner portions 13 of the first hollow structures 11, and the concave folds a1, a1 form downward corner portions 13 of the second hollow structures 12. Thus, it is possible to form the connected hollow structure 1
15 as shown in Fig. 1 by bonding both sides of the partial circumferences 14, 14 of the mutually-adjacent first hollow structures 11, 11 together, while bonding both sides of the partial circumferences 14, 14 of the mutually-adjacent second hollow structures 12, 12
20 together, and by cutting the sheet a, which is being delivered, along a required portion.

The connected hollow structure 1 in the first embodiment shows high withstanding strength, which also acts uniformly on the whole, since the hollow structures
25 11, 12 have the isosceles triangular section, and a plane pressure is applied to the connected hollow structure 1 so as to substantially uniformly act on the

uniformly-inclined side walls 15 common to the adjacent hollow structures 11, 12 adjacent to each other.

When the connected hollow structure is exposed to a plane pressure of not less than a predetermined value, 05 the hollow structures 11, 12 adjacent to each other are transformed such that the inclined side walls thereof are bent as shown in Fig. 2, and as a result, the connected hollow structure 1 shows elasticity (i.e., cushioning properties) within the limit of this 10 transformation.

Thus, the connected hollow structure 1 in this embodiment is used as a panel-shaped packaging member or a cushioning material, and besides, a core material of a heat-insulating panel or like panels, a wall material, a 15 pallet, and a carrier for carrying adsorbents.

Otherwise, the connected hollow structure 1 in this embodiment is used as a packaging frame structure for wholly packaging bottles, fluorescent tubes, elec- 20 tronic parts or like articles by inserting such articles into hollow portions of the hollow structures 11, 12.

An A-flute corrugated fiberboard (having a flute height of 5.5 mm) consisting of a kraft linerboard of 160g/m² and a corrugating medium of 125g/m² was fabricated as well as a connected hollow structure, 25 which has a sectional shape similar to that of the connected hollow structure 1 in this embodiment and shows withstanding strength against a plane pressure

substantially similarly to that of the A-flute corrugated fiberboard. In this case, the latter was about one seventh to one tenth as heavy as the former.

Thus, the connected hollow structure 1 of the
05 sectional shape like the first embodiment is extremely higher in withstanding strength against a plane pressure and also far smaller in apparent specific gravity (g/cc) than the corrugated fiberboard.

Further, the connected hollow structure 1 shows
10 high withstanding strength against an external force applied in the direction of the hollow structures 11, 12, since the hollow structures 11, 12 are connected together in a parallel and dense arrangement.

The strength of elastic force of the connected
15 hollow structure 1 varies depending on the quality and thickness of the sheet a, and the shape and size of the hollow structures 11, 12. When the hollow structures 11, 12 have the isosceles triangular section like the first embodiment, the elasticity is made more flexible,
20 whereas the elastic force or withstanding strength is reduced, according as the bases of the hollow structures 11, 12 in section are enlarged.

It is possible to form the connected hollow structure 1, which has the void content according to the
25 purpose and shows the hardness, withstanding strength and elastic force (cushioning force) according to the purpose, by freely selecting the sectional size of the

hollow structures 11, 12.

Since the connected hollow structure 1 is not formed as a standardized product differently from the corrugated fiberboard, it is possible to select the
05 material or the sectional shape of the hollow structures 11, 12 according to the purpose.

Further, the connected hollow structure 1 takes the shape resembling a unicursal figure in section, and therefore, is fabricated from a piece of sheet. Thus,
10 any step of bonding a plurality of sheets of various sectional shapes together in layers is not needed, differently from a case of fabricating the corrugated fiberboard, and as a result, it is possible to fabricate the connected hollow structure 1 through fewer steps at
15 low cost.

(Second embodiment)

Fig. 4 is a perspective view showing a connected hollow structure in a second embodiment according to the present invention.

20 A connected hollow structure 1 in the second embodiment is substantially similar in basic constitution to the connected hollow structure in the first embodiment.

Dovetailed projections 16 of a width narrowing
25 toward their bases are formed at certain intervals on both surfaces of the connected hollow structure 1 so as

to horizontally project from one side of the partial
circumferences 14 of the first hollow structures 11, 11
adjacent to each other and also from one side of the
partial circumferences 14 of the second hollow
05 structures 12, 12 adjacent to each other. On the other
hand, recess holes 17 fitted to the projections 16 are
formed on the other side of the partial circumferences
14. Thus, the first hollow structures 11, 11 adjacent
to each other and the second hollow structures 12, 12
10 adjacent to each other are respectively connected
together by fitting the projections 16 into the
corresponding recess holes 17.

In order to respectively connect the first hollow
structures 11, 11 and the second hollow structures 12,
15 12 together, the projections 16 are formed by incising
the side walls 15 adjacent to the partial circumferences
14 so as to start incising from portions of the folds
a1, a2 in case of forming the folds a1, a2 on the sheet
a. Any folds a1, a1 are not formed along the bases of
20 the projections 16.

At the same time, the recess holes 17 fitted to
the projections 16 are formed in portions of the side
walls 15, 15 such that the recess holes 17 extend over
the partial circumference 14 adjacent to each side wall
25 up to an extent corresponding to a thickness of the
sheet a.

The projections 16 enter the recess holes 17 so

as to cover the recess holes with the projections, as shown on an enlarged scale in Fig. 6, by forming the projections 16 and the recess holes 17 in required portions of the sheet a as described above. Thus, the
05 projections 16 are smoothly fitted into the recess holes 17, in case of folding the sheet a along the folds a1, a2.

The connected hollow structure 1 in the second embodiment is fabricated more simply, since any step of
10 gluing the sheet a is not needed in case of respectively connecting the partial circumferences 14, 14 of the mutually-adjacent first hollow structures 11, 11 and those of the mutually-adjacent second hollow structures 12, 12 together.

15 Other respects of the functions and effects of the connected hollow structure 1 in the second embodiment are substantially similar to those of the connected hollow structure 1 in the first embodiment, and hence, the description thereof will be omitted.

20 (Third embodiment)

Fig. 7 shows a connected hollow structure in a third embodiment according to the present invention.

According to a connected hollow structure 1 in the third embodiment, a large number of holes 18 of a
25 predetermined shape are formed in the inclined side walls 15 which form the borders between the hollow

structures 11, 12 adjacent to each other.

Since the large number of holes 18 are formed in the side walls 15, the connected hollow structure 1 in this embodiment reduces its whole apparent specific
05 gravity and shows more flexible elasticity (i.e., reduces its elastic force) accordingly.

Thus, it is possible to form a connected hollow structure, which shows desired elasticity, by selecting the shape, size and density of the holes 18.

10 Other respects of the constitution, functions and effects of the connected hollow structure 1 in the third embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

15 (Fourth embodiment)

Fig. 8 shows a connected hollow structure corresponding to claims 6 and 19.

A connected hollow structure 1 in a fourth embodiment has a flat panel-like shape on the whole
20 similarly to the connected hollow structure 1 in the first embodiment, except that first and second hollow structures 11, 12 in the fourth embodiment have a rectangular equilateral triangular section.

The connected hollow structure 1 in this
25 embodiment is fabricated as follows. Firstly, a sheet (not shown) used as a material of the connected hollow

structure 1 is folded along concave and convex folds.
In this case, the folding of the sheet starts according
to the direction as shown by an arrow b in Fig. 8.

Subsequently, while the sheet is being folded in
05 sequence, the partial circumferences 14 adjacent to each
other are connected together by bonding in portions of
upper and lower corner portions 13 such that the hollow
structures 11, 12 of the rectangular equilateral
triangular section are densely arranged in an
10 alternately inverse position in section.

The connected hollow structure 1 in this
embodiment withstands a plane pressure mainly by
vertical side walls 15 and inclined side walls 15 of the
hollow structures 11, 12. Thus, when the connected
15 hollow structure 1 is exposed to a plane pressure of not
less than a predetermined value, the side walls 15 are
bent as shown in Fig. 9 and absorb such a plane
pressure.

Other respects of the constitution, functions and
20 effects of the connected hollow structure in the fourth
embodiment are substantially similar to those of the
connected hollow structure in the first embodiment, and
hence, the description thereof will be omitted.

(Fifth embodiment)

25 Fig. 10 shows a packaging member comprised
of a connected hollow structure in an embodiment

corresponding to claims 48 and 49 according to the present invention.

A connected hollow structure 1 in a fifth embodiment is formed as a corner protection frame, which
05 also serves as a cushioning material for protecting a corner portion of an article when packaged, and is composed of a connected bottom structure 1a, a connected side structure 1b uprightly placed on the top surface of one side of the connected bottom structure 1a, and a
10 connected rear structure 1c uprightly and sideways placed on the top surface of the rear side of the connected bottom structure 1a. The connected bottom, side and rear structures 1a, 1b, 1c are substantially at right angles with one another.

15 First and second hollow structures 11, 12 of the connected bottom, side and rear structures 1a, 1b, 1c are of the same size and have an isosceles triangular section. However, the second hollow structures 12 on both ends of the connected bottom, side and rear
20 structures 1a, 1b, 1c have a right-angled triangular section.

The connected bottom structure 1a and the connected side structure 1b are connected together as one body through connecting sheet portions a3, and the
25 connected bottom structure 1a and the connected rear structure 1c are connected together as one body through another connecting sheet portion a4.

The connected hollow structure 1 in the fifth embodiment is fabricated as follows. Firstly, as shown in Fig. 11, while a sheet a is being delivered in a certain direction, convex folds a2, a2 and concave folds
05 a1, a1 are formed on the sheet a so as to extend in the cross direction of the sheet in an alternate arrangement according to the sectional height and base width of the hollow structures 11, 12, similarly to the case in the first embodiment.

10 Recess portions a7 of a width corresponding to the sectional height of the hollow structures 11, 12 are formed along the border between a sheet portion 1a', which forms the connected bottom structure 1a shown in Fig. 10, and a sheet portion 1b', which forms the
15 connected side structure 1b, by cutting portions other than the connecting sheet portions a3 formed in alignment with portions defined by the adjacent folds a1, a1. A fold a5 is formed on one required end of each connecting sheet portion a3 so as to extend at right
20 angles with the folds a1, a1.

Parallel folds a6, a6 are formed along the border between the sheet portion 1a', which forms the connected bottom structure 1a shown in Fig. 10, and a sheet
portion 1c', which forms the connected rear structure
25 1c, such that the folds a6, a6 are positioned on both sides of the connecting sheet portion a4. Further, a recess portion a8 of a width corresponding to the

sectional height of the hollow structures 11, 12 is formed from a portion of either fold a6 so as to extend over a portion corresponding to the length of the connected rear structure 1c.

05 The required surface of the sheet a is coated with glue (i.e., an adhesive) along the folds a1, a2 and a6.

 Subsequently, while the sheet a is being folded in sequence along the folds a1, a2 and a6 to form the
10 first and second hollow structures 11, 12, the edges of the first hollow structures 11 adjacent to each other and those of the second hollow structures 12 adjacent to each other are bonded together, and the sheet a is cut along a desired portion. However, when a sheet
15 previously cut in a predetermined shape is used, a cutting step is not needed.

 According to the above procedure, a connected hollow structure 1' in a developed state is formed, in which the connected side structure 1b is connected to
20 one end of the connected bottom structure 1a through the connecting sheet portions a3, and the connected rear structure 1c is connected to the side of the connected bottom structure 1a through the connecting sheet portion a4, as shown in Fig. 12.

25 The connected hollow structure 1' in the developed state shown in Fig. 12 is used in distribution as it is. However, when it is necessary to package

articles in a connected hollow structure immediately after the fabrication, the connected hollow structure 1 is formed as shown in Fig. 1 by raising the connected side structure 1b and the connected rear structure 1c together with the respective connecting sheet portions a3, a4 in the direction shown by arrows in Fig. 12.

For instance, in a case where there is a possibility that the connected hollow structure 1 in the state shown in Fig. 10 is collapsed when packed, the connected side structure 1b and the connected rear structure 1c may be fixed to the connected bottom structure 1a by bonding or other appropriate means, at need.

In addition to the procedure of fabrication as described above, the connected hollow structure 1 may be fabricated by independently forming the connected bottom structure 1a, the connected side structure 1b and the connected rear structure 1c, then combining these structures with one another as shown in Fig. 10, and consequently connecting or fixing the combined structures together.

The connected hollow structure in the fifth embodiment is comprised of a piece of sheet as described above, and therefore, may be fabricated through fewer steps at lower cost.

Since each of the hollow structures 11, 12 as the components of the connected hollow structure has the

isosceles triangular section having a sectional height larger than a base, the connected bottom, side and rear structures 1a, 1b, 1c show high withstanding strength against a plane pressure.

05 Further, since the connected bottom, side and rear structures 1a, 1b, 1c are comprised of the same sheet a, and the hollow structures 11, 12 included in these structures have the same shape and are of the same size, the connected bottom, side and rear structures 1a,
10 1b, 1c show substantially uniform withstanding strength against a plane pressure.

Other respects of the constitution, functions and effects of the connected hollow structure in the fifth embodiment are substantially similar to those of the
15 connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Sixth embodiment)

Fig. 13 shows a packaging member formed of
a connected hollow structure in an embodiment
20 corresponding to claims 51 and 53 according to the present invention.

A connected hollow structure 1 in a sixth embodiment is formed as a support block for supporting articles when packaged, and is composed of connected
25 structures 1d, 1e, 1f, 1g, 1h of the same structure and of the same size, which are formed in layers such that

hollow structures 11, 12 (of a regular triangular section) of these connected structures extend in parallel to each other and are arranged in a symmetrical shape.

The connected hollow structure 1 in the sixth
05 embodiment is fabricated as follows. Firstly, as shown in Fig. 15, while a sheet a is being delivered in a certain direction, convex folds a2, a2 and concave folds a1, a1 are formed on the sheet a so as to extend in the cross direction of the sheet in an alternate arrangement
10 according to the sectional height and base width of the hollow structures 11, 12, similarly to the case in the first embodiment.

Folds a9 are formed between the convex folds a2, a2 along the border between sheet portions 1d', 1e',
15 which respectively form the structures 1d, 1e of Fig. 13, and the border between sheet portions 1f', 1g', which respectively form the structures 1f, 1g. Further, breaks a10 are formed along these borders other than portions of the folds a9 so as to be alignment with the
20 folds a9.

On the other hand, folds a9 are formed between the concave folds a1, a1 along the border between sheet portions 1e', 1f', which respectively form the structures 1e, 1f, and the border between sheet portions
25 1g', 1h', which respectively form the structures 1g, 1h. Further, breaks a10 are formed along these borders other than portions of the folds a9 so as to be alignment with

the folds a9.

The required surface of the sheet a is coated with glue (i.e., an adhesive) along the folds a1, a2.

Subsequently, while the sheet a is being folded
05 in sequence along the folds a1, a2 to form the hollow structures 11, 12, the edges of the hollow structures 11 adjacent to each other and those of the hollow structures 12 adjacent to each other are respectively bonded together, and the sheet a is cut along a required
10 portion.

According to the above procedure, a connected hollow structure 1' is formed, in which the structures 1d to 1h are in a developed state, as shown in Fig. 16.

The connected hollow structure 1' in the
15 developed state as shown in Fig. 16 is used for distribution as it is. However, when it is necessary to package articles in a connected hollow structure immediately after the fabrication, a layered connected hollow structure 1 of a block shape is formed as shown
20 in Fig. 13 by alternately making a complete face-about of the structures 1d to 1g under the hinge action of portions of the folds a9.

For instance, in a case where there is a possibility that the connected hollow structure in the
25 state as shown in Fig. 13 is collapsed when packed, the structures 1d to 1h may be fixed together by bonding or other appropriate means.

The connected hollow structure 1 in the sixth embodiment is used as the packaging support block and cushioning block as described above, and besides, a packaging frame structure for packaging bottles or like articles by inserting such articles into the hollow portions. Further, since a large number of hollow portions are arranged densely, the connected hollow structure in this embodiment is suitable for use as a carrier for carrying adsorbents.

10 The connected hollow structure 1 in the sixth embodiment is comprised of a piece of sheet as described above, and therefore, may be fabricated through fewer steps at lower cost, and the structures 1d to 1h show substantially uniform elastic force and withstanding strength against a plane pressure.

15 Since each of the hollow structures 11, 12 as the components of the connected hollow structure has the isosceles triangular section having the sectional height larger than the base, the connected hollow structure 1 shows high withstanding strength against a plane pressure.

20 Further, since the hollow structures 11, 12 are formed densely in parallel to each other, the connected hollow structure 1 shows high withstanding strength against an external force in the direction of the hollow structures 11, 12. Thus, the connected hollow structure 1 in this embodiment is also suitable for use as a core

material of a hollow panel (not shown) by designing the hollow structures 11, 12 to uniformly have a small length, and then inserting the connected hollow structure 1 into the hollow panel such that the hollow
05 structures thus designed extend in the thickness direction of the hollow panel.

As a modification of the sixth embodiment, it is possible to fabricate a connected hollow structure of a block shape by individually forming the structures 1d to
10 1h of the respective layers, arranging these structures in layers and then bonding the layered structures together.

In this case, when a connected hollow structure of a block shape is fabricated such that the hollow
15 structures 11, 12 extend at right angles to each other, it is possible to form a layered connected hollow structure which shows high withstanding strength against an external force in every directions.

Other respects of the constitution, functions and
20 effects of the connected hollow structure in the sixth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Seventh embodiment)

25 Fig. 14 shows a packaging member formed of a connected hollow structure in an embodiment

corresponding to claims 52 and 53 according to the present invention.

A connected hollow structure 1 in a seventh embodiment is a modification of the connected hollow structure in the sixth embodiment, and is composed of the structures 1d to 1h which are layered in a block shape by making use of the hinge action of folds a9, and a quadrangular hole all' is formed in the center of the layered connected hollow structure at right angles with the hollow structures 11, 12.

The connected hollow structure 1 in the seventh embodiment is fabricated as follows. Firstly, as shown in Fig. 17, in a step of forming a sheet a constituted substantially similarly to that shown in Fig. 15, recess holes all, which form the hole all' described above, are formed in required portions in the center of sheet portions 1e to 1h other than a sheet portion 1d' which forms the structure 1d shown in Fig. 14, and the sheet a is folded according to a procedure similar to that in case of the sixth embodiment.

The connected hollow structure 1 in the seventh embodiment has the holes all' formed as described above, and therefore, is suitable for use as a packaging frame structure, which also serves as a cushioning material for an article having a portion fit for the shape of the hole all by inserting such a portion of the article into the hole all.

When a recess hole all is formed in the sheet portion 1d' of Fig. 17 similarly to the recess holes all formed in the sheet portions 1e to 1h, portions of the holes all form a through hole extending through a
05 connected hollow structure 1 of a block shape. The connected hollow structure 1 having the through hole as described above is used for packaging an article fit for the shape of the through hole by inserting such an article through the connected hollow structure 1.

10 Other respects of the constitution, functions and effects of the connected hollow structure in the seventh embodiment are substantially similar to those of the connected hollow structure in the sixth embodiment, and hence, the description thereof will be omitted.

15 (Eighth embodiment)

Fig. 18 shows a packaging member formed of a connected hollow structure in an eighth embodiment corresponding to claims 54 and 55 according to the present invention.

20 A connected hollow structure 1 in the eighth embodiment has a generally tray-like shape and is composed of a connected bottom structure 1a, a pair of connected side structures 1b, 1b uprightly placed on both ends of the connected bottom structure 1a, a
25 connected front structure 1i uprightly placed on the front end of the connected bottom structure 1a, and a

connected rear structure 1c uprightly placed on the rear end of the connected bottom structure 1a.

05 The connected bottom structure 1a is connected to the connected front structure 1i and the connected rear structure 1c through respective connecting portions a4, and the connected front structure 1i and the connected rear structure 1c are connected to the connected side structures 1b, 1b through respective connecting portions a3.

10 First and second hollow structures 11, 12 included in the connected bottom, side, front and rear structures 1a, 1b, 1i, 1c have a right-angled triangular section having a slightly larger height, and are of the substantially same size.

15 The connected hollow structure 1 in the eighth embodiment is fabricated as follows. Firstly, as shown in Fig. 19, while a sheet a of a certain width is being delivered in a certain direction, concave folds a1, a1 and convex folds a2, a2 are formed on the sheet a so as
20 to extend in the cross direction of the sheet in an alternate arrangement according to the sectional height and base width of the hollow structures 11, 12.

Recess portions a7 of a width corresponding to the sectional height of the hollow structures 11, 12 are
25 formed along the border between a sheet portion 1c', which forms the connected rear structure 1c in Fig. 18, and a sheet portion 1b', which forms the connected side

structure 1b, and along the border between a sheet portion 1i', which forms the connected front structure 1i and the sheet portion 1b', by cutting portions other than connecting sheet portions a3 formed in alignment
05 with portions between the folds a1, a1. Further, a fold a5 is formed on one required end of each connecting sheet portion a3 so as to extend at right angles with the folds a1, a1.

Parallel folds a6, a6 are formed along the border
10 between a sheet portion 1a', which forms the connected bottom structure 1a of Fig. 18, and the sheet portion 1i' and along the border between the sheet portion 1a' and the sheet portion 1c' such that the folds a6, a6 are positioned along both sides of the connecting sheet
15 portion a4. Further, unnecessary portions a12, a12 corresponding to length portions of the structures 1b, 1b are cut from portions aligned with either fold a6 of the sheet a.

The required surface of the sheet a is coated
20 with glue (i.e., an adhesive) along the folds a1, a2 and a6.

Subsequently, while the sheet a is being folded in sequence along the folds a1, a2 and a6 to form the hollow structures 11, 12, the edges of the hollow
25 structures 11 adjacent to each other and those of the hollow structures 12 adjacent to each other are respectively bonded together, and the sheet a is cut

along a required portion.

The folding of the sheet a starts according to the direction as shown by an arrow C of Fig. 18, for instance.

05 According to the above procedure, a connected hollow structure in a developed state is formed, in which the connected front and rear structures 1i, 1c are connected to the front and rear portions of the connected bottom structure 1a through the connecting
10 sheet portions a4, and the connected side structures 1b are connected to the sides of the connected front and rear structures 1i, 1c through the connecting sheet portions a3. Incidentally, a developed view thereof will be omitted.

15 The connected hollow structure in the developed state is used for distribution as it is. However, when it is necessary to package articles in a connected hollow structure immediately after the fabrication, a connected hollow structure of a tray-like shape is
20 formed as shown in Fig. 18 by placing the connected side structures 1b, 1b and the connected front and rear structures 1i, 1c on the required portions of the connected bottom structure 1a.

 The connected side, front and rear structures 1b, 1i, 1c may be fixed to the connected bottom structure 1a
25 by bonding or other appropriate means, at need.

 The connected hollow structure 1 in the eighth

embodiment is used as a container or box for carrying or transporting fishery products, frozen food or the like by shrink-packing the whole connected hollow structure 1 with a shrink film along the external shape of the
05 connected hollow structure 1, for instance. Further, the whole connected hollow structure may be shrink-packed even in its developed state. Thus, it is possible to enhance heat-insulation, humidity-resistance and water-tightness of the container by shrink-packing
10 the connected hollow structure in this manner.

The connected hollow structure in the eighth embodiment may be also used as a packaging frame structure, which also serves as a cushioning material for packaging articles by partly inserting such articles
15 into the connected hollow structure, without being shrink-packed as described above.

Further, instead of the above procedure of fabrication, the connected hollow structure 1 may be fabricated by individually forming the structures 1a,
20 1b, 1c, 1i, and then connecting or fixing these structures together as shown in Fig. 18.

Other respects of the constitution, functions and effects of the connected hollow structure in the eighth embodiment are substantially similar to those of the
25 connected hollow structure in the fifth embodiment, and hence, the description thereof will be omitted.

(Ninth embodiment)

Fig. 20 shows a packaging member formed of a connected hollow structure in an embodiment corresponding to claims 23 to 25 according to the present invention.

A connected hollow structure 1 in a ninth embodiment has a generally rectangular gutter-like shape and is composed of a connected bottom structure 1a, and a pair of connected side structures 1c, 1c formed on both sides of the connected bottom structure 1a as one body, and a channel-like portion 1j is formed in the center of the connected hollow structure so as to extend in the length direction of hollow structures 11, 12.

First and second hollow structures 11, 12 included in the connected bottom structure 1a have a rectangular equilateral triangular section, and first and second hollow structures 11, 12 included in the connected side structures 1b, 1b have a right-angled triangular section which is larger in height and narrower in base width than the hollow structures 11, 12 of the connected bottom structure 1a. Thus, the upper portion of each connected side structure 1b forms a projection 14b projecting upwards from the upper surface of the connected bottom structure 1a through a certain difference in level.

The connected hollow structure 1 in the ninth embodiment is fabricated as follows. Firstly, as shown

in Fig. 22, while a sheet a of a predetermined width is being delivered, concave folds a1, a1 and convex folds a2, a2 are formed on the sheet a from its leading end so as to extend in the cross direction of the sheet in an alternate arrangement and in parallel with each other according to the sectional height and base width of the hollow structures 11, 12 of the structures 1a, 1b.

A fold a13 is formed along the border between a sheet portion 1a', which forms the connected bottom structure 1a of Fig. 20, and a sheet portion 1b', which forms one connected side structure 1b. Further, convex folds a2, a2 and concave folds a1, a1 are formed in an alternate arrangement on a sheet portion 1b', which forms the other connected side structure 1b, and the sheet portions 1a', 1b'.

The required surface of the sheet a is coated with glue (i.e., an adhesive) along the folds a1, a2.

Subsequently, while the sheet a is being folded along the folds a1, a2 and a13 in sequence to form the hollow structures 11, 12, the edges of the hollow structures 11 adjacent to each other and those of the hollow structures 12 adjacent to each other respectively are bonded together, and the inner surfaces of the structures 1b, 1b and the edges of both-side upper portions of the hollow structure 1a are bonded together. Then, the sheet a is cut along a required portion. Incidentally, the folding of the sheet a starts

according to the direction as shown by an arrow d in Fig. 20.

The connected hollow structure 1 in the ninth embodiment is suitable for use as a packaging frame structure, which also serves as a cushioning material for packaging an article by partially inserting such an article into the channel-shaped portion 1j.

Alternately, it is possible to form a tray-shaped connected hollow structure as shown in Fig. 18 by fixing other connected structures (not shown) to both ends of the connected hollow structure 1.

The connected hollow structure 1 in the ninth embodiment is designed such that the width of the base of each of the hollow structures 11, 12 in the connected side structures 1b, 1b having a large sectional height is reduced in inverse proportion to the sectional height, and the hollow structures 11, 12 in the connected side structures 1b, 1b are formed at a small pitch. Thus, there is not a great difference between withstanding strength against a plane pressure applied to the connected side structures 1b, 1b and withstanding strength against a plane pressure applied to the connected bottom structure 1a.

Other respects of the constitution, functions and effects of the connected hollow structure in the ninth embodiment are substantially similar to those of the connected hollow structure in the eighth embodiment, and

hence, the description thereof will be omitted.

(Tenth embodiment)

Fig. 21(A) shows a modification of the connected hollow structure in the ninth embodiment.

05 A connected hollow structure 1 in a tenth embodiment is substantially similar to the connected hollow structure in the ninth embodiment, except that first hollow structures 11 of a right-angled triangular section in the tenth embodiment are formed at both side
10 portions of a connected bottom structure 1a, and hollow structures 11, 12 of an isosceles triangular section in the tenth embodiment are formed at portions other than both side portions of the connected bottom structure 1a.

 Since the connected bottom structure 1a is formed
15 in this manner, it is not necessary to form the fold a13 on the sheet a between the sheet portion 1a' and either sheet portion 1b' shown in Fig. 22. Thus, any overlap portion 10' of the sheet as shown in Fig. 22 is not
 formed between the connected bottom structure 1a and one
20 connected side structure 1b, and as a result, one-fold connected hollow structure is fabricated from a piece of sheet as a whole.

 Other respects of the constitution, functions and effects of the connected hollow structure in the tenth
25 embodiment are substantially similar to those of the connected hollow structure in the ninth embodiment, and

hence, the description thereof will be omitted.

(Eleventh embodiment)

Fig. 21(B) shows another modification of the connected hollow structure in the ninth embodiment.

05 A connected hollow structure 1 in an eleventh embodiment is composed of a pair of connected side structures 1b, 1b having hollow structures 11, 12 higher than those of a connected bottom structure 1a, and the connected bottom structure 1a formed in the center
10 between the connected side structures in the vertical direction through adjusting sheet portions a14, and channel-shaped portions ij, ij are formed on both upper and lower surfaces of the connected bottom structure 1a.

 Thus, the upper and lower portions of each
15 connected side structure 1b form projections 14b projecting from the upper and lower surfaces of the connected bottom structure through a certain difference in level.

— Other respects of the constitution, functions and
20 effects of the connected hollow structure 1 in the eleventh embodiment are substantially similar to those of the connected hollow structure in the ninth embodiment, and hence, the description thereof will be omitted.

25 (Twelfth embodiment)

Figs. 23 and 24 respectively show a connected hollow structure in an embodiment corresponding to claim 20 according to the present invention.

05 A connected hollow structure 1 in a twelfth embodiment is composed of two gutter-like connected structures 1k, 1k each having a substantially smooth right-angled circumference including a longitudinal center formed into a chamfered side surface 1m, and an inner surface 1n of a polygonal section close to a
10 semi-circular shape. The two gutter-like connected structures 1k, 1k are connected together through a base sheet portion 14' which forms the base surface of one second hollow structure 12 in completion.

The gutter-like connected structures 1k have the
15 same structure and are of the same size, and the first and second hollow structures 11, 12 adjacent to each other as the components of the gutter-like connected structures have a triangular section, and are not similar to each other. The total sum of angles of
20 outward corner portions 13 of the first hollow structures 11 is smaller than that of angles of inward corner portions 13 of the second hollow structures 12. Further, the shape and size of the hollow structures 11, 12 are designed to be fit to form the gutter-like
25 connected structures 1k as shown in the drawings.

The second hollow structure 12 positioned on the free end of each gutter-like connected structure 1k has

a right-angled triangular section such that the inclined side wall 15 of the first hollow structure 11 adjacent to the second hollow structure 12 on the free end forms the inclined side surface of the second hollow structure 12.

The connected hollow structure 1 in the twelfth embodiment is fabricated as follows. Firstly, while a sheet (not shown) of a predetermined width is being delivered, convex folds and concave folds are sequentially formed on the sheet in parallel to each other in a required order at intervals according to the size of the hollow structures 11, 12, and the required surface of the sheet is coated with glue along the folds.

Subsequently, while the sheet is being folded along the folds according to the direction as shown by an arrow e in Fig. 23, the edges of the hollow structures 11 adjacent to each other and those of the hollow structures 12 adjacent to each other are respectively bonded together, and the sheet is cut.

According to the above procedure, the connected hollow structure 1 is formed, in which the hollow structures 11, 12 adjacent to each other have the side walls, which form the border between the hollow structures adjacent to each other, in common, and are comprised of a piece of sheet so as to take the shape resembling a unicursal figure in section, and the sheet

as a material of the connected hollow structure is not overlapped on any surfaces of the hollow structures 11, 12.

The connected hollow structure 1 in a
05 semi-developed state as shown in Fig. 23 is used for displaying bottles or like cylindrical articles by placing such articles on the inner surfaces 1n.

Otherwise, in case of packaging bottles or like articles having a cylindrical portion, a cylindrical
10 connected hollow structure 1 is formed by guiding such articles to be packaged to the inside of either gutter-like connected structure 1k, and then fitting the gutter-like connected structures 1k, 1k face to face with each other such that the inside edges of the first
15 hollow structures 11, 11 adjacent to the center base sheet portion 14' are brought face to face with each other, and the second hollow structures 12, 12 on the free ends of the gutter-like connected structures 1k, 1k are brought face to face with each other so as to form a
20 second hollow structure 12 of a rectangular equilateral triangular section in the confronting portion of the first hollow structures. Then, the connected hollow structure 1 in this state is packed in a rectangular parallelepiped box (not shown).

25 The connected hollow structure 1 in the twelfth embodiment takes the shape of a truss in section on the whole, and therefore, enables to sufficiently

protect packaged articles, since, even when an external force is suddenly applied to a portion of the circumference in the state as shown in Fig. 24, the side walls 15 common to the hollow structures 11, 12 are bent and absorb such an external force.

Further, the connected hollow structure 1 takes the shape of a truss in section on the whole, and therefore, shows high withstanding strength even in case of using a thin sheet as a material of the connected hollow structure.

Furthermore, the connected hollow structure 1 in this embodiment has an appearance of a substantially quadrangular section, and therefore, is suitably used for packaging one or a plurality of bottles or like articles having a cylindrical portion at a time.

According to the connected hollow structure 1 in this embodiment, the gutter-like connected structures 1k, 1k may be separated from each other.

Other respects of the constitution, functions and effects of the connected hollow structure in the twelfth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Thirteenth embodiment)

Fig. 25 partially shows a connected hollow structure in an embodiment corresponding to claim 20

according to the present invention.

A connected hollow structure 1 in a thirteenth embodiment is formed such that first hollow structures 11 of an isosceles triangular section and second hollow structures of an isosceles triangular section, which is equal in height to and wider in base (i.e., partial circumferences 14) than the first hollow structures 11 (i.e., a corner portion 13 of each second hollow structure 12 is larger than that of each first hollow structure 11) are alternately arranged in an alternately inverse position.

Thus, a cylindrical connected hollow structure or a connected hollow structure of a circular-arc section, in which the bottom of the first hollow structures 11 forms the inner surface, is formed by continuously arranging the hollow structures 11, 12.

The sides (edges) of the partial circumferences 14 of the hollow structures 11 adjacent to each other and the sides of the partial circumferences 14 of the hollow structures 12 adjacent to each other are respectively connected together by bonding, and the hollow structures 11, 12 adjacent to each other have the inclined side walls 15 in common.

The connected hollow structure 1 in the thirteenth embodiment in case of having a cylindrical shape is used as a frame structure for packaging and protecting bottles or like articles having a cylindrical

or cylindroid portion.

On the other hand, the connected hollow structure 1 in the thirteenth embodiment in case of having a circular gutter-like shape is used as a frame structure
05 for displaying bottles or like articles having a cylindrical or cylindroid portion by placing such articles on the circular-arc inner portion. In addition, a combination of two connected hollow structures 1 is suitable for use as a frame structure
10 for packaging and protecting such articles.

The connected hollow structure 1 in this embodiment shows high withstanding strength against an external force applied in the circumferential direction, and also functions as cushions, since, when
15 a sudden external force is partially applied in the circumferential direction, the inclined side walls 15 are bent and absorb such an external force.

Other respects of the functions and effects of the connected hollow structure in the thirteenth
20 embodiment are substantially similar to those of the connected hollow structure in the twelfth embodiment, and hence, the description thereof will be omitted.

(Fourteenth embodiment)

Fig. 26 partially shows a connected hollow
25 structure in an embodiment corresponding to claim 20 according to the present invention.

A connected hollow structure 1 in a fourteenth embodiment is composed of first and second hollow structures 11, 12 of a triangular section close to a right-angled triangular shape, and the first and second
05 hollow structures 11, 12 are designed to have the same shape and be of the same size.

The width of the partial circumference (i.e., an angle of a corner portion 13) of each hollow structure 11 is designed to be smaller than that of the partial
10 circumference 14 (i.e., an angle of a corner portion 13) of each hollow structure 12. The partial circumferences 14 of the hollow structures 11 form a slightly-concave circular-arc surface, and the partial circumferences 14 of the hollow structures 12 form a slightly-convex
15 circular-arc surface.

The connected hollow structure 1 in this embodiment in case of having a cylindrical or circular gutter-like shape on the whole has an inner surface of a substantially-cylindrical or circular-arc shape. Thus,
20 when the connected hollow structure 1 in this embodiment is used for packaging bottles or like articles having a cylindrical or cylindroid portion, the inner surface of this connected hollow structure 1 is sufficiently fit for the outer shape of such articles to be packaged.

25 In comparison with the connected hollow structure 1 in the thirteenth embodiment, the connected hollow structure 1 in the fourteenth embodiment shows slightly

lower withstanding strength against an external force in the circumferential direction, while it shows more flexible elasticity.

Other respects of the constitution, functions and effects of the connected hollow structure 1 in the fourteenth embodiment are substantially similar to those of the connected hollow structure in the thirteenth embodiment, and hence, the description thereof will be omitted.

10 (Fifteenth embodiment)

Fig. 27 shows a connected hollow structure in an embodiment corresponding to claim 21 according to the present invention.

A connected hollow structure 1 in a fifteenth embodiment is formed by folding a piece of sheet along concave folds and convex folds formed on the sheet so as to extend in the cross direction of the sheet in parallel to each other. First hollow structures 11 of a right-angled triangular section and different in height, and second hollow structures 12 including hollow structures of a right-angled triangular section and those of a section other than a right-angled triangular section are alternately arranged in an alternately inverse position, and connected together by bonding.

25 The connected hollow structure 1 has a substantially smooth lower surface formed by connecting

the partial circumferences 14 of the first hollow structures 11, while its upper surface formed by connecting the partial circumferences 14 of the second hollow structures 12 has a rising portion 14a gradually
05 rising from one end to the other so as to be fit for the shape of an article (not shown) to be packaged.

The connected hollow structure 1 in this embodiment varies in withstanding strength against a plane pressure applied to each portion, since each first
10 hollow structures 11 has a substantially uniform base width (i.e, the width of the partial circumference 14), and the height of the first hollow structure 11 gradually varies. When the connected hollow pressure 1 is exposed to a plane pressure of not less than a
15 predetermined value, the vertical side walls 15 common to the first and second hollow structures 11, 12 adjacent to each other are bent and absorb such a pressure.

The connected hollow structure 1 in this
20 embodiment is suitable for use as a support table for an article having a bottom fit for the shape of the upper surface of the connected hollow structure 1, or a frame structure for packaging such an article.

Other respects of the constitution, functions and
25 effects of the connected hollow structure in the fifteenth embodiment are substantially similar to those of the connected hollow structure in the first

embodiment, and hence, the description thereof will be omitted.

(Sixteenth embodiment)

Fig. 28 shows a connected hollow structure in an
05 embodiment corresponding to claim 22 according to the present invention.

A connected hollow structure 1 in a sixteenth embodiment is formed, substantially similarly to the connected hollow structure 1 in the fifteenth
10 embodiment, such that its upper surface formed by connecting the partial circumferences 14 of second hollow structures 12 has a rising portion 14a gradually rising from one end to the other so as to be substantially fit for the shape of the bottom of an
15 article to be packaged.

On the other hand, the connected hollow structure 1 in the sixteenth embodiment is different from the connected hollow structure in the fifteenth embodiment in that a pitch of the hollow structures 11, 12 formed
20 in the rising portion 14a (i.e., the width of the partial circumferences 14 forming the bottom of the hollow structures 11) is made smaller in proportion to the scale of rising.

According to the connected hollow structure 1 in
25 this embodiment, since the pitch of the hollow structures 11, 12 is made smaller in proportion to the

scale of rising on the upper surface as described above, withstanding strength against a plane pressure is easily made uniform in each portion of the connected hollow structure 1.

05 Other respects of the constitution, functions and effects of the connected hollow structure 1 in the sixteenth embodiment are substantially similar to those of the connected hollow structure in the fifteenth embodiment, and hence, the description thereof will be
10 omitted.

(Seventeenth embodiment)

Fig. 29 shows a connected hollow structure in an embodiment corresponding to claim 22 according to the present invention.

15 A connected hollow structure 1 in a seventeenth embodiment is composed of a connected bottom structure 1a, a connected side structure 1b uprightly placed on one side of the connected bottom structure 1a, and a
20 connected rear structure 1c uprightly placed on the rear of the connected bottom structure 1a.

 The connected bottom structure 1a and the connected rear structure 1c are formed as one body, and the upper surface of the connected rear structure 1c has a projection 14b projecting from the upper surface of
25 the end of the connected bottom structure 1a through a difference in level.

The connected side structure 1b is formed separately from the connected bottom structure 1a, and then bonded to one side of the connected bottom structure 1a.

05 The connected bottom, side and rear structures 1a, 1b, 1c are formed by alternately arranging their first and second hollow structures 11, 12 of a triangular section in an alternately inverse position, and then connecting these hollow structures together.

10 The upper surface of the connected bottom structure 1a is formed by connecting the partial circumferences 14, which form the upper surface of the second hollow structures 12, together, and has front and center rising portions 14a gradually rising from
15 portions other than the front and center portions. A pitch of the hollow structures 11, 12 formed in these rising portions 14a is made small.

 The connected bottom structure 1a has a smooth bottom and a narrow center portion.

20 The connected side structure 1b has a center rising portion on its upper surface portion other than the left and right ends in the drawing so as to extend substantially in parallel to the rising portion 14a.

 The hollow structures 11, 12 included in the
25 connected rear structure 1c are higher than those included in the connected bottom structure 1a adjacent to the connected side structure 1c.

The connected hollow structure 1 in this embodiment has a special inner shape defined by the connected bottom structure 1a, the connected side structure 1b and the connected rear structure 1c, and
05 therefore, is suitable for use as a corner protection frame for protecting an article (not shown) partially having a corner portion fit for the inner surface shape of the connected hollow structure by bringing such a corner portion of the article into contact with the
10 inner surface of the connected hollow structure.

Since the pitch of the hollow structures 11, 12 formed in the rising portion 14a of the connected bottom structure 1a is made smaller in proportion to the scale of rising, there is no great difference in
15 withstanding strength against a plane pressure applied to each portion of the connected bottom structure 1a.

Other respects of the constitution, functions and effects of the connected hollow structure 1 in the ~~seventeenth~~ embodiment are substantially similar to
20 those of the connected hollow structure in the fifth embodiment, and hence, the description thereof will be omitted.

(Eighteenth embodiment)

Fig. 30 shows a connected hollow structure in an
25 embodiment corresponding to claim 5 according to the present invention.

A connected hollow structure 1 in an eighteenth embodiment is formed such that first hollow structures 11 of a triangular section including a corner portion 13 directed upwards and a partial circumference 14 forming a base and facing the lower surface, and second hollow structures 12 of a triangular section including a corner portion 13 directed downwards and a partial circumference facing the upper surface are alternately arranged, and is comprised of a piece of sheet as a whole so as to take the shape resembling a unicursal figure in section.

The first hollow structures 11 have an isosceles triangular section and are of the same size, while the second hollow structures 11 include hollow structures of an isosceles triangular section and those of a right-angled triangular section in the ratio of 1:2. The second hollow structures 12 are formed in an alternate arrangement such that the second hollow structures 12, 12 of the right-angled triangular section are placed in a reverse position next to the second hollow structure of the isosceles triangular section.

The partial circumferences 14 on the upper side of the second hollow structures 12 of the right-angled triangular section adjacent to each other are inclined in the reverse direction substantially in the shape of a letter V, and the partial circumferences 14 of the second hollow structures 12 of the right-angled

triangular section partially project so as to overhang the adjacent second hollow structure 12 of the isosceles triangular section.

The first hollow structures 11, 11 adjacent to
05 each other are connected together by bonding in a portion of the corner portion 13 of each second hollow structure 12 positioned between the first hollow structures adjacent to each other, and the second hollow structures 12, 12 adjacent to each other are connected
10 together by bonding in a portion of the corner portion 13 of each first hollow structure 11 positioned between the second hollow structures adjacent to each other.

The partial circumferences 14 of the first hollow structures 11 are connected together to form
15 a smooth lower surface of the connected hollow structure, while the partial circumference 14 of the second hollow structure of the right-angled triangular section and that of the adjacent second hollow structure of the isosceles triangular section are not connected
20 together.

The first hollow structure 11 and the adjacent second hollow structure 12 of the isosceles triangular section, and the first hollow structure 11 and the adjacent second hollow structures 12, 12 of the
25 right-angled triangular section on both sides of the first hollow structure respectively have all the side walls 15 in common. On the other hand, the second

hollow structure 12 of the right-angled triangular section and the adjacent first hollow structure 11 on one side of the second hollow structure merely partially have the side walls 15 between both the hollow
05 structures in common as viewed from the side of the second hollow structures 12.

The connected hollow structure 1 in this embodiment is formed as described above, and therefore, shows relatively low withstanding strength against a
10 plane pressure, while it shows flexible elasticity on the whole, since, when the connected hollow structure 1 is exposed to a plane pressure of not less than a certain extent, the second hollow structures 12 of the right-angled triangular section overhanging the second
15 hollow structures 12 of the isosceles triangular section are partly bent.

Then, the second hollow structures 12 of the right-angled triangular section overhanging the second hollow structures 12 of the isosceles triangular section
20 become partly unable to withstand a load, and as a result, are collapsed, and the collapsed portion is overlapped on the horizontal part 14 of the second hollow structures 12 of the isosceles triangular section. At this time, since the second hollow
25 structures 12 of the right-angled triangular section are transformed into an isosceles triangular section of a size similar to that of the other second hollow

structures 12, the connected hollow structure 1 after transformation shows high withstanding strength against a plane pressure, similarly to the connected hollow structure in the first embodiment, for instance.

05 Namely, at an initial stage of the application of a plane pressure to the connected hollow structure 1, the second hollow structures 12 of the right-angled triangular section are transformed and absorb such a plane pressure. At a stage of the application of a far
10 higher plane pressure, the side walls 15 of the hollow structures 11, 12 adjacent to each other are bent and absorb such a plane pressure. In this manner, the connected hollow structure 1 in this embodiment functions as cushions in two stages.

15 Thus, the connected hollow structure 1 in this embodiment is suitable for use as a packaging member which needs the cushioning properties in two stages.

 Other respects of the constitution, functions and effects of the connected hollow structure 1 in the
20 eighteenth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Nineteenth embodiment)

25 Fig. 31 shows a connected hollow structure in an embodiment corresponding to claim 5 according to the

present invention.

A connected hollow structure 1 in a nineteenth embodiment is formed such that first and second hollow structures 11, 12 of an isosceles triangular section and
05 of the same size are densely and alternately arranged in an alternately inverse position, namely, such that the first, second and first hollow structures 11, 12, 11 are arranged in this order in an alternately inverse position, and another second hollow structure, which is
10 equal in a sectional shape to and is larger in sectional size than the first hollow structures, is arranged next to a group of these small-sized hollow structures in an inverse position.

The first hollow structures 11 adjacent to each
15 other are connected together by bonding at a portion of the corner portion 13 of each second hollow structure 12 positioned between the first hollow structures 11 adjacent to each other, and the second hollow structures 12 adjacent to each other are connected together by
20 bonding in a portion of the corner portion 13 of each first hollow structure 11 positioned between the second hollow structures 12 adjacent to each other.

The partial circumferences 14 of the first hollow structures 11 are connected together to form a smooth
25 plane, while the partial circumferences 14 of the second hollow structures 12 are not connected together.

The second hollow structure 12 positioned at both

ends of the connected hollow structure 1 has the sectional shape of a right-angled triangle equivalent to the half of the sectional shape of the large-sized hollow structure 12.

05 The first hollow structures 11 and the small-sized second hollow structures 12 have all the side walls between the first and second hollow structures adjacent to each other in common, while the first hollow structures 11 and the large-sized second hollow
10 structures 12 partly have the side walls between the first and second hollow structures adjacent to each other in common.

 The connected hollow structure 1 in the nineteenth embodiment is fabricated as follows.

15 Firstly, predetermined convex folds and concave folds are formed on a sheet (not shown) of a predetermined width so as to extend in the cross direction of the sheet, and the folding of the sheet starts from the leading end of the sheet according to the direction as
20 shown by an arrow g in Fig. 31 to form the hollow structures.

 Namely, the hollow structures 12 and 11 are formed in an alternately inverse position by folding the sheet according to the direction as shown by the arrow g
25 in Fig. 31.

 At this time, the first hollow structures 11 are bonded together in a portion of the corner portion of

each second hollow structure 12 positioned between the first hollow structures adjacent to each other, and the large-sized second hollow structures 12 and the small-sized second hollow structures 12 are bonded together
05 such that one side of the partial circumference 14 of each small-sized hollow structure is bonded to a portion of the side wall 15 of each large-sized second hollow structure.

The connected hollow structure 1 formed as
10 described above takes the shape resembling a unicursal figure in section, and has no sheet overlap portion other than the bonded portions, and therefore, its apparent specific gravity is extremely small.

Although the connected hollow structure 1 in this
15 embodiment has a panel-like shape to be substantially uniform in apparent thickness T , it shows more flexible elasticity against a plane pressure than that of the connected hollow structure in the first embodiment, since the partial circumferences 14 of the large-sized
20 second hollow structures 12 project upwards from the partial circumferences 14 of the small-sized second hollow structures 12.

Other respects of the functions and effects of the connected hollow structure 1 in the nineteenth
25 embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Twentieth embodiment)

Fig. 32 shows a connected hollow structure in an embodiment corresponding to claim 5 according to the present invention.

05 A connected hollow structure 1 in a twentieth embodiment is formed such that first hollow structures 11 of an isosceles triangular section, second hollow structures 12 of an isosceles triangular section including a base surface in common with the inclined
10 surfaces of the first hollow structures 11, large-sized first hollow structures 11 of an isosceles triangular section substantially equal in sectional height to and larger in base width than the first hollow structures, and other second hollow structures 12 equal in sectional
15 shape and size to the afore-mentioned second hollow structures 12 and reversed to each other are alternately arranged in this order in an alternately inverse position.

 The first hollow structure 11 positioned at both
20 ends of the connected hollow structure 1 has a right-angled triangular section.

 Both sides of the partial circumference 14 of each first hollow structure 11 having a narrow base (i.e., partial circumference 14) are bonded to portions
25 of the inclined sides of the first hollow structures 11 having a wide base, and the partial circumferences of the first hollow structures having the wide base project

downward from the bottom of the first hollow structures having the narrow base.

The connected hollow structure 1 has a corrugated upper surface, although the upper surface of the
05 connected hollow structure 1 is formed by connecting the partial circumferences 14 of the second hollow structures 12 together.

The connected hollow structure 1 in the twentieth embodiment is fabricated as follows. Firstly,
10 predetermined convex folds and concave folds are formed on a sheet (not shown) of a predetermined width so as to extend in the cross direction of the sheet, and the folding of the sheet starts from the leading end of the sheet according to the direction as shown by an arrow h
15 in Fig. 32 to form the hollow structures.

Namely, the connected hollow structure 1 is fabricated by sequentially bonding the edges of the first hollow structures 11 and those of the second hollow structures 12, together while folding the sheet
20 so as to form the first and second hollow structures 11, 12 in an alternate arrangement according to the direction as shown by the arrow h in Fig. 32.

The connected hollow structure 1 formed as described above takes the shape resembling a unicursal
25 figure in section. In addition, the surfaces of the hollow structures 11, 12 have no sheet overlap portion other than the bonded portions, and the whole apparent

specific gravity of the connected hollow structure 1 is extremely small.

In comparison with the connected hollow structure in the first embodiment, the connected hollow structure 05 1 in the twentieth embodiment shows lower withstanding strength against a plane pressure, while it shows more flexible elasticity.

Other respects of the constitution, functions and effects of the connected hollow structure 1 in the 10 twentieth embodiment are substantially similar to those of the connected hollow structure in the nineteenth embodiment, and hence, the description thereof will be omitted.

(Twenty-first embodiment)

15 Fig. 33 partially shows a connected hollow structure in another embodiment corresponding to claims 10 and 19 according to the present invention.

A connected hollow structure 1 in a twenty-first embodiment is formed such that first hollow structures 20 of a right-angled triangular section and of the same size, and second hollow structures 12 of a quadrangular section and of the same size are arranged alternately and densely. Each second hollow structure 12 has a sectional shape including two right-angled portions and 25 an inclined side wall, and its section takes the special shape.

Each first hollow structure 11 is formed such that an acute-angled corner portion 13 is directed toward the upper surface, and a partial circumference 14 forming a base faces the lower surface. Each second
05 hollow structure 12 is formed such that an acute-angled corner portion 13 is directed toward the lower surface, and a partial circumference 14 between the right-angled corner portions on both sides faces the upper surface.

The partial circumferences 14 of the first hollow
10 structures 11 adjacent to each other are bonded together in a portion of the corner portion 13 of each second hollow structure 12 positioned between the adjacent first hollow structures adjacent to each other, and the partial circumferences 14 of the second hollow
15 structures 12 adjacent to each other are bonded together.

The vertical side walls of the second hollow structures 12 adjacent to each other are overlapped with each other in upper end portions of the second hollow
20 structures so as to extend from the corner portions 13 of the first hollow structures 11 toward the upper ends of the second hollow structures. The sheet as a material of the connected hollow structure is bonded in an overlap state in the upper end portions of the second
25 hollow structures.

The connected hollow structure 1 in the twenty-first embodiment is fabricated as follows. Firstly,

while a sheet (not shown) is being delivered, convex folds and concave folds are formed on the sheet so as to extend in the cross direction of the sheet according to the sectional shape of the hollow structures 11, 12, and
05 the required surface of the sheet 1 is sequentially coated with glue along the folds.

Subsequently, while the sheet is being folded along the folds, the required portions of the sheet are bonded together to sequentially form the first and
10 second hollow structures 11, 12 in an alternate arrangement. After the connected hollow structure 1 of the size meeting the design has been fabricated, the sheet is cut. Incidentally, the sheet may be cut in advance depending on the design.

15 The connected hollow structure 1 formed as described above is comprised of a piece of sheet and takes the shape resembling a unicursal figure in section.

In comparison with the connected hollow structure
20 1 in the first embodiment, the apparent specific gravity of the connected hollow structure 1 in the twenty-first embodiment becomes slightly smaller, whereas the hollow structures 11, 12 of the connected hollow structure in this embodiment are connected together more firmly,
25 since the connected hollow structure in this embodiment has sheet overlap portions, scanty as they are.

When the connected hollow structure 1 is exposed

to a plane pressure of not less than a predetermined value, the vertical side walls 15 and inclined side walls 15 common to the hollow structures 11, 12 are bent, and therefore, show elasticity in some degree to
05 make it possible to absorb such a pressure.

Other respects of the constitution, purposes, functions and effects of the connected hollow structure 1 in the twenty-first embodiment are substantially similar to those of the connected hollow structure in
10 the first embodiment, and hence, the description thereof will be omitted.

(Twenty-second embodiment)

Fig. 34 partly shows a connected hollow structure in an embodiment corresponding to claims 16 and 19
15 according to the present invention.

A connected hollow structure 1 in a twenty-second embodiment is formed such that first hollow structures 11 of a right-angled triangular section, second hollow structures 12 of a quadrangular (special) section,
20 other first hollow structures 11 of a quadrangular section, and other second hollow structures 12 of a right-angled triangular section are alternately arranged in this order.

Each first hollow structure 11 is formed such
25 that an acute-angled corner portion 13 is directed toward the upper surface, and a horizontal partial

circumference 14 faces the lower surface. Each second hollow structure 12 is formed such that an acute-angled corner portion 13 is directed toward the lower surface, and a horizontal partial circumference 14 faces the
05 upper surface.

The sides of the partial circumferences 14 of the first hollow structures 11 adjacent to each other are connected together by bonding, and the sides of the partial circumferences 14 of the second hollow
10 structures 12 adjacent to each other are connected together by bonding. The connected hollow structure 1 has a panel-like shape to have the upper and lower smooth surfaces and to be substantially uniform in apparent thickness T, and takes the shape resembling a
15 unicursal figure in section.

A lower portion of each first hollow structure 11 of the quadrangular section is bonded to a lower portion of each adjacent first hollow structure 11 of the right-angled triangular section in a partially-overlapped
20 state, and an upper portion of each second hollow structure 12 of the quadrangular section is bonded to an upper portion of each adjacent first hollow structure 11 of the right-angled triangular section in a partially-overlapped state.

25 The fabricating method, and other respects of the constitution, functions and effects of the connected hollow structure in the twenty-second embodiment are

substantially similar to those of the connected hollow structure in the twenty-first embodiment, and hence, the description thereof will be omitted.

(Twenty-third embodiment)

05 Fig. 35 shows a connected hollow structure in an embodiment corresponding to claims 7 and 19 according to the present invention.

 A connected hollow structure 1 in a twenty-third embodiment is formed such that first hollow structures
10 11 of a quadrangular (special) section and of the same size and second hollow structures equal in shape and size to the first hollow structures 11 are arranged alternately.

 Each first hollow structure 11 is formed such
15 that an acute-angled corner portion 13 is directed toward the upper surface, and a horizontal partial circumference 14 faces the lower surface. Each second hollow structure 12 is formed such that an acute-angled corner portion 13 is directed toward the lower surface
20 and a horizontal partial circumference 14 faces the upper surface.

 The sides of the partial circumferences 14 of the first hollow structures 11 adjacent to each other are connected together by bonding, and the sides of the
25 partial circumferences 14 of the second hollow structures 12 adjacent to each other are connected

together by bonding. Then, the connected hollow structure 1 has a panel-like shape to have the upper and lower smooth surfaces and to be substantially uniform in apparent thickness T, and takes the shape resembling a unicursal figure in section.

The first hollow structures 11 adjacent to each other and the second hollow structures 12 adjacent to each other are respectively bonded together in a partially-overlapped state in portions of the vertical side walls 15.

The fabricating method and other respects of the constitution, functions and effects of the connected hollow structure in the twenty-third embodiment are substantially similar to those of the connected hollow structure in the twenty-first embodiment, and hence, the description thereof will be omitted.

(Twenty-fourth embodiment)

Fig. 36 partially shows a connected hollow structure in another embodiment corresponding to claims 10 and 19 according to the present invention.

A connected hollow structure 1 in a twenty-fourth embodiment is composed of a large number of laterally-arranged first hollow structures 11 of a pentagonal section and of the same size, and a large number of second hollow structures 12 of an isosceles triangular section and of the same size.

Each first hollow structure 11 is formed such that an upper corner portion 13 is directed toward the upper surface, and a partial circumference 14 forming the lower surface faces the lower surface, and each
05 second hollow structure 12 is formed such that a corner portion 13 is directed toward the lower surface and a partial circumference 14 faces the upper surface.

The sides of the partial circumferences 14 forming the bottom of the first hollow structures 11, 11
10 adjacent to each other are connected together by bonding, and the sides of the partial circumferences 14 of the second hollow structures 12, 12 adjacent to each other are connected together by bonding. Since the partial circumferences 14 of the first hollow structures
15 11 and those of the second hollow structures 12 respectively form horizontal planes, the upper and lower surfaces of the connected hollow structure 1 are formed horizontally, and the connected hollow structure 1 has a panel-like shape to be uniform in apparent thickness.

20 The first and second hollow structures 11, 12 adjacent to each other have the inclined side walls 15, which form each corner portion 13, in common.

The connected hollow structure 1 in the twenty-fourth embodiment is fabricated as follows. Firstly,
25 while a sheet (not shown) of a predetermined width is being delivered, convex folds and concave folds are sequentially formed on the sheet at intervals according

to the size of the hollow structures 11, 12 in a required order, and the required surface of the sheet is coated with glue along the folds.

Subsequently, while the sheet is being folded
05 along the folds so as to start the folding of the sheet according to the direction as shown by an arrow j in Fig. 36, the required edges of the hollow structures are bonded together, and the sheet is cut.

According to the above procedure, it is possible
10 to form the connected hollow structure 1, in which the hollow structures 11, 12 have the side walls 15 forming the border between the hollow structures adjacent to each other in common, and are comprised of a piece of sheet so as to take the shape resembling a unicursal
15 figure in section, and the sheet as a material of the connected hollow structure is overlapped in the vertical sides of the hollow structures 11.

In comparison with the connected hollow structure in the first embodiment, the connected hollow structure
20 1 in the twenty-fourth embodiment shows lower withstanding strength against a plane pressure, while it shows more flexible elasticity, since, when the connected hollow structure 1 is exposed to a plane pressure of not less than a predetermined value, the
25 common side walls 15 forming the corner portions 13 of the hollow structures 11, 12 are bent.

Thus, the connected hollow structure in the

twenty-fourth embodiment is suitable for use as a cushioning material for packaging, and besides, suitably used for keeping or packaging linear fluorescent lamps or like articles by inserting such articles into the
05 hollow portions of the hollow structures 11.

Other respects of the functions and effects of the connected hollow structure in the twenty-fourth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and
10 hence, the description thereof will be omitted.

(Twenty-fifth embodiment)

Fig. 37 shows a connected hollow structure in an embodiment corresponding to claims 14, 19 and 23 according to the present invention.

15 A connected hollow structure 1 in a twenty-fifth embodiment is formed such that first hollow structures 11 each having a corner portion 13 directed toward the upper surface and a partial circumference 14 facing the lower surface, and second hollow structures 12 each
20 having a corner portion 13 directed toward the lower surface and a partial circumference 14 facing the upper surface are alternately arranged.

The sides of the partial circumferences 14 of the first hollow structures 11, 11 adjacent to each other
25 are substantially horizontally connected together by bonding, and the sides of the partial circumferences 14

of the second hollow structures 12, 12 adjacent to each other are substantially horizontally connected together by bonding. Thus, the connected hollow structure 1 has a panel-like shape to be substantially uniform in
05 apparent thickness T, and takes the shape resembling a unicursal figure in section.

While the first hollow structure 11 on both ends of the connected hollow structure 1 has a right-angled triangular section of a small size, other first hollow
10 structures 11 have an isosceles triangular section of the same size.

The second hollow structures 12 uniformly include hollow structures of a pentagonal section of a slightly special shape, and those of an isosceles triangular
15 section. The side walls 15 of the second hollow structures 12 of the pentagonal section and those of the second hollow structures 12 of the isosceles triangular section are partially overlapped with each other.

Since the corner portions 13 of the hollow
20 structures 11, 12 are formed at the same angle, the connected hollow structure 1 in this embodiment is substantially equal in withstanding strength against a plane pressure to the connected hollow structure in the first embodiment. Thus, when the connected hollow
25 structure 1 is exposed to a plane pressure of not less than a predetermined value, the common side walls 15 of the hollow structures 11, 12 are bent, and as a result,

show elasticity to absorb such a pressure.

The connected hollow structure 1 has both ends respectively formed into a chamfered inclined side surface 15a so as to round off the corner at both ends.

05 Other respects of the functions and effects of the connected hollow structure in the twenty-fifth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

10 (Twenty-sixth embodiment)

Fig. 38 partially shows a connected hollow structure in an embodiment corresponding to claims 13 and 19 according to the present invention.

15 A connected hollow structure 1 in a twenty-sixth embodiment is composed of first hollow structures 11 and second hollow structures 12. The first hollow structures 11 include hollow structures of a pentagonal (special) section and of the same size, and those of a quadrangular (special) section and of the same size in
20 the ratio of 1:2. Further, the second hollow structures 12 include hollow structures of a right-angled triangular section and of the same size and those of an isosceles triangular section and of the same size in the ratio of 2:1.

25 A large number of first and second hollow structures 11, 12 as described above are formed in an

alternate arrangement according to a certain repetitive pattern as shown in Fig. 38.

The sides of the partial circumferences 14 of the first hollow structures 11, 11 adjacent to each other
05 are connected together by bonding so as to form a substantially horizontal plane, and the sides of the partial circumferences 14 of the second hollow structures 12, 12 adjacent to each other are connected together by bonding so as to form a substantially
10 horizontal plane. Thus, the connected hollow structure 1 has a panel-like shape to be substantially uniform in apparent thickness, and takes the shape resembling a unicursal figure in section.

There is no great difference in withstanding
15 strength against a plane pressure applied to each portion of the connected hollow structure 1 in this embodiment, since the first and second hollow structures 11, 12 of the sectional shape as described above are formed in an alternately well-balanced arrangement
-20 according to a certain repetitive pattern. The connected hollow structure 1 withstands a plane pressure mainly by the side walls 15 common to the adjacent first and second hollow structures 11, 12 adjacent to each other.

The fabricating method, and other respects of the
25 constitution, functions and effects of the connected hollow structure 1 in the twenty-sixth embodiment are substantially similar to those of the connected hollow

structure in the first embodiment, and hence, the description thereof will be omitted.

(Twenty-seventh embodiment)

Fig. 39 partially shows a connected hollow
05 structure in another embodiment corresponding to claims 16 and 19 according to the present invention.

A connected hollow structure 1 in a twenty-seventh mode is composed of first hollow structures 11 and second hollow structures 12 respectively including
10 hollow structures of a right-angled triangular section and of the same size and those of a pentagonal (special) section and of the same size in the ratio of 2:1. Each of the hollow structures 11, 12 of the pentagonal section corresponds to two hollow structures 12 or 11 of
15 the right-angled triangular section.

A large number of first and second hollow structures 11, 12 as described above are formed in an alternate arrangement according to a certain repetitive pattern as shown in Fig. 39.

20 The sides of the partial circumferences 14 of the first hollow structures 11, 11 adjacent to each other are connected together by bonding so as to form a substantially horizontal plane, and the sides of the partial circumferences 14 of the second hollow
25 structures 12, 12 adjacent to each other are connected together by bonding so as to form a substantially horizontal plane. Thus, the connected hollow structure

1 has a panel-like shape to be substantially uniform in apparent thickness, and takes the shape resembling a unicursal figure in section.

Other respects of the constitution, functions and
05 effects of the connected hollow structure 1 in the twenty-seventh embodiment are substantially similar to those of the connected hollow structure in the twenty-sixth embodiment, and hence, the description thereof will be omitted.

10 (Twenty-eighth embodiment)

Fig. 40 partially shows a connected hollow structure in an embodiment corresponding to claims 17 and 19 according to the present invention.

A connected hollow structure 1 in a twenty-eighth
15 embodiment is composed of first and second hollow structures 11, 12 respectively including hollow structures of a quadrangular section and of the same size, and those of a pentagonal section and of the same size in the ratio of 2:1. Each of the hollow structures
20 11, 12 of the pentagonal section corresponds to two hollow structures 12 or 11 of the quadrangular section.

A large number of first and second hollow structures 11, 12 as described above are formed in an alternate arrangement according to a certain repetitive
25 pattern.

The sides of the partial circumferences 14 of the

first hollow structures 11, 11 adjacent to each other are connected together by bonding so as to form a substantially horizontal plane, and the sides of the partial circumferences 14 of the second hollow
05 structures 12, 12 adjacent to each other are connected together by bonding so as to form a substantially horizontal plane. Thus, the connected hollow structure 1 has a panel-like shape to be substantially uniform in apparent thickness, and takes the shape resembling a
10 unicursal figure in section.

Other respects of the constitution, functions, and effects of the connected hollow structure 1 in the twenty-eighth embodiment are substantially similar to those of the connected hollow structure in the twenty-
15 sixth embodiment, and hence, the description thereof will be omitted.

(Twenty-ninth embodiment)

Fig. 41 partially shows a connected hollow structure in an embodiment corresponding to claims 7 and
20 19 according to the present invention.

A connected hollow structure 1 in a twenty-ninth embodiment is composed of first and second hollow structures 11, 12 which respectively have a pentagonal section close to an isosceles triangular shape and are
25 of the same size. The first and second hollow structures 11, 12 are formed in a dense and alternate

arrangement and in an alternately inverse position.

The partial circumferences 14 of the first hollow structures 11, 11 adjacent to each other are connected together by bonding so as to form a substantially
05 horizontal plane, and the partial circumferences 14 of the second hollow structures 12, 12 adjacent to each other are connected together by bonding so as to form a substantially horizontal plane. Thus, the connected hollow structure 1 has a panel-like shape to be
10 substantially uniform in apparent thickness, and takes the shape resembling a unicursal figure in section.

The connected hollow structure 1 in this embodiment shows high withstanding strength against a plane pressure, even though its apparent specific
15 gravity is small, since each of the hollow structures 11, 12 has a pentagonal section close to an isosceles triangular shape. Further, more uniform withstanding strength is shown in each part, since the hollow structures 11, 12 are of the same size.

20 — Other respects of the constitution, functions and effects of the connected hollow structure 1 in the twenty-ninth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be
25 omitted.

(Thirtieth embodiment)

Fig. 42(C) partially shows a connected hollow structure in an embodiment corresponding to claim 23 according to the present invention.

A connected hollow structure 1 in a thirtieth
05 embodiment is formed such that a right-angled corner portion of each second hollow structure 12 of the right-angled triangular section at both ends of the connected hollow structure 1 in the first embodiment is modified into a chamfered inclined side surface 15a.

10 It is possible to form a connected hollow structure having a rounded-off end, and to prevent the corner of each hollow structure 12 at both ends of the connected hollow structure 1 from being transformed or collapsed by forming the chamfered inclined side surface
15 15a at the ends described above.

A means for forming the chamfered inclined side surface 15a at both ends of the connected hollow structure 1 in this manner may be applied to a
connected hollow structure in other embodiments having a
20 panel-like shape on the whole to be substantially uniform in apparent thickness, or a connected hollow structure having a gradually-rising portion formed on one surface, like the connected hollow structure in the fifteenth embodiment (See Fig. 27) or sixteenth
25 embodiment (See Fig. 28).

(Thirty-first embodiment)

Fig. 42(D) shows a connected hollow structure in an embodiment corresponding to claim 27 according to the present invention.

A connected hollow structure 1 in a thirty-first
05 embodiment is formed such that the hollow structure 12
at both ends of each projection 14b of the connected
side structures 1b, 1b of the connected hollow structure
1 in the ninth, tenth or eleventh embodiment (See Figs.
20 and 21) is modified to have a chamfered inclined side
10 surface 15a extending in the length direction of the
hollow structure 12.

It is possible to form a connected hollow
structure having a rounded-off end, and to prevent the
corner of each hollow structure 12 at both ends of each
15 projection 14b of the connected hollow structure 1 from
being transformed or collapsed by forming the chamfered
inclined side surfaces 15a on each hollow structure
positioned at the ends described above.

Further, when articles 2 to be packaged are
20 inserted into a channel-like portion 1j of the connected
hollow structure 1, the inner inclined side surfaces 15a
of both the projections 14b function as a guide for the
articles 2 when inserted, and enable the smooth
insertion of the articles.

25 (Thirty-second embodiment)

Fig. 43 shows a connected hollow structure in an

embodiment corresponding to claim 21 according to the present invention.

A connected hollow structure 1 in a thirty-second embodiment is formed such that first and second hollow
05 structures 11, 12 included in a connected hollow structure having a gradually-rising portion 14a formed on one surface, like the connected hollow structure in the fifteenth embodiment (See Fig. 27) have a pentagonal section, similarly to the connected hollow structure
10 shown in Fig. 41.

(Thirty-third embodiment)

Fig. 44 shows a connected hollow structure in an embodiment corresponding to claims 21 and 23 according to the present invention.

15 A connected hollow structure 1 in a thirty-third embodiment is formed such that a connected hollow structure having a gradually-rising portion 14a formed on one surface, like the connected hollow structure in the thirty-second mode, is composed of first hollow
20 structures of a pentagonal section, and second hollow structures of a triangular section.

Further, the upper corner portions of the first hollow structures 11 at both ends of the connected hollow structure 1 in this embodiment are modified into
25 chamfered inclined side surfaces 15a, 15a.

When the connected hollow structure 1 having the

rising portion 14a formed on one surface like this embodiment is formed, the first and second hollow structures 11, 12 included in the connected hollow structure 1 may take various shapes as shown in Figs. 33
05 to 35 or 37, instead of the shapes described in the fifteenth, thirty-second and thirty-third embodiments.

(Thirty-fourth embodiment)

Fig. 45 shows a connected hollow structure in an embodiment corresponding to claim 10 or 29 according to
10 the present invention.

A connected hollow structure 1 in a thirty-fourth embodiment is formed such that laterally-arranged first hollow structures of a quadrangular (or parallelogram) section and of the same size, and second hollow
15 structures 12 of a triangular section and of the same size on the upper side of the first hollow structures are connected together in an alternate arrangement.

Each first hollow structure 11 is formed such that a corner portion 13 is directed toward the upper
20 surface, and a partial circumference 14 composed of two side surfaces faces the lower surface. Each second hollow structure 12 is formed such that a corner portion 13 is directed toward the lower surface, and a partial circumference 14 composed of one side surface faces the
25 upper surface.

The partial circumferences 14 of the first hollow

structures 11 adjacent to each other are connected together in a substantially-horizontal state by bonding, and the partial circumferences 14 of the second hollow structures 12 adjacent to each other are similarly
05 connected together by bonding. The first and second hollow structures 11, 12 adjacent to each other have side walls 15, which form each corner portion 13 of the first and second hollow structures adjacent to each other, in common. Thus, the connected hollow structure
10 1 has a substantially-horizontal upper surface and a corrugated lower surface on the whole, and takes the shape resembling a unicursal figure in section.

The connected hollow structure 1 in this embodiment is fabricated as follows. Firstly, while a
15 sheet (not shown) of a predetermined width is being delivered, convex folds and concave folds are sequentially formed on the sheet at intervals according to the size of the hollow structures 11, 12 in a required order, and the required surface of the sheet is
20 coated with glue along the folds.

Subsequently, while the sheet is being folded along the folds so as to start the folding of the sheet according to the direction as shown by an arrow i in Fig. 45, the required edges of the hollow structures are
25 bonded together, and the sheet is cut.

In comparison with the connected hollow structure in the first embodiment, the connected hollow structure

1 in the thirty-fourth embodiment shows lower
withstanding strength against a plane pressure, while it
shows far more flexible elasticity, since, when the
connected hollow structure is exposed to a plane
05 pressure of not less than a predetermined value, the
hollow structures 11, 12 are largely transformed and
absorb such a plane pressure.

In particular, since the partial circumference
14 on the lower side of each first hollow structure 11
10 is composed of two uniformly-projecting side surfaces,
the connected hollow structure in this embodiment shows
highly cushioning properties due to transforming and
restoring action of these side surface portions.

Thus, the connected hollow structure in this
15 embodiment is suitable for use as a cushioning material
for packaging, and besides, other packaging members for
keeping or packaging linear fluorescent lamps or like
articles by inserting such articles into the hollow
portions of the hollow structures 11.

20 (Thirty-fifth embodiment)

Fig. 46 shows a connected hollow structure in
another embodiment corresponding to claim 10 or 29
according to the present invention.

A connected hollow structure 1 in a thirty-fifth
25 embodiment is formed such that while a piece of sheet a
is being folded, first hollow structures 11 of a right-

angled triangular section and of the same size, and second hollow structures 12 of a pentagonal section including a corner portion 13 formed at the same angle as a corner portion 13 of each first hollow structure 11 are alternately arranged in an alternately inverse position as shown in Fig. 46, and the partial circumferences 14 of the hollow structures 11 and those of the hollow structures 12 are respectively connected together by bonding.

10 The connected hollow structure 1 has a substantially-horizontal lower surface formed by connecting the partial circumferences 14 of the first hollow structures 11 together, and a corrugated upper surface formed by connecting the partial circumferences 15 of the second hollow structures 12 together.

 The connected hollow structure 1 in this embodiment shows flexible elasticity, since the partial circumference 14 on the upper side of each second hollow structure 12 is composed of two side surfaces projecting 20 in an angular shape, and these side surface portions are smoothly transformed or restored.

 Other respects of the constitution, functions and effects of the connected hollow structure 1 in the thirty-fifth embodiment are substantially similar to 25 those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Thirty-sixth embodiment)

Fig. 47 shows a connected hollow structure in a further embodiment corresponding to claim 10 or 29 according to the present invention.

05 A connected hollow structure 1 in a thirty-sixth embodiment is formed such that while a piece of sheet a is being folded, first hollow structures 11 of an isosceles triangular section and of the same size, and second hollow structures 12 of a pentagonal section
10 including a corner portion 13 formed at the same angle as a corner portion 13 of each first hollow structure 11 are alternately arranged in an alternately inverse position as shown in Fig. 47, and the partial circumferences 14 of the first hollow structures 11 and
15 those of the second hollow structures 12 are respectively connected together by bonding.

 The connected hollow structure 1 has a substantially-horizontal lower surface formed by connecting the partial circumferences 14 of the first
20 hollow structures 11 together, and a corrugated upper surface formed by connecting the partial circumferences 14 of the second hollow structures 12 together.

 In this embodiment, the connected hollow structure is formed such that each second hollow
25 structure 12 has the pentagonal section, and the partial circumference 14 of each second hollow structure has a trapezoidal shape composed of three side surfaces

and projects upwards, differently from the connected hollow structure 1 in the first embodiment.

The connected hollow structure 1 in this embodiment shows flexible elasticity, since the partial
05 circumference 14 on the upper side of each second hollow structure 12 is composed of two side surfaces projecting in an angular shape, and these side surface portions are smoothly transformed or restored when the connected hollow structure is exposed to a plane pressure.

10 Other respects of the constitution, functions and effects of the connected hollow structure 1 in the thirty-sixth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be
15 omitted.

(Thirty-seventh embodiment)

Fig. 48 partially shows a connected hollow structure in an embodiment corresponding to claim 9 or 29 according to the present invention.

20 A connected hollow structure 1 in a thirty-seventh embodiment is formed such that a large number of first hollow structures 11 of a regular hexagonal section including a corner portion 13 directed toward the upper surface and a partial circumference 14
25 composed of two side surfaces opposite to the corner portion and facing the lower surface, and a large number

of second hollow structures 12 of an isosceles triangular section including a corner portion 13 directed toward the lower surface and a partial circumference 14 composed of a side surface opposite to
05 the corner portion and facing the upper surface are alternately arranged.

The side walls 15b, which are overlapped with each other in a vertical position, of the first hollow structures 11, 11 adjacent to each other are connected
10 together by bonding, and the second hollow structures 12, 12 adjacent to each other are connected together by bonding in a portion of the corner portion 13 of each first hollow structure 11 adjacent to these hollow structures 12, 12. The first and second hollow
15 structures 11, 12 adjacent to each other have the side walls, which form the corner portion 13 of each second hollow structure 13, in common.

The connected hollow structure in this embodiment is fabricated as follows. Firstly, while a sheet (not
—20 shown) of a predetermined width is being delivered, convex folds and concave folds are sequentially formed on the sheet in a required order at intervals according to the size of the hollow structures 11, 12, and the required surface of the sheet is coated with glue along
25 the folds.

Subsequently, while the sheet is being folded along the folds to repeatedly form the hollow structures

11 and the adjacent hollow structures 12 so as to start the folding of the sheet according to the direction as shown in an arrow p in Fig. 48, the required portions of the hollow structures 11, 12 are bonded together, and
05 the sheet is cut.

According to the above procedure, it is possible to form the connected hollow structure 1, which is comprised of a piece of sheet so as to take the shape resembling a unicursal figure in section, and is
10 substantially uniform in apparent thickness T, as shown in Fig. 48.

In comparison with the connected hollow structure in the first embodiment, the connected hollow structure 1 in the thirty-seventh embodiment shows lower
15 withstanding strength against a plane pressure, while it shows more flexible elasticity, since, when the connected hollow structure is exposed to a plane pressure of not less than a predetermined value, the partial circumference 14 composed of two side surfaces
20 projecting substantially uniformly downwards in each hollow structure 11 is transformed and absorbs such a plane pressure.

Thus, the connected hollow structure 1 in this embodiment is suitable for use as a cushioning material
25 for packaging, and besides, suitably used for keeping or packaging linear fluorescent lamps or like articles by inserting such articles into the hollow structures 11,

12.

Further, the connected hollow structure 1 in this embodiment may be rounded into a cylindrical shape with the hollow structures 11 turned to the inside, since, 05 when the connected hollow structure is exposed to an external force sideways, the hollow structures 11 of the hexagonal section are easily transformed in the folding direction.

Other respects of the constitution, functions and 10 effects of the connected hollow structure in the thirty-seventh mode are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Thirty-eighth embodiment)

15 Fig. 49 partially shows a connected hollow structure in an embodiment corresponding to claim 7 or 29 according to the present invention.

A connected hollow structure 1 in a thirty-eighth embodiment is formed such that first hollow structures 20 11 of the same size and of a regular pentagonal section, and second hollow structures 12 of the same size and of a section equal to that of the first hollow structures are alternately arranged in an alternately inverse position.

25 Each first hollow structure 11 is formed such that a corner portion 13 is directed toward the upper

surface, and a partial circumference 14 composed of three side surfaces uniformly projecting downwards faces the lower surface. Each second hollow structure 12 is formed such that a corner portion 13 is directed toward
05 the lower surface, and a partial circumference 14 composed of three side surfaces uniformly projecting upwards faces the upper surface.

The first hollow structures 11, 11 adjacent to each other are connected together by bonding in a
10 portion of the corner portion 13 of each second hollow structure 12 positioned between the first hollow structures adjacent to each other, and the second hollow structures 12, 12 adjacent to each other are connected together by bonding in a portion of the corner portion
15 13 of each first hollow structure 11 positioned between the second hollow structures adjacent to each other.

The first and second hollow structures 11, 12 adjacent to each other have side walls 15, which form the corner portion 13 of each of the first and second
20 hollow structures, in common.

The connected hollow structure 1 in the thirty-eighth embodiment is fabricated as follows. Firstly, while a sheet (not shown) of a predetermined width is being delivered, convex folds and concave folds are
25 sequentially formed on the sheet in a required order at intervals according to the size of the hollow structures 11, 12, and the required surface of the sheet is coated

with glue along the folds.

Subsequently, while the sheet is being folded along the folds to repeatedly form the first hollow structures 11 and the adjacent second hollow structures 12 so as to start the folding of the sheet according to the direction of an arrow n in Fig. 49, the required portions of the hollow structures 11, 12 are bonded together, and the sheet is cut.

According to the above procedure, it is possible to form the connected hollow structure 1, which is comprised of a piece of sheet so as to take the shape resembling a unicursal figure in section, is substantially uniform in apparent thickness T, and has no overlap portion of the sheet used as a material of the connected hollow structure, on any surfaces of the hollow structures 11, 12.

In comparison with the connected hollow structure in the first embodiment, the connected hollow structure 1 in the thirty-eighth embodiment shows lower withstanding strength against a plane pressure, while it shows more flexible elasticity, since, when the connected hollow structure is exposed to a plane pressure of not less than a predetermined value, the hollow structures 11, 12 are easily transformed and absorb such a plane pressure.

Thus, the connected hollow structure in this embodiment is suitable for use as a cushioning material

for packaging, and besides, suitably used for keeping or packaging linear fluorescent lamps or like articles by inserting such articles into the hollow structures 11, 12.

Other respects of the constitution, functions and effects of the connected hollow structure in the thirty-eighth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Thirty-ninth embodiment)

Fig. 50 partially shows a connected hollow structure in another embodiment corresponding to claim 7 or 29 according to the present invention.

A connected hollow structure 1 in a thirty-ninth embodiment is formed such that a large number of first hollow structures 11 of a quadrangular (or parallelogram) section and of the same size, and a large number of second hollow structures 12 of the same size and equal in sectional shape to the first hollow structures are alternately arranged in an alternately inverse position.

Each first hollow structure 11 is formed such that a corner portion 13 is directed toward the upper surface, and a partial circumference 14 composed of two side surfaces uniformly projecting downwards faces the lower surface. On the other hand, each second hollow

structure 12 is formed such that a corner portion 13 is directed toward the lower surface, and a partial circumference 14 composed of two side surfaces uniformly projecting upwards faces the upper surface.

05 The first hollow structures 11, 11 adjacent to each other are connected together by bonding in a portion of the corner portion 13 of each second hollow structure 12 positioned between the first hollow structures adjacent to each other, and the second hollow
10 structures 12, 12 adjacent to each other are connected together by bonding in a portion of the corner portion of each first hollow structure 11 positioned between the second hollow structures adjacent to each other.

 The connected hollow structure 1 in the thirty-
15 ninth embodiment is fabricated as follows. Firstly, while a sheet (not shown) of a predetermined width is being delivered, convex folds and concave folds are sequentially formed on the sheet in a required order at intervals according to the size of the hollow structures
20 11, 12, and the required surface of the sheet is coated with glue along the folds.

 Subsequently, while the sheet is being folded along the folds so as to start the folding of the sheet according to the direction shown by an arrow K in Fig.
25 50, the required portions of the hollow structures 11, 11 and those of the second hollow structures 12, 12 are bonded together, and the sheet is cut.

According to the above procedure, it is possible to form the connected hollow structure 1, which is comprised of a piece of sheet so as to take the shape resembling a unicursal figure in section, and has no
05 overlap portion of the sheet used as a material of the connected hollow structure on any surfaces of the hollow structures 11, 12.

In comparison with the connected hollow structure 1 in the first embodiment, the connected hollow
10 structure 1 in the thirty-ninth embodiment shows far lower withstanding strength against a plane pressure, while it shows extremely flexible elasticity, since, when the connected hollow structure is exposed to a plane pressure of not less than a predetermined value,
15 the hollow structures 11, 12 are easily transformed in the folding direction and absorb such a plane pressure.

Thus, the connected hollow structure in this embodiment is suitable for use as a cushioning material for packaging, and besides, suitably used for keeping or
20 packaging linear fluorescent lamps or like articles by inserting such articles into the hollow structures 11, 12.

The connected hollow structure 1 in this embodiment may be handled in a flatly-folded state on
25 the whole for storage or transportation, since the hollow structures 11, 12 have a quadrangular or parallelogram section, and are connected together in the

portions of their corner portions 13.

Further, the connected hollow structure 1 in this embodiment may be easily rounded into a cylindrical shape with the hollow structures 11 or 12 turned to the inside, since the hollow structures 11, 12 of this connected hollow structure 1 are easily transformed as described above.

Other respects of the constitution, functions, and effects of the connected hollow structure in the thirty-ninth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the description thereof will be omitted.

(Fortieth embodiment)

Fig. 51 partially shows a connected hollow structure in an embodiment corresponding to claim 9 or 29 according to the present invention.

A connected hollow structure 1 in a fortieth embodiment is formed such that a large number of first hollow structures 11 of a regular hexagonal section including a corner portion 13 directed toward the upper surface and a partial circumference 14 composed of two side surfaces on the opposite side to the corner portion and facing the lower surface, and a large number of second hollow structures 12 equal in shape and size to the first hollow structures 11 and including a corner

portion 13 directed toward the lower surface and a partial circumference 14 composed of two side surfaces on the opposite side to the corner portion and facing the upper surface are alternately arranged.

- 05 The side walls 15b, which are overlapped with each other in a vertical position, of the first hollow structures 11, 11 adjacent to each other and those of the second hollow structures 12, 12 adjacent to each other are respectively connected together by bonding.
- 10 The first and second hollow structures 11, 12 adjacent to each other have side walls 15, which form the corner portion 13 of each of the first and second hollow structures, in common.

 The connected hollow structure 1 in the fortieth
15 embodiment is fabricated as follows. Firstly, while a sheet (not shown) of a predetermined width is being delivered, convex folds and concave folds are sequentially formed on the sheet in a required order at intervals according to the size of the hollow structures
20 11, 12, and the required surface of the sheet is coated with glue along the folds.

 Subsequently, while the sheet is being folded along the folds to repeatedly form the first hollow structures 11 and the adjacent second hollow structures
25 12 in an alternate arrangement so as to start the folding of the sheet according to the direction as shown by an arrow m in Fig. 51, the required portions of the

hollow structures 11, 12 are bonded together, and the sheet is cut.

According to the above procedure, it is possible to form the connected hollow structure 1 which is
05 comprised of a piece of sheet so as to take the shape resembling a unicursal figure in section, as shown in Fig. 51.

In comparison with the connected hollow structure in the first embodiment, the connected hollow structure
10 1 in the fortieth embodiment shows far lower withstanding strength against a plane pressure, while it shows more flexible elasticity, since, when the connected hollow structure is exposed to a plane pressure of not less than a predetermined value, the
15 partial circumference 14 composed of two substantially-uniformly projecting side surfaces in each of the hollow structures 11, 12 is easily transformed and absorbs such a plane pressure.

Thus, the connected hollow structure in this
20 embodiment is suitable for use as a cushioning material for packaging, and besides, suitably used for keeping or packaging linear fluorescent lamps or like articles by inserting such articles into the hollow structures 11, 12.

25 The connected hollow structure 1 in this embodiment is handled in a flatly-folded state on the whole for storage or transportation, since the hollow

structures 11, 12 have a regular hexagonal section and are flatly folded, when the connected hollow structure is exposed to an external force sideways.

Further, the connected hollow structure 1 in this
05 embodiment may be rounded into a cylindrical shape with the hollow structures 11 or 12 turned to the inside, since the hollow structures 11, 12 are easily transformed in the folding direction when the connected hollow structure is exposed to the external force
10 sideways, as described above.

Other respects of the constitution, functions and effects of the connected hollow structure 1 in the fortieth embodiment are substantially similar to those of the connected hollow structure in the first
15 embodiment, and hence, the description thereof will be omitted.

(Forty-first embodiment)

Fig. 52 partially shows a connected hollow
structure in an embodiment corresponding to claim 37
20 according to the present invention.

A connected hollow structure 1 in a forty-first embodiment is formed such that a large number of first hollow structures 11 of an isosceles triangular section and of the same size and a large number of second hollow
25 structures equal in sectional shape and size to the first hollow structures are connected together in an

alternate arrangement. The connected hollow structure in this embodiment is substantially similar in end face structure of the hollow portion to the connected hollow structure in the first embodiment.

- 05 The connected hollow structure 1 has a doughnut-like or sectorial plane on the whole, since the hollow structures 11, 12 as the components of the connected hollow structure 1 are formed such that their sectional size is gradually reduced from one end to the other.
- 10 The connected hollow structure in this embodiment is different from the connected hollow structure 1 in the first embodiment in this respect.

(Forty-second embodiment)

- Fig. 53 partially shows a connected hollow
- 15 structure in an embodiment corresponding to claims 34 and 35 according to the present invention.

- A connected hollow structure 1 in a forty-second embodiment is formed such that first hollow structures 11 of an isosceles triangular section and of the same
- 20 size, other than those positioned on both ends of the connected hollow structure, and second hollow structures 12 equal in sectional shape and size to the first hollow structures are alternately arranged in an alternately inverse position. The second hollow structure 12 at
- 25 both ends of the connected hollow structure 1 has a right-angled triangular section so as to hold an

inclined side wall 15 of the adjacent first hollow structure 11 in common.

A stripe of bending node 15c consisting of a small groove is formed at the same level position on one
05 surface of each side wall 15 common to the hollow structures 11, 12 so as to extend in the length direction of the hollow structures 11, 12.

When the connected hollow structure 1 in this embodiment is exposed to a plane pressure of not less
10 than a predetermined value, the side walls 15 of the hollow structures 11, 12 are bent along the nodes 15c as shown in Fig. 54, and absorb such a plane pressure. Thus, in case of using the connected hollow structure 1 as a packaging member, when the packaging member is
15 temporarily exposed to an impact in the direction indicated by a bold arrow in Fig. 54, the side walls are bent and absorb such an impact, so that the packaging member is considerably prevented from being collapsed at a stroke, and an article to be packaged is also
20 prevented from being damaged.

When the connected hollow structure having the bending nodes 15c formed as the grooves on the side walls 15 as described above is exposed to a predetermined load, the side walls 15 are bent with the
25 grooves turned toward the inside as shown in Fig. 54, and therefore, it is possible to control the directivity of bending. In the illustrated embodiment, when the

side walls 15 are bent up to the maximum, portions lower than the bending nodes 15c of both side walls 15, 15 of the second hollow structures 12 at both ends of the connected hollow structure are overlapped with each other in a vertical position, and the vertical overlap portions bear the action of supports. Thus, the connected hollow structure, in which the side walls 15 have been bent up to the maximum, shows extremely high withstanding strength against a plane pressure.

10 According to this embodiment, the bending nodes 15c are formed by forming the grooves on either surface of the side walls 15 by means of press. Otherwise, since the bending nodes attain the most part of their purpose as long as the bending nodes functions as a
15 bending guide when the side walls 15 are exposed to a load of not less than a predetermined value, the bending nodes are not always formed by the grooves. For instance, the side walls 15 may be bent by the bending nodes 15c formed by pressing the side walls 15 from both
20 sides thereof.

Other respects of the constitution, functions and effects of the connected hollow structure in the forty-second embodiment are substantially similar to those of the connected hollow structure in the first embodiment,
25 and hence, the description thereof will be omitted.

(Forty-third embodiment)

Fig. 55 partially shows a connected hollow structure in an embodiment corresponding to claim 39 according to the present invention.

A connected hollow structure 1 in a forty-third
05 embodiment is substantially similar in basic constitution to the connected hollow structure in the first embodiment, except that each side wall 15 common to the hollow structures 11, 12 in the forty-third embodiment has a concave portion 15c slightly bent
10 toward the inner portion of the first or second hollow structure and formed at a certain level position of each side wall so as to extend in the length direction of the side wall 15.

When the connected hollow structure 1 in this
15 embodiment is exposed to a plane pressure of not less than a predetermined value, the concave portions 15c function as a guide for bending, and the side walls 15 are bent so as to enlarge a concave angle of each concave portion 15c and absorb a shock caused by the
20 plane pressure.

When the connected hollow structure is exposed to a high plane pressure, the side walls 15 are further bent, and the portions upper than the concave portions 15c of the side walls 15 are overlapped with each other
25 in a vertical position, so that the vertical overlap portions bear the action of supports. Thus, the connected hollow structure 1, in which the side walls 15

have been bent up to the maximum, shows extremely high withstanding strength against a plane pressure.

(Forty-fourth embodiment)

Fig. 56 partially shows a connected hollow structure in another embodiment corresponding to claim 1 according to the present invention.

A connected hollow structure 1 in a forty-fourth embodiment is composed of a large number of first hollow structures 11 of a transformed hexagonal section and of the same size, a large number of second hollow structures 12 of an isosceles triangular section and placed above portions between the first hollow structures 11, 11 adjacent to each other in an inverse arrangement, and auxiliary hollow structures 11b of a parallelogram section and placed below the second hollow structures 12 and between the first hollow structures 11, 11 adjacent to each other.

The first hollow structures 11, 11 adjacent to each other are connected together by bonding in a portion of the corner portion 13 of each second hollow structure 12 adjacent to the upper side surfaces of the first hollow structures adjacent to each other, and the lower-side partial circumferences 14 forming the bottom of the first hollow structures are connected together by bonding.

The upper-side partial circumferences 14 of the

second hollow structures 12, 12 adjacent to each other are connected together by bonding.

The first and second hollow structures 11, 12 adjacent to each other have side walls 15, which form
05 each corner portion 13 of the first and second hollow structures, in common, and the auxiliary and first hollow structures 11b, 11 adjacent to each other have all the side walls, which form each auxiliary hollow structure 11b, in common.

10 With the constitution described above, the connected hollow structure 1 has concave portions 15d formed on both sides of the auxiliary hollow structures 11b.

The connected hollow structure 1 in the forty-
15 fourth embodiment is fabricated as follows. Firstly, while a sheet (not shown) of a predetermined width is being delivered, convex folds and concave folds are sequentially formed on the sheet in a required order at intervals according to the size of the hollow structures
20 11, 11b, 12, and the required surface of the sheet 1 is coated with glue along the folds.

Subsequently, while the sheet is being folded along the folds to repeatedly form the hollow structures 11, the adjacent hollow structures 12 and the hollow
25 structures 11b below the hollow structures 12 so as to start the folding of the sheet according to the direction as shown by an arrow q in Fig. 56, the

required edges of the hollow structures 11, 12 are bonded together, and the sheet is cut.

According to the above procedure, it is possible to form the connected hollow structure 1, which is
05 comprised of a piece of sheet so as to take the shape resembling a unicursal figure in section, and has no overlap portion of the sheet used as a material of the connected hollow structure on any side surfaces of the hollow structures 11, 12, 11b.

10 The connected hollow structure 1 in this embodiment shows far lower withstanding strength against a plane pressure, while it shows extremely flexible elasticity, since, when the connected hollow structure 1 in this embodiment is exposed to a plane pressure of not
15 less than a predetermined value, the auxiliary hollow structures 11b are transformed so as to be folded, namely, to enlarge the concave angle of each concave portion 15d, and absorb such a plane pressure.

Thus, the connected hollow structure 1 in this
20 embodiment is suitable for use as a cushioning material for packaging, and besides, suitably used for keeping or packaging linear fluorescent lamps or like articles by inserting such articles into the hollow structures 11.

Other respects of the constitution, functions and
25 effects of the connected hollow structure 1 in the forty-fourth embodiment are substantially similar to those of the connected hollow structure in the first

embodiment, and hence, the description thereof will be omitted.

(Forty-fifth embodiment)

Fig. 57 partially shows a connected hollow
05 structure in an embodiment corresponding to claim 38
according to the present invention.

A connected hollow structure 1 in a forty-fifth
embodiment is comprised of a piece of sheet and is
formed such that a large number of first hollow
10 structures 11 of an isosceles triangular section and of
the same size and a large number of second hollow
structures 12 equal in shape and size to the first hollow
structures 11 are alternately arranged in an inverse
position. The second hollow structure 12 positioned at
15 both ends of the connected hollow structure has a right-
angled triangular section.

The connected hollow structure 1 in this
embodiment is substantially similar to the connected
hollow structure in the first embodiment in the range of —
20 the above constitution.

The connected hollow structure 1 in this
embodiment has four small hollow portions 11a, 12a of a
rectangular equilateral triangular section respectively
formed in the first and second hollow structures 12 by
25 folding a sheet a, in a step of alternately forming the
first and second hollow structures 11, 12 in an

alternately inverse position by folding the sheet a.

The connected hollow structure 1 in this embodiment is fabricated as follows. Firstly, while a sheet (not shown) of a predetermined width is being
05 delivered, convex folds and concave folds are sequentially formed on the sheet in a required order at intervals according to the size of the first and second hollow structures 11, 12 and also the inner small hollow portions 11a, 12a of these hollow structures, and the
10 required surface of the sheet is coated with glue along the folds.

Subsequently, while the sheet is being folded along the folds so as to repeatedly form the first hollow structures 11 including the small hollow portions
15 11a, and the second hollow structures 12 including the small hollow portions 12a in an alternate arrangement, the required edges of the hollow structures 11, 12 are bonded together, and the sheet is cut.

According to the above procedure, it is possible
20 to form the connected hollow structure 1, which is comprised of a piece of sheet so as to take the shape resembling a unicursal figure in section, and has no overlap portion of the sheet used as a material of the connected hollow structure on any side surfaces of the
25 first hollow structures 11 including the small hollow portions 11a, and the second hollow structures 12 including the small hollow portions 12a.

In comparison with the connected hollow structure in the first embodiment, the connected hollow structure in the forty-fifth embodiment shows higher withstanding strength against a plane pressure, since the large
05 number of hollow portions having the effect of being reinforced with each other are formed in two, i.e., upper and lower stages. Further, since the hollow portions are formed more densely, the connected hollow structure in this embodiment is suitable for use as a
10 carrier for carrying adsorbents. In addition, in case of cutting the connected hollow structure 1 in this embodiment in round slices at a predetermined pitch, a slice of the connected hollow structure is suitable for use as a core material of a heat-insulating panel or
15 like hollow panel.

Other respects of the constitution, functions and effects of the connected hollow structure 1 in the forty-fifth embodiment are substantially similar to those of the connected hollow structure in the first
20 - embodiment, and hence, the description thereof will be omitted.

(Forty-sixth embodiment)

Fig. 58 partially shows a connected hollow structure in another embodiment corresponding to claim
25 38 according to the present invention.

A connected hollow structure 1 in a forty-sixth

embodiment is a modification of the connected hollow structure in the forty-fifth embodiment, and each of the first and second hollow structures 11, 12 respectively has two small hollow portions 11a or 12a of a
05 rectangular equilateral triangular section and a single small hollow portion 11a or 12a of a parallelogram section.

Other respects of the constitution, functions, and effects of the connected hollow structure 1 in the
10 forty-sixth embodiment are substantially similar to those of the connected hollow structure in the forty-fifth embodiment, and hence, the description thereof will be omitted.

(Forty-seventh embodiment)

15 Fig. 59 partially shows a connected hollow structure in an embodiment corresponding to claim 28 according to the present invention.

A connected hollow structure 1 in a forty-seventh embodiment is formed such that the section of the
20 partial circumference 14 of each second hollow structure 12 in the connected hollow structure in the first embodiment is modified into a partial circumference of a circular arc section so as to substantially uniformly project upwards.

25 According to the connected hollow structure in this embodiment formed as described above, when the

connected hollow structure 1 with the left and right
ends in Fig. 59 constrained is exposed to a plane
pressure of not less than a predetermined value, the
circular arc-shaped partial circumferences 14 forming
05 the upper surface of the second hollow structures 12 are
transformed and restored to absorb such a plain
pressure. Thus, in comparison with a connected hollow
structure in the first embodiment, the connected hollow
structure in the forty-seventh embodiment functions as a
10 cushioning material more highly.

Other respects of the constitution, functions and
effects of the connected hollow structure 1 in the
forty-seventh embodiment are substantially similar to
those of the connected hollow structure in the first
15 embodiment, and hence, the description thereof will be
omitted.

(Forty-eighth embodiment)

Fig. 60 partially shows a connected hollow
structure in another embodiment corresponding to claim
20 28 according to the present invention.

A connected hollow structure 1 in a forty-
eighth embodiment is a modification of the connected
hollow structure in the forty-seventh embodiment,
and the partial circumference 14 on the lower side
25 of each first hollow structure 11 and that of the
partial circumference 14 on the upper side of each

second hollow structure 12 are respectively modified into a partial circumference of a circular arc section so as to substantially uniformly project upwards and downwards.

05 The connected hollow structure 1 in this embodiment is superior in elasticity to the connected hollow structure in the forty-seventh embodiment, and therefore, is suitable for use as a cushioning material for an article to be packaged, since the partial
10 circumferences 14 of the hollow structures 11, 12 project in a circular arc shape.

(Forty-ninth embodiment)

Fig. 61 partially shows a connected hollow structure in a further embodiment corresponding to claim
15 28 according to the present invention.

A connected hollow structure 1 in a forty-ninth embodiment is another modification of the connected hollow structure in the forty-seventh embodiment, and the partial circumference 14 on the upper surface of
20 part of second hollow structures (every other second hollow structure) is modified into a partial circumference of a circular arc section so as to substantially uniformly project upwards.

Namely, it is possible to form the connected
25 hollow structure 1 which shows elasticity according to the purpose as a packaging member by selecting the

density of the hollow structures 11 or 12 having the partial circumferences 14 of the circular-arc section.

(Fiftieth embodiment)

Fig. 62 partially shows a connected hollow
05 structure in a further embodiment corresponding to claim 28 according to the present invention.

A connected hollow structure 1 in a fiftieth embodiment is formed such that each second hollow structure 12 in the connected hollow structure in the
10 thirty-eighth embodiment (See Fig. 49) is modified into a hollow structure of a sectorial section as shown in Fig. 62, instead of the regular pentagonal section, and the partial circumference 14 on the upper side of each hollow structure 12 is modified into a partial
15 circumference of a circular arc section so as to substantially uniformly project upwards.

The effects of the connected hollow structure 1 in this embodiment attained by forming the second hollow structures 12 having the partial circumference 14 of the
20 circular arc section as shown in Fig. 62 is substantially similar to that of the connected hollow structure in the forty-seventh embodiment.

(Fifty-first embodiment)

Fig. 63 partially shows a connected hollow
25 structure in a still further embodiment corresponding to

claim 28 according to the present invention.

A connected hollow structure 1 in a fifty-first embodiment is formed such that the partial circumference 14 on the upper side of each second hollow structure 12 in the connected hollow structure in the fifteenth embodiment (See Fig. 27) is modified into a partial circumference of a circular arc section so as to substantially uniformly project upwards.

In comparison with the connected hollow structure 10 in the fifteenth embodiment, the connected hollow structure 1 in the fifty-first embodiment formed as described above functions as a cushioning material more highly, since, when the connected hollow structure 1 with the left and right ends in Fig. 63 constrained is 15 exposed to a plane pressure of not less than a predetermined value, the circular arc-shaped partial circumferences 14 forming the upper surface of the second hollow structures 12 are transformed and restored to absorb such a plane pressure.

20 Other respects of the constitution, functions and effects of the connected hollow structure 1 in the fifty-first embodiment are substantially similar to those of the connected hollow structure in the fifteenth embodiment, and hence, the description thereof will be 25 omitted.

(Fifty-second embodiment)

Fig. 64 partially shows a connected hollow structure in a still further embodiment corresponding to claim 28 according to the present invention.

A connected hollow structure 1 in a fifty-second
05 embodiment is formed such that the partial circumference
14 of each section hollow structure 12 on the inner side
of the connected hollow structure in the twelfth
embodiment (See Fig. 24) is modified into a partial
circumference of a circular arc section so as to
10 substantially uniformly project toward the inside of the
connected hollow structure.

In comparison with the connected hollow structure
in the fifth embodiment, the connected hollow structure
1 in the fifty-second embodiment formed as described
15 above functions as a cushioning material more highly,
since, when the inner surface of the connected hollow
structure 1 is exposed to a pressure of not less than a
predetermined value, the circular arc-shaped partial
circumferences 14 forming the upper surface of the
20 second hollow structures 12 are transformed and
restored to absorb such a plane pressure.

(Fifty-third embodiment)

Fig. 65 partially shows a connected hollow
structure in a yet further embodiment corresponding to
25 claim 28 according to the present invention.

A connected hollow structure 1 in a fifty-third

embodiment is formed such that the partial circumference 14 of each second hollow structure 12 on the inner side of the connected hollow structure 1 in the twelfth embodiment (See Fig. 24) is modified into a partial
05 circumference of a circular arc section so as to substantially uniformly project toward the inner side of the connected hollow structure.

The connected hollow structure 1 in this embodiment formed as described above functions as a
10 cushioning material more highly, since, when the connected hollow structure 1 is exposed to a load of not less than a predetermined value in the circumferential or inner peripheral direction, the circular arc-shaped partial circumferences 14 of the second hollow
15 structures 12 are transformed and restored to absorb such a plane pressure.

(Fifty-fourth embodiment)

Fig. 66 partially shows a connected hollow structure in a yet further embodiment corresponding to
20 claim 28 according to the present invention.

A connected hollow structure 1 in a fifty-fourth embodiment is formed such that the partial circumference 14 of each second hollow structure 12 on the inner side of the connected hollow structure in the thirteenth
25 embodiment (See Fig. 25) is modified into a partial circumference of a circular arc section so as to

substantially uniformly project toward the inner side of the connected hollow structure.

The effect of the connected hollow structure 1 in this embodiment attained by forming the second
05 hollow structures 2 having the partial circumferences 14 of the circular arc section as shown in Fig. 66 is substantially similar to that of the connected hollow structure in the fifty-third embodiment.

(Fifty-fifth embodiment)

10 Fig. 67 partially shows a connected hollow structure in a yet further embodiment corresponding to claim 28 according to the present invention.

A connected hollow structure 1 in a fifty-fifth embodiment is formed such that the partial circumference
15 14 of each second hollow structure 12 on the inner side of the connected hollow structure 1 in the fourteenth embodiment (See Fig. 26) is modified into a partial circumference of a circular arc section so as to substantially uniformly project toward the inner side of
20 the connected hollow structure.

The effect of the connected hollow structure 1 in this embodiment attained by forming the second hollow structures 12 having the partial circumferences 14 of the circular arc section as shown in Fig. 67 is
25 substantially similar to that of the connected hollow structure in the fifty-third embodiment.

(Fifty-sixth embodiment)

Fig. 68 shows a connected hollow structure in an embodiment corresponding to claims 40 and 41 according to the present invention.

05 A connected hollow structure 1 in a fifty-sixth embodiment is composed of a large number of connecting sheet portions a14 bonded together so as to extend in parallel to each other, and a large number of cylindrical hollow structures 10 connected together by
10 respectively bonding circumferential portions together in the length direction in joint portions a15 between the connecting sheet portions a14, a14 adjacent to each other.

 The connected hollow structure 1 having the above
15 constitution is fabricated as follows. Firstly, while a sheet a (not shown) of a predetermined width is being delivered, convex (or concave) folds are sequentially formed on the sheet a so as to extend in the cross direction of the sheet a according to the sectional
20 peripheral length of each hollow structure 10 and the width of each connecting sheet portion a14, and the fold portions of the sheet are coated with glue.

 Subsequently, while the sheet a is being rounded into cylindrical portions from the leading end of the
25 sheet along the folds, the folds corresponding to the joint portions a15 forming the joints of the cylindrical portions are bonded together. When the connected hollow

structure 1 thus fabricated reaches a predetermined length, the sheet, which is being delivered, is cut.

According to the above procedure, it is possible to form the connected hollow structure 1, which is
05 comprised of a piece of sheet so as to take the shape resembling a unicursal figure in section, and has no overlap portion of the sheet used as a material of the connected hollow structure, other than the joint portions 15.

10 The connected hollow structure 1 in this embodiment shows far lower withstanding strength against a plane pressure, while it shows extremely flexible elasticity, since, when the connected hollow structure is exposed to a plane pressure of not less than a
15 predetermined value, the hollow structures 10 are transformed so as to become flat, and absorb such a plane pressure.

Thus, the connected hollow structure in this embodiment is suitable for use as a cushioning material
20 for packaging, and besides, suitably used for keeping or packaging linear fluorescent lamps or like articles by inserting such articles into the hollow structures 10.

Since the cylindrical hollow structures 10 are transformed by a relatively small external force, the
25 connected hollow structure 1 in the state shown in Fig. 68 may be rounded, for instance, in a cylindrical shape with the hollow structures 10 positioned along the inner

surface. Thus, such a cylindrical connected hollow structure 1 is suitable for use as a frame structure for encasing bottles or like articles.

When a corrugated fiberboard is used for forming
05 the connected hollow structure 1 in this embodiment, the folds are preferably formed in parallel to flutes of the corrugated fiberboard. Further, the hollow structures
10 preferably have a cylindrical or elliptical section.

(Fifty-seventh embodiment)

10 Fig. 69 partially shows a connected hollow structure in another embodiment corresponding to claims 40 to 42 according to the present invention.

A connected hollow structure 1 in a fifty-seventh embodiment is a modification of the connected hollow
15 structure in the fifty-sixth embodiment, and is designed such that the hollow structures 10 are formed at slightly wider intervals (i.e., the connecting sheet portions a15 are formed to be slightly wider). Thus, the connected hollow structure 1 in this embodiment has
20 a cylindrical shape on the whole with the hollow structures 10 lined up along the inner surface such that the hollow structures 10 are spaced slightly, after the connecting sheet portions a15 and the hollow structures 10 have been formed as one body.

25 The cylindrical or elliptical hollow structures 10 are easily transformed when exposed to an external

force, and therefore, show preferable effects from the viewpoint of cushioning properties, since, when the connected hollow structure 1 in this embodiment is used as a packaging frame structure for encasing bottles or
05 like articles by inserting such bottles into the connected hollow structure 1 such that the hollow structures 10 are slightly compressed by the bottles in the circumferential direction, the bottles remain the held state at all times by the action of a predetermined
10 elastic force.

When a corrugated fiberboard is used for forming the connected hollow structure 1 in this embodiment, the folds are preferably formed in parallel to flutes of the corrugated fiberboard.

15 (Fifty-eighth embodiment)

Fig. 70 partially shows a connected hollow structure in an embodiment corresponding to claim 43 according to the present invention.

A connected hollow structure 1 in a fifty-eighth
20 embodiment is composed of a large number of mutually-adjacent hollow structures 10 connected together, and the hollow structures 10 include first hollow structures 11b of a substantially drop-shaped section and second hollow structures 12b of a substantially inverse drop-
25 shaped section.

The first and second hollow structure 11b, 12b

are formed in an alternate arrangement by processing a sheet so as to sequentially form portions 16 of the sectional shape of a letter S and portions 17 of the sectional shape of an inverse letter S in an alternate
05 arrangement, and then connecting the side of each portion 16a of the sectional shape of the letter S and the side of the adjacent portion 17 of the sectional shape of the inverse letter S together.

Since the connected hollow structure 1 in this
10 embodiment is comprised of a piece of sheet on the whole so as to take the shape resembling a unicursal figure in section, and has no overlap portion of the sheet used as a material of the connected hollow structure, other than the joint portions between each portion of the sectional
15 shape of the letter S and the adjacent portion of the sectional shape of the inverse letter S, the apparent specific gravity of this connected hollow structure is extremely small.

The connected hollow structure 1 in this
20 embodiment shows extremely low withstanding strength against a plane pressure, while it shows extremely flexible elasticity, since, when the hollow structures 11b, 12b are exposed to an external force, the hollow structures 11b, 12b are transformed and absorb such an
25 external force.

Thus, the connected hollow structure 1 in this embodiment is suitable for use as a cushioning material

for packaging, and besides, suitably used for keeping or packaging linear fluorescent lamps or like articles by inserting such articles into the hollow structures 11b, 12b.

05 The connected hollow structure in this embodiment may be also used for packaging bottles or like articles having a cylindrical portion by rounding this connected hollow structure in a cylindrical shape on the whole with the hollow structures 11b or 12b turned toward the
10 inner side, since the hollow structures 11b, 12b are easily transformed when exposed to an external force.

 When a corrugated fiberboard is used for forming the connected hollow structure 1 in this embodiment, the folds are preferably formed in parallel to flutes of the
15 corrugated fiberboard.

 Other functions and effects of the connected hollow structure 1 in the fifty-eighth embodiment are substantially similar to those of the connected hollow structure in the first embodiment, and hence, the
20— description thereof will be omitted.

(Fifty-ninth embodiment)

 Fig. 71 shows a connected hollow structure in an embodiment corresponding to claim 44 according to the present invention.

25 A connected hollow structure 1 in a fifty-ninth embodiment is basically similar to the connected hollow

structure in the fifty-eighth embodiment, except that the connected hollow structure in the fifty-ninth embodiment has a cylindrical shape on the whole and the second hollow structures 12b of this connected hollow structure are smaller in peripheral length than the first hollow structures 11b.

The connected hollow structure 1 in this embodiment shows extremely flexible elasticity, since, when the connected hollow structure 1 is exposed to an external force, the hollow structures 11b, 12b are transformed and absorb such an external force.

The connected hollow structure 1 in this embodiment is suitably used for packaging bottles or like articles having a cylindrical portion by inserting such articles into the connected hollow structure, or keeping or packaging linear fluorescent lamps or like articles by inserting such articles into the connected hollow structure.

Other functions and effects of the connected hollow structure in the fifty-ninth embodiment are substantially similar to those of the connected hollow structure in the fifty-eighth embodiment, and hence, the description thereof will be omitted.

(Sixtieth embodiment)

Fig. 72 shows a connected hollow structure in an embodiment corresponding to claims 45 and 46 according

to the present invention.

A connected hollow structure 1 in a sixtieth embodiment is formed such that a large number of hollow structures 10 each formed by symmetrically combining a
05 first hollow portion 10a of an angular section and a second hollow portion 10b of an inverse angular section are arranged densely in parallel to each other, and the hollow structures 10 adjacent to each other are connected together in shape of a letter S or an inverse
10 letter S in section.

The first hollow portions 10a in this embodiment have a semicircular section, and the second hollow portions 10b have a semicircular section reverse to that of the first hollow portions 10a.

15 The connected hollow structure 1 in this embodiment is suitable for use as a packaging member as a cushioning material for articles to be packaged, and besides, other packaging members for protecting linear fluorescent lamps or like rod-shaped or cylindrical
20 articles by inserting such articles into the hollow portions 10a, 10b, since the hollow structures 10 including the hollow portions 10a, 10b show flexible elasticity.

Further, when the connected hollow structure 11
25 having more hollow structures 10 is rounded in a cylindrical shape, the hollow portions positioned on the cylindrically inner surface are compressively

transformed to easily form a cylindrical connected hollow structure. Thus, such a cylindrical connected hollow structure is suitable for use as a packaging member for protecting bottles or like articles to be
05 packaged.

Incidentally, when a corrugated fiberboard is used as a sheet for forming the connected hollow structure, the hollow structures 10 are preferably formed in parallel to flutes of the corrugated
10 fiberboard (not shown).

(Sixty-first embodiment)

Fig. 73 shows a connected hollow structure in another embodiment corresponding to claims 45 and 46 according to the present invention.

15 A connected hollow structure 1 in a sixty-first embodiment is formed such that the first and second hollow portions 10a, 10b included in the hollow structures 10 in the connected hollow structure in the sixtieth embodiment are respectively modified into
20 hollow portions of a trapezoidal section and an inverse trapezoidal section.

The other respects of the constitution, functions and effects of the connected hollow structure 1 in the sixty-first embodiment are substantially similar to
35 those of the connected hollow structure in the sixtieth embodiment, and hence, the description thereof will be

omitted.

(Sixty-second embodiment)

Fig. 74 shows a connected hollow structure in a further embodiment corresponding to claims 45 and 46 according to the present invention.

A connected hollow structure 1 in a sixty-second embodiment is formed such that the first and second hollow portions 10a, 10b included in the hollow structures 10 in the connected hollow structure in the sixtieth embodiment are respectively modified into hollow portions of a triangular section and an inverse triangular section.

Other respects of the constitution, functions and effects of the connected hollow structure 1 in the sixty-second embodiment are substantially similar to those of the connected hollow structure in the sixtieth embodiment, and hence, the description thereof will be omitted.

(Other embodiments)

In the connected hollow structure 1 in the twenty-fourth embodiment as shown in Fig. 36 according to the present invention, the second hollow structures 12 may have a quadrangular (parallelogram) section, instead of a triangular section. The connected hollow structure having the second hollow structures 12 of the

quadrangular section as described above forms the connected hollow structure corresponding to claim 11 according to the present invention.

In the connected hollow structure 1 in the
05 twelfth embodiment as shown in Figs. 23 and 24, and that
in the thirteenth embodiment as shown in Fig. 25
according to the present invention, the partial
circumference 14 of each first hollow structure 11 may
be composed of a plurality of substantially uniformly
10 projecting side surfaces, similarly to the partial
circumference 14 of each first hollow structure 11 in
the connected hollow structure 1 shown in Fig. 67, for
instance. The connected hollow structure 1 formed as
described above forms the connected hollow structure
15 corresponding to claim 31 according to the present
invention.

In the connected hollow structure 1 in the
fifteenth embodiment as shown in Fig. 27, that in the
thirty-second embodiment as shown in Fig. 43 and that in
20 the thirty-third embodiment as shown in Fig. 44
according to the present invention, the partial
circumference 14 of each second hollow structure 12 may
be composed of a plurality of substantially uniformly
projecting side surfaces, similarly to the partial
25 circumference 14 of each second hollow structure 12 in
the connected hollow structure 1 as shown in Figs. 46
and 47, for instance. The connected hollow structure 1

formed as described above forms the connected hollow structure corresponding to claim 32 according to the present invention.

In the connected hollow structure 1 in the
05 sixteenth embodiment as shown in Fig. 28 according to the present invention, the partial circumference 14 of each second hollow structure may be composed of a plurality of substantially uniformly projecting side surfaces, similarly to the partial circumference 14 of
10 each second hollow structure 12 in the connected hollow structure 1 as shown in Figs. 46 and 47, for instance. The connected hollow structure 1 formed as described above forms the connected hollow structure corresponding to claim 33 according to the present invention.

15 (Capability of Industrial Utilization)

The connected hollow structure and packaging member according to the present invention is useful as a protection frame structure for packaging, a cushioning material for packaging, a carrying tray, a core material
20 for a heat-insulating panel or other hollow panels, a wall material, a pallet and a carrier for carrying adsorbents.



CLAIMS:

1. A connected hollow structure, comprising:
a large number of hollow structures 10 having an arbitrary sectional shape and connected in parallel to
05 each other;
wherein said connected hollow structure is comprised of a piece of sheet a and takes the shape resembling a unicursal figure in section.
2. A connected hollow structure according to
10 claim 1, wherein the hollow structures 10 include first hollow structures 11 and second hollow structures 12 each having a corner portion 13 of a convex section, said first hollow structures 11 each formed such that said corner portion 13 is directed to one surface of
15 said connected hollow structure and a partial circumference 14 faces the other surface of said connected hollow structure, and said second hollow structures 12 each formed such that said corner portion 13 is directed to the other surface of said connected
20 hollow structure and a partial circumference 14 faces one surface of said connected hollow structure are arranged alternately, and said first and second hollow structures 11, 12 adjacent to each other have at least a portion of side walls 15, which include each corner
25 portion 13, in common.



3. A connected hollow structure according to claim 1, wherein said first and second hollow structures 11, 12 have a polygonal section, and said connected hollow structure is formed by folding said sheet a along
05 folds a1, a2 formed on said sheet a.

4. A connected hollow structure according to claim 3, wherein said first and second hollow structures 11, 12 in portions other than at least both ends of said connected hollow structure have a polygonal section
10 having sides of the same number.

5. A connected hollow structure according to claim 4, wherein said first and second hollow structures 11, 12 have a triangular section.

6. A connected hollow structure according to
15 claim 5, wherein said first and second hollow structures 11, 12 have an isosceles triangular or right-angled triangular section.

7. A connected hollow structure according to claim 4, wherein said first and second hollow structures
20 11, 12 have a quadrangular or pentagonal section.

8. A connected hollow structure according to claim 4, wherein said first and second hollow structures



11, 12 have a hexagonal or more polygonal section.

9. A connected hollow structure according to claim 3, wherein said first and second hollow structures 11, 12 in portions other than at least both ends of said
05 connected hollow structure have a polygonal section having sides of the same number, and said first hollow structures 11 are different from said second hollow structures 12 in number of sides included in the sectional shape.

10 10. A connected hollow structure according to claim 9, wherein either said first or second hollow structures 11, 12 have an triangular section, and the other hollow structures have a quadrangular or pentagonal section.

15 11. A connected hollow structure according to claim 9, wherein either said first or second hollow structures 11, 12 have a quadrangular section, and the other hollow structures have a pentagonal section.

12. A connected hollow structure according to
20 claim 3, wherein either said first or second hollow structures 11, 12 in portions other than at least both ends of said connected hollow structure have a polygonal section having sides of the same number, and the other



hollow structures include hollow structures of a polygonal section having different sides.

13. A connected hollow structure according to claim 12, wherein said either hollow structures have a
05 triangular section, and the other hollow structures include hollow structures of a quadrangular section and hollow structures of a pentagonal section.

14. A connected hollow structure according to claim 12, wherein said either hollow structures have a
10 triangular section, and the other hollow structures include hollow structures of a triangular section and hollow structures of a pentagonal section.

15. A connected hollow structure according to claim 3, wherein said first and second hollow structures
15 11, 12 in portions other than at least both ends of said connected hollow structure include hollow structures of a polygonal section having different sides.

16. A connected hollow structure according to claim 15, wherein said first and second hollow
20 structures 11, 12 include hollow structures of a triangular section and hollow structures of a quadrangular or pentagonal section.



- 170. -

17. A connected hollow structure according to claim 15, wherein said first and second hollow structures 11, 12 include hollow structures of a quadrangular section and hollow structures of a
05 pentagonal section.

18. A connected hollow structure according to any one of claims 5, 7, 10, 13, 14, 16 and 17, wherein the partial circumference 14 of each of said first and second hollow structures 11, 12 in portions other than
10 at least both ends of said connected hollow structure forms one side surface of said each hollow structure.

19. A connected hollow structure according to claim 18, wherein said partial circumferences 14 of said first hollow structures 11 and those of said second
15 hollow structures 12 are respectively connected together, and said connected hollow structure has a panel-like shape to be substantially uniform in apparent thickness T.

20. A connected hollow structure according to claim 18, wherein said partial circumferences 14 of said
20 first hollow structures 11 and those of said second hollow structures 12 are respectively connected together in at least one surface of said connected hollow structure, and said connected hollow structure has a



cylindrical or gutter-like shape on the whole with said one surface turned toward the inside.

21. A connected hollow structure according to claim 18, wherein said partial circumferences 14 of said
05 first hollow structures 11 and those of said second hollow structures 12 are respectively connected together, and at least one surface of said connected hollow structure has a rising portion 14a gradually rising from one portion toward the other.

10 22. A connected hollow structure according to claim 21, wherein the pitch of said first and second hollow structures 11, 12 formed in said rising portion 14a is made smaller in proportion to the scale of rising.

15 23. A connected hollow structure according to any one of claims 19, 21 and 22, wherein the hollow structure positioned at each end of said connected hollow structure has a chamfered inclined side surface 15a formed to extend in the length direction of said hollow
20 structure.

24. A connected hollow structure according to claim 18, wherein at least one surface of said connected hollow structure has a projection 14b projecting from



one portion to the other so as to extend in the length direction of said hollow structure, and said partial circumferences 14 of said first hollow structures 11 and those of said second hollow structures 12 are connected
05 together in said projection.

25. A connected hollow structure according to claim 24, wherein a plurality of said projections 14b are formed on said connected hollow structure, and a portion between said projections 14b is formed into a
10 channel-like portion 1j.

26. A connected hollow structure according to claim 24 or 25, wherein the pitch of said first and second hollow structures 11, 12 formed in said projection 14b is made smaller than that of said first
15 and second hollow structures formed in portions other than said projection.

27. A connected hollow structure according to any one of claims 24 to 26, wherein the hollow structure positioned at each end of said projection 14b has a
20 chamfered inclined side surface 15a formed to extend in the length direction of the hollow structure positioned at said end.

28. A connected hollow structure according to any one



of claims 19 to 27, wherein all or part of at least either said first or second hollow structures 11, 12 have the partial circumferences 14 of a circular arc section.

05 29. A connected hollow structure according to claim 3, wherein all or part of at least either said first or second hollow structures 11, 12 have the partial circumferences 14 each composed of a plurality of side surfaces substantially uniformly projecting
10 toward one surface of said connected hollow structure, and said hollow structures have a quadrangular or more polygonal section.

30. A connected hollow structure according to claim 29, wherein said partial circumferences 14 of said
15 first hollow structures 11 and those of said second hollow structures 12 are respectively connected together, and said connected hollow structure has a panel-like shape to be substantially uniform in apparent thickness T.

20 31. A connected hollow structure according to claim 29, wherein said partial circumferences 14 of said first hollow structures 11 and those of said second hollow structures 12 are respectively connected together, and said connected hollow structure has a



cylindrical or gutter-like shape on the whole.

32. A connected hollow structure according to claim 29, wherein said partial circumferences 14 of said first hollow structures 11 and those of said second hollow structures 12 are respectively connected together, and at least one surface of said connected hollow structure has a rising portion 14a gradually rising from one portion to the other.

33. A connected hollow structure according to
claim 32, wherein the pitch of said first and second
hollow structures 11, 12 formed in said rising portion
14a is made smaller in proportion to the scale of
rising.

34. A connected hollow structure according to any one
15 of claims 19 to 33, wherein said first and second hollow
structures 11, 12 adjacent to each other have an
appropriate number of bending node stripes 15c formed on
the side walls 15 common to both said hollow structures
11, 12 adjacent to each other so as to extend in the
20 length direction of said hollow structures.

35. A connected hollow structure according to claim 34, wherein each of said bending nodes 15c is a small groove formed on one surface of each side wall 15.



36. A connected hollow structure according to any one of claims 19 to 33, wherein at least part of said first and second hollow structures 11, 12 have an appropriate number of holes 18 formed in portions other than said
05 partial circumferences 14.

37. A connected hollow structure according to claim 3, wherein said first and second hollow structures 11, 12 are formed such as to gradually reduce the sectional size from one end of said hollow structures
10 toward the other.

38. A connected hollow structure according to claim 3, wherein all or part of at least either said first or second hollow structures 11, 12 have a plurality of small hollow portions 11a, 12a.

15 39. A connected hollow structure according to claim 3, wherein said first and second hollow structures 11, 12 have a pentagonal or more polygonal section, and either said first or second hollow structures 11, 12 have portions 15d of a concave section formed on the
20 side walls 15 common to said either hollow structures and the adjacent hollow structures.

40. A connected hollow structure according to claim 1, further comprising:



connecting sheet portions a14 bonded together so as to extend in parallel to each other; and

a large number of cylindrical hollow structures 10 formed by bonding circumferential portions together 05 in the length direction in joint portions a15 between the connecting sheet portions a14 adjacent to each other.

41. A connected hollow structure according to claim 40, wherein said hollow structures 10 have a 10 circular or elliptical section.

42. A connected hollow structure according to claim 40 or 41, wherein said connected hollow structure has a cylindrical shape with said hollow structures 10 positioned along the inner peripheral surface.

15 43. A connected hollow structure according to claim 1, wherein said hollow structures 10 include first — hollow structures 11b of a substantially drop-shaped section and second hollow structures 12b of a substantially inverse drop-shaped section, and a large 20 number of said first hollow structures 11b and a large number of said second hollow structures 12b are arranged alternately in an alternately inverse position by sequentially forming portions a16 of the sectional shape of a letter S and portions a17 of the sectional shape of



an inverse letter S in an alternate arrangement, and then connecting the sides of said portions a16 of the sectional shape of the letter S and the sides of the adjacent portion a17 of the sectional shape of the
05 inverse letter S together.

44. A connected hollow structure according to claim 43, wherein either said first or second hollow structures 11, 12 are smaller in sectional size than the other hollow structures, and said connected hollow
10 structure has a cylindrical shape on the whole with said either hollow structures positioned along the inner peripheral surface.

45. A connected hollow structure according to claim 1, wherein a large number of hollow structures 10
15 each formed by symmetrically combining a first hollow portion 10a of an angular section and a second hollow portion 10b of an inverse angular section are arranged densely in parallel to each other, and the hollow structures 10 adjacent to each other are connected
20 together substantially in the sectional shape of a letter S or an inverse letter S.

46. A connected hollow structure according to claim 45, wherein either said first or second hollow portions 10a, 10b have a semicircular, trapezoidal or triangular



section, and the other hollow portions have a semicircular, trapezoidal or triangular section reverse to that of said either hollow portions.

47. A packaging member, comprising:
05 the connected hollow structure according to any one of claims 1 to 46;

wherein the packaging member is wholly or partly composed of said connected hollow structure.

48. A packaging member, comprising:
10 a connected bottom structure 1a;
a connected side structure 1b placed uprightly on the side of said connected bottom structure 1a; and
a connected rear structure 1c placed uprightly on the rear of said connected bottom structure 1a and at
15 right angle with said connected side structure 1b;

wherein said connected bottom structure 1a, said connected side structure 1b and said connected rear structure 1c are respectively composed of the connected hollow structure according to claim 19 or 30.

20 49. A packaging member according to claim 48, wherein said connected side structure 1b is placed on said connected bottom structure 1a such that first and second hollow structures 11, 12 of said connected side structure 1b are substantially at right angles with



first and second hollow structures 11, 12 of said
connected bottom structure 1a;

said connected rear structure 1c is placed on
said connected bottom structure 1a such that first and
05 second hollow structures 11, 12 of said connected rear
structure 1c extend along the first and second hollow
structures 11, 12 of said connected bottom structure 1a
and are oriented at an angle of 90° with said first and
second hollow structures 11, 12 of said connected bottom
10 structure; and

said connected side structure 1b and said
connected rear structure 1c are connected to said
connected bottom structures 1a through individual
connecting sheet portions a3, a4; and

15 said connected bottom structure 1a, said
connected side structure 1b and said connected rear
structure 1c have the first and second hollow structures
11, 12 of the same sectional shape, and are comprised of
a piece of sheet.

20 50. A packaging member according to claim 48 or 49,
wherein at least part of the hollow structures having
the partial circumferences 14 facing the inside of said
packaging member have the partial circumferences 14 of a
circular arc section.

25 51. A packaging member, comprising:



the layered connected hollow structure according to claim 19 of a block shape with the hollow structures 11, 12 of each layer arranged in parallel to each other.

52. A packaging member according to claim 51, wherein
05 the layered connected hollow structure of the block shape has a hole 11a' formed at right angles with the hollow structures 11, 12 of said connected hollow structure.

53. A packaging member according to claim 51 or 52,
10 wherein the first and second hollow structures 11, 12 of the connected hollow structure in each layer extend in parallel to each other in a symmetrical shape in section, and the connected hollow structures in the layers adjacent to each other are connected together as
15 one body and comprised of a piece of sheet.

54. A packaging member, comprising:
— a connected bottom structure 1a;
a pair of connected side structures 1b, 1b placed
uprightly on both sides of said connected bottom
20 structure 1a;

a connected front structure 1i placed uprightly on the front of said connected bottom structure 1a and at right angles with said connected side structures 1b; and



a connected rear structure 1c placed uprightly on the rear of said connected bottom structure 1a and at right angles with said connected side structures 1b;

wherein said connected bottom structure 1a, both
05 connected side structures 1b, said connected front structure 1i and said connected rear structure 1c are composed of said connected hollow structure according to claim 19 or 30.

55. A packaging member according to claim 54, wherein
10 said connected front structure 1j and said connected rear structure 1c are placed on said connected bottom structure 1a such that first and second hollow structures 11, 12 of said connected front and rear structures extend along first and second hollow
15 structures 11, 12 of said connected bottom structure 1a and are oriented at an angle of 90° with said hollow structures 11, 12 of said connected front and rear
structures;

said both connected side structures 1b, 1b are
20 placed on said connected bottom structure 1a such that first and second hollow structures 11, 12 of said connected side structures 1b are substantially at right angles with the first and second hollow structures 11, 12 of said connected bottom structure 1a;

25 said connected front structure 1i and said connected rear structure 1c are connected to said



- 182 -

connected bottom structure 1a through individual
connecting sheet portions a4, a4;

said connected front structure 1i and one
connected side structure 1b and said connected rear
05 structure 1c and the other connected side structure 1b
are respectively connected together through individual
connecting sheet portions a3, a3; and

said connected bottom structure 1a, said both
connected side structures 1b, 1b, said connected front
10 structure 1i and said connected rear structure 1c have
the first and second hollow structures 11, 12 of the
same sectional shape and are comprised of a piece of
sheet a.