

SYSTEM AND METHOD FOR PROVIDING MASSAGE RELATED SERVICES

5 BACKGROUND

[0001] 1. Field of the Invention

[0002] The present invention relate to systems and methods for providing massage related services using a massage apparatus.

[0003] 2. Description of the Related Art

10 [0004] Massage apparatuses currently available on the market include massage chairs equipped with a massage member capable of applying diverse types of massage actions on a user's body. According to the needs, a user may select a massage program corresponding to a predetermined combination of movement and pressure actions of the massage member for producing certain desirable relaxing effects. Unfortunately, the
15 existing massage apparatuses usually include a fixed set of predetermined massage programs, which may not permit a flexible usage of the massage apparatus and limit the effectiveness of the massages.

[0005] Therefore, there is a need for massage apparatuses that can address at least the foregoing issues and provide enhanced massage experience.

20 SUMMARY

[0006] The present application describes systems and methods of providing massage related services that can enrich the user's experience in using a massage apparatus. In one embodiment, the massage apparatus includes a massage unit, a

driver operable to drive motion of the massage unit, and a microcontroller connected with the driver, wherein the microcontroller is configured to connect with an external device, receive a program code of a massage program from the external device and store the massage program in a memory, and execute the massage program through the
5 massage unit to apply a sequence of massage actions on a body.

[0007] In certain embodiments, the massage apparatus further includes a remote controller operable to show one or more icons associated with massage programs available in the massage apparatus. Once a new massage program is downloaded, a graphical interface displayed by the remote controller is also updated with a new
10 graphical icon selectable by a user to execute the newly downloaded massage program.

[0008] In other embodiments, a method of dispensing massage related services is described. The method comprises providing a massage apparatus, establishing a connection between a terminal device and a server computer, transferring a massage program executable on the massage apparatus from the server computer to the terminal
15 device, establishing a connection between the terminal device and the massage apparatus, and transferring the massage program from the terminal device to the massage apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a schematic view illustrating an embodiment of a system of
20 providing massage related services;

[0010] FIG. 2 is a simplified block diagram illustrating an embodiment of a massage apparatus;

[0011] FIG. 3 is a flowchart illustrating method steps for providing massage programs at a server level;

[0012] FIG. 4 is a flowchart illustrating method steps applied at a terminal device level for purchasing a massage program;

5 [0013] FIGS. 5A-5H are schematic views illustrating examples of displays on the terminal device occurring in an online transaction for buying a massage program;

[0014] FIG. 6 is a flowchart illustrating method steps executed on the massage apparatus; and

[0015] FIGS. 7A and 7B are schematic views illustrating examples of display on
10 a remote controller of a massage apparatus with no downloaded programs and after downloading a new massage program.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0016] FIG. 1 is a schematic diagram illustrating an embodiment of a system of providing massage related services 100. The system 100 can include two server
15 computers 102 and 103, a terminal device 104 and a massage apparatus 106. The server computer 102 can host a digital application distribution platform 112 that allows the terminal device 104 to browse and download diverse application programs, and conduct various transactions. Examples of the digital application distribution platform 112 hosted by the server computer 102 can include the Apple App Store for terminal
20 devices running with the iOS operating system developed by Apple Inc., and the Google Play Store for terminal devices running with the Android operating system developed by Google Inc.

[0017] The server computer 103 can store a plurality of message programs that are executable on the message apparatus 106, and connect with the terminal device 104 to transfer one or more of the message programs via the terminal device 104 to the message apparatus 106. In one embodiment, the server computer 103 can be
5 maintained and operated by a selling entity of the message programs, whereas the server computer 102 may serve as a transaction platform. A message program can be transferred from the server computer 103 to the terminal device 104 as a result of a purchase transaction conducted between the terminal device 104 and the server computer 102.

10 [0018] The terminal device 104 can include a smart phone, a tablet computer, a laptop computer, a personal computer, and the like. The terminal device 104 can execute an application program 114 that allows the terminal device 104 to interact with the server computers 102 and 103 and the message apparatus 106 for providing message related services. More specifically, the application program 114 executed on the
15 terminal device 104 can connect with the server computers 102 and 103 to conduct various transactions including, for example, receiving notifications about the release of new message programs, conducting a purchase transaction for acquiring a new message program, and downloading the message program from the server computer 103. The application program 114 can also connect with the message apparatus 106 to conduct
20 various tasks including, for example, displaying current settings of the message apparatus 106, transferring a purchased message program to the message apparatus 106, and controlling certain functionality of the message apparatus 106.

[0019] The massage apparatus 106 can include any type of devices capable of applying massage to a body. In one embodiment, the massage apparatus 106 can be a massage chair. In other embodiments, the massage apparatus 106 may also be a massage belt, a foot massage apparatus, and the like. The massage apparatus 106 may
5 be operable to apply massage, play music, provide interactive content, and receive updates of new massage programs from an external device, such as the terminal device 104. In one embodiment, the massage apparatus 106 can be provided with a remote controller 150 to facilitate its operation. In particular, the remote controller 150 can have a display capable of showing a list of massage programs for a user's selection.

10 [0020] FIG. 2 is a simplified block diagram illustrating one embodiment of the massage apparatus 106. The massage apparatus 106 can include a massage unit 120, a driver 122 associated with the massage unit 120, a control interface 124, a wireless communication interface 126, a microcontroller 130 and a remote controller 150. The massage unit 120 can include one or more mechanical components operable to apply
15 various types of massage actions, such as kneading and/or tapping actions, scrapping actions and the like. Examples of components in the massage unit 120 can include a motor, an actuator, a pump, a solenoid, etc.

[0021] The driver 122 can be a circuit that provides the interface between the microcontroller 130 and the massage unit 120, and can be operable to drive operation of
20 the component of the massage unit 120 according to control signals outputted by the microcontroller 130.

[0022] The control interface 124 can be connected with sensors and limit switches arranged in the massage apparatus 106, and can deliver various detection

signals to the microcontroller 130 to provide information such as physical height of the user, limits of movements, motor revolutions, etc.

[0023] The wireless communication interface 126 can include a Bluetooth interface and/or Wi-Fi interface that enables data exchange between the microcontroller
5 130 of the massage apparatus 106 and other external devices in a wireless manner.

[0024] The microcontroller 130 can control and supervise the operation of the massage apparatus 106. In one embodiment, the microcontroller 130 can exemplary be a 32-bit Reduced Instruction Set Computing (RISC) microcontroller. The microcontroller 130 can select one of a plurality of massage programs stored internally,
10 execute the massage program through the massage unit 120 to apply a sequence of massage actions on a user's body, and interact with the terminal device 104 via the wireless communication interface 126. In one embodiment, the microcontroller 130 can include a processing unit 132, a first and a second memory 134 and 136 for storing massage program codes, input/output (I/O) ports 138 through which the processing unit
15 132 can exchange signals with the driver 122 of the massage unit 120 and the control interface 124, a transceiver 140 for data exchange with the communication interface 130, and a Universal Serial Bus (USB) interface 142.

[0025] The memory 134 can store preset programming codes of massage programs IMP initially available in the massage apparatus 106. The separate memory
20 136 can store the programming codes of massage programs DMP that are loaded into the massage apparatus 106 by a user from an external device. In one embodiment, the memory 134 can exemplary be flash read-only memory (ROM), and the memory 136 can exemplary be electrically-erasable programmable read-only memory (EEPROM).

The massage programs DMP may be downloaded from a server computer (e.g., the server computer 103) into the terminal device 104, and then transferred from the terminal device 104 to the massage apparatus 106 for storage in the memory 136. The massage programs DMP may be transferred from the external device to the massage apparatus 106 via the wireless communication interface 128 or the USB interface 142.

[0026] The transceiver 140 can be a Universal Asynchronous Receiver and Transmitter through which data can be received by the processing unit 132 of microcontroller 130 and transmitted to a component outside the microcontroller 130.

[0027] The remote controller 150 can be connected with the microcontroller 130. The remote controller 150 can include a display screen driven by a display controller 152, and a microcontroller 154 operable to receive user's inputs on the remote controller 150, to control graphical content shown on the display screen of the remote controller 150, and to interact with the microcontroller 130. In one embodiment, the microcontroller 154 of the remote controller 150 can include an internal memory 156 that stores graphical icons associated with the massage programs IMP and DMP. These graphical icons can be displayed on the screen of the remote controller 150 for facilitating the setting, control and operation of the massage apparatus 106 by the user.

[0028] In conjunction with FIGS. 1 and 2, FIG. 3 is a flowchart illustrating method steps for providing new massage programs at a server level. In initial step 302, a new massage program may be uploaded to the server computer 103. The new massage program may be uploaded in the form of one or more encrypted file to prevent corruption from a malicious agent. In addition to the massage program, the encrypted

file(s) may also include graphical content defining graphical icons associated with the message program.

[0029] In step 304, the server computer 103 may send out a notification about the release of the new message program, which may be relayed via the server computer 5 102 to the terminal device 104. The terminal device 104 can be informed about the release of new message programs via the application program 114.

[0030] In step 306, the server computer 102 can receive a purchase request from the terminal device 104, initiate a payment procedure, and send a request to the server computer 103 for downloading the purchased message program.

10 [0031] In response to the download request from the server computer 102, the server computer 103 in step 308 can deliver one or more file of the purchased message program to the terminal device 104. The purchased message program may be downloaded from the server computer 103 to the terminal device 104 via Internet connection, for example.

15 [0032] In conjunction with FIGS. 1 and 2, FIG. 4 is a flowchart illustrating method steps applied at the level of the terminal device 104 for purchasing online a new message program, and FIGS. 5A-5H are schematic views illustrating examples of displays on the terminal device 104 occurring in the online purchase transaction. In step 402, the application program 114 running on the terminal device 104 can display an 20 image frame F1 as shown in FIG. 5A listing a plurality of message programs 501 available for purchase. The list of available message programs 501 can be provided and updated by the server computer 102 or 103. When the user wants to preview one message program of interest, the application program 114 can display an image frame

F2 introducing the selected massage program. As better shown in FIG. 5B, the image frame F2 can include a field 502 identifying the name of the massage program, a portion 504 that describes the characteristics and features of the massage program, and a BUY icon 506 and a CANCEL icon 508 that can be selected by the user to respectively
5 initiate or cancel the purchase transaction.

[0033] If the user wants to purchase the massage program, the application program 114 in step 404 can conduct a purchase transaction with respect to the selected massage program. For example, the application program 114 can display a confirmation window F3 as shown in FIG. 5C requesting the user to confirm the
10 purchase of the selected massage program at the displayed price, and then query certain identification information via the query popup window F4 as shown in FIG. 5D.

[0034] In next step 406, the application program 114 then can proceed to download the purchased massage program from the server computer 103. The download can be conducted, e.g., via internet connection. While the terminal device
15 104 is receiving one or more file of the purchased massage program, the application program 114 can display a download progress window F5 as shown in FIG. 5E. In one embodiment, the file(s) of the massage program may be downloaded to the terminal device 104 in an encrypted form that can be decrypted only on the massage apparatus 106. This may prevent corruption of the massage program during data transmission.

20 [0035] Once the download of the massage program to the terminal device 104 is completed, the application program 114 may display a query window F6 asking the user whether the downloaded massage program is to be transferred to the massage apparatus 106. Upon confirmation by the user, the application program 114 in step 408 can

establish a connection with the message apparatus 106 and proceed to transfer the downloaded message program to the message apparatus 106. This can be shown by the transfer progress window F7 illustrated in FIG. 5G.

[0036] After the transfer of the message program to the message apparatus 106 is completed, the application program 114 can display a query window F8 as shown in FIG. 5H asking the user whether the message apparatus 106 should start to run the message program. In response to an activate request, the application program 114 in step 410 can send a signal to the message apparatus 106 to trigger the execution of the message program on the message apparatus 106.

[0037] In conjunction with FIGS. 1 and 2, FIG. 6 is a flowchart illustrating method steps performed by the message apparatus 106. In step 602, the microcontroller 130 in the message apparatus 106 can turn on the wireless communication interface 128 in response to a request received from the terminal device 104 for establishing a connection between the terminal device 104 and the message apparatus 106. The switch of the wireless communication interface 128 can be performed automatically by the system, or manually by using the remote controller 150.

[0038] In step 604, the message apparatus 106 can receive one or more encrypted file containing the program code of one message program and graphical data of icons associated therewith. The transfer of the file(s) can be conducted via the wireless communication interface 128, e.g., through Bluetooth connection.

[0039] In step 606, the microcontroller 130 can decrypt the file(s) to recover the message program code and the graphical icons (the icons may be defined as bitmap files), convert the code of the message program into a machine executable form, and

then respectively store the message program code and the icons in the memory 136 and the remote controller 150. The graphical user interface at the remote controller 150 can be thereby updated to display the icon(s) associated with the downloaded message program. FIGS. 7A and 7B are schematic views illustrating examples of display on the remote controller 150 with no downloaded programs and after the download of a new message program. In FIG. 7A, the display of the remote controller 150 can exemplarily show a window frame F9 indicating that there is no downloaded program in the message apparatus 106. In FIG. 7B, the display of the remote controller 150 can show an icon F10 indicating that there is a newly downloaded program available for selection by the user.

[0040] In step 608, in response to an activation signal, the microcontroller 130 then can execute the new message program through the message unit 120 to apply a sequence of message actions on the body of the user. The user can activate the message apparatus 106 to execute the new message program by, e.g., using the terminal device 104 or the remote controller 150.

[0041] While the foregoing describes the use of a wireless transmission between the terminal device 104 and the message apparatus 106, it is worth noting that other methods can be applicable to transfer a new message program to the message apparatus 106. For example, the new message program downloaded to the terminal device 104 first can be stored in an external device, e.g., another terminal device, a USB memory stick or any suitable storage devices. The external device then can be connected with the message apparatus 106, and the new message program can be transferred from the external device to the message apparatus 106 via the USB interface 142. After the

transfer is completed, steps 606 and 608 can be performed as described previously to install the new massage program in the massage apparatus 106.

[0042] At least one advantage of the systems and methods described herein includes the ability to download new massage programs, perform graphical user interface update on the remote controller of the massage apparatus, and using either the remote controller or the external device for execution of new downloaded massage programs on a massage apparatus. Accordingly, the massage apparatus can be used in a more flexible manner, and the user can enjoy enriched massage experience on the massage apparatus.

[0043] Realizations of the systems and methods have been described only in the context of particular embodiments. These embodiments are meant to be illustrative and not limiting. Many variations, modifications, additions, and improvements are possible. Accordingly, plural instances may be provided for components described herein as a single instance. Structures and functionality presented as discrete components in the exemplary configurations may be implemented as a combined structure or component. These and other variations, modifications, additions, and improvements may fall within the scope of the inventions as defined in the claims that follow.

WHAT IS CLAIMED IS:

1. A massage apparatus comprising:

a massage unit;

a remote controller;

5 a driver operable to drive motion of the massage unit; and

a microcontroller connected with the driver, wherein the microcontroller is configured to:

connect with an external device;

receive a program code of a massage program and graphical content

10 of an icon associated with the massage program in an encrypted form from the external device, and store the massage program in a memory;

decrypt the massage program and the graphical content of the icon received from the external device;

15 have the icon stored in the remote controller; and

execute the decrypted massage program through the massage unit to apply a sequence of massage actions on a body.

2. The massage apparatus according to claim 1, wherein the microcontroller includes an internal memory for storing the massage program received from the external
20 device.

3. The massage apparatus according to claim 2, wherein the internal memory includes electrically-erasable programmable read-only memory.

4. The massage apparatus according to claim 1, further including a wireless communication interface through which the microcontroller receives the massage program from the external device.
5. The massage apparatus according to claim 4, wherein the wireless
5 communication interface includes a Bluetooth interface, and/or a Wi-Fi interface.
6. The massage apparatus according to claim 1, further including a Universal Serial Bus interface through which the microcontroller receives the massage program from the external device.
7. The massage apparatus according to claim 1, wherein the microcontroller is
10 configured to:
store the icon in a second memory in the remote controller.
8. The massage apparatus according to claim 7, wherein the icon is defined in a bitmap file.
9. The massage apparatus according to claim 7, wherein the remote controller has a
15 display screen operable to display the icon stored in the second memory, the icon being selectable for executing the massage program.
10. The massage apparatus according to claim 1, being configured as a massage chair.
11. A system of providing massage related services, comprising:
20 the massage apparatus according to claim 1;
a first and a second server computer; and

a terminal device operable to:

conduct a transaction with the first server computer to purchase the
message program;

download the message program from the second server computer; and

5 transfer the message program to the message apparatus.

12. The system according to claim 11, wherein the terminal device is operable to
download the message program from the second server computer via internet
connection, and to transfer the downloaded message program to the message apparatus
via a Bluetooth connection.

10 13. The system according to claim 11, wherein the message program is downloaded
to the terminal device in the encrypted form that is decryptable by the message
apparatus.

14. A method of providing message related services, comprising:

providing a message apparatus;

15 establishing a connection between a terminal device and a server computer;

transferring a message program executable on the message apparatus and

graphical content of an icon associated with the message program from the
server computer to the terminal device;

establishing a connection between the terminal device and the message
20 apparatus; and

transferring the message program and the graphical content of the icon contained
in one or more encrypted file from the terminal device to the message
apparatus; and

through the message apparatus, decrypting the one or more encrypted file to
recover the message program and the graphical content of the icon.

15. The method according to claim 14, wherein the message program is transferred
from the server computer to the terminal device via internet connection.

5 16. The method according to claim 14, wherein the message program is transferred
from the terminal device to the message apparatus via a wireless connection.

17. The method according to claim 16, wherein the wireless connection includes a
Bluetooth connection.

18. The method according to claim 14, further including:
10 storing the decrypted graphical content of the icon associated with the message
program in a remote controller of the message apparatus; and
displaying the icon on the remote controller of the message apparatus.

SYSTEM AND METHOD FOR PROVIDING MESSAGE RELATED SERVICES

ABSTRACT

A method of providing message related services comprises providing a message apparatus, establishing a connection between a terminal device and a server computer, transferring a message program executable on the message apparatus from the server computer to the terminal device, establishing a connection between the terminal device and the message apparatus, and transferring the message program from the terminal device to the message apparatus. Once the new message program is downloaded in the message apparatus, a graphical user interface displayed by a remote controller of the message apparatus can be updated with a new icon associated with the new message program. The new message program then can be executed either from the remote controller or the terminal device. In some embodiments, a message apparatus and a system including the message apparatus are also described.

[FIG. 1]



100

FIG. 1






FIG. 3




FIG. 4




FIG. 5B




FIG. 5A




FIG. 5D




FIG. 5C




FIG. 5F




FIG. 5E




FIG. 5H




FIG. 5G




FIG. 6




FIG. 7B




FIG. 7A